

## RF exposure information

FCC ID: 2AG36HDM-600E

### 1. Introduction:

The EUT is designed to be used in mobile exposure conditions.  
This product is a transmitter operated in 13.56MHz frequency.

### 2. Output power considerations:

Worst case output power transmitter ( $E_{max}$ ): 83.1dB $\mu$ V/m@3m

$$Pt = (E^*d) / (30 \times gt) = 0.0014W = 1.4\text{mw}$$

Pt=transmitter output power in watts;

gt=numeric gain of the transmitting antenna (unites/dBi) = 1/0dBi;

E=electric field strength in V/m =  $(10^{(83.19/20)})/1000000 = 0.014 \text{ V/m}$

d=measurement distance in meters (m) = 3 m

### 3. Compliance criteria:

According to 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50 \text{ mm}$  are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}$   
where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

Calculate:

$$(1.4/5) * (0.01356) ^{0.5} = 0.033 < 3 \text{ for 1g SAR}$$

Then SAR evaluation is not required.