## RF exposure evaluation

The RF exposure evaluation was calculated as below:

- 1) The maximum conducted output power is -5.143dBm (0.31mW) at 2402MHz of GFSK mode. (0dBi antenna gain, with 1.0 numeric antenna gain.)
- 2) For Bluetooth device or fixed location transmitters, no SAR consideration applied.
- 3) Per KDB 447498 D01v05r02, the 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]  $\cdot$  [ $\sqrt{f(GHz)}$ ]  $\leq 3.0$  for 1-g SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- · Power and distance are rounded to the nearest mW and mm before calculation
- When the minimum test separation distance is < 5 mm, a distance of 5 mm according is applied to determine SAR test exclusion.
- The result is rounded to one decimal place for comparison

Test exclusion Power Max. Power Frequency Channel thresholds distance Result (GHz) (dBm) (mW) (mm) for 1-g SAR CH 00 2.402 -5.143 0.31 0.0961 3.0 5

- · Base on the calculation value, the RF exposure evaluation is not required.
- The public is not exposed to radio frequency energy level in excess of the Commission's guideline.