RF EXPOSURE REPORT



Report No.: 15071251-FCC-H Supersede Report No.: N/A

Applicant Shenzhen Osunp Electronics Co.,LTD		
Bluetooth Hat		
BE Link , Gen 3.0 , Gen 4.0		
E-201 , E-202 , E-203 , E-204 , E-205 , E-206 , E-207 , E-208 , E-		
209		
FCC 2.1093:2014		
December 21 to December 30, 2015		
December 30, 2015		
Test Result Pass Fail		
Equipment complied with the specification		
Equipment did not comply with the specification		
Thema	David Huang	
ang	David Huang	
neer	Checked By	
	Bluetooth F BE Link , C E-201 , E-2 209 FCC 2.109 December December Pass ied with the st comply with	Bluetooth Hat BE Link , Gen 3.0 , Gen 4.0 E-201 , E-202 , E-203 , E-204 , E-205 209 FCC 2.1093:2014 December 21 to December 30, 2015 December 30, 2015 Pass Fail ied with the specification t comply with the specification Theng David Huang David Huang David Huang

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park
South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn



Test Report	15071251-FCC-H-
Page	2 of 8

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety



Test Report	15071251-FCC-H-
Page	3 of 8

This page has been left blank intentionally.



Test Report	15071251-FCC-H-
Page	4 of 8

CONTENTS

1.	REPORT REVISION HISTORY	5
2.	CUSTOMER INFORMATION	5
3.	TEST SITE INFORMATION	5
4	EQUIPMENT UNDER TEST (EUT) INFORMATION	6
╼.	EQUI WENT ONDER TEOT (EOT) IN ORWATION	
5.	FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES	. 7
5.1	RF EXPOSURE	7
52	TEST DESUILT	ç



Test Report	15071251-FCC-H-	
Page	5 of 8	

1. Report Revision History

Report No.	Report Version	Description	Issue Date
15071251-FCC-H	NONE	Original	December 30, 2015

2. Customer information

Applicant Name	Shenzhen Osunp Electronics Co.,LTD	
Applicant Add	Room 611,Huiyi Wealth Center,Zhongxin Road,Long Hua New District,Shen	
	Zhen,China	
Manufacturer	Shenzhen Osunp Electronics Co.,LTD	
Manufacturer Add	Building B,Liao Keng Industrial Area,Shi Yan Town, Baoan District,Shen	
	Zhen,China	

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES	
	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park	
Lab Address	South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong	
	China 518108	
FCC Test Site No.	718246	
IC Test Site No.	4842E-1	
Test Software	Radiated Emission Program-To Shenzhen v2.0	



Test Report	15071251-FCC-H-
Page	6 of 8

4. Equipment under Test (EUT) Information

Description of EUT:	Bluetooth Hat
Main Model:	BE Link , Gen 3.0 , Gen 4.0
Serial Model:	E-201 , E-202 , E-203 , E-204 , E-205 , E-206 , E-207 , E-208 , E-209
Date EUT received:	December 21, 2015
Test Date(s):	December 21 to December 30, 2015
Antenna Gain:	Bluetooth: 1.58 dBi
Type of Modulation:	Bluetooth: GFSK, π /4 DQPSK, 8DPSK
RF Operating Frequency (ies):	Bluetooth: 2402-2480 MHz
Number of Channels:	Bluetooth: 79CH
Port:	USB Port
Input Power:	Battery: Spec: 3.7V,180mAh
Trade Name :	3E
FCC ID:	2AG43BELINK



Test Report	15071251-FCC-H-
Page	7 of 8

5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

5.1 RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot \sqrt{f_{(GHz)}} \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, 16 where

- f_(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is ≤ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

result = $P\sqrt{F}/D$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm



Test Report	15071251-FCC-H-
Page	8 of 8

5.2 Test Result

Bluetooth Mode:

Modulation	СН	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-1.503	-1±1	0	1.000	0.31	3
	Mid	2441	-0.565	-1±1	0	1.000	0.31	3
	High	2480	-0.809	-1±1	0	1.000	0.31	3
π /4 DQPSK	Low	2402	-1.216	-1±1	0	1.000	0.31	3
	Mid	2441	-0.431	-1±1	0	1.000	0.31	3
	High	2480	-0.427	-1±1	0	1.000	0.31	3
8-DPSK	Low	2402	-0.543	0±1	1	1.259	0.39	3
	Mid	2441	0.086	0±1	1	1.259	0.39	3
	High	2480	-0.177	0±1	1	1.259	0.40	3

Result: Compliance

No SAR measurement is required.