



## FCC PART 15 B

### TEST REPORT

For

### CLC HONG KONG LIMITED

1011A, 10/F., Harbour Centre Tower 1, No.1 Hok Cheung St., Hung Hom, Kowloon, Hong Kong

**FCC ID: 2AG4WA104**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Ram 3G
<b>Test Engineer:</b> <u>Allen Qiao</u> <i>Allen Qiao</i>	
<b>Report Number:</b> <u>RDG151120006-00C</u>	
<b>Report Date:</b> <u>2015-12-01</u>	
<b>Reviewed By:</b> Jerry Zhang <u>EMC Manager</u>	<i>Jerry Zhang</i>
<b>Test Laboratory:</b> Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>3</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	3
OBJECTIVE .....	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY .....	3
TEST FACILITY.....	4
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>5</b>
DESCRIPTION OF TEST CONFIGURATION .....	5
EUT EXERCISE SOFTWARE .....	5
EQUIPMENT MODIFICATIONS .....	5
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS .....	5
SUPPORT CABLE LIST AND DETAILS .....	5
CONFIGURATION OF TEST SETUP .....	6
<b>SUMMARY OF TEST RESULTS .....</b>	<b>7</b>
<b>FCC§15.107 - CONDUCTED EMISSIONS.....</b>	<b>8</b>
MEASUREMENT UNCERTAINTY .....	8
EUT SETUP .....	8
EMI TEST RECEIVER SETUP.....	9
TEST EQUIPMENT LIST AND DETAILS.....	9
TEST PROCEDURE .....	9
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	9
TEST RESULTS SUMMARY.....	10
TEST DATA .....	10
<b>FCC §15.109 - RADIATED SPURIOUS EMISSIONS .....</b>	<b>13</b>
MEASUREMENT UNCERTAINTY .....	13
EUT SETUP .....	13
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE .....	14
TEST EQUIPMENT LIST AND DETAILS.....	15
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	15
TEST RESULTS SUMMARY.....	15
TEST DATA .....	15
ENVIRONMENTAL CONDITIONS.....	15
<b>DECLARATION LETTER.....</b>	<b>20</b>

## GENERAL INFORMATION

### Product Description for Equipment Under Test (EUT)

The *CLC HONG KONG LIMITED*'s product, model number: *A104 (FCC ID: 2AG4WA104)* (the "EUT") in this report was a *Ram 3G*, which was measured approximately: 12.8 cm (L) x 5.7 cm (W) x 1.6 cm (H), rated input voltage: DC3.7V rechargeable Li-ion battery or DC5.0V charging from adapter.

Adapter information:

Model: PMC03

Input: AC100-240V

Output: DC 5V, 500mA

*Note: The model A104 have different samples , they are the same electromagnetic emissions and electromagnetic compatibility characteristics, the difference between them is the colour, the details was explained in the attached declaration letter.*

*All measurement and test data in this report was gathered from production sample serial number: 151120006 (Assigned byBACL, Dongguan). The EUT was received on 2015-11-23.*

### Objective

This test report is prepared on behalf of *CLC HONG KONG LIMITED*. in accordance with Part 2, Subpart J, and Part 15-Subparts A and B of the Federal Communications Commission's rules.

The objective of the manufacturer is to determine the compliance of EUT with FCC Part 15 B Class B.

### Related Submittal(s)/Grant(s)

FCC Part 15C DSS submissions with FCC ID: 2AG4WA104 .

FCC Part 22H, 24E submissions with FCC ID: 2AG4WA104 .

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Dongguan).

**Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

### EUT Exercise Software

The software “winthrax.exe” was used during test.

### Equipment Modifications

No modification was made to the EUT tested.


### Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	Laptop	PP11L	QDS-BRCM1017
HP	Printer	C3941A	JPTVOB2337
DELL	Keyboard	L100	CNORH656658907BL05DC
AST	Modem	AEM-2100	0293
Kingston	Micro SD card	8GB	/

### Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Serial Cable	yes	no	1.2	Serial Port of Laptop	Modem
Parallel Cable	yes	no	1.2	Parallel Port of Laptop	Printer
Keyboard Cable	yes	no	1.8	USB Port of Laptop	Keyboard
USB Cable	no	no	0.8	USB Port of Laptop	EUT
Earphone Cable	no	no	1.1	Audio Port of EUT	Earphone

## Configuration of Test Setup



## SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	Conducted Emissions	Compliance
§15.109	Radiated Emissions	Compliance

## FCC§15.107 - CONDUCTED EMISSIONS

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are Receiver, cable loss, and LISN.

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If  $U_{\text{lab}}$  is less than or equal to  $U_{\text{cisp}}$  of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non - compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If  $U_{\text{lab}}$  is greater than  $U_{\text{cisp}}$  of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by  $(U_{\text{lab}} - U_{\text{cisp}})$ , exceeds the disturbance limit;
- non - compliance is deemed to occur if any measured disturbance level, increased by  $(U_{\text{lab}} - U_{\text{cisp}})$ , exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of  $U_{\text{cisp}}$

Measurement	$U_{\text{cisp}}$
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

### EUT Setup



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15 B Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter of laptop was connected to a 120V/60Hz AC power source.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2015-10-20	2016-10-20
R&S	L.I.S.N	ESH2-Z5	892107/021	2015-07-16	2016-07-15
R&S	Two-line V-network	ENV 216	3560.6550.12	2014-12-11	2015-12-11
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

\* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Procedure

During the conducted emission test, the adapter of laptop was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

### Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

$V_C$ : corrected voltage amplitude

$V_R$ : reading voltage amplitude

$A_c$ : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15 B Class B, with the worst margin reading of:

**8.10 dB at 0.317235 MHz in the Line conducted mode**

## Test Data


### Environmental Conditions

<b>Temperature:</b>	24.3°C
<b>Relative Humidity:</b>	41 %
<b>ATM Pressure:</b>	101.2 kPa

*The testing was performed by Allen Qiao on 2015-11-24.*

*Test Mode: Downloading*


**AC120V, 60Hz, Line:**



Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)	Comment
0.184529	49.6	9.000	L1	0.2	14.7	64.3	Compliance
0.372042	43.0	9.000	L1	0.2	15.5	58.5	Compliance
0.406123	42.0	9.000	L1	0.2	15.8	57.7	Compliance
0.412647	39.1	9.000	L1	0.2	18.5	57.6	Compliance
0.426011	32.8	9.000	L1	0.2	24.5	57.3	Compliance
0.503608	40.3	9.000	L1	0.2	15.7	56.0	Compliance

Frequency (MHz)	Average (dB $\mu$ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)	Comment
0.183065	41.9	9.000	L1	0.2	12.4	54.3	Compliance
0.264113	40.0	9.000	L1	0.2	11.3	51.3	Compliance
0.288307	36.6	9.000	L1	0.2	14.0	50.6	Compliance
0.317235	41.7	9.000	L1	0.2	8.1	49.8	Compliance
1.239175	33.3	9.000	L1	0.2	12.7	46.0	Compliance
1.289541	34.6	9.000	L1	0.2	11.4	46.0	Compliance

**AC120V, 60Hz, Neutral:**



Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)	Comment
0.206306	46.4	9.000	N	0.2	16.9	63.4	Compliance
0.406123	43.7	9.000	N	0.2	14.0	57.7	Compliance
0.415949	42.7	9.000	N	0.2	14.8	57.5	Compliance
0.429420	39.7	9.000	N	0.2	17.5	57.3	Compliance
1.239175	43.0	9.000	N	0.3	13.0	56.0	Compliance
1.310256	42.5	9.000	N	0.3	13.5	56.0	Compliance

Frequency (MHz)	Average (dB $\mu$ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)	Comment
0.309742	36.7	9.000	N	0.2	13.3	50.0	Compliance
0.624492	28.1	9.000	N	0.2	17.9	46.0	Compliance
0.879690	31.3	9.000	N	0.2	14.7	46.0	Compliance
0.975701	32.0	9.000	N	0.2	14.0	46.0	Compliance
1.239175	35.6	9.000	N	0.3	10.4	46.0	Compliance
1.289541	36.6	9.000	N	0.3	9.4	46.0	Compliance

## FCC §15.109 - RADIATED SPURIOUS EMISSIONS

### Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If  $U_{\text{lab}}$  is less than or equal to  $U_{\text{cispr}}$  of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non - compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If  $U_{\text{lab}}$  is greater than  $U_{\text{cispr}}$  of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by  $(U_{\text{lab}} - U_{\text{cispr}})$ , exceeds the disturbance limit;
- non - compliance is deemed to occur if any measured disturbance level, increased by  $(U_{\text{lab}} - U_{\text{cispr}})$ , exceeds the disturbance limit.


Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:30MHz~200MHz: 5.0 dB; 200MHz~1GHz: 6.2 dB; 1GHz~6GHz: 4.45 dB, 6GHz~18GHz: 5.23 dB

Table 1 – Values of  $U_{\text{cispr}}$


Measurement		$U_{\text{cispr}}$
Radiated disturbance (electric field strength at an OATS or in a SAC)	(30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR)	(1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR)	(6 GHz to 18 GHz)	5.5 dB

### EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

### EMI Test Receiver Setup

The system was investigated from 30 MHz to 6 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	Peak
	1 MHz	10 Hz	/	Ave.

### Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The data was recorded in the Quasi-peak detection mode for below 1 GHz, peak and average detection mode above 1 GHz.

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2015-11-23	2016-11-22
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2015-02-19	2016-02-19
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15 B Class B, with the worst margin reading of:

**6.84 dB at 62.9800 MHz in the Horizontal polarization**

## Test Data

### Environmental Conditions

<b>Temperature:</b>	24.7 °C
<b>Relative Humidity:</b>	43 %
<b>ATM Pressure:</b>	101.2 kPa


*The testing was performed by Allen Qiao on 2015-11-24.*

*Test Result: Compliance*


*Test Mode: Downloading*

**1) Below 1GHz:**


**Horizontal**




Frequency (MHz)	Receiver Reading (dB $\mu$ V)	Detector	Correction Factor (dB/m)	Cord. Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
30.0000	28.23	peak	1.70	29.93	40.00	10.07
62.9800	45.74	peak	-12.58	33.16	40.00	6.84
239.5200	40.10	peak	-7.41	32.69	46.00	13.31
285.1100	38.11	peak	-5.66	32.45	46.00	13.55
374.3500	35.91	peak	-3.65	32.26	46.00	13.74
398.6000	35.85	peak	-3.22	32.63	46.00	13.37

**Vertical**

Frequency (MHz)	Receiver Reading (dB $\mu$ V)	Detector	Correction Factor (dB/m)	Cord. Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
30.9700	23.87	peak	0.92	24.79	40.00	15.21
210.4200	43.40	peak	-8.41	34.99	43.50	8.51
284.1400	39.46	peak	-5.69	33.77	46.00	12.23
374.3500	35.24	peak	-3.65	31.59	46.00	14.41
547.9800	28.69	peak	-0.73	27.96	46.00	18.04
720.6400	29.83	peak	1.82	31.65	46.00	14.35

**2) Above 1GHz:****Horizontal**

Frequency (MHz)	Receiver Reading (dB $\mu$ V)	Detector	Correction Factor (dB/m)	Cord. Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1060.120	48.61	peak	-1.13	47.48	74.00	26.52
1060.120	36.39	AVG	-1.13	35.26	54.00	18.74
1851.703	44.02	peak	-0.15	43.87	74.00	30.13
1851.703	31.56	AVG	-0.15	31.41	54.00	22.59
2122.244	40.77	peak	0.78	41.55	74.00	32.45
2122.244	28.41	AVG	0.78	29.19	54.00	24.81

**Vertical**

Frequency (MHz)	Receiver Reading (dB $\mu$ V)	Detector	Correction Factor (dB/m)	Cord. Amp. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
1060.120	51.86	peak	-1.13	50.73	74.00	23.27
1060.120	39.38	AVG	-1.13	38.25	54.00	15.75
1320.641	46.49	peak	-0.70	45.79	74.00	28.21
1320.641	34.04	AVG	-0.70	33.34	54.00	20.66
2122.244	43.25	peak	0.78	44.03	74.00	29.97
2122.244	30.81	AVG	0.78	31.59	54.00	22.41

## **DECLARATION LETTER**

### **CLC HONG KONG LIMITED**

Add: 1011A, 10/F., Harbour Centre Tower 1, No.1 Hok Cheung St., Hung Hom, Kowloon, Hong Kong

Tel: +852 21229685

Fax: +852 39044979

## **DECLARATION OF SIMILARITY**

Date: 2015-12-28

Dear Sir or Madam:

We, CLC HONG KONG LIMITED, hereby declare that product name: Ram 3G, model: A104, they are the same electromagnetic emissions and electromagnetic compatibility characteristics. A description of the difference among the 2 samples and those that are declared similar are as follows:

1) They have different colours: orange and black

The rest are the same.

Please contact me should there be need for any additional clarification or information.

Best Regards,

Signature:

Kam Chong

Manager



**\*\*\*\*\* END OF REPORT \*\*\*\*\***