

SAR TEST REPORT

FCC ID: 2AG5B-WD03

Product: WiFi hotspot + Power bank

Model No.: WD03

Additional Model No.: MIIFI 3G MOBILE WIFI ROUTER

Trade Mark: Unitone/AlldayInternet/wolder/ekko/HTM

Report No.: TCT151225E007

Issued Date: Feb. 26, 2016

Issued for:

Shenzhen Unitone Electronics co.,Ltd

**13-14 Floor, Pengji Bussiness Mansion, No.50, Bagua 1 Road, Futian District,
Shenzhen, China**

Issued By:

Shenzhen Tongce Testing Lab.

1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China

TEL: +86-755-27673339

FAX: +86-755-27673332

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab.

**This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in
the revision section of the document. The test results in the report only apply to the tested sample.**

TABLE OF CONTENTS

| | |
|---|----|
| 1. Test Certification | 3 |
| 2. Facilities and Accreditations | 4 |
| 2.1. Facilities..... | 4 |
| 2.2. Location | 4 |
| 2.3. Environment Condition:..... | 4 |
| 3. Test Result Summary | 5 |
| 4. EUT Description..... | 6 |
| 5. RF Exposure Limit..... | 7 |
| 6. SAR Measurement System Configuration..... | 8 |
| 6.1. SAR Measurement Set-up | 8 |
| 6.2. E-field Probe | 9 |
| 6.3. Phantom..... | 9 |
| 6.4. Device Holder | 10 |
| 6.5. Data Storage and Evaluation..... | 11 |
| 6.6. Position of the wireless device in relation to the phantom | 12 |
| 6.7. Tissue Verification | 15 |
| 6.8. Tissue Dielectric Parameters | 15 |
| 6.9. Tissue-equivalent Liquid Properties | 16 |
| 6.10. System Check..... | 17 |
| 7. Measurement Procedure..... | 18 |
| 8. Conducted Output Power | 21 |
| 9. SAR Test Results Summary | 25 |
| 9.1. Body-Worn 1g SAR Data | 25 |
| 9.2. Hotspot 1g SAR Data | 26 |
| 10. Exposure Position Consideration | 28 |
| 10.1. EUT Antenna Location..... | 28 |
| 10.2. Test Position Consideration..... | 28 |
| 10.3. Simultaneous Transmission Conclusion..... | 29 |
| 10.4. SAR Simultaneous Transmission Analysis | 30 |
| 10.5. Measurement Uncertainty (450MHz-3Hz) | 32 |
| 10.6. Test Equipment List..... | 34 |
| 11. System Check Results | 35 |
| 12. SAR Test Data..... | 38 |
| Appendix A:EUT Photos..... | 50 |
| Appendix B: Test Setup Photos..... | 51 |
| Appendix C: Probe Calibration Certificate..... | 53 |
| Appendix D: Dipole Calibration Report..... | 62 |

1. Test Certification

| | |
|------------------------------|--|
| Product: | WiFi hotspot + Power bank |
| Model No.: | WD03 |
| Additional Model No. | MIFI 3G MOBILE WIFI ROUTER, |
| Trade Mark: | Unitone/AlldayInternet/wolder/ekko/HTM |
| Applicant: | Shenzhen Unitone Electronics co.,Ltd |
| Address: | 13-14 Floor, Pengji Bussiness Mansion, No.50, Bagua 1 Road, Futian District, Shenzhen, China |
| Manufacturer: | Shenzhen Unitone Electronics co.,Ltd |
| Address: | 13-14 Floor, Pengji Bussiness Mansion, No.50, Bagua 1 Road, Futian District, Shenzhen, China |
| Date of Test: | Feb.16 –Feb. 26, 2016 |
| SAR Max. Values: | 0.85 W/Kg (1g) for Body-worn; 0.89 W/Kg (1g) for hotspot |
| Applicable Standards: | IEEE1528-2013:Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate in the Human Head from Wireless Communications Devices:Measurement Techniques KDB447498 D01:General RF Exposure Guidance v06 KDB248227 D01: 802.11 wi-fi SAR v02r02 KDB865664 D01:SAR measurement 100MHz to 6GHz v01r04 KDB865664 D02:RF Exposure Reporting v01r02. KDB941225 D01:SAR Procedures v03r01 KDB941225 D06:Hotspot Mode v02r01 KDB690783 D01:SAR Listings on Grant v01r03 |

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By: Aero Liu **Date:** Feb.26,2016

Aero Liu

Reviewed By: Joe Zhou **Date:** Feb.26,2016

Joe Zhou

Approved By: Tomsin **Date:** Feb.26,2016

Tomsin

2. Facilities and Accreditations

2.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 572331

Shenzhen Tongce Testing Lab

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen Tongce Testing Lab. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

- CNAS - Registration No.: CNAS L6165

Shenzhen Tongce Testing Lab. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6165.

2.2. Location

Shenzhen Tongce Testing Lab.

Address: 1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China

2.3. Environment Condition:

| | |
|-----------------------|------------|
| Temperature: | 18°C ~25°C |
| Humidity: | 35%~75% RH |
| Atmospheric Pressure: | 1011 mbar |

3. Test Result Summary

The maximum results of Specific Absorption Rate (SAR) found during test as bellows:

<Highest Reported standalone SAR Summary>

| Exposure Position | Frequency Band | Reported SAR (W/kg) | Equipment Class | Highest Reported SAR (W/kg) |
|---|----------------|---------------------|-----------------|-----------------------------|
| Body-worn 1-g SAR (5 mm Gap) | GSM 850 | 0.85 | PCB | 0.85 |
| | GSM 1900 | 0.66 | | |
| | WCDMA Band II | 0.64 | | |
| | WCDMA Band V | 0.64 | | |
| | WLAN 2.4 GHz | 0.13 | DTS | |
| Hopspot1-g SAR 1-g SAR (10mm Gap) | GSM 850 | 0.89 | PCB | 0.89 |
| | GSM 1900 | 0.70 | | |
| | WCDMA Band II | 0.64 | | |
| | WCDMA Band V | 0.56 | | |
| | WLAN 2.4 GHz | 0.23 | DTS | |

<Highest Reported simultaneous SAR Summary>

| Exposure Position | Frequency Band | Highest Reported Simultaneous Transmission SAR (W/kg) |
|---|----------------|---|
| Body-worn 1-g SAR (5 mm Gap) | GSM850+WIFI | 0.98 |
| Hopspot1-g SAR 1-g SAR (10mm Gap) | GSM850+WIFI | 1.12 |

Note:

1. The highest simultaneous transmission is scalar summation of Reported standalone SAR per FCC KDB 690783 D01 v01r03, and scalar SAR summation of all possible simultaneous transmission scenarios are < 1.6W/kg.
2. This device is compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-2005, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013.

4. EUT Description

| | |
|----------------------------------|--|
| Product Name: | WiFi hotspot + Power bank |
| Model : | WD03 |
| Additional Model: | MIFI 3G MOBILE WIFI ROUTER, |
| Trade Mark: | Unitone/AlldayInternet/wolder/ekko/HTM |
| Hardware Version: | M633_V1.1 |
| Software Version: | WD03_D01_151217 |
| Power Supply: | DC 3.7V from rechargeable lithium battery Battery capacity: 2000mAH |
| 2G | |
| Operation Band: | GSM850, PCS1900 |
| Supported type: | GPRS/ EGPRS |
| Power Class: | GSM850:Power Class 5; GSM1900:Power Class 0 |
| Modulation Type: | GMSK for GPRS; GMSK /8PSK for EGPRS , |
| GSM Release Version: | R99 |
| GPRS Multislot Class: | 12 |
| EGPRS Multislot Class: | 12 |
| 3G | |
| Operation Band: | FDD Band II & FDD Band V |
| Power Class: | Power Class 3 |
| Modulation Type: | QPSK for WCDMA/HSDPA/HSUPA |
| WCDMA Release Version: | R99 |
| HSDPA Release Version: | Release 5 |
| HSUPA Release Version: | Release 6 |
| DC-HSUPA Release Version: | Not Supported |
| WiFi | |
| Supported type: | 802.11b/802.11g/802.11n |
| Modulation: | 802.11b: DSSS 802.11g/802.11n:OFDM |
| Operation frequency: | 802.11b/802.11g/802.11n(HT20):2412MHz~2462MHz; |
| Channel number: | 802.11b/802.11g/802.11n(HT20):11; |
| Channel separation: | 5MHz |

5. RF Exposure Limit

| Type Exposure | SAR (W/kg) |
|---|-----------------------------|
| | Uncontrolled Exposure Limit |
| Spatial Peak SAR (10g cube tissue for head and trunk) | 2.00 |
| Spatial Peak SAR (10g cube tissue for limbs) | 4.00 |
| Spatial Peak SAR (10g cube tissue for whole body) | 0.08 |

Note:

1. This limit is according to recommendation 1999/519/EC, Annex II (Basic Restrictions)
2. Occupational/Uncontrolled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation)

6. SAR Measurement System Configuration

6.1. SAR Measurement Set-up

The OPENSAR system for performing compliance tests consist of the following items:

A standard high precision 6-axis robot (KUKA) with controller and software.

KUKA Control Panel (KCP)

A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with a Video Positioning System (VPS).

The stress sensor is composed with mechanical and electronic when the electronic part detects a change on the electro-mechanical switch; it sends an “Emergency signal” to the robot controller that to stop robot's moves A computer operating Windows XP.


OPENSAR software Remote control with teaches pendant and additional circuitry for robot safety such as warning lamps, etc.

The SAM phantom enabling testing left-hand right-hand and body usage.

The Position device for handheld EUT

Tissue simulating liquid mixed according to the given recipes.

System validation dipoles to validate the proper functioning of the system.



KUKA SAR Test System Configuration

6.2. E-field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by MVG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

Probe Specification

Construction Symmetrical design with triangular core
Interleaved sensors
Built-in shielding against static charges
PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration ISO/IEC 17025 calibration service available.

| | |
|--|---|
| Device Type | COMOSAR DOSIMETRIC E FIELD PROBE |
| Manufacturer | MVG |
| Model | SSE5 |
| Serial Number | SN 07/15 EP248 |
| Frequency Range of Probe | 0.45 GHz-3GHz |
| Resistance of Three Dipoles at Connector | Dipole 1:R1=0.180MΩ Dipole 2:R3=0.191MΩ Dipole 3:R3=0.179MΩ |



Photo of E-Field Probe

6.3. Phantom

The SAM Phantom SAM120 is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is in compliance with the specification set in IEEE P1528 and CENELEC EN62209-1, EN62209-2:2010.

The phantom enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region.

A cover prevents the evaporation of the liquid.

Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot


System checking was performed using the flat section, whilst Head SAR tests used the left and right head profile sections.

Body SAR testing also used the flat section between the head profiles.

Name: COMOSAR IEEE SAM PHANTOM

S/N: SN 19/15 SAM 120

Manufacture: MVG



SAM Twin Phantom


6.4. Device Holder

In combination with the Generic Twin Phantom SAM120, the Mounting Device enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeatedly positioned according to the FCC and CENELEC specifications.

The device holder can be locked at different phantom locations (left head, right head, flat phantom).



COMOSAR Mobile phone positioning system



6.5. Data Storage and Evaluation

Data Storage

The OPENSAR software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

Data Evaluation

The OPENSAR software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

| | | |
|--------------------|---------------------------|----------------------|
| Probe parameters: | - Sensitivity | Normi, ai0, ai1, ai2 |
| | - Conversion factor | ConvFi |
| | - Diode compression point | Dcpi |
| Device parameters: | - Frequency | f |
| | - Crest factor | cf |
| Media parameters: | - Conductivity | σ |
| | - Density | ρ |

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the OPENSAR components. In the direct measuring mode of the millimetre option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$Vi = Ui + Ui2 \cdot c f / d c pi$$

| | | |
|------|--------------------------------------|-----------------|
| With | Vi = compensated signal of channel i | (i = x, y, z) |
| | Ui = input signal of channel i | (i = x, y, z) |
| | cf = crest factor of exciting field | (MVG parameter) |
| | dcpi = diode compression point | (MVG parameter) |

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E-field probes: } Ei = (Vi / Normi \cdot ConvF) 1/2$$

$$\text{H-field probes: } Hi = (Vi) 1/2 \cdot (ai0 + ai1 f + ai2 f^2) / f$$

| | | | |
|------|-------|---|---------------|
| With | Vi | = compensated signal of channel i | (i = x, y, z) |
| | Normi | = sensor sensitivity of channel i | (i = x, y, z) |
| | | [mV/(V/m)2] for E-field Probes | |
| | ConvF | = sensitivity enhancement in solution | |
| | aij | = sensor sensitivity factors for H-field probes | |
| | f | = carrier frequency [GHz] | |
| | Ei | = electric field strength of channel i in V/m | |

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{\text{tot}} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{\text{tot}})^2 \cdot \sigma / (\rho \cdot 1000)$$

with SAR = local specific absorption rate in mW/g
 E_{tot} = total field strength in V/m
 σ = conductivity in [mho/m] or [Siemens/m]
 ρ = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

6.6. Position of the wireless device in relation to the phantom

Handset Reference Points

$$P_{\text{pwe}} = E_{\text{tot}}^2 / 3770 \text{ or } P_{\text{pwe}} = H_{\text{tot}}^2 \cdot 37.7$$

With P_{pwe} = equivalent power density of a plane wave in mW/cm²

E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m




W_t Width of the handset at the level of the acoustic

W_b Width of the bottom of the handset


A Midpoint of the width w_t of the handset at the level of the acoustic output

B Midpoint of the width w_b of the bottom of the handset

Positioning for Cheek / Touch



Positioning for Ear / 15° Tilt



Body Worn Accessory Configurations

To position the device parallel to the phantom surface with either keypad up or down.

To adjust the device parallel to the flat phantom.

To adjust the distance between the device surface and the flat phantom to 15mm or holster surface and the flat phantom to 0 mm.




Illustration for Body Worn Position

Wireless Router (Hotspot) Configurations

Some battery-operated handsets have the capability to transmit and receive internet connectivity through simultaneous transmission of WIFI in conjunction with a separate licensed transmitter. The FCC has provided guidance in KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq$

9 cm x 5 cm) are based on a composite test separation distance of 10 mm from the front, back and edges of the device with antennas 2.5 cm or closer to the edge of the device, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. Therefore, SAR must be evaluated for each frequency transmission and mode separately and summed with the WIFI transmitter according to KDB 648474 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.





Illustration for Hotspot Position

Limb-worn device

A limb-worn device is a unit whose intended use includes being strapped to the arm or leg of the user while transmitting (except in idle mode). It is similar to a body-worn device. Therefore, the test positions of 6.1.4.4 also apply. The strap shall be opened so that it is divided into two parts as shown in Figure 9. The device shall be positioned directly against the phantom surface with the strap straightened as much as possible and the back of the device towards the phantom.

If the strap cannot normally be opened to allow placing in direct contact with the phantom surface, it may be necessary to break the strap of the device but ensuring to not damage the antenna.



Test position for limb-worn devices

6.7. Tissue Verification

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine of the dielectric are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.

The following materials are used for producing the tissue-equivalent materials.

| Ingredients (% of weight) | Head Tissue | | | | | |
|---------------------------|-------------|-------|-------|--------|------|--------|
| Frequency Band (MHz) | 750 | 835 | 1800 | 1900 | 2450 | 2600 |
| Water | 39.2 | 41.45 | 52.64 | 55.242 | 62.7 | 55.242 |
| Salt (NaCl) | 2.7 | 1.45 | 0.36 | 0.306 | 0.5 | 0.306 |
| Sugar | 57.0 | 56.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| HEC | 0.0 | 1.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Bactericide | 0.0 | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 |
| Triton X-100 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| DGBE | 0.0 | 0.0 | 47.0 | 44.542 | 36.8 | 44.452 |
| Ingredients (% of weight) | Body Tissue | | | | | |
| Frequency Band (MHz) | 750 | 835 | 1800 | 1900 | 2450 | 2600 |
| Water | 50.3 | 52.4 | 69.91 | 69.91 | 73.2 | 64.493 |
| Salt (NaCl) | 1.60 | 1.40 | 0.13 | 0.13 | 0.04 | 0.024 |
| Sugar | 47.0 | 45.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| HEC | 0.0 | 1.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Bactericide | 0.0 | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 |
| Triton X-100 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| DGBE | 0.0 | 0.0 | 29.96 | 29.96 | 26.7 | 32.252 |

6.8. Tissue Dielectric Parameters

The liquid used for the frequency range of 100MHz-6G consisted of water, sugar, salt and Cellulose. The liquid has been previously proven to be suited for worst-case. The following Table shows the detail solution. It's satisfying the latest tissue dielectric parameters requirements proposed by the IEEE 1528 and IEC 62209. The simulating liquids should be checked at the beginning of a series of SAR measurements to determine of the dielectric parameter are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.

The following materials are used for producing the tissue-equivalent materials

Targets for tissue simulating liquid

| Frequency (MHz) | Liquid Type | Liquid Type (σ) | $\pm 5\%$ Range | Permittivity (ϵ) | $\pm 5\%$ Range |
|-----------------|-------------|--------------------------|-----------------|-----------------------------|-----------------|
| 300 | Head | 0.87 | 0.83~0.91 | 45.3 | 43.04~47.57 |
| 450 | Head | 0.87 | 0.83~0.91 | 43.5 | 41.33~45.68 |
| 835 | Head | 0.90 | 0.86~0.95 | 41.5 | 39.43~43.58 |
| 900 | Head | 0.97 | 0.92~1.02 | 41.5 | 39.43~43.58 |
| 1800-2000 | Head | 1.40 | 1.33~1.47 | 40.0 | 38.00~42.00 |
| 2450 | Head | 1.80 | 1.71~1.89 | 39.2 | 37.24~41.16 |
| 3000 | Head | 2.40 | 2.28~2.52 | 38.5 | 36.58~40.43 |
| 5800 | Head | 5.27 | 5.01~5.53 | 35.3 | 33.54~37.07 |
| 300 | Body | 0.92 | 0.87~0.97 | 58.2 | 55.29~61.11 |
| 450 | Body | 0.94 | 0.89~0.99 | 56.7 | 53.87~59.54 |

| | | | | | |
|-----------|------|------|-----------|------|-------------|
| 835 | Body | 0.97 | 0.92~1.02 | 55.2 | 52.44~57.96 |
| 900 | Body | 1.05 | 1.00~1.10 | 55.0 | 52.25~57.75 |
| 1800-2000 | Body | 1.52 | 1.44~1.60 | 53.3 | 50.64~55.97 |
| 2450 | Body | 1.95 | 1.85~2.05 | 52.7 | 50.07~55.34 |
| 3000 | Body | 2.73 | 2.60~2.87 | 52.0 | 49.40~54.60 |
| 5800 | Body | 6.00 | 5.70~6.30 | 48.2 | 45.79~50.61 |

(ϵ_r = relative permittivity, σ = conductivity and ρ = 1000 kg/m³)

6.9. Tissue-equivalent Liquid Properties


| Frequency (MHz) | Liquid Type | Test Date | Temp °C | ϵ_r | σ (s/m) |
|--------------------|----------------|------------|------------|--------------|----------------|
| 835 | Body | 24/02/2016 | 24 | 54.49 | 0.99 |
| 1900 | Body | 25/02/2016 | 24 | 53.30 | 1.43 |
| 2450 | Body | 26/02/2016 | 24 | 54.61 | 2.01 |

6.10. System Check

The SAR system must be validated against its performance specifications before it is deployed. When SAR probe and system component or software are changed, upgraded or recalibrated, these must be validated with the SAR system(s) that operates with such component. Reference dipoles are used with the required tissue-equivalent media for system validation.

System check results have to be equal or near the values determined during dipole calibration with the relevant liquids and test system ($\pm 10\%$).

System check is performed regularly on all frequency bands where tests are performed with the OPENSAR system.



System Check Set-up

| Verification Results | Frequency (MHz) | Measured Value in 100mW (W/kg) | | Normalized to 1W (W/kg) | | Target Value (W/kg) | | Deviation (%) | |
|----------------------|-----------------|--------------------------------|--------------|-------------------------|--------------|---------------------|--------------|---------------|--------------|
| | | 1 g Average | 10 g Average | 1 g Average | 10 g Average | 1 g Average | 10 g Average | 1 g Average | 10 g Average |
| | 835 | 0.949 | 0.633 | 9.49 | 6.33 | 9.60 | 6.36 | -1.15 | -0.47 |
| | 1900 | 3.766 | 1.992 | 37.66 | 19.92 | 38.73 | 20.48 | -2.76 | -2.64 |
| | 2450 | 5.066 | 2.416 | 50.66 | 24.16 | 50.72 | 24.43 | -2.76 | -2.64 |

Comparing to the original SAR value provided by MVG, the verification data should be within its specification of 10%. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table as below indicates the system performance check can meet the variation criterion and the plots can be referred to Section 10 of this report.

7. Measurement Procedure

Conducted power measurement

For WWAN power measurement, use base station simulator to configure EUT WWAN transition in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.

Read the WWAN RF power level from the base station simulator.

For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band.

Connect EUT RF port through RF cable to the power meter or spectrum analyzer, and measure WLAN/BT output power.

Conducted power measurement

Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.

Place the EUT in positions as Appendix B demonstrates.

Set scan area, grid size and other setting on the MVG software.

Measure SAR results for the highest power channel on each testing position.

Find out the largest SAR result on these testing positions of each band.

Measure SAR results for other channels in worst SAR testing position if the Reported SAR or highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

Power reference measurement

Area scan

Zoom scan

Power drift measurement

Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The MVG software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a “cube” measurement. The measured volume must include the 1g and 10 g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine. The system always gives the maximum values for 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

Extraction of the measured data (grid and values) from the Zoom Scan.

Calculation of the SAR value at every measurement point based on all stored data.

Generation of a high-resolution mesh within the measured volume.

Interpolation of all measured values from the measurement grid to the high-resolution grid

Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface

Calculation of the averaged SAR within masses of 1g and 10g.

Power Reference Measurement

The Power Reference Measurement and Power Drift Measurement are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties

Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10g. Area scan and zoom scan resolution setting follows KDB 865664 D01 v01r04 quoted below.

| | | ≤ 3 GHz | > 3 GHz |
|--|---|--|---|
| Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface | | 5 ± 1 mm | $\frac{1}{2} \cdot 5 \cdot \ln(2) \pm 0.5$ mm |
| Maximum probe angle from probe axis to phantom surface normal at the measurement location | | $30^\circ \pm 1^\circ$ | $20^\circ \pm 1^\circ$ |
| | | ≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm | $3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm |
| Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$ | | When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device. | |
| Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$ | | ≤ 2 GHz: ≤ 8 mm $2 - 3$ GHz: ≤ 5 mm* | $3 - 4$ GHz: ≤ 5 mm* $4 - 6$ GHz: ≤ 4 mm* |
| Maximum zoom scan spatial resolution, normal to phantom surface | uniform grid: $\Delta z_{\text{Zoom}}(n)$ | ≤ 5 mm | $3 - 4$ GHz: ≤ 4 mm $4 - 5$ GHz: ≤ 3 mm $5 - 6$ GHz: ≤ 2 mm |
| | graded grid | $\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface $\Delta z_{\text{Zoom}}(n>1)$: between subsequent points | ≤ 4 mm $\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$ |
| Minimum zoom scan volume | x, y, z | ≥ 30 mm | $3 - 4$ GHz: ≥ 28 mm $4 - 5$ GHz: ≥ 25 mm $5 - 6$ GHz: ≥ 22 mm |

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the reported SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD post-processor scan combine and subsequently superpose these measurement data to calculating the multiband SAR.

SAR Averaged Methods

In MVG, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1g and 10g cubes, the extrapolation distance should not be larger than 5 mm.

Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In MVG measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

Power Drift measurement

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for

8. Conducted Output Power

| Band: GSM 850 | Burst Average Power (dBm) | | | Calculation (dB) | Frame-Average Power(dBm) | | |
|-----------------------|---------------------------|--------|--------|------------------|--------------------------|--------|--------------|
| Channel | 128 | 189 | 251 | | 128 | 189 | 251 |
| Frequency | 824.2 | 836.4 | 824.2 | | 824.2 | 836.4 | 824.2 |
| GRPS (GMSK, 1-slot) | 32.61 | 32.68 | 32.72 | -9.03 | 23.58 | 23.65 | 23.69 |
| GRPS (GMSK, 2-slot) | 30.61 | 30.75 | 30.86 | -6.02 | 24.59 | 24.73 | 24.84 |
| GRPS (GMSK, 3-slot) | 28.64 | 28.76 | 28.88 | -4.26 | 24.38 | 24.5 | 24.62 |
| GRPS (GMSK, 4-slot) | 26.49 | 26.64 | 26.25 | -3.01 | 23.48 | 23.63 | 23.24 |
| EGRPS (8DPSK, 1-slot) | 25.73 | 26.04 | 26.00 | -9.03 | 16.70 | 17.01 | 16.97 |
| EGRPS (8DPSK, 2-slot) | 25.37 | 25.58 | 25.47 | -6.02 | 19.35 | 19.56 | 19.45 |
| EGRPS (8DPSK, 3-slot) | 23.76 | 23.87 | 23.78 | -4.26 | 19.50 | 19.61 | 19.52 |
| EGRPS (8DPSK, 4-slot) | 21.32 | 21.36 | 21.45 | -3.01 | 18.31 | 18.35 | 18.44 |
| Band: GSM 1900 | Burst Average Power (dBm) | | | Calculation (dB) | Frame-Average Power(dBm) | | |
| Channel | 512 | 661 | 810 | | 512 | 661 | 810 |
| Frequency | 1850.2 | 1880.0 | 1909.8 | | 1850.2 | 1880.0 | 1909.8 |
| GRPS (GMSK, 1-slot) | 27.29 | 27.32 | 28.56 | -9.03 | 18.26 | 18.29 | 19.53 |
| GRPS (GMSK, 2-slot) | 25.23 | 25.34 | 26.23 | -6.02 | 19.21 | 19.32 | 20.21 |
| GRPS (GMSK, 3-slot) | 23.55 | 23.64 | 24.57 | -4.26 | 19.29 | 19.38 | 20.31 |
| GRPS (GMSK, 4-slot) | 21.60 | 21.70 | 22.64 | -3.01 | 18.59 | 18.69 | 19.63 |
| EGRPS (8DPSK, 1-slot) | 25.21 | 24.52 | 24.88 | -9.03 | 16.18 | 15.49 | 15.85 |
| EGRPS (8DPSK, 2-slot) | 24.74 | 24.05 | 24.47 | -6.02 | 18.72 | 18.03 | 18.45 |
| EGRPS (8DPSK, 3-slot) | 22.91 | 22.14 | 22.54 | -4.26 | 18.65 | 17.88 | 18.28 |
| EGRPS (8DPSK, 4-slot) | 20.21 | 20.01 | 20.04 | -3.01 | 17.20 | 17.00 | 17.03 |

Note:

- The frame-averaged power is linearly reported the maximum burst averaged power over 8 time slots. The calculated method are shown as below:
The duty cycle "x" of different time slots as below:
1 TX slot is 1/8, 2 TX slots is 2/8, 3 TX slots is 3/8 and 4 TX slots is 4/8
Based on the calculation formula:
Frame-averaged power = Burst averaged power + 10 log (x)
So,
Frame-averaged power (1 TX slot) = Burst averaged power (1 TX slot) - 9.03
Frame-averaged power (2 TX slots) = Burst averaged power (2 TX slots) - 6.02
Frame-averaged power (3 TX slots) = Burst averaged power (3 TX slots) - 4.26
Frame-averaged power (4 TX slots) = Burst averaged power (4 TX slots) - 3.01
- For Hotspot mode SAR testing, GPRS mode should be evaluated, therefore the EUT was set in GPRS 4 TX slots mode due to the highest frame-averaged power.
- For GPRS multi time slots SAR measurement, when the measured maximum output power levels are within 0.25 dB of each other, test the configuration with the most number of time slots.
- Per KDB447498 D01 v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.

Conducted power measurement results of GSM850 and GSM1900 (Hotspot disabled)

| Band: GSM 850 | Burst Average Power (dBm) | | | Calculation (dB) | Frame-Average Power(dBm) | | |
|-----------------------|---------------------------|--------|--------|------------------|--------------------------|--------|--------------|
| Channel | 128 | 189 | 251 | | 128 | 189 | 251 |
| Frequency | 824.2 | 836.4 | 848.8 | | 824.2 | 836.4 | 848.8 |
| GRPS (GMSK, 1-slot) | 30.31 | 30.38 | 30.42 | -9.03 | 21.28 | 21.35 | 21.39 |
| GRPS (GMSK, 2-slot) | 28.31 | 28.45 | 28.56 | -6.02 | 22.29 | 22.43 | 22.54 |
| GRPS (GMSK, 3-slot) | 26.34 | 26.46 | 26.58 | -4.26 | 22.08 | 22.20 | 22.32 |
| GRPS (GMSK, 4-slot) | 24.19 | 24.34 | 23.95 | -3.01 | 21.18 | 21.33 | 20.94 |
| EGRPS (8DPSK, 1-slot) | 23.43 | 23.74 | 23.70 | -9.03 | 14.40 | 14.71 | 14.67 |
| EGRPS (8DPSK, 2-slot) | 23.07 | 23.28 | 23.17 | -6.02 | 17.05 | 17.26 | 17.15 |
| EGRPS (8DPSK, 3-slot) | 21.46 | 21.57 | 21.48 | -4.26 | 17.20 | 17.31 | 17.22 |
| EGRPS (8DPSK, 4-slot) | 19.02 | 19.06 | 19.15 | -3.01 | 16.01 | 16.05 | 16.14 |
| Band: GSM 1900 | Burst Average Power (dBm) | | | Calculation (dB) | Frame-Average Power(dBm) | | |
| Channel | 512 | 661 | 810 | | 512 | 661 | 810 |
| Frequency | 1850.2 | 1880.0 | 1909.8 | | 1850.2 | 1880.0 | 1909.8 |
| GRPS (GMSK, 1-slot) | 24.87 | 24.9 | 25.14 | -9.03 | 15.81 | 15.87 | 16.11 |
| GRPS (GMSK, 2-slot) | 22.81 | 22.92 | 23.81 | -6.02 | 16.75 | 16.90 | 17.79 |
| GRPS (GMSK, 3-slot) | 22.13 | 22.02 | 22.15 | -4.26 | 17.87 | 17.76 | 17.89 |
| GRPS (GMSK, 4-slot) | 19.18 | 19.28 | 20.22 | -3.01 | 16.17 | 16.29 | 17.21 |
| EGRPS (8DPSK, 1-slot) | 22.79 | 22.1 | 22.46 | -9.03 | 13.76 | 13.07 | 13.43 |
| EGRPS (8DPSK, 2-slot) | 22.32 | 21.63 | 22.05 | -6.02 | 16.30 | 15.61 | 16.01 |
| EGRPS (8DPSK, 3-slot) | 20.49 | 19.72 | 20.12 | -4.26 | 16.23 | 15.46 | 15.86 |
| EGRPS (8DPSK, 4-slot) | 19.01 | 19.03 | 19.07 | -3.01 | 14.78 | 14.57 | 14.63 |

Note:

- The frame-averaged power is linearly reported the maximum burst averaged power over 8 time slots. The calculated method are shown as below:
The duty cycle "x" of different time slots as below:
1 TX slot is 1/8, 2 TX slots is 2/8, 3 TX slots is 3/8 and 4 TX slots is 4/8
Based on the calculation formula:
Frame-averaged power = Burst averaged power + 10 log (x)
So,
Frame-averaged power (1 TX slot) = Burst averaged power (1 TX slot) - 9.03
Frame-averaged power (2 TX slots) = Burst averaged power (2 TX slots) - 6.02
Frame-averaged power (3 TX slots) = Burst averaged power (3 TX slots) - 4.26
Frame-averaged power (4 TX slots) = Burst averaged power (4 TX slots) - 3.01
- For Hotspot mode SAR testing, GPRS mode should be evaluated, therefore the EUT was set in GPRS 4 TX slots mode due to the highest frame-averaged power.
- For GPRS multi time slots SAR measurement, when the measured maximum output power levels are within 0.25 dB of each other, test the configuration with the most number of time slots.
- Per KDB447498 D01 v06 , the maximum output power channel is used for SAR testing and for further SAR test reduction.

Conducted power measurement results of GSM850 and GSM1900 (Hotspot activated)

| Band | WCDMA Band II | | | WCDMA Band V | | |
|-----------------|---------------|--------------|--------|--------------|-------|-------|
| Channel | 9262 | 9400 | 9538 | 4132 | 4183 | 4233 |
| Frequency | 1852.4 | 1880.0 | 1907.6 | 826.4 | 836.6 | 846.6 |
| RMC 12.2Kbps | 23.18 | 23.39 | 23.24 | 23.09 | 23.04 | 22.99 |
| HSDPA Subtest-1 | 21.16 | 21.33 | 21.09 | 22.06 | 21.95 | 21.88 |
| HSDPA Subtest-2 | 21.11 | 21.20 | 20.94 | 22.00 | 21.90 | 21.84 |
| HSDPA Subtest-3 | 20.57 | 20.68 | 20.53 | 21.59 | 21.44 | 21.40 |
| HSDPA Subtest-4 | 20.49 | 20.66 | 20.46 | 21.56 | 21.39 | 21.38 |
| HSUPA Subtest-1 | 20.98 | 21.03 | 20.58 | 20.64 | 20.97 | 20.59 |
| HSUPA Subtest-2 | 20.64 | 20.87 | 20.64 | 20.49 | 20.80 | 20.47 |
| HSUPA Subtest-3 | 20.54 | 20.34 | 20.63 | 20.45 | 20.46 | 20.41 |
| HSUPA Subtest-4 | 20.74 | 20.68 | 20.15 | 20.35 | 20.24 | 20.03 |
| HSUPA Subtest-5 | 20.78 | 20.97 | 20.88 | 20.62 | 20.59 | 20.64 |

Note:

1. According to the power listed above, the HSDPA and HSUPA were not determined for SAR testing.
2. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2kbps RMC(reference measurement channel) configuration in test loop mode

Conducted power measurement results of WCDMA Band II and WCDMA Band V (Hotspot disabled)

| Band | WCDMA Band II | | | WCDMA Band V | | |
|-----------------|---------------|--------------|--------|--------------|-------|-------|
| Channel | 9262 | 9400 | 9538 | 4132 | 4183 | 4233 |
| Frequency | 1852.4 | 1880.0 | 1907.6 | 826.4 | 836.6 | 846.6 |
| RMC 12.2Kbps | 20.62 | 20.83 | 20.68 | 20.55 | 20.50 | 20.45 |
| HSDPA Subtest-1 | 18.60 | 18.77 | 18.53 | 19.52 | 19.41 | 19.34 |
| HSDPA Subtest-2 | 18.55 | 18.64 | 18.38 | 19.46 | 19.36 | 19.30 |
| HSDPA Subtest-3 | 18.01 | 18.12 | 17.97 | 19.05 | 18.90 | 18.86 |
| HSDPA Subtest-4 | 17.93 | 18.10 | 17.90 | 19.02 | 18.85 | 18.84 |
| HSUPA Subtest-1 | 18.42 | 18.47 | 18.02 | 18.10 | 18.43 | 18.05 |
| HSUPA Subtest-2 | 18.08 | 18.31 | 18.08 | 18.95 | 18.26 | 18.93 |
| HSUPA Subtest-3 | 17.98 | 17.78 | 18.07 | 18.91 | 18.92 | 18.87 |
| HSUPA Subtest-4 | 18.18 | 18.42 | 18.59 | 19.81 | 19.70 | 19.49 |
| HSUPA Subtest-5 | 18.22 | 18.41 | 18.32 | 18.08 | 18.05 | 18.10 |

Note:

1. According to the power listed above, the HSDPA and HSUPA were not determined for SAR testing.
2. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2kbps RMC(reference measurement channel) configuration in test loop mode

Conducted power measurement results of WCDMA Band II and WCDMA Band V (Hotspot activated)

| WLAN 2.4G | | | | | | |
|---------------------|---------------|-------|-------|---------------|------|-------|
| Mode | 802.11b | | | 802.11g | | |
| Channel | 1 | 6 | 11 | 1 | 6 | 11 |
| Frequency | 2412 | 2437 | 2462 | 2412 | 2437 | 2462 |
| Average Power (dBm) | 13.73 | 11.62 | 14.08 | 10.83 | 8.91 | 11.06 |
| Mode | 802.11n(HT20) | | | 802.11n(HT40) | | |
| Channel | 1 | 6 | 13 | 3 | 6 | 11 |
| Frequency | 2412 | 2437 | 2462 | 2412 | 2437 | 2462 |
| Average Power (dBm) | 8.81 | 7.14 | 9.29 | / | / | / |

Conducted power measurement results of wifi 2.4G

Note

1. The average power of wifi is measured with RMS detector.
2. Per KDB 248227, for wifi 2.4Ghz, highest average RF output channel for the lowest data rat of 802.11b mode was selected for SAR evalutation. SAR test at higher data rates and higher order modulation (including 802.11 g/n) were not required since the maximum average output power for each of these configurations is not more than 1/4 dB higher than the test channel for the lowest data rate of 802.11b mode

9. SAR Test Results Summary

9.1. Body-Worn 1g SAR Data

| Band | Mode | Test Position with5mm | CH. | Freq. (MHz) | Ave. Power (dBm) | Power Drift (%) | Tune-Up Limit (dBm) | Meas. SAR1g (W/kg) | Scaling Factor | Reported SAR1g (W/kg) | Limit (W/Kg) |
|---------------|--------------|-----------------------|------|-------------|------------------|-----------------|---------------------|--------------------|----------------|-----------------------|--------------|
| GSM850 | GPRS 2 slots | Front | 251 | 848.8 | 30.86 | -1.61 | 32.00 | 0.62 | 1.300 | 0.81 | 1.6 |
| | | Back | 251 | 848.8 | 30.86 | 0.20 | 32.00 | 0.65 | 1.300 | 0.85 | |
| GSM1900 | GPRS 3 slots | Front | 810 | 1909.8. | 24.57 | 1.13 | 25.00 | 0.57 | 1.083 | 0.62 | 1.6 |
| | | Back | 810 | 1909.8. | 24.57 | -2.22 | 25.00 | 0.61 | 1.083 | 0.66 | |
| WCDMA Band II | RMC | Front | 9400 | 1880 | 23.39 | -2.05 | 24.00 | 0.56 | 1.047 | 0.59 | 1.6 |
| | | Back | 9400 | 1880 | 23.39 | -4.02 | 24.00 | 0.61 | 1.047 | 0.64 | |
| WCDMA Band V | RMC | Front | 4132 | 826.4 | 23.09 | 1.36 | 24.00 | 0.55 | 1.061 | 0.58 | 1.6 |
| | | Back | 4132 | 826.4 | 23.09 | -0.11 | 24.00 | 0.60 | 1.061 | 0.64 | |
| 2.4G | 802.11b | Front | 11 | 2462 | 14.08 | -3.31 | 15.00 | 0.10 | 1.078 | 0.11 | 1.6 |
| | | Back | 11 | 2462 | 14.08 | 3.48 | 15.00 | 0.12 | 1.078 | 0.13 | |

Note:

1. Per KDB 447498 D01 v06, for each exposure position, if the highest output power channel Reported SAR $\leq 0.8\text{W/kg}$, other channels SAR testing is not necessary.
2. Per KDB 447498 D01 v06, body-worn use is evaluated with the device positioned at 5 mm from a flat phantom filled with head tissue-equivalent medium.
3. Per KDB 447498 D01 v06, the report SAR is measured SAR value adjusted for maximum tune-up tolerance. Scaling Factor=tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.

Reported SAR(W/kg)=Measured SAR (W/kg)*Scaling Factor.

9.2. Hotspot 1g SAR Data

| Band | Mode | Test Position with10mm | CH. | Freq. (MHz) | Ave. Power (dBm) | Power Drift (%) | Tune-Up Limit (dBm) | Meas. SAR1g (W/kg) | Scaling Factor | Reported SAR1g (W/kg) | Limit (W/Kg) |
|--------------|--------------|------------------------|------|-------------|------------------|-----------------|---------------------|--------------------|----------------|-----------------------|--------------|
| GSM850 | GPRS 2 slots | Front | 251 | 848.8 | 28.56 | 0.83 | 30.00 | 0.74 | 1.043 | 0.77 | 1.6 |
| | | Back | 128 | 824.2 | 28.56 | -0.26 | 30.00 | 0.72 | 1.043 | 0.75 | |
| | | Back | 190 | 836.6 | 28.56 | 1.83 | 30.00 | 0.72 | 1.043 | 0.78 | |
| | | Back | 251 | 848.8 | 28.56 | -1.27 | 30.00 | 0.85 | 1.043 | 0.89 | |
| | | Left | 251 | 848.8 | 28.56 | 2.07 | 30.00 | 0.25 | 1.043 | 0.26 | |
| | | Right | 251 | 848.8 | 28.56 | 2.55 | 30.00 | 0.27 | 1.043 | 0.28 | |
| | | Top | 251 | 848.8 | 28.56 | -0.18 | 30.00 | 0.07 | 1.043 | 0.07 | |
| GSM1900 | GPRS 3 slots | Front | 810 | 1909.8. | 22.15 | 0.35 | 24.00 | 0.61 | 1.059 | 0.65 | 1.6 |
| | | Back | 810 | 1909.8. | 22.15 | -1.29 | 24.00 | 0.66 | 1.059 | 0.70 | |
| | | Left | 810 | 1909.8. | 22.15 | -2.30 | 24.00 | 0.33 | 1.059 | 0.35 | |
| | | Right | 810 | 1909.8. | 22.15 | -1.66 | 24.00 | 0.30 | 1.059 | 0.32 | |
| | | Top | 810 | 1909.8. | 22.15 | 3.52 | 24.00 | 0.05 | 1.059 | 0.05 | |
| UMTS Band II | RMC | Front | 9400 | 1880 | 20.83 | -3.33 | 22.00 | 0.53 | 1.080 | 0.57 | 1.6 |
| | | Back | 9400 | 1880 | 20.83 | -3.25 | 22.00 | 0.59 | 1.080 | 0.64 | |
| | | Left | 9400 | 1880 | 20.83 | 1.11 | 22.00 | 0.31 | 1.080 | 0.33 | |
| | | Right | 9400 | 1880 | 20.83 | 1.03 | 22.00 | 0.29 | 1.080 | 0.31 | |
| | | Top | 9400 | 1880 | 20.83 | 4.04 | 22.00 | 0.04 | 1.080 | 0.04 | |
| UMTS Band V | RMC | Front | 4132 | 826.4 | 20.55 | 3.31 | 22.00 | 0.39 | 1.095 | 0.43 | 1.6 |
| | | Back | 4132 | 826.4 | 20.55 | -2.12 | 22.00 | 0.42 | 1.095 | 0.46 | |
| | | Left | 4132 | 826.4 | 20.55 | 2.29 | 22.00 | 0.31 | 1.095 | 0.34 | |
| | | Right | 4132 | 826.4 | 20.55 | -0.51 | 22.00 | 0.29 | 1.095 | 0.32 | |
| | | Top | 4132 | 826.4 | 20.55 | 3.21 | 22.00 | 0.04 | 1.095 | 0.04 | |
| 2.4GHZ | 802.11b | Front | 11 | 2462 | 14.08 | 1.12 | 15.00 | 0.18 | 1.078 | 0.19 | 1.6 |
| | | Back | 11 | 2462 | 14.08 | -1.45 | 15.00 | 0.21 | 1.078 | 0.23 | |
| | | Left | 11 | 2462 | 14.08 | 2.35 | 15.00 | 0.16 | 1.078 | 0.17 | |
| | | Bottom | 11 | 2462 | 14.08 | 1.98 | 15.00 | 0.11 | 1.078 | 0.12 | |

Note:

1. Per KDB 447498 D01 v06, for each exposure position, if the highest output power channel Reported SAR $\leq 0.8\text{W/kg}$, other channels SAR testing is not necessary.
2. Per KDB 447498 D01 v06, body-worn with hotspot use is evaluated with the device positioned at 10 mm from a flat phantom filled with head tissue-equivalent medium.
3. Per KDB 447498 D01 v06, the report SAR is measured SAR value adjusted for maximum tune-up tolerance. Scaling Factor=tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.

Reported SAR(W/kg)=Measured SAR (W/kg)*Scaling Factor.

10. Exposure Position Consideration

10.1. EUT Antenna Location



10.2. Test Position Consideration

| Test Positions | | | | | | | |
|----------------|---------------------|------|-------|----------|-------------|------------|-----------|
| Mode | Exposure Conditions | Back | Front | Top Side | Bottom Side | Right Side | Left Side |
| GSM/WCDMA | Hotspot | Yes | Yes | Yes | No | Yes | Yes |
| WIFI 2.4G | Hotspot | Yes | Yes | No | Yes | No | Yes |

Note:

1. Per KDB 941225 D06 and KDB 648474 D04, particular DUT edges were not required to be evaluated for hotspot SAR if the antenna-to-edge distance is greater than 2.5cm

10.3. Simultaneous Transmission Conclusion

Multi-Band Simultaneous Transmission Considerations

According to FCC KDB Publication 447498 D01 v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the EUT are shown in below Figure and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.



Simultaneous Transmission Possibilities

The Simultaneous Transmission Possibilities of this device are as below:

| NO. | Configuration | Body-worn | Hotspot |
|-----|---------------|-----------|---------|
| 1 | GSM+WIFI | YES | YES |
| 2 | WCDMA+ WIFI | YES | YES |

NOTE:

1.2G&3G share the same Tx antenna and can not transmit simultaneously.

10.4. SAR Simultaneous Transmission Analysis

| Test Position | | Scaled | | Σ SAR (W/kg) | SPLSR | Remark |
|---------------|--------|--------|----------|-----------------|-------|--------|
| | | GSM850 | WIFI2.4G | | | |
| Body-Wron | Front | 0.81 | 0.11 | 0.92 | N/A | N/A |
| | Back | 0.85 | 0.13 | 0.98 | N/A | N/A |
| Hotspot | Front | 0.77 | 0.19 | 0.96 | N/A | N/A |
| | Back | 0.89 | 0.23 | 1.12 | N/A | N/A |
| | Left | 0.26 | 0.17 | 0.43 | N/A | N/A |
| | Right | 0.28 | / | 0.28 | N/A | N/A |
| | Top | 0.07 | / | 0.07 | N/A | N/A |
| | Bottom | / | 0.12 | 0.12 | N/A | N/A |

| Test Position | | Scaled | | Σ SAR (W/kg) | SPLSR | Remark |
|---------------|--------|---------|----------|-----------------|-------|--------|
| | | GSM1900 | WIFI2.4G | | | |
| Body-Wron | Front | 0.62 | 0.11 | 0.73 | N/A | N/A |
| | Back | 0.66 | 0.13 | 0.79 | N/A | N/A |
| Hotspot | Front | 0.65 | 0.19 | 0.84 | N/A | N/A |
| | Back | 0.70 | 0.23 | 0.93 | N/A | N/A |
| | Left | 0.35 | 0.17 | 0.52 | N/A | N/A |
| | Right | 0.32 | / | 0.32 | N/A | N/A |
| | Top | 0.05 | / | 0.05 | N/A | N/A |
| | Bottom | / | 0.12 | 0.12 | N/A | N/A |

| Test Position | | Scaled | | Σ SAR (W/kg) | SPLSR | Remark |
|---------------|--------|-----------------|----------|-----------------|-------|--------|
| | | UMTS Band II | WIFI2.4G | | | |
| Body-Wron | Front | 0.59 | 0.11 | 0.70 | N/A | N/A |
| | Back | 0.64 | 0.13 | 0.77 | N/A | N/A |
| Hotspot | Front | 0.57 | 0.19 | 0.76 | N/A | N/A |
| | Back | 0.64 | 0.23 | 0.87 | N/A | N/A |
| | Left | 0.33 | 0.17 | 0.50 | N/A | N/A |
| | Right | 0.31 | / | 0.31 | N/A | N/A |
| | Top | 0.04 | / | 0.04 | N/A | N/A |
| | Bottom | / | 0.12 | 0.12 | N/A | N/A |

| Test Position | | Scaled | | Σ SAR (W/kg) | SPLSR | Remark |
|---------------|--------|----------------|----------|-----------------|-------|--------|
| | | UMTS Band V | WIFI2.4G | | | |
| Body-Wron | Front | 0.58 | 0.11 | 0.69 | N/A | N/A |
| | Back | 0.64 | 0.13 | 0.77 | N/A | N/A |
| Hotspot | Front | 0.43 | 0.19 | 0.62 | N/A | N/A |
| | Back | 0.46 | 0.23 | 0.69 | N/A | N/A |
| | Left | 0.34 | 0.17 | 0.51 | N/A | N/A |
| | Right | 0.32 | / | 0.32 | N/A | N/A |
| | Top | 0.04 | / | 0.04 | N/A | N/A |
| | Bottom | / | 0.12 | 0.12 | N/A | N/A |

Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01 v06.

10.5. Measurement Uncertainty (450MHz-3Hz)

UNCERTAINTY EVALUATION FOR HANDSET SAR TEST

| Uncertainty Component | Description | Tol. (± %) | Prob. Dist. | Div. | c_l (1 g) | c_u (10 g) | 1 g u_l (± %) | 10 g u_l (± %) | u_l |
|---|-------------|---------------|----------------|------------|-----------------|-----------------|-----------------------|------------------------|-------|
| Measurement System | | | | | | | | | |
| Probe Calibration | 7.2.1 | 5.8 | N | 1 | 1 | 1 | 5.8 | 5.8 | ± |
| Axial Isotropy | 7.2.1.1 | 3.5 | R | $\sqrt{3}$ | $(1-c_p)^{1/2}$ | $(1-c_p)^{1/2}$ | 1.43 | 1.43 | ± |
| Hemispherical Isotropy | 7.2.1.1 | 5.9 | R | $\sqrt{3}$ | $\sqrt{c_p}$ | $\sqrt{c_p}$ | 2.41 | 2.41 | ± |
| Boundary Effect | 7.2.1.4 | 1 | R | $\sqrt{3}$ | 1 | 1 | 0.58 | 0.58 | ± |
| Linearity | 7.2.1.2 | 4.7 | R | $\sqrt{3}$ | 1 | 1 | 2.71 | 2.71 | ± |
| System Detection Limits | 7.2.1.2 | 1 | R | $\sqrt{3}$ | 1 | 1 | 0.58 | 0.58 | ± |
| Modulation response | 7.2.1.3 | 3 | N | 1 | 1 | 1 | 3.00 | 3.00 | ± |
| Readout Electronics | 7.2.1.5 | 0.5 | N | 1 | 1 | 1 | 0.50 | 0.50 | ± |
| Response Time | 7.2.1.6 | 0 | R | $\sqrt{3}$ | 1 | 1 | 0.00 | 0.00 | ± |
| Integration Time | 7.2.1.7 | 1.4 | R | $\sqrt{3}$ | 1 | 1 | 0.81 | 0.81 | ± |
| RF Ambient Conditions - Noise | 7.2.3.7 | 3 | R | $\sqrt{3}$ | 1 | 1 | 1.73 | 1.73 | ± |
| RF Ambient Conditions - Reflections | 7.2.3.7 | 3 | R | $\sqrt{3}$ | 1 | 1 | 1.73 | 1.73 | ± |
| Probe Positioner Mechanical Tolerance | 7.2.2.1 | 1.4 | R | $\sqrt{3}$ | 1 | 1 | 0.81 | 0.81 | ± |
| Probe Positioning with respect to Phantom Shell | 7.2.2.3 | 1.4 | R | $\sqrt{3}$ | 1 | 1 | 0.81 | 0.81 | ± |
| Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation | 7.2.4 | 2.3 | R | $\sqrt{3}$ | 1 | 1 | 1.33 | 1.33 | ± |
| Test sample Related | | | | | | | | | |
| Test Sample Positioning | 7.2.2.4.4 | 2.6 | N | 1 | 1 | 1 | 2.60 | 2.60 | 11 |
| Device Holder Uncertainty | 7.2.2.4.2 | 3 | N | 1 | 1 | 1 | 3.00 | 3.00 | 7 |
| Output Power Variation - SAR drift measurement | 7.2.3.6 | 5 | R | $\sqrt{3}$ | 1 | 1 | 2.89 | 2.89 | ± |
| SAR scaling | 7.2.5 | 2 | R | $\sqrt{3}$ | 1 | 1 | 1.15 | 1.15 | ± |
| Phantom and Tissue Parameters | | | | | | | | | |
| Phantom Uncertainty (shape and thickness tolerances) | 7.2.2.2 | 4 | R | $\sqrt{3}$ | 1 | 1 | 2.31 | 2.31 | ± |
| Uncertainty in SAR correction for deviation (in permittivity and conductivity) | 7.2.6 | 2 | N | 1 | 1 | 0.84 | 2.00 | 1.68 | ± |
| Liquid Conductivity (temperature uncertainty) | 7.2.3.5 | 2.5 | N | 1 | 0.78 | 0.71 | 1.95 | 1.78 | 5 |
| Liquid Conductivity - measurement uncertainty | 7.2.3.3 | 4 | N | 1 | 0.23 | 0.26 | 0.92 | 1.04 | 5 |
| Liquid Permittivity (temperature uncertainty) | 7.2.3.5 | 2.5 | N | 1 | 0.78 | 0.71 | 1.95 | 1.78 | ± |
| Liquid Permittivity - measurement uncertainty | 7.2.3.4 | 5 | N | 1 | 0.23 | 0.26 | 1.15 | 1.30 | ± |
| Combined Standard Uncertainty | | | RSS | | | | 10.63 | 10.54 | |
| Expanded Uncertainty (95% CONFIDENCE INTERVAL) | | | k | | | | 21.26 | 21.08 | |

UNCERTAINTY FOR SYSTEM PERFORMANCE CHECK

| Uncertainty Component | | Tol. (± %) | Prob. Dist. | Div. | c (1 g) | c (10 g) | 1 g u (± %) | 10 g u (± %) | v |
|---|---------|---------------|----------------|------------|-----------------|-----------------|-------------------|--------------------|-------|
| Measurement System | | | | | | | | | |
| Probe Calibration | 7.2.1 | 5.8 | N | 1 | 1 | 1 | 5.80 | 5.80 | × |
| Axial Isotropy | 7.2.1.1 | 3.5 | R | $\sqrt{3}$ | $(1-c_2)^{1/2}$ | $(1-c_2)^{1/2}$ | 1.43 | 1.43 | × |
| Hemispherical Isotropy | 7.2.1.1 | 5.9 | R | $\sqrt{3}$ | $\sqrt{c_2}$ | $\sqrt{c_2}$ | 2.41 | 2.41 | × |
| Boundary Effect | 7.2.1.4 | 1 | R | $\sqrt{3}$ | 1 | 1 | 0.58 | 0.58 | × |
| Linearity | 7.2.1.2 | 4.7 | R | $\sqrt{3}$ | 1 | 1 | 2.71 | 2.71 | × |
| System Detection Limits | 7.2.1.2 | 1 | R | $\sqrt{3}$ | 1 | 1 | 0.58 | 0.58 | × |
| Modulation response | 7.2.1.3 | 0 | N | 1 | 1 | 1 | 0.00 | 0.00 | × |
| Readout Electronics | 7.2.1.5 | 0.5 | N | 1 | 1 | 1 | 0.50 | 0.50 | × |
| Response Time | 7.2.1.6 | 0 | R | $\sqrt{3}$ | 1 | 1 | 0.00 | 0.00 | × |
| Integration Time | 7.2.1.7 | 1.4 | R | $\sqrt{3}$ | 1 | 1 | 0.81 | 0.81 | × |
| RF Ambient Conditions - Noise | 7.2.3.7 | 3 | R | $\sqrt{3}$ | 1 | 1 | 1.73 | 1.73 | × |
| RF Ambient Conditions - Reflections | 7.2.3.7 | 3 | R | $\sqrt{3}$ | 1 | 1 | 1.73 | 1.73 | × |
| Probe Positioner Mechanical Tolerance | | | | | | | | | |
| Probe Positioning with respect to Phantom Shell | 7.2.2.1 | 1.4 | R | $\sqrt{3}$ | 1 | 1 | 0.81 | 0.81 | × |
| Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation | 7.2.2.3 | 1.4 | R | $\sqrt{3}$ | 1 | 1 | 0.81 | 0.81 | × |
| Dipole | | | | | | | | | |
| Deviation of experimental source from numerical source | | | 4 | N | 1 | 1 | 1 | 4.00 | 4.00 |
| Input Power and SAR drift measurement | 7.2.3.6 | | 5 | R | $\sqrt{3}$ | 1 | 1 | 2.89 | 2.89 |
| Dipole Axis to Liquid Distance | | | 2 | R | $\sqrt{3}$ | 1 | 1 | | × |
| Phantom and Tissue Parameters | | | | | | | | | |
| Phantom Uncertainty (shape and thickness tolerances) | | | 4 | R | $\sqrt{3}$ | 1 | 1 | 2.31 | 2.31 |
| Uncertainty in SAR correction for deviation (in permittivity and conductivity) | 7.2.6 | | 2 | N | 1 | 1 | 0.84 | 2.00 | 1.68 |
| Liquid Conductivity (temperature uncertainty) | 7.2.3.5 | | 2.5 | N | 1 | 0.78 | 0.71 | 1.95 | 1.78 |
| Liquid Conductivity - measurement uncertainty | 7.2.3.3 | | 4 | N | 1 | 0.23 | 0.26 | 0.92 | 1.04 |
| Liquid Permittivity (temperature uncertainty) | 7.2.3.5 | | 2.5 | N | 1 | 0.78 | 0.71 | 1.95 | 1.78 |
| Liquid Permittivity - measurement uncertainty | 7.2.3.4 | | 5 | N | 1 | 0.23 | 0.26 | 1.15 | 1.30 |
| Combined Standard Uncertainty | | | | RSS | | | | 10.15 | 10.05 |
| Expanded Uncertainty (95% CONFIDENCE INTERVAL) | | | | k | | | | 20.29 | 20.10 |

10.6. Test Equipment List

| Test Equipment | Manufacturer | Model | Serial Number | Calibration | |
|---------------------------------|--------------|-----------------|------------------------|--------------------------|-------------------------|
| | | | | Calibration Date (D.M.Y) | Calibration Due (D.M.Y) |
| PC | Lenovo | H3050 | N/A | N/A | N/A |
| Signal Generator | Agilent | N5182A | MY47070282 | 12/09/2015 | 11/09/2016 |
| Multimeter | Keithley | MiltiMeter 2000 | 4078275 | 12/09/2015 | 11/09/2016 |
| Network Analyzer | Agilent | 8753E | US38432457 | 12/09/2015 | 11/09/2016 |
| Wireless Communication Test Set | R & S | CMU200 | 111382 | 12/09/2015 | 11/09/2016 |
| Power Meter | Agilent | E4418B | GB43312526 | 12/09/2015 | 11/09/2016 |
| Power Meter | Agilent | E4416A | MY45101555 | 12/09/2015 | 11/09/2016 |
| Power Meter | Agilent | N1912A | MY50001018 | 12/09/2015 | 11/09/2016 |
| Power Sensor | Agilent | E9301A | MY41497725 | 12/09/2015 | 11/09/2016 |
| Power Sensor | Agilent | E9327A | MY44421198 | 12/09/2015 | 11/09/2016 |
| Power Sensor | Agilent | E9323A | MY53070005 | 12/09/2015 | 11/09/2016 |
| Power Amplifier | PE | PE15A4019 | 112342 | N/A | N/A |
| Directional Coupler | Agilent | 722D | MY52180104 | N/A | N/A |
| Attenuator | Chensheng | FF779 | 134251 | N/A | N/A |
| E-Field PROBE | MVG | SSE5 | SN 07/15 EP248 | 11/05/2015 | 10/05/2016 |
| DIPOLE 835 | MVG | SID835 | SN 16/15 DIP 0G835-369 | 11/05/2015 | 10/05/2016 |
| DIPOLE 1900 | MVG | SID1900 | SN 16/15 DIP 1G900-372 | 11/05/2015 | 10/05/2016 |
| DIPOLE 2450 | MVG | SID 2450 | SN 16/15 DIP 2G450-374 | 11/05/2015 | 10/05/2018 |
| Limesar Dielectric Probe | MVG | SCLMP | SN 19/15 OCPG71 | 06/05/2015 | 05/05/2016 |
| Communication Antenna | MVG | ANTA59 | SN 39/14 ANTA59 | N/A | N/A |
| Mobile Phone Position Device | MVG | MSH101 | SN 19/15 MSH101 | N/A | N/A |
| Dummy Probe | MVG | DP66 | SN 13/15 DP66 | N/A | N/A |
| SAM PHANTOM | MVG | SAM120 | SN 19/15 SAM120 | N/A | N/A |
| PHANTOM TABLE | MVG | TABP101 | SN 19/15 TABP101 | N/A | N/A |
| Robot TABLE | MVG | TABP61 | SN 19/15 TABP61 | N/A | N/A |
| 6 AXIS ROBOT | KUKA | KR6-R900 | 501822 | N/A | N/A |

Note:

1. N/A means this equipment no need to calibrate

2. Each Time means this device need to calibrate every use time

11. System Check Results

Date of measurement: 24/02/2016 Test mode: 835 (Body)


Product Description: Validation

Dipole Model: SID835



E-Field Probe: SSE5 (SN 07/15 EP248)

| Phantom | Validation plane |
|--|------------------|
| Input Power | 100mW |
| Crest Factor | 1.0 |
| Probe Conversion factor | 5.22 |
| Frequency (MHz) | 835.000000 |
| Relative permittivity (real part) | 54.494404 |
| Relative permittivity (imaginary part) | 21.016420 |
| Conductivity (S/m) | 0.991041 |
| Variation (%) | -0.090000 |
| SAR 10g (W/Kg) | 0.633115 |
| SAR 1g (W/Kg) | 0.949498 |

SURFACE SAR



VOLUME SAR



Date of measurement: 25/02/2016 Test mode: 1900MHz (Body)


Product Description: Validation

Dipole Model: SID1900



E-Field Probe: SSE5 (SN 07/15 EP248)

| Phantom | Validation plane |
|--|------------------|
| Input Power | 100mW |
| Crest Factor | 1.0 |
| Probe Conversion factor | 5.05 |
| Frequency (MHz) | 1900.000000 |
| Relative permittivity (real part) | 53.299999 |
| Relative permittivity (imaginary part) | 14.329440 |
| Conductivity (S/m) | 1.430354 |
| Variation (%) | -0.610000 |
| SAR 10g (W/Kg) | 1.992264 |
| SAR 1g (W/Kg) | 3.766110 |

SURFACE SAR



VOLUME SAR





Date of measurement: 26/02/2016 Test mode: 2450MHz (Body)

Product Description: Validation

Dipole Model: SID2450

E-Field Probe: SSE5 (SN 07/15 EP248)

| Phantom | Validation plane |
|--|------------------|
| Input Power | 100mW |
| Crest Factor | 1.0 |
| Probe Conversion factor | 4.36 |
| Frequency (MHz) | 2450.000000 |
| Relative permittivity (real part) | 54.616199 |
| Relative permittivity (imaginary part) | 14.930150 |
| Conductivity (S/m) | 2.012159 |
| Variation (%) | -0.230000 |
| SAR 10g (W/Kg) | 2.416243 |
| SAR 1g (W/Kg) | 5.066334 |





12. SAR Test Data


GSM850

MEASUREMENT 1

High Band SAR (Channel 251):

Date: 24/02/2016

| | |
|---|--|
| Frequency (MHz) | 848.799988 |
| Relative permittivity (real part) | 54.494404 |
| Relative permittivity (imaginary part) | 21.016420 |
| Conductivity (S/m) | 0.991041 |
| Variation (%) | 0.200000 |
| E-Field Probe: | SSE5 (SN 07/15 EP248) |
| Crest Factor: | 2.0 |
| Probe Conversion factor | 5.22 |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm</u> |
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back</u> |
| Band | <u>GSM850(GPRS 2slot)</u> |
| SURFACE SAR | VOLUME SAR |
|  |  |
| Maximum location: X=7.00, Y=11.00 SAR Peak:0.78W/kg | |
| SAR 10g (W/Kg) | 0.569446 |
| SAR 1g (W/Kg) | 0.651939 |




MEASUREMENT 2

Low Band SAR (Channel 128):


Date: 24/02/2016

| | |
|---|---|
| Frequency (MHz) | 824.200012 |
| Relative permittivity (real part) | 54.494404 |
| Relative permittivity (imaginary part) | 21.016420 |
| Conductivity (S/m) | 0.991041 |
| Variation (%) | -0.260000 |
| E-Field Probe: | SSE5 (SN 07/15 EP248) |
| Crest Factor: | 2.0 |
| Probe Conversion factor | 5.22 |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h= 5.00 mm</u> |
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back (hotspot)</u> |
| Band | <u>GSM850(GPRS 2slot)</u> |

SURFACE SAR




VOLUME SAR



Maximum location: X=8.00, Y=8.00 SAR Peak: 0.95 W/kg

| | |
|-----------------------|----------|
| SAR 10g (W/Kg) | 0.498601 |
| SAR 1g (W/Kg) | 0.718284 |





MEASUREMENT 3

Middle Band SAR (Channel 190):

Date: 24/02/2016


| | |
|---|---|
| Frequency (MHz) | 836.599976 |
| Relative permittivity (real part) | 54.494404 |
| Relative permittivity (imaginary part) | 21.016420 |
| Conductivity (S/m) | 0.991041 |
| Variation (%) | 1.830000 |
| E-Field Probe: | SSE5 (SN 07/15 EP248) |
| Crest Factor: | 2.0 |
| Probe Conversion factor | 5.22 |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h= 5.00 mm</u> |
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back(hotspot)</u> |
| Band | <u>GSM850(GPRS 2slot)</u> |

SURFACE SAR



Maximum location: X=8.00, Y=16.00 SAR Peak: 0.94 W/kg

| | |
|-----------------------|----------|
| SAR 10g (W/Kg) | 0.502499 |
| SAR 1g (W/Kg) | 0.715043 |





MEASUREMENT 4

High Band SAR (Channel 251):

Date: 24/02/2016


| | |
|---|---|
| Frequency (MHz) | 848.799988 |
| Relative permittivity (real part) | 54.494404 |
| Relative permittivity (imaginary part) | 21.016420 |
| Conductivity (S/m) | 0.991041 |
| Variation (%) | -1.270000 |
| E-Field Probe: | SSE5 (SN 07/15 EP248) |
| Crest Factor: | 2.0 |
| Probe Conversion factor | 5.22 |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h= 5.00 mm</u> |
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back (hotspot)</u> |
| Band | <u>GSM850(GPRS 2slot)</u> |

SURFACE SAR



Maximum location: X=8.00, Y=24.00 SAR Peak: 1.22 W/kg

| | |
|-----------------------|----------|
| SAR 10g (W/Kg) | 0.576232 |
| SAR 1g (W/Kg) | 0.851553 |



GSM1900



MEASUREMENT 1

High Band SAR (Channel 810):

Date: 25/02/2016


| | |
|---|---|
| Frequency (MHz) | 1909.800049 |
| Relative permittivity (real part) | 53.299999 |
| Relative permittivity (imaginary part) | 14.329440 |
| Conductivity (S/m) | 1.430354 |
| Variation (%) | -2.222036 |
| E-Field Probe: | SSE5 (SN 07/15 EP248) |
| Crest Factor: | 2.0 |
| Probe Conversion factor | 5.05 |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm</u> |
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back</u> |
| Band | <u>GSM1900(GPRS 3slot)</u> |

SURFACE SAR



Maximum location: X=8.00, Y=12.00 SAR Peak: 0.73 W/kg

| | |
|-----------------------|----------|
| SAR 10g (W/Kg) | 0.575975 |
| SAR 1g (W/Kg) | 0.610865 |




MEASUREMENT 2

High Band SAR (Channel 810):


Date: 25/02/2016

| | |
|---|---|
| Frequency (MHz) | 1909.800049 |
| Relative permittivity (real part) | 53.299999 |
| Relative permittivity (imaginary part) | 14.329440 |
| Conductivity (S/m) | 1.430354 |
| Variation (%) | -1.290250 |
| E-Field Probe: | SSE5 (SN 07/15 EP248) |
| Crest Factor: | 2.0 |
| Probe Conversion factor | 5.05 |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h= 5.00 mm</u> |
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back(hotspot)</u> |
| Band | <u>GSM1900(GPRS 3slot)</u> |

SURFACE SAR




VOLUME SAR



Maximum location: X=7.00, Y=15.00 SAR Peak: 0.69 W/kg

| | |
|-----------------------|----------|
| SAR 10g (W/Kg) | 0.454397 |
| SAR 1g (W/Kg) | 0.663097 |



WCDMA Band II



MEASUREMENT 1

Middle Band SAR (Channel 9400):

Date: 25/02/2016


| | |
|---|---|
| Frequency (MHz) | 1880.000000 |
| Relative permittivity (real part) | 53.299999 |
| Relative permittivity (imaginary part) | 14.329440 |
| Conductivity (S/m) | 1.430354 |
| Variation (%) | -4.021233 |
| E-Field Probe: | SSE5 (SN 07/15 EP248) |
| Crest Factor: | 1.0 |
| Probe Conversion factor | 5.05 |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h= 5.00 mm</u> |
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back</u> |
| Band | <u>BAND2 WCDMA1900</u> |

SURFACE SAR



Maximum location: X=0.00, Y=-15.00 SAR Peak: 0.75 W/kg

| | |
|-----------------------|----------|
| SAR 10g (W/Kg) | 0.512432 |
| SAR 1g (W/Kg) | 0.612565 |




MEASUREMENT 2

Middle Band SAR (Channel 9400):

Date: 25/02/2016

| | |
|---|---|
| Frequency (MHz) | 1880.000000 |
| Relative permittivity (real part) | 53.299999 |
| Relative permittivity (imaginary part) | 14.329440 |
| Conductivity (S/m) | 1.430354 |
| Variation (%) | -3.254010 |
| E-Field Probe: | SSE5 (SN 07/15 EP248) |
| Crest Factor: | 1.0 |
| Probe Conversion factor | 5.05 |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back(hotspot)</u> |
| Band | <u>BAND2 WCDMA1900</u> |
| SURFACE SAR | VOLUME SAR |
| | |
| Maximum location: X=1.00, Y=-15.00 SAR Peak: 0.57 W/kg | |
| SAR 10g (W/Kg) | 0.327635 |
| SAR 1g (W/Kg) | 0.593310 |



WCDMA Band V


MEASUREMENT 1

Low Band SAR (Channel 4132):

Date: 24/02/2016

| | |
|---|---|
| Frequency (MHz) | 826.400024 |
| Relative permittivity (real part) | 54.494404 |
| Relative permittivity (imaginary part) | 21.016420 |
| Conductivity (S/m) | 0.991041 |
| Variation (%) | -0.110000 |
| E-Field Probe: | SSE5 (SN 07/15 EP248) |
| Crest Factor: | 1.0 |
| Probe Conversion factor | 5.22 |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h= 5.00 mm</u> |
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body back</u> |
| Band | <u>BAND5 WCDMA850</u> |




SURFACE SAR



MEASUREMENT 2

Low Band SAR (Channel 4132):

Date: 24/02/2016

| | |
|--|---|
| Frequency (MHz) | 826.400024 |
| Relative permittivity (real part) | 54.494404 |
| Relative permittivity (imaginary part) | 21.016420 |
| Conductivity (S/m) | 0.991041 |
| Variation (%) | 3.310000 |
| E-Field Probe: | SSE5 (SN 07/15 EP248) |
| Crest Factor: | 1.0 |
| Probe Conversion factor | 5.05 |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |
| Phantom | <u>Validation plane</u> |
| Device Position | <u>Body front(hotspot)</u> |
| Band | <u>BAND5 WCDMA850</u> |
| SURFACE SAR | VOLUME SAR |
|  |  |
| Maximum location: X=2.00, Y=-14.00 SAR Peak: 0.49 W/kg | |
| SAR 10g (W/Kg) | 0.384504 |
| SAR 1g (W/Kg) | 0.422172 |
|  | |

WLAN 2.4


MEASUREMENT 1

Low Band SAR (Channel 1):


Date: 26/02/2016

| | |
|---|---|
| Frequency (MHz) | 2412.000000 |
| Relative permittivity (real part) | 54.616199 |
| Relative permittivity (imaginary part) | 14.930150 |
| Conductivity (S/m) | 2.012159 |
| Variation (%) | 3.480000 |
| E-Field Probe: | SSE5 (SN 07/15 EP248) |
| Crest Factor: | 1.0 |
| Probe Conversion factor | 4.36 |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm</u> |
| Phantom | Validation plane |
| Device Position | Body Back |
| Band | <u>IEEE 802.11b ISM</u> |

SURFACE SAR




VOLUME SAR



Maximum location: X=-7.00, Y=32.00 SAR Peak: 0.26 W/kg



| | |
|-----------------------|----------|
| SAR 10g (W/Kg) | 0.106589 |
| SAR 1g (W/Kg) | 0.122433 |




MEASUREMENT 2

Low Band SAR (Channel 1):

Date: 26/02/2016


| | |
|--|---|
| Frequency (MHz) | 2412.000000 |
| Relative permittivity (real part) | 54.616199 |
| Relative permittivity (imaginary part) | 14.930150 |
| Conductivity (S/m) | 2.012159 |
| Variation (%) | -1.450000 |
| E-Field Probe: | SSE5 (SN 07/15 EP248) |
| Crest Factor: | 1.0 |
| Probe Conversion factor | 4.36 |
| Area Scan | <u>dx=8mm dy=8mm, h= 5.00 mm</u> |
| ZoomScan | <u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u> |
| Phantom | Validation plane |
| Device Position | Body back(hotspot) |
| Band | <u>IEEE 802.11b ISM</u> |
| SURFACE SAR | VOLUME SAR |
|  |  |
| Maximum location: X=-15.00, Y=19.00 SAR Peak: 0.37 W/kg | |
| SAR 10g (W/Kg) | 0.120662 |
| SAR 1g (W/Kg) | 0.210963 |




Appendix A:EUT Photos




Appendix B: Test Setup Photos




Hotspot Front (10mm)




Hotspot Back (10mm)




Hotspot Left (10mm)



Hotspot Right (10mm)



Hotspot Top (10mm)



Hotspot Bottom (10mm)



Body-worn Front (5mm)



Body-worn Back (5mm)

Liquid depth



The Body Liquid of 835MHz (15.4cm)



The Body Liquid of 1900MHz (15.9 cm)



The Body Liquid of 2450MHz (15.3cm)

Appendix C: Probe Calibration Certificate

Appendix D: Dipole Calibration Report

(Pls See SAR Appendix.)

*******END OF REPORT*******