

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Report No: CCISE170600102

FCC REPORT

(BLE)

Applicant: Plus One Marketing Ltd.

Address of Applicant: Sumitomofudosan Hibiya building 2F, 2-8-6 Shinbashi,

Minatoku, Tokyo, Japan

Equipment Under Test (EUT)

Product Name: Smart Phone

Model No.: ÖWN FUN PLUS, FTU17B00

Trade mark: ÖWN, Freetel

FCC ID: 2AG5L-FTU161G

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: 01 Jun., 2017

Date of Test: 02 Jun., to 14 Jun., 2017

Date of report issued: 16 Jun., 2017

Test Result: PASS *

Authorized Signature:



Bruce Zhang Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

^{*} In the configuration tested, the EUT complied with the standards specified above.





2 Version

Version No.	Date	Description
Version No.	Date 16 Jun., 2017	This report was amended on FCC ID: 2AG5L-FTU161G follow FCC Class II Permissive Change which were tested and issued by Shenzhen Zhongjian Nanfang Testing Co., Ltd. The differences between them as below: Memory and camera mode. Base on the differences description, AC Power Line
		Conducted Emission, Spurious Emission for BT/BLE/WIFI, the FCC Part 15 Subpart B were re-tested.

Tested by:	Peterzhu	Date:	16 Jun., 2017	
	Test Engineer			
Reviewed by:	Ryan. Lee	Date:	16 Jun., 2017	
	Project Engineer			



3 Contents

			Page
1	COV	/ER PAGE	1
2	VER	SION	2
3		ITENTS	
4		T SUMMARY	
5		IERAL INFORMATION	
9			
	5.1	CLIENT INFORMATION	
	5.2	GENERAL DESCRIPTION OF E.U.T.	
	5.3	TEST ENVIRONMENT AND MODE	
	5.4	DESCRIPTION OF SUPPORT UNITS	
	5.5	LABORATORY FACILITY	
	5.6	LABORATORY LOCATION	
	5.7	TEST INSTRUMENTS LIST	8
6	TES	T RESULTS AND MEASUREMENT DATA	9
	6.1	ANTENNA REQUIREMENT:	9
	6.2	CONDUCTED EMISSION	10
	6.3	CONDUCTED OUTPUT POWER	13
	6.4	OCCUPY BANDWIDTH	14
	6.5	Power Spectral Density	
	6.6	BAND EDGE	16
	6.6.1		
	6.6.2		
	6.7	Spurious Emission	
	6.7.1		
	6.7.2		
7	TES	T SETUP PHOTO	24
R	FUT	CONSTRUCTIONAL DETAILS	25





4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass*
6dB Emission Bandwidth	15.247 (a)(2)	Pass*
Power Spectral Density	15.247 (e)	Pass*
Band Edge	15.247(d)	Pass*
Spurious Emission	15.205/15.209	Pass

Pass: The EUT complies with the essential requirements in the standard.

Pass*: The test data refer to FCC ID: 2AG5L-FTU161G(CCISE160302802 test report).



5 General Information

5.1 Client Information

Applicant:	Plus One Marketing Ltd.
Address of Applicant:	Sumitomofudosan Hibiya building 2F, 2-8-6 Shinbashi, Minatoku, Tokyo, Japan
Manufacturer:	Nollec Wireless Co.,Ltd.
Address of Manufacturer:	Tower A North, TCL Building, High-tech Industrial Park, Nanshan Dist, Shenzhen, China

5.2 General Description of E.U.T.

Product Name:	Smart Phone
Model No.:	ÖWN FUN PLUS, FTU17B00
Operation Frequency:	2402-2480 MHz
Channel numbers:	40
Channel separation:	2 MHz
Modulation technology:	GFSK
Data speed :	1Mbps
Antenna Type:	Internal Antenna
Antenna gain:	1.1 dBi
Power supply:	Rechargeable Li-ion Battery DC3.7V-2800mAh
AC adapter:	Model: ÖWN Fun+
	Input:100-300V AC,50/60Hz 0.2A
	Output:5V DC MAX 1A
Remark:	The No.: ÖWN FUN PLUS, FTU17B00 were identical inside, the electrical circuit design, layout, components used and internal wiring, with only difference being model name.





Operation	Operation Frequency each of channel						
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2442MHz
The Highest channel	2480MHz



5.3 Test environment and mode

Operating Environment:			
Temperature:	24.0 °C		
Humidity:	54 % RH		
Atmospheric Pressure:	1010 mbar		
Test mode:			
Operation mode	Keep the EUT in continuous transmitting with modulation		

Report No: CCISE170600102

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. Duty cycle setting during the transmission is 100% with maximum power setting for all modulations.

5.4 Description of Support Units

N/A

5.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Registration No.: 817957

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012.

• IC - Registration No.: 10106A-1

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

• CNAS - Registration No.: CNAS L6048

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

5.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,

Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755-23118282 Fax: +86-755-23116366

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road, Bao'an District, Shenzhen, Guangdong, China
Telephone: +86 (0) 755 23118282 Fax: +86 (0) 755 23116366



5.7 Test Instruments list

Rad	Radiated Emission:					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m SAC	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	08-23-2014	08-22-2017
2	BiConiLog Antenna	SCHWARZBECK	VULB9163	CCIS0005	02-25-2017	02-24-2018
3	Horn Antenna	SCHWARZBECK	BBHA9120D	CCIS0006	02-25-2017	02-24-2018
4	Pre-amplifier (10kHz-1.3GHz)	HP	8447D	CCIS0003	02-25-2017	02-24-2018
5	Pre-amplifier (1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	02-25-2017	02-24-2018
6	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	02-25-2017	02-24-2018
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	02-25-2017	02-24-2018
8	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP30	CCIS0023	02-25-2017	02-24-2018
9	EMI Test Receiver	Rohde & Schwarz	ESRP7	CCIS0167	02-25-2017	02-24-2018
10	Loop antenna	Laplace instrument	RF300	EMC0701	02-25-2017	02-24-2018

Con	Conducted Emission:					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	08-23-2014	08-22-2017
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	02-25-2017	02-24-2018
3	LISN	CHASE	MN2050D	CCIS0074	02-25-2017	02-24-2018
4	Coaxial Cable	CCIS	N/A	CCIS0086	02-25-2017	02-24-2018
5	EMI Test Software	AUDIX	E3	N/A	N/A	N/A



6 Test results and Measurement Data

6.1 Antenna requirement:

Standard requirement: F

FCC Part 15 C Section 15.203 /247(c)

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

E.U.T Antenna:

The BLE antenna is an internal antenna which cannot replace by end-user, the best case gain of the antenna is 1.1 dBi.








6.2 Conducted Emission

<u> </u>	Solidadica Elilissio	· ·		
	Test Requirement:	FCC Part 15 C Section 15.207		
	Test Method:	ANSI C63.4: 2009		
	Test Frequency Range:	150 kHz to 30 MHz		
	Class / Severity:	Class B		
	Receiver setup:	RBW=9kHz, VBW=30kHz		
	Limit:	Frequency range (MLI=) Limit (dBuV)		
		Frequency range (MHz) Quasi-peak Average		
		0.15-0.5 66 to 56* 56 to 46*		
		0.5-5 56 46		
		5-30 60 50		
		* Decreases with the logarithm of the frequency.		
	Test procedure	 The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.), which provides a 50ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2009 on conducted measurement. 		
	Test setup:	Reference Plane LISN 40cm 80cm Filter AC power Equipment Test table/Insulation plane Remark E.U.T. Equipment Under Test LISN: Line Impedence Stabilization Network Test table height=0.8m		
	Test Uncertainty:	±3.28 dB		
	Test Instruments:	Refer to section 5.7 for details		
	Test mode:	Refer to section 5.3 for details		
	Test results:	Passed		

Measurement Data



Neutral:



Site


Condition

: CCIS Shielding Room : FCC PART15 B QP LISN NEUTRAL : Smart Phone : OWN FUN PLUS EUT Model Test Mode : BLE mode
Power Rating : AC 120V/60Hz
Environment : Temp: 23 °C Huni:56% Atmos:101KPa
Test Engineer: Peter

Remark	500							
		Read	LISN	Cable		Limit	Over	
	Freq	Level	Factor	Loss	Level	Line	Limit	Remark
	MHz	dBu∜	dB	₫B	dBu∀	dBu∀	<u>dB</u>	
1	0.166	38.03	0.13	0.00	38.16	65.16	-27.00	QP
2	0.170	23.64	0.13	0.00	23.77	54.94	-31.17	Average
3	0.211	34.26	0.16	0.00	34.42	63.18	-28.76	QP
1 2 3 4 5 6 7 8 9	0.211	21.59	0.16	0.00	21.75	53.18	-31.43	Average
5	0.459	23.71	0.24	0.00	23.95	46.71	-22.76	Average
6	0.494	34.08	0.24	0.00	34.32	56.10	-21.78	QP
7	0.497	22.91	0.24	0.00	23.15	46.05	-22.90	Average
8	0.579	30.88	0.28	0.00	31.16	56.00	-24.84	QP
9	0.582	19.55	0.28	0.00	19.83	46.00	-26.17	Average
10	0.876	14.42	0.29	0.00	14.71	46.00	-31.29	Average
11	1.032	30.03	0.26	0.00	30.29	56.00	-25.71	QP
12	1.772	27.34	0.26	0.00	27.60	56.00	-28.40	QP



Line:



Trace: 5

: CCIS Shielding Room : FCC PART15 B QP LISN LINE Site Condition

EUT : Smart Phone : OWN FUN PLUS Model Test Mode : BLE mode

Power Rating: AC 120V/60Hz Environment: Temp: 23 °C Huni:56% Atmos:101KPa Test Engineer: Peter

Remark

CMAIR	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBu₹	dB	dB	dBu₹	dBu∀	<u>dB</u>	
1	0.166	37.94	0.14	0.00	38.08	65.16	-27.08	QP
1 2 3	0.211	34.56	0.15	0.00	34.71	63.18	-28.47	QP
	0.211	20.86	0.15	0.00	21.01	53.18	-32.17	Average
4 5 6 7 8 9	0.461	33.74	0.24	0.00	33.98	56.67	-22.69	QP
5	0.471	20.96	0.24	0.00	21.20	46.49	-25.29	Average
6	0.675	14.57	0.31	0.00	14.88	46.00	-31.12	Average
7	0.928	29.06	0.27	0.00	29.33	56.00	-26.67	QP
8	0.928	13.77	0.27	0.00	14.04	46.00	-31.96	Average
9	1.495	11.57	0.29	0.00	11.86	46.00	-34.14	Average
10	2.581	23.92	0.33	0.00	24.25	56.00	-31.75	QP
11	3.454	10.53	0.34	0.00	10.87	46.00	-35.13	Average
12	7.100	23.72	0.36	0.00	24.08	60.00	-35.92	QP

Notes:

- 1. An initial pre-scan was performed on the live and neutral lines with peak detector.
- 2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3. Final Level =Receiver Read level + LISN Factor + Cable Loss



6.3 Conducted Output Power

Test Requirement:	FCC Part 15 C Section 15.247 (b)(3)
•	
Test Method:	ANSI C63.10:2009 and KDB558074v03r03 section 9.2.2
Limit:	30dBm
Test setup:	
	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Refer to FCC ID: 2AG5L-FTU161G(CCISE160302802 test report)



6.4 Occupy Bandwidth

1 7								
Test Requirement:	FCC Part 15 C Section 15.247 (a)(2)							
Test Method:	NSI C63.10:2009 and KDB558074v03r03 section 8.1							
Limit:	>500kHz							
Test setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane							
Test Instruments:	Refer to section 5.7 for details							
Test mode:	Refer to section 5.3 for details							
Test results:	Refer to FCC ID: 2AG5L-FTU161G(CCISE160302802 test report)							



6.5 Power Spectral Density

Took Dogwingmont	FOC Dort 45 C Continu 45 047 (a)							
Test Requirement:	FCC Part 15 C Section 15.247 (e)							
Test Method:	ANSI C63.10:2009 and KDB558074v03r03 section 10.2							
Limit:	8 dBm							
Test setup:	Spectrum Analyzer E.U.T Non-Conducted Table							
	Ground Reference Plane							
Test Instruments:	Refer to section 5.7 for details							
Test mode:	Refer to section 5.3 for details							
Test results:	Refer to FCC ID: 2AG5L-FTU161G(CCISE160302802 test report)							



6.6 Band Edge

6.6.1 Conducted Emission Method

Tost Poquiroment:	FCC Part 15 C Section 15.247 (d)					
Test Requirement:	` '					
Test Method:	ANSI C63.10:2009 and KDB558074v03r03 section 13					
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Test setup:						
	Spectrum Analyzer					
	Non-Conducted Table					
	Ground Reference Plane					
Test Instruments:	Refer to section 5.7 for details					
Test mode:	Refer to section 5.3 for details					
Test results:	Refer to FCC ID: 2AG5L-FTU161G(CCISE160302802 test report)					



6.6.2 Radiated Emission Method

Tes	st Requirement:	FCC Part 15 C Section 15.209 and 15.205								
Tes	st Method:	ANSI C63.10: 2013 and KDB 558074v03r03 section 12.1								
Tes	t Frequency Range:	2.3GHz to 2.5GHz								
Tes	st site:	Measurement D	Measurement Distance: 3m							
Red	ceiver setup:	Frequency	Detector	RBW	VBW	Remark				
		Above 1GHz	Peak RMS	1MHz 1MHz	3MHz 3MHz	Peak Value Average Value				
Lim	iit·	Freque	1	Limit (dBuV/		Remark				
		Above 1	_	54.0	0	Average Value				
				74.0		Peak Value				
	et Procedure:	 The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasipeak or average method as specified and then reported in a data 								
Tes	et setup:	AE EUT Horn Antenna Tower Ground Reference Plane Test Receiver Controller								
Tes	st Instruments:	Refer to section	5.7 for detail	s						
Tes	st mode:	Refer to section	5.3 for detail	s						
т	st results:	Refer to FCC II	D: 2AG5L-FT	J161G(CCISE	160302802	2 test report)				



6.7 Spurious Emission

6.7.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)						
Test Method:	ANSI C63.10:2009 and KDB558074 section 11						
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.						
Test setup:							
	Spectrum Analyzer						
	Non-Conducted Table						
	Ground Reference Plane						
Test Instruments:	Refer to section 5.7 for details						
Test mode:	Refer to section 5.3 for details						
Test results:	Refer to FCC ID: 2AG5L-FTU161G(CCISE160302802 test report)						






6.7.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205							
Test Method:	ANSI C63.10:2009							
Test Frequency Range:	9KHz to 25GHz							
Test site:	Measurement D	istance: 3m						
Receiver setup:	Frequency Detector RBW VBW Remark							
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value			
	Above 1GHz	Peak	1MHz	3MHz	Peak Value			
	Above IGHZ	RMS	1MHz	3MHz	Average Value			
Limit:	Frequency		Limit (dBuV/m	@3m)	Remark			
	30MHz-88MHz		40.0		Quasi-peak Value			
	88MHz-216MHz	-	43.5		Quasi-peak Value			
	216MHz-960MH	z	46.0		Quasi-peak Value			
	960MHz-1GHz		54.0		Quasi-peak Value			
	Above 1GHz	-			•			
Test Procedure:	Above 1GHz 54.0 Average Value 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasipeak or average method as specified and then reported in a data							










Below 1GHz

Horizontal:



: 3m chamber Site

: FCC PART15 CLASS B 3m VULB9163(30M3G) HORIZONTAL Condition

: Smart Phone : OWN FUN PLUS EUT Model Test mode : BLE mode Power Rating : AC 120V/60Hz

Environment : Temp: 25.5°C Huni: 55% 101KPa


Test Engineer: Peter REMARK

	•								
	Freq		Antenna Factor					Over Limit	Remark
_	MHz	dBu∜	<u>dB</u> /m	<u>d</u> B	<u>ab</u>	dBuV/m	dBuV/m	<u>dB</u>	
1	34.760	36.69	14.62	1.04	29.95	22.40	40.00	-17.60	QP
2	104.536	34.97	10.62	1.99	29.50	18.08	43.50	-25.42	QP
3	143.830	39.56	11.34	2.44	29.25	24.09	43.50	-19.41	QP
4	152.130	41.12	10.47	2.53	29.20	24.92	43.50	-18.58	QP
5	176.888	42.29	9.40	2.71	29.00	25.40	43.50	-18.10	QP
6	286.982	39.02	12.26	2.90	28.47	25.71	46.00	-20.29	QP





Vertical:



: 3m chamber : FCC PART15 CLASS B 3m VULB9163(30M3G) VERTICAL

Condition EUT : Smart Phone
Model : OWN FUN PLUS
Test mode : BLE mode
Power Rating : AC 120V/60Hz
Environment : Temp:25.5°C Huni:55% 101KPa
Test Engineer: Peter
REMARK : Smart Phone

REMARK

	2 · · · · · · · · · · · · · · · · · · ·								
	Freq		Antenna Factor				Limit Line	Over Limit	
i. 	MHz	dBu₹	<u>dB</u> /m	d <u>B</u>	<u>dB</u>	dBu√/m	dBuV/m	<u>d</u> B	
1	45.855	34.09	17.24	1.29	29.85	22.77	40.00	-17.23	QP
2	50.232	36.68	14.97	1.25	29.82	23.08	40.00	-16.92	QP
2	71.330	44.98	6.67	1.54	29.71	23.48	40.00	-16.52	QP
4	131.297	37.55	12.19	2.30	29.32	22.72	43.50	-20.78	QP
5	138.874	37.14	11.77	2.38	29.28	22.01	43.50	-21.49	QP
6	174.424	36.07	9.55	2.69	29.02	19.29	43.50	-24.21	QP



Above 1GHz

Test channel:			Lowest		Le	vel:	Peak	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	48.29	35.99	6.80	41.81	49.27	74.00	-24.73	Vertical
4804.00	47.25	35.99	6.80	41.81	48.23	74.00	-25.77	Horizontal
Т	est channel	•	Lowest		Level:		Average	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	35.36	35.99	6.80	41.81	36.34	54.00	-17.66	Vertical
4804.00	34.29	35.99	6.80	41.81	35.27	54.00	-18.73	Horizontal

Test channel:			Middle		Level:		Peak	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4884.00	51.26	36.38	6.86	41.84	52.66	74.00	-21.34	Vertical
4884.00	50.18	36.38	6.86	41.84	51.58	74.00	-22.42	Horizontal
Test channel:			Middle		Level:		Average	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4884.00	42.36	36.38	6.86	41.84	43.76	54.00	-10.24	Vertical
4884.00	41.25	36.38	6.86	41.84	42.65	54.00	-11.35	Horizontal

Test channel:			Highest		Level:		Peak	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	52.36	36.71	6.91	41.87	54.11	74.00	-19.89	Vertical
4960.00	51.69	36.71	6.91	41.87	53.44	74.00	-20.56	Horizontal
Test channel:			Highest		Level:		Average	
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	40.36	36.71	6.91	41.87	42.11	54.00	-11.89	Vertical
4960.00	41.20	36.71	6.91	41.87	42.95	54.00	-11.05	Horizontal

Remark:

- 1. Final Level =Receiver Read level + Antenna Factor + Cable Loss Preamplifier Factor
- 2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road, Bao'an District, Shenzhen, Guangdong, China
Telephone: +86 (0) 755 23118282 Fax: +86 (0) 755 23116366