

FCC TEST REPORT

For

Shenzhen Ananda Technology Co., Ltd.

Tablet PC (MID)

Model No.: T1

Prepared for : Shenzhen Ananda Technology Co., Ltd.
Address : No:589-1, JinBi Road, BiLing, Pinshan, Longgang district,
Shenzhen, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,
Bao'an District, Shenzhen, Guangdong, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : December 23, 2015
Number of tested samples : 1
Serial number : Prototype
Date of Test : December 23, 2015 – December 31, 2015
Date of Report : December 31, 2015

FCC TEST REPORT
FCC CFR 47 PART 15 C(15.247): 2015

Report Reference No. : LCS1512232324E

Date of Issue : December 31, 2015

Testing Laboratory Name : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China

Testing Location/ Procedure : Full application of Harmonised standards Partial application of Harmonised standards Other standard testing method

Applicant's Name : Shenzhen Ananda Technology Co., Ltd.

Address : No:589-1, JinBi Road, BiLing, Pinshan, Longgang district, Shenzhen, China

Test Specification

Standard : FCC CFR 47 PART 15 C(15.247): 2015

Test Report Form No. : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description : Tablet PC (MID)

Trade Mark : N/A

Model/ Type reference : T1

Ratings : DC 3.7V by battery

Result : **Positive**

Compiled by:




Jacky Li/ File administrators

Supervised by:



Glin Lu/ Technique principal

Approved by:



Gavin Liang/ Manager

FCC -- TEST REPORT

Test Report No. : LCS1512232324E	<u>December 31, 2015</u> Date of issue
---	---

Type / Model..... : T1

EUT..... : Tablet PC (MID)

Applicant..... : Shenzhen Ananda Technology Co., Ltd.

Address..... : No:589-1, JinBi Road, BiLing, Pinshan, Longgang district, Shenzhen,
: China

Telephone..... : 0755-25803012

Fax..... : 0755-33920541

Manufacturer..... : Shenzhen Ananda Technology Co., Ltd.

Address..... : No:589-1, JinBi Road, BiLing, Pinshan, Longgang district, Shenzhen,
China

Telephone..... : 0755-25803012

Fax..... : 0755-33920541

Factory..... : Shenzhen Ananda Technology Co., Ltd.

Address..... : No:589-1, JinBi Road, BiLing, Pinshan, Longgang district, Shenzhen,
China

Telephone..... : 0755-25803012

Fax..... : 0755-33920541

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	5
1.1. DESCRIPTION OF DEVICE (EUT)	5
1.2. HOST SYSTEM CONFIGURATION LIST AND DETAILS	5
1.3. EXTERNAL I/O CABLE.....	5
1.4. DESCRIPTION OF TEST FACILITY	6
1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY	6
1.6. MEASUREMENT UNCERTAINTY	6
1.7. DESCRIPTION OF TEST MODES.....	7
2. TEST METHODOLOGY	8
2.1. EUT CONFIGURATION.....	8
2.2. EUT EXERCISE.....	8
2.3. GENERAL TEST PROCEDURES.....	8
3. SYSTEM TEST CONFIGURATION.....	9
3.1. JUSTIFICATION	9
3.2. EUT EXERCISE SOFTWARE	9
3.3. SPECIAL ACCESSORIES	9
3.4. BLOCK DIAGRAM/SCHEMATICS	9
3.5. EQUIPMENT MODIFICATIONS	9
3.6. TEST SETUP.....	9
4. SUMMARY OF TEST RESULTS	10
5. TEST RESULT.....	11
5.1. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT.....	11
5.2. POWER SPECTRAL DENSITY MEASUREMENT	13
5.3. 6 dB SPECTRUM BANDWIDTH MEASUREMENT	18
5.4. OCCUPIED BANDWIDTH	23
5.5. RADIATED EMISSIONS MEASUREMENT	25
5.6. CONDUCTED SPURIOUS EMISSIONS AND BAND EDGES TEST.....	39
5.7. POWER LINE CONDUCTED EMISSIONS	48
5.8. ANTENNA REQUIREMENTS	51
6. LIST OF MEASURING EQUIPMENTS	52

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : Tablet PC (MID)

Model Number : T1

Power Supply : DC 3.7V by battery

Frequency Range : 2412.00-2462.00MHz for 802.11b/g/n

Channel Spacing : 5MHz for 802.11b/g/n

Channel Number : 11 Channels for 20MHz Bandwidth

Modulation Technology : IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK)
IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK)
IEEE 802.11n: OFDM (64QAM, 16QAM,QPSK,BPSK)

Data Rates : IEEE 802.11b: 1-11Mbps
IEEE 802.11g: 6-54Mbps
IEEE 802.11n: MCS0-MCS7

Antenna Type And Gain : PIFA antenna, 2.4 dBi

1.2. Host System Configuration List and Details

Manufacturer	Description	Model	Serial Number	Certificate
--	AC/DC Adapter	HS-050200	--	VOC

1.3. External I/O Cable

I/O Port Description	Quantity	Cable
DC	1	N/A
USB	1	N/A
TF Card	1	N/A
Earphone	1	N/A

1.4. Description of Test Facility

Site Description

EMC Lab.

: CNAS Registration Number. is L4595.

FCC Registration Number. is 899208.

Industry Canada Registration Number. is 9642A-1.

VCCI Registration Number. is C-4260 and R-3804.

ESMD Registration Number. is ARCB0108.

UL Registration Number. is 100571-492.

TUV SUD Registration Number. is SCN1081.

TUV RH Registration Number. is UA 50296516-001

1.5. Statement of The Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Radiation Uncertainty	9KHz~30MHz	± 3.10dB	(1)
	30MHz~200MHz	± 2.96dB	(1)
	200MHz~1000MHz	± 3.10dB	(1)
	1GHz~26.5GHz	± 3.80dB	(1)
	26.5GHz~40GHz	± 3.90dB	(1)
Conduction Uncertainty	150kHz~30MHz	± 1.63dB	(1)
Power disturbance	30MHz~300MHz	± 1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7. Description Of Test Modes

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.

Worst-case mode and channel used for 150kHz-30 MHz power line conducted emissions was the mode and channel with the highest output power, that was determined to be 802.11b mode(High Channel).

Worst-case mode and channel used for 9kHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be 802.11b mode(High Channel).

Worst-Case data rates were utilized from preliminary testing of the Chipset, worst-case data rates used during the testing are as follows:

802.11b Mode : 1 Mbps, DSSS.

802.11g Mode : 6 Mbps, OFDM.

802.11n Mode HT20: MCS0, OFDM.

Note: The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

Channel List & Frequency

802.11b/g/n(HT20)

Frequency Band	Channel No.	Frequency(MHz)	Channel No.	Frequency(MHz)
2412~2462MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	--	--

2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10: 2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd..

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to FCC's request, Test Procedure KDB558074 D01 DTS Meas. Guidance v03r03 is required to be used for this kind of FCC 15.247 digital modulation device.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

2.3. General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013

3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmit condition.

3.2. EUT Exercise Software

N/A

3.3. Special Accessories

N/A

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST RESULTS

Applied Standard: FCC Part 15 Subpart C		
FCC Rules	Description of Test	Result
§15.247(b)	Maximum Conducted Output Power	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	6dB Bandwidth	Compliant
§15.247(a)	Occupied Bandwidth	Compliant
§15.209, §15.247(d)	Radiated and Conducted Spurious Emissions	Compliant
§15.205	Emissions at Restricted Band	Compliant
§15.207(a)	Conducted Emissions	Compliant
§15.203	Antenna Requirements	Compliant

5. TEST RESULT

5.1. Maximum Conducted Output Power Measurement

5.1.1. Standard Applicable

According to §15.247(b): For systems using digital modulation in the 2400-2483.5 MHz and 5725-5850 MHz band, the limit for maximum peak conducted output power is 30dBm. The limit has to be reduced by the amount in dB that the gain of the antenna exceeds 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter peak output power.


5.1.2. Measuring Instruments and Setting

Please refer to section 6 of equipments list in this report. The following table is the setting of the power meter.

5.1.3. Test Procedures

The transmitter output (antenna port) was connected to the power meter.

5.1.4. Test Setup Layout



5.1.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.1.6. Test Result of Maximum Conducted Output Power

Temperature	25°C	Humidity	60%
Test Engineer	Jacky	Configurations	802.11b/g/n

802.11b

Channel	Frequency (MHz)	Conducted Peak Power (dBm)	Max. Limit (dBm)	Result
1	2412	7.39	30	Complies
6	2437	7.48	30	Complies
11	2462	7.10	30	Complies

802.11g

Channel	Frequency (MHz)	Conducted Peak Power (dBm)	Max. Limit (dBm)	Result
1	2412	7.44	30	Complies
6	2437	7.23	30	Complies
11	2462	6.76	30	Complies

802.11n HT20

Channel	Frequency (MHz)	Conducted Peak Power (dBm)	Max. Limit (dBm)	Result
1	2412	7.04	30	Complies
6	2437	7.05	30	Complies
11	2462	7.24	30	Complies

5.2. Power Spectral Density Measurement

5.2.1. Standard Applicable

According to §15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


5.2.2. Measuring Instruments and Setting

Please refer to section 6 of equipments list in this report. The following table is the setting of Spectrum Analyzer.

5.2.3. Test Procedures

1. The transmitter was connected directly to a Spectrum Analyzer through a directional couple.
2. The power was monitored at the coupler port with a Spectrum Analyzer. The power level was set to the maximum level.
3. Set the RBW = 3 kHz.
4. Set the VBW $\geq 3 \times \text{RBW}$
5. Set the span to 1.5 times the DTS channel bandwidth.
6. Detector = peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. Use the peak marker function to determine the maximum power level in any 3 kHz band segment within the fundamental EBW.

5.2.4. Test Setup Layout



5.2.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.2.6. Test Result of Power Spectral Density

Temperature	25°C	Humidity	60%
Test Engineer	Jakcy	Configurations	802.11b/g/n

802.11b

Channel	Frequency (MHz)	Power Density (dBm/3KHz)	Max. Limit (dBm/3KHz)	Result
1	2412	-18.772	8	Complies
6	2437	-18.500	8	Complies
11	2462	-18.020	8	Complies

802.11g

Channel	Frequency (MHz)	Power Density (dBm/3KHz)	Max. Limit (dBm/3KHz)	Result
1	2412	-23.766	8	Complies
6	2437	-25.601	8	Complies
11	2462	-23.652	8	Complies




802.11n HT20

Channel	Frequency (MHz)	Power Density (dBm/3KHz)	Max. Limit (dBm/3KHz)	Result
1	2412	-23.241	8	Complies
6	2437	-24.144	8	Complies
11	2462	-24.457	8	Complies



802.11b power density



802.11g power density



802.11n HT20 power density



5.3. 6 dB Spectrum Bandwidth Measurement

5.3.1. Standard Applicable

According to §15.247(a)(2): For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

5.3.2. Measuring Instruments and Setting


Please refer to section 6 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> RBW
Detector	Peak
Trace	Max Hold
Sweep Time	100ms

5.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth and the video bandwidth were set according to KDB558074.
3. Measured the spectrum width with power higher than 6dB below carrier.

5.3.4. Test Setup Layout



5.3.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.3.6. Test Result of 6dB Spectrum Bandwidth

Temperature	25°C	Humidity	60%
Test Engineer	Jacky	Configurations	802.11b/g/n

802.11b

Channel	Frequency	6dB Bandwidth (MHz)	Min. Limit (MHz)	Result
1	2412	9.084	0.5	Complies
6	2437	9.081	0.5	Complies
11	2462	9.078	0.5	Complies


802.11g

Channel	Frequency	6dB Bandwidth (MHz)	Min. Limit (MHz)	Result
1	2412	16.540	0.5	Complies
6	2437	16.530	0.5	Complies
11	2462	16.560	0.5	Complies




802.11n HT20

Channel	Frequency	6dB Bandwidth (MHz)	Min. Limit (MHz)	Result
1	2412	17.640	0.5	Complies
6	2437	17.620	0.5	Complies
11	2462	17.640	0.5	Complies


802.11b channel, 6dB bandwidth



802.11g channel, 6dB bandwidth



802.11n HT20 channel, 6dB bandwidth



5.4. Occupied Bandwidth

5.4.1. Standard Applicable

According to §15.247(a): Operation under the provisions of this section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

For systems using digital modulation techniques, the EUT may operate in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

5.4.2. Measuring Instruments and Setting

Please refer to section 6 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.


Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> RBW
RBW	1% to 3% of the band
VBW	3 times the RBW
Detector	Peak
Trace	Max Hold
Sweep Time	100ms

5

5.4.3. Test Procedures

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal bandwidth measurement function is utilized.

5.4.4. Test Setup Layout



5.4.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.4.6. Test Result of 99% Occupied Bandwidth.

Temperature	25°C	Humidity	60%
Test Engineer	Jacky	Configurations	802.11b/g/n

802.11b

Channel	Frequency (MHz)	99% OBW (MHz)
1	2412	12.305
6	2437	12.293
11	2462	12.292

802.11g

Channel	Frequency (MHz)	99% OBW (MHz)
1	2412	16.488
6	2437	16.486
11	2462	16.495

802.11n HT20

Channel	Frequency (MHz)	99% OBW (MHz)
1	2412	17.802
6	2437	17.777
11	2462	17.794

Test plots: Please refer to clause 5.3.6

5.5. Radiated Emissions Measurement

5.5.1. Standard Applicable

According to §15.247 (d): 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies(MHz)	Field Strength(microvolts/meter)	Measurement Distance(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

5.5.2. Measuring Instruments and Setting

Please refer to section 6 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

5.5.3. Test Procedures

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0 ° to 315 ° using 45 ° steps.
- The antenna height is 1.5 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0 ° to 360 °) and by rotating the elevation axes (0 ° to 360 °).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0 ° to 315 ° using 45 ° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45 °) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0 ° to 315 ° using 45 ° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

4) Sequence of testing above 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.

Premeasurement:




- The antenna is moved spherical over the EUT in different polarisations of the antenna.

Final measurement:

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

5.5.4. Test Setup Layout

For radiated emissions below 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

5.5.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.5.6. Results of Radiated Emissions (9kHz~30MHz)

Temperature	25°C	Humidity	60%
Test Engineer	Jacky	Configurations	802.11b/g/n

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = 40 log (specific distance / test distance) (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

5.5.7. Results of Radiated Emissions (30MHz~1GHz)


Temperature	25°C	Humidity	60%
Test Engineer	Jacky	Configurations	802.11b (High CH)

Test result for 802.11b (High Channel)



Freq	Reading	CableLoss	Antfac	Measured	Limit	Over	Remark
MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1 178.41	20.12	0.89	9.57	30.58	43.50	-12.92	QP
2 395.69	24.14	1.30	14.96	40.40	46.00	-5.60	QP
3 534.40	21.77	1.46	17.22	40.45	46.00	-5.55	QP
4 653.71	19.98	1.69	18.64	40.31	46.00	-5.69	QP
5 773.02	17.89	1.63	19.72	39.24	46.00	-6.76	QP
6 891.36	18.75	1.86	21.00	41.61	46.00	-4.39	QP

Note: 1. All readings are Quasi-peak values.
 2. Measured = Reading + Antenna Factor + Cable Loss
 3. The emission that ate 20db blow the official limit are not reported



Env. / Ins: 24 °C / 56%
pol: HORIZONTAL

Freq MHz	Reading dBuV	CabLoss dB	Antfac dB/m	Measured dBuV/m	Limit dBuV/m	Over dB	Remark
1 178.41	24.51	0.89	9.57	34.97	43.50	-8.53	QP
2 296.75	25.02	1.12	13.00	39.14	46.00	-6.86	QP
3 395.69	25.70	1.30	14.96	41.96	46.00	-4.04	QP
4 534.40	21.28	1.46	17.22	39.96	46.00	-6.04	QP
5 653.71	20.38	1.69	18.64	40.71	46.00	-5.29	QP
6 891.36	17.12	1.86	21.00	39.98	46.00	-6.02	QP

Note: 1. All readings are Quasi-peak values.
2. Measured= Reading + Antenna Factor + Cable Loss
3. The emission that ate 20db blow the offfficial limit are not reported

Note:

Pre-scan all mode and recorded the worst case results in this report (802.11b (High Channel)).

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

5.5.8. Results for Radiated Emissions (Above 1GHz)

802.11b

Channel 1

Freq. MHz	Reading dBuv	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4824.00	56.80	33.06	35.04	3.94	58.76	74	-15.24	Peak	Horizontal
4824.00	42.57	33.06	35.04	3.94	44.53	54	-9.47	Average	Horizontal
4824.00	55.79	33.06	35.04	3.94	57.75	74	-16.25	Peak	Vertical
4824.00	40.66	33.06	35.04	3.94	42.62	54	-11.38	Average	Vertical

Channel 6

Freq. MHz	Reading dBuv	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4874.00	56.25	33.16	35.15	3.96	58.22	74	-15.78	Peak	Horizontal
4874.00	42.11	33.16	35.15	3.96	44.08	54	-9.92	Average	Horizontal
4874.00	55.94	33.16	35.15	3.96	57.91	74	-16.09	Peak	Vertical
4874.00	41.28	33.16	35.15	3.96	43.25	54	-10.75	Average	Vertical

Channel 11

Freq. MHz	Reading dBuv	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4924.00	55.97	33.26	35.14	3.98	58.07	74	-15.93	Peak	Horizontal
4924.00	41.74	33.26	35.14	3.98	43.84	54	-10.16	Average	Horizontal
4924.00	55.26	33.26	35.14	3.98	57.36	74	-16.64	Peak	Vertical
4924.00	40.24	33.26	35.14	3.98	42.34	54	-11.66	Average	Vertical

802.11g

Channel 1

Freq. MHz	Reading dBuv	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4824.00	55.82	33.06	35.04	3.94	57.78	74	-16.22	Peak	Horizontal
4824.00	41.70	33.06	35.04	3.94	43.66	54	-10.34	Average	Horizontal
4824.00	54.21	33.06	35.04	3.94	56.17	74	-17.83	Peak	Vertical
4824.00	40.06	33.06	35.04	3.94	42.02	54	-11.98	Average	Vertical

Channel 6

Freq. MHz	Reading dBuv	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4874.00	55.34	33.16	35.15	3.96	57.31	74	-16.69	Peak	Horizontal
4874.00	41.55	33.16	35.15	3.96	43.52	54	-10.48	Average	Horizontal
4874.00	54.50	33.16	35.15	3.96	56.47	74	-17.53	Peak	Vertical
4874.00	40.26	33.16	35.15	3.96	42.23	54	-11.77	Average	Vertical

Channel 11

Freq. MHz	Reading dBuv	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4924.00	55.32	33.26	35.14	3.98	57.42	74	-16.58	Peak	Horizontal
4924.00	41.20	33.26	35.14	3.98	43.30	54	-10.70	Average	Horizontal
4924.00	54.01	33.26	35.14	3.98	56.11	74	-17.89	Peak	Vertical
4924.00	40.35	33.26	35.14	3.98	42.45	54	-11.55	Average	Vertical

802.11n HT20

Channel 1

Freq. MHz	Reading dBuv	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4824.00	55.31	33.06	35.04	3.94	57.27	74	-16.73	Peak	Horizontal
4824.00	41.05	33.06	35.04	3.94	43.01	54	-10.99	Average	Horizontal
4824.00	54.41	33.06	35.04	3.94	56.37	74	-17.63	Peak	Vertical
4824.00	40.50	33.06	35.04	3.94	42.46	54	-11.54	Average	Vertical

Channel 6

Freq. MHz	Reading dBuv	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4874.00	55.15	33.16	35.15	3.96	57.12	74	-16.88	Peak	Horizontal
4874.00	41.48	33.16	35.15	3.96	43.45	54	-10.55	Average	Horizontal
4874.00	54.92	33.16	35.15	3.96	56.89	74	-17.11	Peak	Vertical
4874.00	39.96	33.16	35.15	3.96	41.93	54	-12.07	Average	Vertical

Channel 11

Freq. MHz	Reading dBuv	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuv/m	Limit dBuv/m	Margin dB	Remark	Pol.
4924.00	55.33	33.26	35.14	3.98	57.43	74	-16.57	Peak	Horizontal
4924.00	41.16	33.26	35.14	3.98	43.26	54	-10.74	Average	Horizontal
4924.00	53.97	33.26	35.14	3.98	56.07	74	-17.93	Peak	Vertical
4924.00	40.01	33.26	35.14	3.98	42.11	54	-11.89	Average	Vertical

Notes:

1. Measuring frequencies from 9k~10th harmonic or 26.5GHz (which is less), were made with an instrument using Peak detector mode. No emission found between lowest internal used/generated frequency to 30MHz.
2. Data of measurement within this frequency range shown “---” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

5.5.9. Results of Band Edges Test (Radiated)

802.11b

Tx-2412

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
2390.00	49.00	32.89	35.16	3.51	50.24	74	-23.76	Peak	Horizontal
2390.00	34.82	32.89	35.16	3.51	36.06	54	-17.94	Average	Horizontal
2400.00	53.72	32.92	35.16	3.54	55.02	74	-18.98	Peak	Horizontal
2400.00	41.11	32.92	35.16	3.54	42.41	54	-11.59	Average	Horizontal
2390.00	48.79	32.89	35.16	3.51	50.03	74	-23.97	Peak	Vertical
2390.00	34.54	32.89	35.16	3.51	35.78	54	-18.22	Average	Vertical
2400.00	54.06	32.92	35.16	3.54	55.36	74	-18.64	Peak	Vertical
2400.00	41.84	32.92	35.16	3.54	43.14	54	-10.86	Average	Vertical

Tx-2462

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
2483.50	50.83	33.06	35.18	3.60	52.31	74	-21.69	Peak	Horizontal
2483.50	36.68	33.06	35.18	3.60	38.16	54	-15.84	Average	Horizontal
2483.50	50.68	33.06	35.18	3.60	52.16	74	-21.84	Peak	Vertical
2483.50	36.30	33.06	35.18	3.60	37.78	54	-16.22	Average	Vertical

802.11g

Tx-2412

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
2390.00	48.90	32.89	35.16	3.51	50.14	74	-23.86	Peak	Horizontal
2390.00	35.42	32.89	35.16	3.51	36.66	54	-17.34	Average	Horizontal
2400.00	54.48	32.92	35.16	3.54	55.78	74	-18.22	Peak	Horizontal
2400.00	40.73	32.92	35.16	3.54	42.03	54	-11.97	Average	Horizontal
2390.00	49.21	32.89	35.16	3.51	50.45	74	-23.55	Peak	Vertical
2390.00	34.01	32.89	35.16	3.51	35.25	54	-18.75	Average	Vertical
2400.00	54.42	32.92	35.16	3.54	55.72	74	-18.28	Peak	Vertical
2400.00	41.34	32.92	35.16	3.54	42.64	54	-11.36	Average	Vertical

Tx-2462

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
2483.50	50.58	33.06	35.18	3.60	52.06	74	-21.94	Peak	Horizontal
2483.50	36.63	33.06	35.18	3.60	38.11	54	-15.89	Average	Horizontal
2483.50	51.30	33.06	35.18	3.60	52.78	74	-21.22	Peak	Vertical
2483.50	35.97	33.06	35.18	3.60	37.45	54	-16.55	Average	Vertical

802.11n(HT20)

Tx-2412

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
2390.00	49.37	32.89	35.16	3.51	50.61	74	-23.39	Peak	Horizontal
2390.00	35.54	32.89	35.16	3.51	36.78	54	-17.22	Average	Horizontal
2400.00	52.72	32.92	35.16	3.54	54.02	74	-19.98	Peak	Horizontal
2400.00	40.86	32.92	35.16	3.54	42.16	54	-11.84	Average	Horizontal
2390.00	49.17	32.89	35.16	3.51	50.41	74	-23.59	Peak	Vertical
2390.00	34.34	32.89	35.16	3.51	35.58	54	-18.42	Average	Vertical
2400.00	54.07	32.92	35.16	3.54	55.37	74	-18.63	Peak	Vertical
2400.00	40.96	32.92	35.16	3.54	42.26	54	-11.74	Average	Vertical

Tx-2462

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
2483.50	50.74	33.06	35.18	3.60	52.22	74	-21.78	Peak	Horizontal
2483.50	37.28	33.06	35.18	3.60	38.76	54	-15.24	Average	Horizontal
2483.50	50.56	33.06	35.18	3.60	52.04	74	-21.96	Peak	Vertical
2483.50	35.64	33.06	35.18	3.60	37.12	54	-16.88	Average	Vertical

5.6. Conducted Spurious Emissions and Band Edges Test

5.6.1. Standard Applicable

According to §15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.6.2. Measuring Instruments and Setting

Please refer to section 6 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Detector	Peak
Attenuation	Auto
RB / VB (Emission in restricted band)	100KHz/300KHz
RB / VB (Emission in non-restricted band)	100KHz/300KHz

5.6.3. Test Procedures

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz

The spectrum from 9kHz to 40GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

5.6.4. Test Setup Layout



This test setup layout is the same as that shown in section 5.4.4.


5.6.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


5.6.6. Test Results of Conducted Spurious Emissions



802.11b








802.11g






802.11n HT20






5.6.7. Test Results of Band Edges Test


802.11b



802.11g



802.11n HT20




5.7. Power line conducted emissions

5.7.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

5.7.2 Block Diagram of Test Setup




5.7.3 Test Results

PASS.

The test data please refer to following page.


Test result for 802.11b(AC 120V)



Env. Ins: 24*/56%
 Power Rating: AC 120V/60Hz
 Pol: NEUTRAL

Freq	Reading	LISN	Fac	Cab	Measured	Limit	Over	Remark
MHz	dBuA	dB	dB	dBuA	dBuA	dB		
1	0.15	18.62	9.69	0.02	38.33	55.78	-17.45	Average
2	0.15	39.90	9.69	0.02	59.61	65.78	-6.17	QP
3	0.24	12.51	9.60	0.03	32.14	52.04	-19.90	Average
4	0.24	31.68	9.60	0.03	51.31	62.04	-10.73	QP
5	0.39	16.35	9.61	0.04	36.00	47.99	-11.99	Average
6	0.39	27.78	9.61	0.04	47.43	57.99	-10.56	QP
7	0.45	12.37	9.62	0.04	32.03	46.80	-14.77	Average
8	0.45	26.07	9.62	0.04	45.73	56.80	-11.07	QP
9	0.79	7.12	9.63	0.04	26.79	46.00	-19.21	Average
10	0.79	25.12	9.63	0.04	44.79	56.00	-11.21	QP
11	1.29	0.86	9.63	0.05	20.54	46.00	-25.46	Average
12	1.29	23.86	9.63	0.05	43.54	56.00	-12.46	QP

Remarks: 1. Measured = Reading +Cable Loss.
 2. The emission levels that are 20dB below the official limit are not reported.




Env. Ins: 24*/56%
 Power Rating: AC 120V/60Hz
 Pol: LINE

Freq	Reading	LISN	Fac	Cab	Measured	Limit	Over	Remark
MHz	dBuA	dB	dB	dBuA	dBuA	dB		
1	0.15	23.65	9.57	0.02	43.24	55.96	-12.72	Average
2	0.15	40.86	9.57	0.02	60.45	65.96	-5.51	QP
3	0.18	19.69	9.61	0.02	39.32	54.42	-15.10	Average
4	0.18	38.74	9.61	0.02	58.37	64.42	-6.05	QP
5	0.30	15.61	9.63	0.03	35.27	50.19	-14.92	Average
6	0.30	33.79	9.63	0.03	53.45	60.19	-6.74	QP
7	0.52	7.46	9.62	0.04	27.12	46.00	-18.88	Average
8	0.52	25.87	9.62	0.04	45.53	56.00	-10.47	QP
9	0.98	5.16	9.63	0.05	24.84	46.00	-21.16	Average
10	0.98	25.25	9.63	0.05	44.93	56.00	-11.07	QP
11	2.33	-2.27	9.64	0.05	17.42	46.00	-28.58	Average
12	2.33	20.03	9.64	0.05	39.72	56.00	-16.28	QP

Remarks: 1. Measured = Reading +Cable Loss.
 2. The emission levels that are 20dB below the official limit are not reported.


Test result for 802.11b(AC 230V)



Env. Ins: 24*/56%
 Power Rating: AC 230V/50Hz
 Pol: NEUTRAL

Freq	Reading	LISN	Fac	Cab	Measured	Limit	Over	Remark
MHz	dBuA			dB	dBuA	dBuA	dB	
1	0.15	18.69		9.69	0.02	38.40	55.78	-17.38 Average
2	0.15	39.20		9.69	0.02	58.91	65.78	-6.87 QP
3	0.24	12.15		9.60	0.03	31.78	52.04	-20.26 Average
4	0.24	31.36		9.60	0.03	50.99	62.04	-11.05 QP
5	0.39	16.81		9.61	0.04	36.46	47.99	-11.53 Average
6	0.39	27.20		9.61	0.04	46.85	57.99	-11.14 QP
7	0.45	12.88		9.62	0.04	32.54	46.80	-14.26 Average
8	0.45	26.69		9.62	0.04	46.35	56.80	-10.45 QP
9	0.79	7.28		9.63	0.04	26.95	46.00	-19.05 Average
10	0.79	25.84		9.63	0.04	45.51	56.00	-10.49 QP
11	1.29	0.52		9.63	0.05	20.20	46.00	-25.80 Average
12	1.29	23.24		9.63	0.05	42.92	56.00	-13.08 QP

Remarks: 1. Measured = Reading +Cable Loss.
 2. The emission levels that are 20dB below the official limit are not reported.



Env. Ins: 24*/56%
 Power Rating: AC 230V/50Hz
 Pol: LINE

Freq	Reading	LISN	Fac	Cab	Measured	Limit	Over	Remark
MHz	dBuA			dB	dBuA	dBuA	dB	
1	0.15	23.47		9.57	0.02	43.06	55.96	-12.90 Average
2	0.15	40.12		9.57	0.02	59.71	65.96	-6.25 QP
3	0.18	19.81		9.61	0.02	39.44	54.42	-14.98 Average
4	0.18	38.90		9.61	0.02	58.53	64.42	-5.89 QP
5	0.30	15.16		9.63	0.03	34.82	50.19	-15.37 Average
6	0.30	33.85		9.63	0.03	53.51	60.19	-6.68 QP
7	0.52	7.37		9.62	0.04	27.03	46.00	-18.97 Average
8	0.52	25.11		9.62	0.04	44.77	56.00	-11.23 QP
9	0.98	5.56		9.63	0.05	25.24	46.00	-20.76 Average
10	0.98	25.37		9.63	0.05	45.05	56.00	-10.95 QP
11	2.33	-2.44		9.64	0.05	17.25	46.00	-28.75 Average
12	2.33	20.10		9.64	0.05	39.79	56.00	-16.21 QP

Remarks: 1. Measured = Reading +Cable Loss.
 2. The emission levels that are 20dB below the official limit are not reported.

***Note: Pre-scan all mode and recorded the worst case results in this report (802.11b).

5.8. Antenna Requirements

5.8.1 Standard Applicable

According to antenna requirement of §15.203. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

5.8.2 Antenna Connected Construction

5.8.2.1. Standard Applicable

According to § 15.203 & RSS-Gen, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

5.8.2.2. Antenna Connector Construction

The directional gains of antenna used for transmitting is 2.4dBi, and the PIFA antenna is connect to PCB board and no consideration of replacement. Please see EUT photo for details.

5.8.2.3. Results: Compliance.

6. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Cal Date	Due Date
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	June 18, 2015	June 17, 2016
Signal analyzer	Agilent	E4448A(External mixers to 40GHz)	US44300469	9kHz~40GHz	July 16, 2015	July 15, 2016
Signal analyzer	Agilent	N9020A	MY50510140	9kHz~26.5GHz	October 27, 2014	October 26, 2015
LISN	MESS Tec	NNB-2/16Z	99079	9KHz-30MHz	June 18, 2015	June 17, 2016
LISN (Support Unit)	EMCO	3819/2NM	9703-1839	9KHz-30MHz	June 18, 2015	June 17, 2016
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9KHz-30MHz	June 18, 2015	June 17, 2016
ISN	SCHAFFNER	ISN ST08	21653	9KHz-30MHz	June 18, 2015	June 17, 2016
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30M-1GHz 3m	June 18, 2015	June 17, 2016
Amplifier	SCHAFFNER	COA9231A	18667	9kHz-2GHz	June 18, 2015	June 17, 2016
Amplifier	Agilent	8449B	3008A02120	1GHz-26.5GHz	July 16, 2015	July 15, 2016
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5GHz-40GHz	July 16, 2015	July 15, 2016
Loop Antenna	R&S	HFH2-Z2	860004/001	9k-30MHz	June 18, 2015	June 17, 2016
By-log Antenna	SCHWARZBECK	VULB9163	9163-470	30MHz-1GHz	June 10, 2015	June 09, 2016
Horn Antenna	EMCO	3115	6741	1GHz-18GHz	June 10, 2015	June 09, 2016
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15GHz-40GHz	June 10, 2015	June 09, 2016
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz-1GHz	June 18, 2015	June 17, 2016
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1GHz-40GHz	June 18, 2015	June 17, 2016
Spectrum Meter	R&S	FSP 30	100023	9kHz-30GHz	July 16, 2015	July 15, 2016
Power Meter	R&S	NRVS	100444	DC-40GHz	June 18, 2015	June 17, 2016
Power Sensor	R&S	NRV-Z51	100458	DC-30GHz	June 18, 2015	June 17, 2016
Power Sensor	R&S	NRV-Z32	10057	30MHz-6GHz	June 18, 2015	June 17, 2016
AC Power Source	HPC	HPA-500E	HPA-9100024	AC 0~300V	June 18, 2015	June 17, 2016
DC power Soure	GW	GPC-6030D	C671845	DC 1V-60V	June 18, 2015	June 17, 2016
Temp. and Humidig	Giant Force	GTH-225-20-S	MAB0103-00	N/A	June 18, 2015	June 17, 2016
RF CABLE-1m	JYE Bao	RG142	CB034-1m	20MHz-7GHz	June 18, 2015	June 17, 2016
RF CABLE-2m	JYE Bao	RG142	CB)35-2m	20MHz-1GHz	June 18, 2015	June 17, 2016
Vector signal Generator	R&S	SMU200A	102098	100kHz~6GHz	June 18, 2015	June 17, 2016
Signal Generator	R&S	SMR40	10016	10MHz~40GHz	July 16, 2015	July 15, 2016

Note: All equipment through GRGT EST calibration

-----THE END OF REPORT-----