

**Shenzhen Global Test Service Co.,Ltd.**

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

RF Exposure evaluation**Report Reference No.....: GTS20221031017-1-14****FCC ID.: 2AG7C-6131E-U**

Compiled by

(position+printed name+signature) : File administrators Peter Xiao

Peter Xiao

Supervised by

(position+printed name+signature) : Test Engineer Jenny Zeng

Jenny Zeng

Approved by

(position+printed name+signature) : Manager Jason Hu



Date of issue: Dec.09, 2022

Representative Laboratory Name.: Shenzhen Global Test Service Co.,Ltd.

Address: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

Applicant's name.....: Hangzhou Meari Technology Co., Ltd.

Address: Room 604-605, Building 1, No.768 Jianghong Road, Changhe street, Binjiang District, Hangzhou, zhejiang, China

Test specificationStandard.....: **47CFR §1.1310 Basis and purpose**
47CFR §2.1091 Radiofrequency radiation exposure evaluation:
mobile devices
KDB447498 D01 General RF Exposure Guidance v06

TRF Originator.....: Shenzhen Global Test Service Co.,Ltd.

Master TRF: Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: CAMERA WiFi Module

Trade Mark.....: N/A

Manufacturer: Hangzhou Meari Technology Co., Ltd.

Model/Type reference: 6131E-U

Listed Models: Speed 18T, Speed 18S, PTCam, Speed 4S, Speed 4T, PT-cam, DOME1, DOME1 PRO, P2T, P2F, P2, OUTDOOR1, Mini 18S, Mini 18T, MiniCam, INDOOR1, INDOOR1 PRO

Hardware Version: V5.3

Software Version.....: V5.13.0

Rating.....: DC 3.3V

Result: **PASS**

TEST REPORT

Test Report No. :	GTS20221031017-1-14	Dec.09, 2022
		Date of issue

Equipment under Test : CAMERA WiFi Module

Model /Type : 6131E-U

Listed model : Speed 18T, Speed 18S, PTCam, Speed 4S, Speed 4T, PT-cam, DOME1, DOME1 PRO, P2T, P2F, P2, OUTDOOR1, Mini 18S, Mini 18T, MiniCam, INDOOR1, INDOOR1 PRO

Applicant : **Hangzhou Meari Technology Co., Ltd.**

Address : Room 604-605, Building 1, No.768 Jianghong Road, Changhe street, Binjiang District, Hangzhou, zhejiang, China

Manufacturer : **Hangzhou Meari Technology Co., Ltd.**

Address : 4F of Building 1 and 2-4F of Building 2, No. 91 Chutian Road, Xixing Street, Binjiang District, Hangzhou, Zhejiang, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. SUMMARY4

1.1 EUT CONFIGURATION.....4

1.2 PRODUCT DESCRIPTION4

2. TEST ENVIRONMENT.....5

2.1 ADDRESS OF THE TEST LABORATORY5

2.2 TEST FACILITY5

2.3 ENVIRONMENTAL CONDITIONS5

2.4 STATEMENT OF THE MEASUREMENT UNCERTAINTY5

3. METHOD OF MEASUREMENT.....6

3.1 APPLICABLE STANDARD.....6

3.2 REQUIREMENT6

3.3 LIMIT6

3.4 MPE CALCULATION METHOD7

3.5 ANTENNA INFORMATION7

4. CONDUCTED POWER RESULTS8

5. MANUFACTURING TOLERANCE.....10

6. MEASUREMENT RESULTS.....12

6.1 STANDALONE MPE EVALUATION.....12

6.2 SIMULTANEOUS TRANSMISSION MPE13

7. CONCLUSION14

1. SUMMARY

1.1 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

● /	Length (m) :	/
	Shield :	/
	Detachable :	/

1.2 Product Description

Product Name	CAMERA WiFi Module
Trade Mark	N/A
Model/Type reference	6131E-U
List Models	Speed 18T, Speed 18S, PTCam, Speed 4S, Speed 4T, PT-cam, DOME1, DOME1 PRO, P2T, P2F, P2, OUTDOOR1, Mini 18S, Mini 18T, MiniCam, INDOOR1, INDOOR1 PRO
Model Declaration	PCB board, structure and internal of these model(s) are the same, Only the model name different , So no additional models were tested.
Power supply:	DC 3.3V
Sample ID	GTS20221031017-1-S0001-1#>S20221031017-1-S0001-2#
WIFI(2.4G Band)	
Frequency Range	2412MHz ~ 2462MHz
Channel Spacing	5MHz
Channel Number	11 Channel for 20MHz bandwidth(2412~2462MHz) 7 Channel for 20MHz bandwidth(2422~2452MHz)
Modulation Type	802.11b: DSSS; 802.11g/n: OFDM
WIFI(5.2G/5.3G/5.7G Band)	
Frequency Range	5150MHz ~ 5250MHz, 5250MHz ~ 5350MHz, 5500MHz ~ 5700MHz
Channel Number	4 Channels for 20MHz bandwidth(5180-5240MHz) 4 Channels for 20MHz bandwidth(5260-5320MHz) 11 Channels for 20MHz bandwidth(5500-5700MHz) 2 channels for 40MHz bandwidth(5190~5230MHz) 2 channels for 40MHz bandwidth(5270~5310MHz) 5 Channels for 40MHz bandwidth(5510-5670MHz)
Modulation Type	802.11a/n: OFDM
WIFI (5.8G Band)	
Frequency Range	5745MHz ~ 5825MHz
Channel Number	5 channels for 20MHz bandwidth(5745-5825MHz) 2 channels for 40MHz bandwidth(5755~5795MHz)
Modulation Type	802.11a/n: OFDM
Antenna Description	FPC Antenna, 3.50dBi(Max.) for 2.4G Band and 2.96dBi(Max.) for 5G Band

2. TEST ENVIRONMENT

2.1 Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

2.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1234.

FCC Registered Test Site Number is165725.

2.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. METHOD OF MEASUREMENT

3.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

3.2 Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498 D01 General RF Exposure Guidance v06 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3.3 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3.4 MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

As declared by the Applicant, the EUT transmits with the maximum source-based Duty Cycle of 100%-see the User manual, and the EUT is a wireless device used in a mobile application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum mobile separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna is 3.50&2.96dBi for WLAN, and the power drift from Turn-up Procedure provide by manufacturer as following states, the RF power density can be obtained.

3.5 Antenna Information

6131E-U can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 0	WLANANT 0	FPC antenna	2.4 – 2.5 GHz 5.0 – 6.0 GHz	3.50dBi(Max.) for 2.4G band 2.96dBi(Max.) for 5G band

4. Conducted Power Results

2.4G WLAN

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11b	01	2412	17.50
	06	2437	17.32
	11	2462	18.07
802.11g	01	2412	18.66
	06	2437	18.72
	11	2462	18.78
802.11n(HT20)	01	2412	17.77
	06	2437	18.97
	11	2462	18.01
802.11n(HT20)	03	2422	17.29
	06	2437	18.94
	09	2452	17.88

5.2G WLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	36	5180	12.59
	40	5200	12.52
	48	5240	11.86
802.11n20	36	5180	11.68
	40	5200	10.69
	48	5240	9.92
802.11n40	38	5190	9.99
	46	5230	11.15

5.3G WLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	52	5260	11.61
	56	5280	11.20
	64	5320	10.88
802.11n20	52	5260	10.72
	56	5280	9.22
	64	5320	10.30
802.11n40	54	5270	10.33
	62	5310	11.51

5.7G WLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	100	5500	12.67
	120	5600	12.24
	140	5700	12.14
802.11n20	100	5500	12.34
	120	5600	12.07
	140	5700	11.39
802.11n40	102	5510	11.00
	118	5590	12.00
	134	5670	12.19

5.8GWLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	149	5745	11.10
	157	5785	12.81
	165	5825	13.04
802.11n20	149	5745	11.89
	157	5785	12.82
	165	5825	13.16
802.11n40	151	5755	14.10
	159	5795	11.37

5. Manufacturing Tolerance

2.4GWLAN

IEEE 802.11b (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	17.0	17.00	18.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	18.0	18.0	18.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	17.0	18.0	18.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Peak)			
Channel	Channel 03	Channel 06	Channel 09
Target (dBm)	17.0	18.0	17.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5.2GWLAN

IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	12.0	12.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	10.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n VHT40 (Average)			
Channel	Channel 38	Channel 46	/
Target (dBm)	9.0	11.0	/
Tolerance $\pm$ (dB)	1.0	1.0	/

5.3GWLAN

IEEE 802.11a (Average)			
Channel	Channel 52	Channel 56	Channel 64
Target (dBm)	11.0	11.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 52	Channel 56	Channel 64
Target (dBm)	10.0	9.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n VHT40 (Average)			
Channel	Channel 54	Channel 62	/
Target (dBm)	10.0	11.0	/
Tolerance $\pm$ (dB)	1.0	1.0	/

5.7GWLAN

IEEE 802.11a (Average)			
Channel	Channel 100	Channel 120	Channel 140
Target (dBm)	12.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 100	Channel 120	Channel 140
Target (dBm)	12.0	12.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n VHT40 (Average)			
Channel	Channel 102	Channel 118	Channel 134
Target (dBm)	11.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5.8GWLAN

IEEE 802.11a (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	12.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	12.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Channel	Channel 151	Channel 159	/
Target 6dBm)710.0	14.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	/

6. Measurement Results

6.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

2.4G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MPE Limits (mW/cm^2)
	dBm	mW				
802.11b	19.00	79.4328	3.50	2.2387	0.0354	1.0000
802.11g	19.00	79.4328	3.50	2.2387	0.0354	1.0000
802.11n(HT20)	19.00	79.4328	3.50	2.2387	0.0354	1.0000
802.11n(HT40)	19.00	79.4328	3.50	2.2387	0.0354	1.0000

5.2G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MP20 Limits (mW/cm^2)
	dBm	mW				
802.11a	13.00	19.9526	2.96	1.9770	0.0078	1.0000
802.11n20	12.00	15.8489	2.96	1.9770	0.0062	1.0000
802.11n40	12.00	15.8489	2.96	1.9770	0.0062	1.0000

5.3G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MP20 Limits (mW/cm^2)
	dBm	mW				
802.11a	12.00	15.8489	2.96	1.9770	0.0062	1.0000
802.11n20	11.00	12.5893	2.96	1.9770	0.0050	1.0000
802.11n40	12.00	15.8489	2.96	1.9770	0.0062	1.0000

5.7G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MP20 Limits (mW/cm^2)
	dBm	mW				
802.11a	13.00	19.9526	2.96	1.9770	0.0078	1.0000
802.11n20	13.00	19.9526	2.96	1.9770	0.0078	1.0000
802.11n40	13.00	19.9526	2.96	1.9770	0.0078	1.0000

5.8G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MP17.00
	dBm	mW				
802.11a	14.00	25.1189	2.96	1.9770	0.0099	1.0000
802.11n20	14.00	25.1189	2.96	1.9770	0.0099	1.0000
802.11n40	15.00	31.6228	2.96	1.9770	0.0124	1.0000

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

6.2 Simultaneous Transmission MPE

The sample support one Bluetooth & WLAN modular and one Bluetooth antenna, and two WLAN antennas, WLAN support MIMO, Need consider simultaneous transmission ;

The sample supports 2T2R MIMO technology for WLAN.

According to KDB447498 D01 General RF Exposure Guidance v06 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

Σ of MPE ratios ≤ 1.0

6.2.1 Summary simultaneous transmission results

Maximum Simultaneous transmission MPE Ratios for **2.4GWLAN, 5.8GWLAN** .

Maximum MPE ratio 2.4GWLAN	Maximum MPE ratio 5.8GWLAN	Σ MPE ratios	Limit	Results
0.0354	0.0124	0.0478	1.0	PASS

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB447498 D01 General RF Exposure Guidance v06, No SAR is required.

.....End of Report.....