

Case No. : <u>GTS20250807004-6-03</u>
Ambient Condition: <u>21</u> °C, <u>55</u> %RH
According Standard: ■Part15C
Test Date: <u>2025.8.13-2025.8.25</u> Test Engineer: <u>Evan ouyang</u>


AppendixA.1: DTS Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE	Ant1	2402	0.640	2401.664	2402.304	0.5	PASS
		2440	0.572	2439.704	2440.276	0.5	PASS
		2480	0.504	2479.752	2480.256	0.5	PASS

Test Graphs

BLE_Ant1_2402



BLE_Ant1_2440



BLE_Ant1_2480




AppendixA.2: Occupied Channel Bandwidth

Test Result


TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE	Ant1	2402	1.1083	2401.4352	2402.5435	---	---
		2440	1.0870	2439.4527	2440.5397	---	---
		2480	1.0998	2479.4453	2480.5451	---	---

Test Graphs

BLE_Ant1_2402



BLE_Ant1_2440



BLE_Ant1_2480



AppendixA.3: Maximum conducted output power

Test Result Peak

TestMode	Antenna	Freq(MHz)	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
BLE	Ant1	2402	15.62	≤30	PASS
		2440	16.05	≤30	PASS
		2480	15.67	≤30	PASS

AppendixA.4: Maximum power spectral density

Test Result


TestMode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE	Ant1	2402	-3.01	≤8.00	PASS
		2440	-2.38	≤8.00	PASS
		2480	-3.14	≤8.00	PASS

Test Graphs


BLE_Ant1_2402



BLE_Ant1_2440



BLE_Ant1_2480




Appendix A.5: Band edge measurements

Test Result

TestMode	Antenna	ChName	Freq(MHz)	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE	Ant1	Low	2402	12.05	-42.99	≤ -7.96	PASS
		High	2480	13.15	-47.08	≤ -6.85	PASS

Test Graphs



BLE_Ant1_High_2480

Frequency

Auto Tune

Center Freq
2.510000000 GHzStart Freq
2.470000000 GHzStop Freq
2.550000000 GHzCF Step
8.000000 MHz
AutoFreq Offset
0 Hz

Appendix A.6: Conducted Spurious Emission

Test Result


TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE	Ant1	2402	Reference	10.74	10.74	---	PASS
			30~1000	10.74	-59.82	≤ -9.26	PASS
			1000~26500	10.74	-47.89	≤ -9.26	PASS
		2440	Reference	11.77	11.77	---	PASS
			30~1000	11.77	-59.9	≤ -8.23	PASS
			1000~26500	11.77	-47.08	≤ -8.23	PASS
		2480	Reference	13.18	13.18	---	PASS
			30~1000	13.18	-60.73	≤ -6.82	PASS
			1000~26500	13.18	-47.95	≤ -6.82	PASS

Test Graphs


BLE_Ant1_2402_0-Reference



BLE_Ant1_2402_30-1000




BLE_Ant1_2402_1000-26500




BLE_Ant1_2440_0-Reference




BLE_Ant1_2440_30~1000



BLE_Ant1_2440_1000~26500



BLE_Ant1_2480_0~Reference




AppendixA.7: Duty Cycle

Test Result


TestMode	Antenna	Freq(MHz)	ON Time [ms]	Period [ms]	X	DC [%]	Duty Cycle Factor[dB]	1/T Factor[KHz]
BLE	Ant1	2402	0.40	0.63	0.6349	63.49	1.97	2.50
		2440	0.40	0.63	0.6349	63.49	1.97	2.50
		2480	0.40	0.62	0.6452	64.52	1.90	2.50

Test Graphs


BLE_Ant1_2402



BLE_Ant1_2440



BLE_Ant1_2480



Appendix A.8: Emissions in Restricted Bands

Test Result


TestMode	Antenna	ChName	Freq(MHz)	Detector	Freq [MHz]	Result [dBm]	Limit [dBm]	Result [dBuV/m]	Limit [dBuV/m]	Verdict
BLE	Ant1	Low	2402	AV	2310.000	-49.16	≤-41.20	46.04	≤54	PASS
				AV	2389.145	-48.47	≤-41.20	46.73	≤54	PASS
				AV	2390.000	-48.5	≤-41.20	46.70	≤54	PASS
				Peak	2310.000	-42.68	≤-21.20	52.52	≤74	PASS
				Peak	2389.565	-36.67	≤-21.20	58.53	≤74	PASS
				Peak	2390.000	-40.1	≤-21.20	55.10	≤74	PASS
		High	2480	AV	2483.500	-43.79	≤-41.20	51.41	≤54	PASS
				AV	2483.520	-43.79	≤-41.20	51.41	≤54	PASS
				AV	2500.000	-48.53	≤-41.20	46.67	≤54	PASS
				Peak	2483.500	-39.4	≤-21.20	55.80	≤74	PASS
				Peak	2483.840	-27.74	≤-21.20	67.46	≤74	PASS
				Peak	2500.000	-42.26	≤-21.20	52.94	≤74	PASS

Note:


1. The Antenna Gain is compensated in the graph.
2. The Duty Cycle Factor and RBW Factor is compensated in the graph.
3. The limit in dBm for average detector is conversion from 54dBuV/m, according to 15.209(a). The limit in dBm for peak detector is 20dB above the limit of average detector in dBm.

Test Graphs

BLE_Ant1_Low_2402_AV



BLE_Ant1_Low_2402_Peak



BLE_Ant1_High_2480_AV

