

Case No. : <u>GTS20250807004-6-05</u>
Ambient Condition: <u>21</u> °C, <u>55</u> %RH
According Standard: <u>■Part15E</u>
Test Date: <u>2025.8.13-2025.8.25</u> Test Engineer: <u>Evan ouyang</u>


Appendix F.1: Occupied channel bandwidth

Test Result


TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5745	16.863	5736.5073	5753.3703	---	---
		5785	16.794	5776.5220	5793.3160	---	---
		5825	16.737	5816.5670	5833.3040	---	---
11N20SISO	Ant1	5745	17.873	5735.9883	5753.8613	---	---
		5785	17.806	5776.0122	5793.8182	---	---
		5825	17.771	5816.0552	5833.8262	---	---

Test Graphs


11A_Ant1_5745




11A_Ant1_5785




11A_Ant1_5825




11N20SISO_Ant1_5745



11N20SISO_Ant1_5785



11N20SISO_Ant1_5825




Appendix F.2: Min emission bandwidth

Test Result B4


TestMode	Antenna	Freq(MHz)	6db EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5745	16.480	5736.720	5753.200	0.5	PASS
		5785	16.520	5776.680	5793.200	0.5	PASS
		5825	16.520	5816.680	5833.200	0.5	PASS
11N20SISO	Ant1	5745	17.680	5736.080	5753.760	0.5	PASS
		5785	17.680	5776.080	5793.760	0.5	PASS
		5825	17.680	5816.080	5833.760	0.5	PASS

Test Graphs B4


11A_Ant1_5745




11A_Ant1_5785



11A_Ant1_5825




11N20SISO_Ant1_5745



11N20SISO_Ant1_5785



11N20SISO_Ant1_5825




AppendixF.3: Duty Cycle

Test Result


TestMode	Antenna	Freq(MHz)	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]	1/T Factor[KHz]
11A	Ant1	5745	30.00	30.00	100.00	0.00	0.03
		5785	30.00	30.00	100.00	0.00	0.03
		5825	30.00	30.00	100.00	0.00	0.03
11N20SISO	Ant1	5745	30.00	30.00	100.00	0.00	0.03
		5785	30.00	30.00	100.00	0.00	0.03
		5825	30.00	30.00	100.00	0.00	0.03

Test Graphs


11A_Ant1_5745




11A_Ant1_5785




11A_Ant1_5825




11N20SISO_Ant1_5745



11N20SISO_Ant1_5785



11N20SISO_Ant1_5825



Appendix F.4: Maximum conducted output power

Test Result Channel Power

Test Mode	Antenna	Freq(MHz)	Channel Power [dBm]	Duty Cycle [%]	DC Factor [dBm]	Result [dBm]	Limit [dBm]	Verdict
11A	Ant1	5745	16.50	100.00	0.00	16.50	≤30.00	PASS
		5785	16.73	100.00	0.00	16.73	≤30.00	PASS
		5825	16.94	100.00	0.00	16.94	≤30.00	PASS
11N20SISO	Ant1	5745	16.49	100.00	0.00	16.49	≤30.00	PASS
		5785	16.56	100.00	0.00	16.56	≤30.00	PASS
		5825	16.28	100.00	0.00	16.28	≤30.00	PASS

Appendix F.5: Maximum power spectral density

Test Result

TestMode	Antenna	Freq(MHz)	Result [dBm/MHz]	Limit[dBm/MHz]	Verdict
11A	Ant1	5745	0.43	≤30.00	PASS
		5785	0.64	≤30.00	PASS
		5825	0.90	≤30.00	PASS
11N20SISO	Ant1	5745	-1.09	≤30.00	PASS
		5785	-0.80	≤30.00	PASS
		5825	-0.38	≤30.00	PASS

Note: 1.The Result and Limit Unit is dBm/500 kHz in the band 5.725–5.85 GHz.
2.The Duty Cycle Factorand RBW Factoriscompensatedinthe graph.

Test Graphs

11A_Ant1_5745




11A_Ant1_5785




11A_Ant1_5825




11N20SISO_Ant1_5745



11N20SISO_Ant1_5785



11N20SISO_Ant1_5825



Appendix F.6:Band edge measurements

Test Result B4

TestMode	Antenna	ChName	Freq(MHz)	FreqRange [MHz]	Result [dBm]	Limit [dBm]	Verdict
11A	Ant1	Low	5745	5650~5700	-39.35	≤ -26.27	PASS
				5700~5720	-27.39	≤ 15.43	PASS
				5720~5725	-27.42	≤ 17.13	PASS
				5760~5650	-39.76	≤ -27	PASS
		High	5825	5850~5855	-38.21	≤ 15.73	PASS
				5855~5875	-38.26	≤ 10.51	PASS
				5875~5925	-39.31	≤ -26.91	PASS
				5925~5935	-37.98	≤ -27	PASS
11N20SISO	Ant1	Low	5745	5650~5700	-40.33	≤ -26.87	PASS
				5700~5720	-29.76	≤ 15.34	PASS
				5720~5725	-28.71	≤ 15.82	PASS
				5760~5650	-39.61	≤ -27	PASS
		High	5825	5850~5855	-38.94	≤ 16.34	PASS
				5855~5875	-38.97	≤ 10.21	PASS
				5875~5925	-39.53	≤ -26.91	PASS
				5925~5935	-37.95	≤ -27	PASS

Test GraphsB4


11A_Ant1_Low_5745



11A_Ant1_High_5825



11N20SISO_Ant1_Low_5745






Appendix F.7:Conducted Spurious Emission

Test Result


TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	Max. Fre [MHz]	Max. Level [dBm]	Limit [dBm]	Verdict
11A	Ant1	5745	30~5650	5444.5	-40.62	≤-27	PASS
			5925~27000	24865.81	-31.09	≤-27	PASS
		5785	30~5650	4928.2	-40.43	≤-27	PASS
			5925~27000	26024.23	-30.23	≤-27	PASS
		5825	30~5650	5035.55	-39.67	≤-27	PASS
			5925~27000	24339.63	-30.5	≤-27	PASS
11N20SISO	Ant1	5745	30~5650	3359.48	-40.91	≤-27	PASS
			5925~27000	24848.24	-31.82	≤-27	PASS
		5785	30~5650	3179.26	-39.99	≤-27	PASS
			5925~27000	26792.06	-30.34	≤-27	PASS
		5825	30~5650	4949	-39.82	≤-27	PASS
			5925~27000	23623.79	-31.31	≤-27	PASS

Test Graphs

11A_Ant1_5745_30-5650




11A_Ant1_5745_5925-27000




11A_Ant1_5785_30-5650




11A_Ant1_5785_5925-27000




11A_Ant1_5825_30-5650




11A_Ant1_5825_5925-27000




11N20SISO_Ant1_5745_30-5650




11N20SISO_Ant1_5745_5925-27000




11N20SISO_Ant1_5785_30-5650




11N20SISO_Ant1_5785_5925-27000



11N20SISO_Ant1_5825_30~5650



11N20SISO_Ant1_5825_5925~27000



Appendix F.8:Emissions in Restricted Bands

Test Result


TestMode	Antenna	ChName	Freq(MHz)	Detector	Freq [MHz]	Result [dBm]	Limit [dBm]	Verdict
11A	Ant1	Low	5745	Peak	5650.000	-42.528	≤-27.00	PASS
				Peak	5700.000	-41.29	≤10.00	PASS
				Peak	5720.000	-29.33	≤15.60	PASS
				Peak	5725.000	-22.03	≤27.00	PASS
		High	5825	Peak	5850.000	-34.744	≤27.00	PASS
				Peak	5855.000	-37.61	≤15.60	PASS
				Peak	5875.000	-37.95	≤10.00	PASS
				Peak	5925.000	-37.22	≤-27.00	PASS
11N20SISO	Ant1	Low	5745	Peak	5650.000	-41.71	≤-27.00	PASS
				Peak	5700.000	-44.23	≤10.00	PASS
				Peak	5720.000	-38.1	≤15.60	PASS
				Peak	5725.000	-24.8	≤27.00	PASS
		High	5825	Peak	5850.000	-35.121	≤27.00	PASS
				Peak	5855.000	-36.48	≤15.60	PASS
				Peak	5875.000	-37.91	≤10.00	PASS
				Peak	5925.000	-35.78	≤-27.00	PASS

Note:


1. The Antenna Gain is compensated in the graph.
2. The Duty Cycle Factor and RBW Factor is compensated in the graph.
3. For transmitters operating in 5150-5350 GHz band and 5470-5725 GHz band: The limit in dBm for average detector is conversion from 54dBuV/m, according to 15.209(a). The limit in dBm for peak detector is 20dB above the limit of average detector in dBm.

Test Graphs

11A_Ant1_Low_5745_Peak



11A_Ant1_High_5825_Peak



11N20SISO_Ant1_Low_5745_Peak

