

FCC RF EXPOSURE REPORT

FCC ID: 2AG7CMINI6

Project No. : 2011H045
Equipment : IP CAMERA
Brand Name : N/A
Test Model : Mini 6S
Series Model : Mini 6X
Applicant : Hangzhou Meari Technology Co., Ltd.
Address : Room 604-605, Building 1, No. 768 Jianghong Road,
Changhe street, Binjiang District, Hangzhou, Zhejiang, China
Manufacturer : Hangzhou Meari Technology Co., Ltd.
Address : No. 91 Chutian Road, Xixing Street, Binjiang District,
Hangzhou, Zhejiang, China
Factory : Hangzhou Meari Technology Co., Ltd.
Address : No. 91 Chutian Road, Xixing Street, Binjiang District,
Hangzhou, Zhejiang, China
Date of Receipt : Nov. 26, 2020
Date of Test : Nov. 26, 2020~Dec. 28, 2020
Issued Date : Jan .08, 2021
Report Version : R00
Test Sample : Engineering Sample No.: SH20201123166-6, SH20201123166-7
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Maker Qi

Prepared by : Maker Qi

Ryan. Wang

Approved by : Ryan Wang



Certificate # 5123. 03

Add: No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China
 TEL: +86-021-61765666
 Web: www.newbtl.com

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	Jan .08, 2021

1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

For 2.4G:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Internal	N/A	3

Note:

The antenna gain is provided by the manufacturer.

2. TEST RESULTS

For 2.4GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.00	1.9953	26	398.1072	0.1580	1	Complies

Note: The calculated distance is 20 cm.

Output power including tune up tolerance.

End of Test Report