FCC RF Test Report

APPLICANT : Plume Design Inc
EQUIPMENT : Plume Adaptive Wifi
BRAND NAME : Plume Design Inc

MODEL NAME : B1A

FCC ID : 2AG7G-B1A

STANDARD : FCC Part 15 Subpart C §15.247

CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Jan. 17, 2018 and testing was completed on Mar. 27, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 1 of 36 Report Issued Date : May 10, 2018

1190

: Rev. 04

Report No.: FR811726A

Report Template No.: BU5-FR15CBT4.0 Version 2.0

Report Version

TABLE OF CONTENTS

RE	VISIO	N HISTORY	3
SU	MMAR	RY OF TEST RESULT	4
1	GENI	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Manufacturer	5
	1.3	Product Feature of Equipment Under Test	5
	1.4	Modification of EUT	5
	1.5	Testing Location	6
	1.6	Applicable Standards	6
2	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	7
	2.1	Carrier Frequency Channel	7
	2.2	Test Mode	8
	2.3	Connection Diagram of Test System	9
	2.4	Support Unit used in test configuration and system	10
	2.5	EUT Operation Test Setup	10
	2.6	Measurement Results Explanation Example	10
3	TEST	「RESULT	11
	3.1	6dB and 99% Bandwidth Measurement	
	3.2	Output Power Measurement	16
	3.3	Power Spectral Density Measurement	17
	3.4	Conducted Band Edges and Spurious Emission Measurement	22
	3.5	Radiated Band Edges and Spurious Emission Measurement	
	3.6	AC Conducted Emission Measurement	31
	3.7	Antenna Requirements	33
4	LIST	OF MEASURING EQUIPMENT	34
5	UNC	ERTAINTY OF EVALUATION	36
ΑP	PEND	IX A. CONDUCTED TEST RESULTS	
ΑP	PEND	IX B. AC CONDUCTED EMISSION TEST RESULT	
ΑP	PEND	IX C. RADIATED SPURIOUS EMISSION	
ΑP	PEND	IX D. RADIATED SPURIOUS EMISSION PLOTS	
ΑP	PEND	IX E. DUTY CYCLE PLOTS	
ΑP	PEND	IX F. SETUP PHOTOGRAPHS	

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 2 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No. : FR811726A

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR811726A	Rev. 01	Initial issue of report	Apr. 02, 2018
FR811726A	Rev. 02	Revising connection diagram of test system in section 2.3	Apr. 17, 2018
FR811726A	Rev. 03	Updating setup photographs	Apr. 24, 2018
FR811726A	Rev. 04	Revising antenna information	May 10, 2018

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 3 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No. : FR811726A

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)(3)	Peak Output Power	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	≤ 20dBc	Pass	-
3.5	3.5 15.247(d) Radiated Ba		15.209(a) & 15.247(d)	Pass	Under limit 4.64 dB at 46.200 MHz
3.6	3.6 15.207 AC Conducted Emission		15.207(a)	Pass	Under limit 12.01 dB at 0.695 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 4 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No. : FR811726A

1 General Description

1.1 Applicant

Plume Design Inc

290 S California Ave, Palo Alto, CA94306

1.2 Manufacturer

Plume Design Inc

290 S California Ave, Palo Alto, CA94306

1.3 Product Feature of Equipment Under Test

Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, and Wi-Fi 5GHz 802.11a/n/ac

Product Specification subjective to this standard					
	WLAN				
	<for ant.="" lb=""></for>				
	<ant. 1="">: IFA Antenna</ant.>				
	<ant. 2="">: IFA Antenna</ant.>				
Antenna Type	<for ant.="" hb=""></for>				
Antenna Type	<ant. 1="">: PIFA Antenna</ant.>				
	<ant. 2="">: PIFA Antenna</ant.>				
	<ant. 3="">: IFA Antenna</ant.>				
	<ant. 4="">: IFA Antenna</ant.>				
	Bluetooth: Slot Antenna				

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 5 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.				
	No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park,				
Took Cita Lagation	Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)				
Test Site Location	TEL: +886-3-327-3456				
	FAX: +886-3-328-4978				
Total O'Co No	Sporton	Site No.			
Test Site No.	TH05-HY CO05-HY				

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.
	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd.
Test Site Location	Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)
rest site Location	TEL: +886-3-327-0868
	FAX: +886-3-327-0855
Test Site No.	Sporton Site No.
Test Site NO.	03CH11-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ANSI C63.10-2013

Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 6 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9 10 11 12	2420	30	2462
2400-2483.5 MHz		2422	31	2464
		2424	32	2466
		2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 7 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

	Summary table of Test Cases
Test Item	Data Rate / Modulation
rest item	Bluetooth – LE / GFSK
Conducted	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
TCs	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
ics	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
110011010	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
TCs	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC	
Conducted	Mode 1: WLAN (2.4GHz) Link + Bluetooth Idle + Lan 1 Link + Lan 2 Link
Emission	

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 8 of 36


Report Issued Date : May 10, 2018

Report Version : Rev. 04


Report No.: FR811726A

2.3 Connection Diagram of Test System

<AC Conducted Emission>



<Radiated Spurious Emission>



SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 9 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
2.	Notebook	DELL	Latitude E3340	FCC DoC/ Contains FCC ID: PD97260NGU	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Mobile Phone	Apple	A1687	BCG-E2944A	NA	NA

2.5 EUT Operation Test Setup

The RF test items, utility "CMD" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).
=
$$4.2 + 10 = 14.2$$
 (dB)

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 10 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- 5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
- 6. Measure and record the results in the test report.

3.1.4 Test Setup



SPORTON INTERNATIONAL INC.


TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 11 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

6 dB Bandwidth Plot on Channel 00




Date: 15.FEB.2018 00:53:54

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 12 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04


Report No.: FR811726A

6 dB Bandwidth Plot on Channel 19



Date: 15.FEB.2018 00:57:27

6 dB Bandwidth Plot on Channel 39



Date: 15.FEB.2018 00:44:35

SPORTON INTERNATIONAL INC.


TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 13 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

99% Bandwidth Plot on Channel 00




Date: 15.FEB.2018 00:56:02

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 14 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

99% Occupied Bandwidth Plot on Channel 19



Date: 15.FEB.2018 00:59:14

99% Occupied Bandwidth Plot on Channel 39



Date: 15.FEB.2018 00:48:14

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 15 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

- The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas.
 Guidance v04 section 9.1.3 PKPM1 Peak power meter method.
- 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 16 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

- The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No.
 558074 D01 DTS Meas. Guidance v04
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 6. Measure and record the results in the test report.
- 7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.


SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 17 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A


3.3.6 Test Result of Power Spectral Density Plots (100kHz)

PSD 100kHz Plot on Channel 00



Date: 15.FEB.2018 00:54:37

PSD 100kHz Plot on Channel 19




Date: 15.FEB.2018 00:58:10

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 18 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

PSD 100kHz Plot on Channel 39




Date: 15.FEB.2018 00:45:42

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 19 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No. : FR811726A


3.3.7 Test Result of Power Spectral Density Plots (3kHz)

PSD 3kHz Plot on Channel 00



Date: 15.FEB.2018 00:54:13

PSD 3kHz Plot on Channel 19




Date: 15.FEB.2018 00:57:50

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 20 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

PSD 3kHz Plot on Channel 39



Date: 15.FEB.2018 00:45:12

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 21 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
- 5. Measure and record the results in the test report.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup




TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 22 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A


3.4.5 Test Result of Conducted Band Edges Plots

Low Band Edge Plot on Channel 00



Date: 15.FEB.2018 00:54:59

High Band Edge Plot on Channel 39



Date: 15.FEB.2018 00:52:12


SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 23 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A


3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 15.FEB.2018 00:55:45

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 15.FEB.2018 00:55:28

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 24 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04


Report No.: FR811726A

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 15.FEB.2018 00:58:56

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 15.FEB.2018 00:58:37

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 25 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04


Report No.: FR811726A

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 15.FEB.2018 00:47:55

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 15.FEB.2018 00:47:33

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 26 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency	Field Strength	Measurement Distance		
(MHz)	(microvolts/meter)	(meters)		
0.009 - 0.490	2400/F(kHz)	300		
0.490 – 1.705	24000/F(kHz)	30		
1.705 – 30.0	30	30		
30 – 88	100	3		
88 – 216	150	3		
216 - 960	200	3		
Above 960	500	3		

3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 27 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

3.5.3 Test Procedures

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
- 2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
- 3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 5. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level
- For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
- 7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \ge 1$ GHz for peak measurement. For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


SPORTON INTERNATIONAL INC.
TEL: 886-3-327-3456

FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 28 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04


Report No.: FR811726A

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz




SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 29 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 30 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Eroquency of emission (MUz)	Conducted limit (dBμV)			
Frequency of emission (MHz)	Quasi-peak	Average		
0.15-0.5	66 to 56*	56 to 46*		
0.5-5	56	46		
5-30	60	50		

^{*}Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.


3.6.3 Test Procedures

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 31 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

3.6.4 Test Setup



AMN = Artificial mains network (LISN)

AE = Associated equipment

EUT = Equipment under test

ISN = Impedance stabilization network

3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 32 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 33 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB41292344	N/A	Dec. 20, 2017	Feb. 14, 2018~	Dec. 19, 2018	Conducted
	-					Feb. 15, 2018		(TH05-HY)
Power Sensor	Agilent	E9327A	US40441548	50MHz~18GHz	Dec. 20, 2017	Feb. 14, 2018~ Feb. 15, 2018	Dec. 19, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2017	Feb. 14, 2018~ Feb. 15, 2018	Nov. 20, 2018	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Mar. 27, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Sep. 20, 2017	Mar. 27, 2018	Sep. 19, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Mar. 27, 2018	Nov. 29, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Dec. 08, 2017	Mar. 27, 2018	Dec. 07, 2018	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Mar. 27, 2018	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Mar. 27, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Mar. 27, 2018	Jan. 02, 2019	Conduction (CO05-HY)

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 34 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Amplifier	MITEQ	TTA1840- 35-HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Feb. 11, 2018~ Mar. 20, 2018	Jul. 17, 2018	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Nov. 10, 2016	Feb. 11, 2018~ Mar. 20, 2018	Nov. 09, 2018	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6-06	35414&AT-N0 602	30MHz~1GHz	Oct. 14, 2017	Feb. 11, 2018~ Mar. 20, 2018	Oct. 13, 2018	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Oct. 16, 2017	Feb. 11, 2018~ Mar. 20, 2018	Oct. 15, 2018	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 23, 2017	Feb. 11, 2018~ Mar. 20, 2018	Nov. 22, 2019	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 10, 2016	Feb. 11, 2018~ Mar. 20, 2018	Nov. 09, 2018	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz ~ 44GHz	Oct. 19, 2017	Feb. 11, 2018~ Mar. 20, 2018	Oct. 18, 2018	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Feb. 11, 2018~ Mar. 20, 2018	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Feb. 11, 2018~ Mar. 20, 2018	N/A	Radiation (03CH11-HY)
Preamplifier	MITEQ	AMF-7D-00101 800-30-10P	1590074	1GHz~18GHz	May 22, 2017	Feb. 11, 2018~ Mar. 20, 2018	May 21, 2018	Radiation (03CH11-HY)
Preamplifier	MITEQ	AMF-7D-00101 800	2025787	1GHz~18GHz	Feb. 13, 2017	Feb. 11, 2018~ Mar. 20, 2018	Feb. 12, 2019	Radiation (03CH11-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290053	20Hz to 26.5GHz	Jan. 16, 2018	Feb. 11, 2018~ Mar. 20, 2018	Jan. 15, 2019	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 27, 2017	Feb. 11, 2018~ Mar. 20, 2018	Nov. 26, 2018	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-001042	NA	NA	Feb. 11, 2018~ Mar. 20, 2018	NA	Radiation (03CH11-HY)

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 35 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report Template No.: BU5-FR15CBT4.0 Version 2.0

Report No.: FR811726A



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	2.70	
of 95% (U = 2Uc(y))		

<u>Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)</u>

Measuring Uncertainty for a Level of Confidence	5.20
of 95% (U = 2Uc(y))	5.20

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence	5.50
of 95% (U = 2Uc(y))	5.50

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

<u></u>	
Measuring Uncertainty for a Level of Confidence	5.20
of 95% (U = 2Uc(y))	5.20

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AG7G-B1A Page Number : 36 of 36
Report Issued Date : May 10, 2018
Report Version : Rev. 04

Report No.: FR811726A

Report Number : FR811726A

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Kai Liao	Temperature:	21~25	°C
Test Date:	2018/2/14-2/15	Relative Humidity:	51~54	%

TEST RESULTS DATA 6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.056	0.684	0.50	Pass
BLE	1Mbps	1	19	2440	1.062	0.700	0.50	Pass
BLE	1Mbps	1	39	2480	1.064	0.708	0.50	Pass

TEST RESULTS DATA

<u> </u>	<u>eak</u>	<u> </u>	<u>JWE</u>	er i	ap	<u>іе</u>
				_		

Mod.	Data Rate	N⊤x	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	0.12	30.00	0.50	0.62	36.00	Pass
BLE	1Mbps	1	19	2440	0.20	30.00	0.50	0.70	36.00	Pass
BLE	1Mbps	1	39	2480	0.04	30.00	0.50	0.54	36.00	Pass

TEST RESULTS DATA Average Power Table

_				_	_			_	 Ξ
							_		ī
	/E	2~	nn	4	in	\sim	$\boldsymbol{\cap}$	n	 ١
	T I	ľ	po	"	ш	ч	$\mathbf{\circ}$	ш	,

Мо	d.	Data Rate	3 1 3 1	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BL	E	1Mbps	1	0	2402	2.18	-0.76
BL	E	1Mbps	1	19	2440	2.18	-0.88
BL	E	1Mbps	1	39	2480	2.18	-0.99

TEST RESULTS DATA

Peak Power Density

Mod.	Data Rate	Ntx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	-1.34	-16.40	0.50	8.00	Pass
BLE	1Mbps	1	19	2440	-1.45	-16.58	0.50	8.00	Pass
BLE	1Mbps	1	39	2480	-1.50	-16.68	0.50	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Sharoof Vi	Temperature :	22~24 ℃
rest Engineer.	Shareer Tu	Relative Humidity :	58~62%

Report No. : FR811726A

SPORTON INTERNATIONAL INC. Page Number : B1 of I

EUT Information


 Report NO :
 811726

 Test Mode :
 Mode 1

 Test Voltage :
 120Vac/60Hz

Phase: Line

Full Spectrum




Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250		34.52	55.88	21.36	L1	OFF	19.5
0.152250	45.15		65.88	20.73	L1	OFF	19.5
0.165750	-	36.67	55.17	18.50	L1	OFF	19.5
0.165750	46.74		65.17	18.43	L1	OFF	19.5
0.183750	-	38.48	54.31	15.83	L1	OFF	19.5
0.183750	45.90		64.31	18.41	L1	OFF	19.5
0.208500		33.80	53.27	19.47	L1	OFF	19.5
0.208500	43.88		63.27	19.39	L1	OFF	19.5
0.278250		28.22	50.87	22.65	L1	OFF	19.5
0.278250	36.02		60.87	24.85	L1	OFF	19.5
0.633750	-	24.02	46.00	21.98	L1	OFF	19.5
0.633750	32.63		56.00	23.37	L1	OFF	19.5
0.694500		33.99	46.00	12.01	L1	OFF	19.5
0.694500	37.21		56.00	18.79	L1	OFF	19.5
1.855500		22.85	46.00	23.15	L1	OFF	19.6
1.855500	23.87		56.00	32.13	L1	OFF	19.6
6.105750	-	25.02	50.00	24.98	L1	OFF	19.6
6.105750	26.37		60.00	33.63	L1	OFF	19.6
18.096000		24.55	50.00	25.45	L1	OFF	19.8
18.096000	26.17		60.00	33.83	L1	OFF	19.8

EUT Information

Report NO: 811726
Test Mode: Mode 1
Test Voltage: 120Vac/60Hz
Phase: Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	46.42		65.88	19.46	N	OFF	19.5
0.152250		34.20	55.88	21.68	N	OFF	19.5
0.165750	48.57		65.17	16.60	N	OFF	19.5
0.165750		37.88	55.17	17.29	N	OFF	19.5
0.177000	46.18		64.63	18.45	N	OFF	19.5
0.177000		35.37	54.63	19.26	N	OFF	19.5
0.222000	41.15		62.74	21.59	N	OFF	19.5
0.222000		29.96	52.74	22.78	N	OFF	19.5
0.300750	41.31		60.22	18.91	N	OFF	19.5
0.300750		33.37	50.22	16.85	N	OFF	19.5
0.638250	34.98		56.00	21.02	N	OFF	19.5
0.638250		26.19	46.00	19.81	N	OFF	19.5
0.690000	38.37		56.00	17.63	N	OFF	19.5
0.690000		33.49	46.00	12.51	N	OFF	19.5
2.505750	24.49		56.00	31.51	N	OFF	19.5
2.505750		23.21	46.00	22.79	N	OFF	19.5
10.871250	26.79		60.00	33.21	N	OFF	19.7
10.871250		25.06	50.00	24.94	N	OFF	19.7

Appendix C. Radiated Spurious Emission

Test Engineer :		Temperature :	22~24°C
rest Engineer .	Ken Wu, Jacky Hung, and Hao Hsu	Relative Humidity :	48~52%

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dB _µ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		2389.8	56.44	-17.56	74	46.61	27.13	16.29	33.59	285	270	Р	Н
		2389.065	43.39	-10.61	54	33.57	27.13	16.29	33.6	285	270	Α	Н
	*	2402	92.39	-	-	82.56	27.13	16.29	33.59	285	270	Р	Н
	*	2402	90.51	-	-	80.68	27.13	16.29	33.59	285	270	Α	Н
BLE													Н
CH 00													Н
2402MHz		2341.5	52.29	-21.71	74	42.74	27	16.15	33.6	104	47	Р	V
2402WII 12		2386.545	43.25	-10.75	54	33.43	27.13	16.29	33.6	104	47	Α	V
	*	2402	86.36	-	-	76.53	27.13	16.29	33.59	104	47	Р	V
	*	2402	84.98	-	-	75.15	27.13	16.29	33.59	104	47	Α	V
													V
													٧
		2353.95	52.45	-21.55	74	42.86	27.04	16.15	33.6	274	273	Р	Н
		2348.85	43.1	-10.9	54	33.55	27	16.15	33.6	274	273	Α	Н
	*	2440	92.56	-	-	82.57	27.27	16.31	33.59	274	273	Р	Н
	*	2440	91.89	-	-	81.9	27.27	16.31	33.59	274	273	Α	Н
51.5		2487.92	52.8	-21.2	74	42.66	27.4	16.32	33.58	274	273	Р	Н
BLE CH 19		2497.84	43.54	-10.46	54	33.39	27.4	16.32	33.57	274	273	Α	Н
2440MHz		2368.5	53.06	-20.94	74	43.4	27.04	16.22	33.6	100	46	Р	٧
ZAAUIVINZ		2355	42.92	-11.08	54	33.26	27.04	16.22	33.6	100	46	Α	٧
	*	2440	86.27	-	-	76.28	27.27	16.31	33.59	100	46	Р	٧
	*	2440	84.94	-	-	74.95	27.27	16.31	33.59	100	46	Α	V
		2498.72	53.03	-20.97	74	42.88	27.4	16.32	33.57	100	46	Р	V
		2496.32	43.33	-10.67	54	33.18	27.4	16.32	33.57	100	46	Α	٧

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978



FCC RF Test Report

	*	2480	92.62	-	-	82.53	27.36	16.31	33.58	272	268	Р	Н
	*	2480	91.79	-	-	81.7	27.36	16.31	33.58	272	268	Α	Н
		2483.52	64.53	-9.47	74	54.44	27.36	16.31	33.58	272	268	Р	Н
		2483.6	47.68	-6.32	54	37.59	27.36	16.31	33.58	272	268	Α	Н
													Н
BLE													Н
CH 39 2480MHz	*	2480	85.16	-	-	75.07	27.36	16.31	33.58	100	54	Р	٧
2400WIF12	*	2480	83.75	-	-	73.66	27.36	16.31	33.58	100	54	Α	٧
		2483.52	59.9	-14.1	74	49.81	27.36	16.31	33.58	100	54	Р	V
		2483.52	43.84	-10.16	54	33.75	27.36	16.31	33.58	100	54	Α	V
					·								V
													V

TEL: 886-3-327-3456 FAX: 886-3-328-4978

^{1.} No other spurious found.

Remark

2. All results are PASS against Peak and Average limit line.

2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol
			ļ 	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)		(dBµV/m)	(dB _µ V)	(dB/m)	(dB)	(dB)	(cm)		(P/A)	
		4804	43.93	-30.07	74	67.39	31.26	10.03	64.75	100	0	Р	Н
													Н
BLE													Н
CH 00													Н
2402MHz		4804	41.09	-32.91	74	64.55	31.26	10.03	64.75	100	0	Р	V
													V
													V
													V
		4880	41.51	-32.49	74	64.84	31.38	9.99	64.7	100	0	Р	Н
		7320	44.66	-29.34	74	61.4	36.32	11.77	64.83	100	0	Р	Н
DI E													Н
BLE CH 19													Н
2440MHz		4880	40.14	-33.86	74	63.47	31.38	9.99	64.7	100	0	Р	V
2440111112		7320	43.87	-30.13	74	60.61	36.32	11.77	64.83	100	0	Р	V
													V
													V
		4960	41.3	-32.7	74	64.42	31.54	9.97	64.63	100	0	Р	Н
		7440	43.85	-30.15	74	60.42	36.59	11.72	64.88	100	0	Р	Н
51.5													Н
BLE													Н
CH 39 2480MHz		4960	39.81	-34.19	74	62.93	31.54	9.97	64.63	100	0	Р	V
∠+ovivi⊓Z		7440	42.3	-31.7	74	58.87	36.59	11.72	64.88	100	0	Р	V
													V
													V

Remark 2.

- No other spurious found.
- 2. All results are PASS against Peak and Average limit line.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number

: C3 of C6

Emission below 1GHz 2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)		(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	
		47.01	26.83	-13.17	40	42.99	15.31	1.02	32.49	-	-	Р	Н
		131.25	27.38	-16.12	43.5	40.95	17.32	1.56	32.45	-	-	Р	Н
		159.87	23.95	-19.55	43.5	38.39	16.28	1.71	32.43	-	-	Р	Н
		736.8	29.87	-16.13	46	31.1	27.6	3.53	32.36	-	-	Р	Н
		881	31.82	-14.18	46	30.59	29.1	3.89	31.76	-	-	Р	Н
		953.1	33.06	-12.94	46	29.4	30.76	4.07	31.17	100	0	Р	Н
													Н
													Τ
													Н
													Н
													Н
2.4GHz													Н
BLE LF		46.2	35.36	-4.64	40	51.11	15.72	1.02	32.49	100	0	Р	٧
LF		62.4	28.56	-11.44	40	48.42	11.59	1.04	32.49	-	-	Р	٧
		122.88	26.61	-16.89	43.5	40.26	17.26	1.55	32.46	-	-	Р	٧
		799.8	30.18	-15.82	46	30.54	28.13	3.69	32.18	-	-	Р	٧
		885.2	31.73	-14.27	46	30.51	29.07	3.89	31.74	-	-	Р	٧
		947.5	33.47	-12.53	46	30.25	30.46	3.99	31.23	-	-	Р	٧
													V
													٧
													٧
													V
													V
													V
					<u> </u>				1	1	<u> </u>	1	

Remark

1. No other spurious found.

2. All results are PASS against limit line.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number

: C4 of C6

Note symbol

Report No. : FR811726A

*	Fundamental Frequency which can be ignored. However, the level of any
	unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical

SPORTON INTERNATIONAL INC. Page Number : C5 of C6

A calculation example for radiated spurious emission is shown as below:

Report No.: FR811726A

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dB _µ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	Р	Н
CH 00													
2402MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	Α	Н

- 1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
- 2. Level($dB\mu V/m$) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dB μ V/m) – Limit Line(dB μ V/m)

For Peak Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 54.51(dB\mu V) 35.86 (dB)$
- $= 55.45 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level($dB\mu V/m$) Limit Line($dB\mu V/m$)
- $= 55.45(dB\mu V/m) 74(dB\mu V/m)$
- = -18.55(dB)

For Average Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 42.6(dB\mu V) 35.86 (dB)$
- $= 43.54 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level(dBµV/m) Limit Line(dBµV/m)
- $= 43.54(dB\mu V/m) 54(dB\mu V/m)$
- = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".

SPORTON INTERNATIONAL INC. Page Number : C6 of C6



Appendix D. Radiated Spurious Emission Plots

Test Engineer :		Temperature :	22~24°C
rest Engineer:	Ken Wu, Jacky Hung, and Hao Hsu	Relative Humidity :	48~52%

Report No. : FR811726A


Note symbol

-L	Low channel location
-R	High channel location


SPORTON INTERNATIONAL INC. Page Number : D1 of D13


2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)




TEL: 886-3-327-3456 FAX: 886-3-328-4978






BLE 2.4GHz 2400~2483.5MHz Band Edge @ 3m ANT BLE CH19 2440MHz - R 1 Horizontal **Fundamental** Left blank Peak Left blank Avg.


TEL: 886-3-327-3456 FAX: 886-3-328-4978



BLE 2.4GHz 2400~2483.5MHz Band Edge @ 3m ANT BLE CH19 2440MHz - R 1 Vertical **Fundamental** Left blank Peak Left blank Avg.


TEL: 886-3-327-3456 FAX: 886-3-328-4978






2.4GHz 2400~2483.5MHz


BLE (Harmonic @ 3m)




TEL: 886-3-327-3456 FAX: 886-3-328-4978







Emission below 1GHz 2.4GHz BLE (LF)




TEL: 886-3-327-3456 FAX: 886-3-328-4978



Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
Bluetooth – LE	60.51	380	2.63	3kHz	2.18

Bluetooth - LE



Date: 14.FEB.2018 22:02:28

TEL: 886-3-327-3456 FAX: 886-3-328-4978