


Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT40 5310 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5350.000	42.78	1.02	43.80	54.00	-10.20	AVG
2	5351.760	42.54	1.03	43.57	54.00	-10.43	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT40 5510 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5457.760	39.14	1.75	40.89	54.00	-13.11	AVG
2	5460.000	39.02	1.75	40.77	54.00	-13.23	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT40 5510 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5458.960	40.86	1.75	42.61	54.00	-11.39	AVG
2*	5460.000	40.88	1.75	42.63	54.00	-11.37	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT40 5550 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5454.640	38.68	1.75	40.43	54.00	-13.57	AVG
2	5460.000	38.55	1.75	40.30	54.00	-13.70	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT40 5550 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5458.720	39.83	1.75	41.58	54.00	-12.42	AVG
2	5460.000	39.69	1.75	41.44	54.00	-12.56	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT40 5710 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5456.250	38.26	1.75	40.01	54.00	-13.99	AVG
2	5460.000	38.25	1.75	40.00	54.00	-14.00	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT40 5710 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5458.750	38.94	1.75	40.69	54.00	-13.31	AVG
2	5460.000	38.94	1.75	40.69	54.00	-13.31	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT80 5210 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5149.040	43.94	1.38	45.32	54.00	-8.68	AVG
2*	5150.000	44.39	1.38	45.77	54.00	-8.23	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT80 5210 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5149.040	44.63	1.38	46.01	54.00	-7.99	AVG
2*	5150.000	45.57	1.38	46.95	54.00	-7.05	AVG

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11ac VHT80 5290 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	42.23	1.02	43.25	54.00	-10.75	AVG
2*	5350.320	42.33	1.02	43.35	54.00	-10.65	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT80 5290 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5350.000	43.16	1.02	44.18	54.00	-9.82	AVG
2	5350.320	43.08	1.02	44.10	54.00	-9.90	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT80 5530 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5457.520	40.36	1.75	42.11	54.00	-11.89	AVG
2	5460.000	40.30	1.75	42.05	54.00	-11.95	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT80 5530 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5458.480	43.08	1.75	44.83	54.00	-9.17	AVG
2*	5460.000	43.09	1.75	44.84	54.00	-9.16	AVG

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11ac VHT80 5610 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5456.250	38.76	1.75	40.51	54.00	-13.49	AVG
2*	5460.000	38.81	1.75	40.56	54.00	-13.44	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT80 5610 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5457.525	39.89	1.75	41.64	54.00	-12.36	AVG
2*	5460.000	39.96	1.75	41.71	54.00	-12.29	AVG

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11ac VHT80 5690 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5448.750	38.50	1.73	40.23	54.00	-13.77	AVG
2*	5460.000	38.49	1.75	40.24	54.00	-13.76	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT80 5690 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5457.500	39.34	1.75	41.09	54.00	-12.91	AVG
2*	5460.000	39.39	1.75	41.14	54.00	-12.86	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT160 5250 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5147.040	45.32	1.39	46.71	54.00	-7.29	AVG
2*	5150.000	45.60	1.38	46.98	54.00	-7.02	AVG
3	5350.000	43.16	1.02	44.18	54.00	-9.82	AVG
4	5354.400	43.20	1.06	44.26	54.00	-9.74	AVG

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT160 5250 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.080	46.77	1.39	48.16	54.00	-5.84	AVG
2*	5150.000	47.02	1.38	48.40	54.00	-5.60	AVG
3	5350.000	43.77	1.02	44.79	54.00	-9.21	AVG
4	5366.880	44.08	1.14	45.22	54.00	-8.78	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT160 5570 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5450.725	41.36	1.74	43.10	54.00	-10.90	AVG
2	5460.000	41.30	1.75	43.05	54.00	-10.95	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT160 5570 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5450.300	43.49	1.74	45.23	54.00	-8.77	AVG
2*	5460.000	43.59	1.75	45.34	54.00	-8.66	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT20 5180 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5149.040	43.40	1.38	44.78	54.00	-9.22	AVG
2	5150.000	42.87	1.38	44.25	54.00	-9.75	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11be EHT20 5180 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5148.280	45.32	1.38	46.70	54.00	-7.30	AVG
2	5150.000	45.10	1.38	46.48	54.00	-7.52	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT20 5200 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5148.280	41.13	1.38	42.51	54.00	-11.49	AVG
2	5150.000	41.07	1.38	42.45	54.00	-11.55	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11be EHT20 5200 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5146.000	42.51	1.39	43.90	54.00	-10.10	AVG
2	5150.000	42.38	1.38	43.76	54.00	-10.24	AVG

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT20 5240 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5146.760	40.38	1.39	41.77	54.00	-12.23	AVG
2	5150.000	40.25	1.38	41.63	54.00	-12.37	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5240 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5145.240	41.06	1.38	42.44	54.00	-11.56	AVG
2	5150.000	40.78	1.38	42.16	54.00	-11.84	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT20 5260 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	37.95	1.02	38.97	54.00	-15.03	AVG
2*	5439.120	38.06	1.66	39.72	54.00	-14.28	AVG

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT20 5260 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	38.83	1.02	39.85	54.00	-14.15	AVG
2*	5353.440	39.34	1.04	40.38	54.00	-13.62	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT20 5280 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	38.32	1.02	39.34	54.00	-14.66	AVG
2*	5457.840	37.96	1.75	39.71	54.00	-14.29	AVG

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT20 5280 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5350.000	39.46	1.02	40.48	54.00	-13.52	AVG
2	5353.200	39.35	1.04	40.39	54.00	-13.61	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT20 5320 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5350.000	41.17	1.02	42.19	54.00	-11.81	AVG
2	5350.320	41.15	1.02	42.17	54.00	-11.83	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11be EHT20 5320 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	41.61	1.02	42.63	54.00	-11.37	AVG
2*	5351.760	41.68	1.03	42.71	54.00	-11.29	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT20 5500 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5452.480	39.45	1.75	41.20	54.00	-12.80	AVG
2	5460.000	39.33	1.75	41.08	54.00	-12.92	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5500 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5458.480	40.00	1.75	41.75	54.00	-12.25	AVG
2	5460.000	39.76	1.75	41.51	54.00	-12.49	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT20 5560 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5449.600	38.49	1.74	40.23	54.00	-13.77	AVG
2	5460.000	38.25	1.75	40.00	54.00	-14.00	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5560 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5445.280	38.65	1.70	40.35	54.00	-13.65	AVG
2	5460.000	38.35	1.75	40.10	54.00	-13.90	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT40 5190 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5143.720	41.96	1.38	43.34	54.00	-10.66	AVG
2	5150.000	41.94	1.38	43.32	54.00	-10.68	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11be EHT40 5190 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5146.760	42.81	1.39	44.20	54.00	-9.80	AVG
2	5150.000	42.82	1.38	44.20	54.00	-9.80	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT40 5230 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5142.960	41.29	1.38	42.67	54.00	-11.33	AVG
2	5150.000	41.10	1.38	42.48	54.00	-11.52	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT40 5230 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5145.240	41.75	1.38	43.13	54.00	-10.87	AVG
2	5150.000	41.75	1.38	43.13	54.00	-10.87	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT40 5270 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5350.000	40.03	1.02	41.05	54.00	-12.95	AVG
2	5352.960	40.01	1.04	41.05	54.00	-12.95	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11be EHT40 5270 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	40.23	1.02	41.25	54.00	-12.75	AVG
2*	5354.880	40.47	1.06	41.53	54.00	-12.47	AVG

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT40 5310 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	42.08	1.02	43.10	54.00	-10.90	AVG
2*	5350.320	42.21	1.02	43.23	54.00	-10.77	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT40 5310 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5350.000	42.31	1.02	43.33	54.00	-10.67	AVG
2	5350.560	42.28	1.02	43.30	54.00	-10.70	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT40 5510 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5459.200	39.16	1.75	40.91	54.00	-13.09	AVG
2	5460.000	39.15	1.75	40.90	54.00	-13.10	AVG

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT40 5510 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5458.960	39.65	1.75	41.40	54.00	-12.60	AVG
2	5460.000	39.53	1.75	41.28	54.00	-12.72	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT40 5550 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5455.840	38.80	1.75	40.55	54.00	-13.45	AVG
2	5460.000	38.78	1.75	40.53	54.00	-13.47	AVG

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT40 5550 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5448.640	39.13	1.73	40.86	54.00	-13.14	AVG
2	5460.000	39.08	1.75	40.83	54.00	-13.17	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT80 5210 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5149.040	44.26	1.38	45.64	54.00	-8.36	AVG
2*	5150.000	44.27	1.38	45.65	54.00	-8.35	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11be EHT80 5210 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5148.280	45.11	1.38	46.49	54.00	-7.51	AVG
2*	5150.000	45.37	1.38	46.75	54.00	-7.25	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT80 5290 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	43.08	1.02	44.10	54.00	-9.90	AVG
2*	5353.200	43.12	1.04	44.16	54.00	-9.84	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT80 5290 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	43.94	1.02	44.96	54.00	-9.04	AVG
2*	5351.040	44.33	1.03	45.36	54.00	-8.64	AVG

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT80 5530 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5457.520	41.14	1.75	42.89	54.00	-11.11	AVG
2	5460.000	40.91	1.75	42.66	54.00	-11.34	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT80 5530 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5459.440	42.26	1.75	44.01	54.00	-9.99	AVG
2	5460.000	42.07	1.75	43.82	54.00	-10.18	AVG

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT160 5250 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5142.240	45.27	1.39	46.66	54.00	-7.34	AVG
2	5150.000	45.11	1.38	46.49	54.00	-7.51	AVG
3	5350.000	42.63	1.02	43.65	54.00	-10.35	AVG
4	5353.440	42.76	1.04	43.80	54.00	-10.20	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT160 5250 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5145.120	46.76	1.38	48.14	54.00	-5.86	AVG
2*	5150.000	46.87	1.38	48.25	54.00	-5.75	AVG
3	5350.000	43.83	1.02	44.85	54.00	-9.15	AVG
4	5358.240	44.19	1.08	45.27	54.00	-8.73	AVG

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT160 5570 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5429.050	41.81	1.59	43.40	54.00	-10.60	AVG
2	5460.000	40.99	1.75	42.74	54.00	-11.26	AVG

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11be EHT160 5570 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5429.900	42.76	1.60	44.36	54.00	-9.64	AVG
2	5460.000	42.08	1.75	43.83	54.00	-10.17	AVG

3X3


Below 1 GHz

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11ac VHT40 5190 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	187.1400	43.18	-8.50	34.68	43.50	-8.82	QP
2	227.8800	43.64	-8.44	35.20	46.00	-10.80	QP
3	284.1400	37.32	-5.80	31.52	46.00	-14.48	QP
4	310.3300	38.71	-5.27	33.44	46.00	-12.56	QP
5	575.1400	32.53	-0.43	32.10	46.00	-13.90	QP
6	656.6200	31.01	0.97	31.98	46.00	-14.02	QP

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT40 5190 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	182.2900	41.76	-8.10	33.66	43.50	-9.84	QP
2	230.7900	40.24	-8.22	32.02	46.00	-13.98	QP
3	283.1700	34.52	-5.84	28.68	46.00	-17.32	QP
4	540.2200	35.32	-1.28	34.04	46.00	-11.96	QP
5*	568.3500	37.24	-0.59	36.65	46.00	-9.35	QP
6	642.0700	32.32	0.73	33.05	46.00	-12.95	QP

Harmonic


Above 1 GHz

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5180 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10360.000	32.60	13.36	45.96	68.20	-22.24	peak
2	15540.000	31.37	16.77	48.14	74.00	-25.86	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11a 5180 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10360.000	32.70	13.36	46.06	68.20	-22.14	peak
2	15540.000	30.84	16.77	47.61	74.00	-26.39	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11a 5200 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10400.000	32.51	13.51	46.02	68.20	-22.18	peak
2	15600.000	31.81	16.66	48.47	74.00	-25.53	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11a 5200 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10400.000	32.69	13.51	46.20	68.20	-22.00	peak
2	15600.000	32.20	16.66	48.86	74.00	-25.14	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11a 5240 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10480.000	32.86	13.58	46.44	68.20	-21.76	peak
2	15720.000	31.75	16.57	48.32	74.00	-25.68	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11a 5240 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10480.000	33.99	13.58	47.57	68.20	-20.63	peak
2	15720.000	30.84	16.57	47.41	74.00	-26.59	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11a 5260 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10520.000	32.56	13.61	46.17	68.20	-22.03	peak
2	15780.000	30.54	16.52	47.06	74.00	-26.94	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5260 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10520.000	33.03	13.61	46.64	68.20	-21.56	peak
2	15780.000	31.26	16.52	47.78	74.00	-26.22	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11a 5280 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10560.000	33.29	13.63	46.92	68.20	-21.28	peak
2	15840.000	30.21	16.40	46.61	74.00	-27.39	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11a 5280 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10560.000	32.95	13.63	46.58	68.20	-21.62	peak
2	15840.000	30.69	16.40	47.09	74.00	-26.91	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11a 5320 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10640.000	32.77	13.70	46.47	74.00	-27.53	peak
2*	15960.000	30.56	16.06	46.62	74.00	-27.38	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5320 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10640.000	32.48	13.70	46.18	74.00	-27.82	peak
2*	15960.000	31.17	16.06	47.23	74.00	-26.77	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11a 5500 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11000.000	33.26	14.30	47.56	74.00	-26.44	peak
2*	16500.000	30.14	16.69	46.83	68.20	-21.37	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5500 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11000.000	32.61	14.30	46.91	74.00	-27.09	peak
2*	16500.000	31.10	16.69	47.79	68.20	-20.41	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11a 5560 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11120.000	32.57	14.52	47.09	74.00	-26.91	peak
2*	16680.000	30.28	17.91	48.19	68.20	-20.01	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11a 5560 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11120.000	33.34	14.52	47.86	74.00	-26.14	peak
2*	16680.000	30.89	17.91	48.80	68.20	-19.40	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5700 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11400.000	33.89	14.66	48.55	74.00	-25.45	peak
2*	17100.000	31.76	20.57	52.33	68.20	-15.87	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11a 5700 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11400.000	32.90	14.66	47.56	74.00	-26.44	peak
2*	17100.000	30.28	20.57	50.85	68.20	-17.35	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11a 5720 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11440.000	33.84	14.84	48.68	74.00	-25.32	peak
2*	17160.000	30.98	20.96	51.94	68.20	-16.26	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5720 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11440.000	32.39	14.84	47.23	74.00	-26.77	peak
2*	17160.000	31.16	20.96	52.12	68.20	-16.08	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11a 5745 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11490.000	33.44	15.07	48.51	74.00	-25.49	peak
2*	17235.000	31.17	21.53	52.70	68.20	-15.50	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5745 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11490.000	34.56	15.07	49.63	74.00	-24.37	peak
2*	17235.000	29.94	21.53	51.47	68.20	-16.73	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5785 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11570.000	32.48	14.84	47.32	74.00	-26.68	peak
2*	17355.000	30.85	22.35	53.20	68.20	-15.00	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11a 5785 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11570.000	33.60	14.84	48.44	74.00	-25.56	peak
2*	17355.000	30.57	22.35	52.92	68.20	-15.28	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5825 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11650.000	32.98	14.56	47.54	74.00	-26.46	peak
2*	17475.000	30.40	23.20	53.60	68.20	-14.60	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5825 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11650.000	33.62	14.56	48.18	74.00	-25.82	peak
2*	17475.000	30.01	23.20	53.21	68.20	-14.99	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT20 5180 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10360.000	32.86	13.36	46.22	68.20	-21.98	peak
2	15540.000	31.24	16.77	48.01	74.00	-25.99	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT20 5180 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10360.000	33.28	13.36	46.64	68.20	-21.56	peak
2	15540.000	31.66	16.77	48.43	74.00	-25.57	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11ac VHT20 5200 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10400.000	33.46	13.51	46.97	68.20	-21.23	peak
2	15600.000	30.84	16.66	47.50	74.00	-26.50	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT20 5200 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10400.000	32.68	13.51	46.19	68.20	-22.01	peak
2	15600.000	31.89	16.66	48.55	74.00	-25.45	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT20 5240 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10480.000	33.01	13.58	46.59	68.20	-21.61	peak
2	15720.000	31.31	16.57	47.88	74.00	-26.12	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT20 5240 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10480.000	33.01	13.58	46.59	68.20	-21.61	peak
2	15720.000	31.32	16.57	47.89	74.00	-26.11	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11ac VHT20 5260 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10520.000	33.47	13.61	47.08	68.20	-21.12	peak
2	15780.000	31.48	16.52	48.00	74.00	-26.00	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT20 5260 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10520.000	32.96	13.61	46.57	68.20	-21.63	peak
2	15780.000	30.95	16.52	47.47	74.00	-26.53	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11ac VHT20 5280 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10560.000	34.08	13.63	47.71	68.20	-20.49	peak
2	15840.000	30.69	16.40	47.09	74.00	-26.91	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT20 5280 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10560.000	33.21	13.63	46.84	68.20	-21.36	peak
2	15840.000	31.13	16.40	47.53	74.00	-26.47	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11ac VHT20 5320 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10640.000	35.16	13.70	48.86	74.00	-25.14	peak
2	15960.000	29.71	16.06	45.77	74.00	-28.23	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT20 5320 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10640.000	33.39	13.70	47.09	74.00	-26.91	peak
2*	15960.000	31.99	16.06	48.05	74.00	-25.95	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11ac VHT20 5500 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11000.000	33.41	14.30	47.71	74.00	-26.29	peak
2*	16500.000	31.15	16.69	47.84	68.20	-20.36	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT20 5500 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11000.000	33.98	14.30	48.28	74.00	-25.72	peak
2*	16500.000	31.01	16.69	47.70	68.20	-20.50	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11ac VHT20 5560 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11120.000	33.38	14.52	47.90	74.00	-26.10	peak
2*	16680.000	31.60	17.91	49.51	68.20	-18.69	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT20 5560 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11120.000	32.45	14.52	46.97	74.00	-27.03	peak
2*	16680.000	32.22	17.91	50.13	68.20	-18.07	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT20 5700 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11400.000	33.35	14.66	48.01	74.00	-25.99	peak
2*	17100.000	31.20	20.57	51.77	68.20	-16.43	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11ac VHT20 5700 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11400.000	32.65	14.66	47.31	74.00	-26.69	peak
2*	17100.000	31.09	20.57	51.66	68.20	-16.54	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11ac VHT20 5720 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11440.000	32.25	14.84	47.09	74.00	-26.91	peak
2*	17160.000	31.12	20.96	52.08	68.20	-16.12	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT20 5720 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11440.000	32.47	14.84	47.31	74.00	-26.69	peak
2*	17160.000	31.49	20.96	52.45	68.20	-15.75	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT20 5745 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11490.000	32.53	15.07	47.60	74.00	-26.40	peak
2*	17235.000	29.89	21.53	51.42	68.20	-16.78	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT20 5745 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11490.000	34.44	15.07	49.51	74.00	-24.49	peak
2*	17235.000	30.38	21.53	51.91	68.20	-16.29	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT20 5785 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11570.000	33.49	14.84	48.33	74.00	-25.67	peak
2*	17355.000	30.25	22.35	52.60	68.20	-15.60	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT20 5785 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11570.000	33.21	14.84	48.05	74.00	-25.95	peak
2*	17355.000	30.13	22.35	52.48	68.20	-15.72	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11ac VHT20 5825 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11650.000	33.23	14.56	47.79	74.00	-26.21	peak
2*	17475.000	31.10	23.20	54.30	68.20	-13.90	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT20 5825 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11650.000	33.74	14.56	48.30	74.00	-25.70	peak
2*	17475.000	30.46	23.20	53.66	68.20	-14.54	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT40 5190 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10380.000	33.94	13.44	47.38	68.20	-20.82	peak
2	15570.000	31.49	16.72	48.21	74.00	-25.79	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT40 5190 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10380.000	33.39	13.44	46.83	68.20	-21.37	peak
2	15570.000	31.98	16.72	48.70	74.00	-25.30	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT40 5230 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10460.000	33.82	13.57	47.39	68.20	-20.81	peak
2	15690.000	32.09	16.59	48.68	74.00	-25.32	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT40 5230 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10460.000	32.46	13.57	46.03	68.20	-22.17	peak
2	15690.000	31.21	16.59	47.80	74.00	-26.20	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11ac VHT40 5270 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10540.000	35.64	13.61	49.25	68.20	-18.95	peak
2	15810.000	31.09	16.48	47.57	74.00	-26.43	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11ac VHT40 5270 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10540.000	32.45	13.61	46.06	68.20	-22.14	peak
2	15810.000	30.47	16.48	46.95	74.00	-27.05	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11ac VHT40 5310 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10620.000	33.53	13.66	47.19	74.00	-26.81	peak
2*	15930.000	31.46	16.15	47.61	74.00	-26.39	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT40 5310 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10620.000	32.58	13.66	46.24	74.00	-27.76	peak
2	15930.000	29.93	16.15	46.08	74.00	-27.92	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT40 5510 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11020.000	32.38	14.35	46.73	74.00	-27.27	peak
2*	16530.000	32.47	16.91	49.38	68.20	-18.82	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11ac VHT40 5510 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11020.000	32.64	14.35	46.99	74.00	-27.01	peak
2*	16530.000	30.54	16.91	47.45	68.20	-20.75	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT40 5550 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11100.000	31.97	14.56	46.53	74.00	-27.47	peak
2*	16650.000	31.37	17.73	49.10	68.20	-19.10	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT40 5550 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11100.000	34.26	14.56	48.82	74.00	-25.18	peak
2*	16650.000	30.48	17.73	48.21	68.20	-19.99	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT40 5670 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11340.000	32.65	14.50	47.15	74.00	-26.85	peak
2*	17010.000	29.69	20.06	49.75	68.20	-18.45	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11ac VHT40 5670 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11340.000	33.74	14.50	48.24	74.00	-25.76	peak
2*	17010.000	30.12	20.06	50.18	68.20	-18.02	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT40 5710 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11420.000	33.05	14.75	47.80	74.00	-26.20	peak
2*	17130.000	30.39	20.77	51.16	68.20	-17.04	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT40 5710 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11420.000	32.85	14.75	47.60	74.00	-26.40	peak
2*	17130.000	29.83	20.77	50.60	68.20	-17.60	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT40 5755 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11510.000	33.86	15.09	48.95	74.00	-25.05	peak
2*	17265.000	30.91	21.79	52.70	68.20	-15.50	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT40 5755 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11510.000	32.67	15.09	47.76	74.00	-26.24	peak
2*	17265.000	31.43	21.79	53.22	68.20	-14.98	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11ac VHT40 5795 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11590.000	32.46	14.76	47.22	74.00	-26.78	peak
2*	17385.000	30.18	22.48	52.66	68.20	-15.54	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT40 5795 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11590.000	33.08	14.76	47.84	74.00	-26.16	peak
2*	17385.000	30.72	22.48	53.20	68.20	-15.00	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11ac VHT80 5210 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10420.000	34.57	13.53	48.10	68.20	-20.10	peak
2	15630.000	32.91	16.64	49.55	74.00	-24.45	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT80 5210 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10420.000	34.07	13.53	47.60	68.20	-20.60	peak
2	15630.000	32.50	16.64	49.14	74.00	-24.86	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT80 5290 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10580.000	33.30	13.63	46.93	68.20	-21.27	peak
2	15870.000	30.59	16.31	46.90	74.00	-27.10	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT80 5290 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10580.000	32.71	13.63	46.34	68.20	-21.86	peak
2	15870.000	31.35	16.31	47.66	74.00	-26.34	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT80 5530 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11060.000	33.04	14.46	47.50	74.00	-26.50	peak
2*	16590.000	31.38	17.34	48.72	68.20	-19.48	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT80 5530 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11060.000	33.05	14.46	47.51	74.00	-26.49	peak
2*	16590.000	32.03	17.34	49.37	68.20	-18.83	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT80 5610 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11220.000	33.05	14.34	47.39	74.00	-26.61	peak
2*	16830.000	32.00	19.08	51.08	68.20	-17.12	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT80 5610 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11220.000	34.04	14.34	48.38	74.00	-25.62	peak
2*	16830.000	29.51	19.08	48.59	68.20	-19.61	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT80 5690 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11380.000	32.68	14.60	47.28	74.00	-26.72	peak
2*	17070.000	30.95	20.40	51.35	68.20	-16.85	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT80 5690 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11380.000	32.42	14.60	47.02	74.00	-26.98	peak
2*	17070.000	30.56	20.40	50.96	68.20	-17.24	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT80 5775 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11550.000	33.71	14.92	48.63	74.00	-25.37	peak
2*	17325.000	30.94	22.20	53.14	68.20	-15.06	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT80 5775 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11550.000	32.22	14.92	47.14	74.00	-26.86	peak
2*	17325.000	30.78	22.20	52.98	68.20	-15.22	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11ac VHT160 5250 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10500.000	31.16	13.60	44.76	68.20	-23.44	peak
2	15750.000	32.45	16.55	49.00	74.00	-25.00	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT160 5250 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10500.000	33.13	13.60	46.73	68.20	-21.47	peak
2	15750.000	31.21	16.55	47.76	74.00	-26.24	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT160 5570 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11140.000	33.26	14.47	47.73	74.00	-26.27	peak
2*	16710.000	31.33	18.12	49.45	68.20	-18.75	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11ac VHT160 5570 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11140.000	32.06	14.47	46.53	74.00	-27.47	peak
2*	16710.000	31.11	18.12	49.23	68.20	-18.97	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT20 5180 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10360.000	32.73	13.36	46.09	68.20	-22.11	peak
2	15540.000	33.41	16.77	50.18	74.00	-23.82	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5180 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10360.000	32.95	13.36	46.31	68.20	-21.89	peak
2	15540.000	32.30	16.77	49.07	74.00	-24.93	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11be EHT20 5200 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10400.000	32.76	13.51	46.27	68.20	-21.93	peak
2	15600.000	33.45	16.66	50.11	74.00	-23.89	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT20 5200 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10400.000	31.61	13.51	45.12	68.20	-23.08	peak
2	15600.000	33.91	16.66	50.57	74.00	-23.43	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT20 5240 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10480.000	33.51	13.58	47.09	68.20	-21.11	peak
2	15720.000	33.46	16.57	50.03	74.00	-23.97	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11be EHT20 5240 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10480.000	32.29	13.58	45.87	68.20	-22.33	peak
2	15720.000	32.19	16.57	48.76	74.00	-25.24	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT20 5260 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10520.000	33.50	13.61	47.11	68.20	-21.09	peak
2	15780.000	32.13	16.52	48.65	74.00	-25.35	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5260 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10520.000	33.33	13.61	46.94	68.20	-21.26	peak
2	15780.000	33.96	16.52	50.48	74.00	-23.52	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT20 5280 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10560.000	32.06	13.63	45.69	68.20	-22.51	peak
2	15840.000	32.65	16.40	49.05	74.00	-24.95	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11be EHT20 5280 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10560.000	33.69	13.63	47.32	68.20	-20.88	peak
2	15840.000	33.55	16.40	49.95	74.00	-24.05	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT20 5320 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10640.000	32.48	13.70	46.18	74.00	-27.82	peak
2*	15960.000	33.34	16.06	49.40	74.00	-24.60	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5320 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10640.000	32.59	13.70	46.29	74.00	-27.71	peak
2*	15960.000	33.02	16.06	49.08	74.00	-24.92	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT20 5500 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11000.000	34.04	14.30	48.34	74.00	-25.66	peak
2*	16500.000	31.76	16.69	48.45	68.20	-19.75	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5500 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11000.000	32.78	14.30	47.08	74.00	-26.92	peak
2*	16500.000	32.36	16.69	49.05	68.20	-19.15	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11be EHT20 5560 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11120.000	34.53	14.52	49.05	74.00	-24.95	peak
2*	16680.000	33.47	17.91	51.38	68.20	-16.82	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11be EHT20 5560 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11120.000	33.35	14.52	47.87	74.00	-26.13	peak
2*	16680.000	32.55	17.91	50.46	68.20	-17.74	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11be EHT20 5700 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11400.000	32.70	14.66	47.36	74.00	-26.64	peak
2*	17100.000	33.11	20.57	53.68	68.20	-14.52	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11be EHT20 5700 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11400.000	33.07	14.66	47.73	74.00	-26.27	peak
2*	17100.000	32.75	20.57	53.32	68.20	-14.88	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT20 5720 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11440.000	32.46	14.84	47.30	74.00	-26.70	peak
2*	17160.000	32.37	20.96	53.33	68.20	-14.87	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5720 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11440.000	33.34	14.84	48.18	74.00	-25.82	peak
2*	17160.000	33.17	20.96	54.13	68.20	-14.07	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT20 5745 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11490.000	33.81	15.07	48.88	74.00	-25.12	peak
2*	17235.000	31.80	21.53	53.33	68.20	-14.87	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5745 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11490.000	33.01	15.07	48.08	74.00	-25.92	peak
2*	17235.000	32.03	21.53	53.56	68.20	-14.64	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT20 5785 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11570.000	34.97	14.84	49.81	74.00	-24.19	peak
2*	17355.000	32.66	22.35	55.01	68.20	-13.19	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5785 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11570.000	34.22	14.84	49.06	74.00	-24.94	peak
2*	17355.000	33.29	22.35	55.64	68.20	-12.56	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT20 5825 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11650.000	33.46	14.56	48.02	74.00	-25.98	peak
2*	17475.000	33.09	23.20	56.29	68.20	-11.91	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT20 5825 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11650.000	32.76	14.56	47.32	74.00	-26.68	peak
2*	17475.000	32.03	23.20	55.23	68.20	-12.97	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT40 5190 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10380.000	32.87	13.44	46.31	68.20	-21.89	peak
2	15570.000	33.06	16.72	49.78	74.00	-24.22	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT40 5190 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10380.000	33.91	13.44	47.35	68.20	-20.85	peak
2	15570.000	32.70	16.72	49.42	74.00	-24.58	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT40 5230 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10460.000	33.36	13.57	46.93	68.20	-21.27	peak
2	15690.000	34.07	16.59	50.66	74.00	-23.34	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT40 5230 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10460.000	34.25	13.57	47.82	68.20	-20.38	peak
2	15690.000	33.53	16.59	50.12	74.00	-23.88	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT40 5270 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10540.000	34.41	13.61	48.02	68.20	-20.18	peak
2	15810.000	33.07	16.48	49.55	74.00	-24.45	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT40 5270 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10540.000	32.26	13.61	45.87	68.20	-22.33	peak
2	15810.000	33.34	16.48	49.82	74.00	-24.18	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT40 5310 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10620.000	32.48	13.66	46.14	74.00	-27.86	peak
2*	15930.000	33.75	16.15	49.90	74.00	-24.10	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT40 5310 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10620.000	34.81	13.66	48.47	74.00	-25.53	peak
2*	15930.000	32.84	16.15	48.99	74.00	-25.01	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11be EHT40 5510 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11020.000	34.06	14.35	48.41	74.00	-25.59	peak
2*	16530.000	31.36	16.91	48.27	68.20	-19.93	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11be EHT40 5510 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11020.000	33.65	14.35	48.00	74.00	-26.00	peak
2*	16530.000	32.46	16.91	49.37	68.20	-18.83	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11be EHT40 5550 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11100.000	33.04	14.56	47.60	74.00	-26.40	peak
2*	16650.000	32.85	17.73	50.58	68.20	-17.62	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT40 5550 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11100.000	33.53	14.56	48.09	74.00	-25.91	peak
2*	16650.000	33.26	17.73	50.99	68.20	-17.21	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT40 5670 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11340.000	34.96	14.50	49.46	74.00	-24.54	peak
2*	17010.000	33.88	20.06	53.94	68.20	-14.26	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT40 5670 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11340.000	34.01	14.50	48.51	74.00	-25.49	peak
2*	17010.000	33.24	20.06	53.30	68.20	-14.90	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT40 5710 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11420.000	33.69	14.75	48.44	74.00	-25.56	peak
2*	17130.000	33.02	20.77	53.79	68.20	-14.41	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT40 5710 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11420.000	35.89	14.75	50.64	74.00	-23.36	peak
2*	17130.000	32.27	20.77	53.04	68.20	-15.16	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT40 5755 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11510.000	33.87	15.09	48.96	74.00	-25.04	peak
2*	17265.000	31.55	21.79	53.34	68.20	-14.86	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT40 5755 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11510.000	33.80	15.09	48.89	74.00	-25.11	peak
2*	17265.000	31.88	21.79	53.67	68.20	-14.53	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT40 5795 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11590.000	34.10	14.76	48.86	74.00	-25.14	peak
2*	17385.000	31.23	22.48	53.71	68.20	-14.49	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11be EHT40 5795 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11590.000	34.29	14.76	49.05	74.00	-24.95	peak
2*	17385.000	31.58	22.48	54.06	68.20	-14.14	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT80 5210 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10420.000	33.42	13.53	46.95	68.20	-21.25	peak
2	15630.000	32.64	16.64	49.28	74.00	-24.72	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT80 5210 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10420.000	32.88	13.53	46.41	68.20	-21.79	peak
2	15630.000	33.91	16.64	50.55	74.00	-23.45	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11be EHT80 5290 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10580.000	33.23	13.63	46.86	68.20	-21.34	peak
2	15870.000	32.09	16.31	48.40	74.00	-25.60	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT80 5290 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10580.000	33.08	13.63	46.71	68.20	-21.49	peak
2	15870.000	32.55	16.31	48.86	74.00	-25.14	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT80 5530 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11060.000	34.98	14.46	49.44	74.00	-24.56	peak
2*	16590.000	32.68	17.34	50.02	68.20	-18.18	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT80 5530 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11060.000	35.07	14.46	49.53	74.00	-24.47	peak
2*	16590.000	33.02	17.34	50.36	68.20	-17.84	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT80 5610 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11220.000	34.33	14.34	48.67	74.00	-25.33	peak
2*	16830.000	34.61	19.08	53.69	68.20	-14.51	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT80 5610 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11220.000	33.90	14.34	48.24	74.00	-25.76	peak
2*	16830.000	33.29	19.08	52.37	68.20	-15.83	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT80 5690 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11380.000	33.94	14.60	48.54	74.00	-25.46	peak
2*	17070.000	32.66	20.40	53.06	68.20	-15.14	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT80 5690 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11380.000	33.85	14.60	48.45	74.00	-25.55	peak
2*	17070.000	34.02	20.40	54.42	68.20	-13.78	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT80 5775 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11550.000	33.66	14.92	48.58	74.00	-25.42	peak
2*	17325.000	32.70	22.20	54.90	68.20	-13.30	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT80 5775 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11550.000	33.42	14.92	48.34	74.00	-25.66	peak
2*	17325.000	31.71	22.20	53.91	68.20	-14.29	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT160 5250 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10500.000	34.07	13.60	47.67	68.20	-20.53	peak
2	15750.000	33.27	16.55	49.82	74.00	-24.18	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11be EHT160 5250 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	10500.000	34.19	13.60	47.79	68.20	-20.41	peak
2	15750.000	34.58	16.55	51.13	74.00	-22.87	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT160 5570 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11140.000	34.25	14.47	48.72	74.00	-25.28	peak
2*	16710.000	32.86	18.12	50.98	68.20	-17.22	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11be EHT160 5570 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11140.000	33.58	14.47	48.05	74.00	-25.95	peak
2*	16710.000	33.41	18.12	51.53	68.20	-16.67	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: WLAN 2.4 GHz + 5 GHz+ 6 GHz + Bluetooth LE

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3159.000	41.56	-4.16	37.40	88.20	-50.80	peak
2	5182.000	39.02	1.23	40.25	88.20	-47.95	peak
3*	7103.000	36.95	6.63	43.58	88.20	-44.62	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	WLAN 2.4 GHz + 5 GHz+ 6 GHz + Bluetooth LE		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3278.000	42.06	-4.48	37.58	88.20	-50.62	peak
2	5505.000	38.40	1.79	40.19	88.20	-48.01	peak
3*	7239.000	36.27	7.15	43.42	88.20	-44.78	peak

Band Edge


Peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5180 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5143.720	54.79	1.38	56.17	74.00	-17.83	peak
2	5150.000	56.34	1.38	57.72	74.00	-16.28	peak
3*	5174.120	115.09	1.27	116.36	68.20	48.16	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11a 5180 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.760	54.81	1.39	56.20	74.00	-17.80	peak
2	5150.000	54.20	1.38	55.58	74.00	-18.42	peak
3*	5187.040	113.03	1.20	114.23	68.20	46.03	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11a 5200 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5142.200	54.57	1.39	55.96	74.00	-18.04	peak
2	5150.000	52.60	1.38	53.98	74.00	-20.02	peak
3*	5202.240	115.88	1.13	117.01	68.20	48.81	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11a 5200 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.760	53.48	1.39	54.87	74.00	-19.13	peak
2	5150.000	51.92	1.38	53.30	74.00	-20.70	peak
3*	5196.160	113.36	1.15	114.51	68.20	46.31	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11a 5240 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5104.960	52.91	1.42	54.33	74.00	-19.67	peak
2	5150.000	51.53	1.38	52.91	74.00	-21.09	peak
3*	5242.520	114.62	0.85	115.47	68.20	47.27	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11a 5240 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5140.680	53.36	1.39	54.75	74.00	-19.25	peak
2	5150.000	52.10	1.38	53.48	74.00	-20.52	peak
3*	5246.320	112.99	0.83	113.82	68.20	45.62	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11a 5260 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5252.640	116.70	0.79	117.49	68.20	49.29	peak
2	5350.000	50.74	1.02	51.76	74.00	-22.24	peak
3	5430.000	52.52	1.60	54.12	74.00	-19.88	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11a 5260 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5267.040	113.41	0.75	114.16	68.20	45.96	peak
2	5350.000	47.91	1.02	48.93	74.00	-25.07	peak
3	5444.880	52.35	1.70	54.05	74.00	-19.95	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11a 5280 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5283.360	116.13	0.71	116.84	68.20	48.64	peak
2	5350.000	51.32	1.02	52.34	74.00	-21.66	peak
3	5432.880	52.27	1.62	53.89	74.00	-20.11	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5280 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5277.360	114.01	0.72	114.73	68.20	46.53	peak
2	5350.000	48.10	1.02	49.12	74.00	-24.88	peak
3	5423.280	52.26	1.54	53.80	74.00	-20.20	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11a 5320 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5323.920	116.61	0.83	117.44	68.20	49.24	peak
2	5350.000	56.03	1.02	57.05	74.00	-16.95	peak
3	5352.240	58.34	1.03	59.37	74.00	-14.63	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5320 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5326.560	114.91	0.86	115.77	68.20	47.57	peak
2	5350.000	54.32	1.02	55.34	74.00	-18.66	peak
3	5352.720	56.79	1.04	57.83	74.00	-16.17	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11a 5500 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5457.520	53.63	1.75	55.38	74.00	-18.62	peak
2	5460.000	51.75	1.75	53.50	74.00	-20.50	peak
3	5464.960	53.79	1.75	55.54	68.20	-12.66	peak
4	5470.000	53.79	1.77	55.56	68.20	-12.64	peak
5*	5502.640	115.16	1.80	116.96	68.20	48.76	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11a 5500 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5458.720	52.20	1.75	53.95	74.00	-20.05	peak
2	5460.000	49.61	1.75	51.36	74.00	-22.64	peak
3	5468.320	53.11	1.76	54.87	68.20	-13.33	peak
4	5470.000	50.06	1.77	51.83	68.20	-16.37	peak
5*	5507.440	112.59	1.80	114.39	68.20	46.19	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11a 5560 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5437.600	52.17	1.66	53.83	74.00	-20.17	peak
2	5460.000	51.36	1.75	53.11	74.00	-20.89	peak
3	5468.080	50.91	1.76	52.67	68.20	-15.53	peak
4	5470.000	48.17	1.77	49.94	68.20	-18.26	peak
5*	5563.360	115.74	1.76	117.50	68.20	49.30	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11a 5560 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5433.040	51.52	1.62	53.14	74.00	-20.86	peak
2	5460.000	50.98	1.75	52.73	74.00	-21.27	peak
3	5460.160	50.98	1.75	52.73	68.20	-15.47	peak
4	5470.000	49.61	1.77	51.38	68.20	-16.82	peak
5*	5557.360	114.00	1.77	115.77	68.20	47.57	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11a 5700 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5703.660	115.40	1.58	116.98	68.20	48.78	peak
2	5725.000	52.01	1.78	53.79	68.20	-14.41	peak
3	5728.600	54.93	1.82	56.75	68.20	-11.45	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11a 5700 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5696.990	111.15	1.54	112.69	68.20	44.49	peak
2	5725.000	50.40	1.78	52.18	68.20	-16.02	peak
3	5764.560	53.16	2.08	55.24	68.20	-12.96	peak


Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5720 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5720 MHz		
Remark:			

No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5405.625	51.46	1.41	52.87	74.00	-21.13	peak
2	5460.000	49.22	1.75	50.97	74.00	-23.03	peak
3	5463.750	50.12	1.75	51.87	68.20	-16.33	peak
4	5470.000	48.32	1.77	50.09	68.20	-18.11	peak
5*	5723.750	114.83	1.77	116.60	68.20	48.40	peak
6	5850.000	49.39	2.29	51.68	68.20	-16.52	peak
7	5900.625	52.23	2.38	54.61	68.20	-13.59	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5720 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5720 MHz		
Remark:			


No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5408.125	51.06	1.44	52.50	74.00	-21.50	peak
2	5460.000	50.62	1.75	52.37	74.00	-21.63	peak
3	5463.125	50.57	1.75	52.32	68.20	-15.88	peak
4	5470.000	49.01	1.77	50.78	68.20	-17.42	peak
5*	5718.125	111.18	1.72	112.90	68.20	44.70	peak
6	5850.000	48.95	2.29	51.24	68.20	-16.96	peak
7	5908.125	51.53	2.32	53.85	68.20	-14.35	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11a 5745 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5646.125	52.75	1.57	54.32	68.20	-13.88	peak
2	5650.000	51.33	1.56	52.89	68.20	-15.31	peak
3	5700.000	52.92	1.54	54.46	105.20	-50.74	peak
4	5720.000	52.49	1.74	54.23	110.80	-56.57	peak
5	5725.000	55.30	1.78	57.08	122.20	-65.12	peak
6	5748.875	114.76	2.02	116.78	131.20	-14.42	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5745 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5636.750	51.12	1.59	52.71	68.20	-15.49	peak
2	5650.000	48.32	1.56	49.88	68.20	-18.32	peak
3	5700.000	49.96	1.54	51.50	105.20	-53.70	peak
4	5720.000	50.77	1.74	52.51	110.80	-58.29	peak
5	5725.000	51.25	1.78	53.03	122.20	-69.17	peak
6	5741.000	110.35	1.93	112.28	131.20	-18.92	peak


Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5785 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11a 5785 MHz		
Remark:			

No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5602.250	52.58	1.67	54.25	68.20	-13.95	peak
2	5650.000	48.86	1.56	50.42	68.20	-17.78	peak
3	5700.000	48.99	1.54	50.53	105.20	-54.67	peak
4	5720.000	49.36	1.74	51.10	110.80	-59.70	peak
5	5725.000	53.30	1.78	55.08	122.20	-67.12	peak
6	5790.875	114.12	2.17	116.29	131.20	-14.91	peak
7	5850.000	49.81	2.29	52.10	122.20	-70.10	peak
8	5855.000	49.74	2.31	52.05	110.80	-58.75	peak
9	5875.000	49.45	2.34	51.79	105.20	-53.41	peak
10	5925.000	49.38	2.23	51.61	68.20	-16.59	peak
11	5972.000	50.98	2.10	53.08	68.20	-15.12	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5785 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5785 MHz		
Remark:			


No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5600.000	52.04	1.67	53.71	68.20	-14.49	peak
2	5650.000	49.26	1.56	50.82	68.20	-17.38	peak
3	5700.000	48.87	1.54	50.41	105.20	-54.79	peak
4	5720.000	49.85	1.74	51.59	110.80	-59.21	peak
5	5725.000	49.46	1.78	51.24	122.20	-70.96	peak
6	5780.000	111.88	2.13	114.01	131.20	-17.19	peak
7	5850.000	48.64	2.29	50.93	122.20	-71.27	peak
8	5855.000	49.38	2.31	51.69	110.80	-59.11	peak
9	5875.000	49.16	2.34	51.50	105.20	-53.70	peak
10	5925.000	47.68	2.23	49.91	68.20	-18.29	peak
11	5964.125	51.34	2.09	53.43	68.20	-14.77	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11a 5825 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5828.375	113.64	2.27	115.91	131.20	-15.29	peak
2	5850.000	57.54	2.29	59.83	122.20	-62.37	peak
3	5855.000	54.02	2.31	56.33	110.80	-54.47	peak
4	5875.000	50.32	2.34	52.66	105.20	-52.54	peak
5	5925.000	49.09	2.23	51.32	68.20	-16.88	peak
6	5937.875	50.38	2.14	52.52	68.20	-15.68	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11a 5825 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5820.125	110.94	2.24	113.18	131.20	-18.02	peak
2	5850.000	55.30	2.29	57.59	122.20	-64.61	peak
3	5855.000	50.89	2.31	53.20	110.80	-57.60	peak
4	5875.000	49.90	2.34	52.24	105.20	-52.96	peak
5	5925.000	48.63	2.23	50.86	68.20	-17.34	peak
6*	5939.000	50.90	2.14	53.04	68.20	-15.16	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT20 5180 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5149.040	58.35	1.38	59.73	74.00	-14.27	peak
2	5150.000	55.78	1.38	57.16	74.00	-16.84	peak
3*	5182.480	114.38	1.23	115.61	68.20	47.41	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT20 5180 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.000	55.38	1.39	56.77	74.00	-17.23	peak
2	5150.000	52.86	1.38	54.24	74.00	-19.76	peak
3*	5174.120	113.31	1.27	114.58	68.20	46.38	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11ac VHT20 5200 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5142.960	53.45	1.38	54.83	74.00	-19.17	peak
2	5150.000	51.34	1.38	52.72	74.00	-21.28	peak
3*	5204.520	115.36	1.11	116.47	68.20	48.27	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT20 5200 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5103.440	52.82	1.41	54.23	74.00	-19.77	peak
2	5150.000	51.80	1.38	53.18	74.00	-20.82	peak
3*	5194.640	115.48	1.16	116.64	68.20	48.44	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT20 5240 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5142.200	52.82	1.39	54.21	74.00	-19.79	peak
2	5150.000	51.06	1.38	52.44	74.00	-21.56	peak
3*	5244.040	116.19	0.85	117.04	68.20	48.84	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11ac VHT20 5240 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5124.720	53.69	1.40	55.09	74.00	-18.91	peak
2	5150.000	51.50	1.38	52.88	74.00	-21.12	peak
3*	5234.160	114.80	0.91	115.71	68.20	47.51	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT20 5260 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5264.880	116.33	0.76	117.09	68.20	48.89	peak
2	5350.000	48.84	1.02	49.86	74.00	-24.14	peak
3	5382.240	53.30	1.25	54.55	74.00	-19.45	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11ac VHT20 5260 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5254.800	114.08	0.78	114.86	68.20	46.66	peak
2	5350.000	49.08	1.02	50.10	74.00	-23.90	peak
3	5452.560	51.45	1.75	53.20	74.00	-20.80	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT20 5280 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5284.080	117.06	0.70	117.76	68.20	49.56	peak
2	5350.000	50.97	1.02	51.99	74.00	-22.01	peak
3	5455.920	52.48	1.75	54.23	74.00	-19.77	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT20 5280 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5273.520	113.67	0.74	114.41	68.20	46.21	peak
2	5350.000	49.14	1.02	50.16	74.00	-23.84	peak
3	5431.920	51.46	1.61	53.07	74.00	-20.93	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11ac VHT20 5320 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5325.840	116.65	0.85	117.50	68.20	49.30	peak
2	5350.000	55.84	1.02	56.86	74.00	-17.14	peak
3	5350.560	57.92	1.02	58.94	74.00	-15.06	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT20 5320 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5314.800	113.77	0.77	114.54	68.20	46.34	peak
2	5350.000	52.23	1.02	53.25	74.00	-20.75	peak
3	5352.240	55.16	1.03	56.19	74.00	-17.81	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11ac VHT20 5500 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5452.000	53.39	1.75	55.14	74.00	-18.86	peak
2	5460.000	52.60	1.75	54.35	74.00	-19.65	peak
3	5469.760	56.56	1.77	58.33	68.20	-9.87	peak
4	5470.000	55.47	1.77	57.24	68.20	-10.96	peak
5*	5506.000	115.03	1.79	116.82	68.20	48.62	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT20 5500 MHz		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5423.920	52.15	1.55	53.70	74.00	-20.30	peak
2	5460.000	51.23	1.75	52.98	74.00	-21.02	peak
3	5467.360	53.83	1.76	55.59	68.20	-12.61	peak
4	5470.000	50.68	1.77	52.45	68.20	-15.75	peak
5*	5494.720	111.49	1.80	113.29	68.20	45.09	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT20 5560 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5447.680	52.63	1.72	54.35	74.00	-19.65	peak
2	5460.000	48.38	1.75	50.13	74.00	-23.87	peak
3	5464.240	51.17	1.75	52.92	68.20	-15.28	peak
4	5470.000	49.13	1.77	50.90	68.20	-17.30	peak
5*	5566.000	115.45	1.75	117.20	68.20	49.00	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11ac VHT20 5560 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5452.240	50.87	1.75	52.62	74.00	-21.38	peak
2	5460.000	49.84	1.75	51.59	74.00	-22.41	peak
3	5464.960	49.95	1.75	51.70	68.20	-16.50	peak
4	5470.000	48.64	1.77	50.41	68.20	-17.79	peak
5*	5554.000	114.25	1.77	116.02	68.20	47.82	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT20 5700 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5706.705	114.74	1.61	116.35	68.20	48.15	peak
2	5725.000	54.25	1.78	56.03	68.20	-12.17	peak
3	5758.035	54.58	2.06	56.64	68.20	-11.56	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT20 5700 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5693.365	111.39	1.54	112.93	68.20	44.73	peak
2	5725.000	51.37	1.78	53.15	68.20	-15.05	peak
3	5735.125	53.88	1.88	55.76	68.20	-12.44	peak


Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT20 5720 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT20 5720 MHz		
Remark:			

No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5456.250	51.14	1.75	52.89	74.00	-21.11	peak
2	5460.000	49.16	1.75	50.91	74.00	-23.09	peak
3	5466.875	51.30	1.76	53.06	68.20	-15.14	peak
4	5470.000	49.75	1.77	51.52	68.20	-16.68	peak
5*	5726.875	115.00	1.80	116.80	68.20	48.60	peak
6	5850.000	49.16	2.29	51.45	68.20	-16.75	peak
7	5888.750	51.48	2.36	53.84	68.20	-14.36	peak


Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT20 5720 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT20 5720 MHz		
Remark:			

No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5393.125	51.80	1.33	53.13	74.00	-20.87	peak
2	5460.000	48.34	1.75	50.09	74.00	-23.91	peak
3	5463.750	50.36	1.75	52.11	68.20	-16.09	peak
4	5470.000	48.32	1.77	50.09	68.20	-18.11	peak
5*	5715.625	109.22	1.70	110.92	68.20	42.72	peak
6	5850.000	49.30	2.29	51.59	68.20	-16.61	peak
7	5902.500	51.00	2.36	53.36	68.20	-14.84	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT20 5745 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5640.875	52.47	1.58	54.05	68.20	-14.15	peak
2	5650.000	50.25	1.56	51.81	68.20	-16.39	peak
3	5700.000	52.44	1.54	53.98	105.20	-51.22	peak
4	5720.000	53.22	1.74	54.96	110.80	-55.84	peak
5	5725.000	56.50	1.78	58.28	122.20	-63.92	peak
6	5752.250	114.85	2.03	116.88	131.20	-14.32	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT20 5745 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5606.375	51.60	1.66	53.26	68.20	-14.94	peak
2	5650.000	48.87	1.56	50.43	68.20	-17.77	peak
3	5700.000	50.84	1.54	52.38	105.20	-52.82	peak
4	5720.000	49.68	1.74	51.42	110.80	-59.38	peak
5	5725.000	53.10	1.78	54.88	122.20	-67.32	peak
6	5741.750	110.12	1.94	112.06	131.20	-19.14	peak


Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT20 5785 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT20 5785 MHz		
Remark:			

No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5622.125	52.31	1.63	53.94	68.20	-14.26	peak
2	5650.000	51.13	1.56	52.69	68.20	-15.51	peak
3	5700.000	51.06	1.54	52.60	105.20	-52.60	peak
4	5720.000	49.96	1.74	51.70	110.80	-59.10	peak
5	5725.000	51.14	1.78	52.92	122.20	-69.28	peak
6*	5792.000	115.02	2.18	117.20	131.20	-14.00	peak
7	5850.000	49.56	2.29	51.85	122.20	-70.35	peak
8	5855.000	49.38	2.31	51.69	110.80	-59.11	peak
9	5875.000	49.33	2.34	51.67	105.20	-53.53	peak
10	5925.000	50.85	2.23	53.08	68.20	-15.12	peak
11	5931.875	51.48	2.18	53.66	68.20	-14.54	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT20 5785 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT20 5785 MHz		
Remark:			


No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5622.875	51.67	1.61	53.28	68.20	-14.92	peak
2	5650.000	48.86	1.56	50.42	68.20	-17.78	peak
3	5700.000	49.49	1.54	51.03	105.20	-54.17	peak
4	5720.000	50.24	1.74	51.98	110.80	-58.82	peak
5	5725.000	50.13	1.78	51.91	122.20	-70.29	peak
6	5777.750	110.61	2.13	112.74	131.20	-18.46	peak
7	5850.000	49.85	2.29	52.14	122.20	-70.06	peak
8	5855.000	47.86	2.31	50.17	110.80	-60.63	peak
9	5875.000	49.38	2.34	51.72	105.20	-53.48	peak
10	5925.000	46.92	2.23	49.15	68.20	-19.05	peak
11	5958.875	50.90	2.08	52.98	68.20	-15.22	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT20 5825 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5822.375	113.47	2.24	115.71	131.20	-15.49	peak
2	5850.000	56.19	2.29	58.48	122.20	-63.72	peak
3	5855.000	55.49	2.31	57.80	110.80	-53.00	peak
4	5875.000	50.31	2.34	52.65	105.20	-52.55	peak
5	5925.000	49.15	2.23	51.38	68.20	-16.82	peak
6*	5926.625	50.73	2.21	52.94	68.20	-15.26	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11ac VHT20 5825 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5817.125	110.34	2.24	112.58	131.20	-18.62	peak
2	5850.000	55.14	2.29	57.43	122.20	-64.77	peak
3	5855.000	56.57	2.31	58.88	110.80	-51.92	peak
4	5875.000	49.12	2.34	51.46	105.20	-53.74	peak
5	5925.000	48.17	2.23	50.40	68.20	-17.80	peak
6*	5925.500	50.56	2.23	52.79	68.20	-15.41	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT40 5190 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5142.960	58.82	1.38	60.20	74.00	-13.80	peak
2	5150.000	58.18	1.38	59.56	74.00	-14.44	peak
3*	5196.160	112.78	1.15	113.93	68.20	45.73	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11ac VHT40 5190 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5148.280	61.14	1.38	62.52	74.00	-11.48	peak
2	5150.000	60.60	1.38	61.98	74.00	-12.02	peak
3*	5186.280	110.18	1.20	111.38	68.20	43.18	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT40 5230 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5128.520	54.96	1.39	56.35	74.00	-17.65	peak
2	5150.000	53.37	1.38	54.75	74.00	-19.25	peak
3*	5215.920	114.81	1.03	115.84	68.20	47.64	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11ac VHT40 5230 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5142.960	54.17	1.38	55.55	74.00	-18.45	peak
2	5150.000	50.50	1.38	51.88	74.00	-22.12	peak
3*	5224.280	110.44	0.98	111.42	68.20	43.22	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT40 5270 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5255.040	112.94	0.78	113.72	68.20	45.52	peak
2	5350.000	50.92	1.02	51.94	74.00	-22.06	peak
3	5357.760	54.24	1.08	55.32	74.00	-18.68	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11ac VHT40 5270 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5264.160	112.32	0.76	113.08	68.20	44.88	peak
2	5350.000	50.11	1.02	51.13	74.00	-22.87	peak
3	5363.040	54.35	1.11	55.46	74.00	-18.54	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11ac VHT40 5310 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5316.960	113.52	0.78	114.30	68.20	46.10	peak
2	5350.000	61.15	1.02	62.17	74.00	-11.83	peak
3	5354.160	64.01	1.04	65.05	74.00	-8.95	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT40 5310 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5304.480	112.52	0.70	113.22	68.20	45.02	peak
2	5350.000	57.76	1.02	58.78	74.00	-15.22	peak
3	5358.720	62.58	1.08	63.66	74.00	-10.34	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT40 5510 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5458.480	56.16	1.75	57.91	74.00	-16.09	peak
2	5460.000	53.83	1.75	55.58	74.00	-18.42	peak
3	5468.800	60.77	1.77	62.54	68.20	-5.66	peak
4	5470.000	58.51	1.77	60.28	68.20	-7.92	peak
5*	5495.920	112.15	1.80	113.95	68.20	45.75	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT40 5510 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5458.960	54.07	1.75	55.82	74.00	-18.18	peak
2	5460.000	51.74	1.75	53.49	74.00	-20.51	peak
3	5469.520	61.39	1.77	63.16	68.20	-5.04	peak
4	5470.000	55.46	1.77	57.23	68.20	-10.97	peak
5*	5524.240	110.14	1.80	111.94	68.20	43.74	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11ac VHT40 5550 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5447.440	53.93	1.71	55.64	74.00	-18.36	peak
2	5460.000	50.81	1.75	52.56	74.00	-21.44	peak
3	5467.360	54.30	1.76	56.06	68.20	-12.14	peak
4	5470.000	50.31	1.77	52.08	68.20	-16.12	peak
5*	5538.640	112.24	1.79	114.03	68.20	45.83	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11ac VHT40 5550 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5435.200	52.11	1.63	53.74	74.00	-20.26	peak
2	5460.000	48.95	1.75	50.70	74.00	-23.30	peak
3	5464.480	53.12	1.75	54.87	68.20	-13.33	peak
4	5470.000	48.74	1.77	50.51	68.20	-17.69	peak
5*	5543.920	109.97	1.79	111.76	68.20	43.56	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11ac VHT40 5670 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5656.245	112.73	1.55	114.28	68.20	46.08	peak
2	5725.000	51.28	1.78	53.06	68.20	-15.14	peak
3	5756.005	54.78	2.04	56.82	68.20	-11.38	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT40 5670 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5684.665	109.04	1.54	110.58	68.20	42.38	peak
2	5725.000	50.07	1.78	51.85	68.20	-16.35	peak
3	5760.790	52.20	2.06	54.26	68.20	-13.94	peak


Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT40 5710 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT40 5710 MHz		
Remark:			

No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5448.125	50.90	1.73	52.63	74.00	-21.37	peak
2	5460.000	49.69	1.75	51.44	74.00	-22.56	peak
3	5466.250	51.12	1.76	52.88	68.20	-15.32	peak
4	5470.000	49.92	1.77	51.69	68.20	-16.51	peak
5*	5716.250	111.85	1.70	113.55	68.20	45.35	peak
6	5850.000	49.83	2.29	52.12	68.20	-16.08	peak
7	5854.375	51.95	2.31	54.26	68.20	-13.94	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT40 5710 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT40 5710 MHz		
Remark:			


No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5425.000	51.17	1.56	52.73	74.00	-21.27	peak
2	5460.000	49.11	1.75	50.86	74.00	-23.14	peak
3	5461.875	50.92	1.75	52.67	68.20	-15.53	peak
4	5470.000	48.30	1.77	50.07	68.20	-18.13	peak
5*	5725.625	108.47	1.79	110.26	68.20	42.06	peak
6	5850.000	49.04	2.29	51.33	68.20	-16.87	peak
7	5910.000	51.79	2.32	54.11	68.20	-14.09	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT40 5755 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5644.625	52.62	1.56	54.18	68.20	-14.02	peak
2	5650.000	50.10	1.56	51.66	68.20	-16.54	peak
3	5700.000	52.87	1.54	54.41	105.20	-50.79	peak
4	5720.000	56.12	1.74	57.86	110.80	-52.94	peak
5	5725.000	61.83	1.78	63.61	122.20	-58.59	peak
6	5763.125	111.82	2.07	113.89	131.20	-17.31	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11ac VHT40 5755 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5604.125	51.80	1.65	53.45	68.20	-14.75	peak
2	5650.000	50.00	1.56	51.56	68.20	-16.64	peak
3	5700.000	50.36	1.54	51.90	105.20	-53.30	peak
4	5720.000	52.12	1.74	53.86	110.80	-56.94	peak
5	5725.000	55.89	1.78	57.67	122.20	-64.53	peak
6	5749.625	108.12	2.03	110.15	131.20	-21.05	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT40 5795 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5783.750	110.74	2.15	112.89	131.20	-18.31	peak
2	5850.000	54.29	2.29	56.58	122.20	-65.62	peak
3	5855.000	53.65	2.31	55.96	110.80	-54.84	peak
4	5875.000	52.04	2.34	54.38	105.20	-50.82	peak
5	5925.000	48.01	2.23	50.24	68.20	-17.96	peak
6*	5937.125	51.03	2.14	53.17	68.20	-15.03	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11ac VHT40 5795 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5786.375	107.92	2.17	110.09	131.20	-21.11	peak
2	5850.000	55.19	2.29	57.48	122.20	-64.72	peak
3	5855.000	53.57	2.31	55.88	110.80	-54.92	peak
4	5875.000	49.86	2.34	52.20	105.20	-53.00	peak
5	5925.000	49.47	2.23	51.70	68.20	-16.50	peak
6*	5975.000	51.41	2.11	53.52	68.20	-14.68	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11ac VHT80 5210 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5145.240	60.74	1.38	62.12	74.00	-11.88	peak
2	5150.000	59.29	1.38	60.67	74.00	-13.33	peak
3*	5217.440	108.11	1.02	109.13	68.20	40.93	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT80 5210 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5142.200	58.98	1.39	60.37	74.00	-13.63	peak
2	5150.000	58.88	1.38	60.26	74.00	-13.74	peak
3*	5243.280	105.84	0.85	106.69	68.20	38.49	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT80 5290 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5275.920	109.40	0.73	110.13	68.20	41.93	peak
2	5350.000	57.70	1.02	58.72	74.00	-15.28	peak
3	5362.080	60.43	1.10	61.53	74.00	-12.47	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT80 5290 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5322.960	107.84	0.83	108.67	68.20	40.47	peak
2	5350.000	54.52	1.02	55.54	74.00	-18.46	peak
3	5357.280	57.28	1.07	58.35	74.00	-15.65	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11ac VHT80 5530 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5449.360	59.29	1.74	61.03	74.00	-12.97	peak
2	5460.000	54.82	1.75	56.57	74.00	-17.43	peak
3	5464.720	60.48	1.75	62.23	68.20	-5.97	peak
4	5470.000	56.69	1.77	58.46	68.20	-9.74	peak
5*	5534.320	109.35	1.78	111.13	68.20	42.93	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11ac VHT80 5530 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5445.040	56.05	1.70	57.75	74.00	-16.25	peak
2	5460.000	55.56	1.75	57.31	74.00	-16.69	peak
3	5465.200	58.10	1.75	59.85	68.20	-8.35	peak
4	5470.000	54.06	1.77	55.83	68.20	-12.37	peak
5*	5566.240	106.85	1.75	108.60	68.20	40.40	peak


Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT80 5610 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT80 5610 MHz		
Remark:			

No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5441.375	53.69	1.68	55.37	74.00	-18.63	peak
2	5460.000	50.33	1.75	52.08	74.00	-21.92	peak
3	5469.425	52.81	1.77	54.58	68.20	-13.62	peak
4	5470.000	51.82	1.77	53.59	68.20	-14.61	peak
5*	5616.475	109.87	1.63	111.50	68.20	43.30	peak
6	5725.000	52.23	1.78	54.01	68.20	-14.19	peak
7	5728.250	55.07	1.81	56.88	68.20	-11.32	peak


Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT80 5610 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT80 5610 MHz		
Remark:			

No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5385.700	53.09	1.28	54.37	74.00	-19.63	peak
2	5460.000	49.78	1.75	51.53	74.00	-22.47	peak
3	5466.450	52.06	1.76	53.82	68.20	-14.38	peak
4	5470.000	50.45	1.77	52.22	68.20	-15.98	peak
5*	5604.575	107.33	1.66	108.99	68.20	40.79	peak
6	5725.000	51.07	1.78	52.85	68.20	-15.35	peak
7	5738.025	52.91	1.91	54.82	68.20	-13.38	peak


Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT80 5690 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT80 5690 MHz		
Remark:			

No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5377.500	52.60	1.21	53.81	74.00	-20.19	peak
2	5460.000	50.29	1.75	52.04	74.00	-21.96	peak
3	5469.375	51.28	1.77	53.05	68.20	-15.15	peak
4	5470.000	50.95	1.77	52.72	68.20	-15.48	peak
5*	5676.250	108.77	1.55	110.32	68.20	42.12	peak
6	5850.000	49.89	2.29	52.18	68.20	-16.02	peak
7	5851.875	51.83	2.29	54.12	68.20	-14.08	peak


Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT80 5690 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT80 5690 MHz		
Remark:			

No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5404.375	52.88	1.41	54.29	74.00	-19.71	peak
2	5460.000	49.05	1.75	50.80	74.00	-23.20	peak
3	5468.750	50.43	1.77	52.20	68.20	-16.00	peak
4	5470.000	49.21	1.77	50.98	68.20	-17.22	peak
5*	5666.875	105.90	1.55	107.45	68.20	39.25	peak
6	5850.000	48.51	2.29	50.80	68.20	-17.40	peak
7	5866.875	51.74	2.32	54.06	68.20	-14.14	peak


Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT80 5775 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT80 5775 MHz		
Remark:			

No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5622.875	56.13	1.61	57.74	68.20	-10.46	peak
2	5650.000	52.33	1.56	53.89	68.20	-14.31	peak
3	5700.000	54.88	1.54	56.42	105.20	-48.78	peak
4	5720.000	63.28	1.74	65.02	110.80	-45.78	peak
5	5725.000	73.64	1.78	75.42	122.20	-46.78	peak
6	5781.125	109.24	2.13	111.37	131.20	-19.83	peak
7	5850.000	57.03	2.29	59.32	122.20	-62.88	peak
8	5855.000	58.14	2.31	60.45	110.80	-50.35	peak
9	5875.000	54.79	2.34	57.13	105.20	-48.07	peak
10	5925.000	51.04	2.23	53.27	68.20	-14.93	peak
11	5953.250	50.67	2.08	52.75	68.20	-15.45	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT80 5775 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT80 5775 MHz		
Remark:			


No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5649.500	53.94	1.56	55.50	68.20	-12.70	peak
2	5650.000	52.14	1.56	53.70	68.20	-14.50	peak
3	5700.000	53.82	1.54	55.36	105.20	-49.84	peak
4	5720.000	58.67	1.74	60.41	110.80	-50.39	peak
5	5725.000	69.27	1.78	71.05	122.20	-51.15	peak
6	5784.125	105.37	2.15	107.52	131.20	-23.68	peak
7	5850.000	55.46	2.29	57.75	122.20	-64.45	peak
8	5855.000	55.76	2.31	58.07	110.80	-52.73	peak
9	5875.000	51.90	2.34	54.24	105.20	-50.96	peak
10	5925.000	49.16	2.23	51.39	68.20	-16.81	peak
11	5970.500	51.64	2.10	53.74	68.20	-14.46	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11ac VHT160 5250 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5137.440	62.87	1.40	64.27	74.00	-9.73	peak
2	5150.000	56.68	1.38	58.06	74.00	-15.94	peak
3*	5277.600	106.29	0.72	107.01	68.20	38.81	peak
4	5350.000	57.50	1.02	58.52	74.00	-15.48	peak
5	5401.440	59.76	1.39	61.15	74.00	-12.85	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11ac VHT160 5250 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5123.040	60.52	1.40	61.92	74.00	-12.08	peak
2	5150.000	57.64	1.38	59.02	74.00	-14.98	peak
3*	5182.560	104.47	1.22	105.69	68.20	37.49	peak
4	5350.000	54.80	1.02	55.82	74.00	-18.18	peak
5	5384.160	56.43	1.26	57.69	74.00	-16.31	peak


Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT160 5570 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11ac VHT160 5570 MHz		
Remark:			

No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5429.050	60.68	1.59	62.27	74.00	-11.73	peak
2	5460.000	55.24	1.75	56.99	74.00	-17.01	peak
3	5461.350	58.17	1.75	59.92	68.20	-8.28	peak
4	5470.000	55.89	1.77	57.66	68.20	-10.54	peak
5*	5593.100	105.56	1.69	107.25	68.20	39.05	peak
6	5725.000	53.62	1.78	55.40	68.20	-12.80	peak
7	5738.025	58.50	1.91	60.41	68.20	-7.79	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT160 5570 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11ac VHT160 5570 MHz		
Remark:			


No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5437.550	61.18	1.66	62.84	74.00	-11.16	peak
2	5460.000	53.89	1.75	55.64	74.00	-18.36	peak
3	5464.325	58.52	1.75	60.27	68.20	-7.93	peak
4	5470.000	53.67	1.77	55.44	68.20	-12.76	peak
5*	5505.975	102.51	1.79	104.30	68.20	36.10	peak
6	5725.000	53.25	1.78	55.03	68.20	-13.17	peak
7	5726.550	55.36	1.80	57.16	68.20	-11.04	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT20 5180 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5143.720	65.91	1.38	67.29	74.00	-6.71	peak
2	5150.000	61.61	1.38	62.99	74.00	-11.01	peak
3*	5180.200	110.93	1.24	112.17	68.20	43.97	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11be EHT20 5180 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5148.280	59.23	1.38	60.61	74.00	-13.39	peak
2	5150.000	61.42	1.38	62.80	74.00	-11.20	peak
3*	5185.520	110.78	1.21	111.99	68.20	43.79	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT20 5200 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.760	52.74	1.39	54.13	74.00	-19.87	peak
2	5150.000	50.87	1.38	52.25	74.00	-21.75	peak
3*	5203.760	114.28	1.12	115.40	68.20	47.20	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5200 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.760	52.49	1.39	53.88	74.00	-20.12	peak
2	5150.000	54.39	1.38	55.77	74.00	-18.23	peak
3*	5204.520	111.10	1.11	112.21	68.20	44.01	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11be EHT20 5240 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5104.960	50.29	1.42	51.71	74.00	-22.29	peak
2	5150.000	50.85	1.38	52.23	74.00	-21.77	peak
3*	5231.880	114.77	0.92	115.69	68.20	47.49	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT20 5240 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5130.040	51.87	1.39	53.26	74.00	-20.74	peak
2	5150.000	49.45	1.38	50.83	74.00	-23.17	peak
3*	5234.160	112.00	0.91	112.91	68.20	44.71	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT20 5260 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5268.720	112.18	0.75	112.93	68.20	44.73	peak
2	5350.000	49.37	1.02	50.39	74.00	-23.61	peak
3	5353.920	52.32	1.04	53.36	74.00	-20.64	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5260 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5256.960	113.28	0.78	114.06	68.20	45.86	peak
2	5350.000	48.48	1.02	49.50	74.00	-24.50	peak
3	5361.840	50.62	1.10	51.72	74.00	-22.28	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT20 5280 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5274.000	113.04	0.73	113.77	68.20	45.57	peak
2	5350.000	49.01	1.02	50.03	74.00	-23.97	peak
3	5368.800	52.13	1.16	53.29	74.00	-20.71	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5280 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5274.000	110.49	0.73	111.22	68.20	43.02	peak
2	5350.000	48.75	1.02	49.77	74.00	-24.23	peak
3	5367.600	51.54	1.15	52.69	74.00	-21.31	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11be EHT20 5320 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5325.600	111.65	0.84	112.49	68.20	44.29	peak
2	5350.000	65.40	1.02	66.42	74.00	-7.58	peak
3	5351.520	63.74	1.03	64.77	74.00	-9.23	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT20 5320 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5325.120	110.58	0.84	111.42	68.20	43.22	peak
2	5350.000	57.18	1.02	58.20	74.00	-15.80	peak
3	5350.800	61.46	1.02	62.48	74.00	-11.52	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT20 5500 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5458.720	55.48	1.75	57.23	74.00	-16.77	peak
2	5460.000	56.89	1.75	58.64	74.00	-15.36	peak
3	5464.960	64.11	1.75	65.86	68.20	-2.34	peak
4	5470.000	61.06	1.77	62.83	68.20	-5.37	peak
5*	5506.240	111.62	1.79	113.41	68.20	45.21	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5500 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5456.320	57.05	1.75	58.80	74.00	-15.20	peak
2	5460.000	58.80	1.75	60.55	74.00	-13.45	peak
3	5464.480	61.71	1.75	63.46	68.20	-4.74	peak
4	5470.000	60.43	1.77	62.20	68.20	-6.00	peak
5*	5505.040	108.89	1.79	110.68	68.20	42.48	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT20 5560 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5445.280	49.02	1.70	50.72	74.00	-23.28	peak
2	5460.000	46.77	1.75	48.52	74.00	-25.48	peak
3	5466.880	49.40	1.76	51.16	68.20	-17.04	peak
4	5470.000	47.32	1.77	49.09	68.20	-19.11	peak
5*	5563.120	112.65	1.76	114.41	68.20	46.21	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11be EHT20 5560 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5377.360	50.68	1.21	51.89	74.00	-22.11	peak
2	5460.000	46.70	1.75	48.45	74.00	-25.55	peak
3	5464.720	49.46	1.75	51.21	68.20	-16.99	peak
4	5470.000	47.24	1.77	49.01	68.20	-19.19	peak
5*	5566.720	109.60	1.75	111.35	68.20	43.15	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT20 5700 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5700.760	110.96	1.55	112.51	68.20	44.31	peak
2	5725.000	62.38	1.78	64.16	68.20	-4.04	peak
3	5725.555	64.54	1.79	66.33	68.20	-1.87	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT20 5700 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5702.065	107.73	1.56	109.29	68.20	41.09	peak
2	5725.000	64.63	1.78	66.41	68.20	-1.79	peak
3	5727.150	64.04	1.80	65.84	68.20	-2.36	peak


Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT20 5720 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT20 5720 MHz		
Remark:			


No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5411.875	49.26	1.47	50.73	74.00	-23.27	peak
2	5460.000	47.95	1.75	49.70	74.00	-24.30	peak
3	5468.750	49.31	1.77	51.08	68.20	-17.12	peak
4	5470.000	49.19	1.77	50.96	68.20	-17.24	peak
5*	5710.625	110.53	1.65	112.18	68.20	43.98	peak
6	5850.000	48.40	2.29	50.69	68.20	-17.51	peak
7	5916.250	49.83	2.28	52.11	68.20	-16.09	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11be EHT20 5720 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5441.875	50.42	1.68	52.10	74.00	-21.90	peak
2	5460.000	46.66	1.75	48.41	74.00	-25.59	peak
3	5470.000	48.37	1.77	50.14	68.20	-18.06	peak
4*	5724.375	106.95	1.77	108.72	68.20	40.52	peak
5	5850.000	47.80	2.29	50.09	68.20	-18.11	peak
6	5895.000	49.43	2.37	51.80	68.20	-16.40	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT20 5745 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5603.375	50.47	1.65	52.12	68.20	-16.08	peak
2	5650.000	48.99	1.56	50.55	68.20	-17.65	peak
3	5700.000	53.13	1.54	54.67	105.20	-50.53	peak
4	5720.000	65.71	1.74	67.45	110.80	-43.35	peak
5	5725.000	74.91	1.78	76.69	122.20	-45.51	peak
6	5742.875	110.86	1.95	112.81	131.20	-18.39	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11be EHT20 5745 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5616.875	49.25	1.63	50.88	68.20	-17.32	peak
2	5650.000	46.36	1.56	47.92	68.20	-20.28	peak
3	5700.000	49.12	1.54	50.66	105.20	-54.54	peak
4	5720.000	61.34	1.74	63.08	110.80	-47.72	peak
5	5725.000	66.82	1.78	68.60	122.20	-53.60	peak
6	5751.875	107.83	2.03	109.86	131.20	-21.34	peak


Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT20 5785 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT20 5785 MHz		
Remark:			

No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5614.250	50.02	1.63	51.65	68.20	-16.55	peak
2	5650.000	48.75	1.56	50.31	68.20	-17.89	peak
3	5700.000	48.06	1.54	49.60	105.20	-55.60	peak
4	5720.000	49.55	1.74	51.29	110.80	-59.51	peak
5	5725.000	51.39	1.78	53.17	122.20	-69.03	peak
6	5777.750	112.38	2.13	114.51	131.20	-16.69	peak
7	5850.000	48.65	2.29	50.94	122.20	-71.26	peak
8	5855.000	48.42	2.31	50.73	110.80	-60.07	peak
9	5875.000	47.44	2.34	49.78	105.20	-55.42	peak
10	5925.000	45.85	2.23	48.08	68.20	-20.12	peak
11*	5933.000	49.50	2.17	51.67	68.20	-16.53	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5785 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5785 MHz		
Remark:			


No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5615.375	49.73	1.63	51.36	68.20	-16.84	peak
2	5650.000	46.51	1.56	48.07	68.20	-20.13	peak
3	5700.000	47.19	1.54	48.73	105.20	-56.47	peak
4	5720.000	47.86	1.74	49.60	110.80	-61.20	peak
5	5725.000	48.33	1.78	50.11	122.20	-72.09	peak
6	5787.125	107.81	2.17	109.98	131.20	-21.22	peak
7	5850.000	47.60	2.29	49.89	122.20	-72.31	peak
8	5855.000	49.71	2.31	52.02	110.80	-58.78	peak
9	5875.000	48.71	2.34	51.05	105.20	-54.15	peak
10	5925.000	46.18	2.23	48.41	68.20	-19.79	peak
11	5931.125	49.17	2.18	51.35	68.20	-16.85	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT20 5825 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5828.375	110.62	2.27	112.89	131.20	-18.31	peak
2	5850.000	68.46	2.29	70.75	122.20	-51.45	peak
3	5855.000	63.04	2.31	65.35	110.80	-45.45	peak
4	5875.000	56.56	2.34	58.90	105.20	-46.30	peak
5	5925.000	46.37	2.23	48.60	68.20	-19.60	peak
6*	5943.125	49.01	2.11	51.12	68.20	-17.08	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Vertical		
Test Mode:	802.11be EHT20 5825 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5831.750	107.65	2.26	109.91	131.20	-21.29	peak
2	5850.000	66.30	2.29	68.59	122.20	-53.61	peak
3	5855.000	63.22	2.31	65.53	110.80	-45.27	peak
4	5875.000	52.86	2.34	55.20	105.20	-50.00	peak
5	5925.000	45.92	2.23	48.15	68.20	-20.05	peak
6*	5927.000	49.25	2.21	51.46	68.20	-16.74	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11be EHT40 5190 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5147.520	60.26	1.38	61.64	74.00	-12.36	peak
2	5150.000	58.58	1.38	59.96	74.00	-14.04	peak
3*	5185.520	106.92	1.21	108.13	68.20	39.93	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT40 5190 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5141.440	59.62	1.39	61.01	74.00	-12.99	peak
2	5150.000	59.67	1.38	61.05	74.00	-12.95	peak
3*	5204.520	107.05	1.11	108.16	68.20	39.96	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT40 5230 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5111.040	53.52	1.41	54.93	74.00	-19.07	peak
2	5150.000	52.58	1.38	53.96	74.00	-20.04	peak
3*	5244.800	112.22	0.84	113.06	68.20	44.86	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11be EHT40 5230 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5130.800	52.70	1.39	54.09	74.00	-19.91	peak
2	5150.000	52.90	1.38	54.28	74.00	-19.72	peak
3*	5212.880	108.50	1.05	109.55	68.20	41.35	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT40 5270 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5280.480	110.33	0.71	111.04	68.20	42.84	peak
2	5350.000	53.63	1.02	54.65	74.00	-19.35	peak
3	5358.000	58.13	1.08	59.21	74.00	-14.79	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11be EHT40 5270 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5284.320	108.12	0.70	108.82	68.20	40.62	peak
2	5350.000	51.36	1.02	52.38	74.00	-21.62	peak
3	5352.960	55.50	1.04	56.54	74.00	-17.46	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT40 5310 MHz		
Remark:			




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5315.040	108.22	0.77	108.99	68.20	40.79	peak
2	5350.000	70.64	1.02	71.66	74.00	-2.34	peak
3	5355.360	64.41	1.06	65.47	74.00	-8.53	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11be EHT40 5310 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5297.280	106.92	0.66	107.58	68.20	39.38	peak
2	5350.000	62.86	1.02	63.88	74.00	-10.12	peak
3	5350.560	65.42	1.02	66.44	74.00	-7.56	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal


Test Mode: 802.11be EHT40 5510 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5457.520	58.24	1.75	59.99	74.00	-14.01	peak
2	5460.000	56.88	1.75	58.63	74.00	-15.37	peak
3	5469.040	58.92	1.77	60.69	68.20	-7.51	peak
4	5470.000	56.21	1.77	57.98	68.20	-10.22	peak
5*	5504.560	106.70	1.80	108.50	68.20	40.30	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Vertical
Test Mode: 802.11be EHT40 5510 MHz
Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5458.960	60.78	1.75	62.53	74.00	-11.47	peak
2	5460.000	50.87	1.75	52.62	74.00	-21.38	peak
3	5466.160	62.70	1.76	64.46	68.20	-3.74	peak
4	5470.000	56.18	1.77	57.95	68.20	-10.25	peak
5*	5500.720	103.79	1.80	105.59	68.20	37.39	peak

Standard: Part 15E Test Site: 966 Chamber
Polarization: Horizontal
Test Mode: 802.11be EHT40 5550 MHz
Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5454.880	56.35	1.75	58.10	74.00	-15.90	peak
2	5460.000	50.63	1.75	52.38	74.00	-21.62	peak
3	5466.640	55.85	1.76	57.61	68.20	-10.59	peak
4	5470.000	52.63	1.77	54.40	68.20	-13.80	peak
5*	5568.160	109.82	1.74	111.56	68.20	43.36	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11be EHT40 5550 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5455.360	50.86	1.75	52.61	74.00	-21.39	peak
2	5460.000	50.64	1.75	52.39	74.00	-21.61	peak
3	5467.360	54.96	1.76	56.72	68.20	-11.48	peak
4	5470.000	52.80	1.77	54.57	68.20	-13.63	peak
5*	5542.960	106.49	1.79	108.28	68.20	40.08	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11be EHT40 5670 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5682.780	108.95	1.54	110.49	68.20	42.29	peak
2	5725.000	58.38	1.78	60.16	68.20	-8.04	peak
3	5731.500	64.07	1.84	65.91	68.20	-2.29	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical


Test Mode: 802.11be EHT40 5670 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5657.115	106.34	1.55	107.89	68.20	39.69	peak
2	5725.000	58.50	1.78	60.28	68.20	-7.92	peak
3	5729.905	62.05	1.84	63.89	68.20	-4.31	peak

Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT40 5710 MHz		
Remark:			



Standard:	Part 15E	Test Site:	966 Chamber
Polarization:	Horizontal		
Test Mode:	802.11be EHT40 5710 MHz		
Remark:			


No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5436.875	51.69	1.64	53.33	74.00	-20.67	peak
2	5460.000	47.28	1.75	49.03	74.00	-24.97	peak
3	5465.625	49.74	1.76	51.50	68.20	-16.70	peak
4	5470.000	47.61	1.77	49.38	68.20	-18.82	peak
5*	5709.375	106.51	1.63	108.14	68.20	39.94	peak
6	5850.000	48.48	2.29	50.77	68.20	-17.43	peak
7	5868.125	50.15	2.33	52.48	68.20	-15.72	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11be EHT40 5710 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5414.375	48.99	1.49	50.48	74.00	-23.52	peak
2	5460.000	47.12	1.75	48.87	74.00	-25.13	peak
3	5470.000	49.20	1.77	50.97	68.20	-17.23	peak
4*	5691.250	105.05	1.54	106.59	68.20	38.39	peak
5	5850.000	47.75	2.29	50.04	68.20	-18.16	peak
6	5871.250	49.84	2.33	52.17	68.20	-16.03	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11be EHT40 5755 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5642.375	51.41	1.57	52.98	68.20	-15.22	peak
2	5650.000	48.62	1.56	50.18	68.20	-18.02	peak
3	5700.000	59.97	1.54	61.51	105.20	-43.69	peak
4	5720.000	70.23	1.74	71.97	110.80	-38.83	peak
5	5725.000	73.34	1.78	75.12	122.20	-47.08	peak
6	5768.750	107.37	2.10	109.47	131.20	-21.73	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11be EHT40 5755 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	5635.250	50.20	1.59	51.79	68.20	-16.41	peak
2	5650.000	49.39	1.56	50.95	68.20	-17.25	peak
3	5700.000	57.11	1.54	58.65	105.20	-46.55	peak
4	5720.000	71.80	1.74	73.54	110.80	-37.26	peak
5	5725.000	69.20	1.78	70.98	122.20	-51.22	peak
6	5769.125	106.73	2.10	108.83	131.20	-22.37	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Horizontal

Test Mode: 802.11be EHT40 5795 MHz

Remark:




No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5789.375	108.02	2.17	110.19	131.20	-21.01	peak
2	5850.000	64.81	2.29	67.10	122.20	-55.10	peak
3	5855.000	60.44	2.31	62.75	110.80	-48.05	peak
4	5875.000	58.91	2.34	61.25	105.20	-43.95	peak
5	5925.000	46.93	2.23	49.16	68.20	-19.04	peak
6*	5938.625	48.89	2.14	51.03	68.20	-17.17	peak

Standard: Part 15E Test Site: 966 Chamber

Polarization: Vertical

Test Mode: 802.11be EHT40 5795 MHz

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5787.500	104.96	2.17	107.13	131.20	-24.07	peak
2	5850.000	62.77	2.29	65.06	122.20	-57.14	peak
3	5855.000	56.21	2.31	58.52	110.80	-52.28	peak
4	5875.000	55.58	2.34	57.92	105.20	-47.28	peak
5	5925.000	46.53	2.23	48.76	68.20	-19.44	peak
6*	5931.500	48.86	2.18	51.04	68.20	-17.16	peak