

Hand and Nail Harmony. Inc

Application For Certification

FCC ID: 2AG70-GELISHMTSPK

Wireless Speaker

Model: Gelish/MT speaker

2.4GHz Transceiver

Report No.: 151231019SZN-001

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-14]

Approved by:	
Andy Yan Technical Supervisor	
	Andy Yan

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample
 may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF No.: FCC 15C_TX_c

LIST OF EXHIBITS

INTRODUCTION

EXHIBIT 1: General Description

EXHIBIT 2: System Test Configuration

EXHIBIT 3: Emission Results

EXHIBIT 4: Equipment Photographs

EXHIBIT 5: Product Labelling

EXHIBIT 6: Technical Specifications

EXHIBIT 7: Instruction Manual

EXHIBIT 8: Miscellaneous Information

EXHIBIT 9: Test Equipment List

TRF No.: FCC 15C_TX_c

MEASUREMENT/TECHNICAL REPORT

Hand and Nail Harmony. Inc

Model: Gelish/MT speaker

FCC ID: 2AG7O-GELISHMTSPK

This report concerns (check one:)	Original Grant <u>X</u>	Class II Cha	nge
Equipment Type: DXX - Part 15 Low Pow	er Communication De	vice Transmitter	
Deferred grant requested per 47 CFR 0.4	57(d)(1)(ii)? Ye	es	No _X_
	If yes, defer un	til:date	
Company Name agrees to notify the Com	mission by:		
of the intended date of announcement of date.	the product so that the	date e grant can be is	sued on that
Transition Rules Request per 15.37?	Ye	es	No <u>X</u>
If no, assumed Part 15, Subpart C for Edition] provision.	intentional radiator -	- the new 47 C	FR [10-1-14
Report prepared by:			
	Jenner Liu Intertek Testing Serv Kejiyuan Branch 6F, Block D, Huahar Nanshan District, Sh Phone: (86 755) 86 Fax: (86 755) 86	n Building, Langs nenzhen, P. R. C 114 0639	shan Road,

TRF No.: FCC 15C_TX_c

Table of Contents

1.0 General Description	2
1.1 Product Description 1.2 Related Submittal(s) Grants 1.3 Test Methodology 1.4 Test Facility	2 2
2.0 System Test Configuration	4
2.1 Justification 2.2 EUT Exercising Software. 2.3 Special Accessories 2.4 Equipment Modification 2.5 Measurement Uncertainty 2.6 Support Equipment List and Description	4 4 5
3.0 Emission Results	
3.1 Radiated Test Results	8 8
3.1.2 Radiated Emission Configuration Photograph	9
3.2 Conducted Emissions at Mains Termina	15 15
4.0 Equipment Photographs	19
5.0 Product Labelling	21
6.0 <u>Technical Specifications</u>	23
7.0 Instruction Manual	25
8.0 Miscellaneous Information	27
8.1 Bandedge Plot	
8.2 Discussion of Pulse Desensitization	
8.3 Transmitter Duty Cycle Calculation	
9.0 Test Equipment List	35

TRF No.: FCC 15C_TX_c

List of attached file

Exhibit type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Setup Photo	Conducted Emission	conducted photos.pdf
Test Report	Bandedge Plot	bandedge.pdf
Test Report	20dB BW Plot	bw.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Operation Description	Technical Description	descri.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Confidentiality Letter	request.pdf
Cover Letter	Letter of Agency	agency.pdf

TRF No.: FCC 15C_TX_c FCC ID: 2AG7O-GELISHMTSPK

EXHIBIT 1 GENERAL DESCRIPTION

TRF No.: FCC 15C_TX_c

1.0 General Description

1.1 Product Description

The equipment under test (EUT) is a Wireless Speaker with BT 2.1 with EDR function operating in 2402-2480MHz. The EUT is powered by the fully-charged DC 3.7V, 400mAh new rechargeable battery which was charged by USB port (DC 5V). For more detail information pls. refer to the user manual.

Bluetooth Version: 2.1+ EDR Antenna type: Integral antenna

Modulation Type: GFSK, π/4DQPSK, 8DPSK

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

This is an application for certification of a transceiver for the Wireless Speaker of Bluetooth function. And for the other digital functions were tested and demonstrated in report 151231019SZN-002.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in Semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

1.4 Test Facility

The Semi-anechoic chamber and shielding room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch** and located at 6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 242492).

TRF No.: FCC 15C TX c

EXHIBIT 2 SYSTEM TEST CONFIGURATION

TRF No.: FCC 15C_TX_c

2.0 System Test Configuration

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The EUT was powered by the fully-charged DC 3.7V new rechargeable battery which was charged by an AC/DC adaptor or PC with input of AC 120V, 60Hz during the test.

All packets DH1, DH3 & DH5 mode in modulation type GFSK, π /4DQPSK, 8DPSK were tested and only the worst data was reported in this report.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.

The rear of unit was flushed with the rear of the table with 0.8m height when powered by adapter up to 1GHz and placed in the centre of 1.5 m turntable above 1GHz.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on a turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

The EUT exercise program (provided by client) used during testing was designed to exercise the various system components in a manner similar to a typical use.

2.3 Special Accessories

No special accessory attached.

2.4 Equipment Modification

Any modifications installed previous to testing by Hand and Nail Harmony. Inc will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd Kejiyuan Branch.

TRF No.: FCC 15C_TX_c

2.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

Description	Manufacturer	Model No.
iPod	Apple	A1421
Micro SD card	SanDisk	SDSDQ-2048-P36M
USB & Aux In cable	Hand and Nail Harmony. Inc	Unshielded, Length 40cm
AC/DC adaptor (Provided by Intertek)	TP-Link	T050100-2A3 (Input: AC 100-240V, 50/60Hz, 0.3A Output: DC 5.0V, 1.0A)
Laptop (Provided by Intertek)	Lenovo	T420

TRF No.: FCC 15C_TX_c

EXHIBIT 3 EMISSION RESULTS

TRF No.: FCC 15C_TX_c

Emission Results 3.0

Data is included worst-case configuration (the configuration which resulted in the highest emission levels).

TRF No.: FCC 15C_TX_c FCC ID: 2AG7O-GELISHMTSPK

3.1 Radiated Test Results

A sample calculation, configuration photographs and data tables of the emissions are included.

3.1.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG$$

Where $FS = Field Strength in dB\mu V/m$

RA = Receiver Amplitude (including preamplifier) in dBµV

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB AG = Amplifier Gain in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG$$

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The net field strength for comparison to the appropriate emission limit is 42 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

 $RA = 62.0 dB\mu V$

AF = 7.4 dB

CF = 1.6 dB

 $AG = 29.0 \, dB$

 $FS = 62 + 7.4 + 1.6 - 29 = 42 \, dB\mu V/m$

Level in μ V/m = Common Antilogarithm [(42 dB μ V/m)/20] = 125.9 μ V/m

TRF No.: FCC 15C TX c

3.1.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

3.1.3 Radiated Emissions

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit. Simultaneous transmission was considered.

Worst Case Radiated Emission at 947.135 MHz

Judgement: Passed by 12.4 dB

TEST PERSONNEL:

Sign on file

<u>Jenner Liu, Engineer</u> *Typed/Printed Name*

January 25, 2016
Date

TRF No.: FCC 15C_TX_c

Applicant: Hand and Nail Harmony. Inc

Date of Test: January 25, 2016 Model: Gelish/MT speaker

Sample: 1/1

Worst Case Operating Mode: BT Link and Charging via Adapter

Table 1

Radiated Emissions

Polarization	Frequency	Reading	Pre-	Antenna	Net	Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	209.450	32.5	20.0	12.3	24.8	43.5	-18.7
Horizontal	640.615	26.3	20.0	23.9	30.2	46.0	-15.8
Horizontal	947.135	25.5	20.0	28.1	33.6	46.0	-12.4
Vertical	55.705	29.3	20.0	7.5	16.8	40.0	-23.2
Vertical	132.820	27.7	20.0	9.6	17.3	43.5	-26.2
Vertical	947.620	25.4	20.0	28.1	33.5	46.0	-12.5

NOTES: 1. Quasi-Peak detector is used except for others stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. All emissions are below the QP limit.

TRF No.: FCC 15C_TX_c

3.1.4 Transmitter Spurious Emissions (Radiated)

Worst Case Radiated Emission at 7323.000 MHz

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 10.0 dB

TEST PERSONNEL:

Sign on file

<u>Jenner Liu, Engineer</u> *Typed/Printed Name*

January 25, 2016 Date

TRF No.: FCC 15C_TX_c

Applicant: Hand and Nail Harmony. Inc

Date of Test: January 25, 2016 Model: Gelish/MT speaker

Sample: 1/1

Worst Case Operating Mode: Transmitting and Charging via Adapter

Table 2

Radiated Emissions

(2402MHz)

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)	, ,	, ,	, , ,	
Horizontal	2402.000	93.1	36.7	28.1	84.5	114.0	-29.5
Horizontal	4804.000	54.5	36.7	35.5	53.3	74.0	-20.7
Horizontal	7206.000	61.1	36.1	36.5	61.5	74.0	-12.5
Horizontal	9608.000	61.7	36.2	37.0	62.5	74.0	-11.5

Polarization	Frequency	Reading	Pre-	Antenna	Average	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(-dB)	(dBµV/m)	(dBµV/m)	
			(dB)					
Horizontal	2402.000	93.1	36.7	28.1	22.5	62.0	94.0	-32.0
Horizontal	4804.000	54.5	36.7	35.5	22.5	30.8	54.0	-23.2
Horizontal	7206.000	61.1	36.1	36.5	22.5	39.0	54.0	-15.0
Horizontal	9608.000	61.7	36.2	37.0	22.5	40.0	54.0	-14.0

Notes: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: Jenner Liu

TRF No.: FCC 15C_TX_c

Applicant: Hand and Nail Harmony. Inc

Date of Test: January 25, 2016 Model: Gelish/MT speaker

Sample: 1/1

Worst Case Operating Mode: Transmitting and Charging via Adapter

Table 3

Radiated Emissions

(2441MHz)

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)	, ,	, , ,	, , ,	
Horizontal	2441.000	93.8	36.7	28.1	85.2	114.0	-28.8
Horizontal	4882.000	52.5	36.7	35.5	51.3	74.0	-22.7
Horizontal	7323.000	62.9	36.1	37.2	64.0	74.0	-10.0
Horizontal	9764.000	59.7	36.2	37.0	60.5	74.0	-13.5

Polarization	Frequency	Reading	Pre-	Antenna	Average	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(-dB)	(dBµV/m)	(dBµV/m)	
			(dB)					
Horizontal	2441.000	93.8	36.7	28.1	22.5	62.7	94.0	-31.3
Horizontal	4882.000	52.5	36.7	35.5	22.5	28.8	54.0	-25.2
Horizontal	7323.000	62.9	36.1	37.2	22.5	41.5	54.0	-12.5
Horizontal	9764.000	59.7	36.2	37.0	22.5	38.0	54.0	-16.0

Notes: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: Jenner Liu

TRF No.: FCC 15C_TX_c

Applicant: Hand and Nail Harmony. Inc Date of Test: January 25, 2016

Model: Gelish/MT speaker

Sample: 1/1

Worst Case Operating Mode: Transmitting and Charging via Adapter

Table 4

Radiated Emissions

(2480MHz)

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)		, ,	, ,	
Horizontal	2480.000	92.8	36.7	28.1	84.2	114.0	-29.8
Horizontal	4960.000	54.0	36.7	35.5	52.8	74.0	-21.2
Horizontal	7440.000	59.6	36.1	37.2	60.7	74.0	-13.3
Horizontal	9920.000	59.9	36.3	38.9	62.5	74.0	-11.5

Polarization	Frequency	Reading	Pre-	Antenna	Average	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(-dB)	(dBµV/m)	(dBµV/m)	
			(dB)					
Horizontal	2480.000	92.8	36.7	28.1	22.5	61.7	94.0	-32.3
Horizontal	4960.000	54.0	36.7	35.5	22.5	30.3	54.0	-23.7
Horizontal	7440.000	59.6	36.1	37.2	22.5	38.2	54.0	-15.8
Horizontal	9920.000	59.9	36.3	38.9	22.5	40.0	54.0	-14.0

Notes: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: Jenner Liu

TRF No.: FCC 15C_TX_c

- 3.2 Conducted Emission at Mains Terminal
- 3.2.1 Conducted Emissions Configuration Photograph

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

3.2.2 Conducted Emissions

Worst Case Neutral-Conducted Configuration
At

0.178 MHz

Judgement: Passed by 10.8 dB margin

TEST PERSONNEL:

Sign on file

<u>Jenner Liu, Engineer</u> *Typed/Printed Name*

January 25, 2016 Date

TRF No.: FCC 15C_TX_c

Applicant: Hand and Nail Harmony. Inc


Date of Test: January 25, 2016 Model: Gelish/MT speaker

Sample: 1/1

Worst Case Operating Mode: BT Link and Charging via Adapter

Phase: Live

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.174	52.5	L1	9.8	12.3	64.8
0.470	38.5	L1	9.9	18.0	56.5
1.402	38.9	L1	9.9	17.1	56.0
3.278	38.6	L1	10.0	17.4	56.0
5.150	36.5	L1	10.0	23.5	60.0
14.490	35.8	L1	10.1	24.2	60.0

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.174	29.1	L1	9.8	25.7	54.8
0.470	32.3	L1	9.9	14.2	46.5
1.402	31.4	L1	9.9	14.6	46.0
3.278	31.2	L1	10.0	14.8	46.0
5.150	28.1	L1	10.0	21.9	50.0
14.490	25.8	L1	10.1	24.2	50.0

TRF No.: FCC 15C_TX_c

Applicant: Hand and Nail Harmony. Inc


Date of Test: January 25, 2016 Model: Gelish/MT speaker

Sample: 1/1

Worst Case Operating Mode: BT Link and Charging via Adapter

Phase: Neutral

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)	
0.178	53.8	N	10.2	10.8	64.6	
0.286	43.7	N	10.2	16.9	60.6	
0.466	37.1	N	10.2	19.5	56.6	
1.402	33.6	N	10.3	22.4	56.0	
2.338	33.4	N	10.3	22.6	56.0	
3.278	33.5	N	10.3	22.5	56.0	

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.178	35.7	N	10.2	18.9	54.6
0.286	24.9	N	10.2	25.7	50.6
0.466	31.3	N	10.2	15.3	46.6
1.402	28.4	N	10.3	17.6	46.0
2.338	27.6	N	10.3	18.4	46.0
3.278	28.0	N	10.3	18.0	46.0

TRF No.: FCC 15C_TX_c

EXHIBIT 4 EQUIPMENT PHOTOGRAPHS

TRF No.: FCC 15C_TX_c

4.0 **Equipment Photographs**

For electronic filing, the photographs of the tested EUT are saved with filename: external photos.pdf & internal photos.pdf.

TRF No.: FCC 15C_TX_c

EXHIBIT 5

PRODUCT LABELLING

TRF No.: FCC 15C_TX_c

5.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

TRF No.: FCC 15C_TX_c

EXHIBIT 6 TECHNICAL SPECIFICATIONS

TRF No.: FCC 15C_TX_c

6.0 <u>Technical Specifications</u>

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

TRF No.: FCC 15C_TX_c

EXHIBIT 7 INSTRUCTION MANUAL

TRF No.: FCC 15C_TX_c

7.0 <u>Instruction Manual</u>

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

TRF No.: FCC 15C_TX_c

EXHIBIT 8

MISCELLANEOUS INFORMATION

TRF No.: FCC 15C_TX_c

8.0 <u>Miscellaneous Information</u>

This miscellaneous information includes details of the measured bandedge, the test procedure and calculation of factor such as pulse desensitization.

TRF No.: FCC 15C_TX_c

8.1 Bandedge Plot

For electronic filing, the plot shows the fundamental emission when modulated is saved with filename: bandedge.pdf. From the plot, the field strength of any emissions outside of the specified frequency band are attenuated to the general radiated emission limits in section 15.209. It fulfils the requirement of 15.249(d).

Peak Measurement

Bandedge compliance is determined by applying marker-delta method, i.e (Bandedge Plot).

(i) Lower channel 2402MHz:

Peak Resultant field strength = Fundamental emissions (peak value) - delta from the bandedge plot

 $= 84.5 \text{ dB}\mu\text{v/m}-48.0\text{dB}$ = 36.5 dB\mu\/m

(ii) Upper channel 2480MHz:

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the bandedge plot

 $= 84.2 \text{ dB}\mu\text{v/m}-51.3 \text{ dB}$ = 32.9 dB $\mu\text{v/m}$

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74dBµv/m (Peak Limit) and 54dBµv/m (Average Limit).

TRF No.: FCC 15C_TX_c

8.1 Bandedge Plot (cont'd)

Pursuant to FCC part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

Figure 8.1 Bandwidth

TRF No.: FCC 15C_TX_c

8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period (T_{eff}) is approximately 625µs for Bluetooth. With a resolution bandwidth (3dB) of 1MHz, so the pulse desensitivity factor is 0dB.

TRF No.: FCC 15C_TX_c

8.3 Transmitter Duty Cycle Calculation, FCC Rule 15.35 (b, c)

Based on the Bluetooth Specification Version 2.1 with EDR and worst case AFH mode, transmitter ON time is independent of packet type (DH1, DH3 and DH5) and packet length, the AFH mode Duty cycle connection factor as below:

Channel hop rate = 800 hops/second (AFH Mode)

Adjusted channel hop rate for DH5 mode = 133.33 hops/second

Time per channel hop = 1 / 133.33 hops/second = 7.5 ms

Time to cycle through all channels = 7.5×20 channels = 150 ms

Number of times transmitter hits on one channel = 100 ms / 150 ms = 1 time(s)

Worst case dwell time = 7.5 ms

Duty cycle connection factor = $20\log_{10} (7.5 \text{ms} / 100 \text{ms}) = -22.5 \text{ dB}$

TRF No.: FCC 15C_TX_c

8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.10 - 2013.

The transmitting equipment under test (EUT) is placed on a styrene turntable which is four feet in diameter, up to 1GHz 0.8m and above 1GHz 1.5m in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjust through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

Detector function for conducted emissions is in QP & AV mode and IFBW setting is 9 kHz from the frequency band 150 kHz to 30MHz.

TRF No.: FCC 15C_TX_c

8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.10 - 2013.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. Above 1000 MHz, a resolution bandwidth of 1 MHz is used (RBW 3MHz used for fundamental emission).

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

TRF No.: FCC 15C_TX_c

EXHIBIT9

TEST EQUIPMENT LIST

TRF No.: FCC 15C_TX_c

9.0 <u>Test Equipment List</u>

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-12	BiConiLog Antenna	ETS	3142E	00166158	15-Sep-2015	15-Sep-2016
SZ185-01	EMI Receiver	R&S	ESCI	100547	07-Feb-2015	07-Feb-2016
SZ061-08	Horn Antenna	ETS	3115	00092346	17-Oct-2015	17-Oct-2016
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	29-Apr-2015	29-Apr-2016
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	08-Jun-2015	08-Jun-2016
SZ056-06	Signal Analyzer	R&S	FSV 40	101101	08-Jul-2015	08-Jul-2016
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	07-Feb-2015	07-Feb-2016
SZ188-01	Anechoic Chamber	ETS	RFD-F/A- 100	4102	19-Apr-2014	19-Apr-2016
SZ062-02	RF Cable	RADIALL	RG 213U		28-Dec-2015	28-Jun-2016
SZ062-05	RF Cable	RADIALL	0.04- 26.5GHz		08-Oct-2015	08-Apr-2016
SZ062-12	RF Cable	RADIALL	0.04- 26.5GHz	1	08-Oct-2015	08-Apr-2016
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02	-	20-May-2015	20-May-2016
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	03-Nov-2015	03-Nov-2016
SZ187-01	Two-Line V- Network	R&S	ENV216	100072	03-Nov-2015	03-Nov-2016
SZ187-02	Two-Line V- Network	R&S	ENV216	100073	24-Jun-2015	24-Jun-2016
SZ188-03	Shielding Room	ETS	RFD-100	4100	23-Aug-2014	23-Aug-2016

TRF No.: FCC 15C_TX_c FCC ID: 2AG7O-GELISHMTSPK