

## SAR EVALUATION REPORT

For

## **POSH Mobile Limited**

1011A, 10/F., Harbour Centre Tower 1, No. 1 Hok Cheung St., Hung Hom, Kowloon, Hong Kong

**FCC ID: 2AG8KX551** 

Report Type: **Product Type:** Mobile Phone Original Report Test Engineer: Rocky Xiao **Report Number:** RDG160118001-20 **Report Date:** 2016-01-26 Sula Huang Solo Huge Reviewed By: RF Leader **Test Laboratory:** Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

	At	testation of Test Results					
	Company Name	POSH Mobile Limited					
	<b>EUT Description</b>	Mobile Phone					
	Product Name	Icon Pro HD					
EUT	FCC ID	2AG8KX551					
Information	Tested Model	X551					
	Multiple Model:	X551A,X551B,X551C					
	Serial Number	160118001					
	Test Date	2016-01-18 ,2016-01-19,2016-01-20					
MO	DE	Max. SAR Level(s) Reported(W/Kg)	Limit(W/Kg)				
0075050	1g Head SAR	0.049	, 0,				
GSM 850	1g Body SAR	0.495	=				
	1g Head SAR	0.1	1				
PCS 1900	1g Body SAR	0.509					
	1g Head SAR	0.082					
WCDMA 850	1g Body SAR	0.357	1				
	1g Head SAR	0.175	1.6				
WCDMA 1900	1g Body SAR	0.994	1,0				
	1g Head SAR	0.38					
WLAN	1g Body SAR	0.202					
	1g Head SAR	0.555	1				
Simultaneous	1g Body SAR	1.196	-				
Hotspot	1g Body SAR	1.196					
	Electromagnetic Filed ANSI / IEEE C95.3 IEEE Recommended Electromagnetic Field GHz.	fety Levels with Respect to Human Exposure to Racds,3 kHz to 300 GHz.  : 2002  Practice for Measurements and Computations of Rads With Respect to Human Exposure to SuchFields,1	dio Frequency				
	FCC 47 CFR part 2.	tion exposure evaluation: portable devices					
Applicable Standards	Absorption Rate (SA) Measurement Technic IEC 62209-2:2010 Human exposure to recommunication device to determine the specin close proximity to KDB procedures KDB 447498 D01 Ge KDB 648474 D04 Ha KDB 865664 D01 SA	adio frequency fields from hand-held and body-mouses-Human models, instrumentation, and proceduresific absorption rate (SAR) for wireless communication the human body (frequency range of 30 MHz to 6 General RF Exposure Guidance v06	nted wireless Part 2: Procedure on devices used				
	KDB 941225 D01 3C KDB 941225 D06 Ho	S SAR Procedures v03r01	_				

Report No: RDG160118001-20

**Note:** This wireless device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified in ANSI/IEEE Standards and has been tested in accordance with the measurement procedures specified in IEEE 1528-2013 and RF exposure KDB procedures.

The results and statements contained in this report pertain only to the device(s) evaluated.

SAR Evaluation Report 2 of 71

# TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	5
EUT DESCRIPTION	6
TECHNICAL SPECIFICATION	
REFERENCE, STANDARDS, AND GUILDELINES	
SAR LIMITS	
FACILITIES	
DESCRIPTION OF TEST SYSTEM	
EQUIPMENT LIST AND CALIBRATION	
EQUIPMENTS LIST & CALIBRATION INFORMATION	15
SAR MEASUREMENT SYSTEM VERIFICATION	16
LIQUID VERIFICATION	16
SYSTEM ACCURACY VERIFICATION SAR SYSTEM VALIDATION DATA	
EUT TEST STRATEGY AND METHODOLOGY	
TEST POSITIONS FOR DEVICE OPERATING NEXT TO A PERSON'S EAR	
EAR/TILT POSITION	
TEST POSITIONS FOR BODY-WORN AND OTHER CONFIGURATIONS	
SAR EVALUATION PROCEDURE	
TEST METHODOLOGY	28
CONDUCTED OUTPUT POWER MEASUREMENT	29
PROVISION APPLICABLE	
TEST PROCEDURE	
RADIO CONFIGURATION	
TEST RESULTS:	
SAR MEASUREMENT RESULTS	38
SAR TEST DATA	38
SAR MEASUREMENT VARIABILITY	44
SAR SIMULTANEOUS TRANSMISSION DESCRIPTION	45
SAR PLOTS (SUMMARY OF THE HIGHEST SAR VALUES)	49
APPENDIX A MEASUREMENT UNCERTAINTY	
APPENDIX B EUT TEST POSITION PHOTOS	
BODY-WORN BACK SETUP PHOTO	
BODY-WORN LEFT SETUP PHOTO	
BODY-WORN RIGHT SETUP PHOTO	
BODY-WORN HEADSET SETUP PHOTO	
BODY-WORN BOTTOM SETUP PHOTO	
LEFT HEAD TOUCH SETUP PHOTO	
LEFT HEAD TILT SETUP PHOTO	
RIGHT HEAD TOUCH SETUP PHOTO	66
RIGHT HEAD TILT SETUP PHOTO	66
APPENDIX C EUT PHOTOS	67
EUT – Front View	
EUT –BACK VIEW	
EUT – Side View-1 EUT – Side View-2	
EUT – Side View-2	

Bay	Area	Compl	iance	Laborat	ories	Corp. (	(Dongguan)	)

EUT – BT&WLAN ANTENNA VIEW  APPENDIX D CALIBRATION CERTIFICATES	
EUT – COVER OFF VIEW	
EUT – SIDE VIEW-4	69

Report No: RDG160118001-20

SAR Evaluation Report 4 of 71

## **DOCUMENT REVISION HISTORY**

Revision Number	Report Number	Description of Revision	Date of Revision	
0	RDG160118001-20	Original Report	2016-01-26	

Report No: RDG160118001-20

SAR Evaluation Report 5 of 71

## **EUT DESCRIPTION**

This report has been prepared on behalf of *POSH Mobile Limited* and their product, Model: X551, FCC ID: 2AG8KX551 or the EUT (Equipment under Test) as referred to in the rest of this report.

Report No: RDG160118001-20

## **Technical Specification**

Exposure Category:	Population / Uncontrolled		
Antenna Type(s):	Internal Antenna		
Body-Worn Accessories:	Headset		
Face-Head Accessories:	None		
Multi-slot Class:	Class12		
	GSM Voice, GPRS Data,		
	WCDMA R99 (Voice + Data), HSUPA Rel 6, HSDPA Rel 7,		
Operation Mode:	DC-HSDPA Rel 8, HSPA+ Rel 8		
	WLAN		
	Bluetooth		
	GSM 850 : 824-849 MHz(TX) ; 869-894 MHz(RX)		
	PCS 1900: 1850-1910 MHz(TX) ; 1930-1990 MHz(RX)		
	WCDMA850: 824-849 MHz(TX) ; 869-894 MHz(RX)		
Frequency Band:	WCDMA1900: 1850-1910 MHz(TX) ; 1930-1990 MHz(RX)		
	WLAN: 2412MHz-2462 MHz		
	Bluetooth: 2402MHz-2480 MHz		
	GSM 850 : 33.15 dBm		
	PCS 1900: 30.51 dBm		
	WCDMA 850: 22.51 dBm		
Conducted RF Power:	WCDMA 1900: 22.88 dBm		
	WLAN: 17.87 dBm		
	Bluetooth(BDR/EDR): 5.18 dBm		
	BLE:-2.95 dBm		
Dimensions (L*W*H):	15.32 cm (L) x 7.9 cm (W) x 8.2cm (H)		
Power Source:	3.7 VDC Rechargeable Battery		
Normal Operation:	Head and Body-worn		

SAR Evaluation Report 6 of 71

## REFERENCE, STANDARDS, AND GUILDELINES

#### FCC:

The Report and Order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.1-1992 [6] for an uncontrolled environment (Paragraph 65). According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

Report No: RDG160118001-20

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in North America is 1.6 mW/g average over 1 gram of tissue mass.

#### CE:

The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 2 mW/g as recommended by EN62209-1 for an uncontrolled environment. According to the Standard, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in Europe is 2 mW/g average over 10 gram of tissue mass.

The test configurations were laid out on a specially designed test fixture to ensure the reproducibility of measurements. Each configuration was scanned for SAR. Analysis of each scan was carried out to characterize the above effects in the device.

SAR Evaluation Report 7 of 71

### **SAR Limits**

#### FCC Limit

Report No: RDG160118001-20

	SAR (W/kg)			
EXPOSURE LIMITS	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)		
Spatial Average (averaged over the whole body)	0.08	0.4		
Spatial Peak (averaged over any 1 g of tissue)	1.60	8.0		
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0		

#### **CE Limit**

	SAR (W/kg)			
	(General Population /	(Occupational /		
EXPOSURE LIMITS	Uncontrolled Exposure	Controlled Exposure		
	Environment)	Environment)		
Spatial Average (averaged over the whole body)	0.08	0.4		
Spatial Peak (averaged over any 10 g of tissue)	2.0	10		
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0		

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

General Population/Uncontrolled environments Spatial Peak limit 1.6W/kg (FCC) & 2 W/kg (CE) applied to the EUT.

SAR Evaluation Report 8 of 71

## **FACILITIES**

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Report No: RDG160118001-20

SAR Evaluation Report 9 of 71


## **DESCRIPTION OF TEST SYSTEM**

These measurements were performed with the automated near-field scanning system DASY5 from Schmid & Partner Engineering AG (SPEAG) which is the Fifth generation of the system shown in the figure hereinafter:



## **DASY5 System Description**

The DASY5 system for performing compliance tests consists of the following items:



SAR Evaluation Report 10 of 71

- A standard high precision 6-axis robot (Staubli TX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal application, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win7 professional operating system and the DASY52 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

#### **DASY5 Measurement Server**

The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz Intel ULV Celeron, 128MB chip-disk and 128MB RAM. The necessary circuits for communication with the DAE4 (or DAE3) electronics box, as well as the 16 bit AD-converter system for optical detection and digital I/O interface are contained on the DASY5 I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical



processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized point out, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.

#### **Data Acquisition Electronics**

The data acquisition electronics (DAE4) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of both the DAE4 as well as of the DAE3 box is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

SAR Evaluation Report 11 of 71

Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 $\mu$ W/g to > 100 mW/g Linearity: $\pm$ 0.2 dB (noise: typically < 1 $\mu$ W/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI

#### **SAM Twin Phantom**

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region, where shell thickness

increases to 6 mm). The phantom has three measurement areas:

- Left hand
- Right hand
- Flat phantom

The phantom table for the DASY systems based on the TX90XL and RX160L robots have the size of 100 x 50 x 85 cm (L x W x H).

The phantom table for the compact DASY systems based on the RX60L robot have the size of 100 x 75 x 91 cm (L x W x H); these tables are reinforced for mounting of the robot onto the table.

For easy dislocation these tables have fork lift cut outs at the bottom.

The bottom plate contains three pairs of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. Only one device holder is necessary if two phantoms are used (e.g., for different liquids)

A white cover is provided to cover the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on top of this phantom cover are possible. Three reference marks are provided on the phantom counter. These reference marks are used to teach the absolute phantom position relative to the robot.



Report No: RDG160118001-20

SAR Evaluation Report 12 of 71

#### **Robots**

The DASY5 system uses the high precision industrial robots TX90XL from Staubli SA (France). The TX robot family is the successor of the well known RX robot family and offers the same features important for our application:

Report No: RDG160118001-20

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchrony motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)

The above mentioned robots are controlled by the Staubli CS8c robot controllers. All information regarding the use and maintenance of the robot arm and the robot controller is contained on the CDs delivered along with the robot. Paper manuals are available upon request direct from Staubli.

#### **Area Scans**

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 15mm 2 step integral, with 1.5mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.

#### **Zoom Scan (Cube Scan Averaging)**

The averaging zoom scan volume utilized in the DASY5 software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of  $1000 \text{ kg/m}^3$  is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1g cube is 10 mm, with the side length of the 10 g cube is 21.5 mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 7 x7 x 7 (5mmx5mmx5mm) providing a volume of 30 mm in the X & Y & Z axis.

SAR Evaluation Report 13 of 71

## **Tissue Dielectric Parameters for Head and Body Phantoms**

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Report No: RDG160118001-20

## Recommended Tissue Dielectric Parameters for Head and Body

Frequency	Head	Tissue	Body Tissue			
(MHz)	Er	O'(S/m)	Er	O' (S/m)		
150	52.3	0.76	61.9	0.80		
300	45.3	0.87	58.2	0.92		
450	43.5	0.87	56.7	0.94		
835	41.5	0.90	55.2	0.97		
900	41.5	0.97	55.0	1.05		
915	41.5	0.98	55.0	1.06		
1450	40.5	1.20	54.0	1.30		
1610	40.3	1.29	53.8	1.40		
1800-2000	40.0	1.40	53.3	1.52		
2450	39.2	1.80	52.7	1.95		
3000	38.5	2.40	52.0	2.73		
5800	35.3	5.27	48.2	6.00		

SAR Evaluation Report 14 of 71

## **EQUIPMENT LIST AND CALIBRATION**

## **Equipments List & Calibration Information**


Equipment	Model	S/N	Calibration Date	Calibration Due Date
Robot	RX90	D03636	N/A	N/A
DASY5 Test Software	DASY52.8	N/A	N/A	N/A
DASY5 Measurement Server	DASY5 4.5.12	1470	N/A	N/A
Data Acquisition Electronics	DAE4	1459	2015/9/18	2016/9/18
E-Field Probe	EX3DV4	7329	2015/2/5	2016/2/4
Dipole, 900 MHz	D900V2	1d183	2015/7/14	2018/7/14
Dipole,1900MHz	D1900V2	5d206	2015/7/14	2018/7/14
Dipole,2450MHz	D2450V3	971	2015/7/8	2018/7/8
R&S, universal Radio Communication Tester	CMU200	109038	2015/7/28	2016/7/27
8960 Series 10 Wireless Communication Test Set	E5515C	MY50266471	2016/1/13	2017/1/13
Mounting Device	MD4HHTV5	SD 000 H01 KA	N/A	N/A
Twin SAM	Twin SAM V5.0	1874	N/A	N/A
Simulated Tissue 835 MHz Head	TS-835-H	1512083501	Each Time	/
Simulated Tissue 835 MHz Body	TS-835-B	1512083502	Each Time	/
Simulated Tissue 1900 MHz Head	ТЅ-1900-Н	1512190001	Each Time	/
Simulated Tissue 1900 MHz Body	TS-1900-B	1512190002	Each Time	/
Simulated Tissue 2450 MHz Head	ТЅ-2450-Н	1512245001	Each Time	/
Simulated Tissue 2450 MHz Body	TS-2450-B	1512245002	Each Time	/
Network Analyzer	8752C	3140A02356	2015/6/5	2016/6/4
Dielectric probe kit	85070B	US33020324	2015/6/13	2016/6/13
Signal Generator	E4422B	MY41000355	2015/11/23	2016/11/22
Power Meter	EPM-441A	GB37481494	2015/11/3	2016/11/3
Power Meter Sensor	8481A	T-03-EM-127	2015/11/3	2016/11/3
Power Amplifier	5205PE	1015	N/A	N/A
Directional Coupler	488Z	N/A	N/A	N/A
Attenuator	20dB, 100W	N/A	N/A	N/A

Report No: RDG160118001-20

SAR Evaluation Report 15 of 71

## SAR MEASUREMENT SYSTEM VERIFICATION

## **Liquid Verification**



Report No: RDG160118001-20

Liquid Verification Setup Block Diagram

## **Liquid Verification Results**

Frequency		Liquid Parameter		Target Value		Delta (%)		Tolerance
(MHz)	Liquid Type	ε <sub>r</sub>	O' (S/m)	$\epsilon_{ m r}$	O' (S/m)	$\Delta \epsilon_{ m r}$	ΔΟ΄ (S/m)	(%)
824.2	Simulated Tissue 835 MHz Head	42.916	0.877	41.5	0.9	3.41	-2.56	±5
024.2	Simulated Tissue 835 MHz Body	55.128	0.963	55.2	0.97	-0.13	-0.72	±5
826.4	Simulated Tissue 835 MHz Head	42.9	0.881	41.5	0.9	3.37	-2.11	±5
	Simulated Tissue 835 MHz Body	55.116	0.967	55.2	0.97	-0.15	-0.31	±5
836.6	Simulated Tissue 835 MHz Head	42.85	0.892	41.5	0.9	3.25	-0.89	±5
830.0	Simulated Tissue 835 MHz Body	55.123	0.976	55.2	0.97	-0.14	0.62	±5
846.6	Simulated Tissue 835 MHz Head	42.832	0.896	41.5	0.9	3.21	-0.44	±5
840.0	Simulated Tissue 835 MHz Body	55.037	0.985	55.2	0.97	-0.3	1.55	±5
040 0	Simulated Tissue 835 MHz Head	42.708	0.896	41.5	0.9	2.91	-0.44	±5
848.8	Simulated Tissue 835 MHz Body	55.009	0.987	55.2	0.97	-0.35	1.75	±5
000	Simulated Tissue 835 MHz Head	42.715	0.897	41.5	0.9	2.93	-0.33	±5
900	Simulated Tissue 835 MHz Body	54.986	0.988	55.2	0.97	-0.39	1.86	±5

<sup>\*</sup>Liquid Verification above was performed on 2016-01-18.

SAR Evaluation Report 16 of 71

Frequency	I.''1T	Liquid Parameter		Target Value		Delta (%)		Tolerance
(MHz)	Liquid Type	ε <sub>r</sub>	O' (S/m)	$\epsilon_{ m r}$	O' (S/m)	$\Delta \epsilon_{ m r}$	ΔΟ΄ (S/m)	(%)
1850.2	Simulated Tissue 1900 MHz Head	39.83	1.359	40	1.4	-0.43	-2.93	±5
1830.2	Simulated Tissue 1900 MHz Body	55.267	1.477	53.3	1.52	3.69	-2.83	±5
1852.4	Simulated Tissue 1900 MHz Head	39.873	1.356	40	1.4	-0.32	-3.14	±5
1832.4	Simulated Tissue 1900 MHz Body	55.203	1.476	53.3	1.52	3.57	-2.89	±5
1880	Simulated Tissue 1900 MHz Head	39.734	1.388	40	1.4	-0.66	-0.86	±5
1000	Simulated Tissue 1900 MHz Body	53.741	1.542	53.3	1.52	0.83	1.45	±5
1000	Simulated Tissue 1900 MHz Head	39.658	1.412	40	1.4	-0.85	0.86	±5
1900	Simulated Tissue 1900 MHz Body	54.196	1.516	53.3	1.52	1.68	-0.26	±5
1007.6	Simulated Tissue 1900 MHz Head	39.582	1.413	40	1.4	-1.05	0.93	±5
1907.6	Simulated Tissue 1900 MHz Body	53.601	1.492	53.3	1.52	0.56	-1.84	±5
1000.9	Simulated Tissue 1900 MHz Head	39.599	1.412	40	1.4	-1	0.86	±5
1909.8	Simulated Tissue 1900 MHz Body	53.388	1.493	53.3	1.52	0.17	-1.78	±5

<sup>\*</sup>Liquid Verification above was performed on 2016-01-19.

Frequency	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance
(MHz)	Liquid Type	$\epsilon_{ m r}$	O' (S/m)	$\epsilon_{ m r}$	O' (S/m)	$\Delta \epsilon_{ m r}$	ΔΟ΄ (S/m)	(%)
2412	Simulated Tissue 2450 MHz Head	39.351	1.793	39.2	1.8	0.39	-0.39	±5
2412	Simulated Tissue 2450 MHz Body	53.231	1.94	52.7	1.95	1.01	-0.51	±5
2437	Simulated Tissue 2450 MHz Head	39.189	1.824	39.2	1.8	-0.03	1.33	±5
2437	Simulated Tissue 2450 MHz Body	51.655	1.978	52.7	1.95	-1.98	1.44	±5
2450	Simulated Tissue 2450 MHz Head	39.095	1.827	39.2	1.8	-0.27	1.5	±5
2430	Simulated Tissue 2450 MHz Body	52.234	1.97	52.7	1.95	-0.88	1.03	±5
2462	Simulated Tissue 2450 MHz Head	39	1.841	39.2	1.8	-0.51	2.28	±5
2462	Simulated Tissue 2450 MHz Body	52.216	1.98	52.7	1.95	-0.92	1.54	±5


<sup>\*</sup>Liquid Verification above was performed on 2016-01-20.

SAR Evaluation Report 17 of 71

## **System Accuracy Verification**

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of  $\pm 10\%$ . The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

### **System Verification Setup Block Diagram**



### **System Accuracy Check Results**

Date	Frequency Band	Liquid Type	Measured SAR (W/Kg)		Target Value (W/Kg)	Delta (%)	Tolerance (%)
2016-01-18	-18 900	835MHz Head	1g	11.48	11.828	-2.94	±10
2010-01-18		835MHz Body	1g	11.6	11.072	4.77	±10
2016-01-19	1000	1900MHz Head	1g	41.3	40.7	1.47	±10
2010-01-19	1900	1900MHz Body	1g	42.5	40.8	4.17	±10
2016-01-20	2450	2450MHz Head	1g	54.1	53.3	1.50	±10
		2450MHz Body	1g	52.5	50.6	3.75	±10

<sup>\*</sup>All SAR values are normalized to 1 Watt forward power.

SAR Evaluation Report 18 of 71

#### SAR SYSTEM VALIDATION DATA

Test Laboratory: Bay Area Compliance Labs Corp.(Dongguan)

System Performance 900 MHz Head

DUT: D900V2; Type: 900 MHz; Serial: 1d183

Communication System: CW; Frequency: 900 MHz; Duty Cycle: 1:1

Medium parameters used: f = 900 MHz;  $\sigma = 0.897 \text{ S/m}$ ;  $\varepsilon_r = 42.715$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

#### DASY5 Configuration:

• Probe: EX3DV4 - SN7329; ConvF(9.52, 9.52, 9.52); Calibrated: 2015/2/5;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1459; Calibrated: 2015/9/18

Phantom: SAM (30deg probe tilt) with CRP v5.0 20150321; Type: QD000P40CD; Serial: TP:1874

Report No: RDG160118001-20

Measurement SW: DASY52, Version 52.8 (8);

**System Performance 900 MHz Head /Area Scan (71x131x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm Maximum value of SAR (interpolated) = 14.7 W/kg


**System Performance 900 MHz Head /Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 112.8 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 15.6 W/kg

SAR(1 g) = 11.48 W/kg; SAR(10 g) = 6.54 W/kg

Maximum value of SAR (measured) = 13.8 W/kg



0 dB = 13.8 W/kg = 11.40 dBW/kg

SAR Evaluation Report 19 of 71

#### **System Performance 900 MHz Body**

#### **DUT: D900V2; Type: 900 MHz; Serial: 1d183**

Communication System: CW; Frequency: 900 MHz; Duty Cycle: 1:1

Medium parameters used: f = 900 MHz;  $\sigma = 0.988 \text{ S/m}$ ;  $\varepsilon_r = 54.986$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

#### DASY5 Configuration:

• Probe: EX3DV4 - SN7329; ConvF(9.17, 9.17, 9.17); Calibrated: 2015/2/5;

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2015/9/18
- Phantom: SAM (30deg probe tilt) with CRP v5.0 20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

System Performance 900 MHz Body /Area Scan (71x131x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm Maximum value of SAR (interpolated) = 16.5 W/kg


**System Performance 900 MHz Body /Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 112.6 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 15.8 W/kg

SAR(1 g) = 11.6 W/kg; SAR(10 g) = 6.63 W/kg

Maximum value of SAR (measured) = 14.33 W/kg



0 dB = 14.33 W/kg = 11.56 dBW/kg

SAR Evaluation Report 20 of 71

#### System Performance 1900 MHz Head

DUT: D1900V2; Type: 1900 MHz; Serial: 5d206

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: f = 1900 MHz;  $\sigma = 1.412 \text{ S/m}$ ;  $\varepsilon_r = 39.658$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

#### DASY5 Configuration:

• Probe: EX3DV4 - SN7329; ConvF(7.88, 7.88, 7.88); Calibrated: 2015/2/5;

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2015/9/18
- Phantom: SAM (30deg probe tilt) with CRP v5.0 20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**System Performance 1900 MHz Head /Area Scan (61x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm Maximum value of SAR (interpolated) = 49.4 W/kg


**System Performance 1900 MHz Head /Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 175.6 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 76.8 W/kg

SAR(1 g) = 41.3 W/kg; SAR(10 g) = 21.1 W/kg

Maximum value of SAR (measured) = 46.6 W/kg



0 dB = 46.6 W/kg = 16.68 dBW/kg

SAR Evaluation Report 21 of 71

#### **System Performance 1900 MHz Body**

DUT: D1900V2; Type: 1900 MHz; Serial: 5d206

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: f = 1900 MHz;  $\sigma = 1.516 \text{ S/m}$ ;  $\varepsilon_r = 54.196$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

#### DASY5 Configuration:

• Probe: EX3DV4 - SN7329; ConvF(7.56, 7.56, 7.56); Calibrated: 2015/2/5;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1459; Calibrated: 2015/9/18

• Phantom: SAM (30deg probe tilt) with CRP v5.0 20150321; Type: QD000P40CD; Serial: TP:1874

• Measurement SW: DASY52, Version 52.8 (8);

System Performance 1900 MHz Body /Area Scan (61x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm Maximum value of SAR (interpolated) = 50.3 W/kg


**System Performance 1900 MHz Body /Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 173.3 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 76.8 W/kg

SAR(1 g) = 42.5 W/kg; SAR(10 g) = 22.3 W/kg

Maximum value of SAR (measured) = 47.9 W/kg



0 dB = 47.9 W/kg = 16.80 dBW/kg

SAR Evaluation Report 22 of 71

#### System Performance 2450 MHz Head

**DUT: D2450V3; Type: 2450 MHz; Serial: 971** 

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: f = 2450 MHz;  $\sigma = 1.827 \text{ S/m}$ ;  $\varepsilon_r = 39.095$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

#### DASY5 Configuration:

• Probe: EX3DV4 - SN7329; ConvF(7.06, 7.06, 7.06); Calibrated: 2015/2/5;

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2015/9/18
- Phantom: SAM (30deg probe tilt) with CRP v5.0 20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**System Performance 2450 MHz Head /Area Scan (61x81x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 65.2 W/kg


**System Performance 2450 MHz Head /Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 189.3 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 112 W/kg

SAR(1 g) = 54.1 W/kg; SAR(10 g) = 24.4 W/kg

Maximum value of SAR (measured) = 61.7 W/kg



0 dB = 61.7 W/kg = 17.90 dBW/kg

SAR Evaluation Report 23 of 71

#### **System Performance 2450 MHz Body**

DUT: D2450V3; Type: 2450 MHz; Serial: 971

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: f = 2450 MHz;  $\sigma = 1.97 \text{ S/m}$ ;  $\varepsilon_r = 52.234$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

#### DASY5 Configuration:

Probe: EX3DV4 - SN7329; ConvF(7.2, 7.2, 7.2); Calibrated: 2015/2/5;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1459; Calibrated: 2015/9/18

• Phantom: SAM (30deg probe tilt) with CRP v5.0 20150321; Type: QD000P40CD; Serial: TP:1874

• Measurement SW: DASY52, Version 52.8 (8);

System Performance 2450 MHz Body /Area Scan (61x81x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 64.6 W/kg


**System Performance 2450 MHz Body /Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 183.7 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 115 W/kg

SAR(1 g) = 52.5 W/kg; SAR(10 g) = 24.6 W/kg

Maximum value of SAR (measured) = 59.8 W/kg



0 dB = 59.8 W/kg = 17.77 dBW/kg

SAR Evaluation Report 24 of 71


#### **EUT TEST STRATEGY AND METHODOLOGY**

## Test Positions for Device Operating Next to a Person's Ear

This category includes most wireless handsets with fixed, retractable or internal antennas located toward the top half of the device, with or without a foldout, sliding or similar keypad cover. The handset should have its earpiece located within the upper ¼ of the device, either along the centerline or off-centered, as perceived by its users. This type of handset should be positioned in a normal operating position with the "test device reference point" located along the "vertical centerline" on the front of the device aligned to the "ear reference point". The "test device reference point" should be located at the same level as the center of the earpiece region. The "vertical centerline" should bisect the front surface of the handset at its top and bottom edges. A "ear reference point" is located on the outer surface of the head phantom on each ear spacer. It is located 1.5 cm above the center of the ear canal entrance in the "phantom reference plane" defined by the three lines joining the center of each "ear reference point" (left and right) and the tip of the mouth.

Report No: RDG160118001-20

A handset should be initially positioned with the earpiece region pressed against the ear spacer of a head phantom. For the SCC-34/SC-2 head phantom, the device should be positioned parallel to the "N-F" line defined along the base of the ear spacer that contains the "ear reference point". For interim head phantoms, the device should be positioned parallel to the cheek for maximum RF energy coupling. The "test device reference point" is aligned to the "ear reference point" on the head phantom and the "vertical centerline" is aligned to the "phantom reference plane". This is called the "initial ear position". While maintaining these three alignments, the body of the handset is gradually adjusted to each of the following positions for evaluating SAR:



SAR Evaluation Report 25 of 71

#### **Cheek/Touch Position**

The device is brought toward the mouth of the head phantom by pivoting against the "ear reference point" or along the "N-F" line for the SCC-34/SC-2 head phantom.

This test position is established:


When any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom.

Report No: RDG160118001-20

(or) When any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.

For existing head phantoms – when the handset loses contact with the phantom at the pivoting point, rotation should continue until the device touches the cheek of the phantom or breaks its last contact from the ear spacer.

#### **Cheek / Touch Position**




With the handset aligned in the "Cheek/Touch Position":

- 1) If the earpiece of the handset is not in full contact with the phantom's ear spacer (in the "Cheek/Touch position") and the peak SAR location for the "Cheek/Touch" position is located at the ear spacer region or corresponds to the earpiece region of the handset, the device should be returned to the "initial ear position" by rotating it away from the mouth until the earpiece is in full contact with the ear spacer.
- 2) (otherwise) The handset should be moved (translated) away from the cheek perpendicular to the line passes through both "ear reference points" (note: one of these ear reference points may not physically exist on a split head model) for approximate 2-3 cm. While it is in this position, the device handset is tilted away from the mouth with respect to the "test device reference point" until the inside angle between the vertical centerline on the front surface of the phone and the horizontal line passing through the ear reference point is by 15 80°. After the tilt, it is then moved (translated) back toward the head perpendicular to the line passes through both "ear reference points" until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process should be repeated with a tilt angle less than 15° so that the device and its antenna would touch the phantom simultaneously. This test position may require a device holder or positioner to achieve the translation and tilting with acceptable positioning repeatability.

If a device is also designed to transmit with its keypad cover closed for operating in the head position, such positions should also be considered in the SAR evaluation. The device should be tested on the left and right side of the head phantom in the "Cheek/Touch" and "Ear/Tilt" positions. When applicable, each configuration should be tested with the antenna in its fully extended and fully retracted positions. These test configurations should be tested at the high, middle and low frequency channels of each operating mode; for example, AMPS, CDMA, and TDMA. If the SAR measured at the middle channel for each test configuration (left, right, Cheek/Touch, Tilt/Ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s). If the transmission band of the test device is less than 10 MHz, testing at the high and low frequency channels is optional.

SAR Evaluation Report 26 of 71

#### Ear /Tilt 15° Position



#### Test positions for body-worn and other configurations

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. When multiple accessories that do not contain metallic components are supplied with the device, the device may be tested with only the accessory that dictates the closest spacing to the body. When multiple accessories that contain metallic components are supplied with the device, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (e.g., the same metallic belt-clip used with different holsters with no other metallic components), only the accessory that dictates the closest spacing to the body must be tested.

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.




Figure 5 - Test positions for body-worn devices

SAR Evaluation Report 27 of 71

#### **SAR Evaluation Procedure**

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point or central position was used as a reference value for assessing the power drop. The SAR at this point is measured at the start of the test and then again at the end of the testing.

Report No: RDG160118001-20

- Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 4 mm from the inner surface of the shell. The area covered the entire dimension of the head or radiating structures of the EUT, the horizontal grid spacing was 15 mm x 15 mm, and the SAR distribution was determined by integrated grid of 1.5mm x 1.5mm. Based on these data, the area of the maximum absorption was determined by spline interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.
- Step 3: Around this point, a volume of 30 mm x 30 mm x 30 mm was assessed by measuring 7x 7 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:
  - 1) The data at the surface were extrapolated, since the center of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
  - 2) The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one dimensional splines with the "Not a knot"-condition (in x, y and z-directions). The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the averages.

All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement of the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation was repeated.

#### **Test methodology**

KDB 447498 D01 General RF Exposure Guidance v06

KDB 648474 D04 Handset SAR v01r03

KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04

KDB 865664 D02 RF Exposure Reporting v01r02

KDB 941225 D01 3G SAR Procedures v03r01

KDB 941225 D06 Hotspot Mode v02r01

KDB 248227 D01 802.11 Wi-Fi SAR v02r02

SAR Evaluation Report 28 of 71


#### CONDUCTED OUTPUT POWER MEASUREMENT

#### **Provision Applicable**

The measured peak output power should be greater and within 5% than EMI measurement.

#### **Test Procedure**

The RF output of the transmitter was connected to the input of the EMI Test Receiver through sufficient attenuation.



#### **GSM/WCDMA**

### **Radio Configuration**

The power measurement was configured by the Wireless Communication Test Set CMU200 for all Radio configurations except the HSPA+/DC-HSDPA configured by E5515C.

#### **GSM/GPRS**

Menu select > GSM Mobile Station > GSM 850/1900 Function:

Press Connection control to choose the different menus

Press RESET > choose all the reset all settings

Connection Press Signal Off to turn off the signal and change settings Network Support > GSM + GPRS or GSM + EGSM

Network Support > GSIM + GARD

Main Service > Packet Data

Service selection > Test Mode A – Auto Slot Config. off

MS Signal Press Slot Config Bottom on the right twice to select and change the number of

> 33 dBm for GPRS 850 > 30 dBm for GPRS 1900

BS Signal Enter the same channel number for TCH channel (test channel) and BCCH

channel

Frequency Offset > +0 Hz

Mode > BCCH and TCH

BCCH Level > -85 dBm (May need to adjust if link is not stabe)

BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel

(test channel) and BCCH channel]

Channel Type > Off

P0 > 4 dB

Slot Config > Unchanged (if already set under MS signal)

TCH > choose desired test channel

Hopping > Off

SAR Evaluation Report 29 of 71 Main Timeslot >

Network

Coding Scheme > CS4 (GPRS) Bit Stream > AF/RF

2E9-1 PSR Bit Stream Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input Press Signal on to turn on the signal and change settings

#### **WCDMA Release 99**

Connection

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

	Loopback Mode	Test Mode 1			
WCDMA	Rel99 RMC	12.2kbps RMC			
General Settings	Power Control Algorithm	Algorithm2			
	$\beta_c/\beta_d$	8/15			

#### **HSDPA**

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSDPA	HSDPA	HSDPA	HSDPA			
	Subset	1	2	3	4			
	Loopback Mode			Test Mode	1			
	Rel99 RMC			12.2kbps RM	IC .			
	HSDPA FRC			H-Set1				
WCDMA	Power Control Algorithm			Algorithm2	2			
General	$\beta_{\mathrm{c}}$	2/15	12/15	15/15	15/15			
Settings	$\beta_{ ext{d}}$	15/15	15/15	8/15	4/15			
	$\beta_d(SF)$		64					
	$\beta_{\rm c}/\beta_{\rm d}$	2/15	12/15	15/8	15/4			
	$eta_{ m hs}$	4/15	24/15	30/15	30/15			
	MPR(dB)	0	0	0.5	0.5			
	DACK			8				
	DNAK			8				
HSDPA	DCQI			8				
Specific Settings	Ack-Nack repetition factor	3						
Settings	CQI Feedback			4ms				
	CQI Repetition Factor			2				
	Ahs=βhs/ βc			30/15				

**SAR** Evaluation Report 30 of 71

## **HSUPA**

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA			
	Subset	1	2	3	4	5			
	Loopback Mode			Test Mode 1					
	Rel99 RMC		1	2.2kbps RM	C				
	HSDPA FRC			H-Set1					
	HSUPA Test		HS	UPA Loopba	ack				
	Power Control	Algorithm2							
WCDMA	Algorithm		T		1	1			
General	$\beta_{c}$	11/15	6/15	15/15	2/15	15/15			
Settings	$\beta_d$	15/15	15/15	9/15	15/15	0			
	$\beta_{ec}$	209/225	12/15	30/15	2/15	5/15			
	$\beta_c/\beta_d$	11/15	6/15	15/9	2/15	-			
	$eta_{ m hs}$	22/15	12/15	30/15	4/15	5/15			
	CM(dB)	1.0	3.0	2.0	3.0	1.0			
	MPR(dB)	0	2	1	2	0			
	DACK			8					
	DNAK			8					
	DCQI			8					
HSDPA	Ack-Nack	3							
Specific	repetition factor								
Settings	CQI Feedback	4ms							
	CQI Repetition			2					
	Factor								
	Ahs= $\beta_{hs}/\beta_{c}$			30/15	T	1			
	DE-DPCCH	6	8	8	5	7			
	DHARQ	0	0	0	0	0			
	AG Index	20	12	15	17	21			
	ETFCI	75	67	92	71	81			
	Associated Max	242.1	174.9	482.8	205.8	308.9			
	UL Data Rate kbps	9.2.1	1,,	102.0	200.0	200.5			
HSUPA Specific Settings	Reference E_FCls	E-TFCI 11 E E-TFCI PO 4 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27		E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27				

SAR Evaluation Report 31 of 71

Sub- test	β <sub>c</sub> (Note3)	β <sub>d</sub>	β <sub>HS</sub> (Note1)	β <sub>ec</sub>	β <sub>ed</sub> (2xSF2) (Note 4)	β <sub>ed</sub> (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	E-TFCI (boost)
1	1	0	30/15	30/15	β <sub>ed</sub> 1: 30/15 β <sub>ed</sub> 2: 30/15	β <sub>ed</sub> 3: 24/15 β <sub>ed</sub> 4: 24/15	3.5	2.5	14	105	105

Report No: RDG160118001-20

 $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 30/15$  with  $\beta_{hs} = 30/15 * \beta_{c}$ . Note 1:

Note 2: CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0).

DPDCH is not configured, therefore the  $\beta_c$  is set to 1 and  $\beta_d$  = 0 by default. Note 3:

 $\beta_{ed}$  can not be set directly; it is set by Absolute Grant Value. Note 4:

All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-Note 5: DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH

configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm.

The following tests were conducted according to the test requirements in Table C.11.1.4 of 3GPP TS 34.121-1

#### **DC-HSDPA**

The following tests were conducted according to the test requirements in Table C.8.1.12 of 3GPP TS 34.121-1

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Proces	6
	ses	0
Information Bit Payload ( $N_{\mathit{INF}}$ )	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK

Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.

Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.

SAR Evaluation Report 32 of 71

## **Maximum Target Output Power**

	Max Target Power(dBm)							
Mada/Dand	Channel							
Mode/Band	Low	Middle	High					
GSM 850	33.3	33.3	33.3					
GPRS 1 TX Slot	33	33	33					
GPRS 2 TX Slot	32	32	32					
GPRS 3 TX Slot	30.5	30.5	30.5					
GPRS 4 TX Slot	29.4	29.4	29.4					
PCS 1900	30.6	30.6	30.6					
GPRS 1 TX Slot	30.3	30.3	30.3					
GPRS 2 TX Slot	28.5	28.5	28.5					
GPRS 3 TX Slot	27.3	27.3	27.3					
GPRS 4 TX Slot	25.5	25.5	25.5					
WCDMA850	22.6	22.6	22.6					
HSDPA	21.6	21.6	21.6					
HSUPA	21.6	21.6	21.6					
DC-HSDPA	21.4	21.4	21.4					
HSPA+	21.3	21.3	21.3					
WCDMA1900	23	23	23					
HSDPA	22	22	22					
HSUPA	21.9	21.9	21.9					
DC-HSDPA	21.8	21.8	21.8					
HSPA+	21.7	21.7	21.7					
WLAN	18	18	18					
Bluetooth BDR/EDR	5.3	5.3	5.3					
Bluetooth LE	-2.9	-2.9	-2.9					

Report No: RDG160118001-20

SAR Evaluation Report 33 of 71

### **Test Results:**

#### **GSM**:

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)
	128	824.2	32.85
GSM 850	190	836.6	33.03
	251	848.8	33.15
	512	1850.2	30.05
PCS 1900	661	1880	30.51
	810	1909.8	30.35

Report No: RDG160118001-20

### **GPRS:**

Band	Channel	Frequency	]	RF Output P	ower (dBm)	
Dallu	No. (MHz	(MHz)	1 slot	2 slots	3 slots	4 slots
	128	824.2	32.52	31.18	30.21	29.06
GSM 850	190	836.6	32.87	31.81	30.27	28.91
	251	848.8	32.94	31.86	30.41	29.27
	512	1850.2	29.46	28.41	26.76	25.21
PCS 1900	661	1880	30.15	28.4	27.19	25.41
	810	1909.8	29.45	28.02	26.48	25.16

For SAR, the time based average power is relevant, the difference in between depends on the duty cycle of the TDMA signal.

Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Time based Ave. power compared to slotted Ave. power	-9 dB	-6 dB	-4.25 dB	-3 dB
Crest Factor	8	4	2.66	2

## The time based average power for GPRS

Dand	Channel	Frequency (MHz)	Time based average Power (dBm)				
Band	No.		1 slot	2 slot	3 slots	4 slots	
GSM 850	128	824.2	23.52	25.18	25.96	26.06	
	190	836.6	23.87	25.81	26.02	25.91	
	251	848.8	23.94	25.86	26.16	26.27	
PCS 1900	512	1850.2	20.46	22.41	22.51	22.21	
	661	1880	21.15	22.4	22.94	22.41	
	810	1909.8	20.45	22.02	22.23	22.16	

SAR Evaluation Report 34 of 71

## Note:

1. Rohde & Schwarz Radio Communication Tester (CMU200) was used for the measurement of GSM peak and average output power for active timeslots.

Report No: RDG160118001-20

- 2. For GSM voice, 1 timeslot has been activated with power level 5 (850 MHz band) and 0 (1900 MHz band).
- 3. For GPRS, 1, 2, 3 and 4 timeslots has been activated separately with power level 3(850 MHz band) and 3(1900 MHz band).

#### **WCDMA:**

### Results (12.2kbps RMC)

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)
	4132	826.4	22.31
WCDMA 850	4183	836.6	22.51
	4233	846.6	22.28
WCDMA 1900	9262	1852.4	22.58
	9400	1880	22.51
	9538	1907.6	22.88

## **Results (HSDPA)**

D J	Charact Na	Frequency		RF Output Power (dBm)		
Band	Channel No.	(MHz)	Subset 1	Subset 2	Subset 3	Subset 4
WCDMA 850	4132	826.4	21.24	21.17	21.22	21.14
	4183	836.6	21.43	21.45	21.47	21.5
	4233	846.6	21.15	21.23	21.08	21.16
WCDMA 1900	9262	1852.4	21.35	21.4	21.33	21.38
	9400	1880	21.27	21.28	21.31	21.43
	9538	1907.6	21.86	21.79	21.77	21.8

### **Results (HSUPA)**

D 1	Channel	Frequency	RF Output Power (dBm)				
Band	No.	(MHz)	Subset 1	Subset 2	Subset 3	Subset 4	Subset 5
WCDMA 850	4132	826.4	21.16	21.12	21.15	21.11	21.06
	4183	836.6	21.43	21.45	21.42	21.33	21.37
	4233	846.6	21.04	20.97	21.02	21.06	21
WCDMA1900	9262	1852.4	21.41	21.36	21.33	21.42	21.36
	9400	1880	21.38	21.36	21.33	21.24	21.28
	9538	1907.6	21.71	21.73	21.76	21.65	21.74

SAR Evaluation Report 35 of 71

### **Results (DC-HSDPA):**

D d	Charact Na	Frequency	RF Output Power (dBm)				
Band	Channel No.	(MHz)	Subset 1	Subset 2	Subset 3	Subset 4	
WCDMA 850	4132	826.4	21	20.07	21.05	21.02	
	4183	836.6	21.3	21.25	21.28	21.24	
	4233	846.6	20.95	21.01	20.98	20.94	
WCDMA 1900	9262	1852.4	21.3	21.23	21.36	21.38	
	9400	1880	21.23	21.31	21.18	21.21	
	9538	1907.6	21.69	21.62	21.58	21.55	

## **Results (HSPA+)**

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)
	4132	826.4	20.97
WCDMA 850	4183	836.6	21.22
	4233	846.6	20.89
WCDMA 1900	9262	1852.4	21.32
	9400	1880	21.16
	9538	1907.6	21.59

#### Note:

1. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in Test Loop Model 1. 2. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA/HSPA+/DC-HSDPA when the maximum average output of each RF channel is less than  $\frac{1}{4}$  dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is < 75% of SAR limit.

SAR Evaluation Report 36 of 71

# Bluetooth

Mode	Channel	Channel frequency	RF Output Power
Mode	No.	(MHz)	(dBm)
	0	2402	4.57
BDR(GFSK)	39	2441	5.18
	78	2480	5.1
EDR(4-DQPSK)	0	2402	4.18
	39	2441	4.7
	78	2480	4.57
	0	2402	3.66
EDR(8-DPSK)	39	2441	4.31
	78	2480	4.05
	0	2402	-3.44
Bluetooth LE	19	2440	-2.95
	39	2480	-2.95

# WLAN

Mode	Channel No.	Channel frequency (MHz)	RF Output Power (dBm)
	1	2412	17.68
802.11b	6	2437	17.74
	11	2462	17.87
802.11g	1	2412	15.55
	6	2437	15.79
	11	2462	15.67
002.11	1	2412	15.34
802.11n HT20	6	2437	15.62
11120	11	2462	15.88
000 11	3	2422	14.60
802.11n HT40	6	2437	14.37
11140	9	2452	14.28

#### Note:

The output power was tested under data rate 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n HT20, 13.5Mbps for 802.11n HT40.

SAR Evaluation Report 37 of 71

# SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetric evaluation.

The EUT is capable of function as a WLAN to cellular mobile hotspot. Additional SAR test was performed according to KDB941225 D06. Test was performed with a separation of 1cm between the EUT and the flat phantom. The EUT was positioned for SAR tests with the front and back surfaces facing the edge. Each transmit band was utilized for SAR testing. The tested mode has been selected within each band that exhibits the highest time average output power.

Report No: RDG160118001-20

#### **SAR Test Data**

#### **Environmental Conditions**

Temperature:	23.2-23.8	22.3-23.7	22.1-23.4
Relative Humidity:	28 %	30 %	30 %
ATM Pressure:	1012 mbar	1016 mbar	1015 mbar
Test Date:	2016-01-18	2016-01-19	2016-01-20

Testing was performed by Rocky Xiao

SAR Evaluation Report 38 of 71

#### **GSM 850:**

DUT	E	T4	Power	Max.	Max.	1	lg SAR (V	V/Kg)	
EUT Position	Frequency (MHz)	Test Mode	Drift (dB)	Meas. Power (dBm)	Rated Power (dBm)	Scaled Factor	Meas. SAR	Scaled SAR	Plot
	824.2	GSM	/	/	/	/	/	/	/
Left Head Cheek	836.6	GSM	0.18	33.03	33.3	1.064	0.036	0.038	/
1	848.8	GSM	/	/	/	/	/	/	/
	824.2	GSM	/	/	/	/	/	/	/
Left Head Tilt	836.6	GSM	-0.11	33.03	33.3	1.064	0.024	0.026	/
	848.8	GSM	/	/	/	/	/	/	/
	824.2	GSM	0.14	32.85	33.3	1.109	0.042	0.047	/
Right Head Cheek	836.6	GSM	0.15	33.03	33.3	1.064	0.044	0.047	/
	848.8	GSM	0.03	33.15	33.3	1.035	0.047	0.049	1#
	824.2	GSM	/	/	/	/	1	/	/
Right Head Tilt	836.6	GSM	-0.06	33.03	33.3	1.064	0.027	0.029	/
	848.8	GSM	/	/	/	/	1	/	/
	824.2	GSM	/	/	1	/	/	/	/
Body-Back-Headset (10mm)	836.6	GSM	0.11	33.03	33.3	1.064	0.369	0.393	/
(1011111)	848.8	GSM	/	/	/	/	/	/	/
	824.2	GPRS	0.13	29.06	29.4	1.081	0.446	0.482	/
Body-Back (10mm)	836.6	GPRS	0.14	28.91	29.4	1.119	0.428	0.479	/
(Tollill)	848.8	GPRS	-0.15	29.27	29.4	1.03	0.481	0.495	2#
	824.2	GPRS	/	/	/	/	/	/	/
Body-Left (10mm)	836.6	GPRS	-0.15	28.91	29.4	1.119	0.126	0.141	/
(Tollill)	848.8	GPRS	1	/	/	/	/	/	/
	824.2	GPRS	/	/	/	/	/	/	/
Body-Right (10mm)	836.6	GPRS	0.08	28.91	29.4	1.119	0.082	0.092	/
(1011111)	848.8	GPRS	/	/	/	/	/	/	/
	824.2	GPRS	/	/	/	/	/	/	/
Body-Bottom (10mm)	836.6	GPRS	0.03	28.91	29.4	1.119	0.213	0.217	/
(1011111)	848.8	GPRS	/	/	/	/	/	/	/

#### Note:

- 1. When the 1-g SAR is  $\leq$  0.8W/Kg, testing for other channels are optional.
- 2. The EUT transmit and receive through the same GSM antenna while testing SAR.
- 3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
- 4. When the maximum output power variation across the required test channels is > ½ dB, instead of the middle channel, the highest output power channel must be used.
- 5. The Multi-slot Classes of EUT is Class 12 which has maximum 4 Downlink slots and 4 Uplink slots, the maximum active slots is 5, when perform the multiple slots scan, 1DL+4UL is the worst case.

SAR Evaluation Report 39 of 71

#### PCS 1900:

EUT	E	Т4	Power	Max.	Max.	1	lg SAR (V	V/Kg)	
EUT Position	Frequency (MHz)	Test Mode	Drift (dB)	Meas. Power (dBm)	Rated Power (dBm)	Scaled Factor	Meas. SAR	Scaled SAR	Plot
	1850.2	GSM	0.2	30.05	30.6	1.135	0.086	0.098	/
Left Head Cheek	1880	GSM	0.16	30.51	30.6	1.021	0.098	0.1	3#
	1909.8	GSM	0.02	30.35	30.6	1.059	0.092	0.097	/
	1850.2	GSM	/	/	/	/	/	/	/
Left Head Tilt	1880	GSM	-0.02	30.51	30.6	1.021	0.064	0.065	/
	1909.8	GSM	/	/	/	/	/	/	/
	1850.2	GSM	/	/	/	/	/	/	/
Right Head Cheek	1880	GSM	-0.02	30.51	30.6	1.021	0.088	0.09	/
	1909.8	GSM	/	/	/	/	/	/	/
	1850.2	GSM	/	/	/	/	1	/	/
Right Head Tilt	1880	GSM	0.05	30.51	30.6	1.021	0.059	0.06	/
	1909.8	GSM	/	/	/	/	/	/	/
	1850.2	GSM	/	/	1	/	/	/	/
Body-Back-Headset (10mm)	1880	GSM	-0.06	30.51	30.6	1.021	0.421	0.43	/
(1011111)	1909.8	GSM	/	/	/	/	/	/	/
	1850.2	GPRS	0.12	26.76	27.3	1.132	0.433	0.49	/
Body-Back (10mm)	1880	GPRS	-0.08	27.19	27.3	1.026	0.496	0.509	4#
(1011111)	1909.8	GPRS	0.07	26.48	27.3	1.208	0.405	0.489	/
	1850.2	GPRS	/	/	/	/	/	/	/
Body-Left (10mm)	1880	GPRS	-0.14	27.19	27.3	1.026	0.161	0.165	/
(1011111)	1909.8	GPRS	1	/	/	/	/	/	/
	1850.2	GPRS	/	/	/	/	/	/	/
Body-Right (10mm)	1880	GPRS	-0.15	27.19	27.3	1.026	0.122	0.125	/
(	1909.8	GPRS	/	/	/	/	/	/	/
	1850.2	GPRS	/	/	/	/	/	/	/
Body-Bottom (10mm)	1880	GPRS	0.15	27.19	27.3	1.026	0.225	0.234	/
(	1909.8	GPRS	/	/	/	/	/	/	/

#### Note:

- 1. When the 1-g SAR is  $\leq$  0.8W/Kg, testing for other channels are optional.
- 2. The EUT transmit and receive through the same GSM antenna while testing SAR.
- 3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
- 4. When the maximum output power variation across the required test channels is > ½ dB, instead of the middle channel, the highest output power channel must be used.
- 5. The Multi-slot Classes of EUT is Class 12 which has maximum 4 Downlink slots and 4 Uplink slots, the maximum active slots is 5, when perform the multiple slots scan, 2DL+3UL is the worst case.

SAR Evaluation Report 40 of 71

#### **WCDMA 850:**

EUT	E	Test	Power	Max. Meas.	Max. Rated	1	lg SAR (V	V/Kg)	
Position	Frequency (MHz)	Mode	Drift (dB)	Power (dBm)	Power (dBm)	Scaled Factor	Meas. SAR	Scaled SAR	Plot
	826.4	RMC	/	/	/	/	/	/	/
Left Head Cheek	836.6	RMC	-0.2	22.51	22.6	1.021	0.068	0.069	/
	846.6	RMC	/	/	/	/	/	/	/
	826.4	RMC	/	/	/	/	/	/	/
Left Head Tilt	836.6	RMC	-0.09	22.51	22.6	1.021	0.045	0.046	/
	846.6	RMC	/	/	/	/	/	/	/
	826.4	RMC	0.18	22.31	22.6	1.069	0.074	0.079	/
Right Head Cheek	836.6	RMC	-0.09	22.51	22.6	1.021	0.08	0.082	5#
	846.6	RMC	0.18	22.28	22.6	1.076	0.074	0.08	/
	826.4	RMC	/	/	/	/	1	/	/
Right Head Tilt	836.6	RMC	-0.09	22.51	22.6	1.021	0.053	0.054	/
	846.6	RMC	/	/	/	/	1	/	/
	826.4	RMC	0.15	22.31	22.6	1.069	0.323	0.345	/
Body-Back (10mm)	836.6	RMC	-0.16	22.51	22.6	1.021	0.35	0.357	6#
(1011111)	846.6	RMC	0.18	22.28	22.6	1.076	0.325	0.35	/
	826.4	RMC	/	/	/	/	/	/	/
Body-Left (10mm)	836.6	RMC	0.03	22.51	22.6	1.021	0.108	0.11	/
(1011111)	846.6	RMC	/	/	/	/	/	/	/
	826.4	RMC	/	/	/	/	/	/	/
Body-Right (10mm)	836.6	RMC	0.13	22.51	22.6	1.021	0.063	0.064	/
(1011111)	846.6	RMC	1	/	/	/	/	/	/
	826.4	RMC	/	/	/	/	/	/	/
Body-Bottom (10mm)	836.6	RMC	-0.17	22.51	22.6	1.021	0.172	0.173	/
(1011111)	846.6	RMC	/	/	/	/	/	/	/

# Note:

- 1. When the 1-g SAR is  $\leq$  0.8W/Kg, testing for other channels are optional.
- 2. The EUT transmit and receive through the same antenna while testing SAR.
- 3. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in Test Loop Model.
- 4. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA/HSPA+/DC-HSDPA when the maximum average output of each RF channel is less than ¼ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is < 75% of SAR limit.
- 5. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.

SAR Evaluation Report 41 of 71

#### WCDMA 1900:

EUT	Frequency	Test	Power	Max. Meas.	Max. Rated	1	lg SAR (V	V/Kg)	
Position	(MHz)	Mode	Drift (dB)	Power (dBm)	Power (dBm)	Scaled Factor	Meas. SAR	Scaled SAR	Plot
	1852.4	RMC	0.06	22.58	23	1.102	0.152	0.168	/
Left Head Cheek	1880	RMC	0.02	22.51	23	1.119	0.152	0.17	/
	1907.6	RMC	0.14	22.88	23	1.028	0.17	0.175	7#
	1852.4	RMC	/	/	/	/	/	/	/
Left Head Tilt	1880	RMC	-0.17	22.51	23	1.119	0.092	0.103	/
	1907.6	RMC	/	/	/	/	/	/	/
	1852.4	RMC	/	/	/	/	/	/	/
Right Head Cheek	1880	RMC	0.19	22.51	23	1.119	0.135	0.151	/
	1907.6	RMC	/	/	/	/	/	/	/
	1852.4	RMC	/	/	/	/	1	/	/
Right Head Tilt	1880	RMC	-0.06	22.51	23	1.119	0.093	0.104	/
	1907.6	RMC	/	/	/	/	/	/	/
	1852.4	RMC	0.01	22.58	23	1.102	0.864	0.952	/
Body-Back (10mm)	1880	RMC	0.15	22.51	23	1.119	0.855	0.957	/
(1011111)	1907.6	RMC	-0.13	22.88	23	1.028	0.967	0.994	8#
	1852.4	RMC	/	/	/	/	/	/	/
Body-Left (10mm)	1880	RMC	-0.03	22.51	23	1.119	0.249	0.279	/
(1011111)	1907.6	RMC	/	/	/	/	/	/	/
	1852.4	RMC	/	/	/	/	/	/	/
Body-Right (10mm)	1880	RMC	-0.14	22.51	23	1.119	0.191	0.214	/
(1011111)	1907.6	RMC	1	/	/	/	/	/	/
	1852.4	RMC	/	/	/	/	/	/	/
Body-Bottom (10mm)	1880	RMC	0.05	22.51	23	1.119	0.414	0.464	/
(1011111)	1907.6	RMC	/	/	/	/	/	/	/

# Note:

- 1. When the 1-g SAR is  $\leq$  0.8W/Kg, testing for other channels are optional.
- 2. The EUT transmit and receive through the same antenna while testing SAR.
- 3. The default test configuration is to measure SAR with an established radio link between the EUT and a
- communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in Test Loop Model. 4. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA/HSPA+/DC-HSDPA when the maximum average output of each RF channel is less than ½ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is < 75% of SAR limit.
- 5. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.

SAR Evaluation Report 42 of 71

#### WLAN:

EUT	Frequency	Test	Power	Max. Meas.	Max. Rated		1g SAR (	W/Kg)	
Position	(MHz)	Mode	Drift (dB)	Power (dBm)	Power (dBm)	Scaled Factor	Meas. SAR	Scaled SAR	Plot
	2412	802.11b	0.18	17.68	18	1.076	0.336	0.362	/
Left Head Cheek	2437	802.11b	0.05	17.74	18	1.062	0.342	0.363	/
	2462	802.11b	0.1	17.87	18	1.03	0.369	0.38	9#
	2412	802.11b	/	/	/	/	/	/	/
Left Head Tilt	2437	802.11b	0.11	17.74	18	1.062	0.303	0.322	/
	2462	802.11b	/	/	/	/	/	/	/
	2412	802.11b	/	/	/	/	/	/	/
Right Head Cheek	2437	802.11b	-0.01	17.74	18	1.062	0.314	0.333	/
	2462	802.11b	/	/	/	/	/	/	/
	2412	802.11b	/	/	/	/	/	1	/
Right Head Tilt	2437	802.11b	0.14	17.74	18	1.062	0.286	0.304	/
	2462	802.11b	/	/	/	/	1	/	/
	2412	802.11b	0.01	17.68	18	1.076	0.182	0.196	/
Body-Back (10mm)	2437	802.11b	0.04	17.74	18	1.062	0.18	0.191	/
(1011111)	2462	802.11b	0.04	17.87	18	1.03	0.196	0.202	10#
	2412	802.11b	/	/	/	/	/	/	/
Body-Right (10mm)	2437	802.11b	-0.17	17.74	18	1.062	0.132	0.14	/
(10)	2462	802.11b	/	/	/	/	/	/	/
	2412	802.11b	/	/	/	/	/	/	/
Body-Top (10mm)	2437	802.11b	-0.05	17.74	18	1.062	0.09	0.096	/
(10)	2462	802.11b	1	/	/	/	/	/	/

# Note:

SAR Evaluation Report 43 of 71

<sup>1.</sup> When the 1-g SAR is  $\leq$  0.8 W/Kg, testing for other channels are optional.

<sup>2.</sup> When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.

<sup>3.</sup>KDB248227-SAR is not required for 802.11g channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11b channels.

# **SAR Measurement Variability**

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz v01. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results

Report No: RDG160118001-20

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurement is > 1.20 or when the original or repeated measurement is  $\ge 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.

### The Highest Measured SAR Configuration in Each Frequency Band

#### Head

			Meas. SA	Largest to	
Frequency Band	Freq.(MHz)	EUT Position	Original	Repeated	Smallest SAR Ratio
/	/	/	/	/	/

#### **Body**

			Meas. SA	Largest to		
Frequency Band	ncy Band Freq.(MHz)		Original	Repeated	Smallest SAR Ratio	
WCDMA Band 1900	1880	Back	0.994	0.953	1.043	

#### Note:

Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not > 1.20.

SAR Evaluation Report 44 of 71

# SAR SIMULTANEOUS TRANSMISSION DESCRIPTION





# **Simultaneous Transmission:**

Description of Simult	taneous Transmit Capa	abilities	A dama Distance (com)
Transmitter Combination	Simultaneous?	Hotspot?	Antennas Distance (mm)
GSM + WCDMA	×	×	0
GSM + Bluetooth	$\checkmark$	×	125
GSM + WLAN	$\sqrt{}$	$\checkmark$	125
WCDMA + Bluetooth	$\sqrt{}$	×	125
WCDMA + WLAN	√	√	125

SAR Evaluation Report 45 of 71

#### Standalone SAR test exclusion considerations

Mode	Frequency (MHz)	Pavg (dBm)	Pavg (mW)	Distance (mm)	Calculated value	Threshold (1-g)	SAR Test Exclusion
Bluetooth	2480	5.3	3.39	0	1.1	3	YES

Report No: RDG160118001-20

#### NOTE:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

[( max. power of channel, including tune-up tolerance, mW )/( min. test separation distance, mm)] ·

 $[\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where

- 1. f(GHz) is the RF channel transmit frequency in GHz.
- 2. Power and distance are rounded to the nearest mW and mm before calculation.
- 3. The result is rounded to one decimal place for comparison.
- 4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

#### **Standalone SAR estimation:**

Mode	Frequency (MHz)	Pavg (dBm)	Pavg (mW)	Distance (mm)	Estimated 1-g (W/kg)
BT Head	2480	5.3	3.39	0	0.147
BT Body	2480	5.3	3.39	10	0.074

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

[( max. power of channel, including tune-up tolerance , mW)/( min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)/x}]$ 

W/kg for test separation distances ≤50 mm;

where x = 7.5 for 1-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion

SAR Evaluation Report 46 of 71

# Simultaneous and Hotspot SAR test exclusion considerations:

Mode(SAR1+SAR2)	Position	Reported S	ΣSAR < 1.6W/kg	
		SAR1	SAR2	
	Left Head Cheek	0.038	0.147	0.185
	Left Head Tilt	0.026	0.147	0.173
GSM 850+Bluetooth	Right Head Cheek	0.049	0.147	0.196
	Right Head Tilt	0.029	0.147	0.176
	Body-Back-Headset	0.393	0.074	0.467
	Body-Back	0.495	0.074	0.569
GPRS 850 + Bluetooth	Body- Left	0.141	0.074	0.215
GPRS 830 + Diuetootii	Body- Right	0.092	0.074	0.166
	Body-Bottom	0.217	0.074	0.291
	Left Head Cheek	0.1	0.147	0.247
	Left Head Tilt	0.065	0.147	0.212
PCS1900 +Bluetooth	Right Head Cheek	0.09	0.147	0.237
	Right Head Tilt	0.06	0.147	0.207
	Body-Back-Headset	0.43	0.074	0.504
	Body-Back	0.509	0.074	0.583
GPRS 1900 + Bluetooth	Body- Left	0.165	0.074	0.239
GPRS 1900 + Bluetootil	Body- Right	0.125	0.074	0.199
	Body-Bottom	0.234	0.074	0.308
	Left Head Cheek	0.069	0.147	0.216
	Left Head Tilt	0.046	0.147	0.193
	Right Head Cheek	0.082	0.147	0.229
WCDMA 850+Bluetooth	Right Head Tilt	0.054	0.147	0.201
WCDMA 850+Bluetooth	Body-Back	0.357	0.074	0.431
	Body- Left	0.11	0.074	0.184
	Body- Right	0.064	0.074	0.138
	Body-Bottom	0.173	0.074	0.247
	Left Head Cheek	0.175	0.147	0.322
	Left Head Tilt	0.103	0.147	0.25
	Right Head Cheek	0.151	0.147	0.298
WCDMA 1900+Bluetooth	Right Head Tilt	0.104	0.147	0.251
WCDIVIA 1900+DIUCIOOIII	Body-Back	0.994	0.074	1.068
	Body- Left	0.279	0.074	0.353
	Body- Right	0.214	0.074	0.288
	Body-Bottom	0.464	0.074	0.538

Report No: RDG160118001-20

SAR Evaluation Report 47 of 71

Mode(SAR1+SAR2)	Position	Reported S	ΣSAR < 1.6W/kg	
		SAR1	SAR2	1.0 W/Kg
	Left Head Cheek	0.038	0.38	0.418
	Left Head Tilt	0.026	0.322	0.348
GSM 850+ WLAN	Right Head Cheek	0.049	0.333	0.382
	Right Head Tilt	0.029	0.304	0.333
	Body-Back-Headset	0.393	0.202	0.595
GPRS 850 + WLAN	Body-Back	0.495	0.202	0.697
(Hotspot)	Body- Right	0.092	0.14	0.232
	Left Head Cheek	0.1	0.38	0.48
	Left Head Tilt	0.065	0.322	0.387
PCS1900 + WLAN	Right Head Cheek	0.09	0.333	0.423
	Right Head Tilt	0.06	0.304	0.364
	Body-Back-Headset	0.43	0.202	0.632
GPRS 1900 + WLAN	Body-Back	0.509	0.202	0.711
(Hotspot)	Body- Right	0.125	0.14	0.265
	Left Head Cheek	0.069	0.38	0.449
WCDMA 850+ WLAN	Left Head Tilt	0.046	0.322	0.368
WCDMA 650+ WLAN	Right Head Cheek	0.082	0.333	0.415
	Right Head Tilt	0.054	0.304	0.358
WCDMA 850+ WLAN	Body-Back	0.357	0.202	0.559
(Hotspot)	Body- Right	0.064	0.14	0.204
	Left Head Cheek	0.175	0.38	0.555
WCDMA 1900+ WLAN	Left Head Tilt	0.103	0.322	0.425
	Right Head Cheek	0.151	0.333	0.484
	Right Head Tilt	0.104	0.304	0.408
WCDMA 1900+ WLAN	Body-Back	0.994	0.202	1.196
(Hotspot)	Body- Right	0.214	0.14	0.354

### **Note:**

- Hotspot mode SAR is only required for the edges within 25mm from the transmitting antenna located.
   Hotspot mode SAR is applicable for data transmission mode not for voice call mode, therefor, head use condition is not required for hotspot mode.

# **Conclusion:**

SAR < 1.6 W/kg therefore simultaneous transmission SAR with Volume Scans is **not** required.

SAR Evaluation Report 48 of 71

Test Plot 1#: GSM 850 Right Cheek High Channel

DUT: Icon Pro HD; Type: X551;

Communication System: Generic GSM; Frequency: 846.6 MHz; Duty Cycle: 1:8 Medium parameters used: f = 846.6 MHz;  $\sigma = 0.896$  S/m;  $\varepsilon_r = 42.832$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

### DASY5 Configuration:

• Probe: EX3DV4 - SN7329; ConvF(9.52, 9.52, 9.52); Calibrated: 2015/2/5;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1459; Calibrated: 2015/9/18

Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874

Report No: RDG160118001-20

• Measurement SW: DASY52, Version 52.8 (8);

**Head/GSM 850 Right Cheek/Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm Maximum value of SAR (interpolated) = 0.0483 W/kg


Head/GSM 850 Right Cheek/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.259 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.0570 W/kg

SAR(1 g) = 0.047 W/kg; SAR(10 g) = 0.037 W/kg

Maximum value of SAR (measured) = 0.0495 W/kg



0 dB = 0.0495 W/kg = -13.05 dBW/kg

SAR Evaluation Report 49 of 71

### Test Plot 2#: GSM 850 Back High Channel

### DUT: Icon Pro HD; Type: X551;

Communication System: Generic GPRS-4 slots; Frequency: 846.6 MHz; Duty Cycle: 1:2 Medium parameters used: f = 846.6 MHz;  $\sigma = 0.985$  S/m;  $\varepsilon_r = 55.037$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

#### DASY5 Configuration:

- Probe: EX3DV4 SN7329; ConvF(9.17, 9.17, 9.17); Calibrated: 2015/2/5;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2015/9/18
- Phantom: SAM (30deg probe tilt) with CRP v5.0 20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Body/GSM 850 Back/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.531 W/kg


Body/GSM 850 Back/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.28 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.920 W/kg

SAR(1 g) = 0.481 W/kg; SAR(10 g) = 0.258 W/kg

Maximum value of SAR (measured) = 0.528 W/kg



0 dB = 0.528 W/kg = -2.77 dBW/kg

SAR Evaluation Report 50 of 71

#### Test Plot 3#: PCS 1900 Left Cheek Middle Channel

### DUT: Icon Pro HD; Type: X551;

Communication System: Generic GSM; Frequency: 1880 MHz; Duty Cycle: 1:8 Medium parameters used: f = 1880 MHz;  $\sigma = 1.388$  S/m;  $\varepsilon_r = 39.734$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

#### DASY5 Configuration:

- Probe: EX3DV4 SN7329; ConvF(7.88, 7.88, 7.88); Calibrated: 2015/2/5;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2015/9/18
- Phantom: SAM (30deg probe tilt) with CRP v5.0 20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Head/PCS 1900 Left Cheek/Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm Maximum value of SAR (interpolated) = 0.107 W/kg


Head/PCS 1900 Left Cheek/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.248 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.172 W/kg

SAR(1 g) = 0.098 W/kg; SAR(10 g) = 0.059 W/kg

Maximum value of SAR (measured) = 0.107 W/kg



0 dB = 0.107 W/kg = -9.71 dBW/kg

SAR Evaluation Report 51 of 71

#### Test Plot 4#: PCS 1900 Back Middle Channel

### DUT: Icon Pro HD; Type: X551;

Communication System: Generic GPRS-3 slots; Frequency: 1880 MHz; Duty Cycle: 1:2.66 Medium parameters used: f = 1880 MHz;  $\sigma = 1.542$  S/m;  $\epsilon_r = 53.741$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

#### DASY5 Configuration:

- Probe: EX3DV4 SN7329; ConvF(7.56, 7.56, 7.56); Calibrated: 2015/2/5;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2015/9/18
- Phantom: SAM (30deg probe tilt) with CRP v5.0 20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Body/PCS 1900 Back/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.546 W/kg


Body/PCS 1900 Back/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.130 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.953 W/kg

SAR(1 g) = 0.496 W/kg; SAR(10 g) = 0.242 W/kg

Maximum value of SAR (measured) = 0.547 W/kg



0 dB = 0.547 W/kg = -2.62 dBW/kg

SAR Evaluation Report 52 of 71

### Test Plot 5#: WCDMA 850 Right Cheek Middle Channel

### DUT: Icon Pro HD; Type: X551;

Communication System: Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: f = 836.6 MHz;  $\sigma = 0.892 \text{ S/m}$ ;  $\varepsilon_r = 42.85$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Right Section

#### DASY5 Configuration:

• Probe: EX3DV4 - SN7329; ConvF(9.52, 9.52, 9.52); Calibrated: 2015/2/5;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1459; Calibrated: 2015/9/18

• Phantom: SAM (30deg probe tilt) with CRP v5.0 20150321; Type: QD000P40CD; Serial: TP:1874

• Measurement SW: DASY52, Version 52.8 (8);

**Head/WCDMA 850 Right Cheek/Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm Maximum value of SAR (interpolated) = 0.0809 W/kg


Head/WCDMA 850 Right Cheek/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.495 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.0990 W/kg

SAR(1 g) = 0.080 W/kg; SAR(10 g) = 0.061 W/kg

Maximum value of SAR (measured) = 0.0842 W/kg



0 dB = 0.0842 W/kg = -10.75 dBW/kg

SAR Evaluation Report 53 of 71

#### Test Plot 6#: WCDMA 850 Back Middle Channel

### DUT: Icon Pro HD; Type: X551;

Communication System: Band V; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used: f = 836.6 MHz;  $\sigma = 0.976 \text{ S/m}$ ;  $\varepsilon_r = 55.123$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

#### DASY5 Configuration:

• Probe: EX3DV4 - SN7329; ConvF(9.17, 9.17, 9.17); Calibrated: 2015/2/5;

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2015/9/18
- Phantom: SAM (30deg probe tilt) with CRP v5.0 20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

Body/WCDMA 850 Back/Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.351 W/kg


Body/WCDMA 850 Back/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.33 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 0.680 W/kg

SAR(1 g) = 0.350 W/kg; SAR(10 g) = 0.187 W/kg

Maximum value of SAR (measured) = 0.400 W/kg



0 dB = 0.400 W/kg = -3.98 dBW/kg

SAR Evaluation Report 54 of 71

### Test Plot 7#: WCDMA 1900 Left Cheek High Channel

### DUT: Icon Pro HD; Type: X551;

Communication System: Band II; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used: f = 1907.6 MHz;  $\sigma = 1.413$  S/m;  $\varepsilon_r = 39.582$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

#### DASY5 Configuration:

• Probe: EX3DV4 - SN7329; ConvF(7.88, 7.88, 7.88); Calibrated: 2015/2/5;

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2015/9/18
- Phantom: SAM (30deg probe tilt) with CRP v5.0 20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Head/WCDMA 1900 Left Cheek/Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm Maximum value of SAR (interpolated) = 0.183 W/kg


Head/WCDMA 1900 Left Cheek/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.853 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.278 W/kg

SAR(1 g) = 0.170 W/kg; SAR(10 g) = 0.102 W/kg

Maximum value of SAR (measured) = 0.185 W/kg



0 dB = 0.185 W/kg = -7.33 dBW/kg

SAR Evaluation Report 55 of 71

### Test Plot 8#: WCDMA 1900 Back High Channel

### DUT: Icon Pro HD; Type: X551;

Communication System: Band II; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used: f = 1907.6 MHz;  $\sigma = 1.492$  S/m;  $\varepsilon_r = 53.601$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

#### DASY5 Configuration:

• Probe: EX3DV4 - SN7329; ConvF(7.56, 7.56, 7.56); Calibrated: 2015/2/5;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1459; Calibrated: 2015/9/18

• Phantom: SAM (30deg probe tilt) with CRP v5.0 20150321; Type: QD000P40CD; Serial: TP:1874

• Measurement SW: DASY52, Version 52.8 (8);

**Body/WCDMA 1900 Back/Area Scan (71x121x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm Maximum value of SAR (interpolated) = 0.883 W/kg


Body/WCDMA 1900 Back/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.34 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 2.19 W/kg

SAR(1 g) = 0.967 W/kg; SAR(10 g) = 0.410 W/kg

Maximum value of SAR (measured) = 1.07 W/kg



0 dB = 1.07 W/kg = 0.29 dBW/kg

SAR Evaluation Report 56 of 71

### Test Plot 9#: WLAN B Mode Left Cheek High Channel

### DUT: Icon Pro HD; Type: X551;

Communication System: CW; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used: f = 2462 MHz;  $\sigma = 1.841$  S/m;  $\varepsilon_r = 39$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

#### DASY5 Configuration:

• Probe: EX3DV4 - SN7329; ConvF(7.06, 7.06, 7.06); Calibrated: 2015/2/5;

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1459; Calibrated: 2015/9/18
- Phantom: SAM (30deg probe tilt) with CRP v5.0 20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.8 (8);

**Head/WLAN\_B Mode Left Cheek/Area Scan (105x180x1):** Interpolated grid: dx=1.00 mm, dy=1.00 mm Maximum value of SAR (interpolated) = 0.433 W/kg


Head/WLAN B Mode Left Cheek/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.514 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.776 W/kg

SAR(1 g) = 0.369 W/kg; SAR(10 g) = 0.189 W/kg

Maximum value of SAR (measured) = 0.406 W/kg



0 dB = 0.406 W/kg = -3.91 dBW/kg

SAR Evaluation Report 57 of 71

### Test Plot 10#: WLAN B Mode Back High Channel

### DUT: Icon Pro HD; Type: X551;

Communication System: CW; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used: f = 2462 MHz;  $\sigma = 1.98$  S/m;  $\varepsilon_r = 52.216$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

#### DASY5 Configuration:

Probe: EX3DV4 - SN7329; ConvF(7.2, 7.2, 7.2); Calibrated: 2015/2/5;

• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1459; Calibrated: 2015/9/18

• Phantom: SAM (30deg probe tilt) with CRP v5.0 20150321; Type: QD000P40CD; Serial: TP:1874

• Measurement SW: DASY52, Version 52.8 (8);

**Body/WLAN\_B Mode Back/Area Scan (105x180x1):** Interpolated grid: dx=1.00 mm, dy=1.00 mm Maximum value of SAR (interpolated) = 0.219 W/kg


Body/ WLAN B Mode Back/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.506 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.409 W/kg

SAR(1 g) = 0.196 W/kg; SAR(10 g) = 0.096 W/kg

Maximum value of SAR (measured) = 0.218 W/kg



0 dB = 0.218 W/kg = -6.62 dBW/kg

SAR Evaluation Report 58 of 71

# APPENDIX A MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the measurement system and is given in the following Table.

Report No: RDG160118001-20

# Measurement uncertainty evaluation for IEEE1528-2013 SAR test

Source of uncertainty	Tolerance/ uncertainty ± %	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard uncertainty ± %, (1 g)	Standard uncertainty ± %, (10 g)	
Measurement system								
Probe calibration	6.55	N	1	1	1	6.6	6.6	
Axial Isotropy	4.7	R	√3	1	1	2.7	2.7	
Hemispherical Isotropy	9.6	R	√3	0	0	0.0	0.0	
Boundary effect	1.0	R	√3	1	1	0.6	0.6	
Linearity	4.7	R	√3	1	1	2.7	2.7	
Detection limits	1.0	R	√3	1	1	0.6	0.6	
Readout electronics	0.3	N	1	1	1	0.3	0.3	
Response time	0.0	R	√3	1	1	0.0	0.0	
Integration time	0.0	R	√3	1	1	0.0	0.0	
RF ambient conditions – noise	1.0	R	√3	1	1	0.6	0.6	
RF ambient conditions–reflections	1.0	R	√3	1	1	0.6	0.6	
Probe positioner mech. Restrictions	0.8	R	√3	1	1	0.5	0.5	
Probe positioning with respect to phantom shell	6.7	R	√3	1	1	3.9	3.9	
Post-processing	2.0	R	√3	1	1	1.2	1.2	
		Test sample	e related					
Test sample positioning	2.8	N	1	1	1	2.8	2.8	
Device holder uncertainty	6.3	N	1	1	1	6.3	6.3	
Drift of output power	5.0	R	√3	1	1	2.9	2.9	
		Phantom an	nd set-up					
Phantom uncertainty (shape and thickness tolerances)	4.0	R	√3	1	1	2.3	2.3	
Liquid conductivity target)	5.0	R	√3	0.64	0.43	1.8	1.2	
Liquid conductivity meas.)	2.5	N	1	0.64	0.43	1.6	1.1	
Liquid permittivity target)	5.0	R	√3	0.6	0.49	1.7	1.4	
Liquid permittivity meas.)	2.5	N	1	0.6	0.49	1.5	1.2	
Combined standard uncertainty		RSS				12.2	12.0	
Expanded uncertainty 95 % confidence interval)						24.3	23.9	

SAR Evaluation Report 59 of 71

# Measurement uncertainty evaluation for IEC62209-2 SAR test

Source of uncertainty	Tolerance/ uncertainty ± %	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard uncertainty ± %, (1 g)	Standard uncertainty ± %, (10 g)	
Measurement system								
Probe calibration	6.55	N	1	1	1	6.6	6.6	
Axial Isotropy	4.7	R	√3	1	1	2.7	2.7	
Hemispherical Isotropy	9.6	R	√3	0	0	0.0	0.0	
Linearity	4.7	R	√3	1	1	2.7	2.7	
Modulation Response	0.0	R	√3	1	1	0.0	0.0	
Detection limits	1.0	R	√3	1	1	0.6	0.6	
Boundary effect	1.0	R	√3	1	1	0.6	0.6	
Readout electronics	0.3	N	1	1	1	0.3	0.3	
Response time	0.0	R	√3	1	1	0.0	0.0	
Integration time	0.0	R	√3	1	1	0.0	0.0	
RF ambient conditions – noise	1.0	R	√3	1	1	0.6	0.6	
RF ambient conditions–reflections	1.0	R	√3	1	1	0.6	0.6	
Probe positioner mech. Restrictions	0.8	R	√3	1	1	0.5	0.5	
Probe positioning with respect to phantom shell	6.7	R	√3	1	1	3.9	3.9	
Post-processing	2.0	R	√3	1	1	1.2	1.2	
		Test sample	related					
Device holder Uncertainty	6.3	N	1	1	1	6.3	6.3	
Test sample positioning	2.8	N	1	1	1	2.8	2.8	
Power scaling	4.5	R	√3	1	1	2.6	2.6	
Drift of output power	5.0	R	√3	1	1	2.9	2.9	
		Phantom an	d set-up					
Phantom uncertainty (shape and thickness tolerances)	4.0	R	√3	1	1	2.3	2.3	
Algorithm for correcting SAR for deviations in permittivity and conductivity	1.9	N	1	1	0.84	1.1	0.9	
Liquid conductivity (meas.)	2.5	N	1	0.64	0.43	1.6	1.1	
Liquid permittivity (meas.)	2.5	N	1	0.6	0.49	1.5	1.2	
Temp. unc Conductivity	1.7	R	√3	0.78	0.71	0.8	0.7	
Temp. unc Permittivity	0.3	R	√3	0.23	0.26	0.0	0.0	
Combined standard uncertainty		RSS				12.2	12.1	
Expanded uncertainty 95 % confidence interval)						24.5	24.2	

SAR Evaluation Report 60 of 71

# APPENDIX B EUT TEST POSITION PHOTOS

 $Liquid\ depth \geq 15cm$ 



**Body-worn Back Setup Photo** 



SAR Evaluation Report 61 of 71

# **Body-worn Left Setup Photo**



**Body-worn Right Setup Photo** 



SAR Evaluation Report 62 of 71

# **Body-worn Headset Setup Photo**



**Body-worn Bottom Setup Photo** 




SAR Evaluation Report 63 of 71

# **Body-worn Top Setup Photo**



SAR Evaluation Report 64 of 71

# **Left Head Touch Setup Photo**



**Left Head Tilt Setup Photo** 



SAR Evaluation Report 65 of 71

# **Right Head Touch Setup Photo**



**Right Head Tilt Setup Photo** 



SAR Evaluation Report 66 of 71

# **APPENDIX C EUT PHOTOS**

**EUT - Front View** 



**EUT -Back View** 



SAR Evaluation Report 67 of 71

**EUT – Side View-1** 



**EUT – Side View-2** 



SAR Evaluation Report 68 of 71

**EUT – Side View-3** 



**EUT – Side View-4** 



SAR Evaluation Report 69 of 71

**EUT – Cover off View** 



EUT - BT&WLAN Antenna View



SAR Evaluation Report 70 of 71

# **APPENDIX D CALIBRATION CERTIFICATES**

Please Refer to the Attachment.

\*\*\*\*\* END OF REPORT \*\*\*\*\*

Report No: RDG160118001-20

SAR Evaluation Report 71 of 71