



A Power Indicator	G Modeling Lamp Button	L Hot Shoe Interface
B Power Button	H Test Button	M Micro USB Port
C LCD Screen	I Power Adjust Buttons	N Battery Cover
E TTL/Manual Button	J Channel Button	P Battery Compartment
F Group Button	K Beep Button	



Turning the Unit On and Off

1. Install AAA batteries.
2. Press and hold the power button **B** for 2 seconds to turn the unit on and off.

Modeling Lamp

Press **G** once to set modeling lamp to 50% brightness, once again to set modeling lamp to 100% brightness, and a third time to turn the modeling lamp off.

Beep

Press **K** to toggle audible remote adjustment and recycle tone on and off.

Setting Groups and Channels

Press the **J** to toggle through channels 1-8.

- both the S1 and the TTL remote must be on the same channel
- setting the channel to “-” will disable all radio communication

Press **F** to toggle through groups A-C.

- assigning groups allows you to individually control the lights via the TTL remote

Select a shooting mode (manual or TTL)

Press **E** to toggle between Manual and TTL mode.

Select a sync mode (1st, 2nd, HSS)

Note: Nikon users switch between 1st- and 2nd-curtain sync via the camera and enable HSS by increasing the shutter speed on their camera with Auto FP mode enabled.

Note: HSS is only available in Manual mode, not TTL mode.

Tech Specs

1. frequency: 2.4GHz
2. voltage: 2.2-3.4Vt
3. sync speed: 1/8000s
4. wireless range: ≤20 meters
5. 24 channels

A	1	2	3	4	5	6	7	8
Frequency	2401	2402	2403	2404	2405	2406	2407	2408
B	1	2	3	4	5	6	7	8
Frequency	2401	2402	2403	2404	2405	2406	2407	2408

Note: Remote has A,B,C three groups, and eight channels of these three groups are identical, they are in different flash intensity.

Firmware Upgrade Instructions

visit our website at interfitphotographic.com for firmware updates for new features & fixes

1. Take out all batteries from **P** the battery compartment
2. Insert the micro USB cable into the remote's micro USB **M** port
3. Long-press **B** the power button while connecting the cable to your computer
4. Release the power button **B** when the remote has been recognized as a USB device
5. Start the firmware upgrade application and click connect, then start.
6. When pass is displayed, click disconnect.

FCC STATEMENT

1. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference.
- (2) This device must accept any interference received, including interference that may cause undesired operation.

2. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

Reorient or relocate the receiving antenna.

Increase the separation between the equipment and receiver.

Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

Consult the dealer or an experienced radio/TV technician for help.