

# Appendix B

## Detailed Test Results

|                        |
|------------------------|
| 1. GSM                 |
| GSM850 for Body        |
| GSM1900 for Body       |
| 2. WCDMA               |
| WCDMA Band II for Body |
| WCDMA Band V for Body  |
| 3. LTE                 |
| LTE Band 2 for Body    |
| LTE Band 4 for Body    |
| LTE Band 5 for Body    |
| LTE Band 7 for Body    |
| LTE Band 41 for Body   |
| 4. WIFI&BT             |
| WIFI 2.4GHz for Body   |
| WIFI 5.2GHz for Body   |
| WIFI 5.8GHz for Body   |



Date: 2025/4/17

Test Laboratory: LCS-SAR Lab

**GSM 850 GPRS 3TX 190CH Rear side 0mm****DUT: Smart POS; Type: WIZARPOS Q3 min; Serial: A250325071-1**

Communication System: UID 0, GSM (0); Frequency: 836.6 MHz; Duty Cycle: 1: 2.77

Medium parameters used:  $f = 836.6$  MHz;  $\sigma = 0.912$  S/m;  $\epsilon_r = 41.463$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3805; ConvF(9.08, 9.08, 9.08); Calibrated: 2025/2/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn373; Calibrated: 2025/2/17
- Phantom: SAM v5.0; Type: SAM; Serial: 1850
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/ Body /Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.775 W/kg



**Configuration/ Body /Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.46 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.964 W/kg

**SAR(1 g) = 0.495 W/kg; SAR(10 g) = 0.262 W/kg**

Maximum value of SAR (measured) = 0.764 W/kg





Date: 2025/4/19

Test Laboratory: LCS-SAR Lab

**GSM 1900 GPRS 3TX 661CH Rear side 0mm****DUT: Smart POS; Type: WIZARPOS Q3 min; Serial: A250325071-1**

Communication System: UID 0, GSM (0); Frequency: 1880 MHz; Duty Cycle: 1: 2.77

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.416$  S/m;  $\epsilon_r = 40.649$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3805; ConvF(7.80, 7.80, 7.80); Calibrated: 2025/2/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn373; Calibrated: 2025/2/17
- Phantom: SAM v5.0; Type: SAM; Serial: 1850
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/ Body /Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.924 W/kg



**Configuration/ Body /Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.249 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 1.34 W/kg

**SAR(1 g) = 0.63 W/kg; SAR(10 g) = 0.336 W/kg**

Maximum value of SAR (measured) = 0.974 W/kg



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Date: 2025/4/19

Test Laboratory: LCS-SAR Lab

**WCDMA II RMC 9538CH Rear side 0mm****DUT: Smart POS; Type: WIZARPOS Q3 min; Serial: A250325071-1**

Communication System: UID 0, WCDMA (0); Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1907.6$  MHz;  $\sigma = 1.397$  S/m;  $\epsilon_r = 40.732$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3805; ConvF(7.80, 7.80, 7.80); Calibrated: 2025/2/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn373; Calibrated: 2025/2/17
- Phantom: SAM v5.0; Type: SAM; Serial: 1850
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/ Body /Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.793W/kg



**Configuration/ Body /Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.849 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 0.975 W/kg

**SAR(1 g) = 0.434 W/kg; SAR(10 g) = 0.235 W/kg**

Maximum value of SAR (measured) = 0.772 W/kg



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Date: 2025/4/17

Test Laboratory: LCS-SAR Lab

WCDMA V RMC 4132CH Rear side 0mm

DUT: Smart POS; Type: WIZARPOS Q3 min; Serial: A250325071-1

Communication System: UID 0, WCDMA (0); Frequency: 836.4 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 836.4$  MHz;  $\sigma = 0.908$  S/m;  $\epsilon_r = 41.284$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3805; ConvF(9.08, 9.08, 9.08); Calibrated: 2025/2/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn373; Calibrated: 2025/2/17
- Phantom: SAM v5.0; Type: SAM; Serial: 1850
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/ Body /Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.643 W/kg



Configuration/ Body /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.467 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.849 W/kg

SAR(1 g) = 0.364 W/kg; SAR(10 g) = 0.192 W/kg

Maximum value of SAR (measured) = 0.589 W/kg



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Date: 2025/4/19

Test Laboratory: LCS-SAR Lab

LTE B2 20M QPSK 19100CH 1RB99 Rear side 0mm

DUT: Smart POS; Type: WIZARPOS Q3 min; Serial: A250325071-1

Communication System: UID 0, LTE-FDD (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.384$  S/m;  $\epsilon_r = 40.389$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3805; ConvF(7.80, 7.80, 7.80); Calibrated: 2025/2/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn373; Calibrated: 2025/2/17
- Phantom: SAM v5.0; Type: SAM; Serial: 1850
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/ Body /Area Scan (10x15x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.928 W/kg


**Configuration/ Body /Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.456 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.38 W/kg

**SAR(1 g) = 0.638 W/kg; SAR(10 g) = 0.327 W/kg**

Maximum value of SAR (measured) = 0.955 W/kg



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Date: 2025/4/18

Test Laboratory: LCS-SAR Lab

LTE B4 20M QPSK 20050CH 1RB99 Rear side 0mm

DUT: Smart POS; Type: WIZARPOS Q3 min; Serial: A250325071-1

Communication System: UID 0, LTE-FDD (0); Frequency: 1720 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1720$  MHz;  $\sigma = 1.429$  S/m;  $\epsilon_r = 39.568$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3805; ConvF(8.14, 8.14, 8.14); Calibrated: 2025/2/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn373; Calibrated: 2025/2/17
- Phantom: SAM v5.0; Type: SAM; Serial: 1850
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/ Body /Area Scan (10x15x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.699 W/kg


**Configuration/ Body /Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.251 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 1.11 W/kg

**SAR(1 g) = 0.555 W/kg; SAR(10 g) = 0.31 W/kg**

Maximum value of SAR (measured) = 0.673 W/kg



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Date: 2025/4/17

Test Laboratory: LCS-SAR Lab

**LTE B5 10M QPSK 20525CH 1RB24 Rear side 0mm****DUT: Smart POS; Type: WIZARPOS Q3 min; Serial: A250325071-1**

Communication System: UID 0, LTE-TDD (0); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.5$  MHz;  $\sigma = 0.9145$  m;  $\epsilon_r = 41.453$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3805; ConvF(9.08, 9.08, 9.08); Calibrated: 2025/2/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn373; Calibrated: 2025/2/17
- Phantom: SAM v5.0; Type: SAM; Serial: 1850
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/ Body /Area Scan (10x15x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.713W/kg


**Configuration/ Body /Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.542 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.975W/kg

**SAR(1 g) = 0.474 W/kg; SAR(10 g) = 0.252 W/kg**

Maximum value of SAR (measured) = 0.695 W/kg



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Date: 2025/4/21

Test Laboratory: LCS-SAR Lab

LTE B7 20M QPSK 21100CH 1RB49 Rear side 0mm

DUT: Smart POS; Type: WIZARPOS Q3 min; Serial: A250325071-1

Communication System: UID 0, LTE-FDD (0); Frequency: 2535.5 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2535.5$  MHz;  $\sigma = 1.967$  S/m;  $\epsilon_r = 37.974$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3805; ConvF(7.25, 7.25, 7.25); Calibrated: 2025/2/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn373; Calibrated: 2025/2/17
- Phantom: SAM v5.0; Type: SAM; Serial: 1850
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/ Body /Area Scan (10x15x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.957 W/kg



**Configuration/ Body /Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.46 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.32 W/kg

SAR(1 g) = 0.647 W/kg; SAR(10 g) = 0.337 W/kg

Maximum value of SAR (measured) = 0.929 W/kg



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Date:2025/4/21

Test Laboratory: LCS-SAR Lab

LTE B41 20M QPSK 39750CH 1RB0 Rear side 0mm

DUT: Smart POS; Type: WIZARPOS Q3 min; Serial: A250325071-1

Communication System: UID 0, LTE-TDD (0); Frequency: 2506 MHz;Duty Cycle: 1:1

Medium parameters used:  $f = 2506$  MHz;  $\sigma = 1.996$  S/m;  $\epsilon_r = 38.674$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3805; ConvF(7.25, 7.25, 7.25); Calibrated: 2025/2/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn373; Calibrated: 2025/2/17
- Phantom: SAM v5.0; Type: SAM; Serial: 1850
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/ Body /Area Scan (10x15x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.892 W/kg



**Configuration/ Body /Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.432 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.35 W/kg

**SAR(1 g) = 0.611 W/kg; SAR(10 g) = 0.322 W/kg**

Maximum value of SAR (measured) = 0.903 W/kg





Date: 2025/4/20

Test Laboratory: LCS-SAR Lab

**WIFI 2.4G 802.11b 1CH Rear side 0mm****DUT: Smart POS; Type: WIZARPOS Q3 min; Serial: A250325071-1**

Communication System: UID 0, WIFI 2.4GHz (0); Frequency: 2412 MHz; Duty Cycle: 1:1008

Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.763$  S/m;  $\epsilon_r = 39.354$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3805; ConvF(7.43, 7.43, 7.43); Calibrated: 2025/2/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn373; Calibrated: 2025/2/17
- Phantom: SAM v5.0; Type: SAM; Serial: 1850
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/ Body /Area Scan (10x15x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.894 W/kg


**Configuration/ Body /Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.349 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.14 W/kg

**SAR(1 g) = 0.577 W/kg; SAR(10 g) = 0.299 W/kg**

Maximum value of SAR (measured) = 0.878 W/kg



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Date: 2025/4/22

Test Laboratory: LCS-SAR Lab

**WIFI 5.2G 802.11a 36CH Rear side 0mm****DUT: Smart POS; Type: WIZARPOS Q3 min; Serial: A250325071-1**

Communication System: UID 0, WIFI 5GHz (0); Frequency: 5180 MHz; Duty Cycle: 1:1.058

Medium parameters used:  $f = 5180$  MHz;  $\sigma = 4.516$  S/m;  $\epsilon_r = 36.246$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3805; ConvF(5.36, 5.36, 5.36); Calibrated: 2025/2/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn373; Calibrated: 2025/2/17
- Phantom: SAM v5.0; Type: SAM; Serial: 1850
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/ Body /Area Scan (11x18x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 0.685 W/kg



**Configuration/ Body /Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 3.475 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.886 W/kg

**SAR(1 g) = 0.418 W/kg; SAR(10 g) = 0.236 W/kg**

Maximum value of SAR (measured) = 0.708W/kg





Date: 2025/4/22

Test Laboratory: LCS-SAR Lab

**WIFI 5.8G 802.11a 149CH Rear side 0mm****DUT: Smart POS; Type: WIZARPOS Q3 min; Serial: A250325071-1**


Communication System: UID 0, WIFI 5GHz (0); Frequency: 5745 MHz; Duty Cycle: 1:1.058

Medium parameters used:  $f = 5745 \text{ MHz}$ ;  $\sigma = 5.326 \text{ S/m}$ ;  $\epsilon_r = 35.846$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3805; ConvF(4.86, 4.86, 4.86); Calibrated: 2025/2/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn373; Calibrated: 2025/2/17
- Phantom: SAM v5.0; Type: SAM; Serial: 1850
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Configuration/ Body /Area Scan (11x18x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$ Maximum value of SAR (measured) =  $0.694 \text{ W/kg}$ **Configuration/Body/Zoom Scan (7x7x12)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=2\text{mm}$ Reference Value =  $5.427 \text{ V/m}$ ; Power Drift =  $-0.09 \text{ dB}$ Peak SAR (extrapolated) =  $0.873 \text{ W/kg}$ **SAR(1 g) =  $0.4 \text{ W/kg}$ ; SAR(10 g) =  $0.224 \text{ W/kg}$** Maximum value of SAR (measured) =  $0.671 \text{ W/kg}$ 

Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity