

# The Procter & Gamble Co.

## SAR EXCLUSION REPORT

**SCOPE OF WORK**

SAR EXCLUSION CALCULATION ON THE  
IGROWTH BATH DEVICE MODEL 3284

**REPORT NUMBER**

105935250LEX-007

**ISSUE DATE**

11/20/2024

**PAGES**

14

**DOCUMENT CONTROL NUMBER**

Non-Specific EMC Report Shell Rev. December 2017  
© 2017 INTERTEK



## SAR EXCLUSION REPORT

**Report Number:** 105935250LEX-007

**Project Number:** G105935250

**Report Issue Date:** 11/20/2024

**Model(s) Covered by this Evaluation:** iGrowth Bath Device model 3284

**Standards:** FCC Title 47 CFR Part 2.1093 Radiofrequency Radiation  
Exposure Evaluation: Portable Devices

RSS-102 Issue 6

Tested by:  
Intertek Testing Services NA, Inc.  
731 Enterprise Drive  
Lexington, KY 40510  
USA

Client:  
The Procter & Gamble Co.  
5299 Spring Grove Ave.  
St Bernard, OH 45217  
USA

Report prepared by



Brian Lackey, Staff Engineer

Report reviewed by



Michael Carlson, Team Leader

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.





## Table of Contents

|          |                                                                           |           |
|----------|---------------------------------------------------------------------------|-----------|
| <b>1</b> | <b><i>Introduction and Conclusion.....</i></b>                            | <b>4</b>  |
| <b>2</b> | <b><i>Test Summary .....</i></b>                                          | <b>4</b>  |
| <b>3</b> | <b><i>Client Information .....</i></b>                                    | <b>5</b>  |
| <b>4</b> | <b><i>Description of Equipment under Test and Variant Models.....</i></b> | <b>6</b>  |
| <b>5</b> | <b><i>Test Procedure .....</i></b>                                        | <b>10</b> |
| <b>6</b> | <b><i>Results: .....</i></b>                                              | <b>12</b> |
| <b>7</b> | <b><i>Revision History .....</i></b>                                      | <b>14</b> |



## 1 Introduction and Conclusion

The tests indicated in section 2.0 were performed on the product constructed as described in section 4.0. The remaining test sections are the verbatim text from the actual data sheets used during the investigation. These test sections include the test name, the specified test Method, a list of the actual Test Equipment Used, documentation Photos, Results and raw Data. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, we have concluded the product tested is **exempt** from routine SAR evaluation. The results obtained in this test report pertain only to the item(s) tested. Intertek does not make any claims of compliance for samples or variants which were not tested.

## 2 Test Summary

| Section | Test Full Name                    | Result          |
|---------|-----------------------------------|-----------------|
| 6.1     | FCC SAR Exclusion Calculation     | Exempt from SAR |
| 6.2     | RSS-102 SAR Exclusion Calculation | Exempt from SAR |



### 3 Client Information

This product was tested at the request of the following:

| Client Information           |                                                       |
|------------------------------|-------------------------------------------------------|
| <b>Client Name:</b>          | The Procter & Gamble Co.                              |
| <b>Address:</b>              | 5299 Spring Grove Ave.<br>St Bernard, OH 45217<br>USA |
| <b>Contact:</b>              | Spencer Miller                                        |
| <b>Telephone:</b>            | +1 (513) 627-2572                                     |
| <b>Email:</b>                | miller.s.19@pg.com                                    |
| Manufacturer Information     |                                                       |
| <b>Manufacturer Name:</b>    | The Procter & Gamble Co.                              |
| <b>Manufacturer Address:</b> | 5299 Spring Grove Ave.<br>St Bernard, OH 45217<br>USA |



#### 4 Description of Equipment under Test and Variant Models

| Equipment Under Test                                     |                                    |
|----------------------------------------------------------|------------------------------------|
| <b>Product Name</b>                                      | iGrowth Bath Device                |
| <b>Model Number</b>                                      | 3284                               |
| <b>Serial Number</b>                                     | BT2.0-000443                       |
| <b>Hardware Version</b>                                  | 2.0                                |
| <b>Software Version</b>                                  | 21                                 |
| <b>Embedded Module</b>                                   | Particle Boron B402                |
| <b>Embedded Module FCCID/ICID</b>                        | FCCID: 2AEMI-B402 ICID: 20127-B402 |
| <b>Supported Transmit Modes</b>                          | LTE Cat-M                          |
| <b>Supported Transmit Bands</b>                          | 2, 4, 5, 12, 13                    |
| <b>Transmit Frequency</b>                                | 13.56MHz                           |
| <b>Antenna Type</b>                                      | Integral Antenna                   |
| <b>Rated Voltage</b>                                     | 7.5V                               |
| Description of Equipment Under Test (provided by client) |                                    |
| Research device used to measure toilet paper consumption |                                    |

##### 4.1 Variant Models:

There were no additional variant models covered under this evaluation.



## 4.2 Duty Factor Calculation

The following information was taken from the operational description provided by the client. Deviations from these values may affect compliance. Intertek does not make any claims of compliance for values other than those shown.

The device communicates on a very limited basis:

- The cellular modem duty cycle is determined by the main processor. The main processor powers the cellular modem and attempts communication once per week. This communication is expected to be a maximum of 49 seconds. Messages are limited by firmware to a 40 second window and 9 seconds is expected for initial cellular registration
- If the time limit is reached, a new uplink will be scheduled for 30 minutes later so that unsent data can be transmitted. For Duty cycle calculations, 30 minutes is the longest total averaging (sliding) window
- During this 49s interval the device will transmit for a maximum of 0.76s
- During the 9 seconds window for cellular registration, measurements taken from a test device showed 0.63sec were spent transmitting. See Figures 2 and 3 for this measurement.
- 0.13sec of the remaining 40 seconds is the maximum time used to transmit data packets. This is due to the hardcoded delay of 0.3 seconds between each data message sent and the LTE Category M1 half-duplex connected mode actively transmitting for 1ms within a 10ms radio frame. See Figures 3, 4, and 5 for further elaboration.
- In Total, 0.76s is the maximum transmission time on a 30minute window. This results in a duty cycle of 0.04% which is below the limit of 2.72%. See Figure 5 for detailed calculation.
- This communication pattern is hard coded in firmware
- The end user cannot change the duty cycle because they would need to disassemble the device and to have special equipment and knowledge to reprogram it.



### 4.3 Antenna Gain

The following information was taken from the Particle B402 quick start guide provided by the client. Any deviations from these values may affect compliance. Intertek does not make any claim of compliance for values other than those shown here.

|                                    |                                                                                                                 |                                                                                                                                                                                                                                      |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT</b>                     | B Series B402                                                                                                   |                                                                                                                                                                                                                                      |
| <b>MODEL NAME</b>                  | B402,B402S                                                                                                      |                                                                                                                                                                                                                                      |
| <b>NOMINAL VOLTAGE</b>             | Li+ PIN /Battery connector: DC 3.7V from Li-ion Battery or<br>VUSB PIN /USB connector :DC 5V from USB Host Unit |                                                                                                                                                                                                                                      |
| <b>OPERATING TEMPERATURE RANGE</b> | -20 ~ 75°C                                                                                                      |                                                                                                                                                                                                                                      |
| <b>MODULATION TYPE</b>             | <b>LTE/BLE</b>                                                                                                  | QPSK&16QAM, GFSK(1MHz, 2MHz)                                                                                                                                                                                                         |
| <b>TX OPERATING FREQUENCY</b>      | <b>LTE/BLE</b>                                                                                                  | 1850.7MHz ~ 1909.3MHz (FOR LTE Band2)<br>1710.7MHz ~ 1754.3MHz (FOR LTE Band4)<br>824.7MHz ~ 848.3MHz (FOR LTE Band5)<br>699.7MHz ~ 715.3MHz (FOR LTE Band12)<br>779.5MHz ~ 784.5MHz (FOR LTE Band13)<br>2402MHz ~ 2480MHz (FOR BLE) |
| <b>ANTENNA GAIN</b>                | <b>LTE Band 2</b>                                                                                               | FPC Antenna with 3.5dBi gain                                                                                                                                                                                                         |
|                                    | <b>LTE Band 4</b>                                                                                               | FPC Antenna with 3.5dBi gain                                                                                                                                                                                                         |
|                                    | <b>LTE Band 5</b>                                                                                               | FPC Antenna with 1.0dBi gain                                                                                                                                                                                                         |
|                                    | <b>LTE Band 12</b>                                                                                              | FPC Antenna with 1.0dBi gain                                                                                                                                                                                                         |
|                                    | <b>LTE Band 13</b>                                                                                              | FPC Antenna with 1.0dBi gain                                                                                                                                                                                                         |
|                                    | <b>BLE</b>                                                                                                      | FPCB Antenna with 2.0dBi gain                                                                                                                                                                                                        |



#### 4.5 Output Power and EIRP

The following information was taken from the Particle B402 Test Report SA190606W003 provided by the client. Any deviations from these values may affect compliance. Intertek does not make any claim of compliance for values other than those shown here.

##### LTE

| Band    | Frequency (MHz) | Operating Mode | Antenna Gain (dBi) | Tune-up Power (dBm) | E.I.R.P Power (mW) | Power Density (mW/cm <sup>2</sup> ) | limit (mW/cm <sup>2</sup> ) | PASS / FAIL |
|---------|-----------------|----------------|--------------------|---------------------|--------------------|-------------------------------------|-----------------------------|-------------|
| Band 2  | 1880            | QPSK           | 3.50               | 24.80               | 676.083            | 0.135                               | 1.00                        | PASS        |
| Band 4  | 1720            | QPSK           | 3.50               | 25.00               | 707.946            | 0.141                               | 1.00                        | PASS        |
| Band 5  | 829             | QPSK           | 1.00               | 25.00               | 398.107            | 0.079                               | 0.56                        | PASS        |
| Band 12 | 707.5           | QPSK           | 1.00               | 25.00               | 398.107            | 0.079                               | 0.47                        | PASS        |
| Band 13 | 782.0           | QPSK           | 1.00               | 25.00               | 398.107            | 0.079                               | 0.52                        | PASS        |



## 5 Test Procedure

### 5.1 FCC SAR Exclusion

#### FCC Title 47 CFR Part 2.1093(c)(1):

Evaluation of compliance with the exposure limits in § 1.1310 of this chapter, and preparation of an EA if the limits are exceeded, is necessary for portable devices having single RF sources with more than an available maximum time-averaged power of 1 mW, more than the ERP listed in Table 1 to § 1.1307(b)(3)(i)(C), or more than the Pth in the following formula, whichever is greater. The following formula shall only be used in conjunction with portable devices not exempt by § 1.1307(b)(3)(i)(C) at distances from 0.5 centimeters to 20 centimeters and frequencies from 0.3 GHz to 6 GHz.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

#### FCC KDB 447498 D04 Interim General RF Exposure Guidance v01 § 2.2.1:

Finally, when 10-g extremity SAR applies, SAR test exemption may be considered by applying a factor of 2.5 to the SAR-based exemption thresholds.



## 5.2 RSS-102 SAR Exclusion

### RSS-102 Issue 6 § 6.3 SAR Exemption Limits

Devices operating at or below the applicable output power levels (adjusted for tune-up tolerance) specified in table 11, based on the separation distance, are exempt from SAR evaluation. The separation distance, defined as the distance between the user and/or bystander and the antenna and/or radiating element of the device or the outer surface of the device, shall be less than or equal to 20 cm for these exemption limits to apply.

Table 11: Power limits for exemption from routine SAR evaluation based on the separation distance

| Frequency (MHz) | ≤ 5 mm (mW) | 10 mm (mW) | 15 mm (mW) | 20 mm (mW) | 25 mm (mW) | 30 mm (mW) | 35 mm (mW) | 40 mm (mW) | 45 mm (mW) | > 50 mm (mW) |
|-----------------|-------------|------------|------------|------------|------------|------------|------------|------------|------------|--------------|
| ≤ 300           | 45          | 116        | 139        | 163        | 189        | 216        | 246        | 280        | 319        | 362          |
| 450             | 32          | 71         | 87         | 104        | 124        | 147        | 175        | 208        | 248        | 296          |
| 835             | 21          | 32         | 41         | 54         | 72         | 96         | 129        | 172        | 228        | 298          |
| 1900            | 6           | 10         | 18         | 33         | 57         | 92         | 138        | 194        | 257        | 323          |
| 2450            | 3           | 7          | 16         | 32         | 56         | 89         | 128        | 170        | 209        | 245          |
| 3500            | 2           | 6          | 15         | 29         | 50         | 72         | 94         | 114        | 134        | 158          |
| 5800            | 1           | 5          | 13         | 23         | 32         | 41         | 54         | 74         | 102        | 128          |

The exemption limits in table 11 are based on measurements and simulations of half-wave dipole antennas at separation distances of 5 mm to 50 mm from a flat phantom, which provides a SAR value of approximately 0.4 W/kg for 1 g of tissue.

For limb-worn devices where the 10 gram of tissue applies, the exemption limits for routine evaluation in table 11 are multiplied by a factor of 2.5.

For controlled-use devices where the 8 W/kg for 1 gram of tissue applies, the exemption limits for routine evaluation in table 11 are multiplied by a factor of 5.

When the operating frequency of the device is between two frequencies located in table 11, linear interpolation shall be applied for the applicable separation distance. If the separation distance of the device is between two distances located in table 11, linear interpolation may be applied for the applicable frequency. Alternatively, the limit corresponding to the smaller distance may be employed. For example, in case of a 7 mm separation distance, either use the exception value for a 5 mm separation distance or interpolate between the limits corresponding to 5 mm and 10 mm separation distances.

For implanted medical devices, the exemption limit for routine SAR evaluation is set at an output power of 1 mW, regardless of frequency.

The SAR levels from exempted transmitters shall be included in the compliance assessment and the determination of the TER. Detailed guidance is included in sections 7.1.8 and 8.2.2.1.

**6 Results:****6.1 FCC SAR Exclusion Calculation**

RFID:

| Field Strength @ 3m<br>(dB $\mu$ V/m) | Field Strength @ 3m<br>(V/m) | ERP (mW)              | Limit (mW) | Exempt? |
|---------------------------------------|------------------------------|-----------------------|------------|---------|
| 47.46                                 | $236 \times 10^{-6}$         | $1.02 \times 10^{-5}$ | 1109       | Exempt  |

Cellular:

| RF Source | Frequency (GHz) | Separation Distance (cm) | Output Power (mW/dBm) | Duty Factor (%/dB) | Average Output Power (mW/dBm) | P <sub>th</sub> (mW/dBm) | Exempt from SAR? |
|-----------|-----------------|--------------------------|-----------------------|--------------------|-------------------------------|--------------------------|------------------|
| Band 2    | 1.85            | 0.5                      | 302mW<br>24.8dBm      | 0.04%<br>-34.0dB   | 0.121mW<br>-9.2dBm            | 8.6mW<br>9.3dBm          | Exempt           |
| Band 4    | 1.71            | 0.5                      | 316mW<br>25.0dBm      | 0.04%<br>-34.0dB   | 0.126mW<br>-9.0dBm            | 9.1mW<br>9.6dBm          | Exempt           |
| Band 5    | 0.824           | 0.5                      | 316mW<br>25.0dBm      | 0.04%<br>-34.0dB   | 0.126mW<br>-9.0dBm            | 23.6mW<br>13.7dBm        | Exempt           |
| Band 12   | 0.699           | 0.5                      | 316mW<br>25.0dBm      | 0.04%<br>-34.0dB   | 0.126mW<br>-9.0dBm            | 29.7mW<br>14.7dBm        | Exempt           |
| Band 13   | 0.777           | 0.5                      | 316mW<br>25.0dBm      | 0.04%<br>-34.0dB   | 0.126mW<br>-9.0dBm            | 25.6mW<br>14.1dBm        | Exempt           |

$$(0.121 \text{ mW} / 8.6 \text{ mW}) + (1.02 \times 10^{-5} \text{ mW} / 1109 \text{ mW}) = 0.0141$$

Since the combined SAR-to-limit ratio is  $< 1$ , the device is deemed to comply with simultaneous exposure requirements according to FCC Title 47 CFR Part 1.1307(b)(3)(ii)(B).



## 6.2 RSS-102 SAR Exclusion Calculation

RFID:

| Field Strength @ 3m (dBμV/m) | Field Strength @ 3m (V/m) | ERP (mW)              | Limit (mW) | Exempt? | SAR <sub>estimated</sub> (W/kg) |
|------------------------------|---------------------------|-----------------------|------------|---------|---------------------------------|
| 47.46                        | $236 \times 10^{-6}$      | $1.02 \times 10^{-5}$ | 290        | Exempt  | 0                               |

Cellular:

| RF Source | Frequency (GHz) | Separation Distance (mm) | EIRP (mW/dBm)    | Duty Factor (%/dB) | Average Output Power (mW/dBm) | P <sub>th</sub> (mW/dBm) | SAR <sub>estimated</sub> (W/kg) | Exempt from SAR? |
|-----------|-----------------|--------------------------|------------------|--------------------|-------------------------------|--------------------------|---------------------------------|------------------|
| Band 2    | 1.85            | 5                        | 676mW<br>28.3dBm | 0.04%<br>-34.0dB   | 0.270mW<br>-5.7dBm            | 16.75mW<br>12.24dBm      | 0.016                           | Exempt           |
| Band 4    | 1.71            | 5                        | 708mW<br>28.5dBm | 0.04%<br>-34.0dB   | 0.283mW<br>-5.5dBm            | 21.75mW<br>13.37dBm      | 0.013                           | Exempt           |
| Band 5    | 0.824           | 5                        | 398mW<br>26.0dBm | 0.04%<br>-34.0dB   | 0.159mW<br>-8.0dBm            | 53.25mW<br>17.26dBm      | 0.003                           | Exempt           |
| Band 12   | 0.699           | 5                        | 398mW<br>26.0dBm | 0.04%<br>-34.0dB   | 0.159mW<br>-8.0dBm            | 62.25mW<br>17.94dBm      | 0.003                           | Exempt           |
| Band 13   | 0.777           | 5                        | 398mW<br>26.0dBm | 0.04%<br>-34.0dB   | 0.159mW<br>-8.0dBm            | 56.75mW<br>17.54dBm      | 0.003                           | Exempt           |

$$(0 \text{ W/kg} / 4 \text{ W/kg}) + (0.016 \text{ W/kg} / 4 \text{ W/kg}) = 0.004$$

Since the combined SAR-to-limit ratio is < 1, the device is deemed to comply with simultaneous exposure requirements.



## 7 Revision History

| Revision Level | Date       | Report Number    | Prepared By | Reviewed By | Notes          |
|----------------|------------|------------------|-------------|-------------|----------------|
| 0              | 11/20/2024 | 105935250LEX-007 | BZ          | MC          | Original Issue |
|                |            |                  |             |             |                |
|                |            |                  |             |             |                |
|                |            |                  |             |             |                |
|                |            |                  |             |             |                |