



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 449-822  
 Tel: +82-31-323-6008 Fax: +82-31-323-6010  
<http://www.ltalab.com>

Dates of Tests: January 14 ~ February 3, 2016  
 Test Report S/N: LR500111602C  
 Test Site : LTA CO., LTD.

## CERTIFICATION OF COMPLIANCE

FCC ID.

**2AG9IHER-100**

APPLICANT

**Edge I&D Co., Ltd.**

<b>Equipment Class</b>	:	<b>Digital Transmission System (DTS)</b>
<b>Manufacturing Description</b>	:	<b>EZ HOLDER</b>
<b>Manufacturer</b>	:	<b>Edge I&amp;D Co., Ltd.</b>
<b>Model name</b>	:	<b>EHR-100</b>
<b>Test Device Serial No.:</b>	:	<b>Identical prototype</b>
<b>Rule Part(s)</b>	:	<b>FCC Part 15.247 Subpart C ; ANSI C-63.4-2009</b>
<b>Frequency Range</b>	:	<b>2404 ~ 2468 MHz</b>
<b>Max. Output Power</b>	:	<b>Max -11.29 dBm – Conducted</b>
<b>Data of issue</b>	:	<b>February 4, 2016</b>

This test report is issued under the authority of:

Yong-Cheol, Wang / Manager

The test was supervised by:

Joon-Young, Jeon, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

NVLAP LAB Code.: 200723-0

## **TABLE OF CONTENTS**

1. GENERAL INFORMATION	-----	3
2. INFORMATION ABOUT TEST ITEM	-----	4
3. TEST REPORT	-----	5
3.1 SUMMARY OF TESTS	-----	5
3.2 TECHNICAL CHARACTERISTICS TEST	-----	6
3.2.1 6 dB BANDWIDTH	-----	6
3.2.2 PEAK OUTPUT POWER	-----	9
3.2.3 POWER SPECTRAL DENSITY	-----	12
3.2.4 BAND EDGE	-----	15
3.2.5 CONDUCTED SPURIOUS EMISSIONS	-----	18
3.2.6 RADIATED SPURIOUS EMISSIONS	-----	21
3.2.7 AC CONDUCTED EMISSIONS	-----	27
<b>APPENDIX</b>		
APPENDIX TEST EQUIPMENT USED FOR TESTS	-----	30

## 1. General information

### 1-1 Test Performed

Company name : LTA Co., Ltd.  
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822  
 Web site : <http://www.ltalab.com>  
 E-mail : [chahn@ltalab.com](mailto:chahn@ltalab.com)  
 Telephone : +82-31-323-6008  
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

### 1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2016-09-30	ECT accredited Lab.
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	610755	2017-04-21	FCC filing
FCC	U.S.A	649054	2017-04-13	FCC CAB
VCCI	JAPAN	R2133(10 m), C2307	2017-06-21	VCCI registration
VCCI	JAPAN	T-2009	2016-12-23	VCCI registration
VCCI	JAPAN	G-563	2018-12-13	VCCI registration
IC	CANADA	5799A-1	UPDATING	IC filing
KOLAS	KOREA	NO.551	2017-01-08	KOLAS accredited Lab.

## 2. Information about test item

### 2-1 Client & Manufacturer

Company name : Edge I&D Co., Ltd.  
 Address : 1342-12, Gyeongchung-daero, Chowol-eup, Gwangju-si, Gyeonggi-do Korea  
 Tel / Fax : TEL No : +82-1644-0702 / FAX No : +82-070-4850-7042

### 2-2 Equipment Under Test (EUT)

Trade name : EZ HOLDER  
 Model name : EHR-100  
 Serial number : Identical prototype  
 Date of receipt : January 14, 2016  
 EUT condition : Pre-production, not damaged  
 Antenna type : PCB Printed Antenna (Max Gain : 2.10 dBi)  
 Frequency Range : 2404 ~ 2468 MHz  
 RF output power : Max -11.29 dBm – Conducted  
 Number of channels : 33  
 Type of Modulation : GFSK  
 Power Source : 4.2 Vdc

### 2-3 Tested frequency

	LOW	MID	HIGH
Frequency (MHz)	2404	2434	2468

### 2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
-	-	-	-

### 3. Test Report

#### 3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	6 dB Bandwidth	> 500 kHz	Conducted	C
15.247(b)	Transmitter Peak Output Power	< 1 Watt		C
15.247(d)	Transmitter Power Spectral Density	< 8 dBm @ 3 kHz		C
15.247(d)	Band Edge	> 20 dBc		C
15.209	Field Strength of Harmonics	Emission	Radiated	C
15.207	AC Conducted Emissions	Emissions	Conducted	C
15.203	Antenna requirement	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

#### → Antenna Requirement

The Edge I&D Co., Ltd. FCC ID: 2AG9IHER-100 unit complies with the requirement of §15.203. The antenna type is PCB Printed Antenna.

The sample was tested according to the following specification:

\*FCC Parts 15.247; ANSI C-63.4-2009

\*FCC KDB Publication No. 558074 v03r04

\*FCC TCB Workshop 2012, April

## 3.2 Technical Characteristics Test

### 3.2.1 6 dB Bandwidth

#### Procedure:

The bandwidth at 6 dB below the highest in-band spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 6 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is ( as close as possible to ) even with the reference marker level. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

#### The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz Span = 5 MHz

VBW = 100 kHz (VBW  $\geq$  RBW) Sweep = auto

Trace = max hold Detector function = peak

#### Measurement Data : **Complies**

Frequency (MHz)	Test Results	
	Measured Bandwidth (MHz)	Result
2404	0.84	Complies
2434	0.77	Complies
2468	0.85	Complies

- See next pages for actual measured spectrum plots.

#### Minimum Standard:

6 dB Bandwidth  $>$  500 kHz

#### Measurement Setup






Figure 1: Measurement setup for the carrier frequency separation


## Low Channel



## Middle Channel



## High Channel



### 3.2.2 Peak Output Power Measurement

#### Procedure:

The maximum peak output power was measured with the spectrum analyzer connected to the antenna output of the EUT. The spectrum analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99 % bandwidth. The EUT was operating in transmit mode at the appropriate center frequency.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 1 MHz Span = auto

VBW = 1 MHz (VBW  $\geq$  RBW) Sweep = auto

Detector function = peak

#### Measurement Data : **Complies**

Frequency (MHz)	Test Results		
	dBm	mW	Result
2404	<b>-13.06</b>	<b>0.05</b>	Complies
2434	<b>-12.17</b>	<b>0.06</b>	Complies
2468	<b>-11.29</b>	<b>0.07</b>	Complies

- See next pages for actual measured spectrum plots.


#### Minimum Standard:

Peak output power	< 1 W
-------------------	-------


#### Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)


## Low Channel



## Middle Channel



## High Channel



### 3.2.3 Power Spectral Density

#### Procedure:

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

#### The spectrum analyzer is set to:

RBW = 3 kHz	Span = 300 kHz
VBW = 3 kHz	Sweep = auto
Detector function = peak	Trace = max hold

#### Measurement Data : Complies

Frequency (MHz)	Test Results	
	dBm	Result
2404	-27.38	Complies
2434	-25.52	Complies
2468	-26.70	Complies

- See next pages for actual measured spectrum plots.

#### Minimum Standard:


Power Spectral Density	< 8 dBm @ 3 kHz BW
------------------------	--------------------

#### Measurement Setup


Same as the Chapter 3.2.1 (Figure 1)

## Power Density Measurement


### Low Channel



### Middle Channel



## High Channel



### 3.2.4 Band Edge

### **Procedure:**

The bandwidth at 20 dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 40 MHz      Detector function = peak

Radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a)

The spectrum analyzer is set to:

Center frequency = the highest, the lowest channels

PEAK: RBW = VBW = 1 MHz, Sweep=Auto

Average: RBW = 1 MHz, VBW = 10 Hz, Sweep = Auto

Measurement Distance: 3 m


Polarization: Horizontal / Vertical

**Measurement Data: Complies**


- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	> 20 dBc
--------------------------	----------

Band edge  
Lower edge



Upper edge



**Radiated Band-edges in the restricted band 2310-2390 MHz measurement**

Frequency [MHz]	Reading [dBuV/m]	Pol.	Correction Factor		Limits [dBuV/m]	Result [dBuV/m]		Margin [dB]	
			Antenna	Amp. Gain + Cable Loss		AV / Peak	AV / Peak	AV / Peak	AV / Peak
2364.0	34.1   54.4	V	27.9	24.4	54.0   74.0	37.6   57.9	16.4   16.1		

**Radiated Band-edges in the restricted band 2483.5-2500 MHz measurement**

Frequency [MHz]	Reading [dBuV/m]	Pol.	Correction Factor		Limits [dBuV/m]	Result [dBuV/m]		Margin [dB]	
			Antenna	Amp. Gain + Cable Loss		AV / Peak	AV / Peak	AV / Peak	AV / Peak
2483.8	34.6   52.9	V	27.9	24.4	54.0   74.0	38.1   56.4	15.9   17.6		

**Note : This EUT was tested in 3 orthogonal positions and the worst-case data was presented**

### 3.2.5 Conducted Spurious Emissions

### Procedure:

The test follows KDB558074. The conducted spurious emissions were measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, set the marker on the peak of any spurious emission recorded.

The spectrum analyzer is set to:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions

RBW = 100 kHz Sweep = auto

VBW = 100 kHz      Detector function = peak

Trace = max hold

### Measurement Data: Complies


- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

<b>Minimum Standard:</b>	> 20 dBc
--------------------------	----------


## Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)


Unwanted Emission – Low Channel  
Frequency Range = 30 MHz ~ 26.5 GHz



Unwanted Emission – Middle Channel  
Frequency Range = 30 MHz ~ 26.5 GHz



**Unwanted Emission – High Channel**  
**Frequency Range = 30 MHz ~ 26.5 GHz**



### 3.2.6 Radiated Spurious Emissions

## Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 9 kHz ~ 10<sup>th</sup> harmonic.

RBW = 100 kHz ( 30 MHz ~ 1 GHz)

$$\text{VBW} \geq \text{RBW}$$


$\equiv 1$  MHz (1 GHz  $\sim$  10<sup>th</sup> harmonic)



Span = 100 MHz

Detector function  $\equiv$  peak

Trace = max hold

**below 30 MHz**



**below 1 GHz (30 MHz to 1 GHz)****above 1 GHz****Measurement Data: Complies**

- See next pages for actual measured data.
- No other emissions were detected at a level greater than 20 dB below limit include from 9 kHz to 30 MHz.

**Minimum Standard: FCC Part 15.209(a)**

Frequency (MHz)	Limit (uV/m) @ 3 m
0.009 ~ 0.490	24000/F(kHz) (@ 300 m)
0.490 ~ 1.705	24000/F(kHz) (@ 30 m)
1.705 ~ 30	30(@ 30 m)
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

**Measurement Data : (Above 1 GHz)**

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor		Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
				Antenna	Amp.Gain+Cable						
4933.4	34.3	49.1	V	32.9	16.0	54.0	74.0	51.2	66.0	2.8	8.0

- No other emissions were detected at a level greater than 20 dB below limit.

**Measurement Data : (9 kHz – 30 MHz)**

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor		Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
				Antenna	Amp.Gain+Cable						
-	-	-	-	-	-	-	-	-	-	-	-
No emissions were detected at a level greater than 20 dB below limit.											
-	-	-	-	-	-	-	-	-	-	-	-

\*No emissions were detected at a level greater than 20 dB below limit.

Radiated Emissions – Wireless mode (LOW)


4, Songjuro 236 Beon-gil, Yangji-myeon,  
Cheoin-gu, Youngin-si, Gyeonggi-do,  
449-822 Korea  
Tel: +82-31-3236008,9  
Fax: +82-31-3236010

BUT/Model No.: EHR-100

TEST MODE: Wireless mode (LOW)

Temp Humi : 0 / 35

Tested by: LEE S H



Radiated Emissions – Wireless mode (MID)


4, Songjuro 236 Beon-gil, Yangji-myeon,  
Cheoin-gu, Youngin-si, Gyeonggi-do,  
449-822 Korea  
Tel: +82-31-3236008,9  
Fax: +82-31-3236010

EUT/Model No.: EHR-100

TEST MODE: Wireless mode(MID)

Temp Humi : 0 / 35

Tested by: LEE S H



Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions – Wireless mode (HIGH)


4, Songjuro 236 Beon-gil, Yangji-myeon,  
Cheoin-gu, Youngin-si, Gyeonggi-do,  
449-822 Korea  
Tel: +82-31-3236008,9  
Fax: +82-31-3236010

EUT/Model No.: EHR-100

TEST MODE: Wireless mode(HIGH)

Temp Humi : 0 / 35

Tested by: LEE S H



Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

### 3.2.6 AC Conducted Emissions

#### Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

#### Measurement Data: Complies

- See next pages for actual measured spectrum plots.
- No emissions were detected at a level greater than 20 dB below limit.

#### Minimum Standard: FCC Part 15.207(a) / EN 55022

Class B


Frequency Range	quasi-peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Decreases with the logarithm of the frequency

AC Conducted Emissions – Wireless mode – LINE

4, Songjuro 236 Beon-gil, Yangji-myeon  
Cheoin-gu, Youngin-si, Gyeonggi-do  
449-822 Korea  
Tel: +82-31-3236008,9  
Fax: +82-31-3236010

EUT / Model No. : EHR-100 Phase : LINE  
Test Mode : Wireless mode Test Power : 120 / 60  
Temp. / Humi. : 22 / 38 Test Engineer : LEE S H




Freq MHz	RD QP		RD AV		C.F		Result QP	Result AV	Limit		Margin	
	dBuV	dBuV	dBuV	dB	dB	dB			dBuV	dBuV	dB	dB
0.151	27.93	2.37	19.57		47.50	21.94	65.92	55.92	18.42	33.98		
0.157	28.14	1.06	19.55		47.69	20.61	65.62	55.62	17.93	35.01		
0.157	28.14	1.82	19.55		47.69	21.37	65.60	55.60	17.91	34.23		
0.190	31.17	7.27	19.51		50.68	26.78	64.03	54.03	13.35	27.25		
0.197	33.12	13.79	19.49		52.61	33.28	63.73	53.73	11.12	20.45		
0.201	33.05	13.94	19.49		52.54	33.43	63.56	53.56	11.02	20.13		

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

AC Conducted Emissions – Wireless mode – NEUTRAL

4, Songjuro 236 Beon-gil, Yangji-myeon  
Cheoin-gu, Youngin-si, Gyeonggi-do  
449-822 Korea  
Tel: +82-31-3236008,9  
Fax: +82-31-3236010

EUT / Model No. : EHR-100 Phase : NEUTRAL  
Test Mode : Wireless mode Test Power : 120 / 60  
Temp. / Humi. : 22 / 38 Test Engineer : LEE S H



Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result		Result		Limit		Margin	
				QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.154	28.46	0.78	19.57	48.03	20.35	65.79	55.79	17.76	35.44		
0.160	27.17	0.88	19.57	46.74	20.45	65.48	55.48	18.74	35.03		
0.177	22.15	-3.19	19.54	41.69	16.35	64.63	54.63	22.94	38.28		
0.195	32.72	11.81	19.51	52.23	31.32	63.81	53.81	11.58	22.49		
0.201	32.54	13.49	19.50	52.04	32.99	63.57	53.57	11.53	20.58		
0.280	19.18	-0.39	19.47	38.65	19.08	60.83	50.83	22.18	31.75		

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

## APPENDIX

### **TEST EQUIPMENT USED FOR TESTS**

	Description	Model No.	Serial No.	Manufacturer	Interval	Last Cal. Date
1	Signal Analyzer (9 kHz ~ 30 GHz)	FSV-30	100757	R&S	1 year	2015-03-24
2	Signal Generator (~3.2 GHz)	8648C	3623A02597	HP	1 year	2015-03-23
3	SYNTHESIZED CW GENERATOR	83711B	US34490456	HP	1 year	2015-03-23
4	Attenuator (3 dB)	8491A	37822	HP	1 year	2015-09-14
5	Attenuator (10 dB)	8491A	63196	HP	1 year	2015-09-14
6	Test Receiver (~30 MHz)	ESHS10	828404/009	R&S	1 year	2015-03-23
7	EMI Test Receiver (~7 GHz)	ESCI7	100722	R&S	1 year	2015-09-15
8	RF Amplifier (~1.3 GHz)	8447D OPT 010	2944A07684	HP	1 year	2015-09-14
9	RF Amplifier (1~26.5 GHz)	8449B	3008A02126	HP	1 year	2015-03-23
10	Horn Antenna (1~18 GHz)	3115	00114105	ETS	2 year	2015-04-21
11	DRG Horn (Small)	3116B	81109	ETS-Lindgren	2 year	2014-02-26
12	DRG Horn (Small)	3116B	133350	ETS-Lindgren	2 year	2014-02-26
13	TRILOG Antenna	VULB 9160	9160-3237	SCHWARZBECK	2 year	2015-04-21
14	Temp.Humidity Data Logger	SK-L200TH II A	00801	SATO	1 year	2015-04-03
15	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-	-
16	Power Divider	11636A	06243	HP	1 year	2015-09-14
17	DC Power Supply	6674A	3637A01657	Agilent	-	-
18	Frequency Counter	5342A	2826A12411	HP	1 year	2015-03-23
19	Power Meter	EPM-441A	GB32481702	HP	1 year	2015-03-23
20	Power Sensor	8481A	3318A94972	HP	1 year	2016-01-05
21	Audio Analyzer	8903B	3729A18901	HP	1 year	2015-09-14
22	Modulation Analyzer	8901B	3749A05878	HP	1 year	2015-09-15
23	TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	Jin Young Tech	1 year	2015-09-14
24	Stop Watch	HS-3	812Q08R	CASIO	2 year	2014-04-03
25	LISN	KNW-407	8-1430-1	Kyoritsu	1 year	2015-09-14
26	Two-Lime V-Network	ESH3-Z5	893045/017	R&S	1 year	2015-03-23
27	UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	1 year	2015-03-23
28	Highpass Filter	WHKX1.5/15G-10SS	74	Wainwright Instruments	1 year	2015-03-30
29	Highpass Filter	WHKX3.0/18G-10SS	118	Wainwright Instruments	1 year	2015-03-30
30	Active Loop Antenna	FMZB1519	1519-031	SCHWARZBECK	2 year	2016-01-12
31	OSP120 BASE UNIT	OSP120	101230	R&S	1 year	2015-03-23
32	Signal Generator(100 kHz ~ 40 GHz)	SMB100A03	177621	R&S	1 year	2015-03-24
33	Signal Analyzer (10 Hz ~ 40 GHz)	FSV40	101367	R&S	1 year	2015-03-24