RF Exposure evaluation

FCC ID: 2AGA8-AH-X1

1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01 v05r02: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

KDB447498 D02 SAR Measurement Procedures for USB Dongle Transmitters

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency	Electric Field	Magnetic Field	Power Density	Averaging Time				
Range(MHz)	Strength(V/m)	Strength(A/m)	(mW/cm²)	(minute)				
Limits for Occupational/Controlled Exposure								
0.3 - 3.0	614	1.63	(100) *	6				
3.0 - 30	1842/f	4.89/f	$(900/f^2)*$	6				
30 - 300	61.4	0.163	1.0	6				
300 - 1500	/	/	f/300	6				
1500 – 100,000	/	/	5	6				

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

r · · · · · · · · · · · · · · · · · · ·								
Frequency	Electric Field	Magnetic Field	Power Density	Averaging Time				
Range(MHz)	Strength(V/m)	Strength(A/m)	(mW/cm ²)	(minute)				
Limits for Occupational/Controlled Exposure								
0.3 - 3.0	614	1.63	(100) *	30				
3.0 - 30	824/f	2.19/f	$(180/f^2)*$	30				
30 - 300	27.5	0.073	0.2	30				
300 - 1500	/	/	f/1500	30				
1500 – 100,000	/	/	1.0	30				

F=frequency in MHz

Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 .

^{*=}Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a given distance Equation from page 18 of OET Bulletin 65, Edition 97-01

$S=PG/4\pi R^2$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Result

As declared by the Applicant, the EUT is a wireless device used in a mobile application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum mobile separation distance, r = 20cm, as well as the gain of the used antenna is 0dBi, the RF power density can be obtained.

WIFI

Mode	Max. Output Power Ant1 (dBm)	Max. Output Power Ant2 (dBm)	Antenna Gain (Numeric)	Power Density At 20 cm Ant1 (mW/cm²)	Power Density At 20 cm Ant2 (mW/cm²)	Power Density Limit FCC (mW/cm²)	Test Results
802.11b	17.23	16.04	1.0000	0.0105	0.0080	1.0	PASS
802.11g	12.69	10.65	1.0000	0.0037	0.0023	1.0	PASS
802.11n(HT20)	11.56	10.96	1.0000	0.0028	0.0025	1.0	PASS
802.11n(HT40)	10.14	9.97	1.0000	0.0021	0.0020	1.0	PASS

5. Conclusion

The SAR evaluation is not required.