

Huizhou Weide Electronics Co., Ltd.

Application For Certification

FCC ID: 2AGA9RS70

Bluetooth Headphone

Model: WD-RS70 Additional Models: 3301704, 3301705, Ncredible One

Brand name: WEIDE for model: WD-RS70; Ncredible for model: 3301704, 3301705, Ncredible One

2.4GHz Transceiver

Report No.: 151020024SZN-002

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-14]

Prepared and Checked by: Approved by:

Sign on file

Jenner Liu Engineer Andy Yan

Senior Project Engineer Date: November 24, 2015

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample
 may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF No.: FCC 15C_TX_b

LIST OF EXHIBITS

INTRODUCTION

EXHIBIT 1: General Description

EXHIBIT 2: System Test Configuration

EXHIBIT 3: Emission Results

EXHIBIT 4: Equipment Photographs

EXHIBIT 5: Product Labelling

EXHIBIT 6: Technical Specifications

EXHIBIT 7: Instruction Manual

EXHIBIT 8: Miscellaneous Information

EXHIBIT 9: Confidentiality Request

EXHIBIT 10: Test Equipment List

MEASUREMENT/TECHNICAL REPORT

Huizhou Weide Electronics Co., Ltd. - MODEL: WD-RS70
Additional Model: 3301704, 3301705, Ncredible One

Brand name: WEIDE for model: WD-RS70; Ncredible for model: 3301704, 3301705, Ncredible One

FCC ID: 2AGA9RS70

This report concerns (check one:) Equipment Type: DXX - Part 15 Low Pow	-		_
Deferred grant requested per 47 CFR 0.4		Yes ntil:da	No X
Company Name agrees to notify the Con of the intended date of announcement of date.	•	date	
Transition Rules Request per 15.37? If no, assumed Part 15, Subpart C for Edition] provision.		Yes – the new 47	·
Report prepared by:	Jenner Liu Intertek Testing Ser Kejiyuan Branch 6F, Block D, Huaha Nanshan District, S Phone: (86 755) 8 Fax: (86 755) 8	an Building, Lang Shenzhen, P. R. 0 601 0639	ıshan Road,

Table of Contents

1.0 General Description	
1.1 Product Description	2
1.2 Related Submittal(s) Grants	
1.3 Test Methodology	
1.4 Test Facility	
·	
2.0 System Test Configuration	
2.1 Justification	
2.2 EUT Exercising Software	
2.3 Special Accessories	
2.4 Equipment Modification	
2.5 Measurement Uncertainty	
2.6 Support Equipment List and Description	5
3.0 Emission Results	
3.1 Radiated Test Results	
3.1.1 Field Strength Calculation	
3.1.2 Radiated Emission Configuration Photograph	
3.1.3 Radiated Emissions	
3.1.4 Transmitter Spurious Emissions	
3.2 Conducted Emission at Mains Termina	
3.2.1 Conducted Emissions Configuration Photograph	
3.2.2 Conducted Emissions	
4.0 Equipment Photographs	19
5.0 Product Labelling	21
6.0 Technical Specifications	23
7.0 Instruction Manual	25
0.0 M*: a a Harra a constant for more than	
8.0 Miscellaneous Information	
8.1 Bandedge Plot	
8.2 Discussion of Pulse Desensitization	
8.3 Transmitter Duty Cycle Calculation	
8.4 Emissions Test Procedures	32
9.0 Confidentiality Request	35
10 0 Technical Credifications	25

List of attached file

Exhibit type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Setup Photo	Conducted Emission	conducted photos.pdf
Test Report	Bandedge Plot	bandedge.pdf
Test Report	20dB BW Plot	bw.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Operation Description	Technical Description	descri.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Confidentiality Letter	request.pdf
Cover Letter	Letter of Agency	agency.pdf

EXHIBIT 1 GENERAL DESCRIPTION

1.0 **General Description**

1.1 Product Description

The equipment under test (EUT) is a Bluetooth Headphone. The EUT was powered by the fully-charged DC 3.7V, 400mAh new rechargeable battery which was charged by USB port (DC 5V). For more detail information pls. refer to the user manual.

Bluetooth Version: 4.0 LE modes Antenna Type: Integral antenna

Modulation Type: GFSK

The EUT has Version A and Version B. Version B is only added the reset function based on Version A, all other electronic aspect and function are the same.

The Model: 3301704, 3301705, Ncredible One are the same as the Model: WD-RS70 in hardware aspect (circuitry and electrical, mechanical and physical construction), the only differences are the appearance and model no. for trading purpose.

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

This is an application for certification of a transceiver for the Bluetooth Headphone BT 4.0 LE, and for the BT 3.0, 2.1+EDR mode was tested and demonstrated in report 151020024SZN-001.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). Radiated emission measurement was performed in Semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

1.4 Test Facility

The Semi-anechoic chamber and shielding room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch** and located at 6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC(Registration Number: 242492).

EXHIBIT 2 SYSTEM TEST CONFIGURATION

2.0 **System Test Configuration**

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The EUT was powered by the fully-charged DC 3.7V new rechargeable battery which was charged by an AC/DC adaptor or PC with input of AC 120V, 60Hz during the test.

All packets DH1, DH3 & DH5 mode in modulation type GFSK, π /4DQPSK, 8DPSK were tested, and both versions with or without reset function were tested, only the worst data was reported in this report.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on a turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

The EUT exercise program (provided by client) used during testing was designed to exercise the various system components in a manner similar to a typical use.

2.3 Special Accessories

No special accessories used.

2.4 Equipment Modification

Any modifications installed previous to testing by Huizhou Weide Electronics Co., Ltd. will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd Kejiyuan Branch.

2.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

Description	Manufacturer	Model No.
iPod (Provided by Intertek)	Apple	A1421
USB Cable (Provided by Applicant)	N/A	Unshielded, Length 54cm
AC/DC adaptor (Provided by Intertek)	TP-Link	T050100-2A3 (Input: AC 100- 240V, 50/60Hz, 0.3A Output: DC 5.0V, 1.0A)
Laptop (Provided by Intertek)	Lenovo	T420

EXHIBIT 3 EMISSION RESULTS

3.0 **Emission Results**

Data is included worst-case configuration (the configuration which resulted in the highest emission levels).

3.1 Radiated Test Results

A sample calculation, configuration photographs and data tables of the emissions are included.

3.1.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG$$

Where $FS = Field Strength in dB\mu V/m$

RA = Receiver Amplitude (including preamplifier) in dBµV

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB AG = Amplifier Gain in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG$$

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The net field strength for comparison to the appropriate emission limit is 42 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

 $RA = 62.0 dB\mu V$

AF = 7.4 dB

CF = 1.6 dB

 $AG = 29.0 \, dB$

 $FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 \, dB\mu V/m$

Level in $\mu V/m = Common Antilogarithm [(42 dB<math>\mu V/m)/20] = 125.9 \mu V/m$

TRF No.: FCC 15C_TX_b FCC ID: 2AGA9RS70

8

3.1.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

3.1.3 Radiated Emissions

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Worst Case Radiated Emission at 187.994 MHz

Judgement: Passed by 10.1 dB

TEST PERSONNEL:

Sign on file

Jenner Liu Engineer
Typed/Printed Name

November 24, 2015

Date

Applicant: Huizhou Weide Electronics Co., Ltd.

Date of Test: November 24, 2015

Model: WD-RS70

Sample: Version A without reset function

Worst Case Operating Mode: BT Link and Charging via Adapter

Table 1

Radiated Emissions

Polarization	Frequency	Reading	Pre-	Antenna	Net	Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	30.970	24.7	20.0	16.9	21.6	40.0	-18.4
Horizontal	187.994	42.1	20.0	11.3	33.4	43.5	-10.1
Horizontal	441.765	31.1	20.0	19.3	30.4	46.0	-15.6
Vertical	30.000	25.4	20.0	17.5	22.9	40.0	-17.1
Vertical	134.760	32.3	20.0	9.7	22.0	43.5	-21.5
Vertical	441.765	28.1	20.0	19.3	27.4	46.0	-18.6

NOTES: 1. Quasi-Peak detector is used except for others stated.

- All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.

4. All emissions are below the QP limit.

3.1.4 Transmitter Spurious Emissions (Radiated)

Worst Case Radiated Emission at 2480.000 MHz

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 5.0 dB

TEST PERSONNEL:

Sign on file

Jenner Liu Engineer
Typed/Printed Name

November 24, 2015

Date

Applicant: Huizhou Weide Electronics Co., Ltd.

Date of Test: November 24, 2015

Model: WD-RS70

Sample: Version A without reset function

Worst Case Operating Mode: Transmitting and Charging via Adapter

Table 2

Radiated Emissions

(2402MHz)

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
	, ,	, , ,	Gain	(dB)	(dBµV/m)	(dBµV/m)	, ,
			(dB)	, ,	` ' '	, , ,	
Horizontal	2402.000	110.5	36.7	28.1	101.9	114.0	-12.1
Horizontal	4804.000	58.1	36.7	35.5	56.9	74.0	-17.1
Horizontal	7206.000	57.9	36.1	36.5	58.3	74.0	-15.7
Horizontal	9608.000	58.6	36.2	37.0	59.4	74.0	-14.6

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	2402.000	96.4	36.7	28.1	87.8	94.0	-6.2
Horizontal	4804.000	45.1	36.7	35.5	43.9	54.0	-10.1
Horizontal	7206.000	43.3	36.1	36.5	43.7	54.0	-10.3
Horizontal	9608.000	43.5	36.2	37.0	44.3	54.0	-9.7

Notes: 1. Peak detector is used for the emission measurement (RBW=1MHz / VBW=3MHz for Peak value, and RBW=1MHz / VBW=10Hz for Average value; RBW=3MHz is used for fundamental emission measurement).

- 2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: Jenner Liu

Applicant: Huizhou Weide Electronics Co., Ltd.

Date of Test: November 24, 2015

Model: WD-RS70

Sample: Version A without reset function

Worst Case Operating Mode: Transmitting and Charging via Adapter

Table 3

Radiated Emissions

(2440MHz)

Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
	, ,		Gain	(dB)	(dBµV/m)	(dBµV/m)	, ,
			(dB)	, ,	` ' '	` ' '	
Horizontal	2440.000	110.3	36.7	28.1	101.7	114.0	-12.3
Horizontal	4880.000	59.1	36.7	35.5	57.9	74.0	-16.1
Horizontal	7320.000	58.0	36.1	37.2	59.1	74.0	-14.9
Horizontal	9760.000	60.0	36.2	37.0	60.8	74.0	-13.2

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	2440.000	96.5	36.7	28.1	87.9	94.0	-6.1
Horizontal	4880.000	45.8	36.7	35.5	44.6	54.0	-9.4
Horizontal	7320.000	42.9	36.1	37.2	44.0	54.0	-10.0
Horizontal	9760.000	44.9	36.2	37.0	45.7	54.0	-8.3

Notes: 1. Peak detector is used for the emission measurement (RBW=1MHz / VBW=3MHz for Peak value, and RBW=1MHz / VBW=10Hz for Average value; RBW=3MHz is used for fundamental emission measurement).

- 2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative value in the margin column shows emission below limit.
- 4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: Jenner Liu

Applicant: Huizhou Weide Electronics Co., Ltd.

Date of Test: November 24, 2015

Model: WD-RS70

Sample: Version A without reset function

Worst Case Operating Mode: Transmitting and Charging via Adapter

Table 4

Radiated Emissions

(2480MHz)

1								
	Polarization	Frequency	Reading	Pre-	Antenna	Net	Peak Limit	Margin
		(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
		, ,	, ,	Gain	(dB)	(dBµV/m)	(dBµV/m)	, ,
				(dB)				
	Horizontal	2480.000	111.9	36.7	28.1	103.3	114.0	-10.7
	Horizontal	4960.000	58.7	36.7	35.5	57.5	74.0	-16.5
	Horizontal	7440.000	57.6	36.1	37.2	58.7	74.0	-15.3
	Horizontal	9920.000	57.6	36.3	38.9	60.2	74.0	-13.8

Polarization	Frequency	Reading	Pre-	Antenna	Net	Average Limit	Margin
	(MHz)	(dBµV)	Amp	Factor	at 3m	at 3m	(dB)
			Gain	(dB)	(dBµV/m)	(dBµV/m)	
			(dB)				
Horizontal	2480.000	97.6	36.7	28.1	89.0	94.0	-5.0
Horizontal	4960.000	46.2	36.7	35.5	45.0	54.0	-9.0
Horizontal	7440.000	42.6	36.1	37.2	43.7	54.0	-10.3
Horizontal	9920.000	42.8	36.3	38.9	45.4	54.0	-8.6

- Notes: 1. Peak detector is used for the emission measurement (RBW=1MHz / VBW=3MHz for Peak value, and RBW=1MHz / VBW=10Hz for Average value; RBW=3MHz is used for fundamental emission measurement).
 - 2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
 - 3. Negative value in the margin column shows emission below limit.
 - 4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: Jenner Liu

- 3.2 Conducted Emission at Mains Terminal
- 3.2.1 Conducted Emissions Configuration Photograph

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

3.2.2 Conducted Emissions

Worst Case Conducted Configuration
At

3.154 MHz

Judgement: Passed by 12.5 dB margin

TEST PERSONNEL:

Sign on file

Jenner Liu Engineer
Typed/Printed Name

November 24, 2015

Date

Applicant: Huizhou Weide Electronics Co., Ltd.

Date of Test: November 24, 2015


Model: WD-RS70

Sample: Version A without reset function

Worst Case Operating Mode: BT Link and Charging via Adapter

Phase: Live

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.533	36.7	L1	9.9	19.3	56.0
0.555	38.5	L1	9.9	17.5	56.0
0.614	38.5	L1	10.0	17.5	56.0
2.894	38.6	L1	10.0	17.4	56.0
3.154	38.6	L1	10.0	17.4	56.0
3.370	37.6	L1	10.0	18.4	56.0

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.533	31.6	L1	9.9	14.4	46.0
0.555	32.2	L1	9.9	13.8	46.0
0.614	30.4	L1	10.0	15.6	46.0
2.894	32.0	L1	10.0	14.0	46.0
3.154	33.5	L1	10.0	12.5	46.0
3.370	30.6	L1	10.0	15.4	46.0

Applicant: Huizhou Weide Electronics Co., Ltd.

Date of Test: November 24, 2015


Model: WD-RS70

Sample: Version A without reset function

Worst Case Operating Mode: BT Link and Charging via Adapter

Phase: Neutral

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.173	23.0	N	10.2	41.8	64.8
0.478	38.7	N	10.2	17.7	56.4
0.537	38.5	N	10.2	17.5	56.0
0.626	36.3	N	10.3	19.7	56.0
2.922	36.0	N	10.3	20.0	56.0
3.122	36.1	N	10.3	19.9	56.0

Result Table AV

Frequency (MHz)	Average (dB μ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.173	19.0	N	10.2	35.8	54.8
0.478	32.6	N	10.2	13.8	46.4
0.537	32.5	N	10.2	13.5	46.0
0.626	29.2	N	10.3	16.8	46.0
2.922	30.9	N	10.3	15.1	46.0
3.122	32.4	N	10.3	13.6	46.0

EXHIBIT 4 EQUIPMENT PHOTOGRAPHS

4.0 **Equipment Photographs**

For electronic filing, the photographs of the tested EUT are saved with filename: external photos.pdf & internal photos.pdf.

EXHIBIT 5 PRODUCT LABELLING

5.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

EXHIBIT 6 TECHNICAL SPECIFICATIONS

6.0 <u>Technical Specifications</u>

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

EXHIBIT 7 INSTRUCTION MANUAL

7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

EXHIBIT 8 MISCELLANEOUS INFORMATION

8.0 <u>Miscellaneous Information</u>

This miscellaneous information includes details of the measured bandedge, the test procedure and calculation of factor such as pulse desensitization.

8.1 Bandedge Plot

For electronic filing, the plot shows the fundamental emission when modulated is saved with filename: bandedge.pdf. From the plot, the field strength of any emissions outside of the specified frequency band are attenuated to the general radiated emission limits in section 15.209. It fulfils the requirement of 15.249(d).

Peak Measurement

Bandedge compliance is determined by applying marker-delta method, i.e (Bandedge Plot).

(i) Lower channel 2402MHz:

Peak Resultant field strength = Fundamental emissions (peak value) - delta from the bandedge plot

= $101.9 \text{ dB}\mu\text{v/m}-48.6 \text{ dB}$ = $53.3 \text{ dB}\mu\text{v/m}$

Average Resultant field strength = Fundamental emissions (Average value) – delta from the bandedge plot

 $= 87.8 \text{ dB}\mu\text{v/m}-48.6 \text{ dB}$ = 39.2 dB $\mu\text{v/m}$

(ii) Upper channel 2480MHz:

Peak Resultant field strength = Fundamental emissions (peak value) - delta from the bandedge plot

= $103.3 \text{ dB}\mu\text{v/m-}49.0 \text{ dB}$ = $54.3 \text{ dB}\mu\text{v/m}$

Average Resultant field strength = Fundamental emissions (Average value) – delta from the bandedge plot

 $= 89.0 \text{ dB}\mu\text{v/m}-49.0 \text{ dB}$ = 40.0 dB\mu\/m

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74dBµv/m (Peak Limit) and 54dBµv/m (Average Limit).

8.1 Bandedge Plot (cont'd)

Pursuant to FCC part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

Figure 8.1 Bandwidth

8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

8.3 Transmitter Duty Cycle Calculation, FCC Rule 15.35(b, c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
Х	Not applicable, duty cycle was not used.

8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2009.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjust through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

Detector function for conducted emissions is in QP & AV mode and IFBW setting is 9 kHz from the frequency band 150 kHz to 30MHz.

8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.4 - 2009.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. Above 1000 MHz, a resolution bandwidth of 1 MHz (RBW 3MHz for fundamental emission) is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

EXHIBIT 9 CONFIDENTIALITY REQUEST

9.0 **Confidentiality Request**

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

EXHIBIT10 TEST EQUIPMENT LIST

10.0 **Test Equipment List**

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-12	BiConiLog Antenna	ETS	3142E	00166158	15-Sep-15	15-Sep-16
SZ185-01	EMI Receiver	R&S	ESCI	100547	07-Feb-15	07-Feb-16
SZ061-07	Pyramidal Horn Antenna	ETS	3160-09	00083067	03-Sep-15	03-Sep-16
SZ061-08	Horn Antenna	ETS	3115	00092346	17-Oct-15	17-Oct-16
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	29-Apr-15	29-Apr-16
SZ056-06	Signal Analyzer	R&S	FSV 40	101101	08-Jul-15	08-Jul-16
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	07-Feb-15	07-Feb-16
SZ188-01	Anechoic Chamber	ETS	RFD-F/A- 100	4102	19-Apr-14	19-Apr-16
SZ062-02	RF Cable	RADIALL	RG 213U		27-Jun-15	27-Dec-15
SZ062-05	RF Cable	RADIALL	0.04- 26.5GHz		08-Oct-15	08-Apr-16
SZ062-12	RF Cable	RADIALL	0.04- 26.5GHz		08-Oct-15	08-Apr-16
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02	1	20-May-15	20-May-16
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	02-Nov-15	02-Nov-16
SZ187-01	Two-Line V- Network	R&S	ENV216	100072	02-Nov-15	02-Nov-16
SZ187-02	Two-Line V- Network	R&S	ENV216	100073	24-Jun-15	24-Jun-16
SZ188-03	Shielding Room	ETS	RFD-100	4100	23-Aug-14	23-Aug-16