RF Exposure 2AGAP-SMARTGLASSES

7. RF Exposure Requirements

7. 1 Test Equipment

Please refer to Section 10 this report.

7. 2 Limit

According to FCC 15.247(e)(i) and FCC 1.1307(b)(1), Systems operating under provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commissions guidelines.

According to KDB 447498 D01 General RF Exposure v05, section 4.3.1

SAR Test Exclusion Thresholds for 100 MHz-6GHz and <=5mm

Frequency Range		Maximum measured	SAR Limitation
Low Frequency(MHz)	High Frequency(MHz)	transmitter power frequency(MHz)	(mW)
2402	2480	2440	10

7. 3 Test Result

Product : Smart Glasses Test Mode : Bluetooth 4.0 LE

Test Item : RF Exposure : 25 $^{\circ}$ C Test Voltage : DC 5V Humidity : 56%RH

Test Result : PASS

RF Exposure Requirements	Compliance with FCC Rules	
EIRP=PxG Where: P=Power input to antenna G=Power gain of the antenna relative to an isotropic radiator	Maximum output power at antenna input terminal: 4.75dBm = 2.99 mW (Bluetooth 4.0 LE, 2440MHz) Prediction distance: <=5mm Antenna gain : 0 dBi SAR Test Exclusion Threshold is 10mW Bluetooth 4.0 LE : 2.99 mW The max. output power E.I.R.P < 10mW Conclusion: No SAR is required.	