

# **FCC BLE TEST REPORT**

**No. 150934-BLE**

For

**OBI Connect FZE**

**Product Name: Mobile Phone**

**Model Name: Obi Worldphone SJ1.5**

**Trade Name: OBI**

**Issued Date: 2015-12-14**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of GCCT.

To verify test report authenticity, send full test report to Email: gaoxiaoqing0310@126.com

**Test Laboratory:**

*GCCT, Guangdong Telecommunications Terminal Products Quality Supervision and Testing Center  
Technology Road, High-tech Zone, He Yuan, Guang Dong, PR China 517001  
Tel:+86(0)762-3607221, Fax:+86(0)762-3603336 Email: ncctmail@126.com. [www.ncct.org.cn](http://www.ncct.org.cn)*

## CONTENTS


|   |           |
|---|-----------|
| <b>1. Test Laboratory .....</b>   | <b>4</b>  |
| 1.1 Testing Location.....   | 4         |
| 1.2 Testing Environment.....  | 4         |
| 1.3 Project Data.....   | 4         |
| <b>2. Client Information .....</b>                                      | <b>5</b>  |
| 2.1 Applicant Information.....  | 5         |
| 2.2 Manufacturer Information.....                                       | 5         |
| <b>3. Equipment Under Test (EUT) and Ancillary Equipment (AE) .....</b> | <b>6</b>  |
| 3.1 About EUT.....  | 6         |
| 3.2 Internal Identification of EUT.....                                 | 7         |
| 3.3 Internal Identification of AE .....                                 | 7         |
| <b>4. Test Results.....</b>   | <b>8</b>  |
| 4.1 Summary of Test Results .....                                       | 8         |
| 4.2 Statements .....  | 8         |
| <b>5. Test Equipment Utilized .....</b>                                 | <b>9</b>  |
| <b>ANNEX A: EUT Photograph .....</b>                                    | <b>11</b> |
| <b>ANNEX B: Detailed Test Results.....</b>                              | <b>20</b> |
| B.1Maximum Transmit Power .....   | 20        |
| B.2Maximum Power Spectral Density.....                                  | 21        |
| B.3DTS (6dB)Channel Bandwidth .....                                     | 23        |
| B.4Band Edge .....  | 26        |
| B.5ConductedSpurious Emissions .....                                    | 29        |
| B.6 Radiated Emissions .....  | 34        |
| B.7 AC Conducted Emission .....   | 41        |
| B.8Antenna Requirements .....   | 44        |
| <b>ANNEX C: Report Revision History.....</b>                            | <b>45</b> |

**GENERAL SUMMARY**


|                            |  |
|----------------------------|--|
| <b>Product Name</b>        | Mobile Phone   |
| <b>Model Name</b>          | Obi Worldphone SJ1.5   |
| <b>Trade Name</b>          | OBI  |
| <b>Applicant</b>           | OBI Connect FZE  |
| <b>Manufacturer</b>        | CK Telecom Limited   |
| <b>Test Laboratory</b>     | GCCT, Guangdong Telecommunications Terminal Products Quality Supervision and Testing Center  |
| <b>Reference Standards</b> | FCC CFR 47 Part 15C:“Radio Frequency Devices Sub-Part C: intentional Radiators”<br>ANSI C63.10-2013, “American National Standard for Testing Unlicensed Wireless Devices”<br>KDB 558074 D01 DTS Meas Guidance v03r03                 |
| <b>Test Conclusion</b>     | This portable wireless equipment has been measured in all cases requested by the relevant standards. Test results in annex B of this test report are below limits specified in the relevant standards.<br><br>General Judgment: Pass |
|                            | Date of issue: 2015.12.14  |
| <b>Comment</b>             | The test results in this report apply only to the tested sample of the stated device/equipment.  |

*Approved by:*

Luo Jian  
Manager

*Reviewed by:*

Dong Xiaobo  
Deputy Manager

*Tested by:*

Gao Xiaoqing  
Test Engineer

## 1. Test Laboratory

### 1.1 Testing Location

|                              |   |
|------------------------------|---|
| <b>Company Name</b>          | GCCT, Guangdong Telecommunications Terminal Products Quality Supervision and Testing Center |
| <b>Address</b>               | Technology Road, High-tech Zone, Heyuan, Guangdong Province, PR.China                       |
| <b>CNAS Registration No.</b> | L4992   |
| <b>FCC Registration No.</b>  | 303878  |
| <b>Postal Code</b>           | 517001  |
| <b>Telephone</b>             | +86-762-3607221   |
| <b>Fax</b>                   | +86-762-3603336   |

### 1.2 Testing Environment

| <b>Environment Data</b> | Temperature(°C) | Humidity(%) |
|-------------------------|-----------------|-------------|
| <b>Maximum Ambient</b>  | 25.6            | 44          |
| <b>Minimum Ambient</b>  | 24.1            | 39          |

EUT is under testing environment.

### 1.3 Project Data

|                           |             |
|---------------------------|-------------|
| <b>Project Leader</b>     | Dong Xiaobo |
| <b>Testing Start Date</b> | 2015-10-23  |
| <b>Testing End Date</b>   | 2015-12-14  |

## 2. Client Information

### 2.1 Applicant Information

|                     |   |
|---------------------|---|
| <b>Company Name</b> | OBI Connect FZE   |
| <b>Address</b>      | B-21,Dubai Airport Free zone, PO BOX 371475, United Arab Emirates |
| <b>City</b>         | Dubai   |
| <b>Postal Code</b>  | /   |
| <b>Country</b>      | United Arab Emirates  |

### 2.2 Manufacturer Information

|                     |   |
|---------------------|---|
| <b>Company Name</b> | CK Telecom Limited  |
| <b>Address</b>      | Technology Road.High-Tech Development Zone. Heyuan,<br>Guangdong,P.R.China. |
| <b>City</b>         | Heyuan  |
| <b>Postal Code</b>  | /   |
| <b>Country</b>      | China   |

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1 About EUT**

|                                 |  |
|---------------------------------|--|
| <b>Model Name</b>               | Obi Worldphone SJ1.5   |
| <b>FCC ID</b>                   | 2AGBLSJ15  |
| <b>Tx Frequency</b>             | GSM850:824 ~ 848 MHz<br>PCS1900 : 1850 ~ 1909MHz<br>WCDMA Band V: 826 ~ 846MHz<br>Bluetooth& BLE: 2402 ~ 2480MHz<br>WIFI(802.11b/g/n-20): 2412 ~ 2462MHz<br>WIFI(802.11n-40): 2422 ~ 2452MHz |
| <b>Rx Frequency</b>             | GSM850: 869 ~ 893MHz<br>GSM1900: 1930 ~ 1989MHz<br>WCDMA Band V: 871 ~ 891MHz<br>Bluetooth& BLE: 2402 ~ 2480MHz<br>WIFI(802.11b/g/n-20): 2412 ~ 2462MHz<br>WIFI(802.11n-40): 2422 ~ 2452MHz  |
| <b>Number of Channels</b>       | GSM850 :25<br>GSM1900 : 60<br>WCDMA Band V: 25<br>Bluetooth:79<br>BLE:40<br>WIFI(802.11b/g/n-20):11<br>WIFI(802.11n-40):7  |
| <b>Modulation</b>               | GSM:GMSK<br>WCDMA:BPSK/QPSK<br>BLE:GFSK<br>Bluetooth: GFSK& $\pi$ /4-DQPSK&8DPSK<br>WIFI:CCK/OFDM  |
| <b>Antenna Gain</b>             | GSM850&1900:-0.5dBi<br>WCDMA Band V: -1dBi<br>Bluetooth&BLE&WIFI: -1dBi  |
| <b>Normal Voltage</b>           | 3.8V   |
| <b>Extreme Low Voltage</b>      | 3.7V   |
| <b>Extreme High Voltage</b>     | 4.2V   |
| <b>Extreme Low Temperature</b>  | 0°C  |
| <b>Extreme High Temperature</b> | 40°C   |

Note: Photographs of EUT are shown in ANNEX A of this test report.

Note: high and low voltage values in extreme condition test are given by manufacturer

### **3.2 Internal Identification of EUT**

| <b>EUT ID *</b> | <b>IMEI</b> | <b>HW Version</b> | <b>SW Version</b>    |
|-----------------|-------------|-------------------|----------------------|
| 150934-M01      | /           | V1.0              | OBI-SJ1.5-000-Ver1.5 |
| 150934-M02      | /           | V1.0              | OBI-SJ1.5-000-Ver1.5 |

\*EUT ID: is used to identify the test sample in the lab internally. 150934-M01 and 150934-M02 are the same mobile phone.

### **3.3 Internal Identification of AE**

| <b>AE ID *</b> | <b>Description</b> | <b>Model</b> | <b>Manufacturer</b>                       |
|----------------|--------------------|--------------|---|
| 150934-B01     | Battery            | OB3000CKA    | DONG GUAN DRN NEW ENERGY CO.,LTD.         |
| 150934-C01     | Adapter            | A0D2A5V      | DONG GUAN AOHAI POWER TECHNOLOGY CO.,LTD. |
| 150934-B02     | Battery            | OB3000CKA    | DONG GUAN DRN NEW ENERGY CO.,LTD.         |
| 150934-C02     | Adapter            | A0D2A5V      | DONG GUAN AOHAI POWER TECHNOLOGY CO.,LTD. |

\*AE ID: is used to identify the test sample in the lab internally. 150934-B01 and 150934-B03 are the same accessories, 150934-C01 and 150934-C02 are the same accessories.

## **4. Test Results**

### **4.1 Summary of Test Results**

| <b>No</b> | <b>Test cases</b>               | <b>Sample</b> | <b>Verdict</b> |
|-----------|---------------------------------|---------------|----------------|
| 1         | Maximum transmit power          | M01           | Pass           |
| 2         | Maximum Power Spectral Density  | M01           | Pass           |
| 3         | 6dB Occupied Bandwidth          | M01           | Pass           |
| 4         | Band Edge Compliance            | M01           | Pass           |
| 5         | Conducted Transmitter emissions | M01           | Pass           |
| 6         | Radiated emissions              | M02           | Pass           |
| 7         | AC Conducted Emission           | M02           | Pass           |
| 8         | Antenna Requirements            | M01           | Pass           |

Note: please refer to Annex B in this test report for the detailed test results.

EUT was tested with Channel 0, 19,39.

### **4.2 Statements**

GCCT has evaluated the test cases requested by the applicant/manufacturer as listed in section 4.1 of this report, for the EUT specified in section 3, according to the standards or reference documents listed in general summary.

**5. Test Equipment Utilized****Table 1. Measurement Equipment**

| <b>Hardware</b> |                   |              |            |                    |                  |                      |
|-----------------|-------------------|--------------|------------|--------------------|------------------|----------------------|
| <b>No.</b>      | <b>Name</b>       | <b>Model</b> | <b>SN</b>  | <b>Manufacture</b> | <b>Cal. Date</b> | <b>Cal. Due Date</b> |
| 1               | Spectrum Analyzer | N9020A       | MY52091261 | Agilent            | 2015.08.21       | 2016.08.20           |
| 2               | Switch Unit       | /            | E0112      | /                  | 2015.08.21       | 2016.08.20           |
| 3               | Power Meter       | N1912A       | MY54166002 | Agilent            | 2015.08.21       | 2016.08.20           |
| 4               | Power Sensor      | N1921A       | MY55090055 | Agilent            | 2015.08.21       | 2016.08.20           |
| <b>Software</b> |                   |              |            |                    |                  |                      |
| Tech BT         |                   | v1.0.3       |            |                    |                  |                      |

**Table 2. Radiated emission test system**

| <b>No.</b> | <b>Name</b>                          | <b>Model</b> | <b>SN</b>  | <b>Manufacture</b> | <b>Cal. date</b> | <b>Cal. Due Date</b> |
|------------|--------------------------------------|--------------|------------|--------------------|------------------|----------------------|
| 1          | Spectrum Analyzer                    | E4440A       | MY48250641 | Agilent            | 2015.08.21       | 2016.08.20           |
| 2          | BiCoNilog Antenna                    | 3142E        | 00142015   | ETS-Lindgren       | 2015.09.15       | 2017.09.14           |
| 3          | Horn Antenna                         | 3117         | 129169     | ETS-Lindgren       | 2015.09.15       | 2017.09.14           |
| 4          | Signal Generator                     | N5183A-532   | MY49060563 | Agilent            | 2015.08.21       | 2016.08.20           |
| 5          | Universal Radio Communication Tester | E5515C       | MY48367105 | Agilent            | 2015.08.21       | 2016.08.20           |
| 6          | RF Preselector                       | N9039A       | MY48260024 | Agilent            | /                | /                    |
| 7          | Loop Antenna                         | HFH2         | 860015/00  | R&S                | 2015.08.21       | 2016.08.20           |

**Table 3. Accessories**

| <b>No.</b> | <b>Name</b> | <b>Model</b>   | <b>SN</b>   | <b>Manufacturer</b> | <b>Cal. date</b> | <b>Cal. Due Date</b> |
|------------|-------------|----------------|-------------|---------------------|------------------|----------------------|
| 1          | PC          | Pavilion dv2   | CNC9112F 68 | HP                  | /                | /                    |
| 2          | Printer     | BOISB-060 4-00 | VNF3L523 98 | HP                  | /                | /                    |
| 3          | Mouse       | M-UAV-DE L8    | /           | DELL                | /                | /                    |
| 4          | Power line  | I-SHENG        | /           | /                   | /                | /                    |

**GCCT**

No. 150934-BLE  
Page 10 of 45

5

USB cable

SHIELDED

E174089

/

/

/

## ANNEX A: EUT Photograph


EUT Front View




EUT behind View



**EUT Left View**




**EUT Right View**



**EUT Top View**




**EUT Rear View**




All




Cover off



Main board Front View




Main board Rear View




### Battery Front View




### Battery Back View




**GSM/WCDMA Antenna View**




**BT/WIFI Antenna View**




**Adapter label view**



**Adapter view**




**USB Cable**



## **ANNEX B: Detailed Test Results**

The radiated test setup is shown in each radiated test case section. The conducted test setup except RF Power is shown as following:



All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.

### **B.1 Maximum Transmit Power**

#### **B.1.1 Description**

The maximum Peak Output power shall be equal to or less than 30dBm.

#### **B.1.2 Test procedures**

##### **Conducted Measurement**

EUT was set for low, mid, high channel with modulated mode and highest RF output power

The power meter was connected to the antenna terminal.

##### **Standard Requirement**

One of the following procedures may be used to determine the maximum peak conducted output power of a DTS EUT.

##### **Procedures:**

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

#### **B.1.3 Test Setup**



#### **B.1.4 Test Results**

| <b>Test Mode</b> | <b>Maximum peak output power(dBm)</b> |                |                | <b>Verdict</b> |
|------------------|---------------------------------------|----------------|----------------|----------------|
|                  | <b>2402MHz</b>                        | <b>2440MHz</b> | <b>2480MHz</b> |                |
| GFSK             | -2.795                                | -0.835         | -1.244         | Pass           |

## B.2 Maximum Power Spectral Density

### B.2.1 Description

The maximum spectral density shall be equal to or less than 8dBm

## B.2.2 Test procedures

## Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power. The spectrum analyzer was connected to the antenna terminal.

## Standard Requirement

The DTS rules specify a conducted PSD limit within the DTS bandwidth during any time interval of continuous transmission.<sup>5</sup> Such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. Therefore, if maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option):

## Procedures:

### Method PKPSD (peak PSD)

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth
- c) Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set the VBW  $\geq 3 \text{ RBW}$ .
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### B.2.3 Test Results



|             |             |            |
|-------------|-------------|------------|
| Test Plot 1 | 2401.992920 | -4.750000  |
| Test Plot 2 | 2401.000000 | -19.945000 |

**Fig. Maximum power spectral density of BLE in channel 0**



|             |             |            |
|-------------|-------------|------------|
| Test Plot 1 | 2439.998047 | -3.850000  |
| Test Plot 2 | 2439.000000 | -19.049000 |

**Fig. Maximum power spectral density of BLE in channel 19**



|             |             |            |
|-------------|-------------|------------|
| Test Plot 1 | 2479.993896 | -3.460000  |
| Test Plot 2 | 2479.000000 | -18.660999 |

**Fig. Maximum power spectral density of BLE in channel 39**

## B.3DTS (6dB)Channel Bandwidth

### B.3.1 Description

The Occupied 6dB Bandwidth shall be equal to or more than 500 kHz.

### B.3.2 Test procedures

#### Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power

The spectrum analyzer was connected to the antenna terminal.

#### Standard Requirement

This bandwidth is referred to as the DTS bandwidth.


#### Procedures:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW)  $\geq 3$  RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies. associated with

the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


### B.3.3 Test Results

| Channel | Frequency (MHz) | Limit (MHz) | Occupied Bandwidth (MHz) | Test Results | Verdict |
|---------|-----------------|-------------|--------------------------|--------------|---------|
| 0       | 2402            | 0.5         | 0.695                    | Fig.7        | Pass    |
| 19      | 2440            |             | 0.689                    | Fig.8        | Pass    |
| 39      | 2480            |             | 0.697                    | Fig.9        | Pass    |



|             |             |            |
|-------------|-------------|------------|
| Test plot 1 | 2401.656006 | -10.700000 |
| Test plot 2 | 2402.351318 | -10.730000 |

Fig. 6dB Bandwidth of BLE in channel 0,2402MHz



|             |             |           |
|-------------|-------------|-----------|
| Test plot 1 | 2439.657227 | -9.820000 |
| Test plot 2 | 2440.346680 | -9.820000 |

Fig. 6dB Bandwidth of BLE in channel 19,2440MHz



|             |             |           |
|-------------|-------------|-----------|
| Test plot 1 | 2479.654785 | -9.420000 |
| Test plot 2 | 2480.351318 | -9.440000 |

Fig 6dB Bandwidth of BLE in channel 39,2480MHz

## **B.4 Band Edge**

### **B.4.1 Conducted Measurement**

#### **B.4.1.1 Description**

The Band Edges Compliance shall be equal to or less than -20 dB.

#### **B.4.1.2 Test procedures**

##### **Conducted Measurement**

EUT was set for low, mid, high channel with modulated mode and highest RF output power

The spectrum analyzer was connected to the antenna terminal.

##### **Standard Requirement**

Emissions within 2 MHz of an authorized band edge may be measured using either the marker-delta method (for peak or average emissions) or the integration method (for average emissions only), described below, provided that the OBW edge falls within 2 MHz of the band edge. Otherwise, all unwanted emissions measurements shall be performed using the standard methods.

##### **Procedures**


###### **Peak Detection**

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.


- a) Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).
- b) Set span to 2 MHz
- c) RBW = 100 kHz.
- d) VBW  $\geq$  3 x RBW.
- e) Detector = peak.
- f) Sweep time = auto.
- g) Trace mode = max hold.
- h) Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)
- i) Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency ( $f_{\text{emission}}$ )  $\pm$  0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by  $f_{\text{emission}} \pm 0.5$  MHz.

#### **B.4.1.3 Test Results**

| <b>Channel</b> | <b>Frequency(MHz)</b> | <b>Limit<br/>(dB)</b> | <b>Test Result(dB)</b> |        | <b>Verdict</b> |
|----------------|-----------------------|-----------------------|------------------------|--------|----------------|
| 0              | 2400                  | -20                   | -59.45                 | Fig.10 | Pass           |
| 39             | 2483.5                |                       | -62.48                 | Fig.11 | Pass           |



**Fig. Frequency Band Edges in channel 0,2402MHz**



**Fig. Frequency Band Edges in channel 39,2480MHz**

## B.4.2 Radiated measurement

### B.4.2.1 Procedures:

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT on the rotated table inside the anechoic chamber without connection to measurement instrument. Turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear

range. Repeat above procedures until all measured frequencies were complete.

- c) Set band RBW=1MHz, VBW=3MHz with a convenient frequency span from band edge.
- d) Find the highest point in edge frequency, and then calculated results.
- e) Repeat above procedures until all measured frequencies were complete.

#### **B.4.2.2 Test Results**

| Frequency     | Receiver Reading | Detector    | Turn table Angle | RX Antenna |          | Corrected Factor | Corrected Amplitude | Limit          | Margin        |
|---------------|------------------|-------------|------------------|------------|----------|------------------|---------------------|----------------|---------------|
|               |                  |             |                  | Height     | Polar    |                  |                     |                |               |
| (MHz)         | (dB $\mu$ V)     | (PK/QP/Ave) | Degree           | (m)        | (H/V)    | (dB)             | (dB $\mu$ V/m)      | (dB $\mu$ V/m) | (dB)          |
| 2400MHz       |                  |             |                  |            |          |                  |                     |                |               |
| 485.79        | 13.22            | QP          | 139              | 1.1        | H        | 21.09            | 34.31               | 46.50          | -12.19        |
| 485.79        | 12.94            | QP          | 257              | 1.3        | V        | 21.09            | 34.03               | 46.50          | -12.47        |
| <b>2400</b>   | <b>44.32</b>     | <b>PK</b>   | <b>315</b>       | <b>1.2</b> | <b>V</b> | <b>-1.08</b>     | <b>43.24</b>        | <b>74.00</b>   | <b>-30.76</b> |
| <b>2400</b>   | <b>42.58</b>     | <b>Ave</b>  | <b>315</b>       | <b>1.2</b> | <b>V</b> | <b>-1.08</b>     | <b>41.50</b>        | <b>54.00</b>   | <b>-12.50</b> |
| 4804          | 45.26            | PK          | 242              | 1.4        | V        | -1.06            | 44.2                | 74.00          | -29.80        |
| 4804          | 43.15            | Ave         | 242              | 1.4        | V        | -1.06            | 42.09               | 54.00          | -11.91        |
| 7206          | 44.68            | PK          | 346              | 1.1        | V        | 1.31             | 45.99               | 74.00          | -28.01        |
| 7206          | 43.86            | Ave         | 346              | 1.1        | V        | 1.31             | 45.17               | 54.00          | -8.83         |
| 2483.5MHz     |                  |             |                  |            |          |                  |                     |                |               |
| 485.79        | 14.71            | QP          | 81               | 1.9        | H        | 21.09            | 35.80               | 46.50          | -10.70        |
| 485.79        | 13.80            | QP          | 242              | 1.8        | V        | 21.09            | 34.89               | 46.50          | -11.61        |
| <b>2483.5</b> | <b>42.33</b>     | <b>PK</b>   | <b>309</b>       | <b>1.4</b> | <b>V</b> | <b>-0.31</b>     | <b>42.02</b>        | <b>74.00</b>   | <b>31.98</b>  |
| <b>2483.5</b> | <b>41.62</b>     | <b>Ave</b>  | <b>309</b>       | <b>1.4</b> | <b>V</b> | <b>-0.31</b>     | <b>41.31</b>        | <b>54.00</b>   | <b>12.69</b>  |
| 4960          | 44.78            | PK          | 324              | 1.6        | V        | -0.25            | 44.53               | 74.00          | -29.47        |
| 4960          | 42.79            | Ave         | 324              | 1.6        | V        | -0.25            | 42.54               | 54.00          | -11.46        |
| 7440          | 43.05            | PK          | 256              | 1.6        | V        | 2.86             | 45.91               | 74.00          | -28.09        |
| 7440          | 42.36            | Ave         | 256              | 1.6        | V        | 2.86             | 45.22               | 54.00          | -8.78         |

## B.5 Conducted Spurious Emissions

### B.5.1 Description

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

### B.5.2 Test Procedures

#### Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power

The spectrum analyzer was connected to the antenna terminal.

#### Procedures

- a) The EUT was connected to SA by a low loss cable.
- b) Set  $RBW=100$  kHz,  $VBW \geq RBW$ , scan up to 10th harmonics. All harmonics/Spurs emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.

### B.5.3 Test Results

| Channel | Frequency Range | Test Results | Verdict |
|---------|-----------------|--------------|---------|
| 0       | 30MHz ~ 1GHz    | Fig.9        | Pass    |
|         | 1GHz ~ 3GHz     | Fig.10       | Pass    |
|         | 3GHz ~ 10GHz    | Fig.11       | Pass    |
|         | 10GHz ~ 26GHz   | Fig.12       | Pass    |
| 19      | 30MHz ~ 1GHz    | Fig.13       | Pass    |
|         | 1GHz ~ 3GHz     | Fig.14       | Pass    |
|         | 3GHz ~ 10GHz    | Fig.15       | Pass    |
|         | 10GHz ~ 26GHz   | Fig.16       | Pass    |
| 39      | 30MHz ~ 1GHz    | Fig.17       | Pass    |
|         | 1GHz ~ 3GHz     | Fig.18       | Pass    |
|         | 3GHz ~ 10GHz    | Fig.19       | Pass    |
|         | 10GHz ~ 26GHz   | Fig.20       | Pass    |




Fig. Transmitter spurious emission-Conducted of BLE in channel 0,(30MHz~1GHz)




Fig. Transmitter spurious emission-Conducted of BLE in channel 0,( 1GHz ~10GHz)




Fig. Transmitter spurious emission-Conducted of BLE in channel 0,( 10GHz ~26GHz)




Fig. Transmitter spurious emission-Conducted of BLE in channel 19,(30MHz ~1GHz)




Fig. Transmitter spurious emission-Conducted of BLE in channel 19,( 1GHz ~10GHz)




Fig. Transmitter spurious emission-Conducted of BLE in channel 19,( 10GHz ~26GHz)




Fig. Transmitter spurious emission-Conducted of BLE in channel 39,( 30MHz ~1GHz)





Fig. Transmitter spurious emission-Conducted of BLE in channel 39,( 1GHz ~10GHz)



**Fig. Transmitter spurious emission-Conducted of BLE in channel 39,( 10GHz ~26GHz)**

## B.6 Radiated Emissions

### B.6.1 Limit of Radiated Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below

| Frequency(MHz) | Field Strength(microvolts/meters) | Measurement Distance(Meters) |
|----------------|-----------------------------------|------------------------------|
| 0.009-0.490    | 2400/F(kHz)                       | 3000                         |
| 0.490-1.705    | 24000/F(kHz)                      | 30                           |
| 1.705-30.0     | 30                                | 30                           |
| 30-88          | 100                               | 3                            |
| 88-216         | 150                               | 3                            |
| 216-960        | 200                               | 3                            |
| above 960      | 500                               | 3                            |

### B.6.2 Test Procedure

- The EUT was placed on a turntable with 1.5 meter above ground.
- The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the antenna is varied between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
- For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower(from 1 m to 4 m)and turntable(from 0 degree to 360 degrees)to find the maximum reading.

f. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode. SA setting: Span= wide enough to fully capture the emission being measured; RBW=1MHz ( $f > 1\text{GHz}$ ), RBW=100kHz ( $f < 1\text{GHz}$ ), VBW  $\geq$  RBW, Sweep time=auto, Trace= Max hold. Above 18GHz shall be extrapolated to specified distance using an extrapolation factor 20dB/decade from 3m to 1m.


g. If the emission level of the EUT in peak mode was 20dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the quasi-peak method and reported.

h. Emission level (dB $\mu\text{V}/\text{m}$ ) =  $20 \log \text{Emission level } (\mu\text{V}/\text{m})$ .


### B.6.3 Test Setup


| Frequency Band(MHz) | Function | Resolution Bandwidth | Video Bandwidth |
|---------------------|----------|----------------------|-----------------|
| 30 to 1000          | QP       | 100kHz               | 100kHz          |
| Above 1000          | Peak     | 1MHz                 | 1MHz            |
|                     | Average  | 1MHz                 | 10Hz            |

#### Radiated Emissions Frequency: Below 1GHz



#### Radiated Emissions Frequency: above 1GHz









**Test Mode: Traffic**


**Verdict: Pass**




**Fig. Radiated Emission of channel 0 in 30MHz-1GHz**




**Fig. Radiated Emission of channel 0 in 1GHz-6GHz**




**Fig. Radiated Emission of channel 19 in 30MHz-1GHz**



**Fig. Radiated Emission of channel 19 in 1GHz-6GHz**



**Fig. Radiated Emission of channel 39 in 30MHz-1GHz**



**Fig. Radiated Emission of channel 39 in 1GHz-6GHz**

## B.7 AC Conducted Emission


### B.7.1 Description

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits

### B.7.2 Test Procedure

- a) The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b) Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c) All the support units are connecting to the other LISN.
- d) The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e) The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- f) Both sides of AC line were checked for maximum conducted interference.
- g) The frequency range from 150 kHz to 30 MHz was searched.
- h) Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

### B.7.3 Test Setup



**B.7.4 Test Results****Limit**

| Frequency of Emission(MHz) | Conducted Limit(dB $\mu$ V) |           |
|----------------------------|-----------------------------|-----------|
|                            | Quasi -Peak                 | Average   |
| 0.15-0.5                   | 66 to 56*                   | 56 to 46* |
| 0.5-5                      | 56                          | 46        |
| 5-30                       | 60                          | 50        |

\*Decreases with logarithm of the frequency

**LINE L****Scan Settings (1 Range)**

| Frequencies |        |       | Receiver Settings |        |       |        |
|-------------|--------|-------|-------------------|--------|-------|--------|
| Start       | Stop   | Step  | Res BW            | M-Time | Atten | Preamp |
| 150 kHz     | 30 MHz | 4 kHz | 9 kHz (6dB)       | 5 ms   | Auto  | Off    |

**Final Measurement**


Detectors: AV, QP

Meas Time: see scan settings

Peaks: 6

Acc. Margin: 10 dB

**Pre-measurement Graph**



## Final Measurement Results

| Trace | Frequency (MHz) | Level (dB $\mu$ V) | Limit (dB $\mu$ V) | Delta Limit (dB) | Delta Ref (dB) | Comment |
|-------|-----------------|--------------------|--------------------|------------------|----------------|---------|
| /     | /               | /                  | /                  | /                | /              | /       |

\* = limit exceeded

## LINE N


### Scan Settings (1 Range)

| Frequencies |        |         | Receiver Settings |        |       |        |
|-------------|--------|---------|-------------------|--------|-------|--------|
| Start       | Stop   | Step    | Res BW            | M-Time | Atten | Preamp |
| 150 kHz     | 30 MHz | 4.5 kHz | 9kHz (6dB)        | 15 ms  | Auto  | Off    |

### Final Measurement

|            |        |              |       |
|------------|--------|--------------|-------|
| Detectors: | AV, QP | Meas Time:   | 1 s   |
| Peaks:     | 6      | Acc. Margin: | 10 dB |

### Pre-measurement Graph



### Final Measurement Results

| Trace | Frequency (MHz) | Level (dB $\mu$ V) | Limit (dB $\mu$ V) | Delta Limit (dB) | Delta Ref (dB) | Comment |
|-------|-----------------|--------------------|--------------------|------------------|----------------|---------|
| 1 AV  | 0.564           | 31.39              | 46.00              | -14.61           | /              | N / on  |

\* = limit exceeded

## B.8 Antenna Requirements

### B.8.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### B.8.2 Antenna Connected construction

The Antenna type used in this product is PIFA Antenna without connector and it is considered to meet antenna requirement.

### B.8.3 Antenna Gain

The antenna peak gain of EUT is less than 6dBi, Therefore, it is not necessary to reduced maximum peak output power limit.

**ANNEX C: Report Revision History**

| <b>Report NO.</b> | <b>Report version</b> | <b>Description</b> | <b>Issue Date</b> |
|-------------------|-----------------------|--------------------|-------------------|
| <b>150934-BLE</b> | <b>NONE</b>           | <b>Original</b>    | <b>2015.12.14</b> |
|                   |                       |                    |                   |
|                   |                       |                    |                   |

**\*\*\*END OF REPORT\*\*\***