

**TEST REPORT****Report No.: 16060119HKG-001****Philips Lighting (China) Investment Co., Ltd.**

Application  
For  
Certification  
(Original Grant)  
**(FCC ID: 2AGBW9290011152X)  
(IC: 20812-1152X)**

Transceiver

Prepared and Checked by:

Signed On File  
Lee Shui Tim, Tim  
Lead Engineer

Approved by:

---

Koo Wai Ip  
Assistant Supervisor  
Date: July 12, 2016

- Intertek's standard Terms and Conditions can be obtained at our website <http://www.intertek.com/terms/>.
- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- © 2016 Intertek

## INTERTEK TESTING SERVICES

---

### GENERAL INFORMATION

Grantee:	Philips Lighting (China) Investment Co., Ltd.
Grantee Address:	Building 9, Lane 888, Tianlin Road, Minhang District, Shanghai 200233 China.
Contact Person:	Tao Huang
Tel:	(86) 21 2412 7510
Fax:	(86) 21 5445 1520
e-mail:	N/A
Manufacturer:	Philips Lighting (China) Investment Co., Ltd.
Manufacturer Address:	Building 9, Lane 888, Tianlin Road, Minhang District, Shanghai 200233 China.
Brand Name:	PHILIPS
Model:	9290011152
Type of EUT:	Transceiver
Description of EUT:	Remote Switch
Serial Number:	N/A
FCC ID / IC:	2AGBW9290011152X / 20812-1152X
Date of Sample Submitted:	June 01, 2016
Date of Test:	June 01, 2016 to June 20, 2016
Report No.:	16060119HKG-001
Report Date:	July 12, 2016
Environmental Conditions:	Temperature: +10 to 40°C Humidity: 10 to 90%

# INTERTEK TESTING SERVICES

---

## SUMMARY OF TEST RESULT

TEST SPECIFICATION	REFERENCE	RESULTS
Transmitter Power Line Conducted Emissions	15.207 / RSS-Gen 8.8	Pass
Radiated Emission Radiated Emission on the Bandedge	15.249, 15.209 / RSS-210 A2.9, RSS-210 2.5	Pass
Radiated Emission in Restricted Bands	15.205 / RSS-210 2.2	Pass

The equipment under test is found to be complying with the following standards:

FCC Part 15, October 1, 2014 Edition

RSS-210 Issue 8, December 2010

RSS-Gen Issue 4, November 2014

Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.

2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

# INTERTEK TESTING SERVICES

---

## Table of Contents

1.0	<b><u>General Description</u></b>	1
1.1	Product Description	1
1.2	Related Submittal(s) Grants	1
1.3	Test Methodology	1
1.4	Test Facility	1
2.0	<b><u>System Test Configuration</u></b>	2
2.1	Justification	2
2.2	EUT Exercising Software	2
2.3	Special Accessories	2
2.4	Measurement Uncertainty	2
2.5	Support Equipment List and Description	2
3.0	<b><u>Emission Results</u></b>	3
3.1	Field Strength Calculation	3
3.2	Radiated Emission Configuration Photograph	4
3.3	Radiated Emission Data	4
4.0	<b><u>Equipment Photographs</u></b>	9
5.0	<b><u>Product Labelling</u></b>	9
6.0	<b><u>Technical Specifications</u></b>	9
7.0	<b><u>Instruction Manual</u></b>	9
8.0	<b><u>Miscellaneous Information</u></b>	10
8.1	Radiated Emission on the Bandedge	10
8.2	Discussion of Pulse Desensitization	13
8.3	Calculation of Average Factor	13
8.4	Emissions Test Procedures	15
8.5	Occupied Bandwidth	17
9.0	<b><u>Confidentiality Request</u></b>	18
10.0	<b><u>Equipment List</u></b>	18

## INTERTEK TESTING SERVICES

---

### 1.0 General Description

#### 1.1 Product Description

The Equipment Under Test (EUT) is a Zigbee Remote Switch. The EUT can operate with Zigbee Lightening equipment (provide by client). The Zigbee portion occupies frequency range of 2405MHz to 2475MHz (14 channels with channel spacing of 5MHz).

Any button press cause a fixed magnet to move along coil which generates electricity. The EUT is powered by this bit of power.

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

#### 1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver.

#### 1.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). All radiated measurements were performed in an 3m Chamber. Preliminary scans were performed in the 3m Chamber only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the **“Justification Section”** of this Application.

#### 1.4 Test Facility

The 3m Chamber used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong. This test facility and site measurement data have been placed on file with the FCC and IC.

## INTERTEK TESTING SERVICES

---

### 2.0 System Test Configuration

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The device was powered by 3VDC.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

#### 2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

#### 2.5 Support Equipment List and Description

Zigbee Light Strip  
(Provided by Applicant)

## INTERTEK TESTING SERVICES

---

### 3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

#### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where  $FS$  = Field Strength in  $\text{dB}\mu\text{V}/\text{m}$

$RA$  = Receiver Amplitude (including preamplifier) in  $\text{dB}\mu\text{V}$

$CF$  = Cable Attenuation Factor in dB

$AF$  = Antenna Factor in dB

$AG$  = Amplifier Gain in dB

$AV$  = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where  $FS$  = Field Strength in  $\text{dB}\mu\text{V}/\text{m}$

$RR$  =  $RA - AG - AV$  in  $\text{dB}\mu\text{V}$

$LF$  =  $CF + AF$  in dB

Assume a receiver reading of 52.0  $\text{dB}\mu\text{V}$  is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 32  $\text{dB}\mu\text{V}/\text{m}$ . This value in  $\text{dB}\mu\text{V}/\text{m}$  was converted to its corresponding level in  $\mu\text{V}/\text{m}$ .

$$RA = 52.0 \text{ dB}\mu\text{V}/\text{m}$$

$$AF = 7.4 \text{ dB}$$

$$RR = 18.0 \text{ dB}\mu\text{V}$$

$$CF = 1.6 \text{ dB}$$

$$LF = 9.0 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$AV = 5.0 \text{ dB}$$

$$FS = RR + LF$$

$$FS = 18 + 9 = 27 \text{ dB}\mu\text{V}/\text{m}$$

$$\text{Level in } \mu\text{V}/\text{m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V}/\text{m})/20] = 22.4 \mu\text{V}/\text{m}$$

## **INTERTEK TESTING SERVICES**

---

### **3.2 Radiated Emission Configuration Photograph**

The worst case in radiated emission was found at 822.184 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

### **3.3 Radiated Emission Data**

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 11.8 dB

# INTERTEK TESTING SERVICES

---

Applicant: Philips Lighting (China) Investment Co., Ltd.      Date of Test: June 20, 2016  
 Model: 9290011152  
 Worst-Case Operating Mode: Transmitting

Table 1  
**Radiated Emissions**  
**Pursuant to FCC Part 15 Section 15.249 / RSS-210 A2.9 Requirement**

Lowest Channel

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Average Factor (dB)	Calculated at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2400.000	64.9	33	29.4	61.3	30.8	30.5	54.0	-23.5
H	2405.000	101.5	33	29.4	97.9	30.8	67.1	94.0	-26.9
<b>H</b>	<b>4810.000</b>	<b>47.7</b>	<b>33</b>	<b>34.9</b>	<b>49.6</b>	<b>30.8</b>	<b>18.8</b>	<b>54.0</b>	<b>-35.2</b>
H	7215.000	44.5	33	37.9	49.4	30.8	18.6	54.0	-35.4
H	9620.000	41.1	33	40.4	48.5	30.8	17.7	54.0	-36.3
<b>H</b>	<b>12025.000</b>	<b>43.2</b>	<b>33</b>	<b>40.5</b>	<b>50.7</b>	<b>30.8</b>	<b>19.9</b>	<b>54.0</b>	<b>-34.1</b>
H	14430.000	14.2	33	40.0	52.0	30.8	21.2	54.0	-32.8

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2400.000	64.9	33	29.4	61.3	74.0	-12.7
H	2405.000	101.5	33	29.4	97.9	114.0	-16.1
<b>H</b>	<b>4810.000</b>	<b>47.7</b>	<b>33</b>	<b>34.9</b>	<b>49.6</b>	<b>74.0</b>	<b>-24.4</b>
H	7215.000	44.5	33	37.9	49.4	74.0	-24.6
H	9620.000	41.1	33	40.4	48.5	74.0	-25.5
<b>H</b>	<b>12025.000</b>	<b>43.2</b>	<b>33</b>	<b>40.5</b>	<b>50.7</b>	<b>74.0</b>	<b>-23.3</b>
H	14430.000	45.0	33	40.0	52.0	74.0	-22.0

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

5. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 Section 2.2.

6. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

# INTERTEK TESTING SERVICES

---

Applicant: Philips Lighting (China) Investment Co., Ltd.      Date of Test: June 20, 2016  
 Model: 9290011152  
 Worst-Case Operating Mode: Transmitting

Table 2  
**Radiated Emissions**  
**Pursuant to FCC Part 15 Section 15.249 / RSS-210 A2.9 Requirement**

Middle Channel

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Average Factor (dB)	Calculated at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2450.000	101.6	33	29.4	98.0	30.8	67.2	94.0	-26.8
<b>H</b>	<b>4900.000</b>	<b>47.4</b>	<b>33</b>	<b>34.9</b>	<b>49.3</b>	<b>30.8</b>	<b>18.5</b>	<b>54.0</b>	<b>-35.5</b>
<b>H</b>	<b>7350.000</b>	<b>44.7</b>	<b>33</b>	<b>37.9</b>	<b>49.6</b>	<b>30.8</b>	<b>18.8</b>	<b>54.0</b>	<b>-35.2</b>
H	9800.000	40.8	33	40.4	48.2	30.8	17.4	54.0	-36.6
<b>H</b>	<b>12250.000</b>	<b>43.1</b>	<b>33</b>	<b>40.5</b>	<b>50.6</b>	<b>30.8</b>	<b>19.8</b>	<b>54.0</b>	<b>-34.2</b>
H	14700.000	46.4	33	38.4	51.8	30.8	21.0	54.0	-33.0

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2450.000	101.6	33	29.4	98.0	114.0	-16.0
<b>H</b>	<b>4900.000</b>	<b>47.4</b>	<b>33</b>	<b>34.9</b>	<b>49.3</b>	<b>74.0</b>	<b>-24.7</b>
<b>H</b>	<b>7350.000</b>	<b>44.7</b>	<b>33</b>	<b>37.9</b>	<b>49.6</b>	<b>74.0</b>	<b>-24.4</b>
H	9800.000	40.8	33	40.4	48.2	74.0	-25.8
<b>H</b>	<b>12250.000</b>	<b>43.1</b>	<b>33</b>	<b>40.5</b>	<b>50.6</b>	<b>74.0</b>	<b>-23.4</b>
H	14700.000	46.4	33	38.4	51.8	74.0	-22.2

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

5. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 Section 2.2.

6. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## INTERTEK TESTING SERVICES

---

Applicant: Philips Lighting (China) Investment Co., Ltd.      Date of Test: June 20, 2016  
 Model: 9290011152  
 Worst-Case Operating Mode: Transmitting

Table 3  
**Radiated Emissions**  
**Pursuant to FCC Part 15 Section 15.249 / RSS-210 A2.9 Requirement**

### Highest Channel

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Average Factor (dB)	Calculated at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2475.000	101.7	33	29.4	98.1	30.8	67.3	94.0	-26.7
H	2483.500	63.4	33	29.4	59.8	30.8	29.0	54.0	-25.0
<b>H</b>	<b>4950.000</b>	<b>47.9</b>	<b>33</b>	<b>34.9</b>	<b>49.8</b>	<b>30.8</b>	<b>19.0</b>	<b>54.0</b>	<b>-35.0</b>
<b>H</b>	<b>7425.000</b>	<b>44.4</b>	<b>33</b>	<b>37.9</b>	<b>49.3</b>	<b>30.8</b>	<b>18.5</b>	<b>54.0</b>	<b>-35.5</b>
H	9900.000	41.3	33	40.4	48.7	30.8	17.9	54.0	-36.1
<b>H</b>	<b>12375.000</b>	<b>43.4</b>	<b>33</b>	<b>40.5</b>	<b>50.9</b>	<b>30.8</b>	<b>20.1</b>	<b>54.0</b>	<b>-33.9</b>
H	14850.000	15.9	33	38.4	52.1	30.8	21.3	54.0	-32.7

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2475.000	101.7	33	29.4	98.1	114.0	-15.9
H	2483.500	63.4	33	29.4	59.8	74.0	-14.2
<b>H</b>	<b>4950.000</b>	<b>47.9</b>	<b>33</b>	<b>34.9</b>	<b>49.8</b>	<b>74.0</b>	<b>-24.2</b>
<b>H</b>	<b>7425.000</b>	<b>44.4</b>	<b>33</b>	<b>37.9</b>	<b>49.3</b>	<b>74.0</b>	<b>-24.7</b>
H	9900.000	41.3	33	40.4	48.7	74.0	-25.3
<b>H</b>	<b>12375.000</b>	<b>43.4</b>	<b>33</b>	<b>40.5</b>	<b>50.9</b>	<b>74.0</b>	<b>-23.1</b>
H	14850.000	46.7	33	38.4	52.1	74.0	-21.9

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.
5. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 Section 2.2.
6. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## INTERTEK TESTING SERVICES

---

Applicant: Philips Lighting (China) Investment Co., Ltd.      Date of Test: June 20, 2016  
Model: 9290011152  
Worst-Case Operating Mode: Transmitting Other

Table 4  
**Radiated Emissions**  
**Pursuant to FCC Part 15 Section 15.209 Requirement**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	81.803	29.1	16	7.0	20.1	40.0	-19.9
V	154.471	25.2	16	15.0	24.2	43.5	-19.3
V	316.403	13.8	16	23.0	20.8	46.0	-25.2
V	426.090	16.2	16	25.0	25.2	46.0	-20.8
V	525.053	14.4	16	27.0	25.4	46.0	-20.6
V	822.184	19.2	16	31.0	34.2	46.0	-11.8

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

5. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

6. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## INTERTEK TESTING SERVICES

---

### 4.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

### 5.0 Product Labelling

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

### 6.0 Technical Specifications

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

### 7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States and Canada.

## INTERTEK TESTING SERVICES

---

### 8.0 Miscellaneous Information

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor.


#### 8.1 Radiated Emission on the Bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz to 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.10 (2013) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209 / RSS-210 2.5, whichever is the lesser attenuation, which meet the requirement of part 15.249(d) / RSS-210 A2.9.

# INTERTEK TESTING SERVICES

## Peak Measurement



## INTERTEK TESTING SERVICES

---

### Peak Measurement

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

$$=97.9 \text{ dB}\mu\text{V/m} - 38.4 \text{ dB}$$

$$=59.5 \text{ dB}\mu\text{V/m}$$

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

$$=97.9 \text{ dB}\mu\text{V/m} - 38.4 \text{ dB} - 30.8 \text{ dB}$$

$$=28.7 \text{ dB}\mu\text{V/m}$$

Upper bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

$$=98.1 \text{ dB}\mu\text{V/m} - 45.67 \text{ dB}$$

$$=52.43 \text{ dB}\mu\text{V/m}$$

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

$$=98.1 \text{ dB}\mu\text{V/m} - 45.67 \text{ dB} - 30.8 \text{ dB}$$

$$=21.6 \text{ dB}\mu\text{V/m}$$

The resultant field strength meets the general radiated emission limit in Section 15.209 / RSS-210 2.5, which does not exceed 74 dB $\mu$ V/m (Peak Limit) and 54 dB $\mu$ V/m (Average Limit).

## INTERTEK TESTING SERVICES

---

### 8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period ( $T_{eff}$ ) is approximately 0.96ms for a digital "1" bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 3MHz, so the pulse desensitivity factor is 0dB.

### 8.3 Calculation of Average Factor

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 100 ms



Effective period of the cycle =  $0.96*3$  ms

$DC = 2.88 \text{ ms} / 100 \text{ ms} = 0.0288$

Therefore, the averaging factor is found by  $20\log 0.0288 = -30.8\text{dB}$ .

# INTERTEK TESTING SERVICES

## Average Factor occurred at Normal Operation



## INTERTEK TESTING SERVICES

---

### 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately 0.8m in height above the ground plane for emission measurement at or below 1GHz and 1.5m in height above the ground plane for emission measurement above 1GHz. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

## INTERTEK TESTING SERVICES

---

### 8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.10 (2013).


The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 3 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.


## INTERTEK TESTING SERVICES

### 8.4.1 Radiated Emission Test Setup

The figure below shows the test setup, which is utilized to make these measurements.



Test setup of radiated emissions up to 1GHz



Test setup of radiated emissions above 1GHz


## INTERTEK TESTING SERVICES

### 8.5 Occupied Bandwidth

#### Occupied Bandwidth Results:

	Occupied Bandwidth (MHz)
Low Channel: 2405	2.32
Middle Channel: 2450	2.36
High Channel: 2475	2.38

The worst case is shown as below



## INTERTEK TESTING SERVICES

---

### 9.0 Confidentiality Request

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: request.pdf.

### 10.0 Equipment List

#### 1) Radiated Emissions Test

Equipment	EMI Test Receiver	Spectrum Analyzer
Registration No.	EW-3156	EW-2466
Manufacturer	R&S	R&S
Model No.	ESR26	FSP30
Calibration Date	Nov. 03, 2015	Sep. 16, 2015
Calibration Due Date	Nov. 03, 2016	Aug. 20, 2016

Equipment	BiConiLog Antenna	Pyramidal Horn Antenna	Double Ridged Guide Antenna
Registration No.	EW-3061	EW-0905	EW-1133
Manufacturer	EMCO	EMCO	EMCO
Model No.	3412E	3160-09	3115
Calibration Date	Jul. 22, 2015	Feb. 12, 2016	Nov. 05, 2015
Calibration Due Date	Jul. 22, 2016	Aug. 12, 2017	May 05, 2017

#### 2) Bandedge Measurement

Equipment	Spectrum Analyzer
Registration No.	EW-2249
Manufacturer	R&S
Model No.	FSP30
Calibration Date	Nov. 27, 2015
Calibration Due Date	Nov. 27, 2016

END OF TEST REPORT