



# RF Exposure Evaluation Declaration

Product Name : LED lamp

Model No. : 9290020398

FCC ID : 2AGBW9290020398X

Applicant : Signify (China) Investment Co., Ltd.

Address : Building no.9, Lane 888, Tianlin Road, Minhang  
District, Shanghai 200233, China

Date of Receipt : Mar. 05, 2019

Test Date : Mar. 06, 2019 ~ May. 07, 2019

Issued Date : May. 30, 2019

Report No. : 1952115R-RF-US-P20V01

Report Version : V1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by A2LA or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing & Certification (Suzhou) Co., Ltd.

# Test Report Certification

Issued Date : May. 30, 2019

Report No. : 1952115R-RF-US-P20V01



Product Name : LED lamp  
Applicant : Signify (China) Investment Co., Ltd.  
Address : Building no.9, Lane 888, Tianlin Road, Minhang District, Shanghai 200233, China  
Manufacturer : Signify (China) Investment Co., Ltd.  
Address : Building no.9, Lane 888, Tianlin Road, Minhang District, Shanghai 200233, China  
Model No. : 9290020398  
FCC ID : 2AGBW9290020398X  
Brand name : PHILIPS  
EUT Voltage : 110-130Vac,50-60Hz,5.5W  
Test Voltage : AC120V/60Hz  
Applicable Standard : KDB 447498D01V06  
FCC Part1.1310  
Test Result : Complied  
Performed Location : DEKRA Testing & Certification (Suzhou) Co., Ltd.  
No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006, Jiangsu, China  
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098  
FCC Designation Number: CN1199  
Documented By :   
(Adm. Specialist: Kitty Li)  
Reviewed By :   
(Senior Project Manager: Frank He)  
Approved By :   
(Engineering Supervisor: Jack Zhang)

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

#### Friis Formula

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

$P_d$  = power density in mW/ cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$r$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

## 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18 °C and 78% RH.

## 1.3. Test Result of RF Exposure Evaluation

Product	:	LED lamp
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-6

### ● Antenna Information:

Antenna manufacturer	N/A		
Antenna Delivery	<input checked="" type="checkbox"/> 1*TX+1*RX	<input type="checkbox"/> 2*TX+2*RX	<input type="checkbox"/> 3*TX+3*RX
Antenna technology	<input checked="" type="checkbox"/> SISO <input type="checkbox"/> MIMO		
	<input type="checkbox"/> Basic		
	<input type="checkbox"/> CDD		
	<input type="checkbox"/> Beam-forming		
Antenna Type	<input type="checkbox"/> External	<input type="checkbox"/> Dipole	
	<input type="checkbox"/> Internal	<input type="checkbox"/> PIFA	
	<input checked="" type="checkbox"/> PCB		
	<input type="checkbox"/> Ceramic Chip Antenna		
	<input type="checkbox"/> Monopole antenna		
	<input type="checkbox"/> Stamping Antenna		
	<input type="checkbox"/> Metal plate type F antenna		
Antenna Gain	-3.8dBi		

- **Power Density:**

Test Mode	Frequency Band (MHz)	EIRP (dBm)	Limit of Power Density S(mW/cm <sup>2</sup> )	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
BT	2400 ~ 2483.5	13.41	1	0.0018

Note:

The maximum power density is 0.0018mW/cm<sup>2</sup> for LED lamp without any other radio equipment.

---

 The End 

---