

FCC SAR Measurement and Test Report

For

Smartron India Private Limited

1st Floor, Kapil Tower, Gachibowli, Hyderabad, Telangana

FCC ID: 2AGCE-T1211

FCC Part 2.1093

ANSI / IEEE C95.1:2006

Test Standards: ANSI / IEEE C95.3 :2002

Product Description: <u>Tablet PC</u>

Tested Model: T1211

Report No.: <u>STR15098043H</u>

Max. SAR Values: Body: 1.488 W/kg(1g)

Tested Date: 2016-02-25 to 2016-02-26

Issued Date: <u>2016-02-29</u>

Tested By: <u>Lucy Wei / Engineer</u>

Reviewed By: Silin Chen / EMC Manager

Approved & Authorized By: Jandy So / PSQ Manager

Prepared By:

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,

way wej Silim chen Jungso

Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM. Test Technology Co., Ltd.



TABLE OF CONTENTS

1. General Information	
1.1 Product Description for Equipment Under Test (EUT)	
1.2 Test Standards	
1.3 Test Methodology	
1.4 Test Facility	
2. Summary of Test Results	
3. Specific Absorption Rate (SAR)	
3.1 Introduction	
4. SAR Measurement System	
4.1 The Measurement System	
4.1 The Measurement System 4.2 Probe	
4.3 Probe Calibration Process	
4.4 Phantom	
4.5 Device Holder	
4.6 Test Equipment List	
5. Tissue Simulating Liquids	
5.1 Composition of Tissue Simulating Liquid	
5.2 Tissue Dielectric Parameters for Head and Body Phantoms	
5.3 Tissue Calibration Result	
6. SAR Measurement Evaluation	
6.1 Purpose of System Performance Check	
6.2 System Setup	
7. EUT Testing Position	
7. EUT Testing Position	
7.1 EUT Antenna Position	
8. SAR Measurement Procedures	
8.1 Measurement Procedures	
8.2 Spatial Peak SAR Evaluation	
8.3 Area & Zoom Scan Procedures	
8.4 Volume Scan Procedures	21
8.5 SAR Averaged Methods	
8.6 Power Drift Monitoring	
9. SAR Test Result	
9.1 Conducted RF Output Power	
9.2 Test Results for Standalone SAR Test	
9.3 Simultaneous Multi-band Transmission SAR Analysis	
10. Measurement Uncertainty	
10.1 Uncertainty for EUT SAR Test	
• •	
Annex B. Blets of SAR Magazzament	
Annex C. FUT Photos	
Annex C. EUT Photos	
Annex D. Test Setup Photos	
Annex E. Calibration Certificate	39





1. General Information

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Smartron India Private Limited

Address of applicant: 1st Floor, Kapil Tower, Gachibowli, Hyderabad, Telangana

Manufacturer: Shenzhen Wisky Technology Co., LTD.

Address of manufacturer: 5th Floor, W2-A Building, Hi-tech Park South 1st Road,

Nanshan District, Shenzhen

General Description of EUT	
Product Name:	Tablet PC
Trade Name:	SMARTRON
Model No.:	T1211
Adding Model(s):	1
Rated Voltage:	DC 7.4V battery, Adapter DC 12V charging
Dower Adapter Medal:	PSY1203000
Power Adapter Model:	I/P: AC 100-240V; O/P: DC 12V/3A
Note: The test data is gathered fro	m a production sample provided by the manufacturer.

Report No.: STR15098043H Page 3 of 39 SAR Report





Technical Characteristics of E	UT:
WIFI (2.4G)	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 11b/g/n(HT20) 2422-2452MHz for 11n(HT40)
RF Output Power:	Antenna 1: 13.42dBm, Antenna 2:15.30dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11/7
Channel Separation:	5MHz
Antenna Type:	Internal Antenna
Antenna Gain:	Antenna 1:2.26dBi, Antenna 2:3.59dBi
Bluetooth	
Bluetooth Version:	V4.0
Frequency Range:	2402-2480MHz
RF Output Power:	1.584dBm (Conducted)
Data Rate:	1Mbps, 2Mbps, 3Mbps
Modulation:	GFSK, Pi/4 QDPSK, 8DPSK
Quantity of Channels:	79/40
Channel Separation:	1MHz/2MHz
Antenna Type:	Internal Antenna
Antenna Gain:	2.26dBi

Report No.: STR15098043H Page 4 of 39 SAR Report



1.2 Test Standards

The following report is prepared on behalf of the Smartron India Private Limited in accordance with FCC 47 CFR Part 2.1093, ANSI/IEEE C95.1-2005, ANSI / IEEE C95.3:2002, IEEE 1528-2013, and KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02.

The objective is to determine compliance with FCC Part 2.1093 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02. The public notice KDB 447498 D01 v06 for Mobile and Portable Devices RF Exposure Procedure also.

1.4 Test Facility

• FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

• CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101)

Report No.: STR15098043H Page 5 of 39 SAR Report





2. Summary of Test Results

The maximum results of Specific Absorption Rate (SAR) have found during testing are as follows:

Frequency Band	Body (0mm Gap) Maximum SAR _{1g} (W/kg)	SAR _{1g} Limit (W/kg)	
Antenna 1:WLAN 2.4G	0.799	1.6	
Antenna 2:WLAN 2.4G	0.689	1.6	
simultaneous transmission	1.488	1.6	

The device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2.1093 and ANSI/IEEE C95.1-2005, and had been tested in accordance with the measurement methods and procedure specified in KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02

Report No.: STR15098043H Page 6 of 39 SAR Report





3. Specific Absorption Rate (SAR)

3.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techiques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

3.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = C\left(\frac{\delta T}{\delta t}\right)$$

Where: C is the specific heat capacity, δ T is the temperature rise and δ t is the exposure duration, or related to the

electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

Report No.: STR15098043H Page 7 of 39 SAR Report



4. SAR Measurement System

4.1 The Measurement System

Comosar is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The Comosar system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 10g mass.

4.2 Probe

For the measurements the Specific Dosimetric E-Field Probe SSE5 SN 09/13 EP168 with following specifications is used

- Dynamic range: 0.01-100 W/kg

- Probe Length: 330 mm

- Length of Individual Dipoles: 4.5 mm- Maximum external diameter: 8 mm- Probe Tip External Diameter: 5 mm

- Distance between dipoles / probe extremity: 2.7mm

Report No.: STR15098043H Page 8 of 39 SAR Report




- Probe linearity: <0.25 dB
- Axial Isotropy: <0.25 dB
- Spherical Isotropy: <0.50 dB

- Calibration range: 700 to 3000MHz for head & body simulating liquid.

Angle between probe axis (evaluation axis) and suface normal line:1ess than 30°

Probe calibration is realized, in compliance with EN 62209-1 and IEEE 1528 STD, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the EN 62209-1 annexe technique using reference guide at the five frequencies.



$$SAR = \frac{4\left(P_{fw} - P_{bw}\right)}{ab\delta}\cos^2\left(\pi \frac{y}{a}\right)e^{-(2z/\delta)}$$

Where:

Pfw = Forward Power Pbw = Backward Power

a and b = Waveguide dimensions

I = Skin depth

Keithley configuration:

Rate = Medium; Filter = ON; RDGS = 10; Filter type = Moving Average; Range auto after each calibration, a SAR measurement is performed on a validation dipole and compared with a NPL calibrated probe, to verify it.

Report No.: STR15098043H Page 9 of 39 SAR Report



The calibration factors, CF(N), for the 3 sensors corresponding to dipole 1, dipole 2 and dipole 3 are:

$$CF(N)=SAR(N)/Vlin(N)$$
 (N=1,2,3)

The linearised output voltage Vlin(N) is obtained from the displayed output voltage V(N) using

$$Vlin(N)=V(N)*(1+V(N)/DCP(N))$$
 (N=1,2,3)

where DCP is the diode compression point in mV.

4.3 Probe Calibration Process

Dosimetric Assessment Procedure

Each E-Probe/Probe Amplifier combination has unique calibration parameters. SATIMO Probe calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm2) using an with CALISAR, Antenna proprietary calibration system.

Free Space Assessment Procedure

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1mW/cm2.

Temperature Assessment Procedure

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated head tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

Where:
$$\Delta t = \text{exposure time (30 seconds)},$$

$$C = \text{heat capacity of tissue (brain or muscle)},$$

$$\Delta T = \text{temperature increase due to RF exposure}.$$

SAR is proportional to $\Delta T/\Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. The electric field in the simulated tissue can be used to estimate SAR by equating the thermally derived SAR to that with the E- field component.

Report No.: STR15098043H Page 10 of 39 SAR Report



$$SAR = \frac{\left| \mathbf{E} \right|^2 \cdot \sigma}{\rho}$$

Where:

 $\sigma = \text{simulated tissue conductivity},$


 ρ = Tissue density (1.25 g/cm3 for brain tissue)

4.4 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

4.5 Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1°.



System Material	Permittivity	Loss Tangent
Delrin	3.7	0.005

Report No.: STR15098043H Page 11 of 39 SAR Report





4.6 Test Equipment List

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
E-Field Probe	SATIMO	SSE5	SN 09/13 EP168	2015-06-03	2016-06-02
2450MHz Dipole	SATIMO	SID2450	SN 13/15 DIP 2G450-364	2015-04-13	2016-04-12
Dielectric Probe Kit	SATIMO	SCLMP	SN 47/12 OCPG49	2015-03-16	2016-03-15
SAM Phantom	SATIMO	SAM	SN/ 47/12 SAM95	N/A	N/A
MULTIMETER	KEITHLEY	Keithley 2000	4006367	2015-06-17	2016-06-16
Signal Generator	Rohde & Schwarz	SMR20	100047	2015-06-17	2016-06-16
Universal Tester	Rohde & Schwarz	CMU200	112012	2015-06-17	2016-06-16
Network Analyzer	HP	8753C	2901A00831	2015-06-17	2016-06-16
Data Acquisition Electronics	SATIMO	DAE4	915	2015-06-17	2016-06-16
Directional Couplers	Agilent	778D	20160	2015-06-17	2016-06-16

Report No.: STR15098043H Page 12 of 39 SAR Report



5. Tissue Simulating Liquids

5.1 Composition of Tissue Simulating Liquid

For the measurement of the field distribution inside the SAM phantom with SMTIMO, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. Please see the following photos for the liquid height.



Liquid Height for Body SAR

The Composition of Tissue Simulating Liquid

Frequency	Water	Salt	Triton	HEC	Preventol	DGBE	
(MHz)	(%)	(%)	(%)	(%)	(%)	(%)	
	Body						
2450	55.44	0.32	30.50	0.00	0.00	13.74	

Report No.: STR15098043H Page 13 of 39 SAR Report





5.2 Tissue Dielectric Parameters for Head and Body Phantoms

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

Т Е	Н	ead	Body		
Target Frequency	Conductivity	Permittivity	Conductivity	Permittivity	
(MHz)	(σ)	(E r)	(σ)	(E _r)	
150	0.76	52.3	0.80	61.9	
300	0.87	45.3	0.92	58.2	
450	0.87	43.5	0.94	56.7	
750	0.89	41.9	0.96	55.5	
835	0.90	41.5	0.97	55.2	
900	0.97	41.5	1.05	55.0	
915	0.98	41.5	1.06	55.0	
1450	1.20	40.5	1.30	54.0	
1610	1.29	40.3	1.40	53.8	
1800-2000	1.40	40.0	1.52	53.3	
2450	1.80	39.2	1.95	52.7	
3000	2.40	38.5	2.73	52.0	
5800	5.27	35.3	6.00	48.2	

Report No.: STR15098043H Page 14 of 39 SAR Report





5.3 Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using COMOSAR Dielectric Probe Kit and an Agilent Network Analyzer.

Calibration Result for Dielectric Parameters of Tissue Simulating Liquid

Body Tissue Simulating Liquid									
T	Conductivity Permittivity					T ::4			
Freq.	Temp.	Reading	Target	Delta	Reading	Target	Delta	Limit (%)	Date
MHz.	(0)	(σ)	(σ)	(%)	$(\mathcal{E}\mathbf{r})$	$(\mathcal{E}\mathbf{r})$	(%)	(%)	
2450	21.3	1.91	1.95	-2.05	52.01	52.70	-1.31	±5	2016-02-25

Report No.: STR15098043H Page 15 of 39 SAR Report




6. SAR Measurement Evaluation

6.1 Purpose of System Performance Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

6.2 System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave which comes from a signal generator at frequency 835 MHz and 1900 MHz. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom.



System Verification Setup Block Diagram

Report No.: STR15098043H Page 16 of 39 SAR Report





Setup Photo of Dipole Antenna

The output power on dipole port must be calibrated to 24 dBm(250 mW) before dipole is connected.

6.3 Validation Results

Comparing to the original SAR value provided by SATIMO, the validation data should be within its specification of 10 %. Table 6.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion.

Frequency	Targeted SAR _{1g}	Measured SAR _{1g}	Normalized SAR _{1g}	Tolerance
MHz	(W/kg)	(W/kg)	(W/kg)	(%)
Body				
2450	50.33	12.59	50.36	0.06

Targeted and Measurement SAR


Please refer to Annex A for the plots of system performance check.

Report No.: STR15098043H Page 17 of 39 SAR Report



7. EUT Testing Position

7.1 EUT Antenna Position



Antenna 1

Antenna 2

7.2 EUT Testing Position

Referring to KDB 447498 D01v06 ,SAR Test Exclusion Thresholds for 100 MHz − 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	~
1500	12	24	37	49	61	SAR Test Exclusion
1900	11	22	33	44	54	Threshold (mW)
2450	μ0	19	29	38	48	2 (22)
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

Exclusion Distance Calculation							
Frequency Bands	Service	Maximum Tune-up Power	Avera	Exclusion Distance			
WLAN Antenna 1	802.11b	13.5dBm	13.5dBm 22.39mW		15mm		
WLAN Antenna 2 802.11b 15.5dBm 15.5dBm 35.48mW					20mm		
Note: Refer to Chap	Note: Refer to Chapter 9.1 Conducted RF Output Power						

Remark:

1. Referring to KDB 447498 D01v06 and KDB616217 D04 v01r02, the distance of the antennas to all adjacent edges SAR test exclusion for adjacent edges.

Body mode SAR assessments are required for this device. This EUT was tested in different positions for different SAR test modes, more information as below:

Body SAR tests, Test distance: 0mm						
Antennas	Front	Back	Right Side	Left Side	Top Side	Bottom Side
WLAN(2.4G)	Yes	No	No	No	Yes	No

Remark:

 Referring to KDB 616217 D04 v01r02, KDB 248227 D01 v02r02and KDB 447498 D01 v06, this device is overall diagonal dimension(>20cm) tablet, tested in direct contact (no gap) with flat phantom.

Please refer to Annex D for the EUT test setup photos.

8. SAR Measurement Procedures

Report No.: STR15098043H Page 19 of 39 SAR Report



8.1 Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator (if applicable) or engineering software to transmit RF power continuously (continuous Tx) in the highest power channel.
- (b) Keep EUT to radiate maximum output power or 100% factor (if applicable)
- (c) Measure output power through RF cable and power meter.
- (d) Place the EUT in the positions as Annex E demonstrates.
- (e) Set scan area, grid size and other setting on the SATIMO software.
- (f) Measure SAR results for the highest power channel on each testing position.
- (g) Find out the largest SAR result on these testing positions of each band
- (h) Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.2 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The SATIMO software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine. The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values form the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

Report No.: STR15098043H Page 20 of 39 SAR Report



8.3 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz, and 8x8x8 points with step size 4, 4 and 2.5 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

8.4 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing (step-size is 4, 4 and 2.5 mm). When all volume scan were completed, the software can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.5 SAR Averaged Methods

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimize measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10g and 1 g requires a very fine resolution in the three dimensional scanned data array.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In SATIMO measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

Report No.: STR15098043H Page 21 of 39 SAR Report



9. SAR Test Result

9.1 Conducted RF Output Power

WLAN(2.4G) Antenna 1 - Maximum Average Power							
Test Mode	Test Mode Data Rate		Frequency (MHz)	Average Power (dBm)			
		CH 01	2412	13.42			
802.11b	1Mbps	CH 06	2437	12.69			
		CH 11	2462	12.27			
	54Mbps	CH 01	2412	10.48			
802.11g		CH 06	2437	10.04			
		CH 11	2462	9.83			
		CH 01	2412	10.28			
802.11n (20MHz)	MCS7	CH 06	2437	9.80			
		CH 11	2462	9.51			
		CH 03	2422	8.76			
802.11n (40MHz)	MCS7	CH 06	2437	8.57			
		CH 09	2452	8.53			

WLAN(2.4G) Antenna 2 - Maximum Average Power							
Test Mode	Data Rate	Channel	Frequency (MHz)	Average Power (dBm)			
		CH 01	2412	15.30			
802.11b	1Mbps	CH 06	2437	14.33			
		CH 11	2462	13.15			
	54Mbps	CH 01	2412	10.64			
802.11g		CH 06	2437	9.92			
		CH 11	2462	8.97			
		CH 01	2412	10.44			
802.11n (20MHz)	MCS7	CH 06	2437	9.50			
		CH 11	2462	8.27			
		CH 03	2422	8.83			
802.11n (40MHz)	MCS7	CH 06	2437	8.36			
		CH 09	2452	8.06			

Remark:

- 1. Per KDB 248227 D01 v02r02, choose the highest output power channel to test SAR and determine further SAR exclusion
- 2. Per KDB 248227 D01 v02r02, if 11g and 11n average output power is higher than 1/4 dB higher than 11b mode, SAR will be verified.
- 3. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 1/4 dB higher than those measured at

Report No.: STR15098043H Page 22 of 39 SAR Report



the lowest data rate. For 802.11n mode, SAR test according to the highest power channel with correspondence data rates.

Bluetooth - Maximum Average Power						
Test Mode Data Rate Average Power(dBm)						
GFSK	1Mbps	1.584				
Pi/4 QDPSK	2Mbps	0.312				
8DPSK	3Mbps	-0.390				

Bluetooth - Maximum Average Power							
Test Mode	Data Rate	Data Rate Channel		Average Power (dBm)			
	1Mbps	CH 00	2402	-1.050			
BLE		CH 20	2442	0.094			
		CH 39	2480	-1.048			

Remark:

Bluetooth maximum output power is 1.584dBm, and Maximum Tune-Up output power is 2.0dBm. Per KDB 447498 D01 V06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \cdot [$\sqrt{f(GHz)}$] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR,16 where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation17
- The result is rounded to one decimal place for comparison

Tune-Up Power (dBm)	Max. Power (mW)	Distance (mm)	Frequency (GHz)	Result	Limit
2.0	1.58	5	2.441	0.49	3

The exclusion thresholds is 0.49< 3, therefore, the RF exposure evaluation is not required.

Report No.: STR15098043H Page 23 of 39 SAR Report





9.2 Test Results for Standalone SAR Test

Antenna 1:Body SAR

	WLAN 2.4GHz –Body SAR Test									
Plot		Test	Frequency		Output	Rated	Casling	CAD1	Scaled	
	Mode	Position	СН.	MHz	Power	Limit	Scaling Factor	SAR1g (W/kg)	SAR1g	
No.		Body	CH.	MHZ	(dBm)	(dBm)		(W/Kg)	(W/kg)	
1.	802.11b	Front Side	01	2412	13.42	13.5	1.0186	0.7846	0.7992	
2.	802.11b	Top side	01	2412	13.42	13.5	1.0186	0.2542	0.2589	
Note:	The material o	f EUT back is i	ron. So the	e back side	e of SAR va	lue was not	be scanned.			

Antenna 2:Body SAR

	WLAN 2.4GHz –Body SAR Test									
Plot		Test	Frequ	uency	Output	Output Rated	Casling	CAD1a	Scaled	
	Mode	Position	СН.	MII	Power	Limit	Scaling Factor	SAR1g (W/kg)	SAR1g	
110.	No.	Body	CH. MHz	(dBm)	(dBm)	ractor	(vv/kg)	(W/kg)		
3.	802.11b	Front Side	01	2412	15.30	15.5	1.0471	0.6578	0.6888	
4.	802.11b	Top side	01	2412	15.30	15.5	1.0471	0.1578	0.1652	
Note:	The material o	f EUT back is i	ron, So the	e back side	e of SAR va	lue was not	be scanned.			

Remark: Per KDB 447498 D01 v06, if the highest output channel SAR for each exposure position \leq 0.8 W/kg other channels SAR tests are not necessary.

Report No.: STR15098043H Page 24 of 39 SAR Report



9.3 Simultaneous Multi-band Transmission SAR Analysis

Body SAR

WLAN(2.4G) and WLAN(2.4G)

	Antenna 1	Antenna 2	Summed SAR
Dogition	Scaled SAR	Scaled SAR	
Position	(W/kg)	(W/kg)	(W/kg)
Front	0.7992	0.6888	1.488
Тор	0.2589	0.1652	0.4241

WLAN(2.4G) and Bluetooth

	Antenna 2	Bluetooth	Summed SAR
Position	Scaled SAR	Scaled SAR	(W/kg)
1 osition	(W/kg)	(W/kg)	(11,119)
Front	0.6888	0.0658	0.7546
Тор	0.1652	0.0658	0.231

WLAN(5G) and Bluetooth

·· = (()							
	Antenna 2	Bluetooth	Cummed CAD				
Position	Scaled SAR	Scaled SAR	Summed SAR (W/kg)				
	(W/kg)	(W/kg)					
Front	0.625	0.0658	0.6908				
Тор	0.121	0.0658	0.1868				

Remark:

1. According to the KDB 447498 D01v06, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(GHz)/x}$] W/kg for test separation distances \leq 50 mm;

where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR.

For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01v06 as below:

Bluetooth:

Tune-Up Power	Max. Power	Distance (mm)	Distance (mm) Frequency (GHz)		SAR(1g)
(dBm)	(mW)		1 requeries (Or12)	^	5mm
2.0	1.58	5	2.441	7.5	0.0658

- 2. The maximum SAR summation is calculated based on the same configuration and test position.
- 3. 2.4G WiFi and 5G WiFi cannot transmit simultaneously. For more detail please refer to the report No.

BL-SZ1590111-702 and section 9.3 of this report.

Report No.: STR15098043H Page 25 of 39 SAR Report



10. Measurement Uncertainty

10.1 Uncertainty for EUT SAR Test

a	b	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Sec.	Tol	Prob.	Div.	Ci (1g)	Ci (10g)	1g Ui	10g Ui	Vi
		(+- %)	Dist.				(+-%)	(+-%)	
Measurement System									
Probe calibration	E.2.1	7.0	N	1	1	1	7.00	7.00	œ
Axial Isotropy	E.2.2	2.5	R	√3	(1_Cp)^1/2	(1_Cp)^1/2	1.02	1.02	×
Hemispherical Isotropy	E.2.2	4.0	R	√3	(Cp)^1/2	(Cp)^1/2	1.63	1.63	× ×
Boundary effect	E.2.3	1.0	R	√3	1	1	0.58	0.58	×
Linearity	E.2.4	5.0	R	√3	1	1	2.89	2.89	×
System detection limits	E.2.5	1.0	R	√3	1	1	0.58	0.58	∝
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.02	×
Reponse Time	E.2.7	3.0	R	√3	1	1	1.73	1.73	8
Integration Time	E.2.8	2.0	R	√3	1	1	1.15	1.15	8
RF ambient Conditions – Noise	E.6.1	3.0	R	√3	1	1	1.73	1.73	8
RF ambient Conditions -	E.6.1	3.0	R	√3	1	1	1.73	1.73	×
Reflections									
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	√3	1	1	1.15	1.15	8
Probe positioning with respect to	E.6.3	0.05	R	√3	1	1	0.03	0.03	œ
Phantom Shell									
Extrapolation, interpolation and	E.5	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
integration Algoritms for Max.									
SAR Evaluation									
Test Sample Related									
Test sample positioning	E.4.2	0.03	N	1	1	1	0.03	0.03	N-1
Device Holder Uncertainty	E.4.1	5.00	N	1	1	1	5.00	5.00	
Output power Variation - SAR	E.2.9	12.02	R	√3	1	1	6.94	6.94	8
drift measurement									
SAR scaling	E6.5	0.0	R	√3	1	1	0.0	0.0	8
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and	E.3.1	0.05	R	√3	1	1	0.03	0.03	œ
thickness tolerances)									

Report No.: STR15098043H Page 26 of 39 SAR Report



Uncertainty in SAR correction for	E3.2	1.9	R	√3	1	0.84	1.10	0.90	œ
deviations in permittivity and									
conductivity									
Liquid conductivity - deviation	E.3.2	5.00	R	√3	0.64	0.43	1.85	1.24	8
from target value									
Liquid conductivity -	E.3.3	5.00	N	1	0.64	0.43	3.20	2.15	œ
measurement uncertainty									
Liquid permittivity - deviation	E.3.2	0.37	R	√3	0.6	0.49	0.13	0.10	œ
from target value									
Liquid permittivity -	E.3.3	10.00	N	1	0.6	0.49	6.00	4.90	∞
measurement uncertainty									
Combined Standard Uncertainty			RSS				12.98	12.53	
Expanded Uncertainty			K=2				25.32	24.43	
(95% Confidence interval)									

10.2 Uncertainty for System Performance Check

a	b	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Sec.	Tol	Prob.	Div.	Ci (1g)	Ci (10g)	1g Ui	10g Ui	Vi
		(+- %)	Dist.				(+-%)	(+-%)	
Measurement System									
Probe calibration	E.2.1	7.0	N	1	1	1	7.00	7.00	∞
Axial Isotropy	E.2.2	2.5	R	√3	(1_Cp)^1/2	(1_Cp)^1/2	1.02	1.02	œ
Hemispherical Isotropy	E.2.2	4.0	R	√3	(Cp)^1/2	(Cp)^1/2	1.63	1.63	∞
Boundary effect	E.2.3	1.0	R	√3	1	1	0.58	0.58	œ
Linearity	E.2.4	5.0	R	√3	1	1	2.89	2.89	œ
System detection limits	E.2.5	1.0	R	√3	1	1	0.58	0.58	œ
Modulation response	E.2.5	0	R	√3	0	0	0.0	0.0	∞
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.02	∞
Reponse Time	E.2.7	3.0	R	√3	1	1	1.73	1.73	∞
Integration Time	E.2.8	2.0	R	√3	1	1	1.15	1.15	∞
RF ambient Conditions – Noise	E.6.1	3.0	R	√3	1	1	1.73	1.73	∞
RF ambient Conditions -	E.6.1	3.0	R	√3	1	1	1.73	1.73	∞
Reflections									
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	√3	1	1	1.15	1.15	α

Report No.: STR15098043H Page 27 of 39 SAR Report



						1	1		
Probe positioning with respect to	E.6.3	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Phantom Shell									
Extrapolation, interpolation and	E.5.2	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
integration Algoritms for Max.									
SAR Evaluation									
Dipole									
Dipole axis to liquid Distance	8,E.4.2	1.00	N	$\sqrt{3}$	1	1	0.58	0.58	N-1
Input power and SAR drift	8,6.6.2	12.02	R	√3	1	1	6.94	6.94	∞
measurement									
Deviation of experimental dipole	E.6.4	5.5	R	√3	1	1	3.20	3.20	∞
from numerical dipole									
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and	E.3.1	0.05	R	√3	1	1	0.03	0.03	œ
thickness tolerances)									
Uncertainty in SAR correction for	E3.2	2.0	R	√3	1	0.84	1.10	1.10	×
deviations in permittivity and									
conductivity									
Liquid conductivity - deviation	E.3.2	5.00	R	√3	0.64	0.43	1.85	1.24	
from target value									
Liquid conductivity -	E.3.3	5.00	N	1	0.64	0.43	3.20	2.15	
measurement uncertainty									
Liquid permittivity - deviation	E.3.2	0.37	R	√3	0.6	0.49	0.13	0.10	
from target value									
Liquid permittivity -	E.3.3	10.00	N	1	0.6	0.49	6.00	4.90	M
measurement uncertainty									
Combined Standard Uncertainty			RSS				12.00	11.50	
Expanded Uncertainty			K=2				23.39	22.43	
(95% Confidence interval)									
		1				1	1	1	

Report No.: STR15098043H Page 28 of 39 SAR Report



Annex A. Plots of System Performance Check

MEASUREMENT 1

For Body Liquid

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 02/25/2016

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 5.80; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative Permittivity (real part)	52.010212
Conductivity (S/m)	1.910255
Power Variation (%)	1.369745
Ambient Temperature	21.1
Liquid Temperature	21.2






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	7.119522		
SAR 1g (W/Kg)	12.592360		

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR	0.0000	13.3911	11.7951	9.2945	8.5400	6.3712	4.6225
(W/Kg)							
	13.27 12.25 7.60 WW 6.17 4.50 3.05 2.03	7-		0 17.520.0 22.5 Z (mm)	25.0 27.5 30.0 3	2.5 35.0	



Report No.: STR15098043H Page 30 of 39 SAR Report





Annex B. Plots of SAR Measurement

TYPE	BAND	<u>PARAMETERS</u>
Tablet	Antenna 1:WiFi_802.11b	Measurement 1: Flat Plane with Front side device position on Low Channel in 802.11b mode
Tablet	Antenna 2:WiFi_802.11b	Measurement 3: Flat Plane with Front side device position on Low Channel in 802.11b mode

Remark: SAR plot is showed the highest measured SAR in each exposure configuration, wireless mode and frequency band combination.

Report No.: STR15098043H Page 31 of 39 SAR Report



MEASUREMENT 1

Type: Phone measurement (Complete)
Date of measurement: 02/25/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 5.80; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat Plane
Device Position	Front
Band	WiFi_802.11b
Channels	Low
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	2412.000000
Relative Permittivity (real part)	52.010212
Conductivity (S/m)	1.910255
Power Variation (%)	2.492743
Ambient Temperature	21.1
Liquid Temperature	21.2






Maximum location: X=-2.00, Y=13.00

SAR 10g (W/Kg)	0.453533
SAR 1g (W/Kg)	0.784550

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.0000	0.7863	0.5884	0.4079	0.2991
	0.8-				
	0.7-	\longrightarrow			
	0.6-	+			
	0.6- 0.5- 0.5-				
	≥ 0.5-				
	ි 0.4-				
	0.3-		\rightarrow		
	0.2-				
	0.0 2.5		12.5 15.0 17.5	20.0 22.5 25.0	
			Z (mm)		



Report No.: STR15098043H Page 33 of 39 SAR Report



MEASUREMENT 3

Type: Phone measurement (Complete)
Date of measurement: 02/25/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 5.80; Calibrated: 06/03/2015

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt		
Phantom	Flat Plane		
Device Position	Front		
Band	WiFi_802.11b		
Channels	Low		
Signal	Duty Cycle 1:1		

B. SAR Measurement Results

Frequency (MHz)	2412.000000		
Relative Permittivity (real part)	52.010212		
Conductivity (S/m)	1.910255		
Power Variation (%)	2.492743		
Ambient Temperature	21.1		
Liquid Temperature	21.2		






Maximum location: X=0.00, Y=9.00

SAR 10g (W/Kg)	0.470889		
SAR 1g (W/Kg)	0.657802		

0.00	4.00	9.00	14.00	19.00
0.0000	0.6686	0.4993	0.3714	0.2748
0.7-				
0.6-	\longrightarrow			
₹ 0.5-				
S 04-				
8				
0.3-		++		
0.2				
0.2 - 0.0 2.5	5.0 7.5 10.0	12.5 15.0 17.5	20.0 22.5 25.0	
		Z (mm)		
	0.7- 0.6- 0.5- 0.4- 0.3- 0.2-	0.7- 0.6- 0.5- 0.5- 0.4- 0.3- 0.2- 0.0 2.5 5.0 7.5 10.0	0.7- 0.6- 0.6- 0.8- 0.4- 0.3- 0.2-	0.7- 0.6- 9 0.5- 0.4- 0.3- 0.2- 0.0 2.5 5.0 7.5 10.0 12.5 15.0 17.5 20.0 22.5 25.0



Report No.: STR15098043H Page 35 of 39 SAR Report




Annex C. EUT Photos

EUT View Front



EUT View Back




Report No.: STR15098043H Page 36 of 39 SAR Report



Antenna View

BT/WIFI Antenna 1







Annex D. Test Setup Photos

Test View 1





Top Side







Annex E. Calibration Certificate

Please refer to the exhibit for the calibration certificate

***** END OF REPORT *****

Report No.: STR15098043H Page 39 of 39 SAR Report