

RF-EXPOSURE ASSESSMENT REPORT

FCC 47 CFR Part 2.1091 Industry Canada RSS-102

RF-Exposure evaluation of mobile equipment

Report Reference No...... G0M-1510-5135-TFC091ME-V01

Testing Laboratory Eurofins Product Service GmbH

Address..... Storkower Str. 38c

15526 Reichenwalde

Germany

Accreditation:



A2LA Accredited Testing Laboratory, Certificate No.: 1983.01

FCC Filed Test Laboratory, Reg.-No.: 96970

IC OATS Filing assigned code: 3470A

Applicant's name EMKA Beschlagteile GmbH & Co. KG

Address...... Langenberger Straße 32

42551 Velbert GERMANY

Test specification:

> OET Bulletin 65:1997 RSS-102, Issue 5:2015-03 Safety Code 6:2015-03

Equipment under test (EUT):

Product description AgentE-radino AccessPoint USA/SGP

Model No. 3000-U981-02

Additional Model(s) None

Brand Name(s) EMKA

Hardware version 901.355A001

Firmware / Software version 350000092

FCC-ID: N/A 2AGCT-U98102 IC: N/A

Test result Passed



Possible test case verdicts:			
- neither assessed nor tested		N/N	
- required by standard but not appl. to t	est object:	N/A	
- required by standard but not tested	1	N/T	
- not required by standard for the test of	bject:	N/R	
- test object does meet the requiremen	t:	P (Pass)	
- test object does not meet the requirer	nent:	F (Fail)	
Testing:			
Test Lab Temperature	:	20 – 23 °C	
Test Lab Humidity	:	32 – 38 %	
Date of receipt of test item	:	2015-10-27	
Date (s) of assessment	:	2015-11-18	
Compiled by:	Christian Webe	er	
Assessed by (+ signature): (Responsible for Assessment)	Christian Webe	er	C. Wda
Approved by (+ signature): (Deputy Head of Lab)	Toralf Jahn		Time
Date of issue:	2015-11-18		
Total number of pages:	13		

General remarks:

The test results presented in this report relate only to the object tested.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

Additional comments:



Version History

Version	Issue Date	Remarks	Revised by
01	2015-11-18	Initial Release	



REPORT INDEX

1	EQUIPMENT (TEST ITEM) DESCRIPTION	5
1.1	Reference Documents	6
1.2	Standalone Radiation Sources	7
1.3	Multi-transmitter Modes	8
2	RESULT SUMMARY	9
3	RF-EXPOSURE CLASSIFICATIONS	10
4	ASSESSMENT	11
4.1	MPE Assessment Conditions – 47 CFR 2.1091 / RSS-102	11
4.2	Single-Transmitter Assessment – 47 CFR 2.1091 / RSS-102	13



1 Equipment (Test item) Description

Description	AgentE-radino AccessPoint USA/SGP
Model	3000-U981-02
Additional Model(s)	None
Brand Name(s)	EMKA
Serial number	None
Hardware version	901.355A001
Software / Firmware version	350000092
FCC-ID	N/A 2AGCT-U98102
IC	N/A
Equipment type	End product



1.1 Reference Documents

Document type	Document No.	Issued by	Date
FCC 15.249 Test Report	G0M-1510-1535-TFC249DT-V01	Eurofins Product Service GmbH	2015-11-18



1.2 Standalone Radiation Sources

Mode #	Description			
	Frequency range [MHz]	922.5		
	Transmission modes	GFSK		
	Maximum conducted power [dBm]	-3.49		
922 MHz	Maximum radiated power [dBm]	-2.89		
922 1/11172	Maximum transmission duty cycle [%]	100		
	Antenna gain [dBi]	0.6		
	Antenna diameter [cm]	6.0		
	Assessment Frequency [MHz]	922.5		



1	.3	Multi-transmitte	r Modes
и.		wiuiti-ti ali Sillitte	i woucs

None



2 Result Summary

FCC 47 CFR Part 2.1091, IC RSS-102					
Product Specific Standard Section	Requirement	Result	Remarks		
47 CFR 2.1091	Maximum permissible exposure @ 20cm below limit	PASS			
RSS-102 2.5.2	Maximum permissible exposure @ 20cm below limit	PASS			
Remarks:					



3 RF-Exposure Classifications

Device Types				
Fixed	A fixed device is defined as a device physically secured at one fixed location and cannot be easily re-located.			
Mobile	A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. (47 CFR 2.1091)			
Portable	A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. (47 CFR 2.1093)			
	Exposure Categories			
Occupational / Controlled	Limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.			
General population / uncontrolled	Exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.			



4 Assessment

4.1 MPE Assessment Conditions – 47 CFR 2.1091 / RSS-102

	1		091 / IC RSS-102		VERDICT: PASS
Assessment according to reference		Reference Method			
			FCC OET Bulletin	n 65 / RSS-102 & Sa	fety Code 6
Device type	e			mobile	
Exposure cate	gory			General public	
	IC Limits – O	ccu	pational / Controlle	ed Exposure	
Frequency range [MHz]	Electric field strength [V/M		Magnetic field strength [A/M]	Power density [W/m ²]	Averaging time [min]
0.003-10*	170		180	-	Instantaneous*
0.1-10	-		1.6 / f	-	6**
1.29-10	193 / $f^{0.5}$		-	-	6**
10-20	61.4		0.163	-10	6
20-48	129.8 / f ^{0.25}		0.3444 / f ^{0.25}	44.72 / f ^{0.5}	6
48-100	49.33		0.1309	6.455	6
100-6000	15.60 f ^{0.25}		0.04138 f ^{0.25}	0.6455 f ^{0.5}	6
6000-15000	137		0.364	50	6
15000-150000	137		0.364	50	616000 / f ^{1.2}
150000-300000	0.354 f ^{0.5}		9.40 x 10 ⁻⁴ f ^{0.5}	3.33 x 10 ⁻⁴ f	616000 / f ^{1.2}
IC	Limits - Gener	al P	opulation / Uncont	rolled Exposure	
Frequency range [MHz]	Electric field strength [V/M		Magnetic field strength [A/M]	Power density [W/m²]	Averaging time [min]
0.003-10*	83		90	-	Instantaneous*
0.1-10	-		0.73 / f	-	6**
1.1-10	87 / f ^{0.5}		-	-	6**
10-20	27.46		0.0728	2	6
20-48	58.07 / f ^{0.25}		0.1540 / f ^{0.25}	8.944 / f ^{0.5}	6
48-300	22.06		0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	,	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4		0.163	10	6
15000-150000	61.4		0.163	10	616000 / f ^{1.2}
	0.158 f ^{0.5}		4.21 x 10 ⁻⁴ f ^{0.5}		616000 /f ^{1.2}



Product Service

FCC Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [mW/cm ²]	Averaging time [min]
0.3 - 3.0	614	1.63	(100)*	6
3.0 - 30	1842 / f	4.89 / f	(900 / f ²)*	6
30 - 300	61.4	0.163	1.0	6
300 - 1500	N/A	N/A	f / 300	6
1500 - 100000	N/A	N/A	5.0	6
FCC Limits – General Population / Uncontrolled Exposure				

FC	FCC Limits – General Population / Uncontrolled Exposure					
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [mW/cm ²]	Averaging time [min]		
0.3 – 1.34	614	1.63	(100)*	30		
1.34 - 30	842 / f	2.19 / f	(180 / f ²)*	30		
30 - 300	27.5	0.073	0.2	30		
300 - 1500	N/A	N/A	f / 1500	30		
1500 - 100000	N/A	N/A	1.0	30		

^{* =} Plane wave equivalent power density; f in MHz

Assessment Relations

$$\lambda[m] = \frac{c\left[\frac{m}{s}\right]}{f[Hz]} \; ; \; R_{FF}[m] \ge \frac{2 \cdot D[m]^2}{\lambda[m]}$$

$$S[mW/cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2}$$
; $R[cm] = \sqrt{\frac{P_{E.I.R.P.}[mW]}{4\pi S[mW/cm^2]}}$

$$P_R[mW] = P_C[mW] \cdot G$$
; $P_R[dBm] = P_C[dBm] + G[dBi]$

$$DCC[dB] = 10 \cdot Log_{10} \left(\frac{DC[\%]}{100} \right)$$

Assessment procedure

For each radio and frequency band the worst case transmission mode with the highest peak conducted or radiated power is evaluated at the frequency that results in the most restrictive rf-exposure limit. From the peak power values, antenna gains and duty cycles taken from the reference documents, the source average radiated power values are calculated. From the average radiated power the power densities at antenna far-field distance, at 20cm separation distance from the radiation source is calculated. Compliance with the RF-Exposure limit is determined at 20cm separation distance.



4.2 Single-Transmitter Assessment – 47 CFR 2.1091 / RSS-102

Assessment result - 922 MHz		
Transmission mode		
Operating mode frequency range [MHz]	922.5	
Assessment frequency (f) [MHz]	922.5	
Transmission duty cycle (DC) [%]	100	
Peak conducted power (P _C) [dBm]	-3.49	
Peak radiated power (P _R) [dBm e.i.r.p.]	-2.89	
Peak Antenna gain (G) [dBi]	0.6	
Maximum Antenna Diameter D [cm]	6.0	
Antenna far-field distance		
Transmission frequency wavelength (λ)	0.325 m	32.52 cm
Antenna far-field distance (R _{FF})	0.022 m	2.21 cm
Power evaluation		
Peak conducted power (P _C)	0.45 mW	-3.49 dBm
Peak Antenna Gain (G)	1.15	0.60 dBi
Calculated peak radiated power (P _{R-Calc})	0.51 mW	-2.89 dBm
Measured peak radiated power (P _R)	0.51 mW	-2.89 dBm
Source average Power		
Maximum transmission duty cycle (DC)	100.0 %	
Duty cycle correction (DCC)	1.00	0.00 dB
Measured peak radiated power (P _R)	0.51 mW	-2.89 dBm
Averaged peak radiated power (P _{RAVG})	0.51 mW	-2.89 dBm
Power density		
Compliance power density limit FCC	0.615 mW/cm ²	6.15 W/m ²
Compliance power density limit IC	0.278 mW/cm ²	2.78 W/m ²
Power density @ Antenna far-field distance	0.008 mW/cm ²	0.083 W/m ²
Power density @ 20cm	0.000 mW/cm ²	0.001 W/m ²
Distance for compliance power density FCC	0.003 m	0.26 cm
Distance for compliance power density IC	0.004 m	0.38 cm
Verdict		
The power density of the EUT at 20cm is below the FCC MPE limit!		
The power density of the EUT	at 20cm is below the IC I	MPE limit!
Comments:		