RF Exposure Evaluation Report

: WondaLink Inc. APPLICANT

EQUIPMENT : Grand Central Hub

BRAND NAME : T-Mobile

MODEL NAME : COUPLER

FCC ID : 2AGDE-COUPLER

STANDARD : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Eric Huang / Deputy Manager

Cole huan's

Approved by: Jones Tsai / Manager





Report No.: FA5O0126

SPORTON INTERNATIONAL INC.

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 1 of 6

Report Issued Date: Nov. 12, 2015

Report Version : Rev. 02

Table of Contents

| 1. | ADMINISTRATION DATA | 4 |
|----|--|---|
| | 1.1. Testing Laboratory | 4 |
| 2. | DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) | 5 |
| 3. | MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS | 5 |
| 4. | RF EXPOSURE LIMIT INTRODUCTION | 6 |
| 5. | RADIO FREQUENCY RADIATION EXPOSURE EVALUATION | 6 |
| | 5.1 Standalone Power Density Calculation | 6 |

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 2 of 6

Report Issued Date: Nov. 12, 2015

Report No.: FA5O0126

Report Version : Rev. 02



SPORTON LAB. RF Exposure Evaluation Report

Revision History

| REPORT NO. | VERSION | DESCRIPTION | ISSUED DATE |
|------------|---------|-----------------------------|---------------|
| FA5O0126 | Rev. 01 | Initial issue of report | Nov. 06, 2015 |
| FA5O0126 | Rev. 02 | Revising the equipment name | Nov. 12, 2015 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 3 of 6

Report Issued Date: Nov. 12, 2015

Report No.: FA5O0126

Report Version : Rev. 02

1. Administration Data

1.1. Testing Laboratory

| Testing Laboratory | | | | | |
|--------------------------------------|--|--|--|--|--|
| Test Site SPORTON INTERNATIONAL INC. | | | | | |
| Test Site Location | No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978 | | | | |

| Applicant | | | | | |
|--------------|---|--|--|--|--|
| Company Name | WondaLink Inc. | | | | |
| Address | 2F, NO.23, R&D Road 2, Science-Based Industrial Park, Hsinchu, Taiwan | | | | |

| Manufacturer Manufacturer | | | | | |
|---------------------------|--|--|--|--|--|
| Company Name | Global Brands Manufacture (DongGuan) Ltd. | | | | |
| AUDITESS | Yue Yuan Industrial Estate, Huang Jiang Zhen, DongGuan City, GuangDong Province, China | | | | |

SPORTON INTERNATIONAL INC. Page Number : 4 of 6

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Report Issued Date : Nov. 12, 2015 Report Version : Rev. 02

Report No.: FA5O0126

2. Description of Equipment Under Test (EUT)

| Product Feature & Specification | | | | | |
|--|---------------------------------------|--|--|--|--|
| EUT Type | Grand Central Hub | | | | |
| Brand Name | T-Mobile | | | | |
| Model Name | COUPLER | | | | |
| FCC ID | 2AGDE-COUPLER | | | | |
| Wireless Technology and Frequency Range | WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz | | | | |
| Mode | • 802.11b/g/n HT20 | | | | |
| Antenna Type | PCB Antenna | | | | |
| HW Version | Rev. 1.1 | | | | |
| EUT Stage | Identical Prototype | | | | |

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

3. Maximum RF average output power among production units

| Band / Frequency (MHz) | | IEEE 802.11 Average Power (dBm) | | | |
|------------------------|------|---------------------------------|-------|------|--|
| | | 11b | 11g | HT20 | |
| | 2412 | 13.00 | 10.00 | | |
| | 2422 | | | | |
| 2.4GHz Band | 2437 | | | 9.00 | |
| | 2452 | | | | |
| | 2462 | | | | |

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 5 of 6
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FA5O0126

4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) | |
|--------------------------|-------------------------------|-------------------------------|--|-----------------------------|--|
| 800 St. | (A) Limits for O | ccupational/Controlled Expos | sures | 81 | |
| 0.3-3.0 | 614 | 1.63 | *(100) | 6 | |
| 3.0-30 | 1842/ | f 4.89/1 | *(900/f2) | 6 | |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 | |
| 300-1500 | | | f/300 | 6 | |
| 1500-100,000 | | | 5 | 6 | |
| | (B) Limits for Gene | ral Population/Uncontrolled I | Exposure | | |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 | |
| 1.34-30 | 824/ | f 2.19/1 | *(180/f2) | 30 | |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 | |
| 300-1500 | | | f/1500 | 30 | |
| 1500-100,000 | | | 1.0 | 30 | |

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna

5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

| Band | Frequency (MHz) | Antenna Gain (dBi) | Maximum Power (dBm) | Maximum EIRP (dBm) | Maximum EIRP (W) | Average EIRP (mW) | Power Density at 20cm (mW/cm^2) | Limit (mW/cm^2) |
|-------------|--------------------|--------------------------|---------------------------|--------------------------|------------------------|-------------------------|---------------------------------------|--------------------|
| 2.4GHz WLAN | 2412.0 | 2.00 | 13.00 | 15.000 | 0.032 | 31.623 | 0.006 | 1.000 |

Note: For conservativeness, the lowest uplink frequency of each band is used to determine the MPE limit of that band.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 6 of 6
Report Issued Date : Nov. 12, 2015

Report Version

: Rev. 02

Report No.: FA5O0126