FCC RF Test Report

APPLICANT : WondaLink Inc.

EQUIPMENT : Grand Central Hub

BRAND NAME : T-Mobile

MODEL NAME : COUPLER

FCC ID : 2AGDE-COUPLER

STANDARD : FCC Part 15 Subpart C §15.247

CLASSIFICATION: (DTS) Digital Transmission System

The product was received on Oct. 01, 2015 and testing was completed on Nov. 05, 2015. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 1 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

1190

Report No.: FR500126

TABLE OF CONTENTS

RE	VISIO	ON HISTORY	3
SU	ММА	RY OF TEST RESULT	4
1	GEN	IERAL DESCRIPTION	5
	1.1	Applicant	
	1.2	Manufacturer	
	1.3	Product Feature of Equipment Under Test	
	1.4	Product Specification subjective to this standard	
	1.5	Modification of EUT	
	1.6	Testing Location	
	1.7	Applicable Standards	6
2	TES	T CONFIGURATION OF EQUIPMENT UNDER TEST	7
	2.1	Carrier Frequency Channel	7
	2.2	Pre-Scanned RF Power	8
	2.3	Test Mode	8
	2.4	Connection Diagram of Test System	9
	2.5	Support Unit used in test configuration and system	10
	2.6	EUT Operation Test Setup	10
	2.7	Measurement Results Explanation Example	10
3	TES	T RESULT	11
	3.1	6dB Bandwidth Measurement	11
	3.2	Output Power Measurement	13
	3.3	Power Spectral Density Measurement	14
	3.4	Conducted Band Edges and Spurious Emission Measurement	16
	3.5	Radiated Band Edges and Spurious Emission Measurement	26
	3.6	AC Conducted Emission Measurement	30
	3.7	Antenna Requirements	34
4	LIST	OF MEASURING EQUIPMENT	35
5	UNC	ERTAINTY OF EVALUATION	36
ΑP	PEND	DIX A. CONDUCTED TEST RESULTS	
ΑP	PEND	DIX B. RADIATED TEST RESULTS	
ΑP	PEND	DIX C. SETUP PHOTOGRAPHS	

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 2 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR5O0126

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR5O0126	Rev. 01	Initial issue of report	Nov. 06, 2015
FR5O0126	Rev. 02	Revising the equipment name	Nov. 12, 2015

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 3 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No. : FR5O0126

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.2	15.247(b)	Power Output Measurement	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4 15.247(d)		Conducted Band Edges		Pass	-
		Conducted Spurious Emission	- ≤ 20dBc	Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 0.27 dB at 2390.000 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 9.70 dB at 0.390 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 4 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No. : FR5O0126

1 General Description

1.1 Applicant

WondaLink Inc.

2F, NO. 23, R&D Road 2, Science-Based Industrial Park, Hsinchu, Taiwan

1.2 Manufacturer

Global Brands Manufacture (DongGuan) Ltd.

Yue Yuan Industrial Estate, Huang Jiang Zhen, Dong Guan City, GuangDong Province, China

Report No.: FR5O0126

1.3 Product Feature of Equipment Under Test

Product Feature				
Equipment	Grand Central Hub			
Brand Name	T-Mobile			
Model Name	COUPLER			
FCC ID	2AGDE-COUPLER			
EUT supports Radios application	WLAN 11b/g/n HT20			
HW Version	Rev. 1.1			
EUT Stage	Identical Prototype			

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard				
Tx/Rx Channel Frequency Range	802.11b/g/n : 2412 MHz ~ 2462 MHz			
Maximum (Peak) Output Power to	802.11b : 14.96 dBm (0.0313 W)			
Antenna	802.11g : 19.31 dBm (0.0853 W)			
Antenna	802.11n HT20 : 19.12 dBm (0.0817 W)			
Antenna Type	802.11b/g/n : PCB Antenna type with gain 2.00 dBi			
Type of Medulation	802.11b: DSSS (DBPSK / DQPSK / CCK)			
Type of Modulation	802.11g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM)			

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

 SPORTON INTERNATIONAL INC.
 Page Number
 : 5 of 36

 TEL: 886-3-327-3456
 Report Issued Date
 : Nov. 12, 2015

 FAX: 886-3-328-4978
 Report Version
 : Rev. 02

FCC ID : 2AGDE-COUPLER Report Template No.: BU5-FR15CWL Version 1.0

1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.				
	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park,				
Test Site Location	Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.	van, R.O.C.			
rest Site Location	TEL: +886-3-327-3456				
	FAX: +886-3-328-4978				
Took Site No	Sporton	Site No.			
Test Site No.	TH05-HY	CO05-HY			

Note: The test site complies with ANSI C63.4 2009 requirement.

Test Site	SPORTON INTERNATIONAL INC.				
	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist,				
Took Site Legation	Taoyuan City, Taiwan (R.O.C.)				
Test Site Location	TEL: +886-3-327-0868				
	FAX: +886-3-327-0855				
Test Site No.	Sporton Site No.				
Test Site NO.	03CH10-HY				

Note: The test site complies with ANSI C63.4 2009 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03
- ANSI C63.10-2009

Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. FCC permits the use of the 1.5 meter table as an alternative in C63.10-2013 through inquiry tracking number 961829.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 6 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR500126

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Frequency Band Channel		Channel	Freq. (MHz)
	1	2412	7	2442
	2	2417	8	2447
0400 0400 F MILE	3	2422	9	2452
2400-2483.5 MHz	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 7 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR500126

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

Report No.: FR5O0126

2.4GHz 802.11b mode						
Data Rate (MHz) 1M bps 2M bps 5.5M bps 11M bps						
Peak Power (dBm)	<mark>14.96</mark>	14.93	14.95	14.95		

2.4GHz 802.11g mode								
Data Rate (MHz) 6M bps 9M bps 12M bps 18M bps 24M bps 36M bps 48M bps 54M bps								
Peak Power (dBm)	<mark>19.31</mark>	19.24	19.29	19.28	19.27	19.27	19.29	19.28

2.4GHz 802.11n HT20 mode								
Data Rate (MHz) MCS0 MCS1 MCS2 MCS3 MCS4 MCS5 MCS6 MCS7								
Peak Power (dBm)	<mark>19.12</mark>	19.10	19.11	19.08	19.09	19.07	19.10	19.07

2.3 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.

<2.4GHz>

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0

	Test Cases			
AC				
Conducted	Mode 1: WLAN Link + TC			
Emission				
Remark: TC stands for Test Configuration, and consists of SD Card, mouse, keyboard, HDMI cable, and				
RJ-	-45.			

 SPORTON INTERNATIONAL INC.
 Page Number
 : 8 of 36


 TEL: 886-3-327-3456
 Report Issued Date
 : Nov. 12, 2015

 FAX: 886-3-328-4978
 Report Version
 : Rev. 02


FCC ID : 2AGDE-COUPLER Report Template No.: BU5-FR15CWL Version 1.0

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 9 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR5O0126

2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
2.	LCD Monitor	DELL	U2410	FCC DoC	Shielded, 1.6 m	Unshielded, 1.8 m
3.	(USB) Keyboard	Logitech	K200	FCC DoC	Shielded, 1.5 m	N/A
4.	(USB) Mouse	i-driver	IMS-0802-UPBK	FCC DoC	Shielded, 1.8 m	N/A
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.6 EUT Operation Test Setup

For WLAN function, programmed RF utility, "RF Test Tool" installed in the EUT make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB). = 4.2 + 10 = 14.2 (dB) Report No.: FR500126

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

- 1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r03.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- 5. Measure and record the results in the test report.

3.1.4 Test Setup




TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 11 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR500126

3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A of this test report.



TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 12 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR5O0126

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

- The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas.
 Guidance v03r03 section 9.1.2 PKPM1 Peak power meter method.
- 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A of this test report.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A of this test report.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 13 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR500126

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

- The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 6. Measure and record the results in the test report.

3.3.4 Test Setup




TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 14 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR500126

3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A of this test report.



TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 15 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR5O0126

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
- 5. Measure and record the results in the test report.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 16 of 36


Report Issued Date : Nov. 12, 2015

Report Version : Rev. 02

Report No.: FR500126

3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	20~25 ℃
Test Band :	2.4GHz Low	Relative Humidity :	51~55%
Test Channel :	01	Test Engineer :	Derek Hsu




TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 17 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report Template No.: BU5-FR15CWL Version 1.0

Report No.: FR5O0126

Test Mode :	802.11b	Temperature :	20~25℃
Test Band :	2.4GHz Mid	Relative Humidity :	51~55%
Test Channel:	06	Test Engineer :	Derek Hsu




Page Number : 18 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report Template No.: BU5-FR15CWL Version 1.0

Report No.: FR5O0126

Test Mode :	802.11b	Temperature :	20~25℃
Test Band :	2.4GHz High	Relative Humidity :	51~55%
Test Channel :	11	Test Engineer :	Derek Hsu




Page Number : 19 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR5O0126

 Test Mode :
 802.11g
 Temperature :
 20~25℃

 Test Band :
 2.4GHz Low
 Relative Humidity :
 51~55%


 Test Channel :
 01
 Test Engineer :
 Derek Hsu



TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 20 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR5O0126

Test Mode :	802.11g	Temperature :	20~25℃
Test Band :	2.4GHz Mid	Relative Humidity :	51~55%
Test Channel:	06	Test Engineer :	Derek Hsu




Page Number : 21 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR5O0126

 Test Mode :
 802.11g
 Temperature :
 20~25℃

 Test Band :
 2.4GHz High
 Relative Humidity :
 51~55%


 Test Channel :
 11
 Test Engineer :
 Derek Hsu



TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 22 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR5O0126


Test Mode :	802.11n HT20	Temperature :	20~25℃
Test Band :	2.4GHz Low	Relative Humidity :	51~55%
Test Channel :	01	Test Engineer :	Derek Hsu



Page Number : 23 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR5O0126

Test Mode :	802.11n HT20	Temperature :	20~25℃
Test Band :	2.4GHz Mid	Relative Humidity :	51~55%
Test Channel :	06	Test Engineer :	Derek Hsu




Page Number : 24 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report Template No.: BU5-FR15CWL Version 1.0

Report No.: FR5O0126

Test Mode :	802.11n HT20	Temperature :	20~25℃
Test Band :	2.4GHz High	Relative Humidity :	51~55%
Test Channel :	11	Test Engineer :	Derek Hsu



Page Number : 25 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR5O0126

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 26 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR5O0126

3.5.3 Test Procedures

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
- 2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.

Report No.: FR5O0126


- 3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 5. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level
- 6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
- 7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \ge 1$ GHz for peak measurement. For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle(%)	T(µs)	1/T(kHz)	VBW Setting
802.11b	100	-	-	10Hz
802.11g	96.55	1400	0.71	1kHz
2.4GHz 802.11n HT20	97.04	1310	0.76	1kHz


FCC ID : 2AGDE-COUPLER Report Template No.: BU5-FR15CWL Version 1.0

3.5.4 Test Setup

For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 28 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR5O0126

For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 29 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR5O0126

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission	Conducted Limit (dBμV)		
(MHz)	Quasi-Peak	Average	
0.15-0.5	66 to 56*	56 to 46*	
0.5-5	56	46	
5-30	60	50	

^{*}Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.6.3 Test Procedures

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 30 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR500126

3.6.4 Test Setup



AMN = Artificial mains network (LISN)

AE = Associated equipment

EUT = Equipment under test

ISN = Impedance stabilization network

SPORTON INTERNATIONAL INC.


TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 31 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR500126

3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24 ℃
Test Engineer :	Eric Jeng	Relative Humidity :	49~52%
Test Voltage :	120Vac / 60Hz	Phase :	Line

Function Type: WLAN Link + TC



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	55.1	Off	L1	19.5	10.9	66.0
0.166000	52.7	Off	L1	19.5	12.5	65.2
0.182000	50.0	Off	L1	19.5	14.4	64.4
0.198000	46.4	Off	L1	19.4	17.3	63.7
0.390000	39.9	Off	L1	19.6	18.2	58.1
21.038000	27.9	Off	L1	19.9	32.1	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	37.1	Off	L1	19.5	18.9	56.0
0.166000	35.9	Off	L1	19.5	19.3	55.2
0.182000	33.7	Off	L1	19.5	20.7	54.4
0.198000	31.9	Off	L1	19.4	21.8	53.7
0.390000	38.4	Off	L1	19.6	9.7	48.1
21.038000	22.1	Off	L1	19.9	27.9	50.0

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 32 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR5O0126




 Test Mode :
 Mode 1
 Temperature :
 22~24℃

 Test Engineer :
 Eric Jeng
 Relative Humidity :
 49~52%

 Test Voltage :
 120Vac / 60Hz
 Phase :
 Neutral

Function Type: WLAN Link + TC



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	55.0	Off	N	19.5	11.0	66.0
0.158000	51.9	Off	N	19.5	13.7	65.6
0.182000	49.8	Off	N	19.5	14.6	64.4
0.198000	46.2	Off	N	19.4	17.5	63.7
0.230000	41.4	Off	N	19.5	21.0	62.4
0.390000	37.1	Off	N	19.6	21.0	58.1

Final Result : Average

Frequency	Average	Filtor	Line	Corr.	Margin	Limit
(MHz)	(dBµV)	Filter	Line	(dB)	(dB)	(dBµV)
0.150000	35.5	Off	N	19.5	20.5	56.0
0.158000	33.4	Off	N	19.5	22.2	55.6
0.182000	31.3	Off	N	19.5	23.1	54.4
0.198000	28.8	Off	N	19.4	24.9	53.7
0.230000	28.8	Off	N	19.5	23.6	52.4
0.390000	34.5	Off	N	19.6	13.6	48.1

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 33 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR5O0126

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 34 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR500126

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1240001	300MHz~40GHz	Sep. 17, 2015	Oct. 12, 2015 ~ Oct. 16, 2015	Sep. 16, 2016	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1207349	300MHz~40GHz	Sep. 17, 2015	Oct. 12, 2015 ~ Oct. 16, 2015	Sep. 16, 2016	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz-40GHz	Jun. 18, 2015	Oct. 12, 2015 ~ Oct. 16, 2015	Jun. 17, 2016	Conducted (TH05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz – 2.75GHz	Dec. 01, 2014	Nov. 03, 2015	Nov. 30, 2015	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2014	Nov. 03, 2015	Dec. 01, 2015	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Dec. 08, 2014	Nov. 03, 2015	Dec. 07, 2015	Conduction (CO05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Nov. 03, 2015	N/A	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Oct. 19, 2015 ~ Nov. 05, 2015	Sep. 01, 2016	Radiation (03CH10-HY)
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Nov. 24, 2014	Oct. 19, 2015 ~ Nov. 05, 2015	Nov. 23, 2015	Radiation (03CH10-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1325	1GHz ~ 18GHz	Sep. 30, 2015	Oct. 19, 2015 ~ Nov. 05, 2015	Sep. 29, 2016	Radiation (03CH10-HY)
Preamplifier	Keysight	83017A	MY53270078	1GHz~26.5GHz	Nov. 20, 2014	Oct. 19, 2015 ~ Nov. 05, 2015	Nov. 19, 2015	Radiation (03CH10-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200485	10Hz ~ 44GHZ	Oct. 15, 2015	Oct. 19, 2015 ~ Nov. 05, 2015	Oct. 14, 2016	Radiation (03CH10-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Oct. 19, 2015 ~ Nov. 05, 2015	N/A	Radiation (03CH10-HY)
Turn Table	EMEC	TT 2200	N/A	0-360 degree	N/A	Oct. 19, 2015 ~ Nov. 05, 2015	N/A	Radiation (03CH10-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA91705 76	18GHz ~ 40GHz	Apr. 20, 2015	Oct. 19, 2015 ~ Nov. 05, 2015	Apr. 19, 2016	Radiation (03CH10-HY)
EMI Test Receiver	Agilent Technologies	N9038A	MY53290045	20MHz~8.4GHz	Feb. 03, 2015	Oct. 19, 2015 ~ Nov. 05, 2015	Feb. 02, 2016	Radiation (03CH10-HY)
Bilog Antenna	TESEQ	CBL 6111D	40103	30MHz to 1GHz	Jul. 27, 2015	Oct. 19, 2015 ~ Nov. 05, 2015	Jul. 26, 2016	Radiation (03CH10-HY)
Preamplifier	MITEQ	JS44-1800400 0-33-8P	1840917	18GHz ~ 40GHz	Jun. 02, 2015	Oct. 19, 2015 ~ Nov. 05, 2015	Jun. 01, 2016	Radiation (03CH10-HY)

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 35 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No.: FR5O0126

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of	2.26
Confidence of 95% (U = 2Uc(y))	2.20

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of	4.0
Confidence of 95% (U = 2Uc(y))	4.5

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : 36 of 36
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report No. : FR500126

Appendix A. Conducted Test Results

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AGDE-COUPLER Page Number : A1 of A1
Report Issued Date : Nov. 12, 2015
Report Version : Rev. 02

Report Template No.: BU5-FR15CWL Version 1.0

Report No.: FR5O0126