



RF Exposure Evaluation Declaration

Product Name: Cassia Bluetooth Smart Plug

Model No. : CSK1100

FCC ID : 2AGF9CSK1100

Applicant: Beijing Cassia Networks Technology Co.,Ltd

Address: Room 206, Distrit B, 2/F, No. 12, Xinxi Road, Haidian

District, Beijing

Date of Receipt: Feb. 04, 2016

Issued Date : Feb. 25, 2016

Report No. : 1622021R-RF-US-P20V01

Report Version: V1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of QuieTek Corporation.



Test Report Certification

Issued Date: Feb. 25, 2016

Report No.: 1622021R-RF-US-P20V01



a DEKRA company

Product Name : Cassia Bluetooth Smart Plug

Applicant : Beijing Cassia Networks Technology Co.,Ltd

Address : Room 206, Distrit B, 2/F, No. 12, Xinxi Road, Haidian

District, Beijing

Manufacturer : Beijing Cassia Networks Technology Co.,Ltd

Address : Room 206, Distrit B, 2/F, No. 12, Xinxi Road, Haidian

District, Beijing

Model No. : CSK1100

FCC ID : 2AGF9CSK1100

EUT Voltage : AC 100V-240V,50/60Hz

Brand Name : Cassia

Applicable Standard : KDB 447498D01V06V02

FCC Part1.1310(b)

Test Result : Complied

Performed Location : Quietek Corporation - Suzhou EMC Laboratory

No.99 Hongye Rd., Suzhou Industrial Park, Suzhou,

215006, Jiangsu, China

TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098

FCC Registration Number: 800392

Documented By :

Alice Li

(Senior Adm. Specialist: Alice Ni)

Reviewed By

Jack zhoung

(Senior Engineer! Jack Zhang)

Approved By

(Engineering Manager : Harry Zhao)



Laboratory Information

We, **QuieTek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited/accepted(audited or listed) by the following related bodies in compliance with ISO 17025, EN 45001 and specified testing scope:

Taiwan R.O.C. : BSMI, NCC, TAF

USA : FCC Japan : VCCI

The related certificate for our laboratories about the test site and management system can be downloaded from QuieTek Corporation's Web Site: http://www.quietek.com/english/about/certificates.aspx?bval=5
The address and introduction of QuieTek Corporation's laboratories can be founded in our Web site: http://www.quietek.com/index_en.aspx

If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

HsinChu Testing Laboratory:

LinKou Testing Laboratory:

No.5-22, Ruishukeng, Linkou Dist., New Taipei City 24451, Taiwan, R.O.C.

Suzhou Testing Laboratory:

No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006, Jiangsu, China



History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
1622021R-RF-US-P20V01	V1.0	Initial Issued Report	Feb. 25, 2016



1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm2)	Average Time (Minutes)
(A) Limits for ((A) Limits for Occupational/ Control Exposures			
300-1500	-		F/300	6
1500-100,000	-		5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500			F/1500	6
1500-100,000			1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout*G)/(4*pi*r2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.



1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product		Cassia Bluetooth Smart Plug
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-6

Antenna Gain:

Antenna	Manufacturer	Model No.	Peak Gain	
Monopole Antenna	DONGGUAN WENCHANG	N/A	1.66dBi	
	ELECTRONIC CO LTD			



RF Exposure Evaluation

• Output Power into Antenna & RF Exposure Evaluation Distance:

		Maximum Output	Power Density at R =
Test Mode	Frequency Band (MHz)	Power to Antenna	20 cm
		(mW)	(mW/cm2)
Bluetooth	2402~2480MHz	0.2539	0.000074

Note: The standalone power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is below the limit of 1 mW/cm2.

— The End	