FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Screeneo Model: HDP2510 **Brand: PHILIPS**

Test Report Number: C151028Z01-RP1-1

Prepared for

X-GEM SAS 9, rue de la Négresse 64200 BIARRITZ - FRANCE

Prepared by

COMPLIANCE CERTIFICATION SERVICES (SHENZHEN) INC.

No.10-1, Mingkeda Logistics Park, No.18, Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen China

> TEL: 86-755-28055000 FAX: 86-755-28055221

E-Mail: service@ccssz.com **Issued Date: January 19, 2016**





中国认可 国际互认 检测 **TESTING**



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services (Shenzhen) Inc. This document may be altered or revised by Compliance Certification Services (Shenzhen) Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST, CNAS or any government agencies. The test result of this report relate only to the tested sample identified in this report.



Report No.: C151028Z01-RP1-1

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	January 19, 2016	Initial Issue	ALL	Sinphy Xie

TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION		4
2. EUT DESCRIPTION		5
	S	
4. FACILITIES AND ACCREDITATIO	NS	7
4.1 FACILITIES		7
	Y	
5. SETUP OF EQUIPMENT UNDER 1	TEST	8
5.1 SETUP CONFIGURATION OF E	JT	8
6. FCC PART 15.247 REQUIREMENT	rs	9
6.1 20DB BANDWIDTH		9
	1	
6.3 PEAK POWER	1	5
6.4 PEAK POWER SPECTRAL DEN	SITY1	7
6.5 BAND EDGES MEASUREMENT		8
6.6 FREQUENCY SEPARATION	2	28
	ENCY3	
	TIME)3	
	4	
6.10 POWERLINE CONDUCTED EM	1ISSIONS5	8



Report No.: C151028Z01-RP1-1

1. TEST RESULT CERTIFICATION

Product:	Screeneo
Model:	HDP2510
Brand:	PHILIPS
Tested:	October 28, 2015~January 19, 2016
Applicant:	X-GEM SAS 9, rue de la Négresse 64200 BIARRITZ - FRANCE
Manufacturer:	X-GEM SAS 9, rue de la Négresse 64200 BIARRITZ - FRANCE

APPLICABLE STANDARDS				
STANDARD TEST RESULT				
FCC 47 CFR Part 15 Subpart C	No non-compliance noted			

We hereby certify that:

The above equipment was tested by Compliance Certification Services (Shenzhen) Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10:2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.207, 15.209 and 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Reviewed by:

Sunday Hu

Supervisor of EMC Dept.

Compliance Certification Services (Shenzhen)

Inc.

Ruby Zhang

Supervisor of Report Dept.

Compliance Certification Services (Shenzhen) Inc.



Report No.: C151028Z01-RP1-1

2. EUT DESCRIPTION

Product	Screeneo
Model Number	HDP2510
Brand	PHILIPS
Model Discrepancy	N/A
Identify Number	C151028Z01-RP1-1
Received Date	October 28, 2015
Power Supply	100~240Vac, 0.4A, 50/60Hz
AC Cable	Unshielded, 1.70m
Frequency Range	2402 ~ 2480 MHz
Transmit Power	GFSK : 7.80dBm π/4-DQPSK: 6.64dBm 8DPSK : 6.79dBm
Modulation Technique	FHSS (GFSK for 1Mbps, π /4-DQPSK for 2Mbps, 8DPSK for 3Mbps)
Number of Channels	79 Channels
Antenna Specification	FPC antenna with 1dBi gain (Max)
Temperature Range	5°C ~ 35°C
Hardware Version	9124C
Software Version	V1.00

Note: This submittal(s) (test report) is intended for <u>FCC ID: 2AGG8HDP2510</u> filing to comply with section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.

FCC ID: 2AGG8HDP2510 Page 5 of 61



Report No.: C151028Z01-RP1-1

3. TEST METHODOLOGY

3.1 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Test Item	Test mode	Worse mode
	Mode 1 : AV Play	
	Mode 2 : VGA 1366*768*60Hz	
	Mode 3 : HDMI1 1920*1080*60Hz	\boxtimes
Conducted Emission	Mode 4 : HDMI1 1366*768*60Hz	
	Mode 5 : HDMI1 1024*768*60Hz	
	Mode 6 : HDMI2 1920*1080*60Hz	
	Mode 7 : HDMI3 1920*1080*60Hz	
Radiated Emission	Mode 1: TX	\boxtimes

Channel Low (2402MHz) \cdot Mid (2441MHz) and High (2480MHz) were chosen for pre-testing for GFSK \cdot π /4-DQPSK and 8DPSK, GFSK and 8DPSK were the worse case and print in the report.

4. FACILITIES AND ACCREDITATIONS

4.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No.10-1, Mingkeda Logistics Park, No.18, Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.10:2013, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

4.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

USA A2LA China CNAS

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

USA FCC

Japan VCCI(C-4815, R-4320, T-2317, G-10624)

Canada INDUSTRY CANADA

Copies of granted accreditation certificates are available for downloading from our web site, http://www.ccssz.com

4.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Uncertainty	
Radiated Emission, 30 to 200 MHz Test Site : 966(2)	+/-3.6880dB	
Radiated Emission, 200 to 1000 MHz Test Site: 966(2)	+/-3.6695dB	
Radiated Emission, 1 to 8 GHz	+/-5.1782dB	
Radiated Emission, 8 to 18 GHz	+/-5.2173dB	
Conducted Emissions	+/-3.6836dB	
Band Width	178kHz	
Peak Output Power MU	+/-1.906dB	
Band Edge MU	+/-0.182dB	
Channel Separation MU	416.178Hz	
Duty Cycle MU	0.054ms	
Frequency Stability MU	226Hz	

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance) with the specification limit.

FCC ID: 2AGG8HDP2510 Page 7 of 61

5. SETUP OF EQUIPMENT UNDER TEST

5.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

Report No.: C151028Z01-RP1-1

5.2 SUPPORT EQUIPMENT

No.	Equipment	Model No.	Serial No.	FCC ID	Brand	Data Cable	Power Cord
1	Notebook	B475	WE04591721	DoC	LENOVO	N/A	Unshielded 1.45m (AC Cable) Unshielded 1.75m (DC Cable)
2	PC	CLRDY2X	FO4DA2240828	DoC	DELL	Shielded 1.50m (VGA cable)	Unshielded 1.50m
3	Keyboard	PR1101V	539130-001	DoC	DELL	Shielded 1.50m	N/A
4	Mouse	WB365PA#AB2	2HTJMB101178- 317	DoC	DELL	shielded 1.45m	N/A
5	Modem	DU-562M	ES1X268007883	DoC	D-LINK	Unshielded 1.20m	N/A
6	Printer	DESKJET D1668	CB767-0008	DoC	HP	Shielded 1.40m	Unshielded 1.50m
7	Headset	ST909	N/A	DoC	SENICC	Shielded 2.20m	N/A
8	DVD 1#	DV-410V-G	HKKD010577CN	DoC	PIONEER	Shielded 1.50m (HDMI cable)	Unshielded 2.00m
9	DVD 2#	DVP3690K	N/A	DoC	PHILIPS	Unshielded 1.50m (AV cable) Shielded 1.50m (HDMI cable)	Unshielded 1.50m
10	HD 3.0	WDBACY3201 ABK-PESN	WX61ABOU8031	DoC	WD	Unshielded 0.50m	N/A
11	Speaker 1#	N/A	N/A	DoC	N/A	Shielded 1.00m	N/A
12	Speaker 2#	N/A	N/A	DoC	N/A	Unshielded 1.00m	N/A

Notes:

Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

Report No.: C151028Z01-RP1-1

6. FCC PART 15.247 REQUIREMENTS

6.1 20DB BANDWIDTH


None: for reporting purpose only.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	02/28/2015	02/27/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST CONFIGURATION



TEST PROCEDURE

- 1. Place the EUT on the table and set it in the transmitting mode.
- 2. Remove the antenna from the EUT, then connect a low loss RF cable from antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW=30kHz, VBW=100kHz, Span=3MHz, Sweep = auto.
- 4. Mark the peak frequency and 20dB (upper and lower) frequency.
- 5. Repeat until all the test channels are investigated.


TEST RESULTS

No non-compliance noted


FCC ID: 2AGG8HDP2510 Page 9 of 61

Report No.: C151028Z01-RP1-1

Test plot




Report No.: C151028Z01-RP1-1




Report No.: C151028Z01-RP1-1

Test plot



Report No.: C151028Z01-RP1-1



Report No.: C151028Z01-RP1-1

6.2 ANTENNA GAIN MEASUREMENT

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For normal BT devices, the GFSK mode is used.

MEASUREMENT PARAMETERS

Measurement parameter				
Detector Peak				
Sweep time	Auto			
Resolution bandwidth	3 MHz			
Video bandwidth	3 MHz			
Trace-Mode	Max hold			

LIMITS

FCC	IC	
Antenna	a Gain	
6 dBi		

TEST RESULTS

GFSK

T _{nom}	V _{nom}	Lowest channel 2402MHz	Middle channel 2441MHz	Highest channel 2480MHz
Conducted power [dBm] Measured with GFSK modulation		6.08	7.80	7.71
Radiated power [dBm] Measured with GFSK modulation		4.07	5.63	7.19
Gain [dBi] Calculated		-2.01 -2.17 -0.52		-0.52
Measurement uncertainty		± 1.5	dB (cond.) / ± 3 dB	(rad.)

8DPSK

T _{nom}	V _{nom}	Lowest channel 2402MHz	Middle channel 2441MHz	Highest channel 2480MHz		
Conducted power with 8DPSK modu		4.63	6.79	6.61		
Radiated power [dBm] Measured with 8DPSK modulation		2.15	4.10	6.04		
Gain [dBi] Calculated		-2.48	-0.57			
Measurement und	ertainty	± 1.5 dB (cond.) / ± 3 dB (rad.)				

FCC ID: 2AGG8HDP2510 Page 14 of 61

6.3 PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

Report No.: C151028Z01-RP1-1


- 1. For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
- 2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.
- 3. The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Power Meter	Anritsu	ML2495A	1204003	02/28/2015	02/27/2016
Power Sensor	Anritsu	MA2411B	1126150	02/28/2015	02/27/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.

FCC ID: 2AGG8HDP2510 Page 15 of 61

Report No.: C151028Z01-RP1-1

TEST RESULTS

No non-compliance noted

Test Data

GFSK

Channel	Frequency (MHz)	Reading Power (dBm)	Cable loss (dB)	Output Power (dBm)	Output Power (W)		Peak /AVG	Result
Low	2402	2.58	3.50	6.08	0.00406			PASS
Mid	2441	4.30	3.50	7.80	0.00603	1	peak	PASS
High	2480	4.21	3.50	7.71	0.00590			PASS
Low	2402	2.21	3.50	5.71	0.00372			PASS
Mid	2441	4.03	3.50	7.53	0.00566	1	AVG	PASS
High	2480	3.93	3.50	7.43	0.00553			PASS

π/4-DQPSK

Channel	Frequency (MHz)	Reading Power (dBm)	Cable loss (dB)	Output Power (dBm)	Output Power (W)		Peak /AVG	Result
Low	2402	1.06	3.50	4.56	0.00286			PASS
Mid	2441	3.14	3.50	6.64	0.00461	1	peak	PASS
High	2480	3.02	3.50	6.52	0.00449			PASS
Low	2402	-1.54	3.50	1.96	0.00157			PASS
Mid	2441	0.74	3.50	4.24	0.00265	1	AVG	PASS
High	2480	0.53	3.50	4.03	0.00253			PASS

8DPSK

Channel	Frequency	Reading Power	Cable loss	Output Power	Output Power	Limit	Peak	Result
Charmer	(MHz)	(dBm)	(dB)	(dBm)	(W)	(W)	/AVG	Result
Low	2402	1.13	3.50	4.63	0.00290			PASS
Mid	2441	3.29	3.50	6.79	0.00478	1	peak	PASS
High	2480	3.11	3.50	6.61	0.00458			PASS
Low	2402	-1.48	3.50	2.02	0.00159			PASS
Mid	2441	0.89	3.50	4.39	0.00275	1	AVG	PASS
High	2480	0.66	3.50	4.16	0.00261			PASS

FCC ID: 2AGG8HDP2510 Page 16 of 61



Report No.: C151028Z01-RP1-1

6.4 PEAK POWER SPECTRAL DENSITY

LIMIT


- For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
- 2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	02/28/2015	02/27/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

- 1. Set analyzer center frequency to DTS channel center frequency.
- 2. Set the span to 1.5 times the DTS bandwidth.
- 3. Set the RBW to: 3 kHz ≤RBW ≤100 kHz.
- 4. Set the VBW ≥ 3×RBW.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST RESULTS

Not applicable. Since EUT is the Bluetooth device.

FCC ID: 2AGG8HDP2510 Page 17 of 61

Report No.: C151028Z01-RP1-1

6.5 BAND EDGES MEASUREMENT


LIMIT

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

MEASUREMENT EQUIPMENT USED

	Radiated Er	mission Test S	Site 966 (2)		
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	02/28/2015	02/27/2016
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	02/28/2015	02/27/2016
Amplifier	MITEQ	AM-1604-3000	1123808	03/18/2015	03/18/2016
High Noise Amplifier	Agilent	8449B	3008A01838	02/28/2015	02/27/2016
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	02/28/2015	02/27/2016
Bilog Antenna	SCHAFFNER	CBL6143	5082	02/28/2015	02/27/2016
Horn Antenna	SCHWARZBECK	BBHA9120	D286	02/28/2015	02/27/2016
Loop Antenna	A、R、A	PLA-1030/B	1029	09/25/2015	09/24/2016
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	СТ	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/28/2015	02/27/2016
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Test S/W	FARAD		LZ-RF / CC	S-SZ-3A2	

Test Configuration



FCC ID: 2AGG8HDP2510 Page 18 of 61

TEST PROCEDURE

- 1. The EUT is placed on a turntable, which is 1.5m above the ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

Report No.: C151028Z01-RP1-1

- 4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=1MHz / VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=330Hz / Sweep=AUTO
- 5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.


TEST RESULTS

Refer to attach spectrum analyzer data chart.


FCC ID: 2AGG8HDP2510 Page 19 of 61

Test Data (GFSK)

Band Edges (CH-Low)




Polarity: Vertical Detector mode: Average




No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	38.90	-6.60	45.50	74.00	-28.50	Peak	Vertical
2	2390.0000	28.84	-6.60	35.44	54.00	-18.56	Average	Vertical

FCC ID: 2AGG8HDP2510 Page 20 of 61





Report No.: C151028Z01-RP1-1



No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	40.30	-6.60	46.90	74.00	-27.10	Peak	Horizontal
2	2390.0000	28.80	-6.60	35.40	54.00	-18.60	Average	Horizontal










No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	46.16	-6.24	52.40	74.00	-21.60	Peak	Vertical
2	2483.5000	35.26	-6.24	41.50	54.00	-12.50	Average	Vertical

FCC ID: 2AGG8HDP2510 Page 22 of 61









No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	44.23	-6.24	50.47	74.00	-23.53	Peak	Horizontal
2	2483.5000	33.99	-6.24	40.23	54.00	-13.77	Average	Horizontal

8DPSK


Band Edges (CH-Low)






No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	39.64	-6.60	46.24	74.00	-27.76	Peak	Vertical
2	2390.0000	28.88	-6.60	35.48	54.00	-18.52	Average	Vertical









No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2390.0000	38.18	-6.60	44.78	74.00	-29.22	Peak	Horizontal
2	2390.0000	28.72	-6.60	35.32	54.00	-18.68	Average	Horizontal

mpliance Certification Services (Snenzhen) Inc.Report No.: C151028Z01-RP1-1









No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	44.84	-6.24	51.08	74.00	-22.92	Peak	Vertical
2	2483.5000	33.68	-6.24	39.92	54.00	-14.08	Average	Vertical







No.	Frequency (MHz)	Reading (dBuV)	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Antenna Pole
1	2483.5000	45.36	-6.24	51.60	74.00	-22.40	Peak	Horizontal
2	2483.5000	32.55	-6.24	38.79	54.00	-15.21	Average	Horizontal

6.6 FREQUENCY SEPARATION

LIMIT

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


Report No.: C151028Z01-RP1-1

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	02/28/2015	02/27/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set center frequency of spectrum analyzer = middle of hopping channel.
- 4. Set the spectrum analyzer as RBW=30kHz, VBW=30kHz, Adjust Span to 4 MHz, Sweep = auto.
- 5. Max hold. Mark 3 Peaks of hopping channel and record the 3 peaks frequency.

TEST RESULTS

No non-compliance noted

Test Data

GFSK


Channel Separation (MHz)	Two-thirds of the 20 dB Bandwidth (kHz)	Channel Separation Limit	Result
1.000	633.718	> Two-thirds of the 20 dB Bandwidth	Pass

8DPSK


Channel Separation (MHz)	Two-thirds of the 20 dB Bandwidth (kHz)	Channel Separation Limit	Result
1.000	850.000	> Two-thirds of the 20 dB Bandwidth	Pass

FCC ID: 2AGG8HDP2510 Page 28/61

GFSK



8DPSK



6.7 NUMBER OF HOPPING FREQUENCY

LIMIT


According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	02/28/2015	02/27/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set spectrum analyzer Start=2400MHz, Stop = 2483.5MHz, Sweep = 1ms.
- 4. Set the spectrum analyzer as RBW, VBW=300kHz,
- 5. Max hold, view and count how many channel in the band.

TEST RESULTS

No non-compliance noted


Test Data

Result (No. of CH)	Limit (No. of CH)	Result
79	>15	PASS

Report No.: C151028Z01-RP1-1

Test Plot

Channel Number



6.8 TIME OF OCCUPANCY (DWELL TIME)

LIMIT


According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4s multiplied by the number of hopping channels employed.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	02/28/2015	02/27/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set center frequency of spectrum analyzer = operating frequency.
- 4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
- 5. Repeat above procedures until all frequency measured were complete.

TEST RESULTS

No non-compliance noted

Test Data

GFSK

DH 1

CH Mid: 0.386* (1600/2)/79*31.6 = 123.520(ms)

СН	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	0.386	123.520	31.60	400.00	PASS

DH 3

CH Mid: $1.650^* (1600/4)/79 * 31.6 = 264.000 (ms)$

СН	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	1.650	264.000	31.60	400.00	PASS

DH 5

CH Mid: 2.904* (1600/6)/79 * 31.6 = 309.76(ms)

СН	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	2.904	309.76	31.60	400.00	PASS

8DPSK

DH 1

CH Mid: 0.392* (1600/2)/79*31.6 = 125.440 (ms)

СН	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	0.392	125.440	31.60	400.00	PASS

<u>DH 3</u>

CH Mid: 1.653* (1600/4)/79* 31.6 = 264.480 (ms)

СН	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	1.653	264.480	31.60	400.00	PASS


<u>DH 5</u>

CH Mid: 2.908* (1600/6)/79*31.6 = 310.187(ms)


СН	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Mid	2.908	310.187	31.60	400.00	PASS

Test Plot

GFSK




FCC ID: 2AGG8HDP2510 Page 36/61




FCC ID: 2AGG8HDP2510 Page 37/61

Test Plot 8DPSK



FCC ID: 2AGG8HDP2510 Page 38/61



FCC ID: 2AGG8HDP2510 Page 39/61

6.9 SPURIOUS EMISSIONS

6.9.1. CONDUCTED MEASUREMENT

LIMIT


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	E4446A	US44300399	02/28/2015	02/27/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

Measurements are made over the 10MHz to 26.5GHz range with the transmitter set to the lowest, middle, and highest channels.


TEST RESULTS


No non-compliance noted

Remark: The hopping on mode and hopping off mode were chosen for pre-test and the hopping off mode was the worse case and print in the report.


FCC ID: 2AGG8HDP2510 Page 40/61

Test Plot (GFSK)







FCC ID: 2AGG8HDP2510 Page 42/61




Test Plot (8DPSK)





FCC ID: 2AGG8HDP2510 Page 45/61



FCC ID: 2AGG8HDP2510 Page 46/61

6.9.2. Radiated Emissions

LIMIT

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Note: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength (μV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

FCC ID: 2AGG8HDP2510 Page 47/61


MEASUREMENT EQUIPMENT USED

	Radiated Emission Test Site 966 (2)							
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration			
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	02/28/2015	02/27/2016			
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	02/28/2015	02/27/2016			
Amplifier	MITEQ	AM-1604-3000	1123808	03/18/2015	03/18/2016			
High Noise Amplifier	Agilent	8449B	3008A01838	02/28/2015	02/27/2016			
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	02/28/2015	02/27/2016			
Bilog Antenna	SCHAFFNER	CBL6143	5082	02/28/2015	02/27/2016			
Horn Antenna	SCHWARZBECK	BBHA9120	D286	02/28/2015	02/27/2016			
Loop Antenna	A、R、A	PLA-1030/B	1029	09/25/2015	09/24/2016			
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R			
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R			
Controller	СТ	N/A	N/A	N.C.R	N.C.R			
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/28/2015	02/27/2016			
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R			
Test S/W	FARAD		LZ-RF / CCS	S-SZ-3A2				

Remark: Each piece of equipment is scheduled for calibration once a year.


Test Configuration

Below 30MHz




FCC ID: 2AGG8HDP2510 Page 48/61

Below 1 GHz



Above 1 GHz



TEST PROCEDURE

- 1. The EUT is placed on a turntable, which is 0.8m or 1.5m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.

FCC ID: 2AGG8HDP2510 Page 50/61

TEST RESULTS

Below 1 GHz

Test Mode: TX Tested by: Jack Chen

Ambient temperature: 24°C Relative humidity: 52% RH Date: November 30, 2015

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
143.4900	51.50	-21.43	30.07	43.50	-13.43	V	QP
375.3200	48.57	-16.82	31.75	46.00	-14.25	V	QP
580.9600	45.48	-13.10	32.38	46.00	-13.62	V	QP
640.1300	45.91	-12.47	33.44	46.00	-12.56	V	QP
668.2600	41.73	-12.16	29.57	46.00	-16.43	V	QP
949.5600	41.37	-9.32	32.05	46.00	-13.95	V	QP
220.1200	50.78	-20.37	30.41	46.00	-15.59	Н	QP
375.3200	49.40	-16.82	32.58	46.00	-13.42	Н	QP
432.5500	49.72	-15.61	34.11	46.00	-11.89	Н	QP
500.4500	44.38	-14.35	30.03	46.00	-15.97	Н	QP
666.3200	48.65	-12.22	36.43	46.00	-9.57	Н	QP
833.1600	40.97	-10.63	30.34	46.00	-15.66	Н	QP

^{**}Remark: No emission found between lowest internal used/generated frequency to 30MHz. Notes:

- 1. Measuring frequencies from 9kHz to the 1GHz.
- 2. Radiated emissions measured in frequency range from 30MHz to 1GHz were made with an instrument using Peak/Quasi-peak detector mode.
- 3. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4. The IF bandwidth of SPA between 30MHz to 1GHz was 120kHz.

5. Frequency (MHz). = Emission frequency in MHz

Reading (dBuV) = Receiver reading

Correction Factor(dB/m) = Antenna factor + Cable loss – Amplifier gain Actual FS (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)

Limit (dBuV/m) = Limit stated in standard

Margin(dB) = Measured (dBuV/m) - Limits (dBuV/m)

Antenna Pole(V/H) = Current carrying line of reading

FCC ID: 2AGG8HDP2510 Page 51/61



Above 1 GHz GFSK

Test Mode: TX(CH Low) Tested by: Jack Chen

Ambient temperature: 24°C Relative humidity: 52% RH Date: November 9, 2015

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1351.000	57.57	-12.23	45.34	74.00	-28.66	V	peak
1594.000	61.95	-10.38	51.57	74.00	-22.43	V	peak
1747.000	56.47	-9.07	47.40	74.00	-26.60	V	peak
4051.000	45.26	-0.89	44.37	74.00	-29.63	V	peak
5401.000	42.95	2.54	45.49	74.00	-28.51	V	peak
6985.000	40.42	7.64	48.06	74.00	-25.94	V	peak
1351.000	56.91	-12.23	44.68	74.00	-29.32	Н	Peak
1972.000	48.48	-8.35	40.13	74.00	-33.87	Н	Peak
4051.000	45.14	-0.89	44.25	74.00	-29.75	Н	Peak
4807.000	47.32	1.71	49.03	74.00	-24.97	Н	peak
5401.000	43.37	2.54	45.91	74.00	-28.09	Н	peak
6166.000	41.59	4.11	45.70	74.00	-28.30	Н	peak

Notes:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = auto. b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 330Hz, Sweep time = auto.
- 5. Frequency (MHz) = Emission frequency in MHz

Reading (dBµV/m) =Uncorrected Analyzer / Receiver Reading Correction Factor (dB) = Antenna factor + Cable loss - Amplifier gain

Limit (dBµV/m) = Limit stated in standard

= Result ($dB\mu V/m$)- Limit ($dB\mu V/m$) Margin (dB)

Pk = Peak Reading AV. = Average Reading

Remark = Mark Peak Reading or Average Reading

FCC ID: 2AGG8HDP2510 Page 52/61



Test Mode: TX(CH Mid)

Tested by: Jack Chen

Ambient temperature: <u>24°C</u> Relative humidity: <u>52% RH</u> Date: <u>November 9, 2015</u>

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1351.000	57.40	-12.23	45.17	74.00	-28.83	V	peak
1603.000	61.76	-10.30	51.46	74.00	-22.54	V	peak
4879.000	47.62	2.01	49.63	74.00	-24.37	V	peak
5401.000	43.05	2.54	45.59	74.00	-28.41	V	peak
6742.000	41.28	6.59	47.87	74.00	-26.13	V	peak
8371.000	40.85	9.45	50.30	74.00	-23.70	V	peak
							•
1351.000	56.31	-12.23	44.08	74.00	-29.92	Н	Peak
1594.000	60.54	-10.38	50.16	74.00	-23.84	Н	Peak
4051.000	43.70	-0.89	42.81	74.00	-31.19	Н	Peak
4879.000	44.83	2.01	46.84	74.00	-27.16	Н	peak
5401.000	43.54	2.54	46.08	74.00	-27.92	Н	peak
6751.000	40.43	6.63	47.06	74.00	-26.94	Н	peak

Notes:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = auto.
- b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 330Hz, Sweep time = auto.
- 5. Frequency (MHz) = Emission frequency in MHz

Reading (dBµV/m) =Uncorrected Analyzer / Receiver Reading Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain

 $Limit (dB\mu V/m) = Limit stated in standard$

Margin (dB) = Result (dB μ V/m)- Limit (dB μ V/m)

Pk = Peak Reading
AV. = Average Reading

Remark = Mark Peak Reading or Average Reading

FCC ID: 2AGG8HDP2510 Page 53/61



Test Mode: TX(CH High)

Tested by: Jack Chen

Report No.: C151028Z01-RP1-1

Ambient temperature: 24°C Relative humidity: 52% RH Date: November 9, 2015

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1351.000	57.23	-12.23	45.00	74.00	-29.00	V	peak
4051.000	44.85	-0.89	43.96	74.00	-30.04	V	peak
4960.000	44.06	2.34	46.40	74.00	-27.60	V	peak
5401.000	42.93	2.54	45.47	74.00	-28.53	V	peak
6157.000	40.72	4.07	44.79	74.00	-29.21	V	peak
7579.000	40.80	8.83	49.63	74.00	-24.37	V	peak
1351.000	56.79	-12.23	44.56	74.00	-29.44	Н	Peak
4051.000	42.72	-0.89	41.83	74.00	-32.17	Н	Peak
4960.000	42.10	2.34	44.44	74.00	-29.56	Н	Peak
5401.000	42.98	2.54	45.52	74.00	-28.48	Н	peak
6751.000	43.13	6.63	49.76	74.00	-24.24	Н	peak
7750.000	40.69	9.16	49.85	74.00	-24.15	Н	peak

Notes:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = auto. b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 330Hz, Sweep time = auto.
- 5. Frequency (MHz) = Emission frequency in MHz
 - Reading (dBµV/m) =Uncorrected Analyzer / Receiver Reading Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain
 - Limit ($dB\mu V/m$) = Limit stated in standard
 - Margin (dB) = Result (dB μ V/m)- Limit (dB μ V/m)
 - Pk = Peak Reading
 AV. = Average Reading
 - Remark = Mark Peak Reading or Average Reading

FCC ID: 2AGG8HDP2510 Page 54/61



8DPSK

Test Mode: TX(CH Low) Tested by: Jack Chen

Report No.: C151028Z01-RP1-1

Ambient temperature: 24°C Relative humidity: 52% RH Date: November 9, 2015

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
2089.000	48.34	-7.93	40.41	74.00	-33.59	V	peak
4051.000	44.52	-0.89	43.63	74.00	-30.37	V	peak
4807.000	43.24	1.71	44.95	74.00	-29.05	V	peak
5401.000	42.53	2.54	45.07	74.00	-28.93	V	peak
7057.000	40.08	7.81	47.89	74.00	-26.11	V	peak
8101.000	40.54	9.59	50.13	74.00	-23.87	V	peak
4051.000	44.17	-0.89	43.28	74.00	-30.72	Н	Peak
4807.000	44.20	1.71	45.91	74.00	-28.09	Н	Peak
5401.000	43.31	2.54	45.85	74.00	-28.15	Н	Peak
6751.000	40.78	6.63	47.41	74.00	-26.59	Н	peak
6994.000	40.42	7.67	48.09	74.00	-25.91	Н	peak
8308.000	39.94	9.48	49.42	74.00	-24.58	Н	peak

Notes:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = auto. b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 330Hz, Sweep time = auto.
- 5. Frequency (MHz) = Emission frequency in MHz

Reading (dBµV/m) =Uncorrected Analyzer / Receiver Reading Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain

 $Limit (dB\mu V/m) = Limit stated in standard$

Margin (dB) = Result (dB μ V/m)- Limit (dB μ V/m)

Pk = Peak Reading
AV. = Average Reading

Remark = Mark Peak Reading or Average Reading

FCC ID: 2AGG8HDP2510 Page 55/61



Test Mode: TX(CH Mid)

Tested by: Jack Chen

Ambient temperature: 24°C Relative humidity: 52% RH Date: November 9, 2015

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1351.000	57.49	-12.23	45.26	74.00	-28.74	V	peak
4051.000	43.86	-0.89	42.97	74.00	-31.03	V	peak
4879.000	44.44	2.01	46.45	74.00	-27.55	V	peak
5401.000	42.74	2.54	45.28	74.00	-28.72	V	peak
6733.000	40.98	6.55	47.53	74.00	-26.47	V	peak
7615.000	40.31	8.90	49.21	74.00	-24.79	V	peak
1351.000	56.62	-12.23	44.39	74.00	-29.61	Н	Peak
1603.000	59.97	-10.30	49.67	74.00	-24.33	Н	Peak
4051.000	43.22	-0.89	42.33	74.00	-31.67	Н	Peak
4879.000	42.87	2.01	44.88	74.00	-29.12	Н	peak
5401.000	42.81	2.54	45.35	74.00	-28.65	Н	peak
6985.000	40.40	7.64	48.04	74.00	-25.96	Н	peak

Notes:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = auto. b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 330Hz, Sweep time = auto.
- 5. Frequency (MHz) = Emission frequency in MHz

Reading $(dB\mu V/m)$ = Uncorrected Analyzer / Receiver Reading Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain

 $Limit (dB\mu V/m) = Limit stated in standard$

Margin (dB) = Result (dB μ V/m)- Limit (dB μ V/m)

Pk = Peak ReadingAV. = Average Reading

Remark = Mark Peak Reading or Average Reading

FCC ID: 2AGG8HDP2510 Page 56/61



Test Mode: TX(CH High) Tested by: Jack Chen

Ambient temperature: 24°C Relative humidity: 52% RH Date: November 30, 2015

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
4051.000	43.71	-0.89	42.82	74.00	-31.18	V	peak
4960.000	43.23	2.34	45.57	74.00	-28.43	V	peak
5401.000	43.85	2.54	46.39	74.00	-27.61	V	peak
7210.000	41.82	8.11	49.93	74.00	-24.07	V	peak
7687.000	41.16	9.04	50.20	74.00	-23.80	V	peak
8353.000	41.28	9.46	50.74	74.00	-23.26	V	peak
							•
1765.000	50.95	-8.91	42.04	74.00	-31.96	Н	Peak
2836.000	44.38	-4.59	39.79	74.00	-34.21	Н	Peak
4051.000	43.60	-0.89	42.71	74.00	-31.29	Н	Peak
5401.000	43.66	2.54	46.20	74.00	-27.80	Н	peak
7219.000	40.00	8.13	48.13	74.00	-25.87	Н	peak
7624.000	41.07	8.92	49.99	74.00	-24.01	Н	peak

Notes:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = auto. b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 330Hz, Sweep time = auto.
- 5. Frequency (MHz) = Emission frequency in MHz

Reading (dBµV/m) =Uncorrected Analyzer / Receiver Reading Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain

 $Limit (dB\mu V/m) = Limit stated in standard$

Margin (dB) = Result (dB μ V/m)- Limit (dB μ V/m)

Pk = Peak ReadingAV. = Average Reading

Remark = Mark Peak Reading or Average Reading

FCC ID: 2AGG8HDP2510 Page 57/61

6.10 POWERLINE CONDUCTED EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Fraguency Bongo (MU=)	Limits (c	iΒμV)
Frequency Range (MHz)	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50


Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

MEASUREMENT EQUIPMENT USED

Conducted Emission Test Site									
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration				
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	02/28/2015	02/27/2016				
LISN(EUT)	ROHDE&SCHWARZ	ENV216	101543-WX	02/28/2015	02/27/2016				
LISN	EMCO	3825/2	8901-1459	02/28/2015	02/27/2016				
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	02/28/2015	02/27/2016				
Test S/W	FARAD	EZ-EMC/ CCS-3A1-CE							

Remark: Each piece of equipment is scheduled for calibration once a year.

Test Configuration



See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

- 1. The EUT was placed on a table, which is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. Repeat above procedures until all frequency measured were complete.

TEST RESULTS


The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Test Data

Operation Mode: HDMI1 1920*1080*60Hz Test Date: November 26, 2015

Temperature: 22°C Humidity: 45% RH

Tested by: Jack Chen



Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Line (L1/L2)
0.1500	47.95	32.23	9.58	57.53	41.81	65.99	56.00	-8.46	-14.19	L1
0.1974	50.64	36.08	9.68	60.32	45.76	63.71	53.72	-3.39	-7.96	L1
0.2460	43.53	31.88	9.69	53.22	41.57	61.89	51.89	-8.67	-10.32	L1
0.4620	39.94	18.52	9.68	49.62	28.20	56.66	46.66	-7.04	-18.46	L1
1.8900	34.61	20.97	9.73	44.34	30.70	56.00	46.00	-11.66	-15.30	L1
20.8220	33.88	15.62	9.84	43.72	25.46	60.00	50.00	-16.28	-24.54	L1

Note:


- 1. Measuring frequencies from 0.15 MHz to 30MHz.
- 2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Peak detector, Quasi-peak detector and average detector.
- 3. "---" denotes the emission level was or more than 2dB below the Average limit.
- 4. The IF bandwidth of SPA between 0.15MHz to 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz to 30MHz was 9kHz;
- 5. L1= Line One (Live Line)

Operation Mode: HDMI1 1920*1080*60Hz Test Date: November 26, 2015

Report No.: C151028Z01-RP1-1

Temperature: 22°C Humidity: 45% RH

Tested by: Jack Chen



Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Line (L1/L2)
0.1500	46.80	31.68	9.78	56.58	41.46	65.99	56.00	-9.41	-14.54	L2
0.1983	50.17	34.65	9.79	59.96	44.44	63.68	53.68	-3.72	-9.24	L2
0.2460	40.32	31.16	9.77	50.09	40.93	61.89	51.89	-11.80	-10.96	L2
0.4260	39.23	25.78	9.70	48.93	35.48	57.33	47.33	-8.40	-11.85	L2
1.8820	34.99	21.31	9.74	44.73	31.05	56.00	46.00	-11.27	-14.95	L2
20.8580	34.06	15.67	9.74	43.80	25.41	60.00	50.00	-16.20	-24.59	L2

Note:

- 1. Measuring frequencies from 0.15 MHz to 30MHz.
- 2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Peak detector, Quasi-peak detector and average detector.
- 3. "---" denotes the emission level was or more than 2dB below the Average limit.
- 4. The IF bandwidth of SPA between 0.15MHz to 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz to 30MHz was 9kHz;
- 5. L2= Line Two (Neutral Line)