

Report No: C151028Z01-RP1\_MPE

FCC ID: 2AGG8HDP2510

Date of Issue: January 19, 2016

# RADIO FREQUENCY EXPOSURE

## **LIMIT**

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §15.247(b)(4) and §1.1307(b)(1) of this chapter.

### **Conducted Power Results**

### Bluetooth (BT3.0)

Mode	Channel	Frequency(MHz)	Average Conducted Output Power (dBm)
	00	2402	5.71
GFSK	39	2441	7.53
	78	2480	7.43
	00	2402	1.96
π/4-DQPSK	39	2441	4.24
	78	2480	4.03
	00	2402	2.02
8DPSK	39	2441	4.39
	78	2480	4.16

### Bluetooth (BT4.0)

Mode	Channel	Frequency(MHz)	Average Conducted Output Power (dBm)
GFSK	01	2402	1.68
	20	2440	3.81
	40	2480	3.68

## Manufacturing tolerance

### Bluetooth (BT3.0)

		( )	
GFSK (Average)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	5.0	7.0	7.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
π/4-DQPSK (Average)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	1.0	4.0	4.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK (Average)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	2.0	4.0	4.0
Tolerance ±(dB)	1.0	1.0	1.0



# Compliance Certification Services (Shenzhen) Inc. Report No: C151028Z01-RP1\_MPE FCC ID: 2AGG8HDP2510

Date of Issue: January 19, 2016

# Bluetooth (BT4.0)

GFSK (Average)			
Channel	Channel 00	Channel 19	Channel 39
Target (dBm)	1.0	3.0	3.0
Tolerance ±(dB)	1.0	1.0	1.0



# Compliance Certification Services (Shenzhen) Inc. Report No: C151028Z01-RP1\_MPE FCC ID: 2AGG8HDP2510

Report No: C151028Z01-RP1\_MPE

Date of Issue: January 19, 2016

## **EUT Specification**

Bluetooth (BT3.0)

EUT	Screeneo
	WLAN: 2.412GHz ~ 2.462GHz
	WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz
Frequency band	WLAN: 5.745GHz ~ 5825GHz
(Operating)	Bluetooth: 2.402GHz~ 2.480GHz
	Others
	Portable (<20cm separation)
Device category	Mobile (>20cm separation)
Device category	Others
	Occupational/Controlled exposure $(S = 5mW/cm^2)$
<b>Exposure classification</b>	General Population/Uncontrolled exposure
	$(S=1mW/cm^2)$
	Single antenna
	Multiple antennas
Antenna diversity	Tx diversity
	Rx diversity
	Tx/Rx diversity
Max. output power	8.0dBm (6.31mW)
Antenna gain (Max)	1dBi (Numeric gain:1.26)
F 1 4 11 1	MPE Evaluation
Evaluation applied	SAR Evaluation
Note:	
1. The maximum output power	(including turn tolerance) is <u>8.0dBm (6.31mW)</u> and
maximum antenna gain is I	
S	transmitters, no SAR consideration applied. The minimum
Ü	d is at least 20 cm, even if the calculations indicate that the
MPE distance would be less	

Date of Issue: January 19, 2016

## **TEST RESULT**

No non-compliance noted.

### **Calculation**

Given 
$$S = \frac{P \times G}{4\Pi d^2}$$

Equation 1

Where d = distance in cm

P = Power in mW

G = Numeric antenna gain

 $S = Power Density in mW/cm^2$ 

### **Maximum Permissible Exposure**

EUT Output Power=6.31mW

Numeric antenna gain=1.26

Substituting the MPE safe distance using d=20 cm into *Equation 1*:

Fields

The power density  $S = 6.31 \times 1.26 / (4 \Pi \times 400) \text{ cm}^2 = 0.00158 \text{mW/cm}^2$ 

(For mobile or fixed location transmitters, the maximum power density is  $1.0 \, mW/cm^2$  even if the calculation indicates that the power density would be larger.)