



RF TEST REPORT

Report No.: SET2015-16158

Product Name: Bluetooth speaker

FCC ID: 2AGGU-S100C

Model No.: S100C

Applicant: Shenzhen ZanTan Technology Co.,Ltd.

Address: Room 1307, Baohe Building, Xixiang Baoan, Shenzhen, china

Dates of Testing: 10/28/2015 — 11/08/2015

Issued by: CCIC-SET

Lab Location: Electronic Testing Building, Shahe Road, Xili, Nanshan District,

Shenzhen, 518055, P. R. China

This test report consists of 33 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 20 days since the date when the report is received. It will not be taken into consideration beyond this limit.

CCIC-SET/T (00) Page 1 of 33



Test Report

Product Name: Bluetooth speaker

Brand Name: N/A

Trade Name: N/A

Applicant: Shenzhen ZanTan Technology Co.,Ltd.

Applicant Address.....: Room 1307, Baohe Building, Xixiang Baoan, Shenzhen

Manufacturer....: Shenzhen ZanTan Technology Co.,Ltd.

Manufacturer Address: Room 1307, Baohe Building, Xixiang Baoan, Shenzhen

Test Standards : 47 CFR Part 15 Subpart C: Radio Frequency Devices

ANSI C63.10-2009: American National Standard for

Testing Unlicensed Wireless Devices

KDB 558074D01 v03r03

Test Result: PASS

Tested by::

2015.11.10

Lu Lei, Test Engineer

Reviewed by....::

Zhu Qi

2015.11.10

Zhu Qi, Senior Egineer

Approved by::

War lion

2015.11.10

Wu Li'an, Manager

CCIC-SET/T (00) Page 2 of 33





TABLE OF CONTENTS

GENERAI	LINFORMATION		4
EUT Des	cription		4
Test Stan	dards and Results		5
Facilities	and Accreditations		7
47 CFR PA	ART 15C REQUIREME	NTS	8
Antenna	requirement		8
Peak Out	put Power		9
6dB Band	dwidth		10
Conducte	ed Band Edges and Spurio	ous Emissions	13
Power sp	ectral density (PSD)		18
Radiated	Band Edge and Spurious	Emission	21
Conducte	d Emission		29
LIST OF N	IEASURING EQUIPM	ENT	33
		Change History	
Issue	Date	Reason for change	
1.0	2015-11-10	First edition	
	EUT Des Test Stand Facilities 47 CFR PA Antenna de Peak Out 6dB Band Conducte Power spe Radiated Conducte LIST OF No	EUT Description Test Standards and Results Facilities and Accreditations 47 CFR PART 15C REQUIREME Antenna requirement Peak Output Power 6dB Bandwidth Conducted Band Edges and Spurice Power spectral density (PSD) Radiated Band Edge and Spurious Conducted Emission LIST OF MEASURING EQUIPM Issue Date	





1. General Information

1.1. EUT Description

EUT Type	Bluetooth speaker		
Hardware Version	V2.0		
Software Version	V1.0		
EUT supports Radios application	Bluetooth V3.0+EI	OR / Bluetooth V4.0LE	
Frequency Range	Bluetooth LE 4.0 2402MHz~2480MHz		
Channel Number	Bluetooth LE 4.0 40		
Bit Rate of Transmitter	Bluetooth LE 4.0 1Mbps		
Modulation Type	Bluetooth LE 4.0 GFSK		
Antenna Type	PCB Antenna		
Antenna Gain	0dBi		

- Note 1: The EUT is a Bluetooth speaker, it contain Bluetooth 4.0 LTE Module operating at 2.4GHz ISM band; the frequencies allocated for the Bluetooth 4.0 LTE is F(MHz)=2402+2*n (0<=n<=39). The lowest, middle, highest channel numbers of the Bluetooth Module used and tested in this report are separately 0 (2402MHz), 20(2442MHz) and 39 (2480MHz).
- Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.
- Note 3: The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.





1.2. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Bluetooth, 2.4GHz ISM band radiators) for the EUT FCC Certification:

No.	Identity	Document Title	
1	47 CFR Part 15 Subpart C 2013	Radio Frequency Devices	
2	ANSI C63.10-2009	American National Standard for Testing Unlicensed Wireless Devices	

Test detailed items/section required by FCC rules and results are as below:

No.	Section in CFR 47	Description	Result
1	15.203	Antenna Requirement	PASS
2	15.247(b)	Peak Output Power	PASS
3	15.247(a)	Bandwidth	PASS
4	15.247(d)	Conducted Band Edges and Spurious Emission	
5	15.247(e)	Power spectral density (PSD)	PASS
6	15.207	Conducted Emission	PASS
7	15.209 15.247(d)	Radiated Band Edges and Spurious Emission	PASS

The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.10-2009.

These RF tests were performed according to the method of measurements prescribed in KDB 558074D01 v03r03.

40 channels are provided for Bluetooth LE 4.0

Channel	Frequency(MHz)	Channel	Frequency(MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462



11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

	Test Items	Modulation	Channel
	Peak Conducted Output Power		
	Power Spectral Density		
Bluetooth LE 4.0	6dB Bandwidth	GFSK	0/20/39
	Conducted and Spurious Emission		
	Radiated and Spurious Emission		
	Band Edge	GFSK	0/39

1.3. Table for Supporting Units

No.	Equipment	Brand Name	Model Name	Manufacturer	Serial No.	Note
1	Notebook	DELL	PP11L	DELL	H5914A03	FCC DOC



1.4. Facilities and Accreditations

1.4.1. Facilities

CNAS-Lab Code: L1659

CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd. CCIC is a third party testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659. A 12.8*6.8*6.4 (m) fully anechoic chamber was used for the radiated spurious emissions test.

FCC-Registration No.: 406086

CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 406086, valid time is until October 28, 2017.

IC-Registration No.: 11185A-1

CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on July. 15, 2013, valid time is until July. 15, 2016.

1.4.2. Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15°C - 35°C
Relative Humidity (%):	30% -60%
Atmospheric Pressure (kPa):	86KPa-106KPa



2. 47 CFR Part 15C Requirements

2.1. Antenna requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

And according to FCC 47 CFR Section 15.247(c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

2.1.2. Antenna Information

Antenna Category: Internal antenna

An Internal antenna was soldered to the antenna port of EUT via an adaptor cable, can't be removed.

Antenna General Information:

No.	EUT	Ant. Type	Gain(dBi)
1	Bluetooth speaker	РСВ	0

2.1.3. Result: comply

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.



2.2. Peak Output Power


2.2.1. Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

2.2.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.2.3. Test Setup



2.2.4. Test Procedures

- 1. The testing follows the Measurement Procedure of FCC KDB 558074D01 v03r03.
- 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
 - 3. Set to the maximum power setting and enable the EUT transmit continuously.
 - 4. Measure the conducted output power and record the results in the test report.

2.2.5. Test Result

Channel	Frequency	RF Power(dBm)	Limit	Verdict
CHAINICI	(MHz)	GFSK/1Mbps	(dBm)	VOIGIOU
0	2402	6.11		PASS
20	2442	6.56	30	PASS
39	2480	6.88		PASS



2.3. 6dB Bandwidth


2.3.1. Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

2.3.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.3.3. Test Setup



2.3.4. Test Procedures

- 1. The testing follows FCC KDB 558074D01 v03r03.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
 - 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
- 5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30 kHz and set the Video bandwidth (VBW) = 100 kHz.
 - 6. Measure and record the results in the test report.


2.3.5. Test Results of 6dB Bandwidth

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (MHz)	Result
0	2402	0.71	≥0.5	PASS
20	2442	0.70	≥0.5	PASS
39	2480	0.70	≥0.5	PASS




2.3.6. Test Results (plots) of 6dB Bandwidth

6 dB Bandwidth Plot on channel 0




6 dB Bandwidth Plot on channel 20











2.4. Conducted Band Edges and Spurious Emissions


2.4.1. Limit of Conducted Band Edges and Spurious Emissions

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

2.4.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.4.3. Test Setup




2.4.4. Test Procedure


- 1. The testing follows FCC KDB 558074D01 v03r03.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

 The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
- 5. Measure and record the results in the test report.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.











Conducted Spurious Emission Plot on Bluetooth LE 1Mbps





Channel = 0, 30MHz to 1GHz




Channel = 0, 1GHz to 25GHz









Channel = 20, 30MHz to 1GHz




Channel = 20, 1GHz to 25GHz







Channel = 39, 30MHz to 25GHz



Channel = 39, 30MHz to 25GHz



2.5. Power spectral density (PSD)


2.5.1. Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

2.5.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.5.3. Test Setup



2.5.4. Test Procedures

- 1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB 558074D01 v03r03.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
 - 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
 - 6. Measure and record the results in the test report.
- 7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.



2.5.5. Test Results of Power spectral density


	Spectral power density (dBm)										
Channel	Frequency (MHz)	PSD/3kHz (dBm)	Limit (dBm/3kHz)	Verdict							
0	2402	-10.50	8	PASS							
20	2442	-8.90	8	PASS							
39	2480	-8.02	8	PASS							
Measurem	nent uncertainty: ±1.3c	lB									

Note:


1. Measured power density (dBm) has offset with cable loss.

2.5.6. Test Results (plots) of Power spectral density

PSD Plot on Channel 0







150 kHz/

Center 2.48 GHz

Span 1.5 MHz



2.6. Radiated Band Edge and Spurious Emission

2.6.1. Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Note: Wireless charger configuration was evaluated.


Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

2.6.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.


2.6.3. Test Setup

For radiated emissions from 9kHz to 30MHz






For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz







2.6.4. Test Procedures

- 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- 3. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- 6. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported.
 Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
 - 7. All modes (three orthogonal orientations) of operation were investigated and the worst-case emissions are reported.

NOTE:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.




2.6.5. Test Results of Radiated Band Edge and Spurious Emission

For 9KHz to 30MHz

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


For 30MHz to 1000 MHz



Plot A: 30MHz to 1GHz, Antenna Vertical

Frequency (MHz)	QuasiPeak (dBµV/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dBµV/m)	Antenna	Verdict
833.16	39.08	120.000	100.0	46.0	Vertical	Pass





Plot B: 30MHz to 1GHz, Antenna Horizontal

Frequency (MHz)	QuasiPeak (dB µ V/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dB µ V/m)	Antenna	Verdict
361.74	38.19	120.000	100.0	46.0	Horizontal	Pass



For 1GHz to 25GHz

AN	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (0CH_2402MHz)										
No.	Frequency (MHz)	Emss Lev (dBuV	el	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)		
1	2390.00	57.10	PK	74.0	-16.90	1.01 H	228	24.90	32.20		
2	2390.00	43.60	AV	54.0	-10.40	1.01 H	228	11.40	32.20		
3	*2402.00	104.70	PK	/	/	1.03 H	112	72.50	32.20		
4	*2402.00	103.90	AV	/	/	1.03 H	112	71.70	32.20		
5	4804.00	51.60	PK	74.00	-22.40	1.00 H	254	46.30	5.30		
6	4804.00	45.80	AV	54.00	-8.20	1.00 H	254	40.50	5.30		
A	NTENNA I	POLAR	ITY &	& TEST D	ISTANC	E: VERTIC	CALAT 3 M	(0CH_2402	(MHz)		
No.	No. Frequency (MHz) Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)			
1	2390.00	56.70	PK	74.0	-17.30	1.11 V	228	24.50	32.20		
2	2390.00	44.40	AV	54.0	-9.60	1.11 V	228	12.20	32.20		
3	*2402.00	107.10	PK	/	/	1.09 V	112	74.90	32.20		
4	*2402.00	104.60	AV	/	/	1.03 V	112	72.40	32.20		
5	4804.00	53.40	PK	74.00	-19.60	1.21 V	254	48.10	5.30		
6	4804.00	44.70	AV	54.00	-9.30	1.21 V	254	39.40	5.30		



AN	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (20CH_2442MHz)											
No.	Frequency (MHz)	Emss Lev (dBuV	el	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)			
1	*2442.00	107.60	PK	/	/	1.01 H	210	75.40	32.20			
2	*2442.00	104.80	AV	/	/	1.01 H	210	72.60	32.20			
3	4884.00	53.50	PK	74.00	-20.50	1.03 H	272	48.20	5.30			
4	4884.00	45.90	AV	54.00	-8.10	1.03 H	272	40.60	5.30			
A	NTENNA I	OLAR	ITY 8	t TEST DI	STANCI	E: VERTIC	ALAT 3 M	(20CH_2442	2MHz)			
No.	o. 1 Jevel		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)				
1	*2442.00	108.60	PK	/	/	1.09 V	112	76.40	32.20			
2	*2442.00	105.70	AV	/	/	1.09 V	112	73.50	32.20			
3	4884.00	54.80	PK	74.00	-19.20	1.21 V	254	49.50	5.30			
4	4884.00	42.50	AV	54.00	-8.50	1.21 V	254	40.20	5.30			



AN	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (39CH_2480MHz)										
No.	Frequency (MHz)	Emss Lev (dBuV	el	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)		
1	*2480.00	105.80	PK	/	/	1.05 H	215	73.50	32.30		
2	*2480.00	104.70	AV	/	/	1.05 H	215	72.40	32.30		
3	2483.50	56.90	PK	74.0	-17.10	1.05 H	211	24.50	32.40		
4	2483.50	44.60	AV	54.0	-9.40	1.05 H	211	12.20	32.40		
5	4960.00	52.20	PK	74.0	-11.80	1.45 H	320	46.70	5.50		
6	4960.00	46.90	AV	54.0	-7.10	1.45 H	320	41.40	5.50		
A	NTENNA F	POLAR	ITY 8	TEST DI	STANCI	E: VERTICA	ALAT 3 M	(39CH_2480	OMHz)		
No.	Frequency (MHz)	Emss Lev (dBuV	el	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)		
1	*2480.00	107.40	PK	/	/	1.05 V	174	75.10	32.30		
2	*2480.00	106.80	AV	/	/	1.05 V	174	74.50	32.30		
3	2483.50	56.80	PK	74.0	-17.20	1.05 V	177	24.40	32.40		
4	2483.50	45.40	AV	54.0	-8.60	1.05 V	177	13.00	32.40		
5	4960.00	55.60	PK	74.0	-18.40	1.45 V	201	50.10	5.50		
6	4960.00	45.60	AV	54.0	-8.40	1.45 V	201	40.10	5.50		

REMARKS:

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
 - Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " * ": Fundamental frequency.



2.7. Conducted Emission

2.7.1. Limit of Conducted Emission


For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Eraguanay ranga (MUz)	Conducted Limit (dBµV)				
Frequency range (MHz)	Quai-peak	Average			
0.15 - 0.50	66 to 56	56 to 46			
0.50 - 5	56	46			
5 - 30	60	50			

2.7.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.7.3. Test Setup








2.7.4. Test Procedures


- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

2.7.5. Test Result

- 1. The EUT configuration of the emission tests is Bluetooth Link + USB Cable (Charging from Adapter). Adapter model: DG30
- 2. The power adapter support (100~240V AC, 50/60Hz), the EUT was tested at the both available voltages (120, 240V AC), and 60Hz. Only the worst-case mode (120V/60Hz) was record in this report.









(Plot A: L Phase)

	Conducted Disturbance at Mains Terminals										
	L Test Data										
	QP			AV							
Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)						
0.960	56.0	49.707	0.960	46.0	39.837						
2.877	56.0	47.880	2.877	46.0	41.187						
4.799	56.0	46.034	4.799	46.0	38.703						







(Plot B: N Phase)

	Conducted Disturbance at Mains Terminals										
	N Test Data										
	QP			AV							
Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Frequency (MHz)	Limits (dBµV)	Measurement Value (dBμV)						
0.956	56.0	43.168	0.951	46.0	36.949						
1.532	56.0	42.181	2.855	46.0	35.618						
2.855	56.0	43.631	4.695	46.0	30.412						

Test Result: PASS



3. List of measuring equipment

Description	Manufacturer	Model	Serial No.	Test Date	Due Date	Remark
EMI Test Receiver	R&S	ESIB26	A0304218	2015.06.02	2016.06.01	Radiation
Full-Anechoic Chamber	Albatross	12.8m*6.8m *6.4m	A0412372	2015.01.05	2016.01.04	Radiation
Loop Antenna	Schwarz beck	HFH2-Z2	100047	2015.06.02	2016.06.01	Radiation
Bilog Antenna	Schwarzbeck	VULB 9163	9163-274	2015.06.02	2016.06.01	Radiation
Double ridge horn antenna	R&S	HF906	100150	2015.06.02	2016.06.01	Radiation
Ultra-wideband antenna	R&S	HL562	100089	2015.06.02	2016.06.01	Radiation
Test Antenna – Horn (18-26.5GHz)	ETS	3160-09	A0902607	2015.06.02	2016.06.01	Radiation
Amplifier 20M~3GHz	R&S	PAP-0203H	22018	2015.06.02	2016.06.01	Radiation
Ampilier 1G~18GHz	R&S	MITEQ AFS42-0010 1800	25-S-42	2015.06.02	2016.06.01	Radiation
Ampilier 18G~40GHz	R&S	JS42-180026 00-28-5A	12111.0980.00	2015.06.02	2016.06.01	Radiation
Spectrum Analyzer	R&S	FSP40	1164.4391.40	2015.07.07	2016.07.06	Conducted
Power Meter	R&S	NRVS	1020.1809.02	2015.06.02	2016.06.01	Conducted
Power Sensor	R&S	NRV-Z4	823.3618.03	2015.06.02	2016.06.01	Conducted
LISN	ROHDE&SC HWARZ	ESH2-Z5	A0304221	2015.06.02	2016.06.01	Conducted
Test Receiver	R&S	ESCS30	A0304260	2015.06.02	2016.06.01	Conducted
Cable	SUNHNER	SUCOFLEX 100	/	2015.06.02	2016.06.01	Radiation
Cable	SUNHNER	SUCOFLEX 104	/	2015.06.02	2016.06.01	Radiation

** END OF REPORT **