



FCC/ISED TEST REPORT

Report Number : **709502403357-00B** Date of Issue: April 11, 2025

Model : MT01-5325-069101, MT01-5325-069102, MT01-5325-069101-CT,
MT01-5325-069102-CT, MT01-5325-069001, MT01-5325-069002,
MT01-5325-069001-CT, MT01-5325-069002-CT, MT01-5325-069003,
MT01-5325-069004, MT01-5325-069003-CT, MT01-5325-069004-CT,
MT01-5328-069002, MT01-5328-069001, MT01-5328-069002-CT,
MT01-5328-069001-CT

Product Type : ARC PRO LI-ION TUBULAR MOTOR

Applicant : Rollease Acmeda Inc

Address : 7th Floor / 750 East Main Street, Stamford, CT 06902, USA

Manufacturer : Rollease Acmeda Inc

Address : 7th Floor / 750 East Main Street, Stamford, CT 06902, USA

Test Result : ☒ **Positive** ☐ **Negative**

Total pages including
Appendices : 44



TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.



1 Table of Contents

1	Table of Contents	2
2	Report Modification Record	3
3	Details about the Test Laboratory.....	3
4	Description of the Equipment under Test	4
5	Summary of Test Standards.....	5
6	Summary of Test Results.....	6
7	General Remarks	7
8	Test Setups	8
9	Systems test configuration.....	11
10	Technical Requirement	12
10.1	Conducted Emission	12
10.2	Conducted peak output power and E.I.R.P.	17
10.3	6dB bandwidth	19
10.4	Power spectral density.....	22
10.5	Spurious RF conducted emissions	24
10.6	Band edge	28
10.7	Spurious radiated emissions for transmitter	31
11	Test Equipment List.....	42
12	System Measurement Uncertainty	43
13	Photographs of Test Set-ups	44
14	Photographs of EUT	44



2 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
709502403357-00B	First Issue	04/11/2025

3 Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
No.16 Lane, 1951 Du Hui Road,
Shanghai 201108,
P.R. China

Test Firm FCC
Registration
Number: 820234

Designation
number: CN1183

IC Company
Number: 31668

CAB identifier: CN0101

Telephone: +86 21 6141 0123
Fax: +86 21 6140 8600

4 Description of the Equipment under Test

Product: ARC PRO LI-ION TUBULAR MOTOR

Model no./HVIN/PMN: MT01-5325-069101, MT01-5325-069102, MT01-5325-069101-CT, MT01-5325-069102-CT, MT01-5325-069001, MT01-5325-069002, MT01-5325-069001-CT, MT01-5325-069002-CT, MT01-5325-069003, MT01-5325-069004, MT01-5325-069003-CT, MT01-5325-069004-CT, MT01-5328-069002, MT01-5328-069001, MT01-5328-069002-CT, MT01-5328-069001-CT

FCC ID: 2AGGZ003B9ACA5B

IC: 21769-003B9ACA5B

Rating: USB input 5V

RF Transmission Frequency: 2402~2480 MHz (BLE); 433.92MHz

No. of Operated Channel:

Bluetooth Low Energy							
Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Modulation: 2.4GHz BLE: GFSK, 433.92MHz: GFSK

Antenna Type: Chip antenna for 2.4GHz, Line antenna for 433.92MHz

Antenna Gain: 2.62dBi for 2.4GHz; 3dBi for 433.92MHz

Description of the EUT: The Equipment Under Test (EUT) was an ARC PRO LI-ION TUBULAR MOTOR which support BLE and 433. 92MHz transmit function.All products are identical in electrical and mechanical construction except for the model number, rotate speed, torque and dimension.In addition, the 5325 series and 5328 series use the different inside motor and this different will not affect the RF testing. So, we chose model MT01-5328-069002 to perform all tests.

Test sample no.: SHA-859528-1 (Radiated and Conducted sample)

The sample's mentioned in this report is/are submitted/ supplied/ manufactured by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.

5 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2023 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
RSS-Gen Issue 5 April 2018 + Amendment 1 March 2019 + Amendment 2 February 2021	General Requirements for Compliance of Radio Apparatus
RSS-247 Issue 3 August 2023	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSS) and License-Exempt Local Area Network (LE-LAN) Devices

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 Measurement Guidance and ANSI C63.10-2020.

6 Summary of Test Results

Technical Requirements							
FCC Part 15 Subpart C & RSS-247 Issue 3/RSS-Gen Issue 5							
Test Condition			Pages	Test Site	Test Result		
					Pass	Fail	N/A
§15.207	RSS-GEN 8.8	Conducted emission AC power port	12~16	Site 1	☒	☐	☐
§15.247 (b) (3)	RSS-247 5.4(d)	Conducted peak output power and e.i.r.p.	17~18	Site 1	☒	☐	☐
§15.247(a)(1)	RSS-247 5.1(a) & RSS-Gen 6.7	20dB bandwidth and 99% Occupied Bandwidth	---	---	☐	☐	☒
§15.247(a)(1)	RSS-247 5.1(b)	Carrier frequency separation	---	---	☐	☐	☒
§15.247(a)(1)(iii)	RSS-247 5.1(d)	Number of hopping frequencies	---	---	☐	☐	☒
§15.247(a)(1)(iii)	RSS-247 5.1(d)	Dwell Time - Average Time of Occupancy	---	---	☐	☐	☒
§15.247(a)(2)	RSS-247 5.2(a) & RSS-GEN 6.7	6dB bandwidth and 99% Occupied Bandwidth	19~21	Site 1	☒	☐	☐
§15.247(e)	RSS-247 5.2(b)	Power spectral density	22~23	Site 1	☒	☐	☐
§15.247(d)	RSS-247 5.5	Spurious RF conducted emissions	24~27	Site 1	☒	☐	☐
§15.247(d)	RSS-247 5.5	Band edge	28~30	Site 1	☒	☐	☐
§15.247(d) & §15.209 & §15.205	RSS-247 5.5 & RSS-Gen 6.13	Spurious radiated emissions for transmitter	31~41	Site 1	☒	☐	☐
§15.203	RSS-Gen 6.8	Antenna requirement	See note 1		☒	☐	☐

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses a chip and line antenna, which gain is 2.62dBi for 2.4GHz and 3dBi for 433.92MHz. In accordance to §15.203 and RSS-Gen 6.8, It is considered sufficiently to comply with the provisions of this section.



7 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2AGGZ003B9ACA5B, IC: 21769-003B9ACA5B complies with Section 15.207, 15.205, 15.209, 15.231 of the FCC Part 15, Subpart C Rules. RSS-Gen Issue 5 and RSS-210 issue 11.

This report is only for 2.4GHz BLE, for 433.92MHz refer to report No.709502403357-00C.

SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: October 17,2024

Testing Start Date: October 18,2024

Testing End Date: November 17,2024

-TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Hui TONG
Review Engineer

Prepared by:

Jiayi XU
Project Engineer


Tested by:

Tianji XU
Test Engineer




8 Test Setups

7.1 AC Power Line Conducted Emission test setups




7.2 Radiated test setups


9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:




1GHz ~ 18GHz Test Setup:



18GHz ~ 25GHz Test Setup:



7.3 Conducted RF test setups



9 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenove	E470	PF-OU5TS7 17/09
AC/DC Adapter	--	YLJXA-A050200	---

Test software: nextgencomms.exe, which used to control the EUT in continues transmitting mode.

The system was configured to channel 0, 19, and 39 for the test.

Test Mode Applicability and Tested Channel Detail:

Mode	Tested Channel	Data Rate (Mbps)	Modulation	Index Value (Power level setting)
BLE	1	1	GFSK	By manufacturer
	19	1	GFSK	By manufacturer
	39	1	GFSK	By manufacturer

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power.

10 Technical Requirement

10.1 Conducted Emission

Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line

Limit

According to §15.207 & RSS-GEN Issue 5 8.8, conducted emissions limit as below:

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency

Conducted Emission

150k-30MHz Conducted Emission Test


EUT Information

EUT Name: ARC PRO LI-ION TUBULAR MOTOR
 Model: MT01-5328-069002
 Client: Rollease Acmeda Inc
 Op Cond: AC 120V, 60Hz, charging and TX at 2402MHz
 Operator: Tianji Xu
 Standard: FCC Part 15.207(a)
 Comment: Horizontal
 Sample No.: SHA-859528-1

Scan Setup: Voltage with 2-Line-LISN pre [EMI conducted]

Hardware Setup: Voltage with 2-Line-LISN
 Receiver: [ESR 3]
 Level Unit: dBuV

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
9 kHz - 150 kHz	100 Hz	PK+	200 Hz	0.02 s	0 dB
150 kHz - 30 MHz	4.5 kHz	PK+; AVG	9 kHz	0.01 s	0 dB





Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.303000	---	20.72	50.16	29.44	1000.0	9.000	L1	19.5
0.343500	34.98	---	59.12	24.14	1000.0	9.000	L1	19.5
0.438000	---	23.43	47.10	23.67	1000.0	9.000	L1	19.5
0.438000	35.47	---	57.10	21.63	1000.0	9.000	L1	19.5
0.919500	31.08	---	56.00	24.92	1000.0	9.000	L1	19.5
1.000500	---	19.55	46.00	26.45	1000.0	9.000	L1	19.5
2.139000	30.74	---	56.00	25.26	1000.0	9.000	L1	19.5
2.139000	---	17.54	46.00	28.46	1000.0	9.000	L1	19.5
5.203500	---	12.17	50.00	37.83	1000.0	9.000	L1	19.6
5.365500	18.81	---	60.00	41.19	1000.0	9.000	L1	19.6
25.044000	18.62	---	60.00	41.38	1000.0	9.000	L1	20.9
26.434500	---	8.70	50.00	41.30	1000.0	9.000	L1	20.9

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

150k-30MHz Conducted Emission Test


EUT Information

EUT Name: ARC PRO LI-ION TUBULAR MOTOR
Model: MT01-5328-069002
Client: Rollease Acmeda Inc
Op Cond: AC 120V,60Hz, charging and TX at 2402MHz
Operator: Tianji Xu
Standard: FCC Part 15.207(a)
Comment: Vertical
Sample No.: SHA-859528-1

Scan Setup: Voltage with 2-Line-LISN pre [EMI conducted]

Hardware Setup: Voltage with 2-Line-LISN
Receiver: [ESR 3]
Level Unit: dBuV

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamplifier
9 kHz - 150 kHz	100 Hz	PK+	200 Hz	0.02 s	0 dB
150 kHz - 30 MHz	4.5 kHz	PK+; AVG	9 kHz	0.01 s	0 dB





Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.339000	---	27.01	49.23	22.22	1000.0	9.000	N	19.4
0.348000	32.46	---	59.01	26.55	1000.0	9.000	N	19.4
0.442500	---	31.29	47.01	15.72	1000.0	9.000	N	19.5
0.442500	36.66	---	57.01	20.35	1000.0	9.000	N	19.5
0.879000	31.41	---	56.00	24.59	1000.0	9.000	N	19.5
1.158000	---	26.47	46.00	19.53	1000.0	9.000	N	19.5
2.481000	---	23.93	46.00	22.07	1000.0	9.000	N	19.5
2.953500	29.10	---	56.00	26.90	1000.0	9.000	N	19.5
5.680500	26.69	---	60.00	33.31	1000.0	9.000	N	19.6
5.721000	---	20.97	50.00	29.03	1000.0	9.000	N	19.6
24.760500	22.97	---	60.00	37.03	1000.0	9.000	N	20.6
29.220000	---	14.96	50.00	35.04	1000.0	9.000	N	20.8

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

10.2 Conducted peak output power and E.I.R.P.

Test Method (1)

1. Use the following spectrum analyzer settings:
RBW > the 6 dB bandwidth of the emission being measured, VBW $\geq$ 3RBW, Span $\geq$ 3RBW
Sweep = auto, Detector function = peak, Trace = max hold.
2. Add a correction factor to the display.
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

Limits

According to §15.247 (b) (3) & RSS-247 5.4(d), conducted peak output power limit as below:

	Frequency Range	Limit	Limit
	MHz	W	dBm
Conducted peak output power	2400-2483.5	≤ 1	≤ 30
e.i.r.p.	2400-2483.5	≤ 4	≤ 36


Test result as below table

Antenna gain= 2.62dBi						
Frequency (MHz)	Conducted Peak Output Power (dBm) §15.247 (b) (3)			e.i.r.p. (dBm) RSS-247 5.4(d)		
	Result	limit	Verdict	Result	limit	Verdict
2402MHz	-2.06	≤ 30	Pass	0.56	≤ 36	Pass
2440MHz	-2.93	≤ 30	Pass	-0.31	≤ 36	Pass
2480MHz	-3.74	≤ 30	Pass	-1.12	≤ 36	Pass




Peak output power


Channel 0 (2402MHz)



Channel 19 (2440MHz)



Channel 39 (2480MHz)



10.36dB bandwidth

Test Method for 6 dB Bandwidth

1. Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
2. Set the VBW $\geq [3 \times \text{RBW}]$.
3. Detector = peak.
RBW=100KHz, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Trace mode = max-hold.
5. Sweep = No faster than coupled (auto) time.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.

Test Method for 99 % Bandwidth

1. Connect EUT test port to spectrum analyzer.
Use the following spectrum analyzer settings:
RBW=1% to 5% of the actual occupied, VBW $\geq$ 3RBW, Sweep = auto,
Detector function = peak, Trace = max hold
2. Use the occupied bandwidth measurement capability of test receiver.
3. Allow the trace to stabilize, record the occupied bandwidth value.

Limit


6dB bandwidth Limit [kHz]	99% bandwidth Limit [kHz]
≥ 500	--

Test result

Test Mode	Frequency MHz	6dB bandwidth (MHz)		Result	99% occupied bandwidth MHz
		result	limit	verdict	
BLE	2402	0.647	≥ 0.5	Pass	1.009
	2440	0.653	≥ 0.5	Pass	0.999
	2480	0.644	≥ 0.5	Pass	1.013




6dB Bandwidth





99% Bandwidth



10.4 Power spectral density

Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. The RF output of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
4. Set analyzer center frequency to DTS channel center frequency. RBW=3kHz, VBW $\geq$ 3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
5. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
6. Repeat above procedures until other frequencies measured were completed.


Limit

Limit [dBm/3kHz]

≤ 8

Test result

Data transmission rate	Frequency	Power spectral density	Result
1Mbps	MHz	dBm/3kHz	
	Top channel 2402MHz	-15.89	Pass
	Middle channel 2440MHz	-16.72	Pass
	Bottom channel 2480MHz	-17.52	Pass



10.5 Spurious RF conducted emissions

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
5. The level displayed must comply with the limit specified in this Section. Submit these plots.
6. Repeat above procedures until all frequencies measured were complete.


Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20




Spurious RF conducted emissions

Out-of-Band Emissions
Channel 0 (2402MHz)






Out-of-Band Emissions
Channel 19 (2440MHz)





Out-of-Band Emissions
Channel 39 (2480MHz)



10.6 Band edge

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize, use the peak and delta measurement to record the result.
5. The level displayed must comply with the limit specified in this Section.
6. Repeat above procedures until all frequencies measured were complete and submit all the plots.


Limit



In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under § 15.247(b)(3) and RSS-247 section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB.

Frequency Range MHz	Limit (dBc)
30-25000	-20



Test result





10.7 Spurious radiated emissions for transmitter

Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10
 - 1) Procedure for Unwanted Emissions Measurements Below 1000 MHz
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz to 120kHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.
 - 2) For Peak unwanted emissions Above 1GHz:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 1MHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.
Procedures for average unwanted emissions measurements above 1GHz
 - a) RBW = 1MHz.
 - b) $VBW \setminus [3 \times RBW]$.
 - c) Detector = RMS (power averaging), if $[\text{span} / (\# \text{ of points in sweep})] \setminus RBW / 2$.
Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
 - d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)
 - e) Sweep time = auto.
 - f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of $1 / D$, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
 - g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is $[10 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.

2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is $[20 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.

3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission (AV) at frequency above 1GHz.

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under § 15.247(b)(3) and RSS 247 section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in § 15.209(a) and RSS-Gen is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a) and RSS-Gen section 8.9, must also comply with the radiated emission limits specified in § 15.209(a) and RSS-Gen section 8.10.

Frequency MHz	Field Strength μV/m	Field Strength dBμV/m	Detector	Measurement distance meters
0.009-0.490	2400/F(kHz)	48.5-13.8	AV	300
0.490-1.705	24000/F(kHz)	33.8-23.0	QP	30
1.705-30	30	29.5	QP	30
30-88	100	40	QP	3
88-216	150	43.5	QP	3
216-960	200	46	QP	3
960-1000	500	54	QP	3
Above 1000	500	54	AV	3
Above 1000	5000	74	PK	3

Note 1: Limit 3m(dBμV/m)=Limit 300m(dBμV/m)+40Log(300m/3m) (Below 30MHz)

Note 2: Limit 3m(dBμV/m)=Limit 30m(dBμV/m)+40Log(30m/3m) (Below 30MHz)

Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

Data of measurement within frequency range 9kHz-30MHz and 18-25GHz is the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so test data does not present in this report.

Test result

The worst case of Radiated Emission below 1GHz: Only the worst case listed as below.

30-1000MHz Radiated Emission

EUT Information


EUT Name:	ARC PRO LI-ION TUBULAR MOTOR
Model	MT01-5328-069002
Client:	Rollease Acmeda Inc
Op Cond	AC 120V,60Hz, charging and TX at 2480MHz
Operator:	Tianji Xu
Standard	FCC Part 15.209(a)
Comment:	Horizontal
Sample No.:	SHA-859528-2

Sweep Setup: RE_VULB9168_pre_Cont_30-1000 [EMI radiated]

Hardware Setup:	RE_VULB9168
Receiver:	[ESR 3]
Level Unit:	dBuV/m

Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
30 MHz - 1 GHz	48.5 kHz	PK+	120 kHz	0.2 s	20 dB

RE_VULB9168_pre_Cont_30-1000



Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)
41.360000	20.4	1000.0	120.000	100.0	H	122.0	20.0	19.6
54.240000	21.6	1000.0	120.000	112.0	H	158.0	20.9	18.4
69.240000	24.8	1000.0	120.000	200.0	H	32.0	18.9	15.2
160.480000	20.5	1000.0	120.000	300.0	H	118.0	21.0	23.0
240.680000	21.2	1000.0	120.000	180.0	H	201.0	19.7	24.8
714.800000	31.7	1000.0	120.000	158.0	H	230.0	31.2	14.3

(continuation of the "Limit and Margin" table from column 16 ...)

Frequency (MHz)	Limit - QPK (dBuV/m)	Comment
41.360000	40.0	
54.240000	40.0	
69.240000	40.0	
160.480000	43.5	
240.680000	46.0	
714.800000	46.0	

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

30-1000MHz Radiated Emission

EUT Information


EUT Name: ARC PRO LI-ION TUBULAR MOTOR
Model: MT01-5328-069002
Client: Rollease Acmeda Inc
Op Cond: AC 120V,60Hz, charging and TX at 2480MHz
Operator: Tianji Xu
Standard: FCC Part 15.209(a)
Comment: Vertical
Sample No.: SHA-859528-2

Sweep Setup: RE_VULB9168_pre_Cont_30-1000 [EMI radiated]

Hardware Setup: RE_VULB9168
Receiver: [ESR 3]
Level Unit: dBuV/m

Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamplifier
30 MHz - 1 GHz	48.5 kHz	PK+	120 kHz	0.2 s	20 dB

RE_VULB9168_pre_Cont_30-1000



Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)
37.560000	28.2	1000.0	120.000	202.0	V	156.0	19.5	11.8
39.280000	27.5	1000.0	120.000	110.0	V	227.0	19.7	12.5
58.160000	25.8	1000.0	120.000	150.0	V	302.0	20.7	14.2
69.040000	27.3	1000.0	120.000	224.0	V	186.0	19.0	12.7
134.800000	21.6	1000.0	120.000	196.0	V	224.0	20.0	21.9
727.320000	31.9	1000.0	120.000	168.0	V	196.0	31.7	14.1

(continuation of the "Limit and Margin" table from column 16 ...)

Frequency (MHz)	Limit - QPK (dBuV/m)	Comment
37.560000	40.0	
39.280000	40.0	
58.160000	40.0	
69.040000	40.0	
134.800000	43.5	
727.320000	46.0	


Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Radiated Emission 1-18GHz

Frequency: 2402MHz


RE_HF907_BRF_Pre



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4804.300000	41.6	---	274.0	H	312.0	-2.7	32.4	74.0	---	---
13797.400000	50.9	41.6	131.0	H	11.0	4.7	23.1	74.0	12.4	54.0
16676.800000	51.5	42.9	247.0	H	296.0	7.2	22.5	74.0	11.1	54.0


RE_HF907_BRF_Pre



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)
2379.400000	47.2	1000.000	116.0	H	32.0	-0.8	26.8	74.0
2389.900000	46.8	1000.000	266.0	H	174.0	-0.8	27.2	74.0
2402.000000	85.3	1000.000	119.0	H	156.0	-0.8	--	--


RE_HF907_BRF_Pre



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+	Limit - PK+	Margin - AV	Limit - AV (dBuV/m)
4803.700000	43.9	---	288.0	V	359.0	-2.7	30.1	74.0	---	---
13810.600000	50.9	41.9	229.0	V	359.0	4.7	23.1	74.0	12.1	54.0
17122.300000	51.8	43.9	283.0	V	359.0	7.3	22.2	74.0	10.1	54.0

RE_HF907_BRF_Pre




Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)
2373.940000	47.6	1000.0	1000.000	133.0	V	358.0	-0.8	26.4	74.0
2390.000000	46.3	1000.0	1000.000	282.0	V	358.0	-0.8	27.7	74.0
2402.000000	80.2	1000.0	1000.000	208.0	V	358.0	-0.8	--	--

Frequency: 2440MHz


RE_HF907_BRF_Pre



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+	Limit - PK+	Margin - AV	Limit - AV (dBuV/m)
4947.100000	42.3	---	123.0	H	27.0	-2.3	31.7	74.0	---	---
13825.000000	51.1	42.1	124.0	H	176.0	4.7	22.9	74.0	11.9	54.0
16714.900000	51.8	43.4	233.0	H	269.0	7.2	22.2	74.0	10.6	54.0

RE_HF907_BRF_Pre




Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+	Limit - PK+	Margin - AV	Limit - AV (dBuV/m)
4856.200000	41.8	---	178.0	V	337.0	-2.5	32.2	74.0	---	---
12042.700000	50.1	41.1	227.0	V	16.0	5.1	23.9	74.0	12.9	54.0
17166.000000	51.6	42.6	119.0	V	224.0	7.1	22.4	74.0	11.4	54.0

Frequency:2480MHz


RE_HF907_BRF_Pre



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+	Limit - PK+	Margin - AV	Limit - AV (dBuV/m)
4948.900000	42.3	---	273.0	H	186.0	-2.3	31.7	74.0	---	---
14912.800000	50.1	41.7	250.0	H	227.0	5.0	23.9	74.0	12.3	54.0
16654.300000	51.7	43.1	292.0	H	31.0	7.1	22.3	74.0	10.9	54.0


RE_HF907_BRF_Pre



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)
2480.000000	86.6	1000.000	155.0	H	28.0	-0.3	--	--
2483.500000	47.5	1000.000	230.0	H	47.0	-0.3	26.5	74.0
2492.420000	48.7	1000.000	132.0	H	117.0	-0.3	25.3	74.0


RE_HF907_BRF_Pre



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	AV (dBuV/m)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)	Margin - AV (dB)	Limit - AV (dBuV/m)
4937.500000	42.8	---	185.0	V	31.0	-2.3	31.2	74.0	---	---
14383.900000	50.4	41.5	181.0	V	112.0	4.8	23.6	74.0	12.5	54.0
17245.000000	51.9	43.1	114.0	V	274.0	7.2	22.1	74.0	10.9	54.0

RE_HF907_BRF_Pre



Limit and Margin

Frequency (MHz)	MaxPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - PK+ (dB)	Limit - PK+ (dBuV/m)
2480.000000	80.6	1000.0	1000.000	200.0	V	321.0	-0.3	--	--
2483.500000	46.8	1000.0	1000.000	153.0	V	225.0	-0.3	27.2	74.0
2490.400000	48.5	1000.0	1000.000	272.0	V	186.0	-0.3	25.5	74.0

11 Test Equipment List

List of Test Instruments
Test Site1

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE DATE
RE	EMI Test Receiver	Rohde & Schwarz	ESR3	101906	2024-8-1	2025-7-31
	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2024-8-1	2025-7-31
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9168	961	2024-8-30	2025-8-29
	Horn Antenna	Rohde & Schwarz	HF907	102393	2024-4-14	2025-4-13
	Pre-amplifier	Shenzhen HzEMC	HPA-081843	HYP A23026	2024-4-16	2025-4-15
	Loop antenna	Rohde & Schwarz	HFH2-Z2	100443	2024-6-26	2025-6-25
	Double Ridged Horn Antenna	ETS-Lindgren	3116C	00246076	2023-7-7	2026-7-6
	Band reject filter	Wainwright	WRCGV10-2382-2402-2480-2500-52SS	38	2024-8-1	2025-7-31
	3m Semi-anechoic chamber	TDK	9X6X6	----	2024-5-8	2027-5-7
	Coaxial Cable	----	----	RE Cable 01	2024-8-1	2025-7-31
	Coaxial Cable	----	----	RE Cable 02	2024-8-1	2025-7-31
	Coaxial Cable	----	----	RE Cable 03	2024-8-1	2025-7-31
	Coaxial Cable	----	----	RE Cable 04	2024-8-1	2025-7-31
CE	EMI Test Receiver	Rohde & Schwarz	ESR3	101907	2024-8-1	2025-7-31
	LISN	Rohde & Schwarz	ENV216	101924	2024-8-1	2025-7-31

Measurement Software Information			
Test Item	Software	Manufacturer	Version
C	MTS 8310	MWRFtest	2.0.0.0
RE	EMC 32	Rohde & Schwarz	V10.50.40
CE	EMC 32	Rohde & Schwarz	V9.15.03

C - Conducted RF tests

- Conducted peak output power
- 6dB bandwidth and 99% Occupied Bandwidth
- Power spectral density*
- Spurious RF conducted emissions
- Band edge



12 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

Items	Extended Uncertainty
Conducted Disturbance at Mains Terminals	150kHz to 30MHz, LISN, 3.16dB
Radiated Disturbance	9kHz to 30MHz, 3.52dB 30MHz to 1GHz, 5.03dB (Horizontal) 5.12dB (Vertical) 1GHz to 18GHz, 5.49dB 18GHz to 40GHz, 5.63dB
RF Conducted Measurement	Power related: 1.16dB Frequency related: 6.00×10 ⁻⁸

Measurement Uncertainty Decision Rule:

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2023, clause 4.3.3.



13 Photographs of Test Set-ups

Refer to the < Test Setup photos >.

14 Photographs of EUT

Refer to the < External Photos > & < Internal Photos >.

-----End of Test Report-----