

Radio Exposure Evaluation Report

FCC ID : 2AGMR-AP750NRE
Equipment : 4-radio Narrow-Directional Outdoor Wi-Fi 7 Access Point
Brand Name : Everest Networks
Model Name : AP750NRe
Applicant : Everest Networks, Inc.
42808 Christy Street Suite 108 Fremont, CA 94538
Manufacturer : Everest Networks, Inc.
42808 Christy Street Suite 108 Fremont, CA 94538
Standard : 47 CFR FCC Part 2 Subpart J, section 2.1091

The product was received on Jun. 04, 2024, and testing was started from Jun. 26, 2024 and completed on Jun. 29, 2024. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.


Approved by: Jackson Tsai

SPORTON INTERNATIONAL INC. Hsinhua Laboratory
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT3

SUMMARY OF TEST RESULT4

1 GENERAL DESCRIPTION5

1.1 Information.....5

1.2 Applicable Standards7

1.3 Testing Location7

2 MAXIMUM PERMISSIBLE EXPOSURE8

2.1 Limit of Maximum Permissible Exposure8

2.2 RF Exposure Exempt Measurement9

2.3 Multiple RF Sources Exposure.....10

2.4 MPE Calculation Method11

2.5 Calculated Result and Limit.....12

Photographs of EUT V01



History of this test report

Report No.	Version	Description	Issued Date
FA432804	01	Initial issue of report	Jul. 12, 2024
FA432804	02	Revised typo. (This report is the latest version replacing for the report issued on Jul. 12, 2024.)	Jul. 19, 2024



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

None

Reviewed by: Ben Tseng

Report Producer: Michelle Tsai

1 General Description

1.1 Information

1.1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5700 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)

1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector	Support	Remark
1	Everest	PCB-000017-001-D	PCB	I-PEX	5G	Radio 1
2	Everest	PCB-000017-001-D	PCB	I-PEX		
3	Everest	PCB-000017-001-D	PCB	I-PEX		
4	Everest	PCB-000017-001-D	PCB	I-PEX		
5	Everest	PCB-000016-001-D	PCB	I-PEX		Radio 2
6	Everest	PCB-000016-001-D	PCB	I-PEX		
7	Everest	PCB-000016-001-D	PCB	I-PEX		
8	Everest	PCB-000016-001-D	PCB	I-PEX		
9	Everest	PCB-000049-001-A	PCB	I-PEX	6G	Radio 3
10	Everest	PCB-000049-001-A	PCB	I-PEX	5G	
11	Everest	PCB-000049-001-A	PCB	I-PEX	6G	
12	Everest	PCB-000049-001-A	PCB	I-PEX	5G	
13	Everest	PCB-000049-001-A	PCB	I-PEX	6G	
14	Everest	PCB-000049-001-A	PCB	I-PEX	5G	
15	Everest	PCB-000049-001-A	PCB	I-PEX	6G	
16	Everest	PCB-000049-001-A	PCB	I-PEX	5G	
17	Everest	PCB-000048-001-A	PCB	I-PEX	6G	Radio 4
18	Everest	PCB-000048-001-A	PCB	I-PEX		
19	Everest	PCB-000048-001-A	PCB	I-PEX		
20	Everest	PCB-000048-001-A	PCB	I-PEX		



Ant.	Port	Gain (dBi)				
		5G				6E
		U-NII-1	U-NII-2A	U-NII-2c	U-NII-3	
1	1	-	-	-	9	-
2	2	-	-	-	9	-
3	3	-	-	-	9	-
4	4	-	-	-	9	-
5	1	9	9	-	-	-
6	2	9	9	-	-	-
7	3	9	9	-	-	-
8	4	9	9	-	-	-
9	1	-	-	-	-	12.5
10	2	-	-	11.5	-	-
11	3	-	-	-	-	12.5
12	4	-	-	11.5	-	-
13	5	-	-	-	-	12.5
14	6	-	-	11.5	-	-
15	7	-	-	-	-	12.5
16	8	-	-	11.5	-	-
17	1	-	-	-	-	11
18	2	-	-	-	-	11
19	3	-	-	-	-	11
20	4	-	-	-	-	11

Note 1: The EUT has twenty antennas.

Note 2: The antenna is cross polarized.

For 5GHz function:

For IEEE 802.11 a/n/ac/ax/be mode (4TX/4RX) <Radio 1>

Ant. 1~4 could transmit/receive simultaneously.

For IEEE 802.11 a/n/ac/ax/be mode (4TX/4RX) <Radio 2>

Ant. 5~8 could transmit/receive simultaneously.

For IEEE 802.11 a/n/ac/ax/be mode (4TX/4RX) <Radio 3>

Ant. 10, 12, 14, 16 could transmit/receive simultaneously.

1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 2 Subpart J, section 2.1091
- ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ 47 CFR Part 1.1307
- ♦ 47 CFR Part 1.1310

1.3 Testing Location

Test Lab. : Sporton International Inc. Hsinhua Laboratory		
☒	Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)
		TEL: 886-3-327-3456 FAX: 886-3-327-0973
Test site Designation No. TW3785 with FCC.		
☐	Wen 33rd.St. (TAF: 3785)	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)
		TEL: 886-3-318-0787 FAX: 886-3-318-0287
Test site Designation No. TW0008 with FCC.		

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

Multiple Transmitters Condition

Co-location as simultaneously transmitting (co-transmitting) and the evaluation shall be consider that simultaneous transmissions from co-located devices the individual transmitters are evaluated separately. After sum of the individual value (basic restriction / reference level) are measured/calculated also have to under basic restriction / reference level.

Co-transmitting mode:

1. Radio 1(5GHz WLAN) + Radio 2(5GHz WLAN) + Radio 3(5GHz WLAN)
2. Radio 1(5GHz WLAN) + Radio 2(5GHz WLAN)

2.2 RF Exposure Exempt Measurement

Option	Refer Std.	Exemption Exposure Thresholds (TL)
A	§1.1307(b)(3)(i)(A)	Available maximum time-averaged power is no more than 1 mW
B	§1.1307(b)(3)(i)(B)	$P_{th}(mW) = \begin{cases} ERP_{20cm} (d / 20cm)^x \rightarrow d \leq 20cm \\ ERP_{20cm} \rightarrow 20cm < d \leq 40cm \end{cases}$ $x = -\log_{10} \left(\frac{60}{ERP_{20cm} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$ $\begin{cases} ERP_{20cm} : 0.3GHz \leq f < 1.5GHz \rightarrow 2040f(mW) \\ ERP_{20cm} : 1.5GHz \leq f \leq 6GHz \rightarrow 3060(mW) \end{cases}$
C	§1.1307(b)(3)(i)(C)	$\begin{cases} 0.3 \sim 1.34MHz \rightarrow ERP(W) = 1920R^2 \\ 1.34 \sim 30MHz \rightarrow ERP(W) = 3450R^2 / f^2 \\ 30 \sim 300MHz \rightarrow ERP(W) = 3.83R^2 \\ 300 \sim 1500MHz \rightarrow ERP(W) = 0.0128R^2 f \\ 1500 \sim 100000MHz \rightarrow ERP(W) = 19.2R^2 \end{cases}$ f is in MHz; R is in m; $R > \lambda / 2\pi$

2.3 Multiple RF Sources Exposure

Refer Std.	Exemption Exposure Thresholds (TL)
§1.1307(b)(3)(ii)(A)	The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required)
§1.1307(b)(3)(ii)(B)	$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k} \leq 1$ a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P , including existing exempt transmitters and those being added. b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added. c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters. P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive). P_{th,i} = the exemption threshold power (P_{th}) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i. ERP_j = the ERP of fixed, mobile, or portable RF source j. ERP_{th,j} = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section. Evaluated_k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure. Evaluated Limit_k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.



2.4 MPE Calculation Method

The MPE was calculated at 71 cm to show compliance with the power density limit.
The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

2.5 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Radio 1 5GHz WLAN

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
5.8G;D1D	9.00	26.47	35.47	0.50	2410.5159	71.00	C	9678.720	0.2491

Radio 2 5GHz WLAN

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
5.2G;D1D	9.00	26.47	35.47	0.50	2410.5159	71.00	C	9678.720	0.2491
5.3G;D1D	9.00	20.37	29.37	0.50	591.7115	71.00	C	9678.720	0.0611

Radio 3 5GHz WLAN

Mode	DG	Power	EIRP	Tolerance	Tune-up ERP	Distance	Option	TL ERP	TL Ratio
	(dBi)	(dBm)	(dBm)	(dB)	(mW)	(cm)		(mW)	
5.6G;D1D	11.50	17.98	29.48	0.50	606.8900	71.00	C	9678.720	0.0627

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)



Simultaneous Transmission Analysis Mode:

Radio 1(5GHz WLAN) + Radio 2(5GHz WLAN) + Radio 3(5GHz WLAN)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
5.8G;D1D	9.00	26.47	35.47	0.50	2410.5159	71.00	C	9678.720	0.2491
5.2G;D1D	9.00	26.47	35.47	0.50	2410.5159	71.00	C	9678.720	0.2491
5.6G;D1D	11.50	17.98	29.48	0.50	606.8900	71.00	C	9678.720	0.0627
Sum Ratio	0.5608								
Ratio Limit	1.00000								

Simultaneous Transmission Analysis Mode:

Radio 1(5GHz WLAN) + Radio 2(5GHz WLAN)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
5.8G;D1D	9.00	26.47	35.47	0.50	2410.5159	71.00	C	9678.720	0.2491
5.2G;D1D	9.00	26.47	35.47	0.50	2410.5159	71.00	C	9678.720	0.2491
Sum Ratio	0.4981								
Ratio Limit	1.00000								

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

Note 4: Refer as clause 2.3 Multiple RF Sources Exposure. Please follow below option and sum TL ration table.

Option	Sum TL Ratio_B	Option	Sum TL Ratio_C	Option	Sum TL Ratio_E
B	$\sum_{i=1}^a \frac{P_i}{P_{th,i}}$	C	$\sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}}$	E	$\sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k}$

Note: The above antenna gain was declared by manufacturer.

—THE END—