

# **RF Exposure Report**

Report No.: SA160726C12B

FCC ID: 2AGMRAP12I360

Test Model: AP12I360

Received Date: Jul. 26, 2016

Test Date: Jul. 29 ~ Sep. 09, 2016

**Issued Date:** Nov. 10, 2016

Applicant: Tembo Systems, Inc.

Address: 2933 Bunker Hill Lane, Suite 100, Santa Clara, CA 95054, United States.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan,

R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN (R.O.C.)





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: SA160726C12B Page No. 1 / 7 Report Format Version: 6.1.1 Reference No.: 161101C21



## **Table of Contents**

Re	Release Control Record3				
1	Certificate of Conformity	4			
2	RF Exposure	5			
2	.1 Limits for Maximum Permissible Exposure (MPE) .2 MPE Calculation Formula .3 Classification	5			
3	Calculation Result of Maximum Conducted Power	6			



### **Release Control Record**

Issue No.	Description	Date Issued
SA160726C12B	Original release	Nov. 10, 2016

Page No. 3 / 7 Report Format Version: 6.1.1

Report No.: SA160726C12B Reference No.: 161101C21



#### 1 Certificate of Conformity

Product: AP1002Oi 2-Radio Omni-Directional Indoor Access Point

Brand: EVEREST™ Network Solutions

Test Model: AP12I360

Sample Status: Engineering sample

Applicant: Tembo Systems, Inc.

Test Date: Jul. 29 ~ Sep. 09, 2016

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

**IEEE C95.1** 

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : , Date: Nov. 10, 2016

Polly Chien / Specialist

**Approved by:** , **Date:** Nov. 10, 2016

Ken Liu / Senior Manager



#### 2 RF Exposure

#### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)		
Limits For General Population / Uncontrolled Exposure						
300-1500			F/1500	30		
1500-100,000			1.0	30		

F = Frequency in MHz

#### 2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

#### 2.3 Classification

The antenna of this product, under normal use condition, is at least 28cm away from the body of the user. So, this device is classified as **Mobile Device**.

Report No.: SA160726C12B Reference No.: 161101C21



#### 3 **Calculation Result of Maximum Conducted Power**

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm²)			
	Radio 1							
WLAN: CDD mode								
2412-2462	24.99	9.78	28	0.304	1			
WLAN: Beamforming mode								
2412-2462	18.77	9.78	28	0.073	1			
Radio 2								
WLAN: CDD mode	)							
5180-5240	24.28	11.73	28	0.405	1			
5745-5825	25.46	11.73	28	0.531	1			
WLAN: Beamforming mode								
5180-5240	18.26	11.73	28	0.101	1			
5745-5825	19.44	11.73	28	0.133	1			
Radio 3								
WLAN: CDD mode								
2412-2462	13.03	2.9	28	0.004	1			
Radio 4								
BT LE								
2402-2480	0.11	3.93	28	0.0003	1			
Note:								

Radio 1: 2.4GHz Band:  $10 \log[(10^{G1/20} + 10^{G2/20 + ... + } 10^{GN/20})^2/4] = 9.78dBi$ Radio 2: 5GHz Band: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20 + ... + } 10^{GN/20})^2/4] = 11.73dBi$ Radio 3: 2.4GHz Band: Directional gain = 2.9dBi

Report No.: SA160726C12B Reference No.: 161101C21



#### Conclusion:

Both of the WLAN 2.4G & WLAN 5G & BT LE can transmit simultaneously, the formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 + .....etc. < 1

CPD = Calculation power density

LPD = Limit of power density

	Max. Power (dBm)				
Frequency Band	WLAN 2	2.4GHz	BT EDR	DR Total Power (dBm) Power Lir	
	Radio 1	Radio 3	Radio 4		
2.4GHz	24.99	13.03	0.11	25.27	30

Radio 1 + Radio 2 + Radio 3 (2.4G) + Radio 4 = 0.304+0.531+0.004+0.0003=0.839

Therefore, the maximum calculation of this situation is 0.839, which is less than the "1" limit.

---END---