

**CETECOM™**

**CETECOM ICT Services**  
consulting - testing - certification >>>

## TEST REPORT

Test report no.: 1-0147/15-01-05



Deutsche  
Akkreditierungsstelle  
D-PL-12076-01-00

### Testing laboratory

**CETECOM ICT Services GmbH**  
Untertuerkheimer Strasse 6 – 10  
66117 Saarbruecken / Germany  
Phone: + 49 681 5 98 - 0  
Fax: + 49 681 5 98 - 90 75  
Internet: <http://www.cetecom.com>  
e-mail: [ict@cetecom.com](mailto:ict@cetecom.com)

#### Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2005) by the Deutsche Akkreditierungsstelle GmbH (DAkkS)

The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number: D-PL-12076-01-00

### Applicant

**pro-micron GmbH & Co. KG**  
Innovapark 20  
87600 Kaufbeuren / GERMANY  
Phone: +49 834 191 – 64 10  
Fax: +49 834 191 – 64 20  
Contact: Daniel Uhlemann  
e-mail: [daniel.uhlemann@pro-micron.de](mailto:daniel.uhlemann@pro-micron.de)  
Phone: +49 834 191 – 64 35

### Manufacturer

**pro-micron GmbH & Co. KG**  
Innovapark 20  
87600 Kaufbeuren / GERMANY

### Test standard/s

47 CFR Part 15

Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices

For further applied test standards please refer to section 3 of this test report.

### Test Item

**Kind of test item:** Sensory Tool Holder  
**Model name:** SPIKE Receiver  
**FCC ID:** 2AGNQSRE24AA01A1  
**Frequency:** DTS band 2400 MHz to 2483.5 MHz  
**Technology tested:** ZigBee  
**Antenna:** External antenna  
**Power supply:** 5.0 V DC, USB powered  
**Temperature range:** 0°C to +50°C



This test report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

### Test report authorized:

Marco Bertolino  
Lab Manager  
Radio Communications & EMC

### Test performed:

Christoph Schneider  
Testing Manager  
Radio Communications & EMC

## 1 Table of contents

1	Table of contents .....	2
2	General information .....	3
2.1	Notes and disclaimer .....	3
2.2	Application details.....	3
3	Test standard/s .....	3
3.1	Measurement guidance.....	3
4	Test environment.....	4
5	Test item.....	4
5.1	General description.....	4
5.2	Additional information .....	4
6	Test laboratories sub-contracted .....	4
7	Description of the test setup .....	5
7.1	Shielded semi anechoic chamber.....	6
7.2	Shielded fully anechoic chamber .....	7
7.3	Radiated measurements > 12.75 GHz.....	8
7.4	AC conducted .....	9
7.5	Conducted measurements C.BER system.....	10
8	Measurement uncertainty .....	11
9	Sequence of testing .....	12
9.1	Sequence of testing radiated spurious 9 kHz to 30 MHz.....	12
9.2	Sequence of testing radiated spurious 30 MHz to 1 GHz.....	13
9.3	Sequence of testing radiated spurious 1 GHz to 12.75 GHz .....	14
9.4	Sequence of testing radiated spurious above 12.75 GHz .....	15
10	Summary of measurement results.....	16
11	Additional comments .....	17
12	Measurement results .....	18
12.1	Antenna gain .....	18
12.2	Maximum output power.....	19
12.3	Power spectral density.....	22
12.4	DTS bandwidth.....	25
12.5	Occupied bandwidth – 99% emission bandwidth.....	28
12.6	Band edge compliance radiated.....	31
12.7	Spurious emissions conducted.....	34
12.8	Spurious emissions radiated below 30 MHz .....	38
12.9	Spurious emissions radiated 30 MHz to 1 GHz.....	41
12.10	Spurious emissions radiated above 1 GHz .....	46
12.11	Spurious emissions conducted below 30 MHz (AC conducted).....	53
13	Observations .....	56
Annex A	Document history .....	56
Annex B	Further information.....	56
Annex C	Accreditation Certificate .....	57

## 2 General information

### 2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM ICT Services GmbH.

The testing service provided by CETECOM ICT Services GmbH has been rendered under the current "General Terms and Conditions for CETECOM ICT Services GmbH".

CETECOM ICT Services GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CETECOM ICT Services GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CETECOM ICT Services GmbH test report include or imply any product or service warranties from CETECOM ICT Services GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CETECOM ICT Services GmbH.

All rights and remedies regarding vendor's products and services for which CETECOM ICT Services GmbH has prepared this test report shall be provided by the party offering such products or services and not by CETECOM ICT Services GmbH.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

### 2.2 Application details

Date of receipt of order:	2015-09-26
Date of receipt of test item:	2015-09-17
Start of test:	2015-09-23
End of test:	2015-11-04
Person(s) present during the test:	-/-

## 3 Test standard/s

Test standard	Date	Test standard description
47 CFR Part 15	-/-	Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices

### 3.1 Measurement guidance

Guidance	Version	Description
DTS: KDB 558074 D01	v03r03	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247
ANSI C63.4-2014	-/-	American national standard for methods of measurement of radio-noise emissions from low-voltage electrical and electronic equipment in the range of 9 kHz to 40 GHz
ANSI C63.10-2013	-/-	American national standard of procedures for compliance testing of unlicensed wireless devices

## 4 Test environment

Temperature	:	T <sub>nom</sub> T <sub>max</sub> T <sub>min</sub>	+20 °C during room temperature tests +50 °C during high temperature tests 0 °C during low temperature tests
Relative humidity content	:		55 %
Barometric pressure	:		not relevant for this kind of testing
Power supply	:	V <sub>nom</sub> V <sub>max</sub> V <sub>min</sub>	5.0 V DC, USB powered 5.5 V 4.5 V

## 5 Test item

### 5.1 General description

Kind of test item	:	Sensory Tool Holder
Type identification	:	SPIKE Receiver
S/N serial number	:	-/-
HW hardware status	:	COCK31102A00
SW software status	:	BTKaBlue V13.5
Frequency band	:	DTS band 2400 MHz to 2483.5 MHz (lowest channel 2405 MHz; highest channel 2475 MHz)
Type of modulation	:	OQPSK
Number of channels	:	16
Antenna	:	External antenna
Power supply	:	4.5 V to 5.5 V DC, USB powered
Temperature range	:	0°C to +50°C

### 5.2 Additional information

The content of the following annexes is defined in the QA. It may be that not all of the listed annexes are necessary for this report, thus some values in between may be missing.

Test setup- and EUT-photos are included in test report: 1-0147/15-01-01\_AnnexA  
1-0147/15-01-01\_AnnexB  
1-0147/15-01-01\_AnnexD

## 6 Test laboratories sub-contracted

None

## 7 Description of the test setup

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, RF generating and signaling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).


In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).

### Agenda: Kind of Calibration

k	calibration / calibrated	EK	limited calibration
ne	not required (k, ev, izw, zw not required)	zw	cyclical maintenance (external cyclical maintenance)
ev	periodic self verification	izw	internal cyclical maintenance
Ve	long-term stability recognized	g	blocked for accredited testing
vlkl!	Attention: extended calibration interval		
NK!	Attention: not calibrated	*)	next calibration ordered / currently in progress

## 7.1 Shielded semi anechoic chamber

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 1 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are confirmed with specifications ANSI C63. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analyzers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.



Measurement distance: tri-log antenna 10 meter

$$FS = UR + CL + AF$$

(FS-field strength; UR-voltage at the receiver; CL-loss of the cable; AF-antenna factor)


### Example calculation:

$$FS [dB\mu V/m] = 12.35 [dB\mu V/m] + 1.90 [dB] + 16.80 [dB/m] = 31.05 [dB\mu V/m] (35.69 \mu V/m)$$

### Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No Cetecom	Kind of Calibration	Last Calibration	Next Calibration
1	A	EMI Test Receiver	ESCI 3	R&S	100083	300003312	k	26.01.2015	26.01.2016
2	A	Antenna Tower	Model 2175	ETS-Lindgren	64762	300003745	izw	-/-	-/-
3	A	Positioning Controller	Model 2090	ETS-Lindgren	64672	300003746	izw	-/-	-/-
4	A	Turntable Interface-Box	Model 105637	ETS-Lindgren	44583	300003747	izw	-/-	-/-
5	A	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck	295	300003787	k	22.04.2014	22.04.2016

## 7.2 Shielded fully anechoic chamber



Measurement distance: horn antenna 3 meter; loop antenna 3 meter / 1 meter

FS = UR + CA + AF

(FS-field strength; UR-voltage at the receiver; CA-loss of the signal path; AF-antenna factor)


Example calculation:

FS [dB $\mu$ V/m] = 40.0 [dB $\mu$ V/m] + (-35.8) [dB] + 32.9 [dB/m] = 37.1 [dB $\mu$ V/m] (71.61  $\mu$ V/m)

### Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No Cetecom	Kind of Calibration	Last Calibration	Next Calibration
1	A	Double-Ridged Waveguide Horn Antenna 1-18.0GHz	3115	EMCO	9709-5290	300000212	k	13.08.2015	13.08.2017
2	A	EMI Test Receiver 20Hz- 26,5GHz	ESU26	R&S	100037	300003555	k	22.01.2015	22.01.2016
3	A	Band Reject Filter WRCG2400/2483-2375/2505-50/10SS		Wainwright	26	300003792	ne	-/-	-/-
4	A	Broadband Amplifier 0.5-18 GHz	CBLU5184540	CERNEX	22050	300004482	ev	-/-	-/-
5	A	4U RF Switch Platform	L4491A	Agilent Technologies	MY50000032	300004510	ne	-/-	-/-
6	A	NEXIO EMV-Software	BAT EMC	EMCO	MY50000032	300004682	ne	-/-	-/-

### 7.3 Radiated measurements > 12.75 GHz



Measurement distance: horn antenna 50 cm

$$FS = U_R + CA + AF$$

(FS-field strength;  $U_R$ -voltage at the receiver; CA-loss signal path & distance correction; AF-antenna factor)

Example calculation:


$$FS [dB\mu V/m] = 40.0 [dB\mu V/m] + (-60.1) [dB] + 36.74 [dB/m] = 16.64 [dB\mu V/m] (6.79 \mu V/m)$$

Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No Cetecom	Kind of Calibration	Last Calibration	Next Calibration
1	A	Std. Gain Horn Antenna 12.4 to 18.0 GHz	639	Narda	8402	300000787	k	14.08.2015	14.08.2017
2	A	Std. Gain Horn Antenna 18.0 to 26.5 GHz	638	Narda	8205	300002442	NK!	-/-	-/-
3	A	Amplifier 2-40 GHz	JS32-02004000-57-5P	MITEQ	1777200	300004541	ev	-/-	-/-
4	A	Signal Analyzer 40 GHz	FSV40	R&S	101353	300004819	k	24.08.2015	24.08.2016
5	A	RF-Cable	ST18/SMAm/SMAm/60	Huber & Suhner	Batch no. 606844	400001181	ev	-/-	-/-
6	A	RF-Cable	ST18/SMAm/SMAm/48	Huber & Suhner	Batch no. 600918	400001182	ev	-/-	-/-

## 7.4 AC conducted

### AC conducted



$$FS = UR + CF + VC$$

(FS-field strength; UR-voltage at the receiver; CR-loss of the cable and filter; VC-correction factor of the ISN)


#### Example calculation:

$$FS [dB\mu V/m] = 37.62 [dB\mu V/m] + 9.90 [dB] + 0.23 [dB] = 47.75 [dB\mu V/m] (244.06 \mu V/m)$$

#### Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No Cetecom	Kind of Calibration	Last Calibration	Next Calibration
1	A	Netznachbildung	ESH3-Z5	R&S	892475/017	300002209	k	17.06.2014	17.06.2016
2	A	EMI-Receiver	8542E	HP	3617A00170	300000568	k	28.01.2015	28.01.2016
3	A	Analyzer-Reference-System (Harmonics and Flicker)	ARS 16/1	SPS	A3509 07/0 0205	300003314	Ve	11.02.2014	11.02.2016

## 7.5 Conducted measurements C.BER system



OP = AV + CA  
(OP-output power; AV-analyzer value; CA-loss signal path)

*Example calculation:*  
OP [dBm] = 6.0 [dBm] + 11.7 [dB] = 17.7 [dBm] (58.88 mW)

### Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No Cetecom	Kind of Calibration	Last Calibration	Next Calibration
1	A	Switch / Control Unit	3488A	HP		300000929	ne	-/-	-/-
2	A	Temperature Test Chamber	VT 4002	Heraeus Voetsch	58566046820010	300003019	ev	03.09.2015	03.09.2017
3	A	Power Supply	NGSM 32/10	R&S	3939	400000192	viKI!	22.01.2015	22.01.2017
4	A	USB/GPIB interface	82357B	Agilent Technologies	MY52103346	300004390	ne	-/-	-/-
5	A	Labormessplatzrechner 19" Servergehäuse	Intel Core i3 3225/3,3 GHz, Prozessor	Agilent Technologies	35230157A0370	300004646	ne	-/-	-/-
6	A	Signal Analyzer 20Hz-26,5GHz-150 to + 30 DBM	FSIQ26	R&S	835540/018	300002681	k	30.01.2014	30.01.2016
7	A	USB-GPIB-Interface	82357B	Agilent Technologies	103170	300004852	ne	-/-	-/-
8	A	Power Sensor	NRP-Z81	R&S	100010	300003780	k	08.12.2014	08.12.2016

## 8 Measurement uncertainty

Measurement uncertainty	
Test case	Uncertainty
Antenna gain	± 3 dB
Power spectral density	± 1.5 dB
DTS bandwidth	± 100 kHz (depends on the used RBW)
Occupied bandwidth	± 100 kHz (depends on the used RBW)
Maximum output power	± 1.5 dB
Detailed spurious emissions @ the band edge - conducted	± 1.5 dB
Band edge compliance radiated	± 3 dB
Spurious emissions conducted	± 3 dB
Spurious emissions radiated below 30 MHz	± 3 dB
Spurious emissions radiated 30 MHz to 1 GHz	± 3 dB
Spurious emissions radiated 1 GHz to 12.75 GHz	± 3.7 dB
Spurious emissions radiated above 12.75 GHz	± 4.5 dB
Spurious emissions conducted below 30 MHz (AC conducted)	± 2.6 dB

## 9 Sequence of testing

### 9.1 Sequence of testing radiated spurious 9 kHz to 30 MHz

#### Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

#### Premereasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.5 m.
- At each turntable position the analyzer sweeps with positive-peak detector to find the maximum of all emissions.

#### Final measurement

- Identified emissions during the premeasurement are maximized by the software by rotating the turntable from 0° to 360°. In case of the 2-axis positioner is used the elevation axis is also rotated from 0° to 360°.
- The final measurement is done in the position (turntable and elevation) causing the highest emissions with quasi-peak (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. A plot with the graph of the premeasurement and the limit is stored.

## 9.2 Sequence of testing radiated spurious 30 MHz to 1 GHz

### Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

### Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

### Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position  $\pm 45^\circ$  and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

### 9.3 Sequence of testing radiated spurious 1 GHz to 12.75 GHz

#### Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

#### Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height is 1.5 m.
- At each turntable position and antenna polarization the analyzer sweeps with positive peak detector to find the maximum of all emissions.

#### Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximizes the peaks by rotating the turntable from 0° to 360°. This measurement is repeated for different EUT-table positions (0° to 150° in 30°-steps) and for both antenna polarizations.
- The final measurement is done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

## 9.4 Sequence of testing radiated spurious above 12.75 GHz

### Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet.
- The measurement distance is as appropriate (e.g. 0.5 m).
- The EUT is set into operation.

### Premeasurement

- The test antenna is handheld and moved carefully over the EUT to cover the EUT's whole sphere and different polarizations of the antenna.

### Final measurement

- The final measurement is performed at the position and antenna orientation causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement and the limit is stored.

## 10 Summary of measurement results

<input checked="" type="checkbox"/>	No deviations from the technical specifications were ascertained
<input type="checkbox"/>	There were deviations from the technical specifications ascertained
<input type="checkbox"/>	This test report is only a partial test report. The content and verdict of the performed test cases are listed below.

TC Identifier	Description	Verdict	Date	Remark
RF-Testing	CFR Part 15	See table!	2015-12-04	-/-

Test specification clause	Test case	Guideline	Temperature conditions	Power source voltages	Mode	C	NC	NA	NP	Remark
§15.247(b)(4)	Antenna gain	-/-	Nominal	Nominal	MC	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
§15.247(e)	Power spectral density	KDB 558074 DTS clause: 10.6	Nominal	Nominal	MC	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
§15.247(a)(2)	DTS bandwidth	KDB 558074 DTS clause: 8.1	Nominal	Nominal	MC	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
§15.247(b)(3)	Maximum output power	KDB 558074 DTS clause: 9.2.2.5	Nominal	Nominal	MC	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
§15.205	Band edge compliance radiated	KDB 558074 DTS clause: 13.3.2	Nominal	Nominal	MC	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
§15.247(d)	TX spurious emissions conducted	KDB 558074 DTS clause: 11.1 & 11.2 11.3	Nominal	Nominal	MC	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
§15.209(a)	TX spurious emissions radiated below 30 MHz	-/-	Nominal	Nominal	MC	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
§15.247(d)	TX spurious emissions radiated 30 MHz to 1 GHz	-/-	Nominal	Nominal	MC	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
§15.247(d)	TX spurious emissions radiated above 1 GHz	-/-	Nominal	Nominal	MC	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
§15.109	RX spurious emissions radiated 30 MHz to 1 GHz	-/-	Nominal	Nominal	RX / idle	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
§15.109	RX spurious emissions radiated above 1 GHz	-/-	Nominal	Nominal	RX / idle	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-
§15.107(a) §15.207	Conducted emissions < 30 MHz	-/-	Nominal	Nominal	MC	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-/-

**Note:** C = Complies; NC = Not complies; NA = Not applicable; NP = Not performed; MC = Modulated carrier

## 11 Additional comments

Reference documents: None

Special test descriptions: None

Configuration descriptions: None

Test mode:

No test mode available.  
Iperf was used to ping another device with the largest support packet size

Special software is used.  
EUT is transmitting pseudo random data by itself

Antennas and transmit operating modes:

Operating mode 1 (single antenna)  
- *Equipment with 1 antenna,*  
- *Equipment with 2 diversity antennas operating in switched diversity mode by which at any moment in time only 1 antenna is used,*  
- *Smart antenna system with 2 or more transmit/receive chains, but operating in a mode where only 1 transmit/receive chain is used)*

Operating mode 2 (multiple antennas, no beamforming)  
- *Equipment operating in this mode contains a smart antenna system using two or more transmit/receive chains simultaneously but without beamforming.*

Operating mode 3 (multiple antennas, with beamforming)  
- *Equipment operating in this mode contains a smart antenna system using two or more transmit/receive chains simultaneously with beamforming.  
In addition to the antenna assembly gain (G), the beamforming gain (Y) may have to be taken into account when performing the measurements.*

## 12 Measurement results

### 12.1 Antenna gain

**Measurement:**

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For normal WLAN devices, the DSSS mode is used.

**Measurement parameters:**

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	3 MHz
Video bandwidth:	3 MHz
Trace mode:	Max hold
Test setup:	See sub clause 7.2 A
Measurement uncertainty	See sub clause 8

**Limits:**

FCC	IC
6 dBi	

**Results:**

T <sub>nom</sub>	V <sub>nom</sub>	2405 MHz	2440 MHz	2475 MHz
Conducted power [dBm]		3.0	2.5	1.7
Radiated power [dBm]		9.4	8.7	8.0
Gain [dBi] Calculated		6.4	6.2	6.3

## 12.2 Maximum output power

### Description:

Measurement of the maximum output power conducted and radiated. The measurements are performed using the data rate producing the highest conducted output power.

### Measurement:

Measurement parameter	
According to DTS clause: 9.2.2.5	
Detector:	RMS
Sweep time:	Auto
Resolution bandwidth:	1 – 5 % of the OBW
Video bandwidth:	$\geq 3 \times$ RBW
Span:	Depends on the signal
Integration bandwidth:	99 % power - bandwidth (OBW)
Trace mode:	Max hold (allow trace to fully stabilize)
Measurement function:	Channel power with OBW
Test setup:	See sub clause 7.5 A
Measurement uncertainty	See sub clause 8

### Limits:


FCC	IC
Conducted: 1.0 W – Antenna gain max. 6 dBi	

### Results:

Frequency	Maximum Output Power [dBm]		
	2405 MHz	2440 MHz	2475 MHz
Output power conducted	1.94	1.62	2.15

**Plots:**
**Plot 1: TX mode, lowest channel**

**Plot 2: TX mode, middle channel**


**Plot 3: TX mode, highest channel**

## 12.3 Power spectral density

### Description:

Measurement of the power spectral density of a digital modulated system. The measurement is repeated for both modulations at the lowest, middle and highest channel.

### Measurement:

Measurement parameter	
According to DTS clause: 10.6	
Detector:	RMS
Sweep time:	3s
Resolution bandwidth:	3 kHz
Video bandwidth:	10 kHz
Span:	40 MHz
Trace mode:	Max hold (allow trace to fully stabilize)
Test setup:	See sub clause 7.5 A
Measurement uncertainty	See sub clause 8

### Limits:


FCC	IC
8 dBm / 3kHz (conducted)	

### Results:


Modulation	Power Spectral density [dBm]		
	2405 MHz	2440 MHz	2475 MHz
Frequency			
Power spectral density	-12.06	-13.50	-12.25


**Plots:**

**Plot 1: TX mode, lowest channel**



**Plot 2: TX mode, middle channel**



**Plot 3: TX mode, highest channel**

## 12.4 DTS bandwidth

### Description:

Measurement of the 6 dB bandwidth of the modulated signal.

### Measurement:



Measurement parameter	
According to DTS clause: 8.1	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Span:	40 MHz
Measurement procedure:	Measurement of the 75% bandwidth using the integration function of the analyzer
Trace mode:	Max hold (allow trace to stabilize)
Test setup:	See sub clause 7.5 A
Measurement uncertainty	See sub clause 8

### Limits:

FCC	IC
Systems using digital modulation techniques may operate in the 2400–2483.5 MHz band. The minimum 6 dB bandwidth shall be at least 500 kHz.	

### Results:

Frequency	6 dB bandwidth [kHz]		
	2405 MHz	2440 MHz	2475 MHz
	1560	1660	1610

**Plots:**
**Plot 1: TX mode, lowest channel**

**Plot 2: TX mode, middle channel**


**Plot 3: TX mode, highest channel**

## 12.5 Occupied bandwidth – 99% emission bandwidth

### Description:

Measurement of the 99% bandwidth of the modulated signal acc. RSS-GEN.

### Measurement:



Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	30 kHz
Video bandwidth:	100 kHz
Span:	40 MHz
Measurement procedure:	Measurement of the 99% bandwidth using the integration function of the analyzer
Trace mode:	Max hold (allow trace to stabilize)
Test setup:	See sub clause 7.5 A
Measurement uncertainty	See sub clause 8


### Usage:

-/-	IC
OBW is necessary for Emission Designator	

### Results:

Modulation	99% bandwidth [kHz]		
	2405 MHz	2440 MHz	2475 MHz
	2465	2604	2584

**Plots:**
**Plot 1: TX mode, lowest channel**

**Plot 2: TX mode, middle channel**


**Plot 3: TX mode, highest channel**

## 12.6 Band edge compliance radiated

### Description:

Measurement of the radiated band edge compliance. The EUT is turned in the position that results in the maximum level at the band edge. Then a sweep over the corresponding restricted band is performed. The EUT is set to channel 1 for the lower restricted band and to channel 11 for the upper restricted band. The measurement is repeated for all modulations. Measurement distance is 3 m.

### Measurement:

Measurement parameter for peak measurements	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	1 MHz
Video bandwidth:	1 MHz
Span:	See plot!
Trace mode:	Max Hold
Test setup:	See sub clause 7.2 A
Measurement uncertainty	See sub clause 8



Measurement parameter for average measurements	
According to DTS clause: 13.3.2	
Detector:	RMS
Sweep time:	Auto
Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Span:	2 MHz
Trace mode:	RMS Average over 101 sweeps
Test setup:	See sub clause 7.2 A
Measurement uncertainty	See sub clause 8

### Limits:

FCC	IC
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).	
	74 dB $\mu$ V/m Peak 54 dB $\mu$ V/m AVG

**Results:**

Scenario	Band edge compliance radiated [dB]
Lower band edge	> 20 dB (Peak, blue graph) > 20 dB (AVG, purple graph)
Upper band edge	> 20 dB (Peak, blue graph) > 20 dB (AVG, purple graph)

**Plots:****Plot 1: TX mode, lower band edge, vertical & horizontal polarization****Plot 2: TX mode, upper band edge, vertical & horizontal polarization**

## 12.7 Spurious emissions conducted

### Description:

Measurement of the conducted spurious emissions in transmit mode.

### Measurement:


Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	100 kHz
Video bandwidth:	500 kHz
Span:	9 kHz to 25 GHz
Trace mode:	Max Hold
Test setup:	See sub clause 7.5 A
Measurement uncertainty	See sub clause 8

### Limits:


FCC	IC
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required	

**Results:**


TX Spurious Emissions Conducted					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2405		-3.042	30 dBm		Operating frequency
	No peaks detected. All detected emissions are below the -30 dBc criteria.		-20 dBc (peak) -30 dBc (average)		complies
2440		-3.914	30 dBm		Operating frequency
	No peaks detected. All detected emissions are below the -30 dBc criteria.		-20 dBc (peak) -30 dBc (average)		complies
2475		-3.147	30 dBm		Operating frequency
	No peaks detected. All detected emissions are below the -30 dBc criteria.		-20 dBc (peak) -30 dBc (average)		complies
Measurement uncertainty		± 3 dB			

**Plots:**
**Plot 1: TX mode, lowest channel, up to 25 GHz**


The peak at the beginning of the plot is the LO from the SA.

**Plot 2: TX mode, middle channel, up to 25 GHz**


The peak at the beginning of the plot is the LO from the SA.

**Plot 3: TX mode, highest channel, up to 25 GHz**


The peak at the beginning of the plot is the LO from the SA.

## 12.8 Spurious emissions radiated below 30 MHz

### Description:

Measurement of the radiated spurious emissions in transmit mode below 30 MHz. The EUT is set to channel 6. This measurement is representative for all channels and modes. If peaks are found channel 1 and channel 11 will be measured too. The measurement is performed with the data rate producing the highest output power. The limits are recalculated to a measurement distance of 3 m with 40 dB/decade according CFR Part 2.

### Measurement:



Measurement parameter	
Detector:	Peak / Quasi Peak
Sweep time:	Auto
Resolution bandwidth:	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz
Video bandwidth:	F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz
Span:	9 kHz to 30 MHz
Trace mode:	Max Hold
Test setup:	See sub clause 7.2 A
Measurement uncertainty	See sub clause 8

### Limits:


FCC		IC
Frequency (MHz)	Field Strength (dB $\mu$ V/m)	Measurement distance
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

### Results:

TX Spurious Emissions Radiated < 30 MHz [dB $\mu$ V/m]		
F [MHz]	Detector	Level [dB $\mu$ V/m]
All detected peaks are more than 20 dB below the limit.		

**Plots:****Plot 1: 9 kHz to 30 MHz, low channel****Plot 2: 9 kHz to 30 MHz, mid channel**

**Plot 3: 9 kHz to 30 MHz, high channel**



## 12.9 Spurious emissions radiated 30 MHz to 1 GHz

### Description:

Measurement of the radiated spurious emissions and cabinet radiations below 1 GHz.

### Measurement:

Measurement parameter	
Detector:	Peak / Quasi Peak
Sweep time:	Auto
Resolution bandwidth:	F < 1 GHz: 120 kHz
Video bandwidth:	3 x RBW
Span:	30 MHz to 1 GHz
Trace mode:	Max Hold
Test setup:	See sub clause 7.1 A
Measurement uncertainty	See sub clause 8


The modulation with the highest output power was used to perform the transmitter spurious emissions. If spurious were detected a re-measurement was performed on the detected frequency with each modulation.

### Limits:

FCC	IC												
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).													
<table border="1"> <thead> <tr> <th>Frequency (MHz)</th> <th>Field Strength (dB<math>\mu</math>V/m)</th> <th>Measurement distance</th> </tr> </thead> <tbody> <tr> <td>30 - 88</td> <td>30.0</td> <td>10</td> </tr> <tr> <td>88 - 216</td> <td>33.5</td> <td>10</td> </tr> <tr> <td>216 - 960</td> <td>36.0</td> <td>10</td> </tr> </tbody> </table>		Frequency (MHz)	Field Strength (dB $\mu$ V/m)	Measurement distance	30 - 88	30.0	10	88 - 216	33.5	10	216 - 960	36.0	10
Frequency (MHz)	Field Strength (dB $\mu$ V/m)	Measurement distance											
30 - 88	30.0	10											
88 - 216	33.5	10											
216 - 960	36.0	10											


**Plot:**

**Plot 1:** 30 MHz to 1 GHz, vertical & horizontal polarization, low channel

**Final\_Result:**


Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
31.405350	10.61	30.00	19.39	1000.0	120.000	101.0	V	12	13.5
39.727350	10.46	30.00	19.54	1000.0	120.000	170.0	H	317	14.0
99.778050	20.66	33.50	12.84	1000.0	120.000	170.0	V	265	12.1
232.824600	21.07	36.00	14.93	1000.0	120.000	101.0	V	300	12.8
505.288950	14.96	36.00	21.04	1000.0	120.000	170.0	H	61	18.8
733.531650	19.04	36.00	16.96	1000.0	120.000	170.0	H	227	22.3

**Plot 2:** 30 MHz to 1 GHz, vertical & horizontal polarization, mid channel



#### Final\_Result:


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
99.603000	21.74	33.50	11.76	1000.0	120.000	101.0	V	342	12.1
232.814100	24.94	36.00	11.06	1000.0	120.000	98.0	V	358	12.8
298.744350	22.58	36.00	13.42	1000.0	120.000	98.0	V	116	14.4
726.251700	18.81	36.00	17.19	1000.0	120.000	170.0	V	327	22.1
805.378500	19.44	36.00	16.56	1000.0	120.000	170.0	H	124	22.8
937.220850	20.96	36.00	15.04	1000.0	120.000	170.0	H	116	24.2

**Plot 3:** 30 MHz to 1 GHz, vertical & horizontal polarization, high channel

**Final\_Result:**

Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
99.753000	18.63	33.50	14.87	1000.0	120.000	170.0	V	23	12.1
164.884200	5.91	33.50	27.59	1000.0	120.000	98.0	V	216	9.4
232.797450	26.83	36.00	9.17	1000.0	120.000	98.0	V	30	12.8
298.756650	23.22	36.00	12.78	1000.0	120.000	101.0	V	116	14.4
432.406350	20.07	36.00	15.93	1000.0	120.000	101.0	V	193	17.4
740.250000	19.20	36.00	16.80	1000.0	120.000	170.0	V	239	22.5

**Plot:** RX / Idle mode

**Plot 1:** 30 MHz to 1 GHz, vertical & horizontal polarization



**Final\_Result:**

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
30.458100	10.19	30.00	19.81	1000.0	120.000	170.0	V	39	13.4
99.765750	24.85	33.50	8.65	1000.0	120.000	98.0	V	15	12.1
232.782600	28.77	36.00	7.23	1000.0	120.000	98.0	V	182	12.8
263.979150	18.96	36.00	17.04	1000.0	120.000	98.0	V	23	13.7
298.739850	23.79	36.00	12.21	1000.0	120.000	98.0	V	150	14.4
399.127050	23.81	36.00	12.19	1000.0	120.000	98.0	V	202	16.9

## 12.10 Spurious emissions radiated above 1 GHz

### Description:

Measurement of the radiated spurious emissions above 1 GHz in transmit mode and receiver / idle mode.

### Measurement:

Measurement parameter	
Detector:	Peak / RMS
Sweep time:	Auto
Resolution bandwidth:	$F > 1 \text{ GHz}$ : 1 MHz
Video bandwidth:	3 x RBW
Span:	1 GHz to 26 GHz
Trace mode:	Max Hold
Test setup:	See sub clause 7.2 A / 7.3 A
Measurement uncertainty	See sub clause 8

### Limits:


FCC	IC	
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).		
Frequency (MHz)	Field Strength (dB $\mu$ V/m)	Measurement distance
Above 960	54.0	3

**Results:**

TX Spurious Emissions Radiated [dB $\mu$ V/m]								
2405 MHz			2440 MHz			2475 MHz		
F [MHz]	Detector	Level [dB $\mu$ V/m]	F [MHz]	Detector	Level [dB $\mu$ V/m]	F [MHz]	Detector	Level [dB $\mu$ V/m]
All detected emissions are more than 20 dB below the limit.			All detected emissions are more than 20 dB below the limit.			All detected emissions are more than 20 dB below the limit.		
	Peak			Peak			Peak	
	AVG			AVG			AVG	
	Peak			Peak			Peak	
	AVG			AVG			AVG	


**Plots:**

**Plot 1:** Lowest channel, 1 GHz to 12.75 GHz, vertical & horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.


**Plot 2:** Lowest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



**Plot 3: Lowest channel, 18 GHz to 26 GHz, vertical & horizontal polarization**




**Plot 4:** Middle channel, 1 GHz to 12.75 GHz, vertical & horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.


**Plot 5:** Middle channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



**Plot 6:** Middle channel, 18 GHz to 26 GHz, vertical & horizontal polarization




**Plot 7:** Highest channel, 1 GHz to 12.75 GHz, vertical & horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

**Plot 8:** Highest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



Date: 30.NOV.2015 14:01:43

**Plot 9:** Highest channel, 18 GHz to 26 GHz, vertical & horizontal polarization

## 12.11 Spurious emissions conducted below 30 MHz (AC conducted)

### Description:

Measurement of the conducted spurious emissions in transmit mode below 30 MHz. The EUT is set to channel 6. This measurement is repeated for DSSS and OFDM modulation. If peaks are found channel 1 and channel 11 will be measured too. The measurement is performed with the data rate producing the highest output power. Both power lines, phase and neutral line, are measured. Found peaks are remeasured with average and quasi peak detection to show compliance to the limits.

### Measurement:

Measurement parameter	
Detector:	Peak - Quasi Peak / Average
Sweep time:	Auto
Resolution bandwidth:	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz
Video bandwidth:	F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz
Span:	9 kHz to 30 MHz
Trace mode:	Max Hold
Test setup:	See sub clause 7.4 A
Measurement uncertainty	See sub clause 8

### Limits:

FCC		IC
Frequency (MHz)	Quasi-Peak (dB $\mu$ V/m)	Average (dB $\mu$ V/m)
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30.0	60	50


\*Decreases with the logarithm of the frequency

### Results:


TX Spurious Emissions Conducted < 30 MHz [dB $\mu$ V/m]		
F [MHz]	Detector	Level [dB $\mu$ V/m]
All detected peaks are more than 20 dB below the limit.		

**Plots:**

**Plot 1:** 150 kHz to 30 MHz, phase line



Frequency	Quasi peak level	Margin quasi peak	Average level	Margin average
MHz	dB $\mu$ V	dB $\mu$ V	dB $\mu$ V	dB $\mu$ V
0.24969	28.50	33.26	-3.07	56.22
0.29151	3.41	57.08	15.36	36.60
0.49287	34.63	21.49	20.16	26.05
0.52046	33.62	22.38	19.03	26.97

**Plot 2:** 150 kHz to 30 MHz, neutral line

Frequency	Quasi peak level	Margin quasi peak	Average level	Margin average
MHz	dB $\mu$ V	dB $\mu$ V	dB $\mu$ V	dB $\mu$ V
0.51893	30.18	25.82	6.93	39.07
0.51972	30.19	25.81	7.00	39.00

## 13 Observations

No observations except those reported with the single test cases have been made.

## Annex A Document history

Version	Applied changes	Date of release
	Initial release	2015-12-04

## Annex B Further information

### Glossary

AVG	- Average
DUT	- Device under test
EMC	- Electromagnetic Compatibility
EN	- European Standard
EUT	- Equipment under test
ETSI	- European Telecommunications Standard Institute
FCC	- Federal Communication Commission
FCC ID	- Company Identifier at FCC
HW	- Hardware
IC	- Industry Canada
Inv. No.	- Inventory number
N/A	- Not applicable
PP	- Positive peak
QP	- Quasi peak
S/N	- Serial number
SW	- Software
PMN	Product marketing name
HMN	Host marketing name
HVIN	Hardware version identification number
FVIN	Firmware version identification number

## Annex C Accreditation Certificate

Front side of certificate

Back side of certificate



Deutsche Akkreditierungsstelle GmbH

Befähigte gemäß § 8 Absatz 1 AkkStelleG i.V.m. § 1 Absatz 1 AkkStelleGBV  
Unterzeichnerin der Multilateralen Abkommen  
von EA, ILAC und IAF zur gegenseitigen Anerkennung

**Akkreditierung** 

Die Deutsche Akkreditierungsstelle GmbH bestätigt hiermit, dass das Prüflaboratorium

CETECOM ICT Services GmbH  
Untertürkheimer Straße 6-10, 66117 Saarbrücken

die Kompetenz nach DIN EN ISO/IEC 17025:2005 besitzt, Prüfungen in folgenden Bereichen  
durchzuführen:

Drahtgebundene Kommunikation einschließlich xDSL  
VoIP und DECT  
Akustik  
Funk einschließlich WLAN  
Short Range Devices (SRD)  
RFID  
WiMax und Richtfunk  
Mobilfunk (GSM / DCS, Over the Air (OTA) Performance)  
Elektromagnetische Verträglichkeit (EMV) einschließlich Automotive  
Produktsicherheit  
SAR und Hearing Aid Compatibility (HAC)  
Universal Communication  
Smart Card Terminals  
Bluetooth®  
Wi-Fi®-Services

Die Akkreditierungsurkunde gilt nur in Verbindung mit dem Beischeld vom 07.03.2014 mit der  
Akkreditierungsnr. D-PL-12076-01 und ist gültig 17.01.2018. Sie besteht aus diesem Dokument, der  
Rückseite des Dokuments und der folgenden Anlage mit insgesamt 77 Seiten.

Requisezurnummer der Urkunde: D-PL-12076-01-00

Deutsche Akkreditierungsstelle GmbH

Standort Berlin  
Spittelmarkt 10  
10117 Berlin

Standort Frankfurt am Main  
Gartenstraße 6  
60594 Frankfurt am Main

Standort: Braunschweig  
Bundesallee 100  
38115 Braunschweig

Die auszugsweise Veröffentlichung der Akkreditierungsurkunde kommt der vorherigen schriftlichen  
Zusammen mit der Deutsche Akkreditierungsstelle GmbH (DAkkS). Ausgenommen davon ist die separate  
Websveröffentlichung des Dokuments durch die umseitig genannte Konformitätsbewertungsstelle in  
unveränderter Form.

Es darf nicht der Anschein erweckt werden, dass sich die Akkreditierung auch auf Bereiche erstreckt,  
die über den durch die DAkkS bestätigten Akkreditierungsbereich hinausgehen.

Die Akkreditierung erfolgte gemäß den Gesetzen über die Akkreditierungsstelle (AkkStelleG) vom  
31. Juli 2008 (BGBl. I S. 2620) sowie der Verordnung (EG) Nr. 765/2008 des Europäischen Parlaments  
und des Rates vom 9. Juli 2008 über die Verordnung für die Akkreditierung und Marktbarearbeitung  
im Zusammenhang mit der Vermarktung von Produkten (AAL L 238 vom 9. Juli 2008 S. 30).

Die DAkkS ist Unterzeichnerin der Multilateralen Abkommen zur gegenseitigen Anerkennung der  
European co-operation for Accreditation (EA), des International Accreditation Forum (IAF) und  
der International Laboratory Accreditation Cooperation (ILAC). Die Unterzeichner dieser Abkommen  
erkennen ihre Akkreditierungen gegenseitig an.

Der aktuelle Stand der Mitgliedschaft kann folgenden Webseiten entnommen werden:  
EA: [www.european-accreditation.org](http://www.european-accreditation.org)  
ILAC: [www.ilac.org](http://www.ilac.org)  
IAF: [www.iaf.nu](http://www.iaf.nu)

Frankfurt am Main, 07.03.2014

In Auftrag gegeben von Ralf Egner

Akkreditierungsleiter

### Note:

The current certificate including annex is published on our website (see link below) or may be received from CETECOM ICT Services on request.

<https://www.cetecom.com/en/cetecom-group/europe/germany-saarbruecken/accreditations.html>