



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 15.247

RSS-GEN, ISSUE 5, AMENDMENT 1, MARCH 2019

RSS-247, ISSUE 2, FEBRUARY 2017

TEST REPORT

For

Autel Robotics Co., Ltd.

9th Floor, Bldg.B1, Zhiyuan, 1001 Xueyuan Rd. Xili, Nanshan, Shenzhen, China

FCC ID: 2AGNTEF9RC2409A

IC: 20910-EF9RC2409A

Report Type: Original Report	Product Name: Autel Smart Controller
Report Number: RSZ201027002-00B	
Report Date: 2021-04-28	
Reviewed By:	Ivan Cao Assistant Manager 
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.12, Pulong East 1 st Road, Tangxia Town, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
DECLARATIONS.....	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE	8
EQUIPMENT MODIFICATIONS	11
BLOCK DIAGRAM OF TEST SETUP	11
SUMMARY OF TEST RESULTS	12
FCC §15.247 (i) & §1.1310 & §2.1093, RSS-102 CLAUSE 4- RF Exposure.....	13
APPLICABLE STANDARD	13
FCC §15.203& RSS-GEN CLAUSE 6.8 - ANTENNA REQUIREMENT	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	16
APPLICABLE STANDARD	16
EUT SETUP.....	16
EMI TEST RECEIVER SETUP.....	16
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST DATA	18
FCC §15.209, §15.205 & §15.247(d), RSS-247 CLAUSE 5.5, RSS-GEN CLAUSE 8.10 - SPURIOUS EMISSIONS.....	20
APPLICABLE STANDARD	20
EUT SETUP.....	20
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	21
TEST PROCEDURE	21
CORRECTED AMPLITUDE & MARGIN CALCULATION	21
TEST EQUIPMENT LIST AND DETAILS.....	22
TEST DATA	22
FCC §15.247(a) (2), RSS-247 CLAUSE 5.2 a) &RSS-GEN CLAUSE 6.7–6 dB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....	32
APPLICABLE STANDARD	32
TEST PROCEDURE	33
TEST EQUIPMENT LIST AND DETAILS.....	33
TEST DATA	33
FCC §15.247(b) (3) , RSS-247 CLAUSE 5.4 D - MAXIMUM PEAK CONDUCTED OUTPUT POWER	47
APPLICABLE STANDARD	47
TEST PROCEDURE	47

TEST EQUIPMENT LIST AND DETAILS.....	48
TEST DATA	48
FCC §15.247(d), RSS-247 CLAUSE 5.5 – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE	49
APPLICABLE STANDARD	49
TEST PROCEDURE	49
TEST EQUIPMENT LIST AND DETAILS.....	50
TEST DATA	50
FCC §15.247(e), RSS-247 CLAUSE 5.2 B - POWER SPECTRAL DENSITY	55
APPLICABLE STANDARD	55
TEST PROCEDURE	55
TEST EQUIPMENT LIST AND DETAILS.....	55
TEST DATA	56

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:		Autel Smart Controller
EUT Model:		EF9-1
Operation Frequency:		2.4GHz Band 1.4M:2403.5-2473.5MHz 2.4GHz Band 10M:2407.5-2471.5MHz 900MHz Band 1.4M:906-924MHz 900MHz Band 10M:909-921MHz
Maximum Peak Output Power (Conducted):		2.4GHz Band 1.4M: 20.59 dBm 2.4GHz Band 10M: 20.63 dBm 900MHz Band 1.4M: 21.76 dBm 900MHz Band 10M: 22.08 dBm
Modulation Type:		OFDM
Rated Input Voltage:		DC 11.55V from internal battery
Adapter Information:	Model:	GaN-001
	Input:	100-240VAC~50/60Hz 1.5A
	Output:	USB-C1/C2:5V=3A,9V=3A,12V=3A,15V=3A,20V=3.25A USB-A:3.4-5.5V=5A,5V=3A,9V=3A,12V=3A,20V=3A
Serial Number:		RSZ201027002-RF -S4
EUT Received Date:		2020.10.27
EUT Received Status:		Good

Objective

This report is prepared on behalf of **Autel Robotics Co., Ltd.** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules, RSS-247, Issue 2, February 2017, RSS-Gen Issue 5, Amendment 1, March 2019 of the Innovation, Science and Economic Development Canada.

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.209 and 15.247 rules, RSS-247, Issue 2, February 2017, RSS-Gen Issue 5, Amendment 1, March 2019 of the Innovation, Science and Economic Development Canada.

Related Submittal(s)/Grant(s)

FCC Part 15C DTS, 15E NII submissions with FCC ID: 2AGNTEF9RC2409A
RSS-247 DTSs, LE-LAN submissions with IC: 20910-EF9RC2409A

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And 558074 D01 15.247 Meas Guidance v05r02, RSS-247, Issue 2, February 2017, RSS-Gen Issue 5, Amendment 1, March 2019 of the Innovation, Science and Economic Development Canada.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “△”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

The EUT has 2 antennas for SRD, and supports 1T2R mode for 900MHz band and 2.4GHz band, only Chain 0 was Tx chain. The device supports SRD 1.4MHz/10MHz modes in both 900 MHz band and 2.4GHz band.

For 900MHz band 1.4MHz mode, the system employs 19 channels as below:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	906	11	916
2	907	12	917
...	...	...	...
...	...	18	923
9	914	19	924
10	915	/	/

3 channels were tested: 906MHz, 915MHz and 924MHz

For 900MHz band 10MHz mode, the system employs 13 channels as below:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	909	8	916
2	910	9	917
3	911	10	918
4	912	11	919
5	913	12	920
6	914	13	921
7	915	/	/

3 channels were tested: 909MHz, 915MHz and 921MHz.

For 2.4GHz band 1.4MHz mode, the system employs 71 channels as below:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2403.5	37	2439.5
2	2404.5	38	2440.5
...	...	...	...
...	...	70	2472.5
35	2437.5	71	2473.5
36	2438.5	/	/

3 channels were tested: 2403.5MHz, 2439.5MHz and 2473.5MHz

For 2.4GHz band 10MHz mode, the system employs 65 channels as below:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2407.5	34	2440.5
2	2408.5	35	2441.5
...	...	...	...
...	...	...	...
...	...	64	2470.5
32	2438.5	65	2471.5
33	2439.5	/	/

3 channels were tested: 2407.5 MHz, 2439.5 MHz and 2471.5 MHz.

EUT Exercise Software

Software " SecureCRT " was used during test, the maximum power was configured as below, which was provided by manufacturer ^Δ :

Mode	Channel	Frequency (MHz)	Power level Setting
2.4G 1.4M	Low	2403.5	Default
	Middle	2439.5	Default
	High	2473.5	Default
2.4G 10M	Low	2407.5	Default
	Middle	2439.5	Default
	High	2471.5	Default
900M 1.4M	Low	906	Default
	Middle	915	Default
	High	924	Default
900M 10M	Low	909	Default
	Middle	915	Default
	High	921	Default

The maximum duty cycle as following table:

Test mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
2.4G 1.4M	3.000	4.040	74.26
2.4G 10M	4.040	5.000	80.8
900MHz 1.4M	4.036	5.033	80.19
900MHz 10M	4.017	5.014	80.12

Date: 28.OCT.2020 23:29:20

Ref 30 dBm * Att 40 dB RBW 10 MHz Delta 2 [T1] -0.16 dB
 * VBW 10 MHz SWT 20 ms 5.000000 ms

30 Offset 0.5 dB


Marker 1 [T1] -43.86 dBm
 Delta 1 [T1] -0.36 dB
 5.000000 ms

1 RM
CLRWR

Center 2.4395 GHz 2 ms/


Date: 28.OCT.2020 23:28:05

900MHz 1.4M



Date: 10.NOV.2020 04:43:56

900MHz 10M



Date: 10.NOV.2020 04:42:58

Equipment Modifications

No modification was made to the EUT.


Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	Monitor	U3011t	CN-OPH5NY-74445-16T-290L
Unknown	Resistive load	1ohm	1ohm-1
Unknown	Resistive load	1ohm	1ohm-2

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB-C Cable	Yes	No	1.2	Adapter	EUT
HDMI Cable	Yes	Yes	1.5	EUT	Monitor
USB-A Cable*2	Yes	No	0.2	Adapter	Resistive Load

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i) & §1.1310 & §2.1093 RSS-102 Clause 4	RF Exposure	Compliance
FCC §15.203, RSS-GEN Clause 6.8	Antenna Requirement	Compliance
FCC §15.207 (a); RSS-Gen Clause 8.8	AC Line Conducted Emissions	Compliance
FCC §15.205, §15.209, §15.247(d); RSS-247 Clause 5.5 RSS-Gen Clause 8.10	Spurious Emissions	Compliance
FCC §15.247 (a)(2); RSS-247 Clause 5.2 a) RSS-Gen Clause 6.7	6 dB Bandwidth and 99% Occupied Bandwidth	Compliance
FCC §15.247(b)(3); RSS-247 Clause 5.4 d)	Maximum Conducted Output Power	Compliance
FCC §15.247(d); RSS-247 Clause 5.5	100 kHz Bandwidth of Frequency Band Edge	Compliance
FCC §15.247(e) RSS-247 Clause 5.2 b)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093, RSS-102 CLAUSE 4- RF Exposure**Applicable Standard**

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to RSS-102 Clause 4 Table 3, SAR limits for device used by the general public.

Body Region	Average SAR (W/Kg)	Averaging Time (minutes)	Mass Average (g)
Whole Body	0.08	6	Whole Body
Localized Head, Neck and Trunk	1.6	6	1
Localized Limbs	4	6	10

Test Result

Compliance, Please refer to the SAR report: RSZ201027002-20.

FCC §15.203& RSS-GEN CLAUSE 6.8 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC§ 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

According to RSS-Gen §6.8, The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer. The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

Antenna Connector Construction

The EUT has two internal antennas for Wi-Fi 0, two internal antennas for Wi-Fi 1, two external antennas permanently attached to the unit for SRD, all of them fulfill the requirement of this section. Please refer to the EUT photos.

Usage	Antenna Chain	Antenna Type	input impedance (Ohm)	Antenna Gain ^Δ /Frequency Range
Wi-Fi 0	0	FPC	50	2.1 dBi/2.4~2.5GHz 3.5 dBi/5.15~5.85GHz
	1	FPC	50	2.1 dBi/2.4~2.5GHz 4.1dBi/5.15~5.85GHz
Wi-Fi 1	0	FPC	50	4.4 dBi/5.15~5.85GHz
	1	FPC	50	4.5 dBi/5.15~5.85GHz
SRD	0	PCB	50	2.2 dBi/902-928 MHz 1.3 dBi/2.4~2.5GHz 4.0 dBi/5.15~5.85GHz
	1	PCB	50	2.2 dBi/902-928 MHz 1.3 dBi/2.4~2.5GHz 4.0 dBi/5.15~5.85GHz


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a).

EUT Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main LISN with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase ("hot") line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The "**Margin**" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV 216	101614	2020-09-12	2021-09-12
R&S	EMI Test Receiver	ESCI	101121	2020-07-07	2021-07-07
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2020-09-05	2021-09-05
R&S	Test Software	EMC32	Version 9.10.00	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data

Environmental Conditions

Temperature:	25.1℃
Relative Humidity:	60%
ATM Pressure:	101.21kPa
Tester:	Walker Chen
Test Date:	2021-04-21


Test Mode: Transmitting(2.4G 1.4MHz mode middle channel is the worst)

AC120 V, 60 Hz, Line:



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.169919	---	36.78	54.96	18.18	9.000	L1	9.6
0.174210	42.86	---	64.76	21.90	9.000	L1	9.6
0.373663	47.47	---	58.42	10.95	9.000	L1	9.6
0.385014	---	39.40	48.17	8.77	9.000	L1	9.6
0.511614	48.02	---	56.00	7.98	9.000	L1	9.6
0.514172	---	39.92	46.00	6.08	9.000	L1	9.6
0.777842	39.37	---	56.00	16.63	9.000	L1	9.7
1.159249	---	37.06	46.00	8.94	9.000	L1	9.7
1.306658	38.78	---	56.00	17.22	9.000	L1	9.7
1.306658	---	36.57	46.00	9.43	9.000	L1	9.7
3.190708	---	27.56	46.00	18.44	9.000	L1	9.7
3.190708	31.55	---	56.00	24.45	9.000	L1	9.7

AC120 V, 60 Hz, Neutral:**Final Result**

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.173343	---	39.19	54.80	15.61	9.000	N	9.6
0.253237	41.42	---	61.65	20.23	9.000	N	9.6
0.341579	---	41.93	49.16	7.23	9.000	N	9.6
0.371804	49.39	---	58.46	9.07	9.000	N	9.6
0.511614	48.43	---	56.00	7.57	9.000	N	9.6
0.519327	---	40.58	46.00	5.42	9.000	N	9.6
0.770122	40.63	---	56.00	15.37	9.000	N	9.6
1.159249	---	37.16	46.00	8.84	9.000	N	9.6
1.306658	39.14	---	56.00	16.86	9.000	N	9.6
1.306658	---	36.58	46.00	9.42	9.000	N	9.6
2.173203	29.14	---	56.00	26.86	9.000	N	9.6
3.190708	---	27.20	46.00	18.80	9.000	N	9.6


FCC §15.209, §15.205 & §15.247(d), RSS-247 CLAUSE 5.5, RSS-GEN CLAUSE 8.10 - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205; RSS-247 §5.5, RSS-GEN §8.10.

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission Below 1GHz tests were performed in the 3 meters chamber A, above 1GHz tests were performed in the 3 meters chamber B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247 and RSS-247, RSS-Gen limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiation Below 1GHz					
Sunol Sciences	Antenna	JB3	A060611-1	2020-11-10	2023-11-10
R&S	EMI Test Receiver	ESR3	102453	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2020-05-06	2021-05-06
HP	Amplifier	8447D	2727A05902	2020-09-05	2021-09-05
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Radiation Above 1GHz					
TDK RF	Horn Antenna	HRN-0118	130 084	2018-10-12	2021-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2020-12-05	2023-12-04
R&S	Spectrum Analyzer	FSP 38	100478	2020-07-07	2021-07-07
HUBER+SUHNER	Coaxial Cable	SUCOFLEX 126EA	MY369/26/26E A	2020-09-25	2021-09-25
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-02	2020-09-05	2021-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2020-06-27	2021-06-27
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
E-Microwave	Band-stop Filters	OBSF-2400-2483.5-S	OE01601525	2020-06-16	2021-06-16
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2020-06-16	2021-06-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Test Items	Radiation Below 1GHz	Radiation Above 1GHz
Temperature:	25.8°C	26.8°C
Relative Humidity:	51%	47%
ATM Pressure:	101.3kPa	101.2 kPa
Tester:	Joker Chen	Lee Li
Test Date:	2021-04-20	2021-04-21

Test Result: Compliance, please Refer to the following data


Test Mode: Transmitting

1) 30MHz-1GHz(2.4G 1.4M mode middle channel was the worst)

Horizontal:



Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
51.3400	44.35	peak	-11.79	32.56	40.00	7.44
148.3400	41.28	QP	-6.22	35.06	43.50	8.44
424.7900	33.79	peak	-1.52	32.27	46.00	13.73
742.9500	35.10	peak	2.92	38.02	46.00	7.98
827.3400	34.37	peak	4.38	38.75	46.00	7.25
891.3600	37.75	peak	-0.88	36.87	46.00	9.13

Vertical:




Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
31.9400	35.70	QP	0.01	35.71	40.00	4.29
47.4600	45.32	QP	-10.56	34.76	40.00	5.24
150.2800	41.41	peak	-6.17	35.24	43.50	8.26
426.7300	35.90	peak	-1.49	34.41	46.00	11.59
594.5400	36.36	peak	0.67	37.03	46.00	8.97
742.9500	34.24	peak	2.92	37.16	46.00	8.84

**2) 1-25GHz:
2.4GHz band
1.4M mode:**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2403.5 MHz									
2403.50	81.56	PK	H	24.83	2.50	0.00	108.89	N/A	N/A
2403.50	72.24	AV	H	24.83	2.50	0.00	99.57	N/A	N/A
2403.50	94.45	PK	V	24.83	2.50	0.00	121.78	N/A	N/A
2403.50	83.62	AV	V	24.83	2.50	0.00	110.95	N/A	N/A
2390.00	36.79	PK	V	24.80	2.50	0.00	64.09	74.00	9.91
2390.00	14.52	AV	V	24.80	2.50	0.00	41.82	54.00	12.18
4807.00	42.99	PK	V	29.71	3.59	27.37	48.92	74.00	25.08
4807.00	30.59	AV	V	29.71	3.59	27.37	36.52	54.00	17.48
7210.50	35.83	PK	V	33.94	4.68	27.19	47.26	74.00	26.74
7210.50	23.46	AV	V	33.94	4.68	27.19	34.89	54.00	19.11
Middle Channel: 2439.5 MHz									
2439.50	85.16	PK	H	24.89	2.51	0.00	112.56	N/A	N/A
2439.50	76.47	AV	H	24.89	2.51	0.00	103.87	N/A	N/A
2439.50	93.96	PK	V	24.89	2.51	0.00	121.36	N/A	N/A
2439.50	84.05	AV	V	24.89	2.51	0.00	111.45	N/A	N/A
4879.00	47.53	PK	V	29.86	3.58	27.55	53.42	74.00	20.58
4879.00	35.78	AV	V	29.86	3.58	27.55	41.67	54.00	12.33
7318.50	34.41	PK	V	34.11	4.64	27.27	45.89	74.00	28.11
7318.50	22.78	AV	V	34.11	4.64	27.27	34.26	54.00	19.74
High Channel: 2473.5 MHz									
2473.50	85.42	PK	H	24.95	2.52	0.00	112.89	N/A	N/A
2473.50	75.26	AV	H	24.95	2.52	0.00	102.73	N/A	N/A
2473.50	93.28	PK	V	24.95	2.52	0.00	120.75	N/A	N/A
2473.50	83.14	AV	V	24.95	2.52	0.00	110.61	N/A	N/A
2483.50	35.14	PK	V	24.97	2.53	0.00	62.64	74.00	11.36
2483.50	14.86	AV	V	24.97	2.53	0.00	42.36	54.00	11.64
4947.00	46.03	PK	V	29.99	3.59	27.42	52.19	74.00	21.81
4947.00	36.47	AV	V	29.99	3.59	27.42	42.63	54.00	11.37
7420.50	35.93	PK	V	34.27	4.61	27.19	47.62	74.00	26.38
7420.50	23.78	AV	V	34.27	4.61	27.19	35.47	54.00	18.53




10M mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2407.5 MHz									
2407.50	76.89	PK	H	24.83	2.50	0.00	104.22	N/A	N/A
2407.50	62.41	AV	H	24.83	2.50	0.00	89.74	N/A	N/A
2407.50	91.33	PK	V	24.83	2.50	0.00	118.66	N/A	N/A
2407.50	77.18	AV	V	24.83	2.50	0.00	104.51	N/A	N/A
2390.00	36.74	PK	V	24.80	2.50	0.00	64.04	74.00	9.96
2390.00	20.69	AV	V	24.80	2.50	0.00	47.99	54.00	6.01
4815.00	36.72	PK	V	29.73	3.59	27.39	42.65	74.00	31.35
4815.00	24.56	AV	V	29.73	3.59	27.39	30.49	54.00	23.51
7222.50	35.11	PK	V	33.96	4.67	27.20	46.54	74.00	27.46
7222.50	23.02	AV	V	33.96	4.67	27.20	34.45	54.00	19.55
Middle Channel: 2439.5MHz									
2439.50	77.97	PK	H	24.89	2.51	0.00	105.37	N/A	N/A
2439.50	65.41	AV	H	24.89	2.51	0.00	92.81	N/A	N/A
2439.50	89.90	PK	V	24.89	2.51	0.00	117.30	N/A	N/A
2439.50	76.05	AV	V	24.89	2.51	0.00	103.45	N/A	N/A
4879.00	38.44	PK	V	29.86	3.58	27.55	44.33	74.00	29.67
4879.00	26.41	AV	V	29.86	3.58	27.55	32.30	54.00	21.70
7318.50	34.74	PK	V	34.11	4.64	27.27	46.22	74.00	27.78
7318.50	22.15	AV	V	34.11	4.64	27.27	33.63	54.00	20.37
High Channel: 2471.5 MHz									
2471.50	80.25	PK	H	24.95	2.52	0.00	107.72	N/A	N/A
2471.50	66.55	AV	H	24.95	2.52	0.00	94.02	N/A	N/A
2471.50	89.09	PK	V	24.95	2.52	0.00	116.56	N/A	N/A
2471.50	75.85	AV	V	24.95	2.52	0.00	103.32	N/A	N/A
2483.50	44.66	PK	V	24.97	2.53	0.00	72.16	74.00	1.84
2483.50	25.19	AV	V	24.97	2.53	0.00	52.69	54.00	1.31
4943.00	39.41	PK	V	29.99	3.59	27.43	45.56	74.00	28.44
4943.00	26.78	AV	V	29.99	3.59	27.43	32.93	54.00	21.07
7414.50	35.66	PK	V	34.26	4.62	27.18	47.36	74.00	26.64
7414.50	23.57	AV	V	34.26	4.62	27.18	35.27	54.00	18.73

Test plots(1.4M high channel was the worst)**Horizontal:**

Vertical:

Fundamental
Test with Band
Rejection Filter



900MHz Band:**Bandedge and 1-10GHz:
1.4M mode:**


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel:906 MHz									
906.00	73.36	QP	H	22.40	3.16	0.00	98.92	N/A	N/A
906.00	80.60	QP	V	22.40	3.16	0.00	106.16	N/A	N/A
902.00	15.55	QP	V	22.34	3.12	0.00	41.01	86.16	45.15
1812.00	57.68	PK	V	24.10	2.85	27.82	56.81	86.16	29.35
2718.00	56.87	PK	V	25.31	2.70	27.88	57.00	74.00	17.00
2718.00	45.28	AV	V	25.31	2.70	27.88	45.41	54.00	8.59
3624.00	42.08	PK	V	27.45	3.11	26.71	45.93	74.00	28.07
3624.00	33.83	AV	V	27.45	3.11	26.71	37.68	54.00	16.32
4530.00	35.52	PK	V	29.16	3.40	27.54	40.54	74.00	33.46
4530.00	23.47	AV	V	29.16	3.40	27.54	28.49	54.00	25.51
5436.00	35.13	PK	V	30.97	3.93	26.77	43.26	74.00	30.74
5436.00	23.01	AV	V	30.97	3.93	26.77	31.14	54.00	22.86
Middle Channel: 915 MHz									
915.00	74.29	QP	H	22.40	3.17	0.00	99.86	N/A	N/A
915.00	81.71	QP	V	22.40	3.17	0.00	107.28	N/A	N/A
1830.00	57.49	PK	V	24.10	2.69	27.83	56.45	87.28	30.83
2745.00	58.03	PK	V	25.34	2.72	27.88	58.21	74.00	15.79
2745.00	46.81	AV	V	25.34	2.72	27.88	46.99	54.00	7.01
3660.00	37.12	PK	V	27.52	3.17	26.75	41.06	74.00	32.94
3660.00	25.47	AV	V	27.52	3.17	26.75	29.41	54.00	24.59
4575.00	35.48	PK	V	29.25	3.40	27.42	40.71	74.00	33.29
4575.00	23.58	AV	V	29.25	3.40	27.42	28.81	54.00	25.19
High Channel: 924 MHz									
924.00	74.81	QP	H	22.48	3.22	0.00	100.51	N/A	N/A
924.00	82.10	QP	V	22.48	3.22	0.00	107.80	N/A	N/A
928.00	15.60	QP	V	22.56	3.21	0.00	41.37	87.80	46.43
1848.00	52.17	PK	V	24.10	2.53	27.83	50.97	87.80	36.83
2772.00	53.47	PK	V	25.38	2.74	27.89	53.70	74.00	20.30
2772.00	42.07	AV	V	25.38	2.74	27.89	42.30	54.00	11.70
3696.00	42.26	PK	V	27.59	3.23	26.79	46.29	74.00	27.71
3696.00	30.45	AV	V	27.59	3.23	26.79	34.48	54.00	19.52
4620.00	35.15	PK	V	29.34	3.44	27.40	40.53	74.00	33.47
4620.00	23.36	AV	V	29.34	3.44	27.40	28.74	54.00	25.26
5544.00	34.62	PK	V	31.16	3.77	26.59	42.96	87.8	44.84
6468.00	35.42	PK	V	32.83	4.16	26.60	45.81	87.8	41.99

10M mode:


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 909 MHz									
909.00	67.53	QP	H	22.40	3.18	0.00	93.11	N/A	N/A
909.00	74.50	QP	V	22.40	3.18	0.00	100.08	N/A	N/A
902.00	36.20	QP	V	22.34	3.12	0.00	61.66	80.08	18.42
1818.00	51.76	PK	V	24.10	2.79	27.82	50.83	80.08	29.25
2727.00	51.52	PK	V	25.32	2.70	27.88	51.66	74.00	22.34
2727.00	38.66	AV	V	25.32	2.70	27.88	38.80	54.00	15.20
3636.00	35.98	PK	V	27.47	3.13	26.73	39.85	74.00	34.15
3636.00	23.46	AV	V	27.47	3.13	26.73	27.33	54.00	26.67
4545.00	35.44	PK	V	29.19	3.40	27.50	40.53	74.00	33.47
4545.00	23.48	AV	V	29.19	3.40	27.50	28.57	54.00	25.43
5454.00	34.43	PK	V	31.01	3.90	26.73	42.61	74.00	31.39
5454.00	22.74	AV	V	31.01	3.90	26.73	30.92	54.00	23.08
Middle Channel: 915MHz									
915.00	68.50	QP	H	22.40	3.17	0.00	94.07	N/A	N/A
915.00	75.62	QP	V	22.40	3.17	0.00	101.19	N/A	N/A
1830.00	52.25	PK	V	24.10	2.69	27.83	51.21	81.19	29.98
2745.00	48.64	PK	V	25.34	2.72	27.88	48.82	74.00	25.18
2745.00	39.81	AV	V	25.34	2.72	27.88	39.99	54.00	14.01
3660.00	36.41	PK	V	27.52	3.17	26.75	40.35	74.00	33.65
3660.00	24.78	AV	V	27.52	3.17	26.75	28.72	54.00	25.28
4575.00	35.17	PK	V	29.25	3.40	27.42	40.40	74.00	33.60
4575.00	23.46	AV	V	29.25	3.40	27.42	28.69	54.00	25.31
5490.00	35.26	PK	V	31.08	3.82	26.67	43.49	81.19	37.7
High Channel: 921 MHz									
921.00	68.60	QP	H	22.42	3.23	0.00	94.25	N/A	N/A
921.00	75.80	QP	V	22.42	3.23	0.00	101.45	N/A	N/A
928.00	41.40	QP	V	22.56	3.21	0.00	67.17	81.45	14.28
1842.00	49.45	PK	V	24.10	2.58	27.83	48.30	81.45	33.15
2763.00	48.93	PK	V	25.37	2.74	27.89	49.15	74.00	24.85
2763.00	35.62	AV	V	25.37	2.74	27.89	35.84	54.00	18.16
3684.00	38.32	PK	V	27.57	3.21	26.77	42.33	74.00	31.67
3684.00	26.45	AV	V	27.57	3.21	26.77	30.46	54.00	23.54
4605.00	37.04	PK	V	29.31	3.40	27.37	42.38	74.00	31.62
4605.00	25.14	AV	V	29.31	3.40	27.37	30.48	54.00	23.52
5526.00	35.17	PK	V	31.14	3.78	26.62	43.47	81.45	37.98

Worst Plots(1.4MHz mode, Low Channel):

Horizontal:



Vertical:



FCC §15.247(a) (2), RSS-247 CLAUSE 5.2 a) & RSS-GEN CLAUSE 6.7– 6 dB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH

Applicable Standard

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

According to RSS-247 §5.2 a)

The minimum 6 dB bandwidth shall be 500 kHz.

According to RSS-Gen §6.7

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “x dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:


- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2020-07-07	2021-07-07
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005012	Each time	N/A
Unknown	Coaxial Cable	C-SJ00-0010	C0010/02	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.3 °C
Relative Humidity:	51 %
ATM Pressure:	100.9 kPa
Tester:	Rennes Guo
Test Date:	2020-10-16


Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table and plots:

Test mode	Frequency (MHz)	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit (MHz)
2.4G 1.4M	2403.5	1.110	1.150	≥ 0.5
	2439.5	1.116	1.150	≥ 0.5
	2473.5	1.116	1.156	≥ 0.5
2.4G 10M	2407.5	9.040	9.022	≥ 0.5
	2439.5	9.000	9.022	≥ 0.5
	2471.5	9.080	9.022	≥ 0.5
900MHz 1.4M	906	1.130	1.162	≥ 0.5
	915	1.142	1.144	≥ 0.5
	924	1.166	1.156	≥ 0.5
900MHz 10M	909	9.043	8.942	≥ 0.5
	915	9.032	8.942	≥ 0.5
	921	8.946	8.942	≥ 0.5


6dB Bandwidth:

2.4G 1.4M Low Channel




Date: 28.OCT.2020 22:43:48

2.4G 1.4M Middle Channel




Date: 28.OCT.2020 22:45:12

2.4G 1.4M High Channel




Date: 28.OCT.2020 22:46:23

2.4G 10M Low Channel




Date: 28.OCT.2020 22:48:14

2.4G 10M Middle Channel




Date: 28.OCT.2020 22:50:20

2.4G 10M High Channel




Date: 28.OCT.2020 22:52:32

900MHz 1.4M Low Channel




Date: 16.OCT.2020 03:13:06

900MHz 1.4M Middle Channel




Date: 16.OCT.2020 03:19:09

900MHz 1.4M High Channel




Date: 16.OCT.2020 03:26:19

900MHz 10M Low Channel




Date: 16.OCT.2020 03:32:00

900MHz 10M Middle Channel



Date: 16.OCT.2020 03:39:12


900MHz 10M High Channel




Date: 16.OCT.2020 03:37:25

99% Occupied Bandwidth:

2.4G 1.4M Low Channel



2.4G 1.4M Middle Channel




2.4G 1.4M High Channel




Date: 16.OCT.2020 04:17:26

2.4G 10M Low Channel




Date: 10.NOV.2020 04:26:28

2.4G 10M Middle Channel




Date: 16.OCT.2020 04:20:41

2.4G 10M High Channel



Date: 16.OCT.2020 04:22:01

900MHz 1.4M Low Channel



Date: 16.OCT.2020 03:40:59

900MHz 1.4M Middle Channel




Date: 16.OCT.2020 03:29:04

900MHz 1.4M High Channel




Date: 16.OCT.2020 03:20:48

900MHz 10M Low Channel



Date: 16.OCT.2020 03:30:39

900MHz 10M Middle Channel



Date: 16.OCT.2020 03:34:22

900MHz 10M High Channel



Date: 16.OCT.2020 03:36:00

FCC §15.247(b) (3) , RSS-247 CLAUSE 5.4 D - MAXIMUM PEAK CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to RSS-247§5.4 d) For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. Except as provided in Section 5.4(e), the e.i.r.p. shall not exceed 4 W.

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.
4. Set the power meter to test average output power, record the result as average power.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
E-Microwave	Coaxial Attenuators	EMCA10-5RN-6	OE01203239	2020-09-06	2021-09-06
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005012	Each time	N/A
Unknown	Coaxial Cable	C-SJ00-0010	C0010/02	Each time	N/A
Agilent	USB Wideband Power Sensor	U2021XA	MY5425009	2020-09-12	2021-09-12

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.3 °C
Relative Humidity:	51 %
ATM Pressure:	100.9 kPa
Tester:	Rennes Guo
Test Date:	2020-10-16

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table.

Mode	Channel	Frequency (MHz)	Maximum Conducted Output Power (dBm)	
			Average	Limits
2.4G 1.4M	Low	2403.5	20.36	≤30
	Middle	2439.5	20.59	≤30
	High	2473.5	20.27	≤30
2.4G 10M	Low	2407.5	20.42	≤30
	Middle	2439.5	20.63	≤30
	High	2471.5	20.23	≤30
900MHz 1.4M	Low	906	21.49	≤30
	Middle	915	21.76	≤30
	High	924	21.19	≤30
900MHz 10M	Low	909	21.72	≤30
	Middle	915	21.82	≤30
	High	921	22.08	≤30

Note: The test performed at antenna port, the maximum antenna gain is 2.2dBi for 900MHz band and 1.3 dBi for 2.4GHz band, meet the EIRP limit of ISSED.

FCC §15.247(d), RSS-247 CLAUSE 5.5 – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

According to FCC§15.247(d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to RSS-247 Clause 5.5:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2020-07-07	2021-07-07
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005012	Each time	N/A
Unknown	Coaxial Cable	C-SJ00-0010	C0010/02	Each time	N/A


* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	25.6~27.1 °C
Relative Humidity:	30 ~ 49 %
ATM Pressure:	100.8~101.9 kPa
Tester:	Rennes Guo
Test Date:	2020-10-28~2020-11-10

Test mode: Transmitting

Test Result: Compliance. Please refer to following plots.


2.4GHz band:**1.4M: Band Edge, Left Side**

Date: 28.OCT.2020 23:17:05

1.4M: Band Edge, Right Side


Date: 28.OCT.2020 23:21:25

10M: Band Edge, Left Side



Date: 28.OCT.2020 23:23:40


10M: Band Edge, Right Side




Date: 28.OCT.2020 23:25:24

900MHz Band:


1.4M: Band Edge, Left Side



1.4M: Band Edge, Right Side




10M: Band Edge, Left Side



Date: 10.NOV.2020 04:35:24

10M: Band Edge, Right Side



Date: 10.NOV.2020 04:38:03

FCC §15.247(e), RSS-247 CLAUSE 5.2 B - POWER SPECTRAL DENSITY**Applicable Standard**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

According to RSS-247 §5.2 b):

- b) The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
4. Use the peak marker function to determine the maximum amplitude level.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2020-07-07	2021-07-07
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005012	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-SJ00-0010	C0010/02	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	28.7 °C
Relative Humidity:	53 %
ATM Pressure:	101.2 kPa
Tester:	Rennes Guo
Test Date:	2020-12-01


Test Result: Compliance, Please refer to the following table and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Maximum power spectral density (dBm/3kHz)	
			Result	Limits
2.4G 1.4M	Low	2403.5	5.54	≤8
	Middle	2439.5	6.33	≤8
	High	2473.5	5.81	≤8
2.4G 10M	Low	2407.5	-4.60	≤8
	Middle	2439.5	-0.37	≤8
	High	2471.5	-1.05	≤8
900MHz 1.4M	Low	906	-5.28	≤8
	Middle	915	-4.44	≤8
	High	924	-3.84	≤8
900MHz 10M	Low	909	-4.52	≤8
	Middle	915	-4.73	≤8
	High	921	-4.31	≤8


2.4G

Power Spectral Density, 1.4M Low Channel




Date: 1.DEC.2020 06:10:15

Power Spectral Density, 1.4M Middle Channel




Date: 1.DEC.2020 06:22:14

Power Spectral Density, 1.4M High Channel



Date: 1.DEC.2020 06:21:28


Power Spectral Density, 10M Low Channel




Date: 1.DEC.2020 06:18:18

900MHz


Power Spectral Density, 1.4M Low Channel



Power Spectral Density, 1.4M Middle Channel




Power Spectral Density, 1.4M High Channel




Date: 1.DEC.2020 04:15:28


Power Spectral Density, 10M Low Channel



Date: 1.DEC.2020 04:09:02

Power Spectral Density, 10M Middle Channel

Date: 1.DEC.2020 04:10:25

Power Spectral Density, 10M High Channel

Date: 1.DEC.2020 04:11:27

******* END OF REPORT *******