

TEST REPORT

Applicant: Autel Robotics Co., Ltd

Address: 601,701,801,901, Block B1, Nanshan iPark, No. 1001 Xueyuan Avenue, Nanshan District, Shenzhen, Guangdong, 518055, China

Product Name: EVO Max 4T, EVO Max 4N, EVO Max 4T XE,
EVO Max 4T Pro

FCC ID: 2AGNTMDX600958C

Standard(s): 47 CFR Part 15, Subpart E(15.407)
ANSI C63.10-2013
KDB 789033 D02 General U-NII Test Procedures New Rules v02r01

Report Number: 2402A23350E-RF-00C

Report Date: 2025/2/18

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Pedro Yun

Gavin Xu

Reviewed By: Pedro Yun

Approved By: Gavin Xu

Title: Project Engineer

Title: RF Supervisor

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 ACCESSORY INFORMATION	5
1.3 ANTENNA INFORMATION DETAIL▲	6
1.4 EQUIPMENT MODIFICATIONS	6
2. SUMMARY OF TEST RESULTS	7
3. DESCRIPTION OF TEST CONFIGURATION	8
3.1 OPERATION FREQUENCY DETAIL	8
3.2 EUT OPERATION CONDITION	10
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	10
3.4 SUPPORT CABLE LIST AND DETAILS	10
3.5 BLOCK DIAGRAM OF TEST SETUP	11
3.6 TEST FACILITY	12
3.7 MEASUREMENT UNCERTAINTY	12
4. REQUIREMENTS AND TEST PROCEDURES	13
4.1 AC LINE CONDUCTED EMISSIONS	13
4.1.1 Applicable Standard	13
4.1.2 EUT Setup	14
4.1.3 EMI Test Receiver Setup	14
4.1.4 Test Procedure	15
4.1.5 Corrected Amplitude & Margin Calculation	15
4.1.6 Test Result	15
4.2 RADIATION SPURIOUS EMISSIONS	16
4.2.1 Applicable Standard	16
4.2.2 EUT Setup	17
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	19
4.2.4 Test Procedure	19
4.2.5 Corrected Result & Margin Calculation	20
4.2.6 Test Result	20
4.3 EMISSION BANDWIDTH	21
4.3.1 Applicable Standard	21
4.3.2 EUT Setup	21
4.3.3 Test Procedure	21
4.3.4 Test Result	22
4.4 MAXIMUM CONDUCTED OUTPUT POWER	23
4.4.1 Applicable Standard	23
4.4.2 EUT Setup	23
4.4.3 Test Procedure	23
4.4.4 Test Result	23
4.5 MAXIMUM POWER SPECTRAL DENSITY	24

4.5.1 Applicable Standard	24
4.5.2 EUT Setup	24
4.5.3 Test Procedure	24
4.5.4 Test Result	25
4.6 DUTY CYCLE	26
4.6.1 EUT Setup	26
4.6.2 Test Procedure	26
4.6.3 Judgment	26
4.7 ANTENNA REQUIREMENT	27
4.7.1 Applicable Standard	27
4.7.2 Judgment	27
5. Test DATA AND RESULTS	28
5.1 AC LINE CONDUCTED EMISSIONS	28
5.2 RADIATION SPURIOUS EMISSIONS	29
5.3 EMISSION BANDWIDTH	60
5.4 MAXIMUM CONDUCTED OUTPUT POWER	70
5.5 POWER SPECTRAL DENSITY	72
5.6 DUTY CYCLE	81
EXHIBIT A - EUT PHOTOGRAPHS	83
EXHIBIT B - TEST SETUP PHOTOGRAPHS	84

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2402A23350E-RF-00C	Original Report	2025/2/18

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	EVO Max 4T, EVO Max 4N, EVO Max 4T XE, EVO Max 4T Pro
EUT Model:	MDX
Operation Frequency:	5150-5250 MHz band: SRD 1.4MHz:5154-5246 MHz SRD 10MHz: 5157-5243MHz SRD 20MHz: 5167-5233MHz 5725-5850 MHz band SRD 1.4MHz: 5728-5847 MHz SRD 10MHz: 5733-5842 MHz SRD 20MHz: 5738-5839 MHz
Maximum Average Conducted Output Power:	5150-5250MHz:20.11 dBm 5725-5850MHz:24.95 dBm
Modulation Type:	OFDM(QPSK ,16QAM)
Rated Input Voltage:	DC 14.76V from battery or DC 14.88V from battery
Serial Number:	22WN8-1(For RF Conducted Test) 2WN8-2(For Radiated Spurious Emissions Test)
EUT Received Date:	2024/12/28
EUT Received Status:	Good

Note:

The device can install difference Gimbal camera, test was only performed with Gimbal camera 3#(4T).

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
Adapter	Shenzhen Esun Power Technology Co.,Ltd	MDX120W	Input:100-240Vac,50/60Hz,3.0A Output:Main:17Vdc.7.06A; USB-C:5.0V,3.0A;9.0V,3.0A;12.0V,2.5A Total Output Power:120.02W Max
Battery 1#	Xiamen Ampace Technology Limited	ABX40	DC 14.88V
Battery 2#	Xiamen Ampace Technology Limited	ABX41	DC 14.76V
Battery 3#	Xiamen Ampace Technology Limited	MDX_8070_1488	DC 14.88V

Note: Per 15B report, Powered by Battery 2# was the worst, so only performed it.

1.3 Antenna Information Detail ▲

Antenna	Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Chain 0 (Tx&Rx)	Dongguan YiJia Electronics Communication Technology Co.,Ltd	FPC	50	5150-5250MHz	-1.6dBi
				5725-5850MHz	1.6dBi
Chain 1 (Tx&Rx)		FPC	50	5150-5250MHz	0.7dBi
				5725-5850MHz	1.7dBi
Chain 2 Only Rx		FPC	50	5150-5250MHz	3.0dBi
				5725-5850MHz	3.9dBi
Chain 3 Only Rx		FPC	50	5150-5250MHz	4.2dBi
				5725-5850MHz	3.3dBi

Note:

The system supports 2T2R CDD modes.

Per KDB 662911 D01 Multiple Transmitter Output v02r01:

For power measurements:

CDD Mode:

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$

directional gain=0.7dBi +0dB =0.7dBi for 5150-5250MHz

directional gain=1.7dBi +0dB =1.7dBi for 5725-5850MHz

For power spectral density (PSD) measurements:

Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

directional gain=0.7dBi +3dB =3.7dBi for 5150-5250MHz

directional gain=1.7dBi +3dB =4.7dBi for 5725-5850MHz

The design of compliance with §15.203:



Unit uses a permanently attached antenna.



Unit uses a unique coupling to the intentional radiator.



Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC line conducted emissions	Not Applicable
FCC§15.205& §15.209 &§15.407(b)	Radiation Spurious Emissions	Compliant
FCC§15.407(a) (e)	Emission Bandwidth	Compliant
FCC§15.407(a)	Maximum Conducted Output Power	Compliant
FCC§15.407 (a)	Power Spectral Density	Compliant
§15.203	Antenna Requirement	Compliant
Note 1: Not Applicable, the device was powered by battery when operating.		
Note 2: For Radiated Spurious Emissions 9kHz~1GHz and 18~40GHz, the maximum output power mode and channel was tested.		

3. DESCRIPTION OF TEST CONFIGURATION

3.1 Operation Frequency Detail

For SRD-5.2GHz band:
1.4MHz Bandwidth Mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5154	48	5201
2	5155	49	5202
3	5156	...	...
...	...	...	...
...	...	92	5245
46	5199	93	5246
47	5200	/	/

10MHz Bandwidth Mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5157	45	5201
2	5158	46	5202
3	5159	...	...
...	...	...	...
...	...	86	5242
43	5199	87	5243
44	5200	/	/

20MHz Bandwidth Mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5167	35	5201
2	5168	36	5202
3	5169	...	...
...	...	...	...
...	...	66	5232
33	5199	67	5233
34	5200	/	/

For SRD-5.8GHz band:

1.4MHz Bandwidth Mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5728	61	5788
2	5729	62	5789
3	5730	...	...
...	...	...	...
59	5786	119	5846
60	5787	120	5847

10MHz Bandwidth Mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5733	56	5788
2	5734	57	5789
3	5735	...	...
...	...	...	...
54	5786	109	5841
55	5787	110	5842

20MHz Bandwidth Mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5738	52	5789
2	5739	53	5790
3	5740	...	...
...	...	...	...
50	5787	101	5838
51	5788	102	5839

Note: The above frequencies in bold were performed the test.

3.2 EUT Operation Condition

The system was configured for testing in Engineering Mode, which was provided by the manufacturer. The EUT configuration is below:

EUT Exercise Software:		RRTL6.0.0_VCOM			
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:					
Test Modes	Test Channels	Test Frequency (MHz)	Data rate	Power Level Setting	
				Chain 0	Chain 1
5150-5250 MHz Band(QPSK):					
1.4M	Lowest	5154	120kbps	95	100
	Middle	5201	120kbps	95	100
	Highest	5246	120kbps	95	100
10M	Lowest	5157	19Mbps	65	70
	Middle	5201	19Mbps	65	70
	Highest	5243	19Mbps	65	70
20M	Lowest	5167	38Mbps	55	70
	Middle	5201	38Mbps	55	70
	Highest	5233	38Mbps	60	70
5725-5850 MHz Band(QPSK):					
1.4M	Lowest	5728	120kbps	35	35
	Middle	5789	120kbps	35	35
	Highest	5847	120kbps	35	35
10M	Lowest	5733	19Mbps	35	35
	Middle	5789	19Mbps	35	35
	Highest	5842	19Mbps	35	35
20M	Lowest	5738	38Mbps	35	35
	Middle	5790	38Mbps	35	35
	Highest	5839	38Mbps	35	35
Note:					
1. The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.					
2. The device supports SISO in all BW modes, and MIMO 2TX in all BW modes, per pretest, 2TX mode was the worst mode and reported for all BW modes.					

3.3 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

3.4 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
/	/	/	/	/	/

3.5 Block Diagram of Test Setup

Radiated Spurious Emission:



3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.3dB, 30MHz~200MHz: 4.55 dB, 200MHz~1GHz: 5.92 dB, 1GHz~6GHz: 4.98 dB, 6GHz~18GHz: 5.89 dB, 18GHz~26.5GHz:5.47 dB, 26.5GHz~40GHz:5.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.11 dB (150 kHz to 30 MHz)

4. REQUIREMENTS AND TEST PROCEDURES

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

4.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Result

Please refer to section 5.1.

4.2 Radiation Spurious Emissions

4.2.1 Applicable Standard


FCC §15.407 (b);

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:


- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of – 27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of – 27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of – 27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725-5.850 GHz band:
 - (i) All emissions shall be limited to a level of – 27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
 - (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.
- (8) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (9) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in § 15.207.
- (10) The provisions of § 15.205 apply to intentional radiators operating under this section.
- (11) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.
- (c) The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.



4.2.2 EUT Setup

9kHz~30MHz:



30MHz~1GHz:



1-26.5GHz:**26.5-40GHz:**

The radiated emission tests were performed in the semi-anechoic chamber, using the setup accordance with the ANSI C63.10-2013. The specification used was FCC 15.209, FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9 kHz – 150 kHz	QP/AV	300Hz	1 kHz	200 Hz	QP/AV
150 kHz – 30 MHz	QP/AV	10 kHz	30 kHz	9 kHz	QP/AV
30MHz – 1000 MHz	PK	100 kHz	300 kHz	/	PK
	QP	/	/	120kHz	QP

1GHz- 40GHz:

Pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	PK	Any	1MHz	3 MHz
Ave.	PK	>98%	1MHz	5kHz
		<98%	1MHz	$\geq 1/T$, not less than 5kHz

Final measurement for emission identified during the pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	PK	Any	1MHz	3 MHz
Ave.	PK	>98%	1MHz	10 Hz
		<98%	1MHz	$\geq 1/T$

Note: T is minimum transmission duration

4.2.4 Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1 GHz except 9 – 90 kHz, 110 – 490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

If the maximized peak measured value is under the QP/Average limit by more than 6dB, then it is unnecessary to perform an QP/Average measurement.

If the maximized peak measured value is under the average limit, then it is unnecessary to perform an QP measurement.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as: $E [dB\mu V/m] = EIRP[dBm] + 95.2$, for $d = 3$ meters.

If the maximized peak measured value is under the QP limit by more than 6dB, then it is unnecessary to perform an QP measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

For Radiated 26.5-40GHz test, which was performed at 1.5 m distance, according to C63.10, the test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1.5m

Distance extrapolation Factor = $20 \log (\text{specific distance [3m]}/\text{test distance [1.5m]})$ dB = 6.0 dB

4.2.5 Corrected Result & Margin Calculation

The basic equation except 26.5-40GHz test is as follows:

Factor = Antenna Factor + Cable Loss - Amplifier Gain

For Radiated 26.5-40GHz test:

Factor = Antenna Factor + Cable Loss - Distance extrapolation Factor

Result = Reading + Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.2.6 Test Result

Please refer to section 5.2.

4.3 Emission Bandwidth

4.3.1 Applicable Standard


FCC §15.407 (a),(h)

(h)(2) Radar Detection Function of Dynamic Frequency Selection (DFS). U-NII devices operating with any part of its 26 dB emission bandwidth in the 5.25-5.35 GHz and 5.47-5.725 GHz bands shall employ a DFS radar detection mechanism to detect the presence of radar systems and to avoid co-channel operation with radar systems.

FCC §15.407 (e)

Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

4.3.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.3.3 Test Procedure

26dB Emission Bandwidth:

According to ANSI C63.10-2013 Section 12.4.1

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = peak.
- Trace mode = max hold
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

6 dB emission bandwidth:

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) ≥ 3 RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative

to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described in this section. For devices that use channel aggregation refer to III.A and III.C for determining emission bandwidth.

99% Occupied Bandwidth:

According to ANSI C63.10-2013 Section 12.4.2&6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.4.4 Test Result

Please refer to section 5.3.

4.4 Maximum Conducted Output Power

4.4.1 Applicable Standard


FCC §15.407(a) (1)(i)

For an outdoor access point operating in the band 5.15 – 5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30degrees as measured from the horizon must not exceed 125 mW (21 dBm).

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

4.4.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.4.3 Test Procedure

According to ANSI C63.10-2013 Section 12.3.3.1

Method PM-G is measurement using a gated RF average power meter.

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

4.4.4 Test Result

Please refer to section 5.4.

4.5 Maximum Power Spectral Density

4.5.1 Applicable Standard


FCC §15.407(a) (1)(i)

For an outdoor access point operating in the band 5.15 – 5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30degrees as measured from the horizon must not exceed 125 mW (21 dBm).

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

4.5.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.5.3 Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

Duty cycle $\geq 98\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-1 should be applied.

Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-2 should be applied.

Duty cycle <98%, duty cycle variations exceed $\pm 2\%$


KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-3 should be applied.

4.5.4 Test Result

Please refer to section 5.5.

4.6 Duty Cycle

4.6.1 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.6.2 Test Procedure

According to ANSI C63.10-2013 Section 12.2

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

4.6.3 Judgment

Report Only. Please refer to section 5.6.

4.7 Antenna Requirement

4.7.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

4.7.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.3.

5. Test DATA AND RESULTS

5.1 AC Line Conducted Emissions

Not Applicable, the device was powered by battery when operating.

5.2 Radiation Spurious Emissions

1) 9kHz - 1GHz

Serial Number:	2WN8-2	Test Date:	2025/1/13
Test Site:	Chamber10m	Test Mode:	Transmitting
Tester:	Leesin Xiang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	19.4	Relative Humidity: (%)	38	ATM Pressure: (kPa)	101.8
----------------------	------	------------------------------	----	---------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/25	2026/10/24
Sunol Sciences	Hybrid Antenna	JB3	A060611-1	2023/9/6	2026/9/5
Narda	Coaxial Attenuator	779-6dB	04269	2023/9/6	2026/9/5
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-04	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2024/7/1	2025/6/30
Sonoma	Amplifier	310N	185914	2024/8/26	2025/8/25
R&S	EMI Test Receiver	ESCI	100224	2024/8/26	2025/8/25
Audix	Test Software	E3	191218 V9	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table and plots.

9kHz~30MHz(20MHz mode 5738MHz was tested):

Three antenna orientations (parallel, perpendicular, and ground-parallel) was measured, the worst orientations was below:

Project No.: 2402A23350E-RF

Serial No.: 2WN8-2


Polarization: Parallel

Tester: Leesin Xiang

Test Mode: Transmitting

Note: 4T

RBW:300Hz VBW:1kHz




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.016	8.92	51.22	60.14	123.65	63.51	Peak
2	0.024	9.10	49.13	58.23	120.12	61.89	Peak
3	0.035	24.74	46.67	71.41	116.74	45.33	Peak
4	0.071	9.67	40.46	50.13	110.61	60.48	Peak
5	0.075	6.89	39.75	46.64	110.10	63.46	Peak
6	0.082	4.91	38.61	43.52	109.35	65.83	Peak

Project No.: 2402A23350E-RF
Polarization: Parallel
Test Mode: Transmitting
Note: 4T
RBW:10kHz VBW:30kHz

Serial No.: 2WN8-2
Tester: Leeson Xiang

Date: 2025-01-13




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.601	18.35	22.45	40.80	71.99	31.19	Peak
2	0.647	18.86	22.00	40.86	71.33	30.47	Peak
3	0.871	18.94	19.14	38.08	68.70	30.62	Peak
4	1.135	19.70	15.96	35.66	66.35	30.69	Peak
5	1.223	19.86	15.57	35.43	65.69	30.26	Peak
6	1.511	21.50	14.29	35.79	63.81	28.02	Peak

30MHz-1GHz(20MHz mode 5738MHz was tested):

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 4T
RBW:100kHz VBW:300kHz


Serial No.: 2WN8-2
Tester: Leesin Xiang



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	218.18	47.25	-12.51	34.74	46.00	11.26	Peak
2	476.20	37.06	-4.79	32.27	46.00	13.73	Peak
3	577.08	35.69	-3.16	32.53	46.00	13.47	Peak
4	600.36	40.80	-2.91	37.89	46.00	8.11	Peak
5	798.24	32.09	0.43	32.52	46.00	13.48	Peak
6	875.84	30.96	1.16	32.12	46.00	13.88	Peak

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 4T
RBW:100kHz VBW:300kHz

Serial No.: 2WN8-2
Tester: Leesin Xiang



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	218.18	39.04	-12.51	26.53	46.00	19.47	Peak
2	476.20	39.28	-4.79	34.49	46.00	11.51	Peak
3	577.08	35.09	-3.16	31.93	46.00	14.07	Peak
4	600.36	45.50	-2.91	42.59	46.00	3.41	QP
5	664.38	33.19	-1.70	31.49	46.00	14.51	Peak
6	674.08	31.20	-1.59	29.61	46.00	16.39	Peak

2) 1-40GHz:

Serial Number:	2WN8-2	Test Date:	2025/1/20-2025/1/22
Test Site:	Chamber B	Test Mode:	Transmitting
Tester:	Leo Xiao, Colin Yang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	19.9-20.3	Relative Humidity: (%)	30-35	ATM Pressure: (kPa)	101-101.2
----------------------	-----------	------------------------------	-------	------------------------	-----------





Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	000 527 35	2023/9/7	2026/9/6
Xinhang Macrowave	Coaxial Cable	XH750A-N/J-SMA/J-10M	20231117004 #0001	2024/11/17	2025/11/16
AH	Preamplifier	PAM-0118P	469	2024/4/15	2025/4/14
Audix	Test Software	E3	191218 V9	N/A	N/A
R&S	Spectrum Analyzer	FSV40	101944	2024/9/6	2025/9/5
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2023/2/22	2026/2/21
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-01 1302	2023/2/22	2026/2/21
Xinhang Macrowave	Coaxial Cable	XH360A-2.92/J-2.92/J-6M-A	20231208001 #0001	2024/12/9	2025/12/8
AH	Preamplifier	PAM-1840VH	191	2024/9/5	2025/9/4
Decentest	Multiplex Switch Test Control Set & Filter Switch Unit	DT7220SCU & DT7220FCU	DC79902 & DC79905	2024/8/27	2025/8/26


** Statement of Traceability: Bay Area Compliance Laboratories Corp.(Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:




Please refer to the below table and plots.

**1-18GHz:
5150-5250MHz:****1.4MHz mode, Low Channel, Horizontal****1.4MHz mode, Low Channel, Vertical**

1.4MHz mode, Middle Channel, Horizontal




1.4MHz mode, Middle Channel, Vertical



1.4MHz mode, High Channel, Horizontal

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 1.4MHz high channel 5246MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 2MNB-2
Tester: Leo Xiao



1.4MHz mode, High Channel, Vertical


Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 1.4MHz high channel 5246MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 2MNB-2
Tester: Leo Xiao




Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 1.4MHz high channel 5246MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 2MNB-2
Tester: Leo Xiao



Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 1.4MHz high channel 5246MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 2MNB-2
Tester: Leo Xiao



10MHz mode, Low Channel, Horizontal

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 10MHz low channel 5157MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 2MNB-2
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4891.80	52.71	-3.67	49.04	74.00	24.96	Peak
2	6371.30	51.05	-0.23	50.82	68.20	17.38	Peak

10MHz mode, Low Channel, Vertical

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 10MHz low channel 5157MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 2MNB-2
Tester: Colin Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5030.40	50.25	-2.94	47.31	74.00	26.69	Peak
2	6328.40	50.95	-0.29	50.66	68.20	17.54	Peak

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 10MHz low channel 5157MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 2MNB-2
Tester: Colin Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	10314.00	47.85	2.82	50.67	68.20	17.53	Peak
2	15471.00	47.97	3.62	51.59	74.00	22.41	Peak
3	17788.40	49.31	9.81	59.12	74.00	14.88	Peak
4	17788.40	37.22	9.81	47.03	54.00	6.97	Average


Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 10MHz low channel 5157MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 2MNB-2
Tester: Colin Yang






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	10314.00	47.46	2.82	50.28	68.20	17.92	Peak
2	15471.00	47.54	3.62	51.16	74.00	22.84	Peak
3	17993.10	48.07	11.48	59.55	74.00	14.45	Peak
4	17993.10	36.34	11.48	47.82	54.00	6.18	Average

10MHz mode, Middle Channel, Horizontal



10MHz mode, Middle Channel, Vertical




10MHz mode, High Channel, Horizontal

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 10MHz high channel 5243MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 2MNB-2
Tester: Colin Yang

Date: 2025-01-21




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4941.30	51.69	-3.64	48.05	74.00	25.95	Peak
2	6271.20	51.29	-0.33	50.96	68.20	17.24	Peak

10MHz mode, High Channel, Vertical

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 10MHz high channel 5243MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 2MNB-2
Tester: Colin Yang

Date: 2025-01-21




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5063.40	49.95	-2.33	47.62	74.00	26.38	Peak
2	6165.60	50.96	-0.47	50.49	68.20	17.71	Peak

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 10MHz high channel 5243MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 2MNB-2
Tester: Colin Yang

Date: 2025-01-21




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	10486.00	47.59	2.92	50.51	68.20	17.69	Peak
2	15729.00	48.21	3.43	51.64	74.00	22.36	Peak
3	17998.80	48.51	11.45	59.96	74.00	14.04	Peak
4	17998.80	36.32	11.45	47.77	54.00	6.23	Average

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 10MHz high channel 5243MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 2MNB-2
Tester: Colin Yang

Date: 2025-01-21




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	10486.00	47.45	2.92	50.37	68.20	17.83	Peak
2	15729.00	48.14	3.43	51.57	74.00	22.43	Peak
3	17979.30	47.74	11.37	59.11	74.00	14.89	Peak
4	17979.30	36.27	11.37	47.64	54.00	6.36	Average

20MHz mode, Low Channel, Horizontal

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 20MHz low channel 5167MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 20NB-2
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5100.80	50.49	-2.09	48.40	74.00	25.60	Peak
2	6374.60	51.32	-0.24	51.08	68.20	17.12	Peak

20MHz mode, Low Channel, Vertical

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 20MHz low channel 5167MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 20NB-2
Tester: Colin Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4253.80	53.22	-4.95	48.27	74.00	25.73	Peak
2	5992.90	51.11	-0.35	50.76	68.20	17.44	Peak

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 20MHz low channel 5167MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 20NB-2
Tester: Colin Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	10334.00	46.93	2.81	49.74	68.20	18.46	Peak
2	15501.00	47.87	3.45	51.32	74.00	22.68	Peak
3	17979.30	47.76	11.37	59.13	74.00	14.87	Peak
4	17979.30	36.11	11.37	47.48	54.00	6.52	Average


Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 20MHz low channel 5167MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 20NB-2
Tester: Colin Yang






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	10334.00	47.35	2.81	50.16	68.20	18.04	Peak
2	15501.00	47.59	3.45	51.04	74.00	22.96	Peak
3	17988.50	48.13	11.43	59.56	74.00	14.44	Peak
4	17988.50	36.29	11.43	47.72	54.00	6.28	Average

20MHz mode, Middle Channel, Horizontal




20MHz mode, Middle Channel, Vertical



20MHz mode, High Channel, Horizontal

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 20MHz high channel 5233MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 20NB-2
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4995.20	50.58	-3.13	47.45	74.00	26.55	Peak
2	6447.20	51.13	-0.15	50.98	68.20	17.22	Peak

20MHz mode, High Channel, Vertical

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 20MHz high channel 5233MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 20NB-2
Tester: Colin Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5097.50	50.17	-2.09	48.08	74.00	25.92	Peak
2	6335.00	51.95	-0.26	51.69	68.20	16.51	Peak

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 20MHz high channel 5233MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 20NB-2
Tester: Colin Yang







No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	10466.00	47.54	2.92	50.46	68.20	17.74	Peak
2	15699.00	50.29	3.45	53.74	74.00	20.26	Peak
3	17985.70	47.68	10.84	58.52	74.00	15.48	Peak
4	17985.70	36.29	10.84	47.13	54.00	6.87	Average

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 20MHz high channel 5233MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 20NB-2
Tester: Colin Yang






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	10466.00	49.50	2.92	52.42	68.20	15.78	Peak
2	15699.00	48.84	3.45	52.29	74.00	21.71	Peak
3	17988.50	48.41	11.43	59.84	74.00	14.16	Peak
4	17988.50	36.26	11.43	47.69	54.00	6.31	Average

5725-5850MHz:**1.4MHz mode, Low Channel, Horizontal****1.4MHz mode, Low Channel, Vertical**


1.4MHz mode, Middle Channel, Horizontal






1.4MHz mode, Middle Channel, Vertical



1.4MHz mode, High Channel, Horizontal




1.4MHz mode, High Channel, Vertical



10MHz mode, Low Channel, Horizontal

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 10MHz low channel 5733MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 24N8-2
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5395.60	51.06	-1.35	49.71	74.00	24.29	Peak

10MHz mode, Low Channel, Vertical

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 10MHz low channel 5733MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 24N8-2
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5447.30	50.21	-1.29	48.92	74.00	25.08	Peak

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 10MHz low channel 5733MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 24N8-2
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	11466.00	46.30	4.08	50.38	74.00	23.62	Peak
2	17199.00	47.72	7.31	55.03	68.20	13.17	Peak
3	17940.20	48.58	11.49	60.07	74.00	13.93	Peak
4	17995.40	36.37	11.49	47.86	54.00	6.14	Average


Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 10MHz low channel 5733MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 24N8-2
Tester: Leo Xiao






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	11466.00	46.03	4.08	50.11	74.00	23.89	Peak
2	17199.00	49.36	7.31	56.67	68.20	11.53	Peak
3	17940.20	48.71	11.08	59.79	74.00	14.21	Peak
4	17940.20	36.40	11.08	47.48	54.00	6.52	Average


10MHz mode, Middle Channel, Horizontal






10MHz mode, Middle Channel, Vertical



10MHz mode, High Channel, Horizontal




10MHz mode, High Channel, Vertical



20MHz mode, Low Channel, Horizontal

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 20MHz low channel 5730MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 2MNB-2
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5097.50	49.95	-2.09	47.86	74.00	26.14	Peak
2	6319.60	51.36	-0.34	51.02	68.20	17.18	Peak

20MHz mode, Low Channel, Vertical

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 20MHz low channel 5730MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 2MNB-2
Tester: Colin Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5082.10	50.13	-2.14	47.99	74.00	26.01	Peak
2	6491.20	51.18	-0.11	51.07	68.20	17.13	Peak

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 20MHz low channel 5730MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 2MNB-2
Tester: Colin Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	11476.00	45.90	4.08	49.98	74.00	24.02	Peak
2	17214.00	46.55	7.35	53.90	68.20	14.30	Peak
3	17965.50	47.88	11.27	59.15	74.00	14.85	Peak
4	17965.50	36.34	11.27	47.61	54.00	6.39	Average

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 20MHz low channel 5730MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 2MNB-2
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	11476.00	47.32	4.08	51.40	74.00	22.60	Peak
2	17214.00	47.68	7.35	55.03	68.20	13.17	Peak
3	17963.20	48.13	11.24	59.37	74.00	14.63	Peak
4	17963.20	36.08	11.24	47.32	54.00	6.68	Average

20MHz mode, Middle Channel, Horizontal

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SSB QPSK 20MHz middle channel 5790MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 20NB-2
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4840.10	52.33	-3.84	48.49	74.00	25.51	Peak
2	6394.40	51.10	-0.25	50.85	68.20	17.35	Peak

20MHz mode, Middle Channel, Vertical

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SSB QPSK 20MHz middle channel 5790MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 20NB-2
Tester: Colin Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4956.70	51.63	-3.56	48.07	74.00	25.93	Peak
2	6487.90	51.04	-0.12	50.92	68.20	17.28	Peak

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SSB QPSK 20MHz middle channel 5790MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 20NB-2
Tester: Colin Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	11580.00	47.16	4.05	51.21	74.00	22.79	Peak
2	17370.00	49.21	7.43	56.64	68.20	11.56	Peak
3	17988.50	48.19	11.43	59.62	74.00	14.38	Peak
4	17988.50	36.30	11.43	47.73	54.00	6.27	Average

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SSB QPSK 20MHz middle channel 5790MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 20NB-2
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	11580.00	48.98	4.05	53.03	74.00	20.97	Peak
2	17370.00	47.79	7.43	55.22	68.20	12.98	Peak
3	17988.50	48.49	11.43	59.92	74.00	14.08	Peak
4	17988.50	36.44	11.43	47.87	54.00	6.13	Average

20MHz mode, High Channel, Horizontal

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 20MHz high channel 5839MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 2MNB-2
Tester: Colin Yang

Date: 2025-01-21




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5067.80	49.89	-2.19	47.70	74.00	26.30	Peak
2	6493.40	50.88	-0.09	50.79	68.20	17.41	Peak

20MHz mode, High Channel, Vertical

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 20MHz high channel 5839MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 2MNB-2
Tester: Colin Yang

Date: 2025-01-21




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5370.30	51.71	-1.42	50.29	74.00	23.71	Peak
2	6134.80	51.81	-0.58	51.23	68.20	16.97	Peak

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 20MHz high channel 5839MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 2MNB-2
Tester: Colin Yang

Date: 2025-01-21




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	11678.00	47.54	4.22	51.76	74.00	22.24	Peak
2	17517.00	47.55	8.19	55.74	68.20	12.46	Peak
3	17878.10	48.98	10.58	59.56	74.00	14.44	Peak
4	17878.10	36.42	10.58	47.00	54.00	7.00	Average

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 20MHz high channel 5839MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 2MNB-2
Tester: Colin Yang

Date: 2025-01-21



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	11678.00	51.08	4.22	55.30	74.00	18.70	Peak
2	11678.00	45.36	4.22	49.58	54.00	4.42	Average
3	17517.00	48.71	8.19	56.90	68.20	11.30	Peak
4	17981.60	47.94	11.39	59.33	74.00	14.67	Peak
5	17981.60	36.37	11.39	47.76	54.00	6.24	Average


18-40GHz:

No Emission was detected in the range 18-40GHz, test was performed on the mode and channel which with the maximum power.

20MHz mode, 5738MHz, Horizontal


Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 20MHz low channel 5738MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 24N8-2
Tester: Leo Xiao

**20MHz mode, 5738MHz, Vertical**


Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 20MHz low channel 5738MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 24N8-2
Tester: Leo Xiao




Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SRD QPSK 20MHz low channel 5738MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz





Serial No.: 24N8-2
Tester: Leo Xiao



Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SRD QPSK 20MHz low channel 5738MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 24N8-2
Tester: Leo Xiao



**Bandedge:
5150-5250MHz:****1.4MHz mode, Low Channel, Horizontal****1.4MHz mode, Low Channel, Vertical****1.4MHz mode, High Channel, Horizontal****1.4MHz mode, High Channel, Vertical**

10MHz mode, Low Channel, Horizontal


Project No.: 2402A23350E-RF Serial No.: 24NB-2
Polarization: Horizontal Tester: Colin Yang
Test Mode: Transmitting
Note: SSB QPSK 10MHz low channel 5157MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5150.00	52.42	6.53	58.95	74.00	15.05	Peak
2	5150.00	40.43	6.53	46.96	54.00	7.04	Average

10MHz mode, Low Channel, Vertical


Project No.: 2402A23350E-RF Serial No.: 24NB-2
Polarization: Vertical Tester: Colin Yang
Test Mode: Transmitting
Note: SSB QPSK 10MHz low channel 5157MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5150.00	55.24	6.53	61.77	74.00	12.23	Peak
2	5150.00	44.38	6.53	50.91	54.00	3.09	Average

10MHz mode, High Channel, Horizontal


Project No.: 2402A23350E-RF Serial No.: 24NB-2
Polarization: Horizontal Tester: Colin Yang
Test Mode: Transmitting
Note: SSB QPSK 10MHz high channel 5243MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz







No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5243.00	52.12	7.10	59.22	74.00	14.78	Peak
2	5243.00	40.13	7.10	47.23	54.00	6.77	Average





10MHz mode, High Channel, Vertical

Project No.: 2402A23350E-RF Serial No.: 24NB-2
Polarization: Vertical Tester: Colin Yang
Test Mode: Transmitting
Note: SSB QPSK 10MHz high channel 5243MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5243.00	52.88	7.10	59.98	74.00	14.02	Peak
2	5243.00	40.53	7.10	47.63	54.00	6.37	Average


20MHz mode, Low Channel, Horizontal**20MHz mode, Low Channel, Vertical****20MHz mode, High Channel, Horizontal****20MHz mode, High Channel, Vertical**

5725-5850MHz:**1.4MHz mode, Low Channel, Horizontal****1.4MHz mode, Low Channel, Vertical****1.4MHz mode, High Channel, Horizontal****1.4MHz mode, High Channel, Vertical**

10MHz mode, Low Channel, Horizontal

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SSB QPSK 10MHz low channel 5733MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 24NB-2
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5650.00	51.11	7.89	59.00	68.20	9.20	Peak
2	5700.00	50.33	7.98	58.31	105.20	46.89	Peak
3	5720.00	51.56	8.02	59.58	110.80	51.22	Peak
4	5725.00	54.67	8.03	62.70	122.20	59.50	Peak

10MHz mode, Low Channel, Vertical

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SSB QPSK 10MHz low channel 5733MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 24NB-2
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5650.00	51.17	7.89	59.06	68.20	9.14	Peak
2	5700.00	50.46	7.98	58.44	105.20	46.76	Peak
3	5720.00	56.63	8.02	64.65	110.80	46.15	Peak
4	5725.00	61.13	8.03	69.16	122.20	53.04	Peak

10MHz mode, High Channel, Horizontal

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SSB QPSK 10MHz high channel 5842MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 24NB-2
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5850.00	51.83	8.20	60.03	122.20	62.17	Peak
2	5855.00	51.96	8.21	60.17	110.80	50.63	Peak
3	5875.00	51.41	8.28	59.69	105.20	45.51	Peak
4	5925.00	51.37	8.40	59.77	68.20	8.43	Peak

10MHz mode, High Channel, Vertical

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SSB QPSK 10MHz high channel 5842MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 24NB-2
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5850.00	55.72	8.20	63.92	122.20	58.28	Peak
2	5855.00	51.68	8.21	59.89	110.80	50.91	Peak
3	5875.00	51.33	8.28	59.61	105.20	45.59	Peak
4	5925.00	50.70	8.40	59.10	68.20	9.10	Peak

20MHz mode, Low Channel, Horizontal

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SSB QPSK 20MHz low channel 5730MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 20NB-2
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5650.00	52.78	7.89	60.67	68.20	7.53	Peak
2	5700.00	52.96	7.98	60.94	105.20	44.26	Peak
3	5720.00	58.15	8.02	66.17	110.80	44.63	Peak
4	5725.00	60.19	8.03	68.22	122.20	53.98	Peak

20MHz mode, Low Channel, Vertical

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SSB QPSK 20MHz low channel 5730MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 20NB-2
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5650.00	52.65	7.89	60.54	68.20	7.66	Peak
2	5700.00	54.28	7.98	62.26	105.20	42.94	Peak
3	5720.00	65.12	8.02	73.14	110.80	37.66	Peak
4	5725.00	66.16	8.03	74.19	122.20	48.01	Peak

20MHz mode, High Channel, Horizontal

Project No.: 2402A23350E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: SSB QPSK 20MHz high channel 5830MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 20NB-2
Tester: Colin Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5850.00	61.53	8.20	69.73	122.20	52.47	Peak
2	5855.00	60.56	8.21	68.77	110.80	42.03	Peak
3	5875.00	53.27	8.28	61.55	105.20	43.65	Peak
4	5925.00	52.37	8.40	60.77	68.20	7.43	Peak

20MHz mode, High Channel, Vertical

Project No.: 2402A23350E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: SSB QPSK 20MHz high channel 5830MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 20NB-2
Tester: Colin Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5850.00	71.46	8.20	79.66	122.20	42.54	Peak
2	5855.00	68.79	8.21	77.00	110.80	33.80	Peak
3	5875.00	55.11	8.28	63.39	105.20	41.81	Peak
4	5925.00	53.37	8.40	61.77	68.20	6.43	Peak

5.3 Emission Bandwidth

Serial No.:	2WN8-1	Test Date:	2025/1/23
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jojo Zhou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	24.8	Relative Humidity: (%)	48	ATM Pressure: (kPa)	101.1
-------------------------------	------	---------------------------------------	----	--------------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101461	2024/9/5	2025/9/4
Eastsheep	Coaxial Attenuator	5W-N-JK- 6G-10dB	F-08- EM503	2024/6/7	2025/6/6

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:**26dB Emission Bandwidth**

Test Modes	Test Frequency (MHz)	26 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
1.4M	5154	1.233	1.094
	5201	1.250	1.094
	5246	1.250	1.094
10M	5157	9.580	8.944
	5201	9.580	8.944
	5243	9.580	8.944
20M	5167	19.392	18.003
	5201	19.334	18.003
	5233	19.334	18.003

Note: Test only was performed at Chain 0.

The 99% Occupied Bandwidth have not fall into the band 5250-5350MHz, please refer to the test plots of 99% Occupied Bandwidth.

6dB Emission Bandwidth**5725-5850MHz**

Test Modes	Test Frequency (MHz)	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
1.4M	5728	1.133	1.107
	5789	1.133	1.111
	5847	1.155	1.142
10M	5733	9.001	8.944
	5789	9.001	8.944
	5842	9.001	8.944
20M	5738	18.061	17.945
	5790	18.061	17.945
	5839	18.061	17.945

Note:


6dB Emission Bandwidth Limit: ≥ 0.5 MHz

Test only was performed at Chain 0.

The 99% Occupied Bandwidth have not fall into the band 5470-5725MHz, please refer to the test plots of 99% Occupied Bandwidth.


26dB Bandwidth:

1.4M_5154MHz




ProjectNo.:2402A23350E-RF Tester:Jojo Zhou
Date: 23.JAN.2025 09:19:09

1.4M_5201MHz




ProjectNo.:2402A23350E-RF Tester:Jojo Zhou
Date: 23.JAN.2025 09:23:00

1.4M_5246MHz




ProjectNo.:2402A23350E-RF Tester:Jojo Zhou
Date: 23.JAN.2025 09:27:09

10M_5157MHz




ProjectNo.:2402A23350E-RF Tester:Jojo Zhou
Date: 23.JAN.2025 09:31:13

10M_5201MHz




ProjectNo.:2402A23350E-RF Tester:Jojo Zhou
Date: 23.JAN.2025 09:34:43

10M_5243MHz




ProjectNo.:2402A23350E-RF Tester:Jojo Zhou
Date: 23.JAN.2025 09:37:21

20M_5167MHz




ProjectNo.:2402A23350E-RF Tester:Jojo Zhou
Date: 23.JAN.2025 09:51:34

20M_5201MHz



ProjectNo.:2402A23350E-RF Tester:Jojo Zhou
Date: 23.JAN.2025 10:15:41


20M_5233MHz




ProjectNo.:2402A23350E-RF Tester:Jojo Zhou
Date: 23.JAN.2025 10:25:56

6dB Bandwidth:


1.4M_5728MHz

ProjectNo.:2402A23350E-RF Tester:Jojo Zhou
Date: 23.JAN.2025 10:31:29


1.4M_5789MHz

ProjectNo.:2402A23350E-RF Tester:Jojo Zhou
Date: 23.JAN.2025 10:34:45


1.4M_5847MHz

ProjectNo.:2402A23350E-RF Tester:Jojo Zhou
Date: 23.JAN.2025 10:43:04


10M_5733MHz

ProjectNo.:2402A23350E-RF Tester:Jojo Zhou
Date: 23.JAN.2025 11:05:07

10M_5789MHz

ProjectNo.:2402A23350E-RF Tester:Jojo Zhou
Date: 23.JAN.2025 11:08:06

10M_5842MHz

ProjectNo.:2402A23350E-RF Tester:Jojo Zhou
Date: 23.JAN.2025 11:19:14