



## 1 Cover Page

# RF Exposure REPORT

**Application No.:** SHEM200908089CR  
**FCC ID:** 2AGOFRC451A  
**Applicant:** HCS (Suzhou) Limited  
**Address of Applicant:** 19F-20F,Building B-3rd, No.209 Zhuyuan Road, New District, Suzhou, 215011,China  
**Manufacturer:** HCS (Suzhou) Limited  
**Address of Manufacturer:** 19F-20F,Building B-3rd, No.209 Zhuyuan Road, New District, Suzhou, 215011,China  
**Factory:** WUJIANG CENTURY BILLION ELECTRONIC TECHNOLOGY CO., LTD  
**Address of Factory:** No.149 West Tun Cun Road Tongli Town Wujiang Suzhou Jiangsu People's Republic of China 215216  
**Equipment Under Test (EUT):**  
**EUT Name:** Remote Control  
**Model No.:** RC4513101/01BRP,RC451XXXX/XXRP,RC451XXXX/XXBRP("X"=0-9."B"means packed with battery)  
**Standard(s) :** FCC Rules 47 CFR §2.1093  
KDB447498 D01 General RF Exposure Guidance v06  
**Date of Receipt:** 2020-09-21  
**Date of Test:** 2020-09-23 to 2020-10-11  
**Date of Issue:** 2020-10-21

|                     |              |
|---------------------|--------------|
| <b>Test Result:</b> | <b>Pass*</b> |
|---------------------|--------------|

\* In the configuration tested, the EUT complied with the standards specified above.

Parlam Zhan

Parlam Zhan  
E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.  
Testing Center E&E Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**


NO. 588 West Jindu Road, Songjiang District, Shanghai, China 201612  
中国·上海·松江区金都西路588号 邮编: 201612

t(86-21) 61915666 f(86-21) 61915678 www.sgsgroup.com.cn  
t(86-21) 61915666 f(86-21) 61915678 e.sgs.china@sgs.com

Member of the SGS Group (SGS SA)



| Revision Record |             |            |        |
|-----------------|-------------|------------|--------|
| Version         | Description | Date       | Remark |
| 00              | Original    | 2020-10-21 | /      |
|                 |             |            |        |
|                 |             |            |        |

|                          |  |                                                                                    |  |  |
|--------------------------|--|------------------------------------------------------------------------------------|--|--|
| Authorized for issue by: |  |                                                                                    |  |  |
|                          |  |   |  |  |
|                          |  | Micheal Niu / Project Engineer                                                     |  |  |
|                          |  |  |  |  |
|                          |  | Parlam Zhan / Reviewer                                                             |  |  |



## 2 Contents

|                                                       | Page     |
|-------------------------------------------------------|----------|
| <b>1 COVER PAGE .....</b>                             | <b>1</b> |
| <b>2 CONTENTS .....</b>                               | <b>3</b> |
| <b>3 GENERAL INFORMATION .....</b>                    | <b>4</b> |
| 3.1 GENERAL DESCRIPTION OF E.U.T.....                 | 4        |
| 3.2 DETAILS OF E.U.T.....                             | 4        |
| 3.3 TEST LOCATION.....                                | 5        |
| 3.4 TEST FACILITY.....                                | 5        |
| <b>4 TEST STANDARDS AND LIMITS.....</b>               | <b>6</b> |
| 4.1 FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS..... | 6        |
| <b>5 MEASUREMENT AND CALCULATION.....</b>             | <b>7</b> |
| 5.1 MAXIMUM TRANSMIT POWER.....                       | 7        |
| 5.2 RF EXPOSURE CALCULATION .....                     | 7        |



### 3 General Information

#### 3.1 General Description of E.U.T.

|               |                               |
|---------------|-------------------------------|
| Power supply: | DC 3V By 2*AAA size batteries |
|---------------|-------------------------------|

#### 3.2 Details of E.U.T.

|                      |                    |
|----------------------|--------------------|
| Antenna Gain:        | 0dBi               |
| Antenna Type:        | Monopole Antenna   |
| Bluetooth Version:   | BLE 5.0            |
| Channel Spacing:     | 2MHz               |
| Modulation Type:     | GFSK               |
| Number of Channels:  | 40                 |
| Operation Frequency: | 2402MHz to 2480MHz |

### 3.3 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted

### 3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L4354)**

CNAS has accredited Compliance Certification Services (Kunshan) Inc. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 2541.01)**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

- **FCC (Designation Number: CN1172)**

Compliance Certification Services Inc. has been recognized as an accredited testing laboratory. Designation Number: CN1172.

- **ISED (CAB identifier: CN0072)**

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

CAB Identifier: CN0072.

- **VCCI (Member No.: 1938)**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1600, C-1707, T-1499, G-10216 respectively.

## 4 Test Standards and Limits

### 4.1 FCC Radiofrequency radiation exposure limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max power of channel})/(\text{min test separation distance})][\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

For 2.4G band device, the limit of worse case is

$$P_{\text{max}} \leq 3.0 \cdot D_{\text{min}} / \sqrt{f} = 3.0 \cdot 5 / \sqrt{2.480} = 9.525 \text{ mW}$$



## 5 Measurement and Calculation

### 5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM200900808901.

**Test Data:**

| Test Mode | Test Channel | Power[dBm] | Peak Power (mW) |
|-----------|--------------|------------|-----------------|
| BLE(1M)   | 2402         | 0.23       | 1.05            |
| BLE(1M)   | 2440         | 0.41       | 1.10            |
| BLE(1M)   | 2480         | 0.34       | 1.08            |
| BLE(2M)   | 2402         | 0.28       | 1.07            |
| BLE(2M)   | 2440         | 0.46       | <b>1.11</b>     |
| BLE(2M)   | 2480         | 0.41       | 1.10            |

### 5.2 RF Exposure Calculation

The Max Conducted Peak Output Power is 1.11mW. The best case gain of the antenna is 0dBi.

0dBi logarithmic terms convert to numeric result is nearly 1.0

According to the formula. calculate the EIRP test result:

$$\text{EIRP} = P \times G = 1.11 \text{ mW} \times 1.0 = 1.11\text{mW} < 9.525\text{mW}$$

So the SAR report is not required.

**--End of the Report--**