

#### RF-EXPOSURE ASSESSMENT REPORT

#### FCC 47 CFR Part 2.1091 Industry Canada RSS-102

#### RF-Exposure evaluation of mobile equipment

**Report Reference No......** G0M-1508-4987-TFC091ME-V01

**Testing Laboratory** ...... Eurofins Product Service GmbH

Address..... Storkower Str. 38c

15526 Reichenwalde

Germany

Accreditation .....:



A2LA Accredited Testing Laboratory, Certificate No.: 1983.01

FCC Filed Test Laboratory, Reg.-No.: 96970

IC OATS Filing assigned code: 3470A

Applicant's name ....... TomTom Telematics B.V.

Address...... De Ruijterkade 154

1011 AC Amsterdam NETHERLANDS

**Test specification:** 

KDB 447498 D01 v06:2015-10-23

RSS-102, Issue 5:2015-03 Safety Code 6:2015-03

**Equipment under test (EUT):** 

Product description Telematic Device with GPRS+WCDMA/BT/GPS

Model No. L0530

Additional Model(s) None

Brand Name(s) LINK 530

Hardware version drs\_2\_6b\_pcb24/2015

Firmware / Software version 11\_55\_4640

FCC-ID: 2AGPAL0530 IC: 20911-L0530

Test result Passed



| Possible test case verdicts:                            |  |            |          |
|---|--|------------|----------|
| - neither assessed nor tested                           | N/N                                    |            |          |
| - required by standard but not appl. to t               | est object:                            | N/A        |          |
| - required by standard but not tested                   | :                                      | N/T        |          |
| - not required by standard for the test of              | bject:                                 | N/R        |          |
| - test object does meet the requirement                 | t:                                     | P (Pass)   |          |
| - test object does not meet the requiren                | ment:                                  | F (Fail)   |          |
| Testing:  |  |            |          |
| Test Lab Temperature                                    |  | 20 – 23 °C |          |
| Test Lab Humidity                                       | <u>*</u>                               | 32 – 38 %  |          |
| Date of receipt of test item                            | ······································ | 2015-11-23 |          |
| Date (s) of assessment                                  |  | 2016-01-14 |          |
| Compiled by:  | Christian Webe                         | er         |          |
| Assessed by (+ signature): (Responsible for Assessment) | Christian Webe                         | er         | C. Weber |
| Approved by (+ signature): (Deputy Head of Lab)         | Toralf Jahn                            |            | T. 2     |
| Date of issue: 2016-01-14                               |  |            |          |
| Total number of pages:                                  | 31                                     |            |          |
|   |  |            |          |

#### General remarks:

The test results presented in this report relate only to the object tested.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

#### Additional comments:



# **Version History**

| Version | Issue Date | Remarks         | Revised by |
|---------|------------|-----------------|------------|
| 01      | 2016-01-14 | Initial Release |            |



#### **REPORT INDEX**

| 1   | EQUIPMENT (TEST ITEM) DESCRIPTION                       | 5  |
|-----|---|----|
| 1.1 | Reference Documents                                     | 6  |
| 1.2 | Standalone Radiation Sources                            | 7  |
| 1.3 | Multi-transmitter Modes                                 | 10 |
| 2   | RESULT SUMMARY  | 11 |
| 3   | RF-EXPOSURE CLASSIFICATIONS                             | 12 |
| 4   | ASSESSMENT  | 13 |
| 4.1 | MPE Assessment Conditions – 47 CFR 2.1091 / RSS-102     | 13 |
| 4.2 | Single-Transmitter Assessment – 47 CFR 2.1091 / RSS-102 | 15 |
| 4.3 | Multi-Transmitter Assessment – 47 CFR 2.1091 / RSS-102  | 24 |



## 1 Equipment (Test item) Description

| Description                 | Telematic Device with GPRS+WCDMA/BT/GPS |
|-----------------------------|---|
| Model                       | L0530                                   |
| Additional Model(s)         | None                                    |
| Brand Name(s)               | LINK 530                                |
| Serial number               | None                                    |
| Hardware version            | drs_2_6b_pcb24/2015                     |
| Software / Firmware version | 11_55_4640                              |
| FCC-ID                      | 2AGPAL0530                              |
| IC                          | 20911-L0530                             |
| Equipment type              | End product                             |



#### 1.1 Reference Documents

| Document type           | Document No.               | Issued by                     | Date       |
|-------------------------|----------------------------|-------------------------------|------------|
| FCC 22H/24E Test Report | G0M-1508-4987-TFC224GS-V01 | Eurofins Product Service GmbH | 2016-01-11 |
| FCC 15.247 Test Report  | G0M-1307-2974-TFC247B-V01  | Eurofins Product Service GmbH | 2013-08-28 |



#### 1.2 Standalone Radiation Sources

| Mode #                    | Description                                       |                 |  |
|---------------------------|---|-----------------|--|
|                           | Frequency range [MHz]                             | 824.2 - 848.8   |  |
|                           | Transmission modes                                | GMSK            |  |
|                           | Maximum conducted power [dBm]                     | 31.8            |  |
| GSM /<br>GPRS850 / int.   | Maximum radiated power [dBm]                      | 33.8            |  |
| antenna                   | Maximum transmission duty cycle [%]               | 50              |  |
|                           | Antenna gain [dBi]                                | 2.0             |  |
|                           | Antenna diameter [cm]                             | 4.0             |  |
|                           | Assessment Frequency [MHz]  Frequency range [MHz] | 848.8           |  |
|                           | Frequency range [MHz]                             | 824.2 - 848.8   |  |
|                           | Transmission modes                                | GMSK            |  |
|                           | Maximum conducted power [dBm]                     | 28.9            |  |
| GSM /                     | Maximum radiated power [dBm]                      | 31.1            |  |
| GPRS850 /<br>ext. antenna | Maximum transmission duty cycle [%]               | 50              |  |
|                           | Antenna gain [dBi]                                | 2.2             |  |
|                           | Antenna diameter [cm]                             | 15              |  |
|                           | Assessment Frequency [MHz]                        | 848.8           |  |
|                           | Frequency range [MHz]                             | 1930.2 - 1989.8 |  |
|                           | Transmission modes                                | GMSK            |  |
|                           | Maximum conducted power [dBm]                     | 25.8            |  |
| GSM /<br>GPRS1900 /       | Maximum radiated power [dBm]                      | 29.5            |  |
| int. antenna              | Maximum transmission duty cycle [%]               | 50              |  |
|                           | Antenna gain [dBi]                                | 3.7             |  |
|                           | Antenna diameter [cm]                             | 4.0             |  |
|                           | Assessment Frequency [MHz]                        | 1989.8          |  |



# **Product Service**

|                         | Frequency range [MHz]               | 1930.2 - 1989.8 |
|-------------------------|-------------------------------------|-----------------|
|                         | Transmission modes                  | GMSK            |
|                         | Maximum conducted power [dBm]       | 21.6            |
| GSM /                   | Maximum radiated power [dBm]        | 23.8            |
| GPRS1900 / ext. antenna | Maximum transmission duty cycle [%] | 50              |
|                         | Antenna gain [dBi]                  | 2.2             |
|                         | Antenna diameter [cm]               | 15              |
|                         | Assessment Frequency [MHz]          | 1989.8          |
|                         | Frequency range [MHz]               | 826.4 - 846.6   |
|                         | Transmission modes                  | QPSK            |
|                         | Maximum conducted power [dBm]       | 25.7            |
| UMTS FDDV /             | Maximum radiated power [dBm]        | 27.7            |
| int. antenna            | Maximum transmission duty cycle [%] | 100             |
|                         | Antenna gain [dBi]                  | 2.0             |
|                         | Antenna diameter [cm]               | 4.0             |
|                         | Assessment Frequency [MHz]          | 846.6           |
|                         | Frequency range [MHz]               | 826.4 - 846.6   |
|                         | Transmission modes                  | QPSK            |
|                         | Maximum conducted power [dBm]       | 22.8            |
| UMTS FDDV /             | Maximum radiated power [dBm]        | 25.0            |
| ext. antenna            | Maximum transmission duty cycle [%] | 100             |
|                         | Antenna gain [dBi]                  | 2.2             |
|                         | Antenna diameter [cm]               | 15              |
|                         | Assessment Frequency [MHz]          | 846.6           |
|                         | Frequency range [MHz]               | 1852.4 - 1907.6 |
|                         | Transmission modes                  | QPSK            |
|                         | Maximum conducted power [dBm]       | 21.9            |
| UMTS FDDII /            | Maximum radiated power [dBm]        | 25.6            |
| int. antenna            | Maximum transmission duty cycle [%] | 100             |
|                         | Antenna gain [dBi]                  | 3.7             |
|                         | Antenna diameter [cm]               | 4.0             |
|                         | Assessment Frequency [MHz]          | 1907.6          |



|              | Frequency range [MHz]               | 1852.4 - 1907.6            |
|--------------|-------------------------------------|----------------------------|
|              | Transmission modes                  | QPSK                       |
|              | Maximum conducted power [dBm]       | 17.4                       |
| UMTS FDDII / | Maximum radiated power [dBm]        | 19.6                       |
| ext. antenna | Maximum transmission duty cycle [%] | 100                        |
|              | Antenna gain [dBi]                  | 2.2                        |
|              | Antenna diameter [cm]               | 15                         |
|              | Assessment Frequency [MHz]          | 1907.6                     |
|              | Frequency range [MHz]               | 2402 – 2480                |
|              | Transmission modes                  | GFSK / PI/4-DQPSK / 8-DPSK |
|              | Maximum conducted power [dBm]       | 4.52                       |
| Bluetooth    | Maximum radiated power [dBm]        | 4.52                       |
| Diuelootii   | Maximum transmission duty cycle [%] | 77                         |
|              | Antenna gain [dBi]                  | 0                          |
|              | Antenna diameter [cm]               | 0.6                        |
|              | Assessment Frequency [MHz]          | 2480                       |



#### 1.3 Multi-transmitter Modes

|                  | GSM/GPRS<br>850 | GSM/GPRS<br>1900 | UMTS FDDV | UMTS FDDII | Bluetooth |
|------------------|-----------------|------------------|-----------|------------|-----------|
| GSM/GPRS<br>850  | N/A             | N/A              | N/A       | N/A        | Yes       |
| GSM/GPRS<br>1900 | N/A             | N/A              | N/A       | N/A        | Yes       |
| UMTS FDDV        | N/A             | N/A              | N/A       | N/A        | Yes       |
| UMTS FDDII       | N/A             | N/A              | N/A       | N/A        | Yes       |
| Bluetooth        | Yes             | Yes              | Yes       | N/A        | N/A       |



## 2 Result Summary

| FCC 47 CFR Part 2.1091, IC RSS-102                           |   |      |  |  |  |  |  |
|--|---|------|--|--|--|--|--|
| Product Specific Standard Section Requirement Result Remarks |   |      |  |  |  |  |  |
| 47 CFR 2.1091  | Maximum permissible exposure @ 20cm below limit | PASS |  |  |  |  |  |
| RSS-102 2.5.2  | PASS  |      |  |  |  |  |  |
| Remarks:   |   |      |  |  |  |  |  |



## 3 RF-Exposure Classifications

| Device Types                      |  |  |  |
|-----------------------------------|--|--|--|
| Fixed                             | A fixed device is defined as a device physically secured at one fixed location and cannot be easily re-located.  |  |  |
| Mobile                            | A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. (47 CFR 2.1091)   |  |  |
| Portable                          | A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. (47 CFR 2.1093)   |  |  |
|                                   | Exposure Categories  |  |  |
| Occupational /<br>Controlled      | Limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure. |  |  |
| General population / uncontrolled | Exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.   |  |  |



#### 4 Assessment

#### 4.1 MPE Assessment Conditions – 47 CFR 2.1091 / RSS-102

| Assessment according to reference |                                 | Reference Method |  |                                   |                           |
|-----------------------------------|---------------------------------|------------------|--|-----------------------------------|---------------------------|
|                                   |                                 |                  | FCC OET Bulletin                         | 65 / RSS-102 & Sat                | ety Code 6                |
| Device typ                        | е                               |                  |  | mobile                            |                           |
| Exposure cate                     | egory                           |                  |  | General public                    |                           |
|                                   | IC Limits – C                   | )ccu             | pational / Controlle                     | d Exposure                        |                           |
| Frequency range<br>[MHz]          | Electric field<br>strength [V/M |                  | Magnetic field strength [A/M]            | Power density [W/m <sup>2</sup> ] | Averaging time [min]      |
| 0.003-10*                         | 170                             |                  | 180                                      | -                                 | Instantaneous*            |
| 0.1-10                            | -                               |                  | 1.6 / f                                  | -                                 | 6 <sup>**</sup>           |
| 1.29-10                           | 193 / f <sup>0.5</sup>          |                  | -  | -                                 | 6 <sup>**</sup>           |
| 10-20                             | 61.4                            |                  | 0.163                                    | -10                               | 6                         |
| 20-48                             | 129.8 / f <sup>0.25</sup>       | 5                | 0.3444 / f <sup>0.25</sup>               | 44.72 / f <sup>0.5</sup>          | 6                         |
| 48-100                            | 49.33                           |                  | 0.1309                                   | 6.455                             | 6                         |
| 100-6000                          | 15.60 f <sup>0.25</sup>         |                  | 0.04138 f <sup>0.25</sup>                | 0.6455 f <sup>0.5</sup>           | 6                         |
| 6000-15000                        | 137                             |                  | 0.364                                    | 50                                | 6                         |
| 15000-150000                      | 137                             |                  | 0.364                                    | 50                                | 616000 / f <sup>1.2</sup> |
| 150000-300000                     | 0.354 f <sup>0.5</sup>          |                  | 9.40 x 10 <sup>-4</sup> f <sup>0.5</sup> | 3.33 x 10 <sup>-4</sup> f         | 616000 / f <sup>1.2</sup> |
| IC                                | Limits - Gene                   | ral F            | Population / Uncont                      | rolled Exposure                   |                           |
| Frequency range<br>[MHz]          | Electric field<br>strength [V/M |                  | Magnetic field<br>strength [A/M]         | Power density [W/m²]              | Averaging time [min]      |
| 0.003-10*                         | 83                              |                  | 90                                       | -                                 | Instantaneous*            |
| 0.1-10                            | -                               |                  | 0.73 / f                                 | -                                 | 6**                       |
| 1.1-10                            | 87 / f <sup>0.5</sup>           |                  | -  | -                                 | 6 <sup>**</sup>           |
| 10-20                             | 27.46                           |                  | 0.0728                                   | 2                                 | 6                         |
| 20-48                             | 58.07 / f <sup>0.25</sup>       | i                | 0.1540 / f <sup>0.25</sup>               | 8.944 / f <sup>0.5</sup>          | 6                         |
| 48-300                            | 22.06                           |                  | 0.05852                                  | 1.291                             | 6                         |
| 300-6000                          | 3.142 f <sup>0.341</sup>        | 7                | 0.008335 f <sup>0.3417</sup>             | 0.02619 f <sup>0.6834</sup>       | 6                         |
| 6000-15000                        | 61.4                            |                  | 0.163                                    | 10                                | 6                         |
| 15000-150000                      | 61.4                            |                  | 0.163                                    | 10                                | 616000 / f <sup>1.2</sup> |
| 150000-300000                     | 0.158 f <sup>0.5</sup>          |                  | 4.21 x 10 <sup>-4</sup> f <sup>0.5</sup> | 6.67 x 10 <sup>-5</sup> f         | 616000 /f <sup>1.2</sup>  |



# **Product Service**

| FCC Limits – Occupational / Controlled Exposure         |                                  |                               |                                     |                      |
|---|----------------------------------|-------------------------------|-------------------------------------|----------------------|
| Frequency range<br>[MHz]                                | Electric field<br>strength [V/M] | Magnetic field strength [A/M] | Power density [mW/cm <sup>2</sup> ] | Averaging time [min] |
| 0.3 – 3.0   | 614                              | 1.63                          | (100)*                              | 6                    |
| 3.0 - 30  | 1842 / f                         | 4.89 / f                      | (900 / f <sup>2</sup> )*            | 6                    |
| 30 - 300  | 61.4                             | 0.163                         | 1.0                                 | 6                    |
| 300 - 1500  | N/A                              | N/A                           | f / 300                             | 6                    |
| 1500 - 100000   | N/A                              | N/A                           | 5.0                                 | 6                    |
| FCC Limits – General Population / Uncontrolled Exposure |                                  |                               |                                     |                      |

| ГС                       | FCC Limits - General Population / Oncontrolled Exposure |                               |                                     |                      |  |
|--------------------------|---|-------------------------------|-------------------------------------|----------------------|--|
| Frequency range<br>[MHz] | Electric field<br>strength [V/M]                        | Magnetic field strength [A/M] | Power density [mW/cm <sup>2</sup> ] | Averaging time [min] |  |
| 0.3 – 1.34               | 614   | 1.63                          | (100)*                              | 30                   |  |
| 1.34 - 30                | 842 / f   | 2.19 / f                      | (180 / f <sup>2</sup> )*            | 30                   |  |
| 30 - 300                 | 27.5  | 0.073                         | 0.2                                 | 30                   |  |
| 300 - 1500               | N/A   | N/A                           | f / 1500                            | 30                   |  |

<sup>\* =</sup> Plane wave equivalent power density; f in MHz

N/A

1500 - 100000

#### **Assessment Relations**

N/A

1.0

$$\lambda[m] = \frac{c\left[\frac{m}{s}\right]}{f[Hz]}; R_{FF}[m] \ge \frac{2 \cdot D[m]^2}{\lambda[m]}$$

$$S[mW/cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2}$$
;  $R[cm] = \sqrt{\frac{P_{E.I.R.P.}[mW]}{4\pi S[mW/cm^2]}}$ 

$$P_R[mW] = P_C[mW] \cdot G \; ; \; P_R[dBm] = P_C[dBm] + G[dBi]$$

$$DCC[dB] = 10 \cdot Log_{10} \left( \frac{DC[\%]}{100} \right)$$

#### Assessment procedure

For each radio and frequency band the worst case transmission mode with the highest peak conducted or radiated power is evaluated at the frequency that results in the most restrictive rf-exposure limit. From the peak power values, antenna gains and duty cycles taken from the reference documents, the source average radiated power values are calculated. From the average radiated power the power densities at antenna far-field distance, at 20cm separation distance from the radiation source is calculated. Compliance with the RF-Exposure limit is determined at 20cm separation distance.

Test Report No.: G0M-1508-4987-TFC091ME-V01

30



#### 4.2 Single-Transmitter Assessment – 47 CFR 2.1091 / RSS-102

| Assessment result - GSM / GPRS850 / int. antenna                 |                            |                           |  |
|--|----------------------------|---------------------------|--|
| Transmission mode  |                            |                           |  |
| Operating mode frequency range [MHz]                             | 824.2 - 848.8              |                           |  |
| Assessment frequency (f) [MHz]                                   | 84                         | 48.8                      |  |
| Transmission duty cycle (DC) [%]                                 |                            | 50                        |  |
| Peak conducted power (P <sub>C</sub> ) [dBm]                     | 3                          | 31.8                      |  |
| Peak radiated power (P <sub>R</sub> ) [dBm e.i.r.p.]             | 3                          | 33.8                      |  |
| Peak Antenna gain (G) [dBi]                                      | :                          | 2.0                       |  |
| Maximum Antenna Diameter D [cm]                                  |                            | 4.0                       |  |
| Antenna far-field distance                                       |                            |                           |  |
| Transmission frequency wavelength (λ)                            | 0.353 m                    | 35.34 cm                  |  |
| Antenna far-field distance (R <sub>FF</sub> )                    | 0.009 m                    | 0.91 cm                   |  |
| Power evaluation   |                            |                           |  |
| Peak conducted power (P <sub>C</sub> )                           | 1513.56 mW                 | 31.80 dBm                 |  |
| Peak Antenna Gain (G)  | 1.58                       | 2.00 dBi                  |  |
| Calculated peak radiated power (P <sub>R-Calc</sub> )            | 2398.83 mW                 | 33.80 dBm                 |  |
| Measured peak radiated power (P <sub>R</sub> )                   | 2398.83 mW                 | 33.80 dBm                 |  |
| Source average Power   |                            |                           |  |
| Maximum transmission duty cycle (DC)                             | 50.0 %                     |                           |  |
| Duty cycle correction (DCC)                                      | 0.50 -3.01 dB              |                           |  |
| Measured peak radiated power (P <sub>R</sub> )                   | 2398.83 mW                 | 33.80 dBm                 |  |
| Averaged peak radiated power (P <sub>RAVG</sub> )                | 1199.42 mW                 | 30.79 dBm                 |  |
| Power density  |                            |                           |  |
| Compliance power density limit FCC                               | 0.566 mW/cm <sup>2</sup>   | 5.66 W/m <sup>2</sup>     |  |
| Compliance power density limit IC                                | 0.263 mW/cm <sup>2</sup>   | 2.63 W/m <sup>2</sup>     |  |
| Power density @ Antenna far-field distance                       | 116.437 mW/cm <sup>2</sup> | 1164.373 W/m <sup>2</sup> |  |
| Power density @ 20cm   | 0.239 mW/cm <sup>2</sup>   | 2.386 W/m <sup>2</sup>    |  |
| Distance for compliance power density FCC                        | 0.130 m                    | 12.99 cm                  |  |
| Distance for compliance power density IC                         | 0.191 m                    | 19.06 cm                  |  |
| Verdict  |                            |                           |  |
| The power density of the EUT at 20cm is below the FCC MPE limit! |                            |                           |  |
| The power density of the EUT                                     | at 20cm is below the IC N  |                           |  |
| Comments:  |                            |                           |  |



| Assessment result - GS                                | SM / GPRS850 / ext. anter  | nna                    |  |
|---|----------------------------|------------------------|--|
| Transmission mode                                     |                            |                        |  |
| Operating mode frequency range [MHz]                  | 824.2 - 848.8              |                        |  |
| Assessment frequency (f) [MHz]                        | 84                         | 18.8                   |  |
| Transmission duty cycle (DC) [%]                      | 5                          | 50                     |  |
| Peak conducted power (P <sub>C</sub> ) [dBm]          | 28                         | 8.9                    |  |
| Peak radiated power (P <sub>R</sub> ) [dBm e.i.r.p.]  | 3                          | 1.1                    |  |
| Peak Antenna gain (G) [dBi]                           | 2                          | 2.2                    |  |
| Maximum Antenna Diameter D [cm]                       | 1                          | 15                     |  |
| Antenna far-field distance                            |                            |                        |  |
| Transmission frequency wavelength (λ)                 | 0.353 m                    | 35.34 cm               |  |
| Antenna far-field distance (R <sub>FF</sub> )         | 0.127 m                    | 12.73 cm               |  |
| Power evaluation                                      |                            |                        |  |
| Peak conducted power (P <sub>C</sub> )                | 776.25 mW                  | 28.90 dBm              |  |
| Peak Antenna Gain (G)                                 | 1.66                       | 2.20 dBi               |  |
| Calculated peak radiated power (P <sub>R-Calc</sub> ) | 1288.25 mW                 | 31.10 dBm              |  |
| Measured peak radiated power (P <sub>R</sub> )        | 1288.25 mW                 | 31.10 dBm              |  |
| Source average Power                                  |                            |                        |  |
| Maximum transmission duty cycle (DC)                  | 50.0 %                     |                        |  |
| Duty cycle correction (DCC)                           | 0.50                       | -3.01 dB               |  |
| Measured peak radiated power (P <sub>R</sub> )        | 1288.25 mW                 | 31.10 dBm              |  |
| Averaged peak radiated power (P <sub>RAVG</sub> )     | 644.12 mW                  | 28.09 dBm              |  |
| Power density   |                            |                        |  |
| Compliance power density limit FCC                    | 0.566 mW/cm <sup>2</sup>   | 5.66 W/m <sup>2</sup>  |  |
| Compliance power density limit IC                     | 0.263 mW/cm <sup>2</sup>   | 2.63 W/m <sup>2</sup>  |  |
| Power density @ Antenna far-field distance            | 0.316 mW/cm <sup>2</sup>   | 3.162 W/m <sup>2</sup> |  |
| Power density @ 20cm                                  | 0.128 mW/cm <sup>2</sup>   | 1.281 W/m <sup>2</sup> |  |
| Distance for compliance power density FCC             | 0.095 m                    | 9.52 cm                |  |
| Distance for compliance power density IC              | 0.140 m                    | 13.96 cm               |  |
| Verdict   |                            |                        |  |
| The power density of the EUT a                        | at 20cm is below the FCC I | MPE limit!             |  |
| The power density of the EUT                          | at 20cm is below the IC M  | IPE limit!             |  |
| Comments:   |                            |                        |  |



| Assessment result - GSM / GPRS1900 / int. antenna     |                           |                         |  |
|---|---------------------------|-------------------------|--|
| Transmission mode                                     |                           |                         |  |
| Operating mode frequency range [MHz]                  | 1930.2 - 1989.8           |                         |  |
| Assessment frequency (f) [MHz]                        | 19                        | 89.8                    |  |
| Transmission duty cycle (DC) [%]                      |                           | 50                      |  |
| Peak conducted power (P <sub>C</sub> ) [dBm]          | 2                         | 5.8                     |  |
| Peak radiated power (P <sub>R</sub> ) [dBm e.i.r.p.]  | 2                         | 9.5                     |  |
| Peak Antenna gain (G) [dBi]                           | 3                         | 3.7                     |  |
| Maximum Antenna Diameter D [cm]                       | 4                         | 4.0                     |  |
| Antenna far-field distance                            |                           |                         |  |
| Transmission frequency wavelength (λ)                 | 0.151 m                   | 15.08 cm                |  |
| Antenna far-field distance (R <sub>FF</sub> )         | 0.021 m                   | 2.12 cm                 |  |
| Power evaluation                                      | ·                         |                         |  |
| Peak conducted power (P <sub>C</sub> )                | 380.19 mW                 | 25.80 dBm               |  |
| Peak Antenna Gain (G)                                 | 2.34                      | 3.70 dBi                |  |
| Calculated peak radiated power (P <sub>R-Calc</sub> ) | 891.25 mW                 | 29.50 dBm               |  |
| Measured peak radiated power (P <sub>R</sub> )        | 891.25 mW                 | 29.50 dBm               |  |
| Source average Power                                  |                           |                         |  |
| Maximum transmission duty cycle (DC)                  | 50.0 %                    |                         |  |
| Duty cycle correction (DCC)                           | 0.50                      | -3.01 dB                |  |
| Measured peak radiated power (P <sub>R</sub> )        | 891.25 mW                 | 29.50 dBm               |  |
| Averaged peak radiated power (P <sub>RAVG</sub> )     | 445.63 mW                 | 26.49 dBm               |  |
| Power density   |                           |                         |  |
| Compliance power density limit FCC                    | 1.000 mW/cm <sup>2</sup>  | 10.00 W/m <sup>2</sup>  |  |
| Compliance power density limit IC                     | 0.470 mW/cm <sup>2</sup>  | 4.70 W/m <sup>2</sup>   |  |
| Power density @ Antenna far-field distance            | 7.872 mW/cm <sup>2</sup>  | 78.720 W/m <sup>2</sup> |  |
| Power density @ 20cm                                  | 0.089 mW/cm <sup>2</sup>  | 0.887 W/m <sup>2</sup>  |  |
| Distance for compliance power density FCC             | 0.060 m                   | 5.95 cm                 |  |
| Distance for compliance power density IC              | 0.087 m                   | 8.68 cm                 |  |
| Verdict   |                           |                         |  |
| The power density of the EUT                          | at 20cm is below the FCC  | MPE limit!              |  |
| The power density of the EUT                          | at 20cm is below the IC N | IPE limit!              |  |
| Comments:   |                           |                         |  |



| Assessment result - GSM / GPRS1900 / ext. antenna     |                            |                        |  |
|---|----------------------------|------------------------|--|
| Transmission mode                                     |                            |                        |  |
| Operating mode frequency range [MHz]                  | 1930.2 - 1989.8            |                        |  |
| Assessment frequency (f) [MHz]                        | 198                        | 89.8                   |  |
| Transmission duty cycle (DC) [%]                      | 5                          | 50                     |  |
| Peak conducted power (P <sub>C</sub> ) [dBm]          | 2.                         | 1.6                    |  |
| Peak radiated power (P <sub>R</sub> ) [dBm e.i.r.p.]  | 23                         | 3.8                    |  |
| Peak Antenna gain (G) [dBi]                           | 2                          | 2.2                    |  |
| Maximum Antenna Diameter D [cm]                       | 1                          | 15                     |  |
| Antenna far-field distance                            |                            |                        |  |
| Transmission frequency wavelength (λ)                 | 0.151 m                    | 15.08 cm               |  |
| Antenna far-field distance (R <sub>FF</sub> )         | 0.298 m                    | 29.85 cm               |  |
| Power evaluation                                      |                            |                        |  |
| Peak conducted power (P <sub>C</sub> )                | 144.54 mW                  | 21.60 dBm              |  |
| Peak Antenna Gain (G)                                 | 1.66                       | 2.20 dBi               |  |
| Calculated peak radiated power (P <sub>R-Calc</sub> ) | 239.88 mW                  | 23.80 dBm              |  |
| Measured peak radiated power (P <sub>R</sub> )        | 239.88 mW                  | 23.80 dBm              |  |
| Source average Power                                  |                            |                        |  |
| Maximum transmission duty cycle (DC)                  | 50.0 %                     |                        |  |
| Duty cycle correction (DCC)                           | 0.50                       | -3.01 dB               |  |
| Measured peak radiated power (P <sub>R</sub> )        | 239.88 mW                  | 23.80 dBm              |  |
| Averaged peak radiated power (P <sub>RAVG</sub> )     | 119.94 mW                  | 20.79 dBm              |  |
| Power density   |                            |                        |  |
| Compliance power density limit FCC                    | 1.000 mW/cm <sup>2</sup>   | 10.00 W/m <sup>2</sup> |  |
| Compliance power density limit IC                     | 0.470 mW/cm <sup>2</sup>   | 4.70 W/m <sup>2</sup>  |  |
| Power density @ Antenna far-field distance            | 0.011 mW/cm <sup>2</sup>   | 0.107 W/m <sup>2</sup> |  |
| Power density @ 20cm                                  | 0.024 mW/cm <sup>2</sup>   | 0.239 W/m <sup>2</sup> |  |
| Distance for compliance power density FCC             | 0.031 m                    | 3.09 cm                |  |
| Distance for compliance power density IC              | 0.045 m                    | 4.50 cm                |  |
| Verdict   |                            |                        |  |
| The power density of the EUT a                        | at 20cm is below the FCC I | MPE limit!             |  |
| The power density of the EUT                          | at 20cm is below the IC M  | IPE limit!             |  |
| Comments:   |                            |                        |  |



| Assessment result - UMTS FDDV / int. antenna          |                           |                          |  |
|---|---------------------------|--------------------------|--|
| Transmission mode                                     |                           |                          |  |
| Operating mode frequency range [MHz]                  | 826.4 - 846.6             |                          |  |
| Assessment frequency (f) [MHz]                        | 8                         | 46.6                     |  |
| Transmission duty cycle (DC) [%]                      |                           | 100                      |  |
| Peak conducted power (P <sub>C</sub> ) [dBm]          | 2                         | 25.7                     |  |
| Peak radiated power (P <sub>R</sub> ) [dBm e.i.r.p.]  | 2                         | 27.7                     |  |
| Peak Antenna gain (G) [dBi]                           |                           | 2.0                      |  |
| Maximum Antenna Diameter D [cm]                       |                           | 4.0                      |  |
| Antenna far-field distance                            |                           |                          |  |
| Transmission frequency wavelength (λ)                 | 0.354 m                   | 35.44 cm                 |  |
| Antenna far-field distance (R <sub>FF</sub> )         | 0.009 m                   | 0.90 cm                  |  |
| Power evaluation                                      |                           |                          |  |
| Peak conducted power (P <sub>C</sub> )                | 371.54 mW                 | 25.70 dBm                |  |
| Peak Antenna Gain (G)                                 | 1.58                      | 2.00 dBi                 |  |
| Calculated peak radiated power (P <sub>R-Calc</sub> ) | 588.84 mW                 | 27.70 dBm                |  |
| Measured peak radiated power (P <sub>R</sub> )        | 588.84 mW                 | 27.70 dBm                |  |
| Source average Power                                  |                           |                          |  |
| Maximum transmission duty cycle (DC)                  | 100.0 %                   |                          |  |
| Duty cycle correction (DCC)                           | 1.00                      | 0.00 dB                  |  |
| Measured peak radiated power (P <sub>R</sub> )        | 588.84 mW                 | 27.70 dBm                |  |
| Averaged peak radiated power (P <sub>RAVG</sub> )     | 588.84 mW                 | 27.70 dBm                |  |
| Power density   |                           |                          |  |
| Compliance power density limit FCC                    | 0.564 mW/cm <sup>2</sup>  | 5.64 W/m <sup>2</sup>    |  |
| Compliance power density limit IC                     | 0.262 mW/cm <sup>2</sup>  | 2.62 W/m <sup>2</sup>    |  |
| Power density @ Antenna far-field distance            | 57.461 mW/cm <sup>2</sup> | 574.614 W/m <sup>2</sup> |  |
| Power density @ 20cm                                  | 0.117 mW/cm <sup>2</sup>  | 1.171 W/m <sup>2</sup>   |  |
| Distance for compliance power density FCC             | 0.091 m                   | 9.11 cm                  |  |
| Distance for compliance power density IC              | 0.134 m                   | 13.36 cm                 |  |
| Verdict   |                           |                          |  |
| The power density of the EUT                          | at 20cm is below the FCC  | MPE limit!               |  |
| The power density of the EUT                          | at 20cm is below the IC N | MPE limit!               |  |
| Comments:   |                           |                          |  |



| Assessment result - UMTS FDDV / ext. antenna          |                           |                        |  |
|---|---------------------------|------------------------|--|
| Transmission mode                                     |                           |                        |  |
| Operating mode frequency range [MHz]                  | 826.4 - 846.6             |                        |  |
| Assessment frequency (f) [MHz]                        | 8-                        | 46.6                   |  |
| Transmission duty cycle (DC) [%]                      | •                         | 100                    |  |
| Peak conducted power (P <sub>C</sub> ) [dBm]          | 2                         | 22.8                   |  |
| Peak radiated power (P <sub>R</sub> ) [dBm e.i.r.p.]  | 2                         | 25.0                   |  |
| Peak Antenna gain (G) [dBi]                           | ;                         | 2.2                    |  |
| Maximum Antenna Diameter D [cm]                       |                           | 15                     |  |
| Antenna far-field distance                            |                           |                        |  |
| Transmission frequency wavelength (λ)                 | 0.354 m                   | 35.44 cm               |  |
| Antenna far-field distance (R <sub>FF</sub> )         | 0.127 m                   | 12.70 cm               |  |
| Power evaluation                                      |                           |                        |  |
| Peak conducted power (P <sub>C</sub> )                | 190.55 mW                 | 22.80 dBm              |  |
| Peak Antenna Gain (G)                                 | 1.66                      | 2.20 dBi               |  |
| Calculated peak radiated power (P <sub>R-Calc</sub> ) | 316.23 mW                 | 25.00 dBm              |  |
| Measured peak radiated power (P <sub>R</sub> )        | 316.23 mW                 | 25.00 dBm              |  |
| Source average Power                                  |                           |                        |  |
| Maximum transmission duty cycle (DC)                  | 100                       | 0.0 %                  |  |
| Duty cycle correction (DCC)                           | 1.00                      | 0.00 dB                |  |
| Measured peak radiated power (P <sub>R</sub> )        | 316.23 mW                 | 25.00 dBm              |  |
| Averaged peak radiated power (P <sub>RAVG</sub> )     | 316.23 mW                 | 25.00 dBm              |  |
| Power density   |                           |                        |  |
| Compliance power density limit FCC                    | 0.564 mW/cm <sup>2</sup>  | 5.64 W/m <sup>2</sup>  |  |
| Compliance power density limit IC                     | 0.262 mW/cm <sup>2</sup>  | 2.62 W/m <sup>2</sup>  |  |
| Power density @ Antenna far-field distance            | 0.156 mW/cm <sup>2</sup>  | 1.560 W/m <sup>2</sup> |  |
| Power density @ 20cm                                  | 0.063 mW/cm <sup>2</sup>  | 0.629 W/m <sup>2</sup> |  |
| Distance for compliance power density FCC             | 0.067 m                   | 6.68 cm                |  |
| Distance for compliance power density IC              | 0.098 m                   | 9.79 cm                |  |
| Verdict   |                           |                        |  |
| The power density of the EUT                          | at 20cm is below the FCC  | MPE limit!             |  |
| The power density of the EUT                          | at 20cm is below the IC N | MPE limit!             |  |
| Comments:   |                           |                        |  |



| Assessment result - UMTS FDDII / int. antenna         |                           |                         |  |
|---|---------------------------|-------------------------|--|
| Transmission mode                                     |                           |                         |  |
| Operating mode frequency range [MHz]                  | 1852.4 - 1907.6           |                         |  |
| Assessment frequency (f) [MHz]                        | 19                        | 907.6                   |  |
| Transmission duty cycle (DC) [%]                      |                           | 100                     |  |
| Peak conducted power (P <sub>C</sub> ) [dBm]          | 2                         | 21.9                    |  |
| Peak radiated power (P <sub>R</sub> ) [dBm e.i.r.p.]  | 2                         | 25.6                    |  |
| Peak Antenna gain (G) [dBi]                           |                           | 3.7                     |  |
| Maximum Antenna Diameter D [cm]                       |                           | 4.0                     |  |
| Antenna far-field distance                            |                           |                         |  |
| Transmission frequency wavelength (λ)                 | 0.157 m                   | 15.73 cm                |  |
| Antenna far-field distance (R <sub>FF</sub> )         | 0.020 m                   | 2.03 cm                 |  |
| Power evaluation                                      |                           |                         |  |
| Peak conducted power (P <sub>C</sub> )                | 154.88 mW                 | 21.90 dBm               |  |
| Peak Antenna Gain (G)                                 | 2.34                      | 3.70 dBi                |  |
| Calculated peak radiated power (P <sub>R-Calc</sub> ) | 363.08 mW                 | 25.60 dBm               |  |
| Measured peak radiated power (P <sub>R</sub> )        | 363.08 mW                 | 25.60 dBm               |  |
| Source average Power                                  |                           |                         |  |
| Maximum transmission duty cycle (DC)                  | 100.0 %                   |                         |  |
| Duty cycle correction (DCC)                           | 1.00                      | 0.00 dB                 |  |
| Measured peak radiated power (P <sub>R</sub> )        | 363.08 mW                 | 25.60 dBm               |  |
| Averaged peak radiated power (P <sub>RAVG</sub> )     | 363.08 mW                 | 25.60 dBm               |  |
| Power density   |                           |                         |  |
| Compliance power density limit FCC                    | 1.000 mW/cm <sup>2</sup>  | 10.00 W/m <sup>2</sup>  |  |
| Compliance power density limit IC                     | 0.457 mW/cm <sup>2</sup>  | 4.57 W/m <sup>2</sup>   |  |
| Power density @ Antenna far-field distance            | 6.978 mW/cm <sup>2</sup>  | 69.784 W/m <sup>2</sup> |  |
| Power density @ 20cm                                  | 0.072 mW/cm <sup>2</sup>  | 0.722 W/m <sup>2</sup>  |  |
| Distance for compliance power density FCC             | 0.054 m                   | 5.38 cm                 |  |
| Distance for compliance power density IC              | 0.080 m                   | 7.95 cm                 |  |
| Verdict   |                           |                         |  |
| The power density of the EUT                          | at 20cm is below the FCC  | MPE limit!              |  |
| The power density of the EUT                          | at 20cm is below the IC N | MPE limit!              |  |
| Comments:   |                           |                         |  |



| Assessment result - UMTS FDDII / ext. antenna         |                           |                        |  |
|---|---------------------------|------------------------|--|
| Transmission mode                                     |                           |                        |  |
| Operating mode frequency range [MHz]                  | 1852.4 - 1907.6           |                        |  |
| Assessment frequency (f) [MHz]                        | 19                        | 07.6                   |  |
| Transmission duty cycle (DC) [%]                      | 1                         | 00                     |  |
| Peak conducted power (P <sub>C</sub> ) [dBm]          | 1                         | 7.4                    |  |
| Peak radiated power (P <sub>R</sub> ) [dBm e.i.r.p.]  | 1:                        | 9.6                    |  |
| Peak Antenna gain (G) [dBi]                           | 2                         | 2.2                    |  |
| Maximum Antenna Diameter D [cm]                       | ,                         | 15                     |  |
| Antenna far-field distance                            |                           |                        |  |
| Transmission frequency wavelength (λ)                 | 0.157 m                   | 15.73 cm               |  |
| Antenna far-field distance (R <sub>FF</sub> )         | 0.286 m                   | 28.61 cm               |  |
| Power evaluation                                      |                           |                        |  |
| Peak conducted power (P <sub>C</sub> )                | 54.95 mW                  | 17.40 dBm              |  |
| Peak Antenna Gain (G)                                 | 1.66                      | 2.20 dBi               |  |
| Calculated peak radiated power (P <sub>R-Calc</sub> ) | 91.20 mW                  | 19.60 dBm              |  |
| Measured peak radiated power (P <sub>R</sub> )        | 91.20 mW                  | 19.60 dBm              |  |
| Source average Power                                  |                           |                        |  |
| Maximum transmission duty cycle (DC)                  | 100                       | 0.0 %                  |  |
| Duty cycle correction (DCC)                           | 1.00                      | 0.00 dB                |  |
| Measured peak radiated power (P <sub>R</sub> )        | 91.20 mW                  | 19.60 dBm              |  |
| Averaged peak radiated power (P <sub>RAVG</sub> )     | 91.20 mW                  | 19.60 dBm              |  |
| Power density   |                           |                        |  |
| Compliance power density limit FCC                    | 1.000 mW/cm <sup>2</sup>  | 10.00 W/m <sup>2</sup> |  |
| Compliance power density limit IC                     | 0.457 mW/cm <sup>2</sup>  | 4.57 W/m <sup>2</sup>  |  |
| Power density @ Antenna far-field distance            | 0.009 mW/cm <sup>2</sup>  | 0.089 W/m <sup>2</sup> |  |
| Power density @ 20cm                                  | 0.018 mW/cm <sup>2</sup>  | 0.181 W/m <sup>2</sup> |  |
| Distance for compliance power density FCC             | 0.027 m                   | 2.69 cm                |  |
| Distance for compliance power density IC              | 0.040 m                   | 3.98 cm                |  |
| Verdict   |                           |                        |  |
| The power density of the EUT                          | at 20cm is below the FCC  | MPE limit!             |  |
| The power density of the EUT                          | at 20cm is below the IC M | IPE limit!             |  |
| Comments:   |                           |                        |  |



| Assessment result - Bluetooth                         |                           |                          |  |
|---|---------------------------|--------------------------|--|
| Transmission mode                                     |                           |                          |  |
| Operating mode frequency range [MHz]                  | 2402 – 2480               |                          |  |
| Assessment frequency (f) [MHz]                        | 2                         | 480                      |  |
| Transmission duty cycle (DC) [%]                      |                           | 77                       |  |
| Peak conducted power (P <sub>C</sub> ) [dBm]          | 4                         | 1.52                     |  |
| Peak radiated power (P <sub>R</sub> ) [dBm e.i.r.p.]  | 4                         | 1.52                     |  |
| Peak Antenna gain (G) [dBi]                           |                           | 0                        |  |
| Maximum Antenna Diameter D [cm]                       |                           | 0.6                      |  |
| Antenna far-field distance                            |                           |                          |  |
| Transmission frequency wavelength (λ)                 | 0.121 m                   | 12.10 cm                 |  |
| Antenna far-field distance (R <sub>FF</sub> )         | 0.001 m                   | 0.06 cm                  |  |
| Power evaluation                                      |                           |                          |  |
| Peak conducted power (P <sub>C</sub> )                | 2.83 mW                   | 4.52 dBm                 |  |
| Peak Antenna Gain (G)                                 | 1.00                      | 0.00 dBi                 |  |
| Calculated peak radiated power (P <sub>R-Calc</sub> ) | 2.83 mW                   | 4.52 dBm                 |  |
| Measured peak radiated power (P <sub>R</sub> )        | 2.83 mW                   | 4.52 dBm                 |  |
| Source average Power                                  |                           |                          |  |
| Maximum transmission duty cycle (DC)                  | 77.0 %                    |                          |  |
| Duty cycle correction (DCC)                           | 0.77                      | -1.14 dB                 |  |
| Measured peak radiated power (P <sub>R</sub> )        | 2.83 mW                   | 4.52 dBm                 |  |
| Averaged peak radiated power (P <sub>RAVG</sub> )     | 2.18 mW                   | 3.38 dBm                 |  |
| Power density   |                           |                          |  |
| Compliance power density limit FCC                    | 1.000 mW/cm <sup>2</sup>  | 10.00 W/m <sup>2</sup>   |  |
| Compliance power density limit IC                     | 0.547 mW/cm <sup>2</sup>  | 5.47 W/m <sup>2</sup>    |  |
| Power density @ Antenna far-field distance            | 48.973 mW/cm <sup>2</sup> | 489.728 W/m <sup>2</sup> |  |
| Power density @ 20cm                                  | 0.000 mW/cm <sup>2</sup>  | 0.004 W/m <sup>2</sup>   |  |
| Distance for compliance power density FCC             | 0.004 m                   | 0.42 cm                  |  |
| Distance for compliance power density IC              | 0.006 m                   | 0.56 cm                  |  |
| Verdict   |                           |                          |  |
| The power density of the EUT                          | at 20cm is below the FCC  | MPE limit!               |  |
| The power density of the EUT                          | at 20cm is below the IC N | MPE limit!               |  |
| Comments:   |                           |                          |  |



#### 4.3 Multi-Transmitter Assessment – 47 CFR 2.1091 / RSS-102

| Assessment result - GSM / GPRS850 / int. antenna + Bluetooth    |  |                        |  |  |  |
|---|--|------------------------|--|--|--|
| Concurrent Operating Modes                                      | Concurrent Operating Modes                     |                        |  |  |  |
| Number of concurrent operating modes                            | mber of concurrent operating modes 2           |                        |  |  |  |
| Compliance Distance   |  |                        |  |  |  |
| Distance to EUT used for compliance evaluation [cm]             | 20   | )                      |  |  |  |
| GSM / GPRS850 / int. antenna                                    |  |                        |  |  |  |
| FCC limit (S <sub>FCCLimit</sub> )                              | 0.566 mW/cm <sup>2</sup>                       | 5.66 W/m <sup>2</sup>  |  |  |  |
| IC limit (S <sub>ICLimit</sub> )                                | 0.263 mW/cm <sup>2</sup>                       | 2.63 W/m <sup>2</sup>  |  |  |  |
| Power density @ compliance distance (S <sub>CD</sub> )          | 0.239 mW/cm <sup>2</sup>                       | 2.39 W/m <sup>2</sup>  |  |  |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>FCCLimit</sub> ) FCC        | 0.42   |                        |  |  |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>ICLimit</sub> ) IC          | 0.91   |                        |  |  |  |
| Bluetooth   |  |                        |  |  |  |
| FCC limit (S <sub>FCCLimit</sub> )                              | 1.000 mW/cm <sup>2</sup>                       | 10.00 W/m <sup>2</sup> |  |  |  |
| IC limit (S <sub>ICLimit</sub> )                                | 0.547 mW/cm <sup>2</sup>                       | 5.47 W/m <sup>2</sup>  |  |  |  |
| Power density @ compliance distance (S <sub>CD</sub> )          | 0.000 mW/cm <sup>2</sup>                       | 0.00 W/m <sup>2</sup>  |  |  |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>FCCLimit</sub> ) FCC        | 0.0  | 00                     |  |  |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>ICLimit</sub> ) IC          | 0.0  | 00                     |  |  |  |
| Sum of MPE Ratios   |  |                        |  |  |  |
| ∑ S <sub>CD</sub> / S <sub>FCCLimit</sub> FCC                   | 0.4  | 2                      |  |  |  |
| ∑ S <sub>CD</sub> / S <sub>ICLimit</sub> IC                     | S <sub>CD</sub> / S <sub>ICLimit</sub> IC 0.91 |                        |  |  |  |
| Verdict   |  |                        |  |  |  |
| The EUT fulfills the FCC multi-transmitter MPE limit @ 20.00cm! |  |                        |  |  |  |
| The EUT fulfills the IC multi-transmitter MPE limit @ 20.00cm!  |  |                        |  |  |  |
| Comments:   |  |                        |  |  |  |



| Assessment result - GSM / GPRS850 / ext. antenna + Bluetooth    |                          |                        |
|---|--------------------------|------------------------|
| Concurrent Operating Modes                                      |                          |                        |
| Number of concurrent operating modes                            | 2                        |                        |
| Compliance Distance   |                          |                        |
| Distance to EUT used for compliance evaluation [cm]             | 20                       |                        |
| GSM / GPRS850 / ext. antenna                                    |                          |                        |
| FCC limit (S <sub>FCCLimit</sub> )                              | 0.566 mW/cm <sup>2</sup> | 5.66 W/m <sup>2</sup>  |
| IC limit (S <sub>ICLimit</sub> )                                | 0.263 mW/cm <sup>2</sup> | 2.63 W/m <sup>2</sup>  |
| Power density @ compliance distance (S <sub>CD</sub> )          | 0.128 mW/cm <sup>2</sup> | 1.28 W/m <sup>2</sup>  |
| MPE Ratio (S <sub>CD</sub> / S <sub>FCCLimit</sub> ) FCC        | 0.23                     |                        |
| MPE Ratio (S <sub>CD</sub> / S <sub>ICLimit</sub> ) IC          | 0.49                     |                        |
| Bluetooth   |                          |                        |
| FCC limit (S <sub>FCCLimit</sub> )                              | 1.000 mW/cm <sup>2</sup> | 10.00 W/m <sup>2</sup> |
| IC limit (S <sub>ICLimit</sub> )                                | 0.547 mW/cm <sup>2</sup> | 5.47 W/m <sup>2</sup>  |
| Power density @ compliance distance (S <sub>CD</sub> )          | 0.000 mW/cm <sup>2</sup> | 0.00 W/m <sup>l</sup>  |
| MPE Ratio (S <sub>CD</sub> / S <sub>FCCLimit</sub> ) FCC        | 0.00                     |                        |
| MPE Ratio (S <sub>CD</sub> / S <sub>ICLimit</sub> ) IC          | 0.00                     |                        |
| Sum of MPE Ratios   |                          |                        |
| ∑ S <sub>CD</sub> / S <sub>FCCLimit</sub> FCC                   | 0.23                     |                        |
| Σ S <sub>CD</sub> / S <sub>ICLimit</sub> IC                     | 0.49                     |                        |
| Verdict   |                          |                        |
| The EUT fulfills the FCC multi-transmitter MPE limit @ 20.00cm! |                          |                        |
| The EUT fulfills the IC multi-transmitter MPE limit @ 20.00cm!  |                          |                        |
| Comments:   |                          |                        |



| Assessment result - GSM / GPRS1900 / int. antenna + Bluetooth   |                          |                        |  |
|---|--------------------------|------------------------|--|
| Concurrent Operating Modes                                      |                          |                        |  |
| Number of concurrent operating modes                            | 2                        |                        |  |
| Compliance Distance   | Compliance Distance      |                        |  |
| Distance to EUT used for compliance evaluation [cm]             | 20                       |                        |  |
| GSM / GPRS1900 / int. antenna                                   |                          |                        |  |
| FCC limit (S <sub>FCCLimit</sub> )                              | 1.000 mW/cm <sup>2</sup> | 10.00 W/m <sup>2</sup> |  |
| IC limit (S <sub>ICLimit</sub> )                                | 0.470 mW/cm <sup>2</sup> | 4.70 W/m <sup>2</sup>  |  |
| Power density @ compliance distance (S <sub>CD</sub> )          | 0.089 mW/cm <sup>2</sup> | 0.89 W/m <sup>2</sup>  |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>FCCLimit</sub> ) FCC        | 0.09                     |                        |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>ICLimit</sub> ) IC          | 0.19                     |                        |  |
| Bluetooth   |                          |                        |  |
| FCC limit (S <sub>FCCLimit</sub> )                              | 1.000 mW/cm <sup>2</sup> | 10.00 W/m <sup>2</sup> |  |
| IC limit (S <sub>ICLimit</sub> )                                | 0.547 mW/cm <sup>2</sup> | 5.47 W/m <sup>2</sup>  |  |
| Power density @ compliance distance (S <sub>CD</sub> )          | 0.000 mW/cm <sup>2</sup> | 0.00 W/m <sup>2</sup>  |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>FCCLimit</sub> ) FCC        | 0.00                     |                        |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>ICLimit</sub> ) IC          | 0.00                     |                        |  |
| Sum of MPE Ratios   |                          |                        |  |
| ∑ S <sub>CD</sub> / S <sub>FCCLimit</sub> FCC                   | 0.09                     |                        |  |
| ∑ S <sub>CD</sub> / S <sub>ICLimit</sub> IC                     | 0.19                     |                        |  |
| Verdict   |                          |                        |  |
| The EUT fulfills the FCC multi-transmitter MPE limit @ 20.00cm! |                          |                        |  |
| The EUT fulfills the IC multi-transmitter MPE limit @ 20.00cm!  |                          |                        |  |
| Comments:   |                          |                        |  |



| Assessment result - GSM / GPRS1900 / ext. antenna + Bluetooth   |                          |                        |
|---|--------------------------|------------------------|
| Concurrent Operating Modes                                      |                          |                        |
| Number of concurrent operating modes                            | 2                        |                        |
| Compliance Distance   |                          |                        |
| Distance to EUT used for compliance evaluation [cm]             | 20                       |                        |
| GSM / GPRS1900 / ext. antenna                                   |                          |                        |
| FCC limit (S <sub>FCCLimit</sub> )                              | 1.000 mW/cm <sup>2</sup> | 10.00 W/m <sup>2</sup> |
| IC limit (S <sub>ICLimit</sub> )                                | 0.470 mW/cm <sup>2</sup> | 4.70 W/m <sup>2</sup>  |
| Power density @ compliance distance (S <sub>CD</sub> )          | 0.024 mW/cm <sup>2</sup> | 0.24 W/m <sup>2</sup>  |
| MPE Ratio (S <sub>CD</sub> / S <sub>FCCLimit</sub> ) FCC        | 0.02                     |                        |
| MPE Ratio (S <sub>CD</sub> / S <sub>ICLimit</sub> ) IC          | 0.05                     |                        |
| Bluetooth   |                          |                        |
| FCC limit (S <sub>FCCLimit</sub> )                              | 1.000 mW/cm <sup>2</sup> | 10.00 W/m <sup>2</sup> |
| IC limit (S <sub>ICLimit</sub> )                                | 0.547 mW/cm <sup>2</sup> | 5.47 W/m <sup>2</sup>  |
| Power density @ compliance distance (S <sub>CD</sub> )          | 0.000 mW/cm <sup>2</sup> | 0.00 W/m <sup>2</sup>  |
| MPE Ratio (S <sub>CD</sub> / S <sub>FCCLimit</sub> ) FCC        | 0.00                     |                        |
| MPE Ratio (S <sub>CD</sub> / S <sub>ICLimit</sub> ) IC          | 0.00                     |                        |
| Sum of MPE Ratios   |                          |                        |
| ∑ S <sub>CD</sub> / S <sub>FCCLimit</sub> FCC                   | 0.02                     |                        |
| Σ S <sub>CD</sub> / S <sub>ICLimit</sub> IC                     | 0.05                     |                        |
| Verdict   |                          |                        |
| The EUT fulfills the FCC multi-transmitter MPE limit @ 20.00cm! |                          |                        |
| The EUT fulfills the IC multi-transmitter MPE limit @ 20.00cm!  |                          |                        |
| Comments:   |                          |                        |



| Assessment result - UMTS FDDV / int. antenna + Bluetooth        |                          |                        |  |
|---|--------------------------|------------------------|--|
| Concurrent Operating Modes                                      |                          |                        |  |
| Number of concurrent operating modes                            | 2                        |                        |  |
| Compliance Distance   | Compliance Distance      |                        |  |
| Distance to EUT used for compliance evaluation [cm]             | 20                       |                        |  |
| UMTS FDDV / int. antenna  |                          |                        |  |
| FCC limit (S <sub>FCCLimit</sub> )                              | 0.564 mW/cm <sup>2</sup> | 5.64 W/m <sup>2</sup>  |  |
| IC limit (S <sub>ICLimit</sub> )                                | 0.262 mW/cm <sup>2</sup> | 2.62 W/m <sup>2</sup>  |  |
| Power density @ compliance distance (S <sub>CD</sub> )          | 0.117 mW/cm <sup>2</sup> | 1.17 W/m <sup>2</sup>  |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>FCCLimit</sub> ) FCC        | 0.21                     |                        |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>ICLimit</sub> ) IC          | 0.45                     |                        |  |
| Bluetooth   |                          |                        |  |
| FCC limit (S <sub>FCCLimit</sub> )                              | 1.000 mW/cm <sup>2</sup> | 10.00 W/m <sup>2</sup> |  |
| IC limit (S <sub>ICLimit</sub> )                                | 0.547 mW/cm <sup>2</sup> | 5.47 W/m <sup>2</sup>  |  |
| Power density @ compliance distance (S <sub>CD</sub> )          | 0.000 mW/cm <sup>2</sup> | 0.00 W/m <sup>2</sup>  |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>FCCLimit</sub> ) FCC        | 0.00                     |                        |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>ICLimit</sub> ) IC          | 0.00                     |                        |  |
| Sum of MPE Ratios   | Sum of MPE Ratios        |                        |  |
| ∑ S <sub>CD</sub> / S <sub>FCCLimit</sub> FCC                   | 0.21                     |                        |  |
| Σ S <sub>CD</sub> / S <sub>ICLimit</sub> IC                     | 0.45                     |                        |  |
| Verdict   |                          |                        |  |
| The EUT fulfills the FCC multi-transmitter MPE limit @ 20.00cm! |                          |                        |  |
| The EUT fulfills the IC multi-transmitter MPE limit @ 20.00cm!  |                          |                        |  |
| Comments:   |                          |                        |  |



| Assessment result - UMTS FDDV / ext. antenna + Bluetooth        |                          |                        |  |
|---|--------------------------|------------------------|--|
| Concurrent Operating Modes                                      |                          |                        |  |
| Number of concurrent operating modes                            | 2                        |                        |  |
| Compliance Distance   | Compliance Distance      |                        |  |
| Distance to EUT used for compliance evaluation [cm]             | 20                       |                        |  |
| UMTS FDDV / ext. antenna  |                          |                        |  |
| FCC limit (S <sub>FCCLimit</sub> )                              | 0.564 mW/cm <sup>2</sup> | 5.64 W/m <sup>2</sup>  |  |
| IC limit (S <sub>ICLimit</sub> )                                | 0.262 mW/cm <sup>2</sup> | 2.62 W/m <sup>2</sup>  |  |
| Power density @ compliance distance (S <sub>CD</sub> )          | 0.063 mW/cm <sup>2</sup> | 0.63 W/m <sup>2</sup>  |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>FCCLimit</sub> ) FCC        | 0.11                     |                        |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>ICLimit</sub> ) IC          | 0.24                     |                        |  |
| Bluetooth   |                          |                        |  |
| FCC limit (S <sub>FCCLimit</sub> )                              | 1.000 mW/cm <sup>2</sup> | 10.00 W/m <sup>2</sup> |  |
| IC limit (S <sub>ICLimit</sub> )                                | 0.547 mW/cm <sup>2</sup> | 5.47 W/m <sup>2</sup>  |  |
| Power density @ compliance distance (S <sub>CD</sub> )          | 0.000 mW/cm <sup>2</sup> | 0.00 W/m <sup>2</sup>  |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>FCCLimit</sub> ) FCC        | 0.00                     |                        |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>ICLimit</sub> ) IC          | 0.00                     |                        |  |
| Sum of MPE Ratios   | Sum of MPE Ratios        |                        |  |
| ∑ S <sub>CD</sub> / S <sub>FCCLimit</sub> FCC                   | 0.11                     |                        |  |
| Σ S <sub>CD</sub> / S <sub>ICLimit</sub> IC                     | 0.24                     |                        |  |
| Verdict   |                          |                        |  |
| The EUT fulfills the FCC multi-transmitter MPE limit @ 20.00cm! |                          |                        |  |
| The EUT fulfills the IC multi-transmitter MPE limit @ 20.00cm!  |                          |                        |  |
| Comments:   |                          |                        |  |



| Assessment result - UMTS FDDII / int. antenna + Bluetooth       |                          |                        |
|---|--------------------------|------------------------|
| Concurrent Operating Modes                                      |                          |                        |
| Number of concurrent operating modes                            | 2                        |                        |
| Compliance Distance   |                          |                        |
| Distance to EUT used for compliance evaluation [cm]             | 20                       |                        |
| UMTS FDDII / int. antenna                                       |                          |                        |
| FCC limit (S <sub>FCCLimit</sub> )                              | 1.000 mW/cm <sup>2</sup> | 10.00 W/m <sup>2</sup> |
| IC limit (S <sub>ICLimit</sub> )                                | 0.457 mW/cm <sup>2</sup> | 4.57 W/m <sup>2</sup>  |
| Power density @ compliance distance (S <sub>CD</sub> )          | 0.072 mW/cm <sup>2</sup> | 0.72 W/m <sup>2</sup>  |
| MPE Ratio (S <sub>CD</sub> / S <sub>FCCLimit</sub> ) FCC        | 0.07                     |                        |
| MPE Ratio (S <sub>CD</sub> / S <sub>ICLimit</sub> ) IC          | 0.16                     |                        |
| Bluetooth   |                          |                        |
| FCC limit (S <sub>FCCLimit</sub> )                              | 1.000 mW/cm <sup>2</sup> | 10.00 W/m <sup>2</sup> |
| IC limit (S <sub>ICLimit</sub> )                                | 0.547 mW/cm <sup>2</sup> | 5.47 W/m <sup>2</sup>  |
| Power density @ compliance distance (S <sub>CD</sub> )          | 0.000 mW/cm <sup>2</sup> | 0.00 W/m <sup>2</sup>  |
| MPE Ratio (S <sub>CD</sub> / S <sub>FCCLimit</sub> ) FCC        | 0.00                     |                        |
| MPE Ratio (S <sub>CD</sub> / S <sub>ICLimit</sub> ) IC          | 0.00                     |                        |
| Sum of MPE Ratios   |                          |                        |
| ∑ S <sub>CD</sub> / S <sub>FCCLimit</sub> FCC                   | 0.07                     |                        |
| Σ S <sub>CD</sub> / S <sub>ICLimit</sub> IC                     | 0.16                     |                        |
| Verdict   |                          |                        |
| The EUT fulfills the FCC multi-transmitter MPE limit @ 20.00cm! |                          |                        |
| The EUT fulfills the IC multi-transmitter MPE limit @ 20.00cm!  |                          |                        |
| Comments:   |                          |                        |



| Assessment result - UMTS FDDII / ext. antenna + Bluetooth       |                          |                        |  |
|---|--------------------------|------------------------|--|
| Concurrent Operating Modes                                      |                          |                        |  |
| Number of concurrent operating modes                            | 2                        |                        |  |
| Compliance Distance   | Compliance Distance      |                        |  |
| Distance to EUT used for compliance evaluation [cm]             | 20                       |                        |  |
| UMTS FDDII / ext. antenna                                       |                          |                        |  |
| FCC limit (S <sub>FCCLimit</sub> )                              | 1.000 mW/cm <sup>2</sup> | 10.00 W/m <sup>2</sup> |  |
| IC limit (S <sub>ICLimit</sub> )                                | 0.457 mW/cm <sup>2</sup> | 4.57 W/m <sup>2</sup>  |  |
| Power density @ compliance distance (S <sub>CD</sub> )          | 0.018 mW/cm <sup>2</sup> | 0.18 W/m <sup>2</sup>  |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>FCCLimit</sub> ) FCC        | 0.02                     |                        |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>ICLimit</sub> ) IC          | 0.04                     |                        |  |
| Bluetooth   |                          |                        |  |
| FCC limit (S <sub>FCCLimit</sub> )                              | 1.000 mW/cm <sup>2</sup> | 10.00 W/m <sup>2</sup> |  |
| IC limit (S <sub>ICLimit</sub> )                                | 0.547 mW/cm <sup>2</sup> | 5.47 W/m <sup>2</sup>  |  |
| Power density @ compliance distance (S <sub>CD</sub> )          | 0.000 mW/cm <sup>2</sup> | 0.00 W/m <sup>2</sup>  |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>FCCLimit</sub> ) FCC        | 0.00                     |                        |  |
| MPE Ratio (S <sub>CD</sub> / S <sub>ICLimit</sub> ) IC          | 0.00                     |                        |  |
| Sum of MPE Ratios   | Sum of MPE Ratios        |                        |  |
| ∑ S <sub>CD</sub> / S <sub>FCCLimit</sub> FCC                   | 0.02                     |                        |  |
| Σ S <sub>CD</sub> / S <sub>ICLimit</sub> IC                     | 0.04                     |                        |  |
| Verdict   |                          |                        |  |
| The EUT fulfills the FCC multi-transmitter MPE limit @ 20.00cm! |                          |                        |  |
| The EUT fulfills the IC multi-transmitter MPE limit @ 20.00cm!  |                          |                        |  |
| Comments:   |                          |                        |  |