



TEST REPORT

APPLICANT : SamKnows Limited

PRODUCT NAME : SamKnows Whitebox 8.0+

MODEL NAME : SK-WB8+

BRAND NAME : SamKnows

FCC ID : 2AGPP-SKWB8V3

STANDARD(S) : 47 CFR Part 15 Subpart E

RECEIPT DATE : 2020-11-11

TEST DATE : 2020-11-29 to 2021-03-14

ISSUE DATE : 2021-04-27

Edited by:

Peng Mi (Rapporteur)

Approved by:

Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

1. Technical Information	3
1.1. Applicant and Manufacturer Information	3
1.2. Equipment Under Test (EUT) Description	3
1.3. Modulation Type and Data Rate of EUT	5
1.4. The Channel Number and Frequency	6
1.5. Test Standards and Results	7
1.6. Environmental Conditions	8
2. 47 CFR Part 15E Requirements	9
2.1. Antenna Requirement	9
2.2. Duty Cycle of the Test Signal	10
2.3. Maximum Conducted Output Power	15
2.4. Emission Bandwidth	21
2.5. Peak Power Spectral Density	60
2.6. Frequency Stability	101
2.7. Conducted Emission	104
2.8. Restricted Frequency Bands	108
2.9. Radiated Emission	128
Annex A Test Uncertainty	159
Annex B Testing Laboratory Information	160

Change History		
Version	Date	Reason for change
1.0	2021-04-27	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	SamKnows Limited
Applicant Address:	94 New Bond Street, London W1S 1SJ, United Kingdom
Manufacturer:	Taicang T & W Electronics Co., Ltd
Manufacturer Address:	No. 89, Jiangnan Road, Loudong Street, Taicang, Jiangsu Province 215412, P. R. China

1.2. Equipment Under Test (EUT) Description

Product Name:	SamKnows Whitebox 8.0+	
Serial No.:	(N/A, marked #1 by test site)	
Hardware Version:	3	
Software Version:	20160115	
Modulation Technology:	OFDM	
Modulation Mode:	802.11a, 802.11n (HT20), 802.11n (HT40) 802.11ac (VHT20), 802.11ac (VHT40), 802.11ac (VHT80)	
Operating Frequency Range:	5180MHz-5240MHz; 5260MHz-5320MHz; 5500MHz-5720MHz; 5745MHz-5825MHz	
Channel Number:	Refer to 1.3	
Antenna Type:	External Antenna	
Antenna Gain:	ANT 0: 5.00dBi; ANT 1: 5.00dBi	
Directional Gain:	8.01dBiNote 2	
Accessory Information:	AC Adapter	
	Brand Name:	N/A
	Model No.:	S24B72-120A200-0K
	Serial No.:	(N/A, marked #1 by test site)
	Rated Output:	12V=2A
	Rated Input:	100-240V~50/60Hz, 0.8A
	Manufacturer:	Shenzhen Gongjin Electronics Co., Ltd.



Note 1: The EUT supports a MIMO function. Physically, the EUT provides two completed transmitters and two receivers for 802.11n and 802.11ac modulation mode.

Modulation Mode:	TX Function
802.11n	2TX
802.11ac	2TX

Note 2: According to KDB 662911 D01, the directional gain = $G_{ANT} + 10\log(N_{ANT})$ dBi, where G_{ANT} is the maximum antenna gain in dBi, N_{ANT} is the number of outputs.

Note 3: For conducted test item Conducted Output Power and Peak Power Spectral Density of each modulation mode, we recorded the test result of two antennas separately, for other conducted test items both of the two antennas were tested separately, we only recorded the worst test result (ANT0) in this report.

Note 4: All radiation test items for 802.11n and 802.11ac modulation mode operate at MIMO mode during the test. Other modulation mode operate at SISO mode, both of the two antennas were tested separately, we only recorded the worst test result(ANT0) in this report.

Note 5: WIFI hotspot does not support U-NII band.

Note 6: We use the dedicated software to control the EUT continuous transmission.

Note 7: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.3. Modulation Type and Data Rate of EUT

Modulation Technology	Modulation Type	Data Rate (Mbps) ^{Note1}
OFDM (802.11a)	BPSK	6/9
	QPSK	12/18
	16QAM	24/36
	64QAM	48/54
OFDM (802.11n)	BPSK	6.5
	QPSK	13/19.5
	16QAM	26/39
	64QAM	52/58.5/65
OFDM (802.11ac)	BPSK	6.5
	QPSK	13/19.5
	16QAM	26/39
	64QAM	52/58.5/65
	256QAM	78

Note1: The worst-case mode (black bold) in all data rates has been determined during the pre-scan, only the test data of the worst-case were recorded in this report.

1.4. The Channel Number and Frequency

Frequency Range: 5150MHz-5250MHz				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	36	5180	40	5200
	44	5220	48	5240
40MHz	38	5190	46	5230
80MHz	42	5210		
Frequency Range: 5250MHz-5350MHz				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	52	5260	56	5280
	60	5300	64	5320
40MHz	54	5270	62	5310
80MHz	58	5290		
Frequency Range: 5470MHz-5725MHz				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	100	5500	105	5520
	108	5540	112	5560
	116	5580	120	5600
	124	5620	128	5640
	132	5660	136	5680
	140	5700	144	5720
40MHz	102	5510	110	5550
	118	5590	126	5630
	134	5670	142	5710
80MHz	106	5530	122	5610
	138	5690		
Frequency Range: 5725MHz-5825MHz				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	149	5745	153	5765
	157	5785	161	5805
	165	5825		
40MHz	151	5775	159	5795
80MHz	155	5775		

Note 1: The black bold channels were selected for test.



1.5. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart E (U-NII band) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15(5-1-14 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	ANSI C63.10	Duty Cycle of the Test Signal	Dec 26, 2020	Ouyang Feng	PASS	No deviation
3	15.407(a)	Maximum Conducted Output Power	Dec 26, 2020	Ouyang Feng	PASS	No deviation
4	15.407(a) (e)	Emission Bandwidth	Dec 25&26, 2020	Ouyang Feng	PASS	No deviation
5	15.407(a)	Peak Power Spectral Density	Dec 25, 2020	Ouyang Feng	PASS	No deviation
6	15.407(g)	Frequency Stability	Dec 26, 2020	Ouyang Feng	PASS	No deviation
7	15.207	Conducted Emission	Nov 29, 2020	Huang Zhiye	PASS	No deviation
8	15.407(b)	Restricted Frequency Bands	Mar 14, 2021	Gao Jianrou	PASS	No deviation
9	15.407(b)	Radiated Emission	Mar 02, 2021	Gao Jianrou	PASS	No deviation

Note 1: The DFS test report was documented in a separate report (Report No.: SZ20110143W03).

Note 2: The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.102013.

Note 3: These RF tests were performed according to the method of measurements prescribed in KDB789033 D02 v02r01, KDB662911 D01 v02r01.



Note 4: The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The ref offset 12.5dB contains two parts that cable loss 2.5dB and Attenuator 10dB.

Note 5: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 6: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% risk level.

1.6. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106



2.47 CFR Part 15E Requirements

2.1. Antenna Requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Test Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Duty Cycle of the Test Signal


2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be nonconstant.

2.2.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.2.3. Test Procedure


KDB 789033 Section B was used in order to prove compliance.

2.2.4. Test Result


A.Test Verdict:

Test Mode	Duty Cycle (%) (D)	Duty Factor (10*log[1/D])
802.11a	87.54	0.58
802.11n (HT20)	86.86	0.61
802.11n (HT40)	75.52	1.22
802.11ac (VHT20)	86.69	0.62
802.11ac (VHT40)	76.45	1.17
802.11ac (VHT80)	48.48	3.14


B.Test Plot:




(Channel 36, 5180MHz, 802.11a)




(Channel 36, 5180MHz, 802.11n (HT20))




(Channel 38, 5190MHz, 802.11n (HT40))



(Channel 36, 5180MHz, 802.11ac (VHT20))



(Channel 38, 5190MHz, 802.11ac (VHT40))



(Channel 42, 5210MHz, 802.11ac (VHT80))

2.3. Maximum Conducted Output Power

2.3.1. Requirement

(1) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11\text{dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


(4) According to KDB662911D01 Measure-and-sum technique, the conducted emission level (e.g., transmit power or power in specified bandwidth) is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically to determine the total emission level from the device. Summing is performed in units that are directly proportional to power.

(5) According to KDB 662911 D01, the directional gain = $G_{\text{ANT}} + 10\log(N_{\text{ANT}})\text{dBi}$, where G_{ANT} is the antenna gain in dBi, N_{ANT} is the number of outputs.

2.3.2. Test Description


Section E) 3) of KDB 789033 defines a methodology using a USB Wideband Power Sensor.

Test Setup:



The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in USB Wideband Power Sensor.

For ac (VHT80) mode power



The EUT (Equipment under the test) is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

2.3.3.Limits

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

Mode	Band	Channel (MHz)	26dB BW (MHz)	$10+10\log(26\text{dB BW})$	Limits (dBm)
a	UNII-2a	5260	22.35	24.49	24.00
		5300	22.53	24.53	24.00
		5320	22.65	24.55	24.00
	UNII-2c	5500	23.62	24.73	24.00
		5600	25.22	25.02	24.00
		5720	25.37	25.04	24.00
n20	UNII-2a	5260	24.23	24.84	24.00
		5300	23.60	24.73	24.00
		5320	23.92	24.79	24.00
	UNII-2c	5500	25.64	25.09	24.00
		5600	25.97	25.14	24.00
		5720	26.70	25.27	24.00
ac20	UNII-2a	5260	24.59	24.91	24.00
		5300	24.65	24.92	24.00
		5320	23.82	24.77	24.00
	UNII-2c	5500	26.35	25.21	24.00
		5600	25.49	25.06	24.00
		5720	27.19	25.34	24.00

**2.3.4.Test Result****Maximum Average Conducted Output Power****802.11a Mode**

Frequency (MHz)	Average Power							Limit		Verdict
	Measured		Duty Factor	Duty factor Calculated						
	ANT0	ANT1		ANT0		ANT1				
	dBm	dBm		dBm	W	dBm	W			
5180	15.07	14.32	0.58	15.65	0.037	14.90	0.031	24	0.25	PASS
5220	15.48	13.64		16.06	0.040	14.22	0.026			PASS
5240	15.58	13.72		16.16	0.041	14.30	0.027			
5260	15.60	14.77		16.18	0.041	15.35	0.034			
5300	16.47	15.12		17.05	0.051	15.70	0.037			
5320	16.58	15.37		17.16	0.052	15.95	0.039			
5500	17.51	15.88		18.09	0.064	16.46	0.044			
5600	17.39	16.95		17.97	0.063	17.53	0.057			
5720	17.09	16.40		17.67	0.058	16.98	0.050			
5745	17.89	17.67		18.47	0.070	18.25	0.067	30	1	
5785	17.59	17.92		18.17	0.066	18.50	0.071			
5825	18.58	17.83		19.16	0.082	18.41	0.069			



802.11n (HT20) Mode

Frequency (MHz)	Average Power				Limit		Verdict	
	Measured		Duty Factor	Total Power with Duty Factor				
	ANT0	ANT1			dBm	W		dBm
5180	14.49	13.82	0.61	17.78	0.060	21.99	0.16	PASS
5220	15.33	13.61		18.20	0.066			PASS
5240	15.60	13.57		18.33	0.068			
5260	15.81	14.71		18.92	0.078			
5300	16.09	14.81		19.14	0.082			
5320	16.28	15.15		19.40	0.087			
5500	17.11	16.22		20.29	0.107			
5600	17.58	16.30		20.61	0.115			
5720	17.00	16.63		20.45	0.111			
5745	17.91	17.42		21.30	0.135	27.99	0.63	
5785	18.45	17.75		21.73	0.149			
5825	18.65	18.21		22.07	0.161			
Note: Directional gain = 5.00dBi +10log(2) = 8.01dBi>6dBi, so the power limit shall be reduced to 24-(8.01-6) = 21.99dBm for 5.18-5.24 GHz band and reduced to 30-(8.01-6) = 27.99dBm for 5.745-5.825 GHz band.								

802.11n (HT40) Mode

Frequency (MHz)	Average Power					Limit		Verdict
	Measured		Duty Factor	Total Power with Duty Factor				
	ANT0	ANT1						
	dBm	dBm		dBm	W	dBm	W	
5190	12.43	11.57	0.18	16.23	0.042	21.99	0.16	PASS
5230	13.62	13.38		17.71	0.059			PASS
5270	14.72	13.72		18.45	0.070			
5310	15.10	14.05		18.86	0.077			
5510	16.03	14.75		19.68	0.093			
5630	16.61	16.18		20.64	0.116			
5710	16.54	14.71		19.96	0.099			
5755	17.51	15.88		21.00	0.126	27.99	0.63	
5795	17.64	16.26		21.24	0.133			
Note: Directional gain = 5.00dBi +10log(2) = 8.01dBi> 6dBi, so the power limit shall be reduced to 24-(8.01-6) = 21.99dBm for 5.18-5.24 GHz band and reduced to 30-(8.01-6) = 27.99dBm for 5.745-5.825 GHz band.								

**802.11ac (VHT20) Mode**

Frequency (MHz)	Average Power					Limit		Verdict
	Measured		Duty Factor	Total Power with Duty Factor				
	ANT0	ANT1						
	dBm	dBm		dBm	W	dBm	W	
5180	15.03	13.97	0.08	18.20	0.066	21.99	0.16	PASS
5220	15.68	13.65		18.39	0.069			PASS
5240	15.79	13.54		18.45	0.070			
5260	16.01	14.79		19.08	0.081			
5300	16.34	14.95		19.34	0.086			
5320	16.34	16.78		20.21	0.105			
5500	17.37	17.38		21.00	0.126			
5600	17.16	17.65		21.04	0.127			
5720	17.17	15.09		19.87	0.097			
5745	18.17	17.64		21.55	0.143	27.99	0.63	
5785	18.24	17.95		21.73	0.149			
5825	18.53	17.95		21.88	0.154			
Note: Directional gain = 5.00dBi +10log(2) = 8.01dBi>6dBi, so the power limit shall be reduced to 24-(8.01-6) = 21.99dBm for 5.18-5.24 GHz band and reduced to 30-(8.01-6) = 27.99dBm for 5.745-5.825 GHz band.								

802.11ac (VHT40) Mode

Frequency (MHz)	Average Power					Limit		Verdict
	Measured		Duty Factor	Total Power with Duty Factor				
	ANT0	ANT1						
	dBm	dBm		dBm	W	dBm	W	
5190	14.78	13.26	0.16	18.26	0.067	21.99	0.16	PASS
5230	15.37	12.83		18.45	0.070			PASS
5270	15.95	14.12		19.29	0.085			
5310	18.38	14.41		21.00	0.126			
5510	18.27	15.32		21.21	0.132			
5630	17.22	16.36		21.00	0.126			
5710	17.10	16.37		20.93	0.124			
5755	17.98	17.39		21.88	0.154	27.99	0.63	
5795	18.23	17.64		22.12	0.163			
Note: Directional gain = 5.00dBi +10log(2) = 8.01dBi>6dBi, so the power limit shall be reduced to 24-(8.01-6) = 21.99dBm for 5.18-5.24 GHz band and reduced to 30-(8.01-6) = 27.99dBm for 5.745-5.825 GHz band.								

**802.11ac (VHT80) Mode**

Frequency (MHz)	Average Power					Limit		Verdict
	Measured		Duty Factor	Total Power with Duty Factor				
	ANT0	ANT1						
	dBm	dBm		W	dBm	dBm	W	
5210	13.21	10.46	0.33	18.20	0.066	21.99	0.16	PASS
5290	13.53	11.36		18.75	0.075			
5530	13.79	12.99		19.54	0.090			
5610	13.54	12.57		19.24	0.084			
5690	12.57	11.45		18.20	0.066			
5775	12.58	11.47		18.20	0.066	27.99	0.63	
Note: Directional gain = 5.00dBi +10log(2) = 8.01dBi> 6dBi, so the power limit shall be reduced to 24-(8.01-6) = 21.99dBm for 5.18-5.24 GHz band and reduced to 30-(8.01-6) = 27.99dBm for 5.745-5.825 GHz band.								


2.4. Emission Bandwidth

2.4.1. Requirement

For purposes of this subpart the emission bandwidth shall be determined by measuring the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that are 26 dB down relative to the maximum level of the modulated carrier. Determination of the emissions bandwidth is based on the use of measurement instrumentation employing a peak detector function with an instrument resolution bandwidth approximately equal to 1.0 percent of the emission bandwidth of the device under measurement. Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

2.4.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading.

2.4.3. Test Procedure

1. KDB 789033 Section C) 1) Emission Bandwidth was used in order to prove compliance
 - a) Set RBW = approximately 1% of the emission bandwidth.
 - b) Set VBW > RBW.
 - c) Detector = Peak.
 - d) Trace mode = max hold.
 - e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
 2. KDB 789033 Section C) 2) minimum emission bandwidth for the band 5.725-5.85GHz was used in order to prove compliance.
- Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:



- a) Set RBW = 100 kHz.
- b) Set video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

2.4.4. Test Result


802.11a Mode

A. Test Verdict:


Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
36	5180	19.80
44	5220	19.87
48	5240	19.65
52	5260	19.45
60	5300	19.71
64	5320	19.73
100	5500	24.81
120	5600	33.67
144	5720	30.03
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
144	5720	16.26
149	5745	16.04
157	5785	16.19
165	5825	16.31




B.Test Plot:




(Channel 36, 5180MHz, 802.11a)




(Channel 44, 5220 MHz, 802.11a)




(Channel 48, 5240MHz, 802.11a)




(Channel 52, 5260MHz, 802.11a)




(Channel 60, 5300 MHz, 802.11a)




(Channel 64, 5320MHz, 802.11a)




(Channel 100,5500MHz, 802.11a)




(Channel 120, 5600 MHz, 802.11a)




(Channel 144, 5720MHz, 802.11a)




(Channel 144, 5720MHz, 802.11a)



(Channel 149,5745MHz, 802.11a)



(Channel 157,5785MHz, 802.11a)



(Channel 165, 5825MHz, 802.11a)



802.11n (HT20) Mode


A.Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
36	5180	20.30
44	5220	20.19
48	5240	20.43
52	5260	20.70
60	5300	20.84
64	5320	20.20
100	5500	29.96
120	5600	31.86
144	5720	31.79
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
144	5720	15.40
149	5745	17.25
157	5785	14.69
165	5825	15.50


B.Test Plot:




(Channel 36, 5180MHz, 802.11n (HT20))




(Channel 44, 5220MHz, 802.11n (HT20))




(Channel 48, 5240MHz, 802.11n (HT20))




(Channel 52, 5260MHz, 802.11n (HT20))




(Channel 60, 5300MHz, 802.11n (HT20))




(Channel 64, 5320MHz, 802.11n (HT20))




(Channel 100, 5500MHz, 802.11n (HT20))




(Channel 120, 5600MHz, 802.11n (HT20))




(Channel 144, 5720MHz, 802.11n (HT20))




(Channel 144, 5720MHz, 802.11 n (HT20))



(Channel 149, 5745MHz, 802.11 n (HT20))



(Channel 157, 5785MHz, 802.11 n (HT20))



(Channel 165, 5825MHz, 802.11 n (HT20))




802.11n (HT40) Test mode


A.Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
38	5190	39.71
46	5230	39.72
54	5270	39.88
62	5310	40.14
102	5510	59.96
126	5630	68.15
142	5710	67.41
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
142	5710	35.21
151	5755	35.20
159	5795	34.23


B.Test Plot:




(Channel 38, 5190MHz, 802.11n (HT40))




(Channel 46, 5230MHz, 802.11n (HT40))




(Channel 54, 5270MHz, 802.11n (HT40))



(Channel 62, 5310MHz, 802.11n (HT40))




(Channel 102, 5510MHz, 802.11n (HT40))




(Channel 126, 5630MHz, 802.11n (HT40))



(Channel 142, 5710MHz, 802.11n (HT40))



(Channel 142, 5710MHz, 802.11n (HT40))



(Channel 151, 5755MHz, 802.11n (HT40))



(Channel 159, 5795MHz, 802.11n (HT40))




802.11ac (VHT20) Mode


A.Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
36	5180	20.27
44	5220	20.11
48	5240	20.10
52	5260	20.31
60	5300	20.30
64	5320	20.61
100	5500	30.87
120	5600	30.84
144	5720	29.80
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
144	5720	15.49
149	5745	17.58
157	5785	16.97
165	5825	16.92


B.Test Plot:



(Channel 36, 5180MHz, 802.11ac (VHT20))



(Channel 44, 5220MHz, 802.11ac (VHT20))




(Channel 48, 5240MHz, 802.11ac (VHT20))



(Channel 52, 5260MHz, 802.11ac (VHT20))




(Channel 60, 5300MHz, 802.11ac (VHT20))




(Channel 64, 5320MHz, 802.11ac (VHT20))




(Channel 100, 5500MHz, 802.11ac (VHT20))



(Channel 120, 5600MHz, 802.11ac (VHT20))




(Channel 144, 5720MHz, 802.11ac (VHT20))




(Channel 144, 5720MHz, 802.11ac (VHT20))



(Channel 149, 5745MHz, 802.11 ac (VHT20))



(Channel 157, 5785MHz, 802.11 ac (VHT20))



(Channel 165, 5825MHz, 802.11 ac (VHT20))




802.11ac (VHT40) Mode


A.Test Verdict:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
38	5190	39.51
46	5230	39.89
54	5270	40.99
62	5310	39.79
102	5510	62.66
126	5630	68.44
142	5710	68.44
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
142	5710	35.27
151	5755	35.37
159	5795	35.07


B.Test Plot:




(Channel 38, 5190MHz, 802.11ac (VHT40))




(Channel 46, 5230MHz, 802.11ac (VHT40))




(Channel 54, 5270MHz, 802.11ac (VHT40))




(Channel 62, 5310MHz, 802.11ac (VHT40))




(Channel 102, 5510MHz, 802.11ac (VHT40))




(Channel 126, 5630MHz, 802.11ac (VHT40))




(Channel 142, 5710MHz, 802.11ac (VHT40))



(Channel 142, 5710MHz, 802.11ac (VHT40))




(Channel 151, 5755MHz, 802.11ac (VHT40))




(Channel 159, 5795MHz, 802.11ac (VHT40))

**802.11ac (VHT80) Mode****A.Test Verdict:**


Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
42	5210	79.45
58	5290	79.52
106	5530	118.80
122	5610	119.50
138	5690	119.90
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)
138	5690	75.10
155	5775	75.09

B.Test Plot:


(Channel 42, 5210MHz, 802.11ac (VHT80))




(Channel 58, 5290MHz, 802.11ac (VHT80))




(Channel 106, 5530MHz, 802.11ac (VHT80))




(Channel 122, 5610MHz, 802.11ac (VHT80))



(Channel 138, 5690MHz, 802.11ac (VHT80))



(Channel 138, 5690MHz, 802.11ac (VHT80))



(Channel 155, 5775MHz, 802.11ac (VHT80))

2.5. Peak Power Spectral Density

2.5.1. Requirement

(1) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

(3) For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30dBm in any 500kHz band.


If transmitting antennas of directional gain greater than 6dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(4) According to KDB662911D01 Measure-and-sum technique, the conducted emission level (e.g., transmit power or power in specified bandwidth) is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically to determine the total emission level from the device. Summing is performed in units that are directly proportional to power.

(5) According to KDB 662911 D01, the directional gain = $G_{ANT} + 10\log(N_{ANT})$ dBi, where G_{ANT} is the antenna gain in dBi, N_{ANT} is the number of outputs.

2.5.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.



2.5.3.Test Procedure

KDB 789033 Section F) Maximum Power Spectral Density (PSD) Method SA-3 was used in order to prove compliance

- 1) Set span to encompass the entire 26-dB emission bandwidth
- 2) Set RBW = 1MHz. Set VBW $\geq$ 3MHz
- 3) Number of points in sweep $\geq$ 2 Span / RBW. Sweep time = auto
- 4) Detector = Average
- 5) Trace mode=Max hold
- 6) Record the max value

2.5.4.Test Result


802.11a Mode

A.Test Verdict:


Frequency (MHz)	Measured PPSD (dBm/MHz)		Duty Factor	Corrected PPSD (dBm/MHz)		Limit (dBm/MHz)	Verdict
	ANT0	ANT1		ANT0	ANT1		
5180	4.89	3.54	0.58	5.47	4.12	11	PASS
5220	5.56	3.63		6.14	4.21		
5240	5.88	3.36		6.46	3.94		
5260	5.86	4.65		6.44	5.23		
5300	6.27	4.87		6.85	5.45		
5320	6.38	4.84		6.96	5.42		
5500	7.27	5.68		7.85	6.26		
5600	7.35	5.78		7.93	6.36		
5720	6.89	6.35		7.47	6.93		
Frequency (MHz)	Measured PPSD (dBm/500KHz)		Duty Factor	Total PPSD (dBm/500KHz)		Limit (dBm/500KHz)	Verdict
	ANT0	ANT1		ANT0	ANT1		
5720	4.10	3.58	0.58	4.68	4.16	30	PASS
5745	5.08	4.79		5.66	5.37		
5785	5.39	5.01		5.97	5.59		
5825	5.65	4.87		6.23	5.45		




B.Test Plot:




(Channel 36, 5180MHz, 802.11a, ANT0)




(Channel 44, 5220MHz, 802.11a, ANT0)




(Channel 48, 5240MHz, 802.11a, ANT0)




(Channel 52, 5260MHz, 802.11a, ANT0)




(Channel 60, 5300MHz, 802.11a, ANT0)




(Channel 64, 5320MHz, 802.11a, ANT0)




(Channel 100, 5500MHz, 802.11a, ANT0)




(Channel 120, 5600MHz, 802.11a, ANT0)




(Channel 144, 5720MHz, 802.11a, ANT0)




(Channel 144, 5720MHz, 802.11a, ANT0)



(Channel 149, 5745MHz, 802.11a, ANT0)



(Channel 157, 5785MHz, 802.11a, ANT0)



(Channel 165, 5825MHz, 802.11a, ANT0)




802.11n (HT20) Mode

A.Test Verdict:


Frequency (MHz)	Measured PPSD (dBm/MHz)		Duty Factor	Total PPSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
	ANT0	ANT1				
5180	4.04	3.27	0.61	7.29	8.99	PASS
5220	4.93	3.16		7.75		
5240	5.04	3.13		7.81		
5260	5.38	4.30		8.49		
5300	5.63	4.48		8.71		
5320	5.84	4.70		8.93		
5500	5.80	4.56		8.84		
5600	4.93	4.00		8.11		
5720	5.05	3.94		8.15		
Frequency (MHz)	Measured PPSD (dBm/500KHz)		Duty Factor	Total PPSD (dBm/500KHz)	Limit (dBm/500KHz)	Verdict
	ANT0	ANT1				
5720	4.01	3.41	0.61	7.34	27.99	PASS
5745	4.79	4.23		8.14		
5785	5.25	4.57		8.54		
5825	5.52	4.92		8.85		
Note: Directional gain = 5.00dBi +10log(2) = 8.01dBi>6dBi, so the limit shall be reduced to 11-(8.01-6) = 8.99dBm for 5.18-5.24 GHz band and reduced to 30-(8.01-6) = 27.99dBm for 5.745-5.825 GHz band.						




B.Test Plot:




(Channel 36, 5180MHz, 802.11n (HT20), ANT0)




(Channel 44, 5220MHz, 802.11n (HT20), ANT0)




(Channel 48, 5240MHz, 802.11n (HT20), ANT0)




(Channel 52, 5260MHz, 802.11n (HT20), ANT0)




(Channel 60, 5300MHz, 802.11n (HT20), ANT0)




(Channel 64, 5320MHz, 802.11n (HT20), ANT0)




(Channel 100, 5500MHz, 802.11n (HT20), ANT0)




(Channel 120, 5600MHz, 802.11n (HT20), ANT0)




(Channel 144, 5720MHz, 802.11n (HT20), ANT0)




(Channel 144, 5720MHz, 802.11n (HT20), ANT0)



(Channel 149, 5745MHz, 802.11n (HT20), ANT0)



(Channel 157, 5785MHz, 802.11n (HT20), ANT0)




(Channel 165, 5825MHz, 802.11n (HT20), ANT0)


**802.11n (HT40) Mode****A.Test Verdict:**

Frequency (MHz)	Measured PPSD (dBm/MHz)		Duty Factor	Total PPSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
	ANT0	ANT1				
5190	0.90	-0.18	1.22	4.62	8.99	PASS
5230	1.67	-0.29		5.03		
5270	2.00	0.90		5.72		
5310	2.31	1.06		5.96		
5510	3.03	2.07		6.81		
5630	3.49	2.61		7.30		
5710	3.00	2.67		7.07		
Frequency (MHz)	Measured PPSD (dBm/500KHz)		Duty Factor	Total PPSD (dBm/500KHz)	Limit (dBm/500KHz)	Verdict
	ANT0	ANT1				
5710	0.15	-0.24	1.22	4.19	27.99	PASS
5755	1.21	0.80		5.24		
5795	1.63	0.80		5.47		
Note: Directional gain = 5.00dBi +10log(2) = 8.01dBi>6dBi, so the limit shall be reduced to 11-(8.01-6) = 8.99dBm for 5.18-5.24 GHz band and reduced to 30-(8.01-6) = 27.99dBm for 5.745-5.825 GHz band.						


B.Test Plot:




(Channel 38, 5190MHz, 802.11n (HT40), ANT0)




(Channel 46, 5230MHz, 802.11n (HT40), ANT0)




(Channel 54, 5270MHz, 802.11n (HT40), ANT0)




(Channel 62, 5310MHz, 802.11n (HT40), ANT0)




(Channel 102, 5510MHz, 802.11n (HT40), ANT0)




(Channel 126, 5630 MHz, 802.11n (HT40), ANT0)




(Channel 142, 5710MHz, 802.11n (HT40), ANT0)



(Channel 142, 5710MHz, 802.11n (HT40), ANT0)



(Channel 151, 5755MHz, 802.11n (HT40), ANT0)



(Channel 159, 5795MHz, 802.11n (HT40), ANT0)




802.11ac (VHT20) Mode

A.Test Verdict:


Frequency (MHz)	Measured PPSD (dBm/MHz)		Duty Factor	Total PPSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
	ANT0	ANT1				
5180	4.68	3.39	0.62	7.71	8.99	PASS
5220	5.15	3.32		7.96		
5240	5.50	3.07		8.08		
5260	5.56	4.34		8.62		
5300	5.93	4.53		8.92		
5320	5.86	4.68		8.94		
5500	5.12	4.43		8.42		
5600	5.40	4.44		8.58		
5720	5.68	4.63		8.82		
Frequency (MHz)	Measured PPSD (dBm/500KHz)		Duty Factor	Total PPSD (dBm/500KHz)	Limit (dBm/500KHz)	Verdict
	ANT0	ANT1				
5720	3.97	1.79	0.62	6.65	27.99	PASS
5745	4.83	4.24		8.18		
5785	5.13	4.64		8.52		
5825	5.20	4.77		8.62		
Note: Directional gain = 5.00dBi +10log(2) = 8.01dBi>6dBi, so the limit shall be reduced to 11-(8.01-6) = 8.99dBm for 5.18-5.24 GHz band and reduced to 30-(8.01-6) = 27.99dBm for 5.745-5.825 GHz band.						




B.Test Plot:




(Channel 36, 5180MHz, 802.11ac (VHT20), ANT0)




(Channel 44, 5220MHz, 802.11ac (VHT20), ANT0)




(Channel 48, 5240MHz, 802.11ac (VHT20), ANT0)




(Channel 52, 5260MHz, 802.11ac (VHT20), ANT0)




(Channel 60, 5300MHz, 802.11ac (VHT20), ANT0)




(Channel 64, 5320MHz, 802.11ac (VHT20), ANT0)




(Channel 100, 5500MHz, 802.11ac (VHT20), ANT0)




(Channel 120, 5600MHz, 802.11ac (VHT20), ANT0)




(Channel 144, 5720MHz, 802.11ac (VHT20), ANT0)




(Channel 144, 5720MHz, 802.11ac(VHT20), ANT0)



(Channel 149, 5745MHz, 802.11ac (VHT20), ANT0)



(Channel 157, 5785MHz, 802.11ac (VHT20), ANT0)




(Channel 165, 5825MHz, 802.11ac (VHT20), ANT0)


**802.11ac (VHT40) Mode****A.Test Verdict:**

Frequency (MHz)	Measured PPSD (dBm/MHz)		Duty Factor	Total PPSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
	ANT0	ANT1				
5190	0.56	-1.13	1.17	3.98	8.99	PASS
5230	1.38	-1.20		4.46		
5270	1.95	-0.05		5.24		
5310	4.11	0.37		6.81		
5510	4.53	1.49		7.45		
5630	3.17	2.22		6.90		
5710	3.12	2.35		6.93		
Frequency (MHz)	Measured PPSD (dBm/500KHz)		Duty Factor	Total PPSD (dBm/500KHz)	Limit (dBm/500KHz)	Verdict
	ANT0	ANT1				
5710	0.13	-0.66	1.17	3.93	27.99	PASS
5755	1.11	0.51		5.00		
5795	1.38	0.79		5.28		
Note: Directional gain = 5.00dBi +10log(2) = 8.01dBi>6dBi, so the limit shall be reduced to 11-(8.01-6) = 8.99dBm for 5.18-5.24 GHz band and reduced to 30-(8.01-6) = 27.99dBm for 5.745-5.825 GHz band.						


B.Test Plot:




(Channel 38, 5190MHz, 802.11ac (VHT40), ANT0)




(Channel 46, 5230MHz, 802.11ac (VHT40), ANT0)




(Channel 54, 5270MHz, 802.11ac (VHT40), ANT0)




(Channel 62, 5310MHz, 802.11ac (VHT40), ANT0)




(Channel 102, 5510MHz, 802.11ac (VHT40), ANT0)




(Channel 126, 5630MHz, 802.11ac (VHT40), ANT0)




(Channel 142, 5710MHz, 802.11ac (VHT40), ANT0)



(Channel 142, 5710MHz, 802.11ac (VHT40), ANT0)



(Channel 151, 5755MHz, 802.11ac (VHT40), ANT0)



(Channel 159, 5795MHz, 802.11ac (VHT40), ANT0)




802.11ac (VHT80) Mode

A.Test Verdict:

Frequency (MHz)	Measured PPSD (dBm/MHz)		Duty Factor	Total PPSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
	ANT0	ANT1				
5210	-1.82	-4.82	3.14	3.08	8.99	PASS
5290	-0.81	-3.50		4.20		
5530	-0.21	-2.46		4.96		
5610	-0.19	-1.76		5.25		
5690	-0.20	-1.09		5.53		
Frequency (MHz)	Measured PPSD (dBm/500KHz)		Duty Factor	Total PPSD (dBm/500KHz)	Limit (dBm/500KHz)	Verdict
	ANT0	ANT1				
5690	-2.96	-3.50	3.14	2.93	27.99	PASS
5775	-2.03	-1.92		4.18		

Note: Directional gain = 5.01dBi + 10log(2) = 8.01dBi > 6dBi, so the limit shall be reduced to 11-(8.01-6) = 8.99dBm for 5.18-5.24 GHz band and reduced to 30-(8.01-6) = 27.99dBm for 5.745-5.825 GHz band.

B.Test Plot:



(Channel 42, 5210MHz, 802.11ac (VHT80), ANT0)