

TEST REPORT

Applicant Name : Sam Radios Ltd.
Address : No.18 Daxiamei Industrial Park, Nan'an, Quanzhou, Fujian, 362300, China
Report Number : XMTN1220517-21002E-01A
FCC ID: 2AGPQ-GMRS1

Test Standard (s)

FCC PART 15B

Sample Description

Product Type: GMRS RADIO
Model No.: FT-28
Trade Mark: N/A
Date Received: 2022-05-17
Date of Test: 2022-05-24 to 2022-05-27
Report Date: 2022-06-21

Test Result:	Pass*
--------------	-------


* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:



Black Ding
EMC Engineer

Approved By:



Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk ★.

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk **. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
OBJECTIVE.....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY.....	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
JUSTIFICATION	5
EUT EXERCISE SOFTWARE	5
SPECIAL ACCESSORIES	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
BLOCK DIAGRAM OF RADIATED TEST SETUP.....	6
SUMMARY OF TEST RESULTS.....	7
TEST EQUIPMENT LIST	8
FCC §15.107 – CONDUCTED EMISSIONS	9
APPLICABLE STANDARD	9
EUT SETUP.....	9
EMI TEST RECEIVER SETUP.....	9
TEST PROCEDURE	10
FACTOR & OVER LIMIT CALCULATION.....	10
TEST DATA	10
FCC §15.109 - RADIATED EMISSIONS	17
APPLICABLE STANDARD	17
EUT SETUP.....	17
EMI TEST RECEIVER SETUP.....	18
TEST PROCEDURE	18
FACTOR & OVER LIMIT CALCULATION.....	18
TEST DATA	19
FCC §15.111 - ANTENNA CONDUCTED POWER FOR RECEIVERS.....	32
APPLICABLE STANDARD	32
EUT SETUP.....	32
TEST PROCEDURE	32
TEST DATA	32

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	GMRS RADIO
Tested Model	FT-28
Frequency Range	462.5500-467.725MHz(Receiver/Scan)
Voltage Range	DC 3.7V from battery or DC 5V from USB port
Sample number	XMTN1220517-21002E-RF-S1 (Assigned by ATC)
Sample/EUT Status	Good condition
Adapter information	Model: AS011Z-0501000UU; Input: 100-240V~50/60Hz, 0.45A; Output: 5.0V1.0A

Objective

This report is in accordance with Part 2-Subpart J, and Part 15-Subparts A and B of the Federal Communication Commission's rules.

The objective of the manufacturer is to determine the compliance of EUT with FCC Part 15, Class B device.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter	Uncertainty	
Occupied Channel Bandwidth	5%	
RF Frequency	0.082*10 ⁻⁷	
RF output power, conducted	0.73dB	
Unwanted Emission, conducted	1.6dB	
AC Power Lines Conducted Emissions	2.72dB	
Emissions, Radiated	9kHz - 30MHz	2.66dB
	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
	26.5GHz - 40GHz	4.72dB
Temperature	1 °C	
Humidity	6%	
Supply voltages	0.4%	

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189.

Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 4297.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

Test mode 1: Charging + Scanning

Test mode 2: Charging + Receiver at 462.6375MHz

Test mode 3: Charging + Receiver at 467.6375MHz

EUT Exercise Software

No exercise software.

Special Accessories

No special accessory was used.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Unknown	Earphone	Unknown	Unknown
AGILENT	Vector Signal Generator	N5182A	MY50143401

External I/O Cable


Cable Description	Length (m)	From/Port	To
Un-shielding Un-Detachable USB Cable	1.0	Adapter	EUT
Audio Cable	1.2	EUT	Earphone

Block Diagram of Radiated Test Setup

For conducted emission:



For Radiated emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	Conducted Emissions	Compliant
§15.109	Radiated Emissions	Compliant
§15.111	Antenna Conducted Power for receivers	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted emission					
Rohde & Schwarz	EMI Test Receiver	ESCI	100784	2021/12/13	2022/12/12
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2021/12/13	2022/12/12
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2021/12/13	2022/12/12
Unknown	RF Coaxial Cable	No.17	N0350	2021/12/14	2022/12/13
AGILENT	Vector Signal Generator	N5182A	MY50143401	2021/12/13	2022/12/12
Conducted Emission Test Software: e3 19821b (V9)					
Radiated Emissions Test					
Rohde & Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
Rohde & Schwarz	Spectrum Analyzer	FSV40	101949	2021/12/13	2022/12/12
A.H. Systems, inc.	Preamplifier	PAM-0118P	531	2021/11/09	2022/11/08
SONOMA INSTRUMENT	Amplifier	310 N	186131	2021/11/09	2022/11/08
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Bilog Antenna	VULB9163	9163-194	2020/01/05	2023/01/04
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-655	2020/01/05	2023/01/04
AGILENT	Vector Signal Generator	N5182A	MY50143401	2021/12/13	2022/12/12
Unknown	RF Coaxial Cable	No.10	N050	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
Radiated Emission Test Software: e3 19821b(V9)					
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2021/12/13	2022/12/12
AGILENT	Vector Signal Generator	N5182A	MY50143401	2021/12/13	2022/12/12
Unknown	RF Coaxial Cable	No.33	RF-03	Each time	


* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.107 – CONDUCTED EMISSIONS

Applicable Standard

According to FCC§15.107

EUT Setup



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.4-2014. The related limit was specified in FCC Part 15.107 Class B.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\text{Over Limit} = \text{Level} - \text{Limit}$$


$$\text{Level} = \text{Read Level} + \text{Factor}$$

Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	50 %
ATM Pressure:	101.1 kPa

The testing was performed by Jason Liu on 2022-05-24.

Test mode 1: Charging + Scanning**AC 120V/60Hz, Line:**

Site : Shielding Room

Condition: Line


Job No. : XMTN1220517-21002E-RF

Mode : Charging + Scanning

Power : AC 120V 60Hz


Freq	Factor	Read		Limit		Over	Remark
		MHz	dB	Level	dBuV	Line	dB
1	0.152	9.80	30.92	40.72	55.87	-15.15	Average
2	0.152	9.80	43.27	53.07	65.87	-12.80	QP
3	0.181	9.80	20.98	30.78	54.46	-23.68	Average
4	0.181	9.80	32.52	42.32	64.46	-22.14	QP
5	0.412	9.80	17.31	27.11	47.60	-20.49	Average
6	0.412	9.80	32.39	42.19	57.60	-15.41	QP
7	0.530	9.81	13.71	23.52	46.00	-22.48	Average
8	0.530	9.81	25.44	35.25	56.00	-20.75	QP
9	2.757	9.83	6.45	16.28	46.00	-29.72	Average
10	2.757	9.83	18.32	28.15	56.00	-27.85	QP
11	24.708	10.05	7.97	18.02	50.00	-31.98	Average
12	24.708	10.05	15.53	25.58	60.00	-34.42	QP

AC 120V/60Hz, Neutral:



Site : Shielding Room
Condition: Neutral
Job No. : XMTN1220517-21002E-RF
Mode : Charging + Scanning
Power : AC 120V 60Hz


	Freq	Read	Limit	Over		
	MHz	dB	dBuV	dBuV	Line Limit	Remark
1	0.163	9.80	27.21	37.01	55.32	-18.31 Average
2	0.163	9.80	39.39	49.19	65.32	-16.13 QP
3	0.200	9.80	22.58	32.38	53.62	-21.24 Average
4	0.200	9.80	34.26	44.06	63.62	-19.56 QP
5	0.333	9.80	15.70	25.50	49.38	-23.88 Average
6	0.333	9.80	27.72	37.52	59.38	-21.86 QP
7	0.891	9.81	15.83	25.64	46.00	-20.36 Average
8	0.891	9.81	24.76	34.57	56.00	-21.43 QP
9	2.271	9.82	11.13	20.95	46.00	-25.05 Average
10	2.271	9.82	22.57	32.39	56.00	-23.61 QP
11	24.545	10.15	9.08	19.23	50.00	-30.77 Average
12	24.545	10.15	14.39	24.54	60.00	-35.46 QP

Test mode 2: Charging + Receiver at 462.6375MHz**AC 120V/60Hz, Line:**

Site : Shielding Room
Condition: Line
Job No. : XMTN1220517-21002E-RF
Mode : Charging + Receiver at 462.6375MHz
Power : AC 120V 60Hz


Freq	Factor	Read		Limit		Over	Remark
		MHz	dB	dBuV	dBuV	Line	
1	0.167	9.80	22.65	32.45	55.11	-22.66	Average
2	0.167	9.80	32.57	42.37	65.11	-22.74	QP
3	0.282	9.80	19.74	29.54	50.77	-21.23	Average
4	0.282	9.80	29.33	39.13	60.77	-21.64	QP
5	0.457	9.80	24.48	34.28	46.75	-12.47	Average
6	0.457	9.80	33.24	43.04	56.75	-13.71	QP
7	0.666	9.81	16.28	26.09	46.00	-19.91	Average
8	0.666	9.81	25.31	35.12	56.00	-20.88	QP
9	2.668	9.83	13.99	23.82	46.00	-22.18	Average
10	2.668	9.83	25.08	34.91	56.00	-21.09	QP
11	19.596	10.00	25.58	35.58	50.00	-14.42	Average
12	19.596	10.00	31.37	41.37	60.00	-18.63	QP

AC 120V/60Hz, Neutral:



Site : Shielding Room
Condition: Neutral
Job No. : XMTN1220517-21002E-RF
Mode : Charging + Receiver at 462.6375MHz
Power : AC 120V 60Hz


Freq	Factor	Read		Limit		Over	Remark
		MHz	dB	dBuV	dBuV	Line	dB
1	0.162	9.80	21.83	31.63	55.37	-23.74	Average
2	0.162	9.80	33.64	43.44	65.37	-21.93	QP
3	0.200	9.80	18.52	28.32	53.61	-25.29	Average
4	0.200	9.80	28.05	37.85	63.61	-25.76	QP
5	0.402	9.80	25.14	34.94	47.81	-12.87	Average
6	0.402	9.80	33.68	43.48	57.81	-14.33	QP
7	0.562	9.81	19.07	28.88	46.00	-17.12	Average
8	0.562	9.81	28.11	37.92	56.00	-18.08	QP
9	2.662	9.83	12.68	22.51	46.00	-23.49	Average
10	2.662	9.83	25.67	35.50	56.00	-20.50	QP
11	18.438	10.08	24.56	34.64	50.00	-15.36	Average
12	18.438	10.08	29.38	39.46	60.00	-20.54	QP

Test mode 3: Charging + Receiver at 467.6375MHz**AC 120V/60Hz, Line:**

Site : Shielding Room
 Condition: Line
 Job No. : XMTN1220517-21002E-RF
 Mode : Charging + Receiver at 467.6375MHz
 Power : AC 120V 60Hz

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB	dBuV	dBuV		
1	0.163	9.80	23.41	33.21	55.32	-22.11	Average
2	0.163	9.80	34.19	43.99	65.32	-21.33	QP
3	0.200	9.80	18.30	28.10	53.61	-25.51	Average
4	0.200	9.80	30.21	40.01	63.61	-23.60	QP
5	0.398	9.80	16.10	25.90	47.89	-21.99	Average
6	0.398	9.80	32.18	41.98	57.89	-15.91	QP
7	0.668	9.81	16.79	26.60	46.00	-19.40	Average
8	0.668	9.81	25.97	35.78	56.00	-20.22	QP
9	2.668	9.83	14.31	24.14	46.00	-21.86	Average
10	2.668	9.83	25.80	35.63	56.00	-20.37	QP
11	19.622	10.00	24.78	34.78	50.00	-15.22	Average
12	19.622	10.00	31.67	41.67	60.00	-18.33	QP

AC 120V/60Hz, Neutral:



Site : Shielding Room
Condition: Neutral
Job No. : XMTN1220517-21002E-RF
Mode : Charging + Receiver at 467.6375MHz
Power : AC 120V 60Hz

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB	dBuV	dBuV	Line	Limit
1	0.155	9.80	19.33	29.13	55.71	-26.58	Average
2	0.155	9.80	30.56	40.36	65.71	-25.35	QP
3	0.203	9.80	18.79	28.59	53.50	-24.91	Average
4	0.203	9.80	28.30	38.10	63.50	-25.40	QP
5	0.402	9.80	25.03	34.83	47.80	-12.97	Average
6	0.402	9.80	33.71	43.51	57.80	-14.29	QP
7	0.561	9.81	18.28	28.09	46.00	-17.91	Average
8	0.561	9.81	27.45	37.26	56.00	-18.74	QP
9	2.666	9.83	13.92	23.75	46.00	-22.25	Average
10	2.666	9.83	25.40	35.23	56.00	-20.77	QP
11	18.475	10.08	24.38	34.46	50.00	-15.54	Average
12	18.475	10.08	29.06	39.14	60.00	-20.86	QP


FCC §15.109 - RADIATED EMISSIONS

Applicable Standard


FCC §15.109

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 5 GHz.

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	120 kHz	300 kHz	120kHz	QP
Above 1 GHz	1MHz	3 MHz	/	Peak
	1MHz	10Hz	/	AV

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz, Peak and average detection mode above 1 GHz.

If the maximized peak measured value complies with the limit, then it is unnecessary to perform QP/Average measurement.

Factor & Over Limit Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Over Limit} = \text{Level} - \text{Limit}$$

$$\text{Level} = \text{Reading} + \text{Factor}$$

Test Data

Environmental Conditions

Temperature:	25°C
Relative Humidity:	59 %
ATM Pressure:	101.0 kPa


The testing was performed by Level Li on 2022-05-27.

Note: Pre-scan in the X, Y and Z axes of orientation, the worst case Y-axis of orientation was recorded.

30MHz-1GHz:

Test mode 1: Charging + Scanning

Horizontal:



Site : chamber


Condition: 3m HORIZONTAL

Job No. : XMTN1220429-17465E-RF

Test Mode: Charging+Scanning

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	55.585	-10.23	44.67	34.44	40.00	-5.56	QP
2	61.024	-11.04	43.13	32.09	40.00	-7.91	QP
3	89.472	-14.16	49.12	34.96	43.50	-8.54	Peak
4	157.421	-14.61	49.99	35.38	43.50	-8.12	Peak
5	242.632	-10.74	49.01	38.27	46.00	-7.73	Peak
6	275.519	-9.87	46.77	36.90	46.00	-9.10	Peak

Vertical




Site : chamber

Condition: 3m VERTICAL

Job No. : XMTN1220429-17465E-RF

Test Mode: Charging+Scanning

	Freq	Read Factor	Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	31.180	-12.27	49.04	36.77	40.00	-3.23	QP
2	52.876	-10.15	46.50	36.35	40.00	-3.65	QP
3	89.433	-14.17	50.38	36.21	43.50	-7.29	Peak
4	146.566	-15.47	50.87	35.40	43.50	-8.10	Peak
5	170.868	-13.49	47.59	34.10	43.50	-9.40	Peak
6	276.729	-9.79	44.78	34.99	46.00	-11.01	Peak

Test mode 2: Charging + Receiver at 462.6375MHz**Horizontal:**

Site : chamber


Condition: 3m HORIZONTAL

Job No. : XMTN1220429-17465E-RF

Test Mode: Charging+Receirer at 462.6375

	Freq	Read Factor	Level	Limit Level	Line Limit	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	31.166	-12.27	37.82	25.55	40.00	-14.45	Peak
2	55.585	-10.23	43.20	32.97	40.00	-7.03	QP
3	89.472	-14.16	48.12	33.96	43.50	-9.54	Peak
4	157.421	-14.61	51.99	37.38	43.50	-6.12	Peak
5	242.632	-10.74	50.01	39.27	46.00	-6.73	Peak
6	275.519	-9.87	47.77	37.90	46.00	-8.10	Peak

Vertical



Site : chamber

Condition: 3m VERTICAL


Job No. : XMTN1220429-17465E-RF

Test Mode: Charging+Receirer at 462.6375

	Freq	Read Factor	Level	Limit Level	Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	31.180	-12.27	51.00	38.73	40.00	-1.27	QP
2	32.520	-12.09	47.20	35.11	40.00	-4.89	QP
3	52.876	-10.15	47.41	37.26	40.00	-2.74	QP
4	89.433	-14.17	51.38	37.21	43.50	-6.29	Peak
5	146.566	-15.47	52.87	37.40	43.50	-6.10	Peak
6	276.729	-9.79	45.78	35.99	46.00	-10.01	Peak

Test mode 3: Charging + Receiver at 467.6375MHz

Horizontal:



Site : chamber


Condition: 3m HORIZONTAL

Job No. : XMTN1220429-17465E-RF

Test Mode: Charging+Receirer at 467.6375

	Freq	Read Factor	Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	59.806	-10.55	42.64	32.09	40.00	-7.91	QP
2	73.424	-15.94	46.75	30.81	40.00	-9.19	Peak
3	92.544	-13.14	47.33	34.19	43.50	-9.31	Peak
4	157.766	-14.54	50.81	36.27	43.50	-7.23	Peak
5	243.377	-10.69	48.75	38.06	46.00	-7.94	Peak
6	274.916	-9.92	48.59	38.67	46.00	-7.33	Peak

Vertical




Site : chamber

Condition: 3m VERTICAL

Job No. : XMTN1220429-17465E-RF

Test Mode: Charging+Receirer at 467.6375

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	31.234	-12.27	50.21	37.94	40.00	-2.06	QP
2	32.605	-12.08	47.17	35.09	40.00	-4.91	QP
3	52.992	-10.17	46.40	36.23	40.00	-3.77	QP
4	93.727	-12.77	48.71	35.94	43.50	-7.56	QP
5	148.051	-15.38	52.55	37.17	43.50	-6.33	Peak
6	275.640	-9.86	46.31	36.45	46.00	-9.55	Peak

Above 1 GHz:**Test mode 1: Charging + Scanning****Horizontal:**


Site : chamber

Condition: 3m HORIZONTAL

Job No. : XMTN1220517-21002E-RF

Test Mode: Charging+Scanning

	Freq	Read Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1825.400	-8.56	38.56	30.00	74.00	-44.00	Peak
2	4998.000	-2.90	37.85	34.95	74.00	-39.05	Peak
3	9325.000	6.00	40.24	46.24	74.00	-27.76	Peak

Vertical


Site : chamber

Condition: 3m VERTICAL

Job No. : XMTN1220517-21002E-RF

Test Mode: Charging+Scanning

Freq	Factor	Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 1345.000	-10.04	38.26	28.22	74.00	-45.78 Peak
2 3149.533	-5.86	40.28	34.42	74.00	-39.58 Peak
3 5752.000	-1.89	43.52	41.63	74.00	-32.37 Peak

Test mode 2: Charging + Receiver at 462.6375MHz**Horizontal:**


Site : chamber

Condition: 3m HORIZONTAL

Job No. : XMTN1220517-21002E-RF

Test Mode: Charging+Receiver at 462.6375

	Freq	Read Factor	Level	Limit Level	Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2275.000	-7.24	37.66	30.42	74.00	-43.58	Peak
2	5410.000	-2.29	40.57	38.28	74.00	-35.72	Peak
3	10352.500	8.10	38.27	46.37	74.00	-27.63	Peak

Vertical


Site : chamber

Condition: 3m VERTICAL

Job No. : XMTN1220517-21002E-RF

Test Mode: Charging+Receiver at 462.6375

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
1	1654.000	-9.06	37.49	28.43	74.00	-45.57	Peak
2	3149.500	-5.86	39.53	33.67	74.00	-40.33	Peak
3	5854.000	-1.82	42.38	40.56	74.00	-33.44	Peak

Test mode 3: Charging + Receiver at 467.6375MHz**Horizontal:**


Site : chamber

Condition: 3m HORIZONTAL

Job No. : XMTN1220517-21002E-RF

Test Mode: Charging+Receiver at 467.6375

	Freq	Read Factor	Limit Level	Limit Line	Over dB	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	1160.500	-10.30	36.99	26.69	74.00	-47.31 Peak
2	2272.000	-7.23	36.85	29.62	74.00	-44.38 Peak
3	6929.500	2.06	42.17	44.23	74.00	-29.77 Peak

Vertical

Site : chamber

Condition: 3m VERTICAL

Job No. : XMTN1220517-21002E-RF

Test Mode: Charging+Receiver at 467.6375

	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1225.000	-10.19	36.27	26.08	74.00	-47.92	Peak
2	3359.500	-6.00	40.00	34.00	74.00	-40.00	Peak
3	8078.500	4.42	38.17	42.59	74.00	-31.41	Peak

FCC §15.111 - ANTENNA CONDUCTED POWER FOR RECEIVERS

Applicable Standard


FCC §15.111

Limit

The antenna conducted power of the receiver as defined in §15.111 shall not exceed the values given in the following tables

Frequency Range	Limit
9 kHz to 5 GHz	2.0 nW (-57 dBm)

EUT Setup



Test Procedure


1. The receiver antenna terminal connected to a spectrum analyzer.
2. The test data of the worst case condition (mode 2) was reported on the following Data page.

Test Data


Environmental Conditions

Temperature:	24 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Cat Kang on 2022-05-24.


Test mode 1: Charging + Scanning**Conducted Measurement (9 kHz to 150 kHz)**

Date: 24.MAY.2022 08:59:45

Conducted Measurement (150 kHz to 30MHz)


Date: 24.MAY.2022 08:59:30

Conducted Measurement (30MHz to 1GHz)




Date: 24.MAY.2022 08:59:15


Conducted Measurement (1GHz to 5GHz)



Date: 24.MAY.2022 08:58:59


Test mode 2: Charging + Receiver at 462.6375MHz**Conducted Measurement (9 kHz to 150 kHz)**

Date: 24.MAY.2022 09:01:24

Conducted Measurement (150 kHz to 30MHz)


Date: 24.MAY.2022 09:01:09

Conducted Measurement (30MHz to 1GHz)





Date: 24.MAY.2022 09:00:54


Conducted Measurement (1GHz to 5GHz)



Date: 24.MAY.2022 09:00:39


Test mode 3: Charging + Receiver at 467.6375MHz**Conducted Measurement (9 kHz to 150 kHz)****Conducted Measurement (150 kHz to 30MHz)**

Conducted Measurement (30MHz to 1GHz)



Date: 24.MAY.2022 09:02:32

Conducted Measurement (1GHz to 5GHz)



Date: 24.MAY.2022 09:02:17

*****END OF REPORT*****