

#### Shenzhen Huatongwei International Inspection Co., Ltd.

1/F,Bldg 3,Hongfa Hi-tech Industrial Park,Genyu Road,Tianliao,Gongming,Shenzhen,China Phone:86-755-26748019 Fax:86-755-26748089 http://www.szhtw.com.cn



# **TEST REPORT**

**Report Reference No.....: TRE1511016203** R/C.....: 87232

FCC ID.....: 2AGRP-G716

Applicant's name.....: Distribuidora Bridge Comm, C.A.

Caracas. Venezuela

Manufacturer...... SINTAVE TECHNOLOGY (GROUP) CO.,LTD

Address...... Sang Tai Technology Park,Liuxiandong,Xili,NanShan

District, Shen Zhen City, Guangdong Province, China

Test item description .....: 3G Mobile Phone

Trade Mark ...... Digitel

Model/Type reference...... G716

Listed Model(s) ..... ---

Standard .....: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of receipt of test sample............ Nov 26,2015

Date of issue...... Dec 07,2015

Result...... PASS

Compiled by

( position+printedname+signature)...: File administrators Candy Liu

Supervised by

(position+printedname+signature)....: Project Engineer Lion Cai

Approved by

(position+printedname+signature)....: RF Manager Hans Hu

Testing Laboratory Name .....: Shenzhen Huatongwei International Inspection Co., Ltd

Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Report No: TRE1511016203 Page: 2 of 47 Issued: 2015-12-07

# Contents

<u>1.</u>	TEST STANDARDS ANDTEST DESCRIPTION	3
_		
1.1.	Test Standards	3
1.2.	Test Description	3
		•
<u>2.</u>	SUMMARY	4
0.4		
2.1.	Client Information	4
2.2.	Product Description	4
2.3.	Operation state	4
2.4.	EUT configuration	5
2.5.	Modifications	5
<u>3.</u>	TEST ENVIRONMENT	6
3.1.	Address of the test laboratory	6
3.2.	Test Facility	6
3.3.	Environmental conditions	7
3.4.	Statement of the measurement uncertainty	7
3.5.	Equipments Used during the Test	8
<u>4.</u>	TEST CONDITIONS AND RESULTS	9
		_
4.1.	Antenna requirement	9
4.2.	Conducted Emission (AC Main)	10
4.3.	Conducted Peak Output Power	13
4.4.	20dB Emission Bandwidth	16
4.5.	Carrier Frequencies Separation	19
4.6.	Hopping Channel Number	21
4.7.	Dwell Time	23
4.8.	Pseudorandom Frequency Hopping Sequence	26
4.9.	Restricted band (radiated)	27
4.10.	Bandedge and Spurious Emission (conducted)	31
4.11.	Spurious Emission (radiated)	41
<u>5.</u>	TEST SETUP PHOTOS OF THE EUT	46
<u>6.</u>	EXTERNAL AND INTERNAL PHOTOS OF THE EUT	47
<u>v.</u>	EXTERNAL AND INTERNAL FIROTOS OF THE LOT	<u> 4 / </u>

Report No: TRE1511016203 Page: 3 of 47 Issued: 2015-12-07

# 1. TEST STANDARDS ANDTEST DESCRIPTION

## 1.1. Test Standards

The tests were performed according to following standards:

<u>FCC Rules Part 15.247</u>: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devicese

# 1.2. Test Description

ReportSection	Test Item	Section in CFR 47	Result
4.1	Antenna Requirement	15.203/15.247 (c)	Pass
4.2	AC Power Line Conducted Emission	15.207	Pass
4.3	Conducted Peak Output Power	15.247 (b)(1)	Pass
4.4	20dB Occupied Bandwidth	15.247 (a)(1)	Pass
4.5	Carrier Frequencies Separation	15.247 (a)(1)	Pass
4.6	Hopping Channel Number	15.247 (a)(1)	Pass
4.7	Dwell Time	15.247 (a)(1)	Pass
4.8	Pseudorandom Frequency Hopping Sequence	15.247(b)(4)&TCB Exclusion List (7 July 2002)	Pass
4.9	Restricted band	15.247(d)/15.205	Pass
4.10/4.11	Radiated Emission	15.247(d)/15.209	Pass

Remark: The measurement uncertainty is not included in the test result.

Report No: TRE1511016203 Page: 4 of 47 Issued: 2015-12-07

# 2. **SUMMARY**

# 2.1. Client Information

Applicant:	Distribuidora Bridge Comm, C.A.	
Address:	4ta transversal de Boleita Sur, Galpon 14-34. Municipio Sucre. Caracas. Venezuela	
Manufacturer:	SINTAVE TECHNOLOGY (GROUP) CO.,LTD	
Address:	Sang Tai Technology Park,Liuxiandong,Xili,NanShan District,ShenZhen City,Guangdong Province,China	

# 2.2. Product Description

Name of EUT	3G Mobile Phone	
Trade Mark:	Digitel	
Model No.:	G716	
Listed Model(s):		
Power supply:	DC 3.7V From internal battery	
Adapter information: Model:G716		
	Input:AC 100-240V 50/60Hz 1.0A	
	Output:5Vd.c., 500mA	
Bluetooth		
Version:	Supported BT2.1+EDR	
Modulation:	GFSK, π/4DQPSK, 8DPSK	
Operation frequency:	2402MHz~2480MHz	
Channel number: 79		
Channel separation: 1MHz		
Antenna type:	enna type: Internal Antenna	
Antenna gain:	0.5dBi	

# 2.3. Operation state

# ◆ <u>Test frequency list</u>

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

Channel	Frequency (MHz)
0	2402
1	2403
:	i :
39	2441
i	i i
77	2479
78	2480

Report No: TRE1511016203 Page: 5 of 47 Issued: 2015-12-07

## **♦** Test mode

For RF test items:

the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions:

the EUT was set to connect with the Bluetooth under large package sizes transmission.

# 2.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer
- O supplied by the lab

0	Power Cable	Length (m):	1
		Shield :	1
		Detachable :	1
0	Multimeter	Manufacturer :	1
		Model No. :	1

## 2.5. Modifications

No modifications were implemented to meet testing criteria.

Report No: TRE1511016203 Page: 6 of 47 Issued: 2015-12-07

# 3. TEST ENVIRONMENT

# 3.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China Phana: 86, 755, 26748010, Favy 86, 755, 26748020

Phone: 86-755-26748019 Fax: 86-755-26748089

## 3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories

(identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: February 28, 2015. Valid time is until February 27, 2018.

#### A2LA-Lab Cert. No. 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for tec hnical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time is until December 31, 2016.

## FCC-Registration No.: 317478

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FC C is maintained in our files. Registration 317478, Renewal date Jul. 18, 2014, valid time is until Jul. 18, 2017.

### IC-Registration No.: 5377A&5377B

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377A on Dec. 31, 2013, valid time is until Dec. 31, 2016.

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377B on Dec.03, 2014, valid time is until Dec.03, 2017.

#### **ACA**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Aust ralian C-Tick mark as a result of our A2LA accreditation.

#### VCCI

The 3m Semi-

anechoic chamber (12.2m×7.95m×6.7m) of Shenzhen Huatongwei International Inspection Co., Ltd.

has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2484. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 29, 2015.

Radiated disturbance above 1GHz measurement of Shenzhen Huatongwei International Inspection Co., Ltd. h as been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-292. Date of Registration: Dec. 24, 2013. Valid time is until Dec. 23, 2016.

Main Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-2726. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 19, 2015.

Telecommunication Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: T-1837. Date of Registration: May 07, 2013. Valid time is until May 06, 2016.

#### DNV

Shenzhen Huatongwei International Inspection Co., Ltd. has been found to comply with the requirements of D NV towards subcontractor of EMC and safety testing services in conjunction with the EMC and Low voltage Di rectives and in the voluntary field. The acceptance is based on a formal quality Audit and follow-ups according to relevant parts of ISO/IEC Guide 17025 (2005), in accordance with the requirements of the D NV Laboratory Quality Manual towards subcontractors. Valid time is until Aug. 24, 2016.

Report No: TRE1511016203 Page: 7 of 47 Issued: 2015-12-07

## 3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
lative Humidity:	30~60 %
Air Pressure:	950~1050mba

## 3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01"Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1"and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongweilaboratory is reported:

Test Items	MeasurementUncertainty	Notes
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	1.60 dB	(1)
Radiated spurious emission 9KHz-40 GHz	2.20 dB	(1)
Conducted Emission 9KHz-30MHz	3.39 dB	(1)
Radiated Emission30~1000MHz	4.24 dB	(1)
Radiated Emissio 1~18GHz	5.16 dB	(1)
Radiated Emissio 18-40GHz	5.54 dB	(1)
Occupied Bandwidth		(1)

<sup>(1)</sup> This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

Report No: TRE1511016203 Page: 8 of 47 Issued: 2015-12-07

# 3.5. Equipments Used during the Test

Cond	Conducted Emission (AC Main)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal	
1	Artificial Mains	Rohde&Schwarz	ESH2-Z5	100028	2015/11/02	
2	EMI Test Receiver	Rohde&Schwarz	ESCI3	100038	2015/11/02	
3	Pulse Limiter	Rohde&Schwarz	ESHSZ2	100044	2015/11/02	
4	EMI Test Software	Rohde&Schwarz	ES-K1 V1.71	N/A	N/A	

Radia	Radiated Emission				
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal
1	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	538	2015/11/02
2	EMI TEST RECEIVER	Rohde&Schwarz	ESI 26	100009	2015/11/02
3	EMI TEST Software	Audix	E3	N/A	N/A
4	TURNTABLE	ETS	2088	2149	N/A
5	ANTENNA MAST	ETS	2075	2346	N/A
6	EMI TEST Software	Rohde&Schwarz	ESK1	N/A	N/A
7	HORNANTENNA	ShwarzBeck	9120D	1011	2015/11/02
8	Amplifer	Sonoma	310N	E009-13	2015/11/02
9	JS amplifer	Rohde&Schwarz	JS4-00101800- 28-5A	F201504	2015/11/02
10	High pass filter	Compliance Direction systems	BSU-6	34202	2015/11/02
11	HORNANTENNA	ShwarzBeck	9120D	1012	2015/11/02
12	Amplifer	Compliance Direction systems	PAP1-4060	120	2015/11/02
13	Loop Antenna	Rohde&Schwarz	HFH2-Z2	100020	2015/11/02
14	TURNTABLE	MATURO	TT2.0		N/A
15	ANTENNA MAST	MATURO	TAM-4.0-P		N/A
16	Horn Antenna	SCHWARZBECK	BBHA9170	25841	2015/11/02
17	ULTRA-BROADBAND ANTENNA	Rohde&Schwarz	HL562	100015	2015/11/02

Maxir	Maximum Peak Output Power / Power Spectral Density / 6dB Bandwidth / Band Edge Compliance of RF					
Emiss	Emission / Spurious RF Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal	
1	Spectrum Analyzer	Rohde&Schwarz	FSP	1164.4391.40	2015/11/02	

The Cal.Interval was one year

Report No: TRE1511016203 Page: 9 of 47 Issued: 2015-12-07

# 4. TEST CONDITIONS AND RESULTS

## 4.1. Antenna requirement

#### Requirement

#### FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of anantenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

## **Test Result:**

The antenna is integralantenna, the best case gain of the antenna is 0.5dBi



Report No: TRE1511016203 Page: 10 of 47 Issued: 2015-12-07

# 4.2. Conducted Emission (AC Main)


#### **LIMIT**

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Fraguenov rongo (MHz)	Limit (dBuV)		
Frequency range (MHz)	Quasi-peak	Average	
0.15-0.5	66 to 56*	56 to 46*	
0.5-5	56	46	
5-30	60	50	

<sup>\*</sup> Decreases with the logarithm of the frequency.

#### **TEST CONFIGURATION**



#### **TEST PROCEDURE**


- The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
- 2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
- 3. The EUT and simulators are connected to the main power through a line impedancestabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for themeasuring equipment.
- 4. The peripheral devices are also connected to the main power through aLISN. (Please refer to the block diagram of the test setup and photographs)
- 5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor,was individually connected through a LISN to the input power source.
- 6. The excess length of the power cord between the EUT and the LISN receptacle were foldedback and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
- 7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHzusing a receiver bandwidth of 9 kHz.

#### **TEST RESULTS**

Report No: TRE1511016203 Page: 11 of 47 Issued: 2015-12-07

Test mode:AC 120V BT Polarization L

#### SCAN TABLE: "Voltage (9K-30M)FIN" Short Description: 150K-30M Voltage



# MEASUREMENT RESULT: "GM120151017\_fin"

12/2/2015 1:	57PM						
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.222000	48.90	10.2	63	13.8	QP	L1	GND
0.276000	46.30	10.2	61	14.6	QP	Ll	GND
2.269500	41.10	10.2	56	14.9	QP	Ll	GND
2.323500	42.60	10.3	56	13.4	QP	Ll	GND
2.373000	43.30	10.3	56	12.7	QP	Ll	GND
2.404500	39.70	10.3	56	16.3	QP	Ll	GND


#### MEASUREMENT RESULT: "GM120151017 fin2"

12/2/2015	1:57PM						
Frequenc M	cy Level Hz dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.44250	30.60	10.2	47	16.4	AV	L1	GND
1.98600	00 29.10	10.2	46	16.9	AV	Ll	GND
2.26500	00 32.50	10.2	46	13.5	AV	Ll	GND
2.31900	00 33.50	10.3	46	12.5	AV	L1	GND
2.42700	00 31.40	10.3	46	14.6	AV	Ll	GND
2.49000	00 26.40	10.3	46	19.6	AV	Ll	GND

Report No: TRE1511016203 Page: 12 of 47 Issued: 2015-12-07

Test mode: AC 120V BT Polarization N

#### SCAN TABLE: "Voltage (9K-30M)FIN" Short Description: 150K-30M Voltage



# MEASUREMENT RESULT: "GM120151018\_fin"

						0PM	12/2/2015 2:0
PE	Line	Detector	Margin dB	Limit dBµV	Transd dB	Level dBµV	Frequency MHz
GND	N	QP	17.3	6.5	10.2	48.00	0.163500
GND	N	QP	16.4	6.3	10.2	46.30	0.222000
GND	N	QP	17.0	61	10.2	43.90	0.276000
GND	N	QP	19.2	60	10.2	40.30	0.330000
GND	N	QP	19.4	56	10.3	36.60	2.373000
GND	N	QP	21.7	56	10.3	34.30	2.377500

#### MEASUREMENT RESULT: "GM120151018 fin2"

12/2/2015							
Frequen M	icy Level Hz dBµV		Limit dBµV	Margin dB	Detector	Line	PE
0.2220	00 29.80	10.2	53	22.9	AV	N	GND
0.2760	00 27.80	10.2	51	23.1	AV	N	GND
0.4380	00 24.10	10.2	47	23.0	AV	N	GND
2.2605	00 24.20	10.2	46	21.8	AV	N	GND
2.3190	00 24.20	10.3	46	21.8	AV	N	GND
2.4270	00 23.40	10.3	46	22.6	AV	N	GND


Report No: TRE1511016203 Page: 13 of 47 Issued: 2015-12-07

# 4.3. Conducted Peak Output Power

# **LIMIT**

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

# **TEST CONFIGURATION**



# **TEST PROCEDURE**


Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum.

# **TEST RESULTS**


Modulation type	Channel	Output power (dBm)	Limit (dBm)	Result		
	00					
GFSK	39	5.13	30.00	Pass		
	78	5.46				
	00	5.22				
π/4DQPSK	39	5.57	21.00	Pass		
	78	5.87				
	00	5.27				
8DPSK	39	5.64	21.00	Pass		
	78	5.90				

Test plot as follows:

Report No: TRE1511016203 Page: 14 of 47 Issued: 2015-12-07



Report No: TRE1511016203 Page: 15 of 47 Issued: 2015-12-07




Report No: TRE1511016203 Page: 16 of 47 Issued: 2015-12-07

# 4.4. 20dB Emission Bandwidth

## **LIMIT**

N/A

# **TEST CONFIGURATION**



## **TEST PROCEDURE**


- 1. The transmitter output was connected to the spectrum analyzer through an attenuator.
- 2. The bandwidth of the fundamental frequency was measured by spectrum analyzer withRBW≥1% of the 20 dB bandwidthand VBW≥RBW.
- 3. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

# **TEST RESULTS**


Modulation type	Channel	20dB Bandwidth (MHz)	Limit (MHz)	Result
	00	0.886		
GFSK	39	0.884	1	Pass
	78	0.880		
	00	1.198		
π/4DQPSK	39	1.193	1	Pass
	78	1.192		
	00	1.156		
8DPSK	39	1.154	/	Pass
	78	1.163		

Test plot as follows:

Report No: TRE1511016203 Page: 17 of 47 Issued: 2015-12-07



Report No: TRE1511016203 Page: 18 of 47 Issued: 2015-12-07



Report No: TRE1511016203 Page: 19 of 47 Issued: 2015-12-07


# 4.5. Carrier Frequencies Separation

## **LIMIT**

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the 2/3\*20dB bandwidth of the hopping channel, whichever is greater.

## **TEST CONFIGURATION**



## **TEST PROCEDURE**


- 1. The transmitter output was connected to the spectrum analyzer through an attenuator.
- 2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=30 KHz and VBW=100KHz.

## **TEST RESULTS**

Modulation type	Channel	Carrier Frequencies Separation (MHz)	Limit (MHz)	Result
GFSK	39	1.000	0.886	Pass
π/4DQPSK	39	1.005	0.799	Pass
8DPSK	39	1.000	0.775	Pass

Test plot as follows:

Report No: TRE1511016203 Page: 20 of 47 Issued: 2015-12-07



Report No: TRE1511016203 Page: 21 of 47 Issued: 2015-12-07


# 4.6. Hopping Channel Number

## **LIMIT**

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

## **TEST CONFIGURATION**



# **TEST PROCEDURE**


- 1. The transmitter output was connected to the spectrum analyzer through an attenuator.
- 2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=1MHz and VBW=3MHz.

## **TEST RESULTS**

Modulation type	Channel number	Limit (MHz)	Result
GFSK	79		
π/4DQPSK	79	15	Pass
8DPSK	79		

Test plot as follows:

Report No: TRE1511016203 Page: 22 of 47 Issued: 2015-12-07



Report No: TRE1511016203 Page: 23 of 47 Issued: 2015-12-07


#### 4.7. Dwell Time

### **LIMIT**

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a pe-riod of 0.4 seconds multiplied by the number of hopping channels employed.

# **TEST CONFIGURATION**



#### **TEST PROCEDURE**

- 1. The transmitter output was connected to the spectrum analyzer through an attenuator.
- 2. Set center frequency of spectrum analyzer=operating frequency with RBW=1MHz and VBW=1MHz,Span=0Hz.

#### **TEST RESULTS**


Modulation type	Channel	Dwell time (Second)	Limit (Second)	Result
	DH1	0.136		
GFSK	DH3	0.260	0.40	Pass
	DH5	0.310		
	2-DH1	0.124		
π/4DQPSK	2-DH3	0.266	0.40	Pass
	2-DH5	0.310	0.40	
	3-DH1	0.128		
8DPSK	3-DH3	0.266	0.40	Pass
	3-DH5	0.286		

#### Note:


- 1. We have tested all mode at high, middle and low channel, and recoreded worst case at middle channel.
- 2. Dwell time=Pulse time (ms) ×  $(1600 \div 2 \div 79)$  ×31.6 Second for DH1, 2-DH1, 3-DH1 Dwell time=Pulse time (ms) ×  $(1600 \div 4 \div 79)$  ×31.6 Second for DH3, 2-DH3, 3-DH3 Dwell time=Pulse time (ms) ×  $(1600 \div 6 \div 79)$  ×31.6 Second for DH5, 2-DH5, 3-DH5

Test plot as follows:

Report No: TRE1511016203 Page: 24 of 47 Issued: 2015-12-07



Report No: TRE1511016203 Page: 25 of 47 Issued: 2015-12-07



Report No: TRE1511016203 Page: 26 of 47 Issued: 2015-12-07

# 4.8. Pseudorandom Frequency Hopping Sequence

## **LIMIT**


FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems shall have hopping channel carrier fre-quencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hop-ping channel, whichever is greater. Al-ternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier fre-quencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo ran-domly ordered list of hopping fre-quencies. Each frequency must be used equally on the average by each trans-mitter. The system receivers shall have input bandwidths that match the hop-ping channel bandwidths of their cor-responding transmitters and shall shift frequencies in synchronization with the transmitted signals.

#### **TEST RESULTS**


The pseudorandom frequency hopping sequence may be generated in a nice-stage shift register whose 5<sup>th</sup> and 9<sup>th</sup> stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the friststage. The sequence begins with the frist one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages:9
- Length of pseudo-random sequence:29-1=511 bits
- Longest sequence of zeros:8(non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An explame of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

Report No: TRE1511016203 Page: 27 of 47 Issued: 2015-12-07


# 4.9. Restricted band (radiated)

## **LIMIT**

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m @3m)	Value
Above 1GHz	54.00	Average
Above IGHZ	74.00	Peak

#### **TEST CONFIGURATION**




#### **TEST PROCEDURE**

- The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
- 2. The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated360 degrees to determine the position of the maximum emission level.
- 3. The EUT waspositioned such that the distance from antenna to the EUT was 3 meters.
- 4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. Thisis repeated for both horizontal and vertical polarization of the antenna. In order to find themaximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
- The receiver set as follow:
  - RBW=1MHz, VBW=3MHz for Peak value
  - RBW=1MHz, VBW=10Hz for Average value.
- 6. The frequency range from 2310MHz to 2483.5MHz harmonic is checked.

## **TEST RESULTS**


Report No: TRE1511016203 Page: 28 of 47 Issued: 2015-12-07

Worst mode:	GFSK Modulation	Test Channel:	00
Deteccter:	Peak	Polarization:	Horizontal



Mark	Frequency MHz	Reading dBuV/m				Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2353.59					A STATE OF THE STA		-36.97	
2	2390.03	39.14	27.53	6.81	37.57	35.91	74.00	-38.09	Peak
3	2401.99	96.87	27.57	6.83	37.58	93.69	74.00	19.69	Peak


Worst mode:	GFSK Modulation	Test Channel:	00
Deteccter:	Peak	Polarization:	Vertical



Mark	Frequency MHz		Antenna dB			Le∨el dBuV/m	Limit dBuV/m	O∨er limit	Remark
1	2357.84	39.63	27.43	6.75	37.55	36.26	74.00	-37.74	Peak
2	2390.03	38.04	27.53	6.81	37.57	34.81	74.00	-39.19	Peak
3	2401.99	96.97	27.57	6.83	37.58	93.79	74.00	19.79	Peak


Report No: TRE1511016203 Page: 29 of 47 Issued: 2015-12-07

Worst mode:	GFSK Modulation	Test Channel:	78
Deteccter:	Peak	Polarization:	Horizontal



Mark	Frequency MHz	Reading dBuV/m				Level dBuV/m	Limit dBuV/m	0∨er limit	Remark
1	2480.01	101.25	27.83	6.94	37.64	98.38	74.00	24.38	Peak
2	2483.50	61.45	27.85	6.96	37.65	58.61	74.00	-15.39	Peak
3	2493.40	45.61	27.88	6.97	37.65	42.81	74.00	-31.19	Peak


Worst mode:	GFSK Modulation	Test Channel:	78
Deteccter:	Peak	Polarization:	Vertical



Mark	Frequency MHz	Reading dBuV/m				Le∨el dBuV/m	Limit dBuV/m	O∨er limit	Remark
1	2480.01	95.52	27.83	6.94	37.64	92.65	74.00	18.65	Peak
2	2483.50	56.42	27.85	6.96	37.65	53.58	74.00	-20.42	Peak
3	2497.16	42.95	27.90	6.97	37.66	40.16	74.00	-33.84	Peak


Report No: TRE1511016203 Page: 30 of 47 Issued: 2015-12-07

Worst mode:	GFSK Modulation	Test Channel:	78
Deteccter:	AVG	Polarization:	Horizontal



Mark	Frequency	Reading	Antenna	a Cable	Preamp	Le∨el	Limit	0∨er	Remark
	MHz	dBuV/m	dB	dB	dB	dBuV/m	dBuV/m	limit	
1	2483.51	52.51	27.85	6.96	37.65	49.67	54.00	-4.33	Average

Worst mode:	GFSK Modulation	Test Channel:	78
Deteccter:	AVG	Polarization:	Vertical



2483.51 53.44 6.96 -3.40 Average 27.85 37.65 50.60 54.00

Note: Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report and the Peak Level result is lower than the AV limit, so the AV result is not require.

Report No: TRE1511016203 Page: 31 of 47 Issued: 2015-12-07

+


# 4.10. Bandedge and Spurious Emission (conducted)

### **LIMIT**

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

## **TEST CONFIGURATION**




#### **TEST PROCEDURE**

- 1. The transmitter output was connected to the spectrum analyzer through an attenuator.
- 2. Conducted spurious emission the bandwidth of the fundamental frequency was measured by spectrum analyzer withRBW=100 KHz and VBW=300KHz.
- 3. Below -20dB of the highest emission level in operating band.


#### **TEST RESULTS**

Test plot as follows:


Report No: TRE1511016203 Page: 32 of 47 Issued: 2015-12-07




Report No: TRE1511016203 Page: 33 of 47 Issued: 2015-12-07




Report No: TRE1511016203 Page: 34 of 47 Issued: 2015-12-07




Report No: TRE1511016203 Page: 35 of 47 Issued: 2015-12-07




Report No: TRE1511016203 Page: 36 of 47 Issued: 2015-12-07




Report No: TRE1511016203 Page: 37 of 47 Issued: 2015-12-07




Report No: TRE1511016203 Page: 38 of 47 Issued: 2015-12-07



Report No: TRE1511016203 Page: 39 of 47 Issued: 2015-12-07



Report No: TRE1511016203 Page: 40 of 47 Issued: 2015-12-07



Report No: TRE1511016203 Page: 41 of 47 Issued: 2015-12-07

# 4.11. Spurious Emission (radiated)


## **LIMIT**

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value	
30MHz-88MHz	40.00	Quasi-peak	
88MHz-216MHz	43.50	Quasi-peak	
216MHz-960MHz	46.00	Quasi-peak	
960MHz-1GHz	54.00	Quasi-peak	
Above 1GHz	54.00	Average	
Above IGHZ	74.00	Peak	

# **TEST CONFIGURATION**


## ♦ Below 30MHz



# ♦ 30MHz~1000MHz



# ♦ Above 1GHz



Report No: TRE1511016203 Page: 42 of 47 Issued: 2015-12-07

#### **TEST PROCEDURE**

1. The EUT was placed on the top of a rotating table 0.8 meters above the groundat a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

- 2. The EUT was set 3 meters away from the interference-receiving antenna, whichwas mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4. For each suspected emission, the EUT was arranged to its worst case and thenthe antenna was tuned to heights from 1 meter to 4 meters and the rotatablewas turned from 0 degrees to 360 degrees to find the maximum reading.
- 5. Use the following spectrum analyzer settings
  - a) Span shall wide enough to fully capture the emission being measured;
  - b) Below 1GHz, RBW=120KHz, VBW=300KHz, Sweep=auto, Detector function=peak, Trace=max hold; If the emission level of the EUT measured by the peak detectoris 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, theemission measurement will be repeated using the guasi-peak detector and reported.
  - c) Above 1GHz, RBW=1MHz, VBW=3MHz for Peak value

RBW=1MHz, VBW=10Hz for Average value.

#### **TEST RESULTS**

#### Noted:

Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report.


#### Measurement data:

#### ■ 9kHz ~ 30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


#### ■ 30MHz ~ 1GHz

Report No: TRE1511016203 Page: 43 of 47 Issued: 2015-12-07



# MEASUREMENT RESULT: "GM1204606\_red"

12/4/2015 9:1 Frequency MHz	lOAM Level dBµV/m	Transd dB		Margin dB	Det.	Height cm	Azimuth deg	Polarization
80.440000	22.90	-18.6	40.0	17.1	QP	100.0	210.00	HORIZONTAL
114.390000	26.20	-15.4	43.5	17.3	QP	100.0	171.00	HORIZONTAL
179.380000	24.90	-15.9	43.5	18.6	QP	100.0	284.00	HORIZONTAL
189.080000	23.90	-14.8	43.5	19.6	QP	100.0	266.00	HORIZONTAL
350.100000	26.90	-12.2	46.0	19.1	QP	100.0	80.00	HORIZONTAL
862.260000	33.80	1.8	46.0	12.2	QP	100.0	23.00	HORIZONTAL



# MEASUREMENT RESULT: "GM1204603\_red"

1	12/4/2015 9:02AM Frequency Level Transd Limit Margin Det. Height Azimuth Polarization											
	Frequency MHz	Level dBµV/m		Limit dBµV/m	_	Det.	Height cm	Azimuth deg	Polarization			
	31.940000	32.40	-16.5	40.0	7.6	QD	100.0	0.00	VERTICAL			
	59.100000	32.00	-14.8	40.0	8.0	QP	100.0	201.00	VERTICAL			
	73.650000	32.00	-17.6	40.0	8.0	QP	100.0	253.00	VERTICAL			
	103.720000	31.10	-14.6	43.5	12.4	QP	100.0	281.00	VERTICAL			
	768.170000	33.50	-0.3	46.0	12.5	QP	100.0	348.00	VERTICAL			
	945.680000	33.90	3.6	46.0	12.1	OP	100.0	269.00	VERTICAL			

Report No: TRE1511016203 Page: 44 of 47 Issued: 2015-12-07

## ■ Above 1GHz

CH00 for GFSK									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
4804.00	49.02	31.28	5.66	35.29	50.67	74.00	-23.33	Vertical	
7206.00	36.88	36.22	6.87	35.15	44.82	74.00	-29.18	Vertical	
9608.00	36.49	37.85	8.80	35.55	47.59	74.00	-26.41	Vertical	
12010.00	*							Vertical	Dools
4804.00	48.53	31.28	5.66	35.29	50.18	74.00	-23.82	Horizontal	Peak
7206.00	37.15	36.22	6.87	35.15	45.09	74.00	-28.91	Horizontal	
9608.00	36.42	37.85	8.80	35.55	47.52	74.00	-26.48	Horizontal	
12010.00	*							Horizontal	
4804.00	42.99	31.28	5.66	35.29	44.64	54.00	-9.36	Vertical	
7206.00	29.70	36.22	6.87	35.15	37.64	54.00	-16.36	Vertical	
9608.00	28.64	37.85	8.80	35.55	39.74	54.00	-14.26	Vertical	1
12010.00	*							Vertical	A
4804.00	43.02	31.28	5.66	35.29	44.67	54.00	-9.33	Horizontal	Average
7206.00	29.70	36.22	6.87	35.15	37.64	54.00	-16.36	Horizontal	
9608.00	28.69	37.85	8.80	35.55	39.79	54.00	-14.21	Horizontal	
12010.00	*							Horizontal	

CH39 for GFSK									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
4882.00	48.56	30.88	5.70	35.27	49.87	74.00	-24.13	Vertical	
7323.00	36.46	35.82	6.91	35.13	44.06	74.00	-29.94	Vertical	
9764.00	37.19	37.45	8.84	35.53	47.95	74.00	-26.05	Vertical	
12205.00	*							Vertical	Dools
4882.00	49.33	30.88	5.70	35.27	50.64	74.00	-23.36	Horizontal	Peak
7323.00	38.24	35.82	6.91	35.13	45.84	74.00	-28.16	Horizontal	
9764.00	36.86	37.45	8.84	35.53	47.62	74.00	-26.38	Horizontal	
12205.00	*							Horizontal	
4882.00	42.74	30.88	5.70	35.27	44.05	54.00	-9.95	Vertical	
7323.00	29.65	35.82	6.91	35.13	37.25	54.00	-16.75	Vertical	
9764.00	28.68	37.45	8.84	35.53	39.44	54.00	-14.56	Vertical	
12205.00	*							Vertical	Average
4882.00	43.55	30.88	5.70	35.27	44.86	54.00	-9.14	Horizontal	Average
7323.00	29.64	35.82	6.91	35.13	37.24	54.00	-16.76	Horizontal	
9764.00	29.20	37.45	8.84	35.53	39.96	54.00	-14.04	Horizontal	
12205.00	*							Horizontal	

## Remark:

- 1. Final Level =Receiver Read level + Antenna Factor + Cable Loss Preamplifier Factor
- 2. "\*", means this data is the too weak instrument of signal is unable to test.
- 3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Report No: TRE1511016203 Page: 45 of 47 Issued: 2015-12-07

CH78 for GFSK									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
4960.00	48.37	30.98	5.73	35.32	49.76	74.00	-24.24	Vertical	
7440.00	36.60	35.92	6.94	35.18	44.28	74.00	-29.72	Vertical	
9920.00	37.22	37.55	8.87	35.58	48.06	74.00	-25.94	Vertical	
12400.00	*							Vertical	Dools
4960.00	48.87	30.98	5.73	35.32	50.26	74.00	-23.74	Horizontal	Peak
7440.00	37.75	35.92	6.94	35.18	45.43	74.00	-28.57	Horizontal	
9920.00	37.25	37.55	8.87	35.58	48.09	74.00	-25.91	Horizontal	
12400.00	*							Horizontal	
4960.00	43.37	30.98	5.73	35.32	44.76	54.00	-9.24	Vertical	
7440.00	29.91	35.92	6.94	35.18	37.59	54.00	-16.41	Vertical	
9920.00	28.80	37.55	8.87	35.58	39.64	54.00	-14.36	Vertical	
12400.00	*							Vertical	A.,
4960.00	43.44	30.98	5.73	35.32	44.83	54.00	-9.17	Horizontal	Average
7440.00	29.94	35.92	6.94	35.18	37.62	54.00	-16.38	Horizontal	
9920.00	28.62	37.55	8.87	35.58	39.46	54.00	-14.54	Horizontal	
12400.00	*							Horizontal	

#### Remark:

- 1. Final Level =Receiver Read level + Antenna Factor + Cable Loss Preamplifier Factor
- 2. "\*", means this data is the too weak instrument of signal is unable to test.
- 3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Report No: TRE1511016203 Page: 46 of 47 Issued: 2015-12-07

# 5. Test Setup Photos of the EUT

Radiated Emission





Conducted Emission (AC Mains)



Report No: TRE1511016203 Page: 47 of 47 Issued: 2015-12-07

Reference to Test Report TRE151101620	1
	End of Report