

EMC Test Report

Application for Grant of Equipment Authorization

Industry Canada RSS-Gen Issue 4 / RSS 247 Issue 1 FCC Part 15 Subpart C

Model: R006 (900MHz PA radio module)

FCC ID: 2AGSF-R006

APPLICANT: Sensor Industries

601 Daily Drive, STE 300N Camarillo, CA 93010

TEST SITE(S): National Technical Systems - Silicon Valley

41039 Boyce Road.

Fremont, CA. 94538-2435

IC SITE REGISTRATION #: 2845B-3; 2845B-4, 2845B-5, 2845B-7

REPORT DATE: February 16, 2016

REISSUE DATE: April 27, 2016

FINAL TEST DATES: December 11, 29, and 31, 2015

TOTAL NUMBER OF PAGES: 59

PROGRAM MGR / TECHNICAL REVIEWER: QUALITY ASSURANCE DELEGATE / FINAL REPORT PREPARER:

Mark È Hill Staff Engineer

David Guidotti Senior Technical Writer



National Technical Systems - Silicon Valley is accredited by the A2LA, certificate number 0214.26, to perform the test(s) listed in this report, except where noted otherwise. This report and the information contained herein represent the results of testing test articles identified and selected by the client performed to specifications and/or procedures selected by the client. National Technical Systems (NTS) makes no representations, expressed or implied, that such testing is adequate (or inadequate) to demonstrate efficiency, performance, reliability, or any other characteristic of the articles being tested, or similar products. This report should not be relied upon as an endorsement or certification by NTS of the equipment tested, nor does it represent any statement whatsoever as to its merchantability or fitness of the test article, or similar products, for a particular purpose. This report shall not be reproduced except in full

File: R100697 Rev 1 Page 1

Project number JD100279 Reissue Date: April 27, 2016

REVISION HISTORY

| Rev# | Date | Comments | Modified By |
|------|-------------------|----------------------------------------------------------------|-------------|
| - | February 16, 2016 | First release | |
| 1.0 | April 27, 2016 | Added plots for compliance at bandedges. Additional data added | MEH |
| | | for modified shield. | |



TABLE OF CONTENTS

| REVISION HISTORY | |
|-------------------------------------------------------------------------------------------------|----------|
| TABLE OF CONTENTS | 3 |
| SCOPE | |
| OBJECTIVE | |
| STATEMENT OF COMPLIANCE | |
| DEVIATIONS FROM THE STANDARDS | |
| | |
| TEST RESULTS SUMMARY DIGITAL TRANSMISSION SYSTEMS (902 – 928 MHz) | |
| GENERAL REQUIREMENTS APPLICABLE TO ALL BANDS | 6 |
| MEASUREMENT UNCERTAINTIES | |
| EQUIPMENT UNDER TEST (EUT) DETAILS | |
| GENERAL | |
| ANTENNA SYSTEM | |
| ENCLOSURE | |
| MODIFICATIONS | |
| SUPPORT EQUIPMENT | 9 |
| EUT INTERFACE PORTS | |
| EUT OPERATION | 9 |
| TEST SITE | |
| GENERAL INFORMATION | |
| CONDUCTED EMISSIONS CONSIDERATIONS | |
| RADIATED EMISSIONS CONSIDERATIONS | |
| MEASUREMENT INSTRUMENTATION | |
| RECEIVER SYSTEM | |
| INSTRUMENT CONTROL COMPUTER | 11 |
| LINE IMPEDANCE STABILIZATION NETWORK (LISN) | |
| FILTERS/ATTENUATORS | |
| ANTENNASANTENNA MAST AND EQUIPMENT TURNTABLE | |
| INSTRUMENT CALIBRATION | |
| TEST PROCEDURES | |
| EUT AND CABLE PLACEMENT | 13 13 |
| CONDUCTED EMISSIONS | |
| RADIATED EMISSIONS | |
| CONDUCTED EMISSIONS FROM ANTENNA PORT | |
| BANDWIDTH MEASUREMENTS | |
| SPECIFICATION LIMITS AND SAMPLE CALCULATIONS | 18 |
| GENERAL TRANSMITTER RADIATED EMISSIONS SPECIFICATION LIMITS | |
| RECEIVER RADIATED SPURIOUS EMISSIONS SPECIFICATION LIMITS | |
| OUTPUT POWER LIMITS – DIGITAL TRANSMISSION SYSTEMS | |
| TRANSMIT MODE SPURIOUS RADIATED EMISSIONS LIMITS – FHSS AND DTS SYSTEMS | |
| SAMPLE CALCULATIONS - CONDUCTED EMISSIONS | |
| SAMPLE CALCULATIONS - RADIATED EMISSIONSSAMPLE CALCULATIONS - FIELD STRENGTH TO EIRP CONVERSION | |
| | |
| APPENDIX A TEST EQUIPMENT CALIBRATION DATA | |
| APPENDIX B TEST DATA | |
| END OF REPORT | 50 |

Project number JD100279 Reissue Date: April 27, 2016

SCOPE

An electromagnetic emissions test has been performed on the Sensor Industries model R006 (900MHz PA radio module), pursuant to the following rules:

Industry Canada RSS-Gen Issue 4 RSS 247 Issue 1 "Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices" FCC Part 15 Subpart C

Conducted and radiated emissions data has been collected, reduced, and analyzed within this report in accordance with measurement guidelines set forth in the following reference standards and as outlined in National Technical Systems - Silicon Valley test procedures:

ANSI C63.10-2013 FCC DTS Measurement Guidance KDB558074

The intentional radiator above has been tested in a simulated typical installation to demonstrate compliance with the relevant Industry Canada performance and procedural standards.

Final system data was gathered in a mode that tended to maximize emissions by varying orientation of EUT, orientation of power and I/O cabling, antenna search height, and antenna polarization.

Every practical effort was made to perform an impartial test using appropriate test equipment of known calibration. All pertinent factors have been applied to reach the determination of compliance.

OBJECTIVE

The primary objective of the manufacturer is compliance with the regulations outlined in the previous section.

Prior to marketing in the USA, all unlicensed transmitters and transceivers require certification. Receive-only devices operating between 30 MHz and 960 MHz are subject to either certification or a manufacturer's declaration of conformity, with all other receive-only devices exempt from the technical requirements.

Prior to marketing in Canada, Class I transmitters, receivers and transceivers require certification. Class II devices are required to meet the appropriate technical requirements but are exempt from certification requirements.

Certification is a procedure where the manufacturer submits test data and technical information to a certification body and receives a certificate or grant of equipment authorization upon successful completion of the certification body's review of the submitted documents. Once the equipment authorization has been obtained, the label

Project number JD100279 Reissue Date: April 27, 2016

indicating compliance must be attached to all identical units, which are subsequently manufactured.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product which may result in increased emissions should be checked to ensure compliance has been maintained (i.e., printed circuit board layout changes, different line filter, different power supply, harnessing or I/O cable changes, etc.).

STATEMENT OF COMPLIANCE

The tested sample of Sensor Industries model R006 (900MHz PA radio module) complied with the requirements of the following regulations:


Industry Canada RSS-Gen Issue 4 RSS 247 Issue 1 "Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices" FCC Part 15 Subpart C

Maintenance of compliance is the responsibility of the manufacturer. Any modifications to the product should be assessed to determine their potential impact on the compliance status of the device with respect to the standards detailed in this test report.

The test results recorded herein are based on a single type test of Sensor Industries model R006 (900MHz PA radio module) and therefore apply only to the tested sample. The sample was selected and prepared by Steve Smith of Sensor Industries.

DEVIATIONS FROM THE STANDARDS

No deviations were made from the published requirements listed in the scope of this report.



Project number JD100279 Report Date: February 16, 2016 Reissue Date: April 27, 2016

TEST RESULTS SUMMARY

DIGITAL TRANSMISSION SYSTEMS (902 – 928 MHz)

| FCC Rule Part | RSS Rule Part | Description | Measured Value / Comments | Limit / Requirement | Result |
|-----------------------|------------------------------|--------------------------------------------------------|---------------------------------------------------|-----------------------------------------------------------------------------------------|----------|
| 15.247(a) | RSS 247 5.2 | Digital Modulation | Systems uses DSSS techniques | System must utilize a digital transmission technology | Complies |
| 15.247 (a) (2) | RSS 247 5.2 (1) | 6dB Bandwidth | 535 kHz | >500kHz | Complies |
| 15.247 (b) (3) | RSS 247 5.4 (4) | Output Power, 902 – 928 MHz | 9.5 dBm (0.009 Watts) EIRP = 0.009 W Note 1 | 1Watt, EIRP limited to 4 Watts. | Complies |
| 15.247(d) | RSS 247 5.2 (2) | Power Spectral Density | 5.2 dBm/3kHz | 8dBm/3kHz | Complies |
| 15.247(c) | RSS 247 5.5 | Antenna Port Spurious Emissions 30MHz – 9.28 GHz | All spurious emissions < -20dBc | < -20dBc | Complies |
| 15.247(c) / 15.209 | RSS 247 5.5 / RSS- GEN | Radiated Spurious Emissions 30MHz – 9.28 GHz | 53.4 dBµV/m @ 2744.5 MHz (-0.6 dB) | Refer to the limits section (p19) for restricted bands, all others < -20dBc | Complies |
| Note 1: EIRP ca | alculated using ar | ntenna gain of 0 dBi for the I | nighest EIRP system. | | |

GENERAL REQUIREMENTS APPLICABLE TO ALL BANDS

| FCC Rule Part | RSS Rule part | Description | Measured Value / Comments | Limit / Requirement | Result (margin) |
|------------------------------|---------------------------|-----------------------------|-----------------------------------------------|--------------------------------------------|--------------------|
| 15.203 | - | RF Connector | EUT uses a permanently connected antenna | Unique or integral antenna required | Complies |
| 15.207 | RSS GEN Table 3 | AC Conducted Emissions | 34.7dBµV @ 0.46MHz (-12.0dB) | Refer to page 20 | Complies |
| 15.109 | RSS GEN Table 2 | Receiver spurious emissions | 37.4 dBµV/m @ 38.83 MHz (-2.6 dB) | Refer to page 19 | Complies |
| 15.247 (b) (5) 15.407 (f) | RSS 102 | RF Exposure Requirements | Refer to MPE calculations in separate exhibit | Refer to OET 65, FCC Part 1 and RSS 102 | Complies |
| - | RSP 100 RSS GEN 6.6 | Occupied Bandwidth | 565 kHz | Information only | N/A |

Project number JD100279 Reissue Date: April 27, 2016

MEASUREMENT UNCERTAINTIES

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level and were calculated in accordance with UKAS document LAB 34.

| Measurement Type | Measurement Unit | Frequency Range | Expanded Uncertainty |
|-----------------------------------------|------------------|-------------------|-------------------------|
| RF power, conducted (power meter) | dBm | 25 to 7000 MHz | ± 0.52 dB |
| RF power, conducted (Spectrum analyzer) | dBm | 25 to 7000 MHz | ± 0.7 dB |
| Conducted emission of transmitter | dBm | 25 to 26500 MHz | ± 0.7 dB |
| Conducted emission of receiver | dBm | 25 to 26500 MHz | ± 0.7 dB |
| Radiated emission (substitution method) | dBm | 25 to 26500 MHz | ± 2.5 dB |
| Padiated emission (field etranath) | dDu\//m | 25 to 1000 MHz | ± 3.6 dB |
| Radiated emission (field strength) | dBµV/m | 1000 to 40000 MHz | ± 6.0 dB |
| Conducted Emissions (AC Power) | dΒμV | 0.15 to 30 MHz | ± 2.4 dB |

Project number JD100279 Reissue Date: April 27, 2016

EQUIPMENT UNDER TEST (EUT) DETAILS GENERAL

The Sensor Industries model R006 (900MHz PA radio module) is a 900MHz radio module which is designed to communicate with other radios. Since the EUT would normally be floor-standing during operation, the EUT was treated as floor-standing equipment during testing to simulate the end-user environment. The electrical rating of the EUT is 3.3 Volts, 0.2 Amps.

The sample was received on December 11, 2015 and tested on December 11, 29, and 31, 2015. The EUT consisted of the following component(s):

| Company | Model | Description | Serial Number | FCC ID |
|-------------------|-------|-----------------|-------------------------------------------------------|------------|
| Sensor Industries | R006 | PA Radio Module | 15331507730235 (used for radiated measurements) | 2AGSF-R006 |
| Sensor Industries | R006 | PA Radio Module | 0192 (used for antenna port measurements) | 2AGSF-R006 |

For AC conducted emissions per 15.207, the module was tested in a representative host system.

| Company | Model | Description | Serial Number | FCC ID |
|-------------------|----------|-------------|---------------|--------|
| Sensor Industries | UnitNode | Repeater | 340 | - |

ANTENNA SYSTEM

The antenna system consists of 0dBi bent wire soldered to the pcb.

ENCLOSURE

The EUT has no enclosure. It is designed to be installed within the enclosure of a host system.

MODIFICATIONS

After all testing was completed, a sample with a modified shield was provided. A validation of the spurious emissions was performed.

Project number JD100279 Reissue Date: April 27, 2016

SUPPORT EQUIPMENT

The following equipment was used as support equipment for testing:

Radiated Spurious and RF Conducted

| Company | Model | Description | Serial Number | FCC ID |
|-------------------|---------------|-----------------------|---------------|--------|
| HP | Compaq nw8440 | Laptop | CNU7212PXN | DoC |
| Texas Instruments | CC Debugger | USB to Serial adapter | - | - |

For AC conducted emissions, no support equipment was used.

EUT INTERFACE PORTS

The I/O cabling configuration during testing was as follows:

Radiated Spurious and RF Conducted

| Port | Connected To | • | Cable(s) | |
|-------------|-------------------|-------------------------------|------------------------|-----------|
| 1 Oit | Port Connected to | | Shielded or Unshielded | Length(m) |
| Laptop USB | CC Debugger | USB Cable – Multiconductor | Shielded | 1.5 |
| CC Debugger | EUT | Ribbon | Unshielded | 15cm |

AC Conducted

| Port | Connected To | i | Cable(s) | 1 |
|-----------------------|--------------|-----------------------|------------------------|-----------|
| TOIL | Connected 10 | Description | Shielded or Unshielded | Length(m) |
| AC Port (Repeater) | AC Mains | 3wire extension cable | Unshielded | 0.8 |

EUT OPERATION

During radiated spurious and RF conducted testing, the EUT was configured for continuous transmission on the noted channel.

During AC conducted emissions, the repeater was operating as it would during normal usage with the radio transmitting.

Project number JD100279 Reissue Date: April 27, 2016

TEST SITE

GENERAL INFORMATION

Final test measurements were taken at the test sites listed below. Pursuant to section 2.948 of the FCC's Rules and section 3.3 of RSP-100, construction, calibration, and equipment data has been filed with the Commission and with industry Canada.

| Site | Designation / Reg | Designation / Registration Numbers | | |
|-----------|-------------------|------------------------------------|---------------------------|--|
| Sile | FCC | Canada | Location | |
| Chamber 4 | US0027 | 2845B-4 | 41039 Boyce Road | |
| Chamber 7 | US0027 | 2845B-7 | Fremont, CA 94538-2435 | |

ANSI C63.4 recommends that ambient noise at the test site be at least 6 dB below the allowable limits. Ambient levels are below this requirement. The test site(s) contain separate areas for radiated and conducted emissions testing. Considerable engineering effort has been expended to ensure that the facilities conform to all pertinent requirements of ANSI C63.4.

CONDUCTED EMISSIONS CONSIDERATIONS

Conducted emissions testing is performed in conformance with ANSI C63.10. Measurements are made with the EUT connected to the public power network through a nominal, standardized RF impedance, which is provided by a line impedance stabilization network, known as a LISN. A LISN is inserted in series with each current-carrying conductor in the EUT power cord.

RADIATED EMISSIONS CONSIDERATIONS

The FCC has determined that radiation measurements made in a shielded enclosure are not suitable for determining levels of radiated emissions. Radiated measurements are performed in an open field environment or in a semi-anechoic chamber. The test sites are maintained free of conductive objects within the CISPR defined elliptical area incorporated in ANSI C63.4 guidelines and meet the Normalized Site Attenuation (NSA) requirements of ANSI C63.4.

Project number JD100279 Reissue Date: April 27, 2016

MEASUREMENT INSTRUMENTATION

RECEIVER SYSTEM

An EMI receiver as specified in CISPR 16-1-1 is used for emissions measurements. The receivers used can measure over the frequency range of 9 kHz up to 2000 MHz. These receivers allow both ease of measurement and high accuracy to be achieved. The receivers have Peak, Average, and CISPR (Quasi-peak) detectors built into their design so no external adapters are necessary. The receiver automatically sets the required bandwidth for the CISPR detector used during measurements. If the repetition frequency of the signal being measured is below 20Hz, peak measurements are made in lieu of Ouasi-Peak measurements.

For measurements above the frequency range of the receivers, a spectrum analyzer is utilized because it provides visibility of the entire spectrum along with the precision and versatility required to support engineering analysis. Average measurements above 1000MHz are performed on the spectrum analyzer using the linear-average method with a resolution bandwidth of 1 MHz and a video bandwidth of 10 Hz, unless the signal is pulsed in which case the average (or video) bandwidth of the measuring instrument is reduced to onset of pulse desensitization and then increased.

INSTRUMENT CONTROL COMPUTER

The receivers utilize either a Rohde & Schwarz EZM Spectrum Monitor/Controller or contain an internal Spectrum Monitor/Controller to view and convert the receiver measurements to the field strength at an antenna or voltage developed at the LISN measurement port, which is then compared directly with the appropriate specification limit. This provides faster, more accurate readings by performing the conversions described under Sample Calculations within the Test Procedures section of this report. Results are printed in a graphic and/or tabular format, as appropriate. A personal computer is used to record all measurements made with the receivers. The software used for radiated and conducted emissions measurements is NTS EMI Test Software (rev 2.10)

The Spectrum Monitor provides a visual display of the signal being measured. In addition, the controller or a personal computer run automated data collection programs which control the receivers. This provides added accuracy since all site correction factors, such as cable loss and antenna factors are added automatically.

LINE IMPEDANCE STABILIZATION NETWORK (LISN)

Line conducted measurements utilize a fifty microhenry Line Impedance Stabilization Network as the monitoring point. The LISN used also contains a 250 uH CISPR adapter. This network provides for calibrated radio frequency noise measurements by the design of the internal low pass and high pass filters on the EUT and measurement ports, respectively.

Project number JD100279 Reissue Date: April 27, 2016

FILTERS/ATTENUATORS

External filters and precision attenuators are often connected between the receiving antenna or LISN and the receiver. This eliminates saturation effects and non-linear operation due to high amplitude transient events.

ANTENNAS

A loop antenna is used below 30 MHz. For the measurement range 30 MHz to 1000 MHz either a combination of a biconical antenna and a log periodic or a bi-log antenna is used. Above 1000 MHz, horn antennas are used. The antenna calibration factors to convert the received voltage to an electric field strength are included with appropriate cable loss and amplifier gain factors to determine an overall site factor, which is then programmed into the test receivers or incorporated into the test software.

ANTENNA MAST AND EQUIPMENT TURNTABLE

The antennas used to measure the radiated electric field strength are mounted on a non-conductive antenna mast equipped with a motor-drive to vary the antenna height. Measurements below 30 MHz are made with the loop antenna at a fixed height of 1m above the ground plane.

ANSI C63.10 specifies that the test height above ground for table mounted devices shall be 80 centimeters. Floor mounted equipment shall be placed on the ground plane if the device is normally used on a conductive floor or separated from the ground plane by insulating material from 3 to 12 mm if the device is normally used on a non-conductive floor as specified in ANSI C63.4. During radiated measurements, the EUT is positioned on a motorized turntable in conformance with this requirement.

INSTRUMENT CALIBRATION

All test equipment is regularly checked to ensure that performance is maintained in accordance with the manufacturer's specifications. All antennas are calibrated at regular intervals with respect to tuned half-wave dipoles. An exhibit of this report contains the list of test equipment used and calibration information.

TEST PROCEDURES

EUT AND CABLE PLACEMENT

The regulations require that interconnecting cables be connected to the available ports of the unit and that the placement of the unit and the attached cables simulate the worst case orientation that can be expected from a typical installation, so far as practicable. To this end, the position of the unit and associated cabling is varied within the guidelines of ANSI C63.10, and the worst-case orientation is used for final measurements.

CONDUCTED EMISSIONS

Conducted emissions are measured at the plug end of the power cord supplied with the EUT. Excess power cord length is wrapped in a bundle between 30 and 40 centimeters in length near the center of the cord. Preliminary measurements are made to determine the highest amplitude emission relative to the specification limit for all the modes of operation. Placement of system components and varying of cable positions are performed in each mode. A final peak mode scan is then performed in the position and mode for which the highest emission was noted on all current carrying conductors of the power cord.




Figure 1 Typical Conducted Emissions Test Configuration

Project number JD100279 Reissue Date: April 27, 2016


RADIATED EMISSIONS


A preliminary scan of the radiated emissions is performed in which all significant EUT frequencies are identified with the system in a nominal configuration. At least two scans are performed, one scan for each antenna polarization (horizontal and vertical; loop parallel and perpendicular to the EUT). During the preliminary scans, the EUT is rotated through 360°, the antenna height is varied (for measurements above 30 MHz) and cable positions are varied to determine the highest emission relative to the limit. Preliminary scans may be performed in a fully anechoic chamber for the purposes of identifying the frequencies of the highest emissions from the EUT.

A speaker is provided in the receiver to aid in discriminating between EUT and ambient emissions. Other methods used during the preliminary scan for EUT emissions involve scanning with near field magnetic loops, monitoring I/O cables with RF current clamps, and cycling power to the EUT.


Final maximization is a phase in which the highest amplitude emissions identified in the spectral search are viewed while the EUT azimuth angle is varied from 0 to 360 degrees relative to the receiving antenna. The azimuth, which results in the highest emission is then maintained while varying the antenna height from one to four meters (for measurements above 30 MHz, measurements below 30 MHz are made with the loop antenna at a fixed height of 1m). The result is the identification of the highest amplitude for each of the highest peaks. Each recorded level is corrected in the receiver using appropriate factors for cables, connectors, antennas, and preamplifier gain.

When testing above 18 GHz, the receive antenna is located at 1meter from the EUT and the antenna height is restricted to a maximum of 2.5 meters.






Typical Test Configuration for Radiated Field Strength Measurements



The anechoic materials on the walls and ceiling ensure compliance with the normalized site attenuation requirements of CISPR 16 / CISPR 22 / ANSI C63.4 for an alternate test site at the measurement distances used.

Floor-standing equipment is placed on the floor with insulating supports between the unit and the ground plane.




<u>Test Configuration for Radiated Field Strength Measurements</u> <u>Semi-Anechoic Chamber, Plan and Side Views</u>

Project number JD100279 Reissue Date: April 27, 2016

CONDUCTED EMISSIONS FROM ANTENNA PORT

Direct measurements of power, bandwidth and power spectral density are performed, where possible, with the antenna port of the EUT connected to either the power meter or spectrum analyzer via a suitable attenuator and/or filter. These are used to ensure that the front end of the measurement instrument is not overloaded by the fundamental transmission.



Test Configuration for Antenna Port Measurements

Measurement bandwidths (video and resolution) are set in accordance with the relevant standards and NTS Silicon Valley's test procedures for the type of radio being tested. When power measurements are made using a resolution bandwidth less than the signal bandwidth the power is calculated by summing the power across the signal bandwidth using either the analyzer channel power function or by capturing the trace data and calculating the power using software. In both cases the summed power is corrected to account for the equivalent noise bandwidth (ENBW) of the resolution bandwidth used.

If power averaging is used (typically for certain digital modulation techniques), the EUT is configured to transmit continuously. Power averaging is performed using either the built-in function of the analyzer or, if the analyzer does not feature power averaging, using external software. In both cases the average power is calculated over a number of sweeps (typically 100). When the EUT cannot be configured to continuously transmit then either the analyzer is configured to perform a gated sweep to ensure that the power is averaged over periods that the device is transmitting or power averaging is disabled and a max-hold feature is used.

If a power meter is used to make output power measurements the sensor head type (peak or average) is stated in the test data table.

BANDWIDTH MEASUREMENTS

The 6dB, 20dB, 26dB and/or 99% signal bandwidth are measured using the bandwidths recommended by ANSI C63.10 and RSS GEN.

Project number JD100279 Reissue Date: April 27, 2016

SPECIFICATION LIMITS AND SAMPLE CALCULATIONS

The limits for conducted emissions are given in units of microvolts, and the limits for radiated emissions are given in units of microvolts per meter at a specified test distance. Data is measured in the logarithmic form of decibels relative to one microvolt, or dB microvolts (dBuV). For radiated emissions, the measured data is converted to the field strength at the antenna in dB microvolts per meter (dBuV/m). The results are then converted to the linear forms of uV and uV/m for comparison to published specifications.

For reference, converting the specification limits from linear to decibel form is accomplished by taking the base ten logarithm, then multiplying by 20. These limits in both linear and logarithmic form are as follows:

Project number JD100279 Reissue Date: April 27, 2016

GENERAL TRANSMITTER RADIATED EMISSIONS SPECIFICATION LIMITS

The table below shows the limits for the spurious emissions from transmitters that fall in restricted bands¹.

| Frequency Range (MHz) | Limit (uV/m) | Limit (dBuV/m @ 3m) |
|-----------------------------|------------------------------|------------------------------------------------------|
| 0.009-0.490 | 2400/F _{KHz} @ 300m | 67.6-20*log ₁₀ (F _{KHz}) @ 300m |
| 0.490-1.705 | 24000/F _{KHz} @ 30m | 87.6-20*log ₁₀ (F _{KHz}) @ 30m |
| 1.705 to 30 | 30 @ 30m | 29.5 @ 30m |
| 30 to 88 | 100 @ 3m | 40 @ 3m |
| 88 to 216 | 150 @ 3m | 43.5 @ 3m |
| 216 to 960 | 200 @ 3m | 46.0 @ 3m |
| Above 960 | 500 @ 3m | 54.0 @ 3m |

RECEIVER RADIATED SPURIOUS EMISSIONS SPECIFICATION LIMITS

The table below shows the limits for the spurious emissions from receivers as detailed in FCC Part 15.109, RSS 210 Table 2, RSS GEN Table 1 and RSS 310 Table 3. Note that receivers operating outside of the frequency range 30 MHz – 960 MHz are exempt from the requirements of 15.109.

| Frequency Range (MHz) | Limit (uV/m @ 3m) | Limit (dBuV/m @ 3m) |
|-----------------------------|----------------------|------------------------|
| 30 to 88 | 100 | 40 |
| 88 to 216 | 150 | 43.5 |
| 216 to 960 | 200 | 46.0 |
| Above 960 | 500 | 54.0 |

OUTPUT POWER LIMITS - DIGITAL TRANSMISSION SYSTEMS

The table below shows the limits for output power and output power density. Where the signal bandwidth is less than 20 MHz the maximum output power is reduced to the power spectral density limit plus 10 times the log of the bandwidth (in MHz).

| Operating Frequency (MHz) | Output Power | Power Spectral Density |
|---------------------------|-----------------|------------------------|
| 902 – 928 | 1 Watt (30 dBm) | 8 dBm/3kHz |

The maximum permitted output power is reduced by 1dB for every dB the antenna gain exceeds 6dBi.

-

¹ The restricted bands are detailed in FCC 15.205, RSS-GEN Table 3

Project number JD100279 Reissue Date: April 27, 2016

TRANSMIT MODE SPURIOUS RADIATED EMISSIONS LIMITS – FHSS and DTS SYSTEMS

The limits for unwanted (spurious) emissions from the transmitter falling in the restricted bands are those specified in the general limits sections of FCC Part 15 and RSS 247. All other unwanted (spurious) emissions shall be at least 20dB below the level of the highest in-band signal level (30dB if the power is measured using the sample detector/power averaging method).

SAMPLE CALCULATIONS - CONDUCTED EMISSIONS

Receiver readings are compared directly to the conducted emissions specification limit (decibel form) as follows:

$$R_r - S = M$$

where:

 R_r = Receiver Reading in dBuV

S = Specification Limit in dBuV

M = Margin to Specification in +/- dB

SAMPLE CALCULATIONS - RADIATED EMISSIONS

Receiver readings are compared directly to the specification limit (decibel form). The receiver internally corrects for cable loss, preamplifier gain, and antenna factor. The calculations are in the reverse direction of the actual signal flow, thus cable loss is added and the amplifier gain is subtracted. The Antenna Factor converts the voltage at the antenna coaxial connector to the field strength at the antenna elements.

A distance factor, when used for electric field measurements above 30MHz, is calculated by using the following formula:

$$F_d = 20*LOG_{10} (D_m/D_s)$$

where:

 F_d = Distance Factor in dB

 D_m = Measurement Distance in meters

 D_S = Specification Distance in meters

Measurement Distance is the distance at which the measurements were taken and Specification Distance is the distance at which the specification limits are based. The antenna factor converts the voltage at the antenna coaxial connector to the field strength at the antenna elements.

The margin of a given emission peak relative to the limit is calculated as follows:

$$R_c = R_r + F_d$$

and

$$M = R_C - L_S$$

Project number JD100279 Reissue Date: April 27, 2016

where:

 R_r = Receiver Reading in dBuV/m

 F_d = Distance Factor in dB

 R_c = Corrected Reading in dBuV/m

 L_S = Specification Limit in dBuV/m

M = Margin in dB Relative to Spec

SAMPLE CALCULATIONS - FIELD STRENGTH TO EIRP CONVERSION

Where the radiated electric field strength is expressed in terms of the equivalent isotropic radiated power (eirp), or where a field strength measurement of output power is made in lieu of a direct measurement, the following formula is used to convert between eirp and field strength at a distance of d (meters) from the equipment under test:

$$E = \frac{1000000 \sqrt{30 P}}{d}$$
 microvolts per meter

where P is the eirp (Watts)

For a measurement at 3m the conversion from a logarithmic value for field strength (dBuV/m) to an eirp power (dBm) is -95.3dB.

Project number JD100279 Reissue Date: April 27, 2016

Report Date: February 16, 2016

Appendix A Test Equipment Calibration Data

| T1 | Ω | 20 | 2 |
|----|----------|-----|-----|
| T1 | UU | 13(| JZ. |

| Manufacturer | Description | <u>Model</u> | Asset # | Calibrated | Cal Due |
|----------------------------|---------------------------------------------------------------------------------|-----------------------------|--------------|-------------------------|-------------------------|
| Radiated Spurious E NTS | missions, 30 - 9300 MHz, 11-De NTS EMI Software (rev 2.10) | e c-15 N/A | 0 | | N/A |
| Hewlett Packard | Microwave Preamplifier, 1- 26.5GHz | 8449B | 870 | 2/20/2015 | 2/20/2016 |
| Hewlett Packard | Spectrum Analyzer (SA40) Red 30 Hz -40 GHz | 8564E (84125C) | 1148 | 10/17/2015 | 10/17/2016 |
| EMCO Hewlett Packard | Antenna, Horn, 1-18 GHz High Pass filter, 1.5 GHz (Purple System) | 3115 P/N 84300- 80037 | 1561 1769 | 6/27/2014 11/3/2015 | 6/27/2016 11/3/2016 |
| Radio Antenna Port (| Power and Spurious Emission | s), 11-Dec-15 | | | |
| Rohde & Schwarz | Power Meter, Single Channel, +1795+1796 | NRVS | 1534 | 7/20/2015 | 7/20/2016 |
| Rohde & Schwarz | Peak Power Sensor 100 uW - 2 Watts (w/ 20 dB pad, SN BJ5155) | NRV-Z32 | 1536 | 1/15/2015 | 1/15/2016 |
| Agilent Technologies | PSA, Spectrum Analyzer, (installed options, 111, 115, 123, 1DS, B7J, HYX, | E4446A | 2139 | 6/22/2015 | 6/22/2016 |
| Radiated Emissions, | 30 - 5,000 MHz, 31-Dec-15 | | | | |
| EMCO Rohde & Schwarz | Antenna, Horn, 1-18GHz EMI Test Receiver, 20 Hz-7 | 3115 ESIB7 | 868 1538 | 6/26/2014 12/19/2015 | 6/26/2016 12/19/2016 |
| Ronde & Schwarz | GHz | ESID1 | 1330 | 12/19/2015 | 12/19/2010 |
| Sunol Sciences | Biconilog, 30-3000 MHz | JB3 | 1549 | 6/2/2015 | 6/2/2017 |
| Hewlett Packard | Microwave Preamplifier, 1-26.5GHz | 8449B | 2199 | 10/9/2015 | 10/9/2016 |
| Hewlett Packard | Spectrum Analyzer (SA40) Purple 9 kHz - 40 GHz, | 8564E (84125C) | 2415 | 3/7/2015 | 3/7/2016 |
| Hewlett Packard | 9KHz-1300MHz pre-amp | 8447F | 2777 | 3/4/2015 | 3/5/2016 |
| T100337 | | | | | |
| Conducted Emission | s - AC Power Ports, 29-Dec-15 | | | | |
| Rohde & Schwarz | EMI Test Receiver, 20 Hz-7 GHz | ESIB7 | 1538 | 12/19/2015 | 12/19/2016 |
| Rohde & Schwarz | Pulse Limiter | ESH3 Z2 | 1594 | 5/14/2015 | 5/14/2016 |
| Com-Power | 9KHz-30MHz, 50uH, 15Aac, 10Adc, max CISPR 15 | LI-215A | 2672 | 6/26/2015 | 6/26/2016 |
| Radiated Emissions, | 30 - 26,500 MHz, 13-Apr-16 | | | | |
| EMCO | Antenna, Horn, 1-18GHz | 3115 | 868 | 26-Jun-14 | 26-Jun-16 |
| Rohde & Schwarz | EMI Test Receiver, 20 Hz-7 GHz | ESIB7 | 1538 | 19-Dec-15 | 19-Dec-16 |
| Sunol Sciences | Biconilog, 30-3000 MHz | JB3 | 1549 | 02-Jun-15 | 02-Jun-17 |
| Hewlett Packard | High Pass filter, 1.5 GHz (Purple System) | P/N 84300- 80037 | 1769 | 03-Nov-15 | 03-Nov-16 |
| Hewlett Packard | Microwave Preamplifier, 1-26.5GHz | 8449B | 2199 | 09-Oct-15 | 09-Oct-16 |
| Hewlett Packard | Spectrum Analyzer (SA40) Purple 9 kHz - 40 GHz, | 8564E (84125C) | 2415 | 19-Mar-16 | 19-Mar-17 |
| Hewlett Packard | 9KHz-1300MHz pre-amp | 8447F | 2777 | 26-Jan-16 | 26-Jan-17 |
| | | | | | |

Project number JD100279 Reissue Date: April 27, 2016

Report Date: February 16, 2016

Appendix B Test Data

T100302 Pages 24 – 53 T100337 Pages 54 – 58



| The control of the co | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| Client: WateR8 | Job Number: JD100279 |
| Product R006 (900MHz radio module) | T-Log Number: T100302 |
| System Configuration: - | Project Manager: Sheareen Jacobs |
| Contact: Steve Smith | Project Coordinator: - |
| Emissions Standard(s): FCC 15.247 | Class: B |
| Immunity Standard(s): - | Environment: - |

EMC Test Data

For The

WateR8

Product

R006 (900MHz radio module)

Date of Last Test: 4/13/2016



| Client: | WateR8 | Job Number: | JD100279 |
|-----------|----------------------------|----------------------|-----------------|
| Madal | DOGG (000MHz radio modulo) | T-Log Number: | T100302 |
| Model. | R006 (900MHz radio module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |

Duty Cycle

Date of Test: 12/11/2015
Test Engineer: Mark Hill
Test Location: FT Chamber #4


Duty cycle measurements performed on the worse case data rate for power.

Notes: Measurements taken with maximum RBW/VBW settings allowed.

| Mode | Data Rate | Duty Cycle (x) | Constant DC? | T (ms) | Pwr Cor Factor* | Lin Volt Cor Factor** | Min VBW for FS (Hz) |
|------|-----------|----------------|--------------|--------|--------------------|-----------------------------|------------------------|
| - | 38.4 kHz | 100.00 | Yes | - | 0 | 0 | 10 |

^{*} Correction factor when using RMS/Power averaging - 10*log(1/x)

T = Minimum transmission duration



^{**} Correction factor when using linear voltage average - 20*log(1/x)



| 100 | | | |
|-----------|----------------------------|----------------------|-----------------|
| Client: | WateR8 | Job Number: | JD100279 |
| Model: | DOGG (000MHz radio modulo) | T-Log Number: | T100302 |
| | R006 (900MHz radio module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |

RSS-247 and FCC 15.247 (DTS) Radiated Spurious Emissions

Test Specific Details

Objective: The objective of this test session is to perform engineering evaluation testing of the EUT with respect to the specification listed above.

General Test Configuration

The EUT and all local support equipment were located on the turntable for radiated spurious emissions testing. For radiated emissions testing the measurement antenna was located 3 meters from the EUT, unless otherwise noted.

Ambient Conditions: Temperature: 23 °C

> Rel. Humidity: 38 %

Summary of Results - Device Operating in the 900 MHz Band

| Run# | Mode | Channel | Target Power Setting | Passing Power Setting | Test Performed | Limit | Result / Margin | | | | | | |
|------|--------------|--------------|----------------------------|-----------------------------|--------------------|-------------------|----------------------|----------------------|----|----|--------------------|-------------------|----------------------|
| 10 | Тх | 902.6MHz | -5 | -10 | Radiated Emissions | FCC Part 15.209 / | 47.7 dBµV/m @ 4507.5 | | | | | | |
| 1a | ΙX | 902.01/172 | -0 | -10 | 30 MHz-9.3GHz | 15.247(d) | MHz (-6.3 dB) | | | | | | |
| 16 | 1b Tx 915MHz | | Tv 015MU- | Tv 015MU- | Ty 015MU= | Tv 045MU- | 015MU= | Tv 015MU- | -5 | -5 | Radiated Emissions | FCC Part 15.209 / | 53.4 dBµV/m @ 2744.5 |
| 10 | | | -0 | -5 | 30 MHz-9.3GHz | 15.247(d) | MHz (-0.6 dB) | | | | | | |
| | | | | -5 | -5 | Restricted Band | FCC Part 15.209 / | 23.3 dBµV/m @ 960.67 | | | | | |
| 1c | Tx | Tx 927.4MHz | -0 | -5 | at 960 MHz | 15.247(d) | MHz (-30.7 dB) | | | | | | |
| | 1 X | 321.4IVII IZ | _ | 5 | Radiated Emissions | FCC Part 15.209 / | 87.6 dBµV/m @ 1854.5 | | | | | | |
| | | | -5 | -5 | 30 MHz-9.3GHz | 15.247(d) | MHz (-3.8 dB) | | | | | | |

Modifications Made During Testing

No modifications were made to the EUT during testing

Deviations From The Standard

No deviations were made from the requirements of the standard.



| Client: | WateR8 | Job Number: | JD100279 |
|-----------|----------------------------|----------------------|-----------------|
| Madali | DOGG (000MHz radio modula) | T-Log Number: | T100302 |
| iviodei. | R006 (900MHz radio module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |

Procedure Comments:

Measurements performed in accordance with FCC KDB 558074

Peak measurements performed with: RBW=1MHz, VBW=3MHz, peak detector, max hold, auto sweep time

Unless otherwise stated/noted, emission has duty cycle ≥ 98% and was measured using RBW=1MHz, VBW=10Hz, peak detector, linear average mode, auto sweep time, max hold.

Preliminary evaluation through three orientations performed to determine worse case (module flat). All results presented here performed in the worse case orientation.

| Mode | Data Rate | Duty Cycle (x) | Constant DC? | T (ms) | Pwr Cor Factor* | Lin Volt Cor Factor** | Min VBW for FS (Hz) |
|------|-----------|----------------|--------------|--------|--------------------|-----------------------------|------------------------|
| - | 38.4 kHz | 100.00 | Yes | - | 0 | 0 | 10 |

Sample Notes

Sample S/N: 15331507730235

Driver: -

Antenna: Bent Wire - 0dBi

Power setting = -5 dBm, unless noted otherwise.

Measurement Specific Notes:

| | | · · · · I · · · · · · · · · · · · · · · · · · · |
|---|---------|--------------------------------------------------------------------------------------------------------------------|
| 1 | Note 1: | Emission in non-restricted band, but limit of 15.209 used. |
| ١ | Note 2: | Emission in non-restricted band, the limit was set 30dB below the level of the fundamental and measured in 100kHz. |

Sample S/N: 235 (30-1000MHz)



| ' | LE ENGINEER SOCOESS | | |
|-----------|--------------------------------|----------------------|-----------------|
| Client: | WateR8 | Job Number: | JD100279 |
| Model: | R006 (900MHz radio module) | T-Log Number: | T100302 |
| | Rood (900IVII 12 Tadio Module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |

Run #1: Radiated Spurious Emissions, 30 - 9300 MHz

Date of Test: 12/11/15 Config. Used: 1
Test Engineer: Mark Hill Config Change: -

Test Location: FT#4 EUT Voltage: 120V/60 - Host

Run #1a: Low Channel @ 902.6 MHz

Fundamental Signal Field Strength: Peak and average values measured in 1 MHz, and peak value measured in 100kHz

Measured at power setting -5

| Frequency | Level | Pol | 15.209 | / 15.247 | Detector | Azimuth | Height | Comments |
|-----------|--------|-----|--------|----------|-----------|---------|--------|------------------------------|
| MHz | dBμV/m | v/h | Limit | Margin | Pk/QP/Avg | degrees | meters | |
| 902.390 | 110.1 | Н | - | • | PK | 109 | 1.0 | POS; RB 2 MHz; VB: 3 MHz |
| 902.390 | 110.0 | Н | - | • | PK | 109 | 1.0 | POS; RB 100 kHz; VB: 300 kHz |
| 902.410 | 108.4 | ٧ | - | • | PK | 61 | 1.5 | POS; RB 100 kHz; VB: 300 kHz |
| 902.289 | 108.4 | V | - | - | PK | 61 | 1.5 | POS; RB 2 MHz; VB: 3 MHz |


| Fundamental emission level @ 3m in 100kHz RBW: | 110.0 dBμV/m |
|--------------------------------------------------|---------------|
| Limit for emissions outside of restricted bands: | 90.0 dBμV/m L |
| Limit for emissions outside of restricted bands: | 80.0 dBμV/m L |

Limit is -20dBc (Peak power measurement)
Limit is -30dBc (UNII power measurement)

Other Spurious Emissions

| 4507.500 47.7 H 54.0 -6.3 Peak 162 1.00 2707.400 47.6 V 54.0 -6.4 AVG 140 0.99 Pwr setting = -10 5407.500 46.7 H 54.0 -7.3 Peak 342 1.00 3609.630 38.8 H 54.0 -15.2 AVG 45 1.81 Pwr setting = -10 | Frequency | Level | / Level | Pol | 15.209 | / 15.247 | Detector | Azimuth | Height | Comments |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|--------|---------|-----|--------|----------|-----------|---------|--------|----------------------------------|
| 4507.500 47.7 H 54.0 -6.3 Peak 162 1.00 2707.400 47.6 V 54.0 -6.4 AVG 140 0.99 Pwr setting = -10 5407.500 46.7 H 54.0 -7.3 Peak 342 1.00 3609.630 38.8 H 54.0 -15.2 AVG 45 1.81 Pwr setting = -10 | MHz | dBμV/m | dBμV/m | v/h | Limit | Margin | Pk/QP/Avg | degrees | meters | |
| 2707.400 47.6 V 54.0 -6.4 AVG 140 0.99 Pwr setting = -10 5407.500 46.7 H 54.0 -7.3 Peak 342 1.00 3609.630 38.8 H 54.0 -15.2 AVG 45 1.81 Pwr setting = -10 | 1804.870 | 88.1 | 88.1 | V | - | - | Pk | 87 | 1.06 | Note 4, RB 100 kHz;VB 300 kHz;Pk |
| 5407.500 46.7 H 54.0 -7.3 Peak 342 1.00 3609.630 38.8 H 54.0 -15.2 AVG 45 1.81 Pwr setting = -10 | 4507.500 | 47.7 | 47.7 | Н | 54.0 | -6.3 | Peak | 162 | 1.00 | |
| 3609.630 38.8 H 54.0 -15.2 AVG 45 1.81 Pwr setting = -10 | 2707.400 | 47.6 | 47.6 | V | 54.0 | -6.4 | AVG | 140 | 0.99 | Pwr setting = -10 |
| | 5407.500 | 46.7 | 46.7 | Н | 54.0 | -7.3 | Peak | 342 | 1.00 | |
| | 3609.630 | 38.8 | 38.8 | Н | 54.0 | -15.2 | AVG | 45 | 1.81 | Pwr setting = -10 |
| 114.950 25.8 V 43.5 -17.7 QP 50 1.0 Pwr setting = -5 | 114.950 | 25.8 | 25.8 | V | 43.5 | -17.7 | QP | 50 | 1.0 | Pwr setting = -5 |
| 2707.330 51.3 V 74.0 -22.7 PK 140 0.99 Pwr setting = -10 | 2707.330 | 51.3 | 51.3 | V | 74.0 | -22.7 | PK | 140 | 0.99 | Pwr setting = -10 |
| 3609.500 46.8 H 74.0 -27.2 PK 45 1.81 Pwr setting = -10 | 3609.500 | 46.8 | 46.8 | Н | 74.0 | -27.2 | PK | 45 | 1.81 | Pwr setting = -10 |

| Note 3: | There was no signal within 1000 to 1500 MHz related to radio module. |
|---------|------------------------------------------------------------------------|
| Note 4: | Emission in a non-restricted band, refer to antenna port measurements. |





| Client: | WateR8 | Job Number: | JD100279 |
|-----------|----------------------------|----------------------|-----------------|
| | | T-Log Number: | |
| | R006 (900MHz radio module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |

Run #1b: Center Channel @ 915 MHz


| Frequency | Level | Pol | 15.209 | / 15.247 | Detector | Azimuth | Height | Comments |
|-----------|--------|-----|--------|----------|-----------|---------|--------|------------------------------|
| MHz | dBμV/m | v/h | Limit | Margin | Pk/QP/Avg | degrees | meters | |
| 914.810 | 111.4 | Н | - | - | PK | 115 | 1.0 | POS; RB 2 MHz; VB: 3 MHz |
| 915.130 | 111.4 | Н | - | - | PK | 115 | 1.0 | POS; RB 100 kHz; VB: 300 kHz |
| 914.810 | 108.5 | V | - | - | PK | 112 | 1.0 | POS; RB 1 MHz; VB: 3 MHz |
| 914.810 | 108.5 | V | - | - | PK | 112 | 1.0 | POS; RB 100 kHz; VB: 300 kHz |

| Fundamental emission level @ 3m in 100kHz RBW: | 111.4 dBμV/m |
|--------------------------------------------------|--------------|
| Limit for emissions outside of restricted bands: | 91.4 dBμV/m |
| Limit for emissions outside of restricted bands: | 81.4 dBuV/m |

Limit is -20dBc (Peak power measurement)
Limit is -30dBc (UNII power measurement)


| Frequency | Level | Pol | 15.209 | / 15.247 | Detector | Azimuth | Height | Comments |
|-----------|--------|-----|--------|----------|-----------|---------|--------|----------------------------|
| MHz | dBμV/m | v/h | Limit | Margin | Pk/QP/Avg | degrees | meters | |
| 2744.500 | 53.4 | V | 54.0 | -0.6 | AVG | 307 | 1.27 | |
| 3659.250 | 49.4 | V | 54.0 | -4.6 | AVG | 329 | 1.22 | |
| 1830.370 | 86.6 | V | 91.4 | -4.8 | Pk | 89 | 1.02 | RB 100 kHz;VB 300 kHz;Peak |
| 119.419 | 26.9 | V | 43.5 | -16.6 | QP | 246 | 1.0 | QP (1.00s) |
| 2744.570 | 55.9 | V | 74.0 | -18.1 | PK | 307 | 1.27 | |
| 3659.170 | 53.5 | V | 74.0 | -20.5 | PK | 329 | 1.22 | |

Note 3: There was no signal within 1000 to 1500 MHz related to radio module.





| | Cold Building 1990 Per State Colored C | | |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|-----------------|
| Client: | WateR8 | Job Number: | JD100279 |
| Model: | DOGG (000MHz radio modulo) | T-Log Number: | T100302 |
| | R006 (900MHz radio module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |





| Client: | WateR8 | Job Number: | JD100279 |
|-----------|----------------------------|----------------------|-----------------|
| | | T-Log Number: | |
| | R006 (900MHz radio module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |

Run #1c: High Channel @ 927.4 MHz.

Fundamental Signal Field Strength: Peak and average values measured in 1 MHz, and peak value measured in 100kHz

| | J | | | | | | | |
|-----------|--------|-----|--------|----------|-----------|---------|--------|------------------------------|
| Frequency | Level | Pol | 15.209 | / 15.247 | Detector | Azimuth | Height | Comments |
| MHz | dBμV/m | v/h | Limit | Margin | Pk/QP/Avg | degrees | meters | |
| 927.550 | 111.4 | Н | - | - | PK | 225 | 1.0 | POS; RB 100 kHz; VB: 300 kHz |
| 927.550 | 112.2 | Н | - | - | PK | 225 | 1.0 | POS; RB 2 MHz; VB: 3 MHz |
| 927.230 | 109.3 | V | - | - | PK | 58 | 1.0 | POS; RB 2 MHz; VB: 3 MHz |
| 927.550 | 109.1 | V | - | - | PK | 58 | 1.0 | POS; RB 100 kHz; VB: 300 kHz |

| Fundamental emission level @ 3m in 100kHz RBW: | 111.4 dBμV/m | |
|--------------------------------------------------|--------------|------------------------------------------|
| Limit for emissions outside of restricted bands: | 91.4 dBμV/m | Limit is -20dBc (Peak power measurement) |
| Limit for emissions outside of restricted bands: | 81.4 dBμV/m | Limit is -30dBc (UNII power measurement) |

Band Edge Signal Field Strength - Direct measurement of field strength

| Frequency | Level | Pol | 15.209 | / 15.247 | Detector | Azimuth | Height | Comments |
|-----------|--------|-----|--------|----------|-----------|---------|--------|------------|
| MHz | dBμV/m | v/h | Limit | Margin | Pk/QP/Avg | degrees | meters | |
| 960.669 | 23.3 | V | 54.0 | -30.7 | QP | 8 | 1.0 | QP (1.00s) |
| 960.734 | 23.2 | Н | 54.0 | -30.8 | QP | 56 | 1.0 | QP (1.00s) |


Other Spurious Emissions


| | Title Countries Entire Control | | | | | | | | | |
|-----------|--------------------------------|-----|--------|----------|-----------|---------|--------|----------------------------|--|--|
| Frequency | Level | Pol | 15.209 | / 15.247 | Detector | Azimuth | Height | Comments | | |
| MHz | dBμV/m | v/h | Limit | Margin | Pk/QP/Avg | degrees | meters | | | |
| 1854.470 | 87.6 | Н | 91.4 | -3.8 | Pk | 93 | 1.00 | RB 100 kHz;VB 300 kHz;Peak | | |
| 2782.650 | 49.4 | Н | 54.0 | -4.6 | AVG | 37 | 1.00 | | | |
| 3708.850 | 48.6 | Н | 54.0 | -5.4 | AVG | 35 | 1.54 | | | |
| 4635.000 | 44.1 | Н | 54.0 | -9.9 | Peak | 130 | 2.00 | | | |
| 255.815 | 27.4 | Н | 46.0 | -18.6 | QP | 288 | 1.0 | QP (1.00s) | | |
| 3708.920 | 52.6 | Н | 74.0 | -21.4 | PK | 35 | 1.54 | | | |
| 2782.850 | 52.4 | Н | 74.0 | -21.6 | PK | 37 | 1.00 | | | |
| | | | | | | | | | | |

Note 3: There was no signal within 1000 to 1500 MHz related to radio module.



| | CALL STATES OF THE PROPERTY OF THE STATES OF | | |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|-----------------|
| Client: | WateR8 | Job Number: | JD100279 |
| Model: | R006 (900MHz radio module) | T-Log Number: | T100302 |
| | ROOD (900IVIAZ TAGIO MOGUIE) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |







| Client: | WateR8 | Job Number: | JD100279 |
|-----------|------------------------------|----------------------|-----------------|
| Madali | R006 (900MHz radio module) | T-Log Number: | T100302 |
| Model. | ROOD (900IVIAZ Tadio Module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |

Receiver Radiated Spurious Emissions

Test Specific Details

Objective: The objective of this test session is to perform engineering evaluation testing of the EUT with respect to the specification listed above.

General Test Configuration

The EUT and all local support equipment were located on the turntable for radiated spurious emissions testing. For radiated emissions testing the measurement antenna was located 3 meters from the EUT, unless otherwise noted.

Ambient Conditions: 15-18 °C Temperature:

> Rel. Humidity: 30-35 %

Summary of Results - Device Operating in the 900 MHz Band

| Run# | Mode | Channel | Target Power Setting | Passing Power Setting | Test Performed | Limit | Result / Margin |
|-------|----------------|-------------|----------------------------|-----------------------------|--------------------|------------------------|---------------------|
| 1a | Rx | 902.6MHz | | | Radiated Emissions | FCC Part 15.109 (Class | 37.0 dBµV/m @ 38.94 |
| Ta | IVA | 302.0WII 12 | - | - | 30 MHz-3GHz | B) | MHz (-3.0 dB) |
| 1h | 1b Rx 915.6MHz | | | | Radiated Emissions | FCC Part 15.109 (Class | 37.4 dBµV/m @ 38.83 |
| 10 | | | - | - | 30 MHz-3GHz | B) | MHz (-2.6 dB) |
| 1a Dv | Dv | Rx 927.4MHz | - | - | Radiated Emissions | FCC Part 15.109 (Class | 35.2 dBµV/m @ 38.47 |
| 1c | KX | | | | 30 MHz-3GHz | B) | MHz (-4.8 dB) |

Modifications Made During Testing

No modifications were made to the EUT during testing

Deviations From The Standard

No deviations were made from the requirements of the standard.

Procedure Comments:

Peak measurements performed with: RBW=1MHz, VBW=3MHz, peak detector, max hold, auto sweep time Unless otherwise stated/noted, emission has duty cycle ≥ 98% and was measured using RBW=1MHz, VBW=10Hz, peak detector, linear average mode, auto sweep time, max hold.

Preliminary evaluation through three orientations performed to determine worse case (module flat). All results presented here performed in the worse case orientation.



| Client: | WateR8 | Job Number: | JD100279 |
|-----------|----------------------------|----------------------|-----------------|
| Model: | DOGG (000MHz radio modula) | T-Log Number: | T100302 |
| | R006 (900MHz radio module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |

Sample Notes

Sample S/N: 15331507730235

Driver: -

Antenna: Bent Wire - 0dBi

Measurement Specific Notes:

Note 1:


Run #1: Radiated Spurious Emissions, 30 - 9300 MHz

Date of Test: 12/31/15 Config. Used: 1
Test Engineer: Mehran Birgani Config Change: -

Test Location: Chamber #7 Host EUT Voltage: 120V/ 60Hz


Run #1a: Low Channel @ 902.6 MHz

| Frequency | Level | Pol | 15.109 | Class B | Detector | Azimuth | Height | Comments |
|-----------|--------|-----|--------|---------|-----------|---------|--------|------------------------|
| MHz | dBμV/m | v/h | Limit | Margin | Pk/QP/Avg | degrees | meters | |
| 38.941 | 37.0 | V | 40.0 | -3.0 | QP | 293 | 1.0 | QP (1.00s) |
| 60.398 | 33.9 | V | 40.0 | -6.1 | QP | 132 | 1.0 | QP (1.00s) |
| 92.389 | 36.4 | V | 43.5 | -7.1 | QP | 182 | 1.0 | QP (1.00s) |
| 101.155 | 32.5 | V | 43.5 | -11.0 | QP | 212 | 1.0 | QP (1.00s) |
| 2408.000 | 35.7 | Н | 54.0 | -18.3 | AVG | 4 | 2.2 | RB 1 MHz;VB 10 Hz;Peak |
| 2406.990 | 44.0 | Н | 74.0 | -30.0 | PK | 4 | 2.2 | RB 1 MHz;VB 3 MHz;Peak |





| | THE STATES WATCHEST PROGRAMMED AND THE | | |
|-----------|----------------------------------------|----------------------|-----------------|
| Client: | WateR8 | Job Number: | JD100279 |
| Madalı | R006 (900MHz radio module) | T-Log Number: | T100302 |
| iviodei. | ROOD (900IVIAZ Tadio Module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |





Run #1b: Center Channel @ 915 MHz

| Frequency | Level | Pol | 15.109 | Class B | Detector | Azimuth | Height | Comments |
|-----------|--------|-----|--------|---------|-----------|---------|--------|------------------------|
| MHz | dBμV/m | v/h | Limit | Margin | Pk/QP/Avg | degrees | meters | |
| 38.825 | 37.4 | V | 40.0 | -2.6 | QP | 228 | 1.0 | QP (1.00s) |
| 95.991 | 36.2 | V | 43.5 | -7.3 | QP | 122 | 1.0 | QP (1.00s) |
| 60.592 | 32.6 | V | 40.0 | -7.4 | QP | 107 | 1.0 | QP (1.00s) |
| 2429.220 | 32.1 | Н | 54.0 | -21.9 | AVG | 284 | 1.0 | RB 1 MHz;VB 10 Hz;Peak |
| 1899.500 | 30.2 | V | 54.0 | -23.8 | AVG | 11 | 1.9 | RB 1 MHz;VB 10 Hz;Peak |
| 2429.150 | 43.1 | Н | 74.0 | -30.9 | PK | 284 | 1.0 | RB 1 MHz;VB 3 MHz;Peak |
| 1899.790 | 42.0 | V | 74.0 | -32.0 | PK | 11 | 1.9 | RB 1 MHz;VB 3 MHz;Peak |



| | COLOR STATES HAVE STATES AND ACCOUNTS AND AC | | |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|-----------------|
| Client: | WateR8 | Job Number: | JD100279 |
| Model: | DOGG (000MHz radio modulo) | T-Log Number: | T100302 |
| | R006 (900MHz radio module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |








| Client | WateR8 | Job Number: | ID100270 |
|-----------|-------------------------------|----------------------|-----------------|
| Ciletit. | vvalerio | | |
| Model: | R006 (900MHz radio module) | T-Log Number: | T100302 |
| | Rood (900IMI IZ Tadio Module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |


Run #1c: High Channel @ 927.4 MHz.

| | gii onamo | - /=/// | | | | | | • |
|-----------|-----------|---------|--------|---------|-----------|---------|--------|------------------------|
| Frequency | Level | Pol | 15.109 | Class B | Detector | Azimuth | Height | Comments |
| MHz | dBμV/m | v/h | Limit | Margin | Pk/QP/Avg | degrees | meters | |
| 38.474 | 35.2 | V | 40.0 | -4.8 | QP | 333 | 1.0 | QP (1.00s) |
| 87.435 | 29.7 | V | 40.0 | -10.3 | QP | 208 | 1.0 | QP (1.00s) |
| 59.687 | 26.8 | V | 40.0 | -13.2 | QP | 192 | 1.5 | QP (1.00s) |
| 102.284 | 27.9 | V | 43.5 | -15.6 | QP | 288 | 1.0 | QP (1.00s) |
| 2398.800 | 32.1 | Η | 54.0 | -21.9 | AVG | 300 | 2.5 | RB 1 MHz;VB 10 Hz;Peak |
| 2400.990 | 32.0 | Н | 54.0 | -22.0 | AVG | 300 | 2.5 | RB 1 MHz;VB 10 Hz;Peak |
| 2222.910 | 30.8 | ٧ | 54.0 | -23.2 | AVG | 142 | 1.6 | RB 1 MHz;VB 10 Hz;Peak |
| 2399.260 | 43.7 | Н | 74.0 | -30.3 | PK | 300 | 2.5 | RB 1 MHz;VB 3 MHz;Peak |
| 2399.170 | 43.6 | Н | 74.0 | -30.4 | PK | 300 | 2.5 | RB 1 MHz;VB 3 MHz;Peak |
| 2222.140 | 42.3 | V | 74.0 | -31.7 | PK | 142 | 1.6 | RB 1 MHz;VB 3 MHz;Peak |





| | COLOR STATES HAVE STATES AND ACCOUNTS AND AC | | |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|-----------------|
| Client: | WateR8 | Job Number: | JD100279 |
| Model: | DOGG (000MHz radio modulo) | T-Log Number: | T100302 |
| | R006 (900MHz radio module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |





| Client: | WateR8 | Job Number: | JD100279 |
|-----------|------------------------------|----------------------|-----------------|
| Model: | R006 (900MHz radio module) | T-Log Number: | T100302 |
| | ROOD (900IVIAZ Tadio Module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |

RSS-247 and FCC 15.247 (DTS) Radiated Spurious Emissions

Test Specific Details

Objective: The objective of this test session is to perform engineering evaluation testing of the EUT with respect to the specification listed above.

General Test Configuration

The EUT and all local support equipment were located on the turntable for radiated spurious emissions testing. For radiated emissions testing the measurement antenna was located 3 meters from the EUT, unless otherwise noted.

Ambient Conditions: Temperature: 23 °C

38 % Rel. Humidity:

Summary of Results - Device Operating in the 900 MHz Band

| Run # | Mode | Channel | Target Power Setting | Passing Power Setting | Test Performed | Limit | Result / Margin |
|-------|------|---------|----------------------------|-----------------------------|----------------------------------|--------------------------------|---------------------------------------|
| 1b | Тх | 915MHz | -5 | -5 | Radiated Emissions 30 MHz-9.3GHz | FCC Part 15.209 / 15.247(d) | 47.9 dBµV/m @ 2744.4 MHz (-6.1 dB) |

Modifications Made During Testing

Modified shield

Deviations From The Standard

No deviations were made from the requirements of the standard.



| Client: | WateR8 | Job Number: | JD100279 |
|-----------|------------------------------|----------------------|-----------------|
| Model: | R006 (900MHz radio module) | T-Log Number: | T100302 |
| | ROOD (900IVIAZ Tadio Module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |

Procedure Comments:

Measurements performed in accordance with FCC KDB 558074

Peak measurements performed with: RBW=1MHz, VBW=3MHz, peak detector, max hold, auto sweep time

Unless otherwise stated/noted, emission has duty cycle ≥ 98% and was measured using RBW=1MHz, VBW=10Hz, peak detector, linear average mode, auto sweep time, max hold.

Preliminary evaluation through three orientations performed to determine worse case (module flat). All results presented here performed in the worse case orientation.

| Mode | Data Rate | Duty Cycle (x) | Constant DC? | T (ms) | Pwr Cor Factor* | Lin Volt Cor Factor** | Min VBW for FS (Hz) |
|------|-----------|----------------|--------------|--------|--------------------|-----------------------------|------------------------|
| - | 38.4 kHz | 100.00 | Yes | • | 0 | 0 | 10 |

Sample Notes

Sample S/N: 15331507730130

Driver: -

Antenna: Bent Wire - 0dBi

Power setting = -5 dBm, unless noted otherwise.

Measurement Specific Notes:

| | · · |
|---------|--------------------------------------------------------------------------------------------------------------------|
| Note 1: | Emission in non-restricted band, but limit of 15.209 used. |
| Note 2: | Emission in non-restricted band, the limit was set 30dB below the level of the fundamental and measured in 100kHz. |



| Client: | WateR8 | Job Number: | JD100279 |
|-----------|----------------------------|----------------------|-----------------|
| Model: | DOGG (000MHz radio modula) | T-Log Number: | T100302 |
| | R006 (900MHz radio module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |

Run #1: Radiated Spurious Emissions, 30 - 9300 MHz

Date of Test: 04/13/16 Config. Used: 1 Test Engineer: M. Birgani

Config Change: -EUT Voltage: 120V/60 - Host Test Location: Chamber #7

| Frequency | Level | Pol | 15.209 | / 15.247 | Detector | Azimuth | Height | Comments |
|-----------|--------|-----|--------|----------|-----------|---------|--------|--------------------------------|
| MHz | dBμV/m | v/h | Limit | Margin | Pk/QP/Avg | degrees | meters | |
| 2744.430 | 47.9 | V | 54.0 | -6.1 | AVG | 114 | 1.6 | RB 1 MHz;VB 10 Hz;Peak |
| 2744.410 | 46.1 | Н | 54.0 | -7.9 | AVG | 115 | 1.2 | RB 1 MHz;VB 10 Hz;Peak |
| 3660.540 | 45.5 | V | 54.0 | -8.5 | AVG | 215 | 1.7 | RB 1 MHz;VB 10 Hz;Peak |
| 2745.380 | 53.0 | V | 74.0 | -21.0 | PK | 114 | 1.6 | RB 1 MHz;VB 3 MHz;Peak |
| 3660.720 | 50.9 | V | 74.0 | -23.1 | PK | 215 | 1.7 | RB 1 MHz;VB 3 MHz;Peak |
| 2744.440 | 50.2 | Н | 74.0 | -23.8 | PK | 115 | 1.2 | RB 1 MHz;VB 3 MHz;Peak |
| 1829.610 | 82.9 | V | - | - | PK | 156 | 1.8 | Note 4; RB 100 kHz; VB 300 kHz |

| Note 3: | There was no signal within 1000 to 1500 MHz related to radio module. |
|---------|------------------------------------------------------------------------|
| Note 4: | Emission in a non-restricted band, refer to antenna port measurements. |



| " | | | | | | | | |
|-----------|----------------------------|----------------------|-----------------|--|--|--|--|--|
| Client: | WateR8 | Job Number: | JD100279 | | | | | |
| Model: | R006 (900MHz radio module) | T-Log Number: | T100302 | | | | | |
| | Root (900MH2 Tadio Module) | Project Manager: | Sheareen Jacobs | | | | | |
| Contact: | Steve Smith | Project Coordinator: | - | | | | | |
| Standard: | FCC 15.247 | Class: | N/A | | | | | |

Receiver Radiated Spurious Emissions

Test Specific Details

Objective: The objective of this test session is to perform engineering evaluation testing of the EUT with respect to the specification listed above.

General Test Configuration

The EUT and all local support equipment were located on the turntable for radiated spurious emissions testing. For radiated emissions testing the measurement antenna was located 3 meters from the EUT, unless otherwise noted.

Ambient Conditions: 15-18 °C Temperature:

> Rel. Humidity: 30-35 %

Summary of Results - Device Operating in the 900 MHz Band

| Run # | Mode | Channel | Target Power Setting | Passing Power Setting | Test Performed | Limit | Result / Margin |
|-------|------|----------|----------------------------|-----------------------------|-----------------------------------|---------------------------|--------------------------------------|
| 1b | Rx | 915.6MHz | - | - | Radiated Emissions 30 MHz-3GHz | FCC Part 15.109 (Class B) | 37.0 dBµV/m @ 95.99 MHz (-6.5 dB) |

Modifications Made During Testing

linear average mode, auto sweep time, max hold.

Modified shield

Deviations From The Standard

No deviations were made from the requirements of the standard.

Procedure Comments:

Peak measurements performed with: RBW=1MHz, VBW=3MHz, peak detector, max hold, auto sweep time Unless otherwise stated/noted, emission has duty cycle ≥ 98% and was measured using RBW=1MHz, VBW=10Hz, peak detector,

Preliminary evaluation through three orientations performed to determine worse case (module flat). All results presented here performed in the worse case orientation.



| | Marin | | |
|-----------|----------------------------|----------------------|-----------------|
| Client: | WateR8 | Job Number: | JD100279 |
| Model: | DOGG (000MHz radio modulo) | T-Log Number: | T100302 |
| | R006 (900MHz radio module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |

Sample Notes

Sample S/N: 15331507730130

Driver:

Measurement Specific Notes:

Note 1: -

Run #1: Radiated Spurious Emissions, 30 - 9300 MHz

Run #1b: Center Channel @ 915.6 MHz

Date of Test: 04/13/16 Config. Used: 1
Test Engineer: M. Birgani Config Change: -

Test Location: Chamber #7 EUT Voltage: 120V/60 - Host

| Frequency | Level | Pol | 15.109 | Class B | Detector | Azimuth | Height | Comments |
|-----------|--------|-----|--------|---------|-----------|---------|--------|------------|
| MHz | dBμV/m | v/h | Limit | Margin | Pk/QP/Avg | degrees | meters | |
| 95.991 | 37.0 | V | 43.5 | -6.5 | QP | 345 | 1.0 | QP (1.00s) |
| 38.825 | 24.7 | V | 40.0 | -14.3 | QP | 345 | 1.0 | QP (1.00s) |

No other emissions observed



| Client: | WateR8 | Job Number: | JD100279 |
|-----------|------------------------------|----------------------|-----------------|
| Model: | R006 (900MHz radio module) | T-Log Number: | T100302 |
| | ROOD (900IVIAZ Tadio Module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |

RSS-247 and FCC 15.247 (DTS) Antenna Port Measurements Power, PSD, Bandwidth and Spurious Emissions

Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 12/11/2015 Config. Used: 1 Test Engineer: R. Varelas / M. Birgani Config Change: None

Test Location: FT Lab #4A EUT Voltage: 120V/60 - Host

General Test Configuration

The EUT was connected to the spectrum analyzer or power meter via a suitable attenuator. All measurements were made on a single

All measurements have been corrected to allow for the external attenuators used.

Ambient Conditions: Temperature: 18-20 °C

35-40 % Rel. Humidity:

Summary of Results

| Run# | Pwr setting | Avg Pwr | Test Performed | Limit | Pass / Fail | Result / Margin |
|------|-------------|---------|---------------------------------|-----------|-------------|------------------------|
| 1 | | | Output Power | 15.247(b) | Pass | 9.5 dBm |
| 2 | | | Power spectral Density (PSD) | 15.247(d) | Pass | 5.2 dBm/3kHz |
| 3 | | | Minimum 6dB Bandwidth 15.247(a) | | Pass | 535 kHz |
| 3 | | | 99% Bandwidth | RSS GEN | - | 565 kHz |
| | | | | | | All emissions are more |
| 4 | | | Spurious emissions | 15.247(b) | Pass | than 10dB below the |
| | | | | | | limit |

Modifications Made During Testing

No modifications were made to the EUT during testing

Deviations From The Standard

No deviations were made from the requirements of the standard.

Sample Notes

Sample S/N: 0192

Driver:



| | Marin | | |
|-----------|----------------------------|----------------------|-----------------|
| Client: | WateR8 | Job Number: | JD100279 |
| Model: | DOGG (000MHz radio modulo) | T-Log Number: | T100302 |
| | R006 (900MHz radio module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |

Procedure Comments:

Measurements performed in accordance with FCC KDB 558074

| Mode | Data Rate | Duty Cycle (x) | Constant DC? | T (ms) | Pwr Cor Factor* | Lin Volt Cor Factor** | Min VBW for FS (Hz) |
|------|-----------|----------------|--------------|--------|--------------------|-----------------------------|------------------------|
| - | 38.4 kHz | 100.00 | Yes | - | 0 | 0 | 10 |

Run #1: Output Power

HGM On and Manchester Mode

| Power | Fragues ov (MHz) | Output | Power | Antenna | Dogult | Ell | RP | Output | Power |
|----------------------|------------------|--------------------|-------|------------|--------|-----|-------|--------------------|-------|
| Setting ² | Frequency (MHz) | (dBm) ¹ | mW | Gain (dBi) | Result | dBm | W | (dBm) ³ | mW |
| -10 | 902.6 | 9.5 | 8.9 | 0.0 | Pass | 9.5 | 0.009 | | |
| -10 | 915.0 | 8.4 | 6.9 | 0.0 | Pass | 8.4 | 0.007 | | |
| -10 | 927.4 | 6.8 | 4.8 | 0.0 | Pass | 6.8 | 0.005 | | |

| Note 1: | Output power measured using a peak power meter, spurious limit is -20dBc. |
|---------|----------------------------------------------------------------------------------------------|
| Note 2: | Power setting - the software power setting used during testing, included for reference only. |




| Client: | WateR8 | Job Number: | JD100279 |
|-----------|----------------------------|----------------------|-----------------|
| Model: | DOGG (000MHz radio modulo) | T-Log Number: | T100302 |
| | R006 (900MHz radio module) | Project Manager: | Sheareen Jacobs |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.247 | Class: | N/A |

Run #2: Power spectral Density

HGM On and Manchester Mode

| Power | Fraguency (MUz) | PSD | Limit | Dogult | |
|---------|-----------------|-------------------|-------|--------|--|
| Setting | Frequency (MHz) | (dBm/3kHz) Note 1 | | Result | |
| -10 | 902.6 | 5.2 | 8.0 | Pass | |
| -10 | 915.0 | 4.0 | 8.0 | Pass | |
| -10 | 927.4 | 2.5 | 8.0 | Pass | |

Note 1: Test performed per method PKSPD, in KDB 558074. Power spectral density measured using: 3kHz ≤ RBW ≤ 100kHz, VBW=3*RBW, peak detector, span = 1.5*DTS BW, auto sweep time, max hold.






| Client: | WateR8 | Job Number: | JD100279 | |
|-----------|----------------------------|----------------------|-----------------|--|
| Madalı | DOGG (000MHz radio modula) | T-Log Number: | : T100302 | |
| iviodei. | R006 (900MHz radio module) | Project Manager: | Sheareen Jacobs | |
| Contact: | Steve Smith | Project Coordinator: | - | |
| Standard: | FCC 15.247 | Class: | N/A | |

Run #3: Signal Bandwidth

| Power | Frequency (MHz) | Bandwid | th (MHz) | RBW Sett | ing (MHz) |
|---------|------------------|---------|----------|----------|-----------|
| Setting | Frequency (MITZ) | 6dB | 99% | 6dB | 99% |
| -5 | 902.6 | 0.55 | 0.57 | 100kHz | 10kHz |
| -5 | 915.0 | 0.54 | 0.56 | 100kHz | 10kHz |
| -5 | 927.4 | 0.54 | 0.55 | 100kHz | 10kHz |

| NI . C . A | DTS BW: RBW=100kHz, VBW ≥ 3*RBW, peak detector, max hold, auto sweep time, Span 2-5 times measured BW. | | |
|------------|--------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|--|
| ľ | Note 1: | 99% BW: RBW=1-5% of 99%BW VBW ≥ 3*RBW peak detector max hold auto sweep time. Span 1.5-5 times OBW | |






| Client | WateR8 | Job Number: | ID100270 | |
|-----------|----------------------------|----------------------|-----------------|--|
| Ciletit. | vvalerio | | | |
| Madalı | R006 (900MHz radio module) | T-Log Number: | Г100302 | |
| iviodei. | ROOD (900MHz Tadio Module) | Project Manager: | Sheareen Jacobs | |
| Contact: | Steve Smith | Project Coordinator: | - | |
| Standard: | FCC 15.247 | Class: | N/A | |

Run #4a: Out of Band Spurious Emissions

| Frequency | (MHz) | Power Setting | Mode | Limit | Result |
|-----------|-------|------------------|------|--------|--------|
| 902.6 |) | -5 | - | -20dBc | Pass |
| 915.0 |) | -5 | • | -20dBc | Pass |
| 927.4 | | -5 | - | -20dBc | Pass |

RBW = 100 kHz and VBW = 300 kHz for all plots.

Plots for low channel





| Client: | WateR8 | Job Number: | JD100279 | | | |
|-----------|------------------------------|----------------------|-----------------|--|--|--|
| Model: | R006 (900MHz radio module) | T-Log Number: | er: T100302 | | | |
| | ROOD (900IVIAZ TAGIO MOGUIE) | Project Manager: | Sheareen Jacobs | | | |
| Contact: | Steve Smith | Project Coordinator: | - | | | |
| Standard: | FCC 15.247 | Class: | N/A | | | |

Additional plot showing -20dBc at 902MHz



Rohde&Schwarz,ESI CF: 902.600 MHz SPAN: 2,000 MHz RB: 100 kHz VB: 300 kHz Detector: POS Attn: 10 DB RL Offset: 0.0 DB Sweep Time: 5.0ms Ref Lvl: 87.0 DBUV

Comments Center = 902.6MHz PA Sample

Cursor 1 903.0589 **+** -*- 6-80.1 **♦ ♦** Cursor 2 902.0810 60.1


Delta Freq. 978 kHz Delta Amplitude 20.0






| | 1961 J. 1850 C. S. MICH SCHOOL STATE CONTROL OF THE | | | | | |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|-----------------|--|--|--|
| Client: | WateR8 | Job Number: | JD100279 | | | |
| Model: | DOGG (000MHz radio modula) | T-Log Number: | | | | |
| | R006 (900MHz radio module) | Project Manager: She | Sheareen Jacobs | | | |
| Contact: | Steve Smith | Project Coordinator: | - | | | |
| Standard: | FCC 15.247 | Class: | N/A | | | |


Plots for center channel



Plots for high channel









| Client: WateR8 | Job Number: JD100279 |
|--------------------------------------------|------------------------------------|
| Product UnitNode (Repeater) | T-Log Number: T100337 |
| System Configuration: - | Project Manager: Christine Krebill |
| Contact: Steve Smith | Project Coordinator: |
| Emissions Standard(s): FCC 15.B / EN 55022 | Class: B |
| Immunity Standard(s): - | Environment: - |

EMC Test Data

For The

WateR8

Product

UnitNode (Repeater)

Date of Last Test: 2/11/2016



| Client: | WateR8 | Job Number: | JD100279 | | |
|-----------|------------------------|-----------------------|-------------------|--|--|
| Model: | UnitNode (Repeater) | T-Log Number: T100337 | | | |
| | Official de (Repeater) | Project Manager: | Christine Krebill | | |
| Contact: | Steve Smith | Project Coordinator: | - | | |
| Standard: | FCC 15.B / EN 55022 | Class: | В | | |

Conducted Emissions

(NTS Silicon Valley, Fremont Facility, Semi-Anechoic Chamber)

Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the

specification listed above.

Date of Test: 12/29/2015 Config. Used: 1
Test Engineer: Mehran Birgani Config Change: -

Test Location: Chamber #7 EUT Voltage: Refer to each run

General Test Configuration

The EUT was located on a non-conductive table inside the semi-anechoic chamber, 40 cm from a vertical coupling plane and 80cm

from the LISN.

Ambient Conditions: Temperature: 15-17 °C

Rel. Humidity: 30-35 %

Summary of Results

| Run # | Test Performed | Limit | Result | Margin |
|-------|------------------------|---------|--------|------------------------------|
| 1 | CE, AC Power,120V/60Hz | Class B | PASS | 44.8dBµV @ 0.76MHz (-11.2dB) |

Modifications Made During Testing

No modifications were made to the EUT during testing

Deviations From The Standard


No deviations were made from the requirements of the standard.


Note: The unit was transmitting during testing and working in normal operation mode.



| | 1963 S | | | | | |
|-----------|---------------------|----------------------|-------------------|--|--|--|
| Client: | WateR8 | Job Number: | JD100279 | | | |
| Madal | UnitNode (Repeater) | T-Log Number: | nber: T100337 | | | |
| Model. | milivoue (Repealer) | Project Manager: | Christine Krebill | | | |
| Contact: | Steve Smith | Project Coordinator: | - | | | |
| Standard: | FCC 15.B / EN 55022 | Class: | В | | | |

Run #1: AC Power Port Conducted Emissions, 0.15 - 30MHz, 120V/60Hz








| Client: | WateR8 | Job Number: | JD100279 |
|-----------|---------------------|-----------------------|-------------------|
| Model: | UnitNada (Panastar) | T-Log Number: T100337 | |
| | UnitNode (Repeater) | Project Manager: | Christine Krebill |
| Contact: | Steve Smith | Project Coordinator: | - |
| Standard: | FCC 15.B / EN 55022 | Class: | В |

Run #1: AC Power Port Conducted Emissions, 0.15 - 30MHz, 120V/60Hz

Preliminary peak readings captured during pre-scan (peak readings vs. average limit)

| Frequency | Level | AC | Class B | | Detector | Comments |
|-----------|-------|---------|---------|--------|----------|----------|
| MHz | dΒμV | Line | Limit | Margin | QP/Ave | |
| 0.499 | 53.7 | Line | 46.0 | 7.7 | Peak | |
| 0.764 | 50.2 | Neutral | 46.0 | 4.2 | Peak | |
| 1.609 | 49.2 | Line | 46.0 | 3.2 | Peak | |
| 2.551 | 49.1 | Neutral | 46.0 | 3.1 | Peak | |
| 0.371 | 51.2 | Line | 48.4 | 2.8 | Peak | |
| 0.401 | 50.6 | Line | 47.8 | 2.8 | Peak | |
| 1.130 | 48.8 | Neutral | 46.0 | 2.8 | Peak | |
| 0.344 | 51.8 | Neutral | 49.1 | 2.7 | Peak | |
| 0.433 | 49.8 | Line | 47.2 | 2.6 | Peak | |
| 0.492 | 48.8 | Neutral | 46.2 | 2.6 | Peak | |
| 2.553 | 48.4 | Line | 46.0 | 2.4 | Peak | |
| 6.524 | 39.1 | Neutral | 50.0 | -10.9 | Peak | |
| 6.425 | 37.6 | Line | 50.0 | -12.4 | Peak | |
| 8.152 | 35.0 | Line | 50.0 | -15.0 | Peak | |
| | | | | | | |



Report Date: February 16, 2016

Project number JD100279 Reissue Date: April 27, 2016

End of Report

This page is intentionally blank and marks the last page of this test report.