



## Shenzhen Asia Test Technology Co., Ltd.

7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District, Shenzhen, China  
Tel: +86)-0755-23284990 Email: [att@att-lab.com](mailto:att@att-lab.com) Http: // [www.att-lab.cn](http://www.att-lab.cn)

# FCC RADIO TEST REPORT

## FCC ID: 2AGSWBLK27

<b>Product :</b>	WiFi connected digital frame for streaming art
<b>Trade Name :</b>	Meural
<b>Model Name :</b>	MEU1BLK27
<b>Serial Model :</b>	MEU1LGT27

### Prepared for

Meural Inc.
902 Broadway 6th Floor, New York NY, USA, 10010

### Prepared by

Shenzhen Asia Test Technology Co.,Ltd.
7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District, Shenzhen, China
Tel: +(86)-0755-23284990 Fax: +(86)-0755-23284990 Http: <a href="http://www.att-lab.cn">www.att-lab.cn</a>



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 2 of 55 -

## TEST RESULT CERTIFICATION

<b>Manufacturer's Name</b> .....	Wintec Industries
Address .....	675 Sycamore Road, Milpitas CA, USA, 95035
<b>Product description</b>	
Product name .....	WiFi connected digital frame for streaming art
Model and/or type reference .....	MEU1BLK27
Additional Model .....	MEU1LGT27
<b>Standards</b> .....	FCC Part15.247
Test procedure .....	ANSI C63.4-2009

This device described above has been tested by ATT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ATT, this document may be altered or revised by ATT, personal only, and shall be noted in the revision of the document.

<b>Date of Test</b> .....	
Date (s) of performance of tests .....	Nov. 12 2015 ~Dec. 17 2015
Date of Issue .....	Dec. 17 2015
Test Result .....	<b>Pass</b>

Testing Engineer	:	<i>Jack Yu</i>
		(Jack Yu)
Technical Manager	:	<i>Jerry You</i>
		(Jerry You)
Authorized Signatory	:	<i>Can Liu</i>
		(Can Liu)



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 3 of 55 -

Table of Contents	Page
<b>1 . SUMMARY OF TEST RESULTS</b>	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
<b>2 . GENERAL INFORMATION</b>	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
<b>3 . EMC EMISSION TEST</b>	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST PROCEDURE	14
3.1.3 DEVIATION FROM TEST STANDARD	14
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS	14
3.1.6 TEST RESULTS	15
3.2 RADIATED EMISSION MEASUREMENT	17
3.2.1 RADIATED EMISSION LIMITS	17
3.2.2 TEST PROCEDURE	17
3.2.3 DEVIATION FROM TEST STANDARD	18
3.2.4 TEST SETUP	19
3.2.5 EUT OPERATING CONDITIONS	20
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	21
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	22
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	23
<b>4 . POWER SPECTRAL DENSITY TEST</b>	36
4.1 APPLIED PROCEDURES / LIMIT	36
4.1.1 TEST PROCEDURE	36
4.1.2 DEVIATION FROM STANDARD	36
4.1.3 TEST SETUP	36



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 4 of 55 -

Table of Contents	Page
4.1.4 EUT OPERATION CONDITIONS	36
4.1.5 TEST RESULTS	37
<b>5 . BANDWIDTH TEST</b>	<b>41</b>
5.1 APPLIED PROCEDURES / LIMIT	41
5.1.1 TEST PROCEDURE	41
5.1.2 EUT OPERATION CONDITIONS	41
5.1.3 TEST RESULTS	42
<b>6 . PEAK OUTPUT POWER TEST</b>	<b>46</b>
6.1 APPLIED PROCEDURES / LIMIT	46
6.1.1 TEST PROCEDURE	46
6.1.2 DEVIATION FROM STANDARD	46
6.1.3 TEST SETUP	46
6.1.4 EUT OPERATION CONDITIONS	46
6.1.5 TEST RESULTS	47
<b>7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE</b>	<b>48</b>
7.1 DEVIATION FROM STANDARD	48
7.2 TEST SETUP	48
7.3 EUT OPERATION CONDITIONS	48
7.4 TEST RESULTS	49
<b>8 . ANTENNA REQUIREMENT</b>	<b>53</b>
8.1 STANDARD REQUIREMENT	53
8.2 EUT ANTENNA	53
<b>9 . EUT TEST PHOTO</b>	<b>54</b>
<b>APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS</b>	



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 5 of 55 -

## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

### NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 6 of 55 -

## 1.1 TEST FACILITY

DongGuan Yaxu(AiT) Technology Limited  
No. 22, JinQianLing Street 3, JiTiGang Village, Huang-Jiang Town, DongGuan, Guangdong,  
523757 China

FCC Registration No.: 248337

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 7 of 55 -

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment		WiFi connected digital frame for streaming art
Model Name		MEU1BLK27
Serial Model		MEU1LGT27
Model Difference		All models are identical except model name.
Product Description	The EUT is a WiFi connected digital frame for streaming art	
	Operation Frequency:	802.11b/g: 2412~2462MHz
	Modulation Type:	BPSK/QPSK16-QAM
	Bit Rate of Transmitter	802.11b: DBPSK, DQPSK(11, 5.5, 2, 1 Mbps) 802.11g: BPSK,QPSK,16QAM, 64QAM (54,48,36,24,18,12,9,6 Mbps)
	Number Of Channel	802.11b/g:11CH
	Antenna Designation:	Please see Note 3.
	Output Power(Conducted):	802.11b: 8.74 dBm (Max. AV) 802.11g: 8.16dBm (Max. AV)
	Antenna Gain (dBi)	0dbi
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
	Channel List	Please refer to the Note 2.
Ratings		12Vdc from adapter,AC 120V/60Hz for adapter
Adapter		Model: FJ-SW1204000U Input: 100-240V~50/60Hz 1.5A Output: 12Vdc 4000mA
Battery		N/A
Connecting I/O Port(s)		Please refer to the User's Manual
hardware version		DPF21_20151013_V1.0
Software version		V1.1
Note:		
1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 8 of 55 -

2.

Channel List for 802.11b/g							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

3.

Table for Filed Antenna

Ant .	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
A	N/A	N/A	PCB Antenna	ipex	0	Wifi Antenna



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 9 of 55 -

## 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.	
Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	Link Mode

For Conducted Emission	
Final Test Mode	Description
Mode 3	Link Mode
For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11

Note:
(1) The measurements are performed at the highest, middle, lowest available channels.
(2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported. The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.
(3) measurements are performed according to the KDB 558074 D01 DTS Meas Guidance v03r03

Test Items	Mode	Data Rate	Channel
Maximum Peak Conducted Output Power Power Spectral Density 6dB Bandwidth Spurious RF conducted emission Radiated Emission 9kHz~1GHz& Radiated Emission 1GHz~10th Harmonic	11b/DSSS	1 Mbps	1/6/11
	11g/OFDM	6 Mbps	1/6/11
Band Edge	11b/DSSS	1 Mbps	1/11
	11g/OFDM	6 Mbps	1/11



# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1201016F  
- Page 10 of 55 -

NOTE: Typical working modes for each IEEE 802.11 mode are selected to perform tests. The manufacturer provide special test software(rftesttool\_v47) to control TX duty cycle >98% for TX test. Set the output power to 13.5dbm(PK)


Test Mode	Test Modes Description
11b	IEEE 802.11b with data rate of 1 Mbps using SISO mode.
11g	IEEE 802.11g with data rate of 6 Mbps using SISO mode.

## 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


RE



RF conducted measurement



CE





## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 11 of 55 -

### 2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	WiFi connected digital frame for streaming art	Meural	MEU1BLK27	N/A	EUT
E-2	adapter	N/A	FJ-SW1204000U	N/A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	1.5m	Adapter DC Cable

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in『Length』column.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 12 of 55 -

## 2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

### For Conducted Test (In Shielded Room)

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	EMI Receiver	R&S	ESCI	100124	2015.06.26	1Y
2	L.I.S.N.#1	Kyoritsu	KNW-242	8-837-4	2015.06.26	1Y
3	L.I.S.N.#2	Kyoritsu	KNW-407	8-1789-4	2015.06.26	1Y
4	Coaxial Switch	Anritsu	MP59B	6200264417	2015.06.26	6M
5	Cable 0.09-30MHz	N/A	AIT005	C001	2015.07.10	1 Y

### For Radiation Test and other conducted test (bandwidth,output power, power spectral density)

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	ADVANTEST	R3182	150900201	2015.06.26	1Y
2	EMI Measuring Receiver	R&S	ESR	101160	2015.06.26	1Y
3	Preamplifier	Tsj	MLA-10K01-B01-27	1205323	2015.06.26	1Y
4	Preamplifier	Tsj	MLA-0120-A02-34	2648A04738	2015.12.02	1Y
5	Bilog Antenna	SCHWARZBECK	VULB9160	3206	2015.12.03	1Y
6	Horn Antenna	SCHWARZBECK	BBHA 9120D	452	2015.12.03	1Y
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.05.29	1 Y
8	Loop Antenna	TESEQ	HLA6120	35779	2015.05.29	1 Y
9	Coaxial Switch	Anritsu	MP59B	6200264416	2015.09.25	6M
10	Power Mete	Anritsu	ML2487B	110553	2015.07.10	1Y
11	Power Sensor	Anritsu	MA2411B	100345	2015.07.10	1Y
12	Cable below 30MHz	N/A	AIT005	R005	2015.07.10	1Y
13	RF Cabl 30-1000MHz	N/A	AIT001	R001	2015.07.10	1Y
14	RF Cabl 1-25GHz	N/A	AIT001	R001	2015.07.10	1Y



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 13 of 55 -

## 3. EMC EMISSION TEST

### 3.1 CONDUCTED EMISSION MEASUREMENT

#### 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 14 of 55 -


### 3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 DEVIATION FROM TEST STANDARD

No deviation

### 3.1.4 TEST SETUP



Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

### 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 15 of 55 -


## 3.1.6 TEST RESULTS

EUT :	WiFi connected digital frame for streaming art	Model Name. :	MEU1BLK27
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter	Test Mode :	Mode 3

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor(dB)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)	Margin (dB)	Detector
0.1500	40.01	11.94	51.95	65.99	-14.04	QP
0.1500	23.23	11.94	35.17	55.99	-20.82	Average
4.0619	25.73	10.00	35.73	56.00	-20.27	QP
4.0619	14.78	10.00	24.78	46.00	-21.22	Average
25.3460	47.25	2.23	49.48	60.00	-10.52	QP
25.3460	39.04	2.23	41.27	50.00	-8.73	Average

### Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. N/A means All Data have pass Limit





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1201016F  
- Page 16 of 55 -

EUT :	WiFi connected digital frame for streaming art	Model Name. :	MEU1BLK27
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter	Test Mode :	Mode 3

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor(dB)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)	Margin (dB)	Detector
0.1500	42.00	11.94	53.94	65.99	-12.05	QP
0.1500	29.84	11.94	41.78	55.99	-14.21	Average
3.8020	24.79	9.99	34.78	56.00	-21.22	QP
3.8020	13.92	9.99	23.91	46.00	-22.09	Average
25.4660	45.66	2.23	47.89	60.00	-12.11	QP
25.4660	37.78	2.23	40.01	50.00	-9.99	Average

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. N/A means All Data have pass Limit





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 17 of 55 -

## 3.2 RADIATED EMISSION MEASUREMENT

### 3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Notes:
(1) The limit for radiated test was performed according to FCC PART 15C.
(2) The tighter limit applies at the band edges.
(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average
Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

### 3.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 18 of 55 -

- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- g. For the radiated emission test above 1GHz:  
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


## 3.2.3 DEVIATION FROM TEST STANDARD

No deviation




## 3.2.4 TEST SETUP

### (A) Radiated Emission Test-Up Frequency Below 30MHz



### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz






# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 20 of 55 -

## (C) Radiated Emission Test-Up Frequency Above 1GHz



### 3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 21 of 55 -

### 3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

EUT:	WiFi connected digital frame for streaming art	Model Name. :	MEU1BLK27
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	TX	Polarization :	--

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State
--	--	--	--	P
--	--	--	--	P

#### NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);  
Limit line = specific limits(dBuV) + distance extrapolation factor.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 22 of 55 -

## 3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	20 °C	Relative Humidity :	48%
Pressure:	1010 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	802.11B TX 2412		

Polarization	Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Detect or Type	Comment
								Below 1G
Horizontal	40.5591	42.91	-16.74	26.17	40.00	-13.83	QP	57.62
Horizontal	67.9128	44.52	-19.08	25.44	40.00	-14.56	QP	128.56
Horizontal	159.7844	45.33	-15.01	30.32	43.50	-13.18	QP	226.35
Horizontal	231.7178	45.69	-12.57	33.12	46.00	-12.88	QP	280.52
Horizontal	366.8231	42.74	-7.57	35.17	46.00	-10.83	QP	360.15
Horizontal	545.1825	43.13	-3.86	39.27	46.00	-6.73	QP	479.62
Vertical	32.0667	43.95	-15.35	28.60	40.00	-11.40	QP	43.51
Vertical	46.9947	43.79	-14.28	29.51	40.00	-10.49	QP	176.36
Vertical	106.3850	44.60	-15.50	29.10	43.50	-14.40	QP	254.63
Vertical	243.3771	44.79	-11.56	33.23	46.00	-12.77	QP	360.16
Vertical	414.7223	42.45	-6.63	35.82	46.00	-10.18	QP	420.32
Vertical	549.0193	43.04	-3.58	39.46	46.00	-6.54	QP	515.73

Note: test perform on 802.11b/g mode, "802.11b TX2412" mode is the worst mode and has been reported.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 23 of 55 -

## 3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Detect or Type	Comment
Low Channel (2412 MHz)-Above 1G							
4824.000	57.88	5.08	62.96	74.00	-11.04	Pk	Vertical
4824.000	45.29	5.08	50.37	54.00	-3.63	Av	Vertical
7236.000	46.39	7.16	53.55	74.00	-20.45	Pk	Vertical
7236.000	35.71	7.16	42.87	54.00	-11.13	Av	Vertical
4824.000	57.42	5.08	62.50	74.00	-11.50	Pk	Horizontal
4824.000	43.23	5.08	48.31	54.00	-5.69	Av	Horizontal
7236.000	48.29	7.16	55.45	74.00	-18.55	Pk	Horizontal
7236.000	37.43	7.16	44.59	54.00	-9.41	Av	Horizontal
Mid Channel (2437 MHz)-Above 1G							
4874.000	58.30	5.13	63.43	74.00	-10.57	Pk	Vertical
4874.000	44.22	5.13	49.35	54.00	-4.65	Av	Vertical
7311.000	48.58	7.49	56.07	74.00	-17.93	Pk	Vertical
7311.000	36.19	7.49	43.68	54.00	-10.32	Av	Vertical
4874.000	57.54	5.13	62.67	74.00	-11.33	Pk	Horizontal
4874.000	42.37	5.13	47.50	54.00	-6.50	Av	Horizontal
7311.000	48.61	7.49	56.10	74.00	-17.90	Pk	Horizontal
7311.000	36.40	7.49	43.89	54.00	-10.11	Av	Horizontal
High Channel (2462 MHz)- Above 1G							
4924.000	57.47	5.18	62.65	74.00	-11.35	Pk	Vertical
4924.000	42.58	5.18	47.76	54.00	-6.24	Av	Vertical
7386.000	50.60	7.82	58.42	74.00	-15.58	Pk	Vertical
7386.000	36.21	7.82	44.03	54.00	-9.97	Av	Vertical
4924.000	56.15	5.18	61.33	74.00	-12.67	Pk	Horizontal
4924.000	41.34	5.18	46.52	54.00	-7.48	Av	Horizontal
7386.000	50.50	7.82	58.32	74.00	-15.68	Pk	Horizontal
7386.000	37.26	7.82	45.08	54.00	-8.92	Av	Horizontal

Note: test perform on 802.11b/g mode, "802.11b" mode is the worst mode and has been reported.





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 24 of 55 -

## Conducted Spurious Emissions at Antenna Port:



### 802.11b Low Channel





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 25 of 55 -




802.11b Middle Channel



# Shenzhen Asia Test Technology Co., Ltd.



Report No. ATT-2015SZ1201016F  
- Page 26 of 55 -





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 27 of 55 -





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 28 of 55 -




This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1201016F  
- Page 29 of 55 -





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1201016F  
- Page 30 of 55 -





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1201016F  
- Page 31 of 55 -





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1201016F  
- Page 32 of 55 -





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1201016F  
- Page 33 of 55 -





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1201016F  
- Page 34 of 55 -





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 35 of 55 -





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 36 of 55 -

## 4. POWER SPECTRAL DENSITY TEST

### 4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


#### 4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW  $\geq$  3 kHz.
4. Set the VBW  $\geq$  3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

#### 4.1.2 DEVIATION FROM STANDARD

No deviation.

#### 4.1.3 TEST SETUP



#### 4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.



# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1201016F  
- Page 37 of 55 -

## 4.1.5 TEST RESULTS

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	TX b Mode /CH01, CH06, CH11		

Note: The relevant measured result has the offset with cable loss already.


Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2412 MHz	-8.02	8	PASS
2437 MHz	-8.60	8	PASS
2462 MHz	-7.85	8	PASS





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 38 of 55 -






# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 39 of 55 -

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	TX g Mode /CH01, CH06, CH11		

Note: The relevant measured result has the offset with cable loss already.


Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2412 MHz	-14.96	8	PASS
2437 MHz	-15.92	8	PASS
2462 MHz	-15.58	8	PASS





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 40 of 55 -





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 41 of 55 -

## 5. BANDWIDTH TEST


### 5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

#### 5.1.1 TEST PROCEDURE

According to KDB 558074 D01 DTS Meas Guidance v03r03

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



#### 5.1.2 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 42 of 55 -

## 5.1.3 TEST RESULTS

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	TX b Mode /CH01, CH06, CH11		


Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	10.776	500	Pass
Middle	2437	9.217	500	Pass
High	2462	10.197	500	Pass





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 43 of 55 -






# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 44 of 55 -

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	TX g Mode /CH01, CH06, CH11		


Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	16.440	500	Pass
Middle	2437	16.440	500	Pass
High	2462	16.440	500	Pass





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 45 of 55 -





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 46 of 55 -

## 6. PEAK OUTPUT POWER TEST

### 6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS


#### 6.1.1 TEST PROCEDURE

a. The EUT was directly connected to the Power meter

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### 6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 47 of 55 -

## 6.1.5 TEST RESULTS

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	TX b/g Mode		

Test Channel	Frequency (MHz)	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(AV)	LIMIT (dBm)
		(dBm)	(dBm)	
802.11b				
CH01	2412	13.45	8.21	30
CH06	2437	13.26	8.74	30
CH11	2462	13.33	8.56	30
802.11g				
CH01	2412	12.94	8.14	30
CH06	2437	12.77	8.16	30
CH11	2462	12.93	8.12	30

Note: the highest AVG powers for:
802.11b: 1Mbps
802.11g: 6Mbps



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 48 of 55 -

## 7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

### APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


### TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 1 MHz and VBW of spectrum analyzer to 3 MHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

### 7.1 DEVIATION FROM STANDARD

No deviation.

### 7.2 TEST SETUP



### 7.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 49 of 55 -

### 7.4 TEST RESULTS

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter

Frequency Band	Delta Peak to band emission (dBc)	>Limit (dBc)	Result
802.11b			
≤2400	34.48	20	Pass
≥2483.5	60.25	20	Pass
802.11g			
≤2400	27.42	20	Pass
≥2483.5	31.91	20	Pass



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 50 of 55 -


Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Detect or Type	Comment
802.11b							
2390.0	44.83	9.86	54.69	74.00	-19.31	Pk	Vertical
2390.0	38.17	9.86	48.03	54.00	-5.97	Av	Vertical
2483.5	40.25	10.14	50.39	74.00	-23.61	Pk	Vertical
2483.5	32.31	10.14	42.45	54.00	-11.55	Av	Vertical
802.11g							
2390.0	41.36	9.86	51.22	74.00	-22.78	Pk	Vertical
2390.0	35.42	9.86	45.28	54.00	-8.72	Av	Vertical
2483.5	40.79	10.14	50.93	74.00	-23.07	Pk	Vertical
2483.5	34.11	10.14	44.25	54.00	-9.75	Av	Vertical




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 51 of 55 -

## 802.11b: Band Edge, Left Side



## : Band Edge, Right Side







# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 52 of 55 -

## 802.11g: Band Edge, Left Side



## 802.11g: Band Edge, Right Side





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 53 of 55 -

## 8. ANTENNA REQUIREMENT

### 8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 8.2 EUT ANTENNA

The EUT antenna is PCB Antenna. Use ipex antenna connector. It comply with the standard requirement.




## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 54 of 55 -

### 9. EUT TEST PHOTO

Radiated Measurement Photos



This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1201016F  
- Page 55 of 55 -

## Conducted Measurement Photos

