



## Shenzhen Asia Test Technology Co., Ltd.

7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District, Shenzhen, China  
Tel: +86)-0755-23284990 Email: [att@att-lab.com](mailto:att@att-lab.com) Http: // [www.att-lab.cn](http://www.att-lab.cn)

# FCC RADIO TEST REPORT

## FCC ID: 2AGSWBLK27

<b>Product :</b>	WiFi connected digital frame for streaming art
<b>Trade Name :</b>	Meural
<b>Model Name :</b>	MEU1BLK27
<b>Serial Model :</b>	MEU1LGT27

### Prepared for

Meural Inc.
902 Broadway 6th Floor, New York NY, USA, 10010

### Prepared by

Shenzhen Asia Test Technology Co.,Ltd.
7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District, Shenzhen, China
Tel: +(86)-0755-23284990 Fax: +(86)-0755-23284990 Http: <a href="http://www.att-lab.cn">www.att-lab.cn</a>

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 2 of 68 -

## TEST RESULT CERTIFICATION

Manufacturer's Name .....	Wintec Industries
Address .....	675 Sycamore Road, Milpitas CA, USA, 95035
<b>Product description</b>	
Product name .....	WiFi connected digital frame for streaming art
Model and/or type reference .....	MEU1BLK27
Additional Model .....	MEU1LGT27
<b>Standards .....</b>	FCC Part15.247
Test procedure .....	ANSI C63.4-2009
This device described above has been tested by ATT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.	
This report shall not be reproduced except in full, without the written approval of ATT, this document may be altered or revised by ATT, personal only, and shall be noted in the revision of the document.	
Date of Test .....	
Date (s) of performance of tests .....	Nov. 12 2015 ~Nov. 25 2015
Date of Issue .....	Nov. 25 2015
Test Result .....	<b>Pass</b>

Testing Engineer	:	<i>Jack Yu</i>
		(Jack Yu)
Technical Manager	:	<i>Jerry You</i>
		(Jerry You)
Authorized Signatory	:	<i>Can Liu</i>
		(Can Liu)



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 3 of 68 -

Table of Contents	Page
<b>1 . SUMMARY OF TEST RESULTS</b>	<b>6</b>
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
<b>2 . GENERAL INFORMATION</b>	<b>8</b>
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	11
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	12
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
<b>3 . EMC EMISSION TEST</b>	<b>14</b>
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	14
3.1.2 TEST PROCEDURE	15
3.1.3 DEVIATION FROM TEST STANDARD	15
3.1.4 TEST SETUP	15
3.1.5 EUT OPERATING CONDITIONS	15
3.1.6 TEST RESULTS	15
3.2 RADIATED EMISSION MEASUREMENT	18
3.2.1 RADIATED EMISSION LIMITS	18
3.2.2 TEST PROCEDURE	19
3.2.3 DEVIATION FROM TEST STANDARD	19
3.2.4 TEST SETUP	20
3.2.5 EUT OPERATING CONDITIONS	21
3.2.6 TEST RESULTS (BELOW 30 MHZ)	22
3.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ)	23
<b>4 . NUMBER OF HOPPING CHANNEL</b>	<b>37</b>
4.1 APPLIED PROCEDURES / LIMIT	37
4.1.1 TEST PROCEDURE	37
4.1.2 DEVIATION FROM STANDARD	37



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 4 of 68 -

Table of Contents	Page
4.1.3 TEST SETUP	37
4.1.4 EUT OPERATION CONDITIONS	37
4.1.5 TEST RESULTS	38
<b>5 . AVERAGE TIME OF OCCUPANCY</b>	<b>40</b>
5.1 APPLIED PROCEDURES / LIMIT	40
5.1.1 TEST PROCEDURE	40
5.1.2 DEVIATION FROM STANDARD	40
5.1.3 TEST SETUP	41
5.1.4 EUT OPERATION CONDITIONS	41
5.1.5 TEST RESULTS	42
<b>6 . HOPPING CHANNEL SEPARATION MEASUREMENT</b>	<b>46</b>
6.1 APPLIED PROCEDURES / LIMIT	46
6.1.1 TEST PROCEDURE	46
6.1.2 DEVIATION FROM STANDARD	46
6.1.3 TEST SETUP	46
6.1.4 EUT OPERATION CONDITIONS	46
6.1.5 TEST RESULTS	47
<b>7 . BANDWIDTH TEST</b>	<b>51</b>
7.1 APPLIED PROCEDURES / LIMIT	51
7.1.1 TEST PROCEDURE	51
7.1.2 DEVIATION FROM STANDARD	51
7.1.3 TEST SETUP	51
7.1.4 EUT OPERATION CONDITIONS	51
7.1.5 TEST RESULTS	52
<b>8 . PEAK OUTPUT POWER TEST</b>	<b>56</b>
8.1 APPLIED PROCEDURES / LIMIT	56
8.1.1 TEST PROCEDURE	56
8.1.2 DEVIATION FROM STANDARD	56
8.1.3 TEST SETUP	56
8.1.4 EUT OPERATION CONDITIONS	56
8.1.5 TEST RESULTS	57
<b>9 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE</b>	<b>58</b>

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 5 of 68 -

Table of Contents	Page
<b>9.1 DEVIATION FROM STANDARD</b>	<b>58</b>
<b>9.2 TEST SETUP</b>	<b>59</b>
<b>9.3 EUT OPERATION CONDITIONS</b>	<b>59</b>
<b>9.4 TEST RESULTS</b>	<b>60</b>
<b>10 . ANTENNA REQUIREMENT</b>	<b>66</b>
<b>10.1 STANDARD REQUIREMENT</b>	<b>66</b>
<b>10.2 EUT ANTENNA</b>	<b>66</b>
<b>11 . EUT TEST PHOTO</b>	<b>67</b>
<b>APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS</b>	



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 6 of 68 -

## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(c)	Radiated Spurious Emission	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

### NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 7 of 68 -

## 1.1 TEST FACILITY

DongGuan Yaxu(AiT) Technology Limited  
No. 22, JinQianLing Street 3, JiTiGang Village, Huang-Jiang Town, DongGuan, Guangdong,  
523757 China

FCC Registration No.: 248337

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 8 of 68 -

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	WiFi connected digital frame for streaming art														
Model Name	MEU1BLK27														
Serial number	N/A														
Serial Model	MEU1LGT27														
Model Difference	All models are identical except model name.														
Product Description	<p>The EUT is a WiFi connected digital frame for streaming art</p> <table border="1"><tr><td>Operation Frequency:</td><td>2402~2480 MHz</td></tr><tr><td>Bluetooth version:</td><td>2.1+EDR</td></tr><tr><td>Modulation Type:</td><td>GFSK, <math>(\pi/4)</math>DQPSK, 8DPSK</td></tr><tr><td>Bit Rate of Transmitter</td><td>1Mbps,2Mbps,3Mbps</td></tr><tr><td>Number Of Channel</td><td>79 CH</td></tr><tr><td>Antenna Designation:</td><td>Please see Note 3.</td></tr><tr><td>Output Power(Conducted):</td><td>2.29 dBm PK</td></tr></table> <p>Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</p>	Operation Frequency:	2402~2480 MHz	Bluetooth version:	2.1+EDR	Modulation Type:	GFSK, $(\pi/4)$ DQPSK, 8DPSK	Bit Rate of Transmitter	1Mbps,2Mbps,3Mbps	Number Of Channel	79 CH	Antenna Designation:	Please see Note 3.	Output Power(Conducted):	2.29 dBm PK
Operation Frequency:	2402~2480 MHz														
Bluetooth version:	2.1+EDR														
Modulation Type:	GFSK, $(\pi/4)$ DQPSK, 8DPSK														
Bit Rate of Transmitter	1Mbps,2Mbps,3Mbps														
Number Of Channel	79 CH														
Antenna Designation:	Please see Note 3.														
Output Power(Conducted):	2.29 dBm PK														
Channel List	Please refer to the Note 2.														
Ratings	12Vdc from adapter,AC 120V/60Hz for adapter														
Adapter	Model: FJ-SW1204000U Input: 100-240V~50/60Hz 1.5A Output: 12Vdc 4000mA														
Battery	N/A														
Connecting I/O Port(s)	Please refer to the User's Manual														
hardware version	DPF21_20151013_V1.0														
Software version	V1.1														

Note:	
1.	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 9 of 68 -

2.	Channel List						
	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	
00	2402	27	2429	54	2456		
01	2403	28	2430	55	2457		
02	2404	29	2431	56	2458		
03	2405	30	2432	57	2459		
04	2406	31	2433	58	2460		
05	2407	32	2434	59	2461		
06	2408	33	2435	60	2462		
07	2409	34	2436	61	2463		
08	2410	35	2437	62	2464		
09	2411	36	2438	63	2465		
10	2412	37	2439	64	2466		
11	2413	38	2440	65	2467		
12	2414	39	2441	66	2468		
13	2415	40	2442	67	2469		
14	2416	41	2443	68	2470		
15	2417	42	2444	69	2471		
16	2418	43	2445	70	2472		
17	2419	44	2446	71	2473		
18	2420	45	2447	72	2474		
19	2421	46	2448	73	2475		
20	2422	47	2449	74	2476		
21	2423	48	2450	75	2477		
22	2424	49	2451	76	2478		
23	2425	50	2452	77	2479		
24	2426	51	2453	78	2480		
25	2427	52	2454				
26	2428	53	2455				
3.	Table for Filed Antenna						
	Ant .	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
	1	N/A	N/A	PCB Antenna	ipex connector	0	



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 10 of 68 -

## 2.2 DESCRIPTION OF TEST MODES

	To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.										
	<table border="1"><thead><tr><th>Pretest Mode</th><th>Description</th></tr></thead><tbody><tr><td>Mode 1</td><td>CH00</td></tr><tr><td>Mode 2</td><td>CH39</td></tr><tr><td>Mode 3</td><td>CH78</td></tr><tr><td>Mode 4</td><td>Link BT</td></tr></tbody></table>	Pretest Mode	Description	Mode 1	CH00	Mode 2	CH39	Mode 3	CH78	Mode 4	Link BT
Pretest Mode	Description										
Mode 1	CH00										
Mode 2	CH39										
Mode 3	CH78										
Mode 4	Link BT										
	<table border="1"><thead><tr><th colspan="2">For Conducted Emission</th></tr><tr><th>Final Test Mode</th><th>Description</th></tr></thead><tbody><tr><td>Mode 4</td><td>Link BT</td></tr></tbody></table>	For Conducted Emission		Final Test Mode	Description	Mode 4	Link BT				
For Conducted Emission											
Final Test Mode	Description										
Mode 4	Link BT										
	<table border="1"><thead><tr><th colspan="2">For Radiated Emission</th></tr><tr><th>Final Test Mode</th><th>Description</th></tr></thead><tbody><tr><td>Mode 1</td><td>CH00</td></tr><tr><td>Mode 2</td><td>CH39</td></tr><tr><td>Mode 3</td><td>CH78</td></tr></tbody></table>	For Radiated Emission		Final Test Mode	Description	Mode 1	CH00	Mode 2	CH39	Mode 3	CH78
For Radiated Emission											
Final Test Mode	Description										
Mode 1	CH00										
Mode 2	CH39										
Mode 3	CH78										
	<p>Note:</p> <p>(1) The measurements are performed at the highest, middle, lowest available channels.</p> <p>(2) Measurements are performed according to the Public Notice-DA 00-705.</p> <p>(3) Test perform on all mode(BDR and EDR), only records worse cases in the test report.</p>										




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 11 of 68 -


## 2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

	During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS															
	<table border="1"><tr><td>Test software Version</td><td colspan="3">Test program: Broadcom</td></tr><tr><td>Frequency</td><td>2402 MHz</td><td>2441 MHz</td><td>2480 MHz</td></tr><tr><td>Parameters</td><td>DEF</td><td>DEF</td><td>DEF</td></tr></table>				Test software Version	Test program: Broadcom			Frequency	2402 MHz	2441 MHz	2480 MHz	Parameters	DEF	DEF	DEF
Test software Version	Test program: Broadcom															
Frequency	2402 MHz	2441 MHz	2480 MHz													
Parameters	DEF	DEF	DEF													
	Test software Version	2402 MHz	2441 MHz	2480 MHz												
	Parameters	DEF	DEF	DEF												


## 2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



RF conducted measurement



CE





## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 12 of 68 -

### 2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	WiFi connected digital frame for streaming art	Meural	MEU1BLK27	N/A	EUT
E-2	adapter	N/A	FJ-SW1204000U	N/A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	1.5cm	Adapter DC Cable

Note:	
(1)	The support equipment was authorized by Declaration of Confirmation.
(2)	For detachable type I/O cable should be specified the length in cm in 『Length』 column.
(3)	“YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 13 of 68 -

## 2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

### For Conducted Test (In Shielded Room)

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	EMI Receiver	R&S	ESCI	100124	2015.06.26	1Y
2	L.I.S.N.#1	Kyoritsu	KNW-242	8-837-4	2015.06.26	1Y
3	L.I.S.N.#2	Kyoritsu	KNW-407	8-1789-4	2015.06.26	1Y
4	Coaxial Switch	Anritsu	MP59B	6200264417	2015.06.26	6M
5	Cable 0.09-30MHz	N/A	AIT005	C001	2015.07.10	1 Y

### For Radiation Test and other conducted test (bandwidth,output power, power spectral density)

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	ADVANTEST	R3182	150900201	2015.06.26	1Y
2	EMI Measuring Receiver	R&S	ESR	101160	2015.06.26	1Y
3	Preamplifier	Tsj	MLA-10K01-B01-27	1205323	2015.06.26	1Y
4	Preamplifier	Tsj	MLA-0120-A02-34	2648A04738	2014.12.02	1Y
5	Bilog Antenna	SCHWARZBECK	VULB9160	3206	2014.12.03	1Y
6	Horn Antenna	SCHWARZBECK	BBHA 9120D	452	2014.12.03	1Y
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.05.29	1 Y
8	Loop Antenna	TESEQ	HLA6120	35779	2015.05.29	1 Y
9	Coaxial Switch	Anritsu	MP59B	6200264416	2015.09.25	6M
10	Power Mete	Anritsu	ML2487B	110553	2015.07.10	1Y
11	Power Sensor	Anritsu	MA2411B	100345	2015.07.10	1Y
12	Cable below 30MHz	N/A	AIT005	R005	2015.07.10	1Y
13	RF Cabl 30-1000MHz	N/A	AIT001	R001	2015.07.10	1Y
14	RF Cabl 1-25GHz	N/A	AIT001	R001	2015.07.10	1Y



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 14 of 68 -

## 3. EMC EMISSION TEST

### 3.1 CONDUCTED EMISSION MEASUREMENT

#### 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 15 of 68 -


## 3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

## 3.1.3 DEVIATION FROM TEST STANDARD

No deviation

## 3.1.4 TEST SETUP



**Note:** 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

## 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

## 3.1.6 TEST RESULTS

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
-------	--	--------------	-----------

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 16 of 68 -

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	Line
Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter	Test Mode :	4

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor(dB)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)	Margin (dB)	Detector
0.1819	38.33	11.36	49.69	64.39	-14.70	QP
0.1819	28.96	11.36	40.32	54.39	-14.07	Average
3.9260	24.35	10.00	34.35	56.00	-21.65	QP
3.9260	13.30	10.00	23.30	46.00	-22.70	Average
25.5980	45.45	2.23	47.68	60.00	-12.32	QP
25.5980	37.85	2.23	40.08	50.00	-9.92	Average

Remark: Factor = Absorbing clamp Factor + Cable Loss.






# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 17 of 68 -

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	Neutral
Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter	Test Mode :	4

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor(dB)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)	Margin (dB)	Detector
0.1500	41.96	11.94	53.90	65.99	-12.09	QP
0.1500	24.18	11.94	36.12	55.99	-19.87	Average
3.9620	25.13	10.00	35.13	56.00	-20.87	QP
3.9620	15.02	10.00	25.02	46.00	-20.98	Average
25.4740	47.00	2.23	49.23	60.00	-10.77	QP
25.4740	38.98	2.23	41.21	50.00	-8.79	Average

Remark: Factor = Absorbing clamp Factor + Cable Loss.





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 18 of 68 -

## 3.2 RADIATED EMISSION MEASUREMENT

### 3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10 <sup>th</sup> carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 19 of 68 -

### 3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

I. For the radiated emission test above 1GHz:  
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

Note:  
Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


### 3.2.3 DEVIATION FROM TEST STANDARD

No deviation




## 3.2.4 TEST SETUP

### (A) Radiated Emission Test-Up Frequency Below 30MHz



### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz






# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 21 of 68 -

## C) Radiated Emission Test-Up Frequency Above 1GHz



### 3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 22 of 68 -

### 3.2.6 TEST RESULTS (BELOW 30 MHZ)

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	TX	Polarization :	---

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	P
--	--	--	--	P

#### NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $20 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 23 of 68 -

## 3.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ)

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	24 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Mode :	TX 2402
Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	35.8746	44.01	-16.76	27.25	40.00	-12.75	QP
V	107.8876	46.26	-13.46	32.80	43.50	-10.70	QP
V	131.2965	45.90	-14.88	31.02	43.50	-12.48	QP
V	231.7178	46.36	-12.57	33.79	46.00	-12.21	QP
V	287.9904	45.15	-9.85	35.30	46.00	-10.70	QP
V	472.1759	43.89	-6.05	37.84	46.00	-8.16	QP
H	46.9947	44.25	-14.28	29.97	40.00	-10.03	QP
H	63.5356	43.68	-17.78	25.90	40.00	-14.10	QP
H	90.2205	44.41	-16.79	27.62	43.50	-15.88	QP
H	171.3925	45.54	-12.99	32.55	43.50	-10.95	QP
H	293.0842	44.78	-9.90	34.88	46.00	-11.12	QP
H	414.7223	42.91	-6.63	36.28	46.00	-9.72	QP

### Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit

Note: test perform on BDR/EDR mode, "BDR TX 2402" mode is the worst mode and has been reported.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 24 of 68 -

## 3.2.8 TEST RESULTS (Above 1GHz~ 10th harmonic)

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	24 °C	Relative Humidity :	48%
Pressure :	1010hPa	Test Mode :	TX
Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter		

Low Channel (2402 MHz)-Above 1G							
Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type	Polar (H/V)
4804.000	53.71	5.06	58.77	74.00	-15.23	Pk	Vertical
4804.000	41.30	5.06	46.36	54.00	-7.64	Av	Vertical
7206.000	45.52	7.03	52.55	74.00	-21.45	Pk	Vertical
7206.000	33.13	7.03	40.16	54.00	-13.84	Av	Vertical
4804.000	52.21	5.06	57.27	74.00	-16.73	Pk	Horizontal
4804.000	40.50	5.06	45.56	54.00	-8.44	Av	Horizontal
7206.000	46.33	7.03	53.36	74.00	-20.64	Pk	Horizontal
7206.000	34.64	7.03	41.67	54.00	-12.33	Av	Horizontal
Mid Channel (2441 MHz)-Above 1G							
4882.000	54.07	5.14	59.21	74.00	-14.79	Pk	Vertical
4882.000	42.26	5.14	47.40	54.00	-6.60	Av	Vertical
7323.000	48.59	7.54	56.13	74.00	-17.87	Pk	Vertical
7323.000	35.38	7.54	42.92	54.00	-11.08	Av	Vertical
4882.000	54.09	5.14	59.23	74.00	-14.77	Pk	Horizontal
4882.000	42.68	5.14	47.82	54.00	-6.18	Av	Horizontal
7323.000	46.37	7.54	53.91	74.00	-20.09	Pk	Horizontal
7323.000	35.14	7.54	42.68	54.00	-11.32	Av	Horizontal
High Channel (2480MHz)- Above 1G							
4960.000	54.24	5.22	59.46	74.00	-14.54	Pk	Vertical
4960.000	41.36	5.22	46.58	54.00	-7.42	Av	Vertical
7440.000	47.15	8.06	55.21	74.00	-18.79	Pk	Vertical
7440.000	34.28	8.06	42.34	54.00	-11.66	Av	Vertical
4960.000	54.14	5.22	59.36	74.00	-14.64	Pk	Horizontal
4960.000	39.62	5.22	44.84	54.00	-9.16	Av	Horizontal
7440.000	46.58	8.06	54.64	74.00	-19.36	Pk	Horizontal
7440.000	34.43	8.06	42.49	54.00	-11.51	Av	Horizontal

Note: test perform on BDR/EDR mode, "BDR" mode is the worst mode and has been reported.


This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 25 of 68 -


Conducted Spurious Emissions at Antenna Port  
(there are 150001 points are used for each measurement plot)





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1128655F1  
- Page 26 of 68 -





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1128655F1  
- Page 27 of 68 -





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1128655F1  
- Page 28 of 68 -





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1128655F1  
- Page 29 of 68 -





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1128655F1  
- Page 30 of 68 -





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1128655F1  
- Page 31 of 68 -





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1128655F1  
- Page 32 of 68 -





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1128655F1  
- Page 33 of 68 -





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1128655F1  
- Page 34 of 68 -





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1128655F1  
- Page 35 of 68 -





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 36 of 68 -



Note: test perform on BDR/EDR mode, the worst mode has been reported.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 37 of 68 -

## 4. NUMBER OF HOPPING CHANNEL

### 4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	≥15	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	≥ 1% of the span
VB	VBW ≥ RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


### 4.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW= 1MHz, VBW=1MHz, Sweep time = Auto.

### 4.1.2 DEVIATION FROM STANDARD

No deviation.

### 4.1.3 TEST SETUP



### 4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 38 of 68 -

## 4.1.5 TEST RESULTS

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	Hopping Mode-1Mbps		

Number of Hopping Channel	79
---------------------------	----






# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 39 of 68 -

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	Hopping Mode-3Mbps		

Number of Hopping Channel	79
---------------------------	----





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 40 of 68 -

## 5. AVERAGE TIME OF OCCUPANCY

### 5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

#### 5.1.1 TEST PROCEDURE

a.	The transmitter output (antenna port) was connected to the spectrum analyzer
b.	Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
c.	Use a video trigger with the trigger level set to enable triggering only on full pulses.
d.	Sweep Time is more than once pulse time.
e.	Set the center frequency on any frequency would be measure and set the frequency span to zero span.
f.	Measure the maximum time duration of one single pulse.
h.	Measure the maximum time duration of one single pulse.

#### 5.1.2 DEVIATION FROM STANDARD


No deviation.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 41 of 68 -

### 5.1.3 TEST SETUP



### 5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 42 of 68 -

## 5.1.5 TEST RESULTS

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	TX		


Data rate	Frequency	Plus Duration (ms)	Dwell Time (s)	Limits (s)
DH1	2441MHz	0.452	0.144	0.4
DH3	2441MHz	1.212	0.193	0.4
DH5	2441MHz	2.944	0.314	0.4





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 43 of 68 -






# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 44 of 68 -

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	TX		


Data rate	Frequency	Plus Duration (ms)	Dwell Time (s)	Limits (s)
3DH1	2441MHz	0.460	0.147	0.4
3DH3	2441MHz	1.704	0.272	0.4
3DH5	2441MHz	2.960	0.315	0.4





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 45 of 68 -





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 46 of 68 -

## 6. HOPPING CHANNEL SEPARATION MEASUREMENT

### 6.1 APPLIED PROCEDURES / LIMIT

<input type="checkbox"/>	Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.
--------------------------	--

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	100 kHz
VB	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 6.1.1 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- b. The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised for channel separation measurement.

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### 6.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.



# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2015SZ1128655F1  
- Page 47 of 68 -

## 6.1.5 TEST RESULTS

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	24 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	CH00 / CH39 /CH78 (1Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.004	Complies
2441 MHz	1.001	Complies
2480 MHz	1.004	Complies


Ch. Separation Limits: >20dB bandwidth





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 48 of 68 -



This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 49 of 68 -

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	24 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	CH00 / CH39 /CH78 (3Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.007	Complies
2441 MHz	1.013	Complies
2480 MHz	1.004	Complies


## Ch. Separation Limits: >20dB bandwidth





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 50 of 68 -





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 51 of 68 -

## 7. BANDWIDTH TEST

### 7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	100 kHz
VB	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 7.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW= 100KHz, VBW=300KHz, Sweep time = Auto.

#### 7.1.2 DEVIATION FROM STANDARD

No deviation.

#### 7.1.3 TEST SETUP



#### 7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 52 of 68 -

## 7.1.5 TEST RESULTS

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	CH00 / CH39 /C78(1Mbps)		


Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.0969	PASS
2441 MHz	1.0969	PASS
2480 MHz	1.0999	PASS





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 53 of 68 -






# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 54 of 68 -

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	CH00 / CH39 /C78(3Mbps)		

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.336	PASS
2441 MHz	1.339	PASS
2480 MHz	1.342	PASS





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 55 of 68 -



This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 56 of 68 -

## 8. PEAK OUTPUT POWER TEST

### 8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(i)	Peak Output Power	0.125 w or 1w	2400-2483.5	PASS


#### 8.1.1 TEST PROCEDURE

a. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power Meter.

#### 8.1.2 DEVIATION FROM STANDARD

No deviation.

#### 8.1.3 TEST SETUP



#### 8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 57 of 68 -

### 8.1.5 TEST RESULTS

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter
Test Mode :	CH00/ CH39 /CH78		

Note: The relevant measured result has the offset with cable loss already.

<b>1Mbps</b>			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)
CH00	2402	2.15	30
CH39	2440	2.29	30
CH78	2480	2.23	30

<b>3Mbps</b>			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)
CH00	2402	1.88	21
CH39	2440	1.75	21
CH78	2480	1.13	21



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 58 of 68 -

## 9. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

### 9.1 DEVIATION FROM STANDARD


No deviation.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 59 of 68 -

### 9.2 TEST SETUP



### 9.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 60 of 68 -

## 9.4 TEST RESULTS

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	24 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter

Frequency Band (MHz)	Delta Peak to band emission (dBc)	> Limit (dBc)	Result
1Mbps Non-hopping			
≤2400	44.84	20	Pass
≥2483.5	59.52	20	Pass
1Mbps hopping			
≤2400	48.63	20	Pass
≥2483.5	62.15	20	Pass

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Detector Type	Comment
1Mbps Non-hopping							
2390.0	56.14	-13.06	43.08	54.00	-10.92	peak	Vertical
2390.0	58.73	-13.06	45.67	54.00	-8.33	peak	Horizontal
2483.5	56.52	-12.78	43.74	54.00	-10.26	peak	Vertical
2483.5	57.11	-12.78	44.33	54.00	-9.67	peak	Horizontal

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Detector Type	Comment
1Mbps hopping							
2390.0	55.23	-13.06	42.17	54.00	-11.83	peak	Vertical
2390.0	54.17	-13.06	41.11	54.00	-12.89	peak	Horizontal
2483.5	53.52	-12.78	40.74	54.00	-13.26	peak	Vertical
2483.5	54.35	-12.78	41.57	54.00	-12.43	peak	Horizontal

Note: Test method to see chapter 3.2 . When PK value is lower than the Average value limit, average didn't record.


This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 61 of 68 -

## Band Edge, Left Side





This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 62 of 68 -

## Band Edge, Right Side



This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 63 of 68 -

EUT :	WiFi connected digital frame for streaming art	Model Name :	MEU1BLK27
Temperature :	24 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V from adapter, AC 120V/60Hz for adapter

Frequency Band	Delta Peak to band emission (dBc)	> Limit (dBc)	Result
3Mbps Non-hopping			
≤2400	50.38	20	Pass
≥2483.5	57.32	20	Pass
3Mbps hopping			
≤2400	55.55	20	Pass
≥2483.5	59.10	20	Pass

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Detector Type	Comment		
3Mbps Non-hopping									
2390	55.23	-13.06	42.17	54.00	-11.83	peak	Vertical		
2390	58.21	-13.06	45.15	54.00	-8.85	peak	Horizontal		
2483.5	57.09	-12.78	44.31	54.00	-9.69	peak	Vertical		
2483.5	57.16	-12.78	44.38	54.00	-9.62	peak	Horizontal		

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Detector Type	Comment		
3Mbps hopping									
2390	53.52	-13.06	40.46	54.00	-13.54	peak	Vertical		
2390	55.17	-13.06	42.11	54.00	-11.89	peak	Horizontal		
2483.5	54.49	-12.78	41.71	54.00	-12.29	peak	Vertical		
2483.5	58.36	-12.78	45.58	54.00	-8.42	peak	Horizontal		

Note: Test method to see chapter 3.2 . When PK value is lower than the Average value limit, average didn't record.


This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 64 of 68 -

## Band Edge, Left Side







# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 65 of 68 -

## Band Edge, Right Side





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 66 of 68 -

## 10. ANTENNA REQUIREMENT

### 10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 10.2 EUT ANTENNA

The EUT antenna is PCB Antenna. Use ipex antenna connector. It comply with the standard requirement.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 67 of 68 -

### 11. EUT TEST PHOTO

#### Conducted Measurement Photos



#### Radiated Measurement Photos

##### Between 30MHz-1GHz





## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ1128655F1  
- Page 68 of 68 -

### Above 1GHz

