

Razor USA LLC

SAR COMPLIANCE REPORT

Report Type:
FCC SAR assessment report

Model:
C45

REPORT NUMBER:
221201042SHA-002

ISSUE DATE:
February 13, 2023

DOCUMENT CONTROL NUMBER:
TTRFFCCSAR-01_V2 © 2022 Intertek



Applicant: Razor USA LLC
12723 166th Street, Cerritos CA90703, USA

Manufacturer: Razor USA LLC
12723 166th Street, Cerritos CA90703, USA

Factory: Zhejiang Bosuer Motion Apparatus CO., LTD
No. 9, Hardware East Road, Hardware Machinery Industrial Estate,
Wuyi City, Zhejiang Province, China

FCC ID: 2AGU6008

SUMMARY:


The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D04 Interim General RF Exposure Guidance v01

FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

PREPARED BY:**REVIEWED BY:**

Scout Gong
Project Engineer


Eric Li
Reviewer

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Report No.	Version	Description	Issued Date
221201042SHA-002	Rev. 01	Initial issue of report	February 13, 2023

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Razor Electric Scooter
Type/Model:	C45
Description of EUT:	The EUT is an adult electric scooter with BLE function.
Rating:	Battery charger adapter: Input 100-240VAC, 50/60Hz, 2.5A. Output 54.6V, 1.5A Battery capacity: 46.8V, 7.6Ah
Category of EUT:	Class B
EUT type:	☐ Tabletop ☒ Floor standing
Software Version:	/
Hardware Version:	/
Sample Identification No.:	0230108-51-001
Sample received date:	January 20, 2023
Date of test:	January 21, 2023– February 10, 2023

1.2 Technical Specification

Frequency Band:	2400MHz ~ 2483.5MHz
Support Standards:	Bluetooth LE 5.0
Type of Modulation:	GFSK
Channel Number:	40
Data Rate:	1Mbps
Channel Separation:	2MHz
Antenna Information:	-1.0dBi gain, PCB antenna

TEST REPORT

1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road (North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Member No: 3598 (Registration No.: R-14243, G-10845, C-14723, T-12252)
	A2LA Accreditation Lab Certificate Number: 3309.02

2 SAR Assessment

Test result: Pass

2.1 SAR Test Exclusion Limit

This method shall only be used at separation distances up to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula below:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula above.

The example values shown in below are for illustration only.

Frequency (MHz)	Distance (mm)										
		5	10	15	20	25	30	35	40	45	50
300		39	65	88	110	129	148	166	184	201	217
450		22	44	67	89	112	135	158	180	203	226
835		9	25	44	66	90	116	145	175	207	240
1900		3	12	26	44	66	92	122	157	195	236
2450		3	10	22	38	59	83	111	143	179	219
3600		2	8	18	32	49	71	96	125	158	195
5800		1	6	14	25	40	58	80	106	136	169

2.2 Assessment Results

The highest EIRP adjusted with tune-up tolerance is -1.01dBm = 0.79mW
 0.79mW < 3mW (Test Exclusion Thresholds of 2450MHz at 5mm). Therefore, the SAR requirement is deemed to be satisfied without test.

***** END *****