

Pablo Inc

MPE ASSESSMENT REPORT

Report Type:

FCC MPE assessment report

Model:

Talia, Tile

REPORT NUMBER:

200600311SHA-002

ISSUE DATE:

August 11, 2020

DOCUMENT CONTROL NUMBER:

TTRFFCCMPE-02_V1 © 2018 Intertek





Total Quality. Assured.

TEST REPORT

Intertek Testing Services Shanghai
Building No.86, 1198 Qinzhou Road (North)
Caohejing Development Zone
Shanghai 200233, China

Telephone: 86 21 6127 8200
www.intertek.com

Report no.: 200600311SHA-002

Applicant : **Pablo Inc**
888 Marin Street San Francisco, CA

Manufacturer : **Pablo Inc**
888 Marin Street San Francisco, CA

Factory : **Shanghai Arex Electronics Co., Ltd.**
No.789 Subway, Jia-xin Road, Jiading

FCC ID : **2AGV2TALTIL**

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

FCC PART 1 SECTION 1.1310

PREPARED BY:

Project Engineer
Erick Liu

REVIEWED BY:

Reviewer
Daniel Zhao

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT**Revision History**

Report No.	Version	Description	Issued Date
200600311SHA-002	Rev. 01	Initial issue of report	August 11, 2020

TEST REPORT**Measurement result summary**

TEST ITEM	FCC REFERENCE	TEST RESULT	NOTE
RF Exposure	1.1310	Pass	-

Notes: 1: NA =Not Applicable

2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

3: Additions, Deviations and Exclusions from Standards: None.

TEST REPORT**1 GENERAL INFORMATION****1.1 Description of Equipment Under Test (EUT)**

Product name:	Portable Lamp
Type/Model:	Talia, Tile
Description of EUT:	EUT is a wireless charger Portable Lamp. Model "Talia" contains one wireless charging module, while model "Tile" contains two wireless charging modules. We test all two models and list the results in this report.
Rating:	120V, 60Hz, 24W
Category of EUT:	Class B
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	June 11, 2020
Date of test:	June 13, 2020 ~ July 28, 2020

1.2 Technical Specification

Frequency Range:	110kHz – 205kHz
------------------	-----------------

TEST REPORT**1.3 Description of Test Facility**

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN1175
	IC Registration Lab CAB identifier.: CN0051
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

TEST REPORT

2 TEST SPECIFICATIONS

2.1 Standards or specification

FCC PART 1 SECTION 1.1310
KDB 680106 D01 RF Exposure Wireless Charging App v03

2.2 Mode of operation during the test

Within this test report, EUT was tested under all modes and tested under its rating voltage and frequency. Other voltage and frequency are specified if used. The worst data was listed in the report.

2.3 Test peripherals list

Item No.	Name	Band and Model	Description
1	Wireless load	KjB/ZS3012	100% power level
2	Wireless load	KjB/ZS3012	50% power level
3	Wireless load	KjB/ZS3012	0% power level
4	USB load	RX21	Used for PL-0170UQ

2.4 Record of climatic conditions

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (kPa)
RF Exposure	24	53	101

TEST REPORT**2.5 Instrument list**

Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Exposure Level Tester	Narda	ELT-400	EC 2928	2021-08-15
<input checked="" type="checkbox"/>	Field sensor & Field meter	AR	FL17000	EC 5818-1	2021-05-21

TEST REPORT

3 RF Exposure Assessment

Test result: Pass

3.1 Assessment Limit

Reference: 47 CFR §1.1310, KDB 680106


Limits for General Population/Uncontrolled Exposure

Frequency range [MHz]	Electric field strength [V/m]	Magnetic field strength [A/m]	Power density [mW/cm ²]	Averaging time [minutes]
0.1 – 0.3	614	1.63	*100	30
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 – 1 500	-	-	f/1500	30
1 500 – 100 000	-	-	1.0	30

Limits for Occupational/Controlled Exposure

Frequency range [MHz]	Electric field strength [V/m]	Magnetic field strength [A/m]	Power density [mW/cm ²]	Averaging time [minutes]
0.1 – 0.3	614	1.63	*100	6
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30 – 300	61.4	0.163	1.0	6
300 – 1 500	-	-	f/300	6
1 500 – 100 000	-	-	5	6

3.2 Assessment Configuration



TEST REPORT**3.3 Assessment Results**

Model Name: Talia

Test result of Magnetic Field Strength:

Test Position	Test distance (cm)	Test result (A/m)	Limit (A/m)	Result (Pass/Fail)
A: Right	15	0.043	1.63 *0.5	Pass
B: Left	15	0.042	1.63 *0.5	Pass
C: Front	15	0.035	1.63 *0.5	Pass
D: Back	15	0.038	1.63 *0.5	Pass
E: Top	20	0.041	1.63 *0.5	Pass

Test result of Electric Field Strength:

Test Position	Test distance (cm)	Test result (V/m)	Limit (V/m)	Result (Pass/Fail)
A: Right	15	0.74	614 *0.5	Pass
B: Left	15	0.84	614 *0.5	Pass
C: Front	15	0.93	614 *0.5	Pass
D: Back	15	0.83	614 *0.5	Pass
E: Top	20	0.86	614 *0.5	Pass

TEST REPORT

Model Name: Tile

Test result of Magnetic Field Strength:

Test Position	Test distance (cm)	Test result (A/m)	Limit (A/m)	Result (Pass/Fail)
A: Right	15	0.053	1.63 *0.5	Pass
B: Left	15	0.052	1.63 *0.5	Pass
C: Front	15	0.049	1.63 *0.5	Pass
D: Back	15	0.057	1.63 *0.5	Pass
E: Top	20	0.049	1.63 *0.5	Pass

Test result of Electric Field Strength:

Test Position	Test distance (cm)	Test result (V/m)	Limit (V/m)	Result (Pass/Fail)
A: Right	15	0.88	614 *0.5	Pass
B: Left	15	0.89	614 *0.5	Pass
C: Front	15	0.86	614 *0.5	Pass
D: Back	15	0.94	614 *0.5	Pass
E: Top	20	0.91	614 *0.5	Pass

***** END *****