

Issued: 2016-3-25

TEST REPORT

Applicant Name & : POMCUBE Inc.

Address 19363 Brockton Ln Saratoga California United States 95070

Manufacturing Site : Shenzhen 3sun Electronics Co.,Ltd

3sun Electronics Industrial Park,No.10Jinlong First Road,Baolong Community,Longgang District,Shenzhen,Guangdong,China

Sample Description

Product : iCAN

FCC ID : 2AGZ2-PO1AAW1

Operation : 178kHz

frequency

Model No. : PO1-AAW1

Electrical Rating : 90-130Vac/60Hz/Max.10A

Date Received : 03 November 2015

Date Test Conducted : 05 November 2015-22 March 2016

Test standards : FCC Part 18: 2014

Test Result : Pass

Conclusion : The submitted samples complied with the above rules/standards.

Remark : The report is for wireless charger function.

Prepared and Checked By:

Sky Zhu

Project Engineer

Intertek Guangzhou

Approved By:

Helen Ma

Team Leader

Intertek Guangzhou

25 March 2016

Date

Signature

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

The test report only allows to be revised within three years from its original issued date unless further standard or the requirement was noticed.

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch
Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD Guangzhou, China
Tel / Fax: 86-20-8213 9688/86-20-3205 7538
© 2016 Intertek

FCC ID: 2AGZ2-PO1AAW1 Page 1 of 15



Issued: 2016-3-25

CONTENT

T]	EST REPO	ORT	1
C	ONTENT.		2
1	TEST	RESULTS SUMMARY	3
2	TEST	RESULTS CONCLUSION	4
3	LABO	PRATORY MEASUREMENTS	5
4		RESULTS	
	4.1 Con	NDUCTED DISTURBANCE VOLTAGE AT MAINS PORTS	6
	4.1.1	Used Test Equipment	6
	4.1.2	Block Diagram of Test Setup	
	4.1.3	Test Setup and Procedure	
	4.1.4	Limit	
	4.1.5	Test Data	
	4.1.6	Emission Curve	
	4.1.7	Measurement Uncertainty	
	4.2 RAD	DIATED EMISSION (BELOW 30MHz)	
	4.2.1	Used Test Equipment	
	4.2.2	Block Diagram of Test Setup	
	4.2.3	Test Setup and Procedure	
	4.2.4	Limit	
	4.2.5	Test Data and Curve	
		DIATED EMISSION (30 MHz -1000 MHz)	
		DIATED EMISSION ABOVE 1 GHZ	
_		NDIX I - PHOTOS OF TEST SETUP	
	AFFE	NIZIA I = I IIV I VAZ VE TEAZT ARTUE	



Issued: 2016-3-25

1 <u>TEST RESULTS SUMMARY</u>

Classification of EUT: non-ISM frequency equipment

Test Item	Standard	Result				
Conducted disturbance voltage at	FCC Part 18: 2014	Pass				
mains ports						
Radiated emission (Below 30MHz)	FCC Part 18: 2014	Pass				
Radiated emission (30 MHz–1 GHz)	FCC Part 18: 2014	N/A				
Radiated emission (Above 1 GHz)	FCC Part 18: 2014	N/A				
Remark:						
Reference publication is used for methods of measurement: MP-5:1986						

Remark: 1. The symbol "N/A" in above table means Not Applicable.

2. When determining the test results, measurement uncertainty of tests has been considered.

FCC ID: 2AGZ2-PO1AAW1 Page 3 of 15



Issued: 2016-3-25

2 Test Results Conclusion

(with Justification)

RE: EMC Testing Pursuant to FCC Part 18 Performed on the iCAN, Model: PO1-AAW1.

We tested the iCAN, Model: PO1-AAW1, to determine if it was in compliance with the relevant FCC rules as marked on the Test Results Summary. We found that the unit met the requirement of FCC Part 18 when tested as received. The worst case's test data was presented in this test report.

Conclusion:

The sample as received complied with the FCC Part 18 requirement.

The production units are required to conform to the initial sample as received when the units are placed on the market.

FCC ID: 2AGZ2-PO1AAW1 Page 4 of 15



Issued: 2016-3-25

3 LABORATORY MEASUREMENTS

Configuration Information

Equipment Under Test (EUT): iCAN

Model: PO1-AAW1

Serial No.: Not Labeled

Support Equipment: N/A

Rated Voltage: AC 120V/60Hz

Condition of Environment: Temperature : 22~28°C

Relative Humidity: 35~60% Atmosphere Pressure 86~106kPa

Notes:

1. The EMI measurements had been made in the operating mode producing the largest emission in the frequency band being investigated consistent with normal applications.

An attempt had been made to maximize the emission by varying the configuration of the EUT.

2. Test Sites:

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

All tests were performed at:

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD Guangzhou, China

Except Radiated Disturbance was performed at:

Room 101, Block A, No.11 Jing Ye San Street, Yu Shu Industrial Park, Guangzhou Science City, GETDD Guangzhou

FCC ID: 2AGZ2-PO1AAW1 Page 5 of 15



Issued: 2016-3-25

4 TEST RESULTS


4.1 Conducted Disturbance Voltage at mains ports

Test Result: Pass

4.1.1 Used Test Equipment

Equipment No.	Equipment	Model	Manufactu Cal.Due date rer		Calibration Interval
EM004-04	EMC shield Room	8m×3m×3m	Zhongyu	2015-08-04	1Y
EM080-05	EMI receiver	ESCI	R&S	2015-08-04	1Y
EM006-05	LISN	ENV216	R&S	2015-09-12	1Y

4.1.2 Block Diagram of Test Setup



4.1.3 Test Setup and Procedure

Test was performed according to FCC OST/ MP-5:1986. The EUT was set to achieve the maximum emission level. The mains terminal disturbance voltage was measured with the EUT in a shielded room. The EUT was connected to AC power source through an Artificial Mains Network which provides a 50Ω linear impedance Artificial hand is used if appropriate (for handheld apparatus). The load/control terminal disturbance voltage was measured with passive voltage probe if appropriate.

The table-top EUT was placed on a 0.8m high non-metallic table above earthed ground plane(Ground Reference Plane). And for floor standing EUT, was placed on a 10mm high non-metallic supported on GRP. The EUT keeps a distance of at least 0.8m from any other of the metallic surface. The Artificial Mains Network is situated at a distance of 0.8m from the EUT.

During the test, mains lead of EUT excess 0.8m was folded back and forth parallel to the lead so as to form a horizontal bundle with a length between 0.3m and 0.4m.

The bandwidth of test receiver was set at 9 kHz. The frequency range from 150 kHz to 30MHz was checked.

FCC ID: 2AGZ2-PO1AAW1



Issued: 2016-3-25

4.1.4 Limit

Class B

Frequency range MHz	AC mains terminals dB (uV)			
141112	Quasi-peak	Average		
0.15 to 0.5	66 to 56	56 to 46		
0.5 to 5	56	46		
5 to 30	60	50		

Note 1: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Note 2: The lower limit is applicable at the transition frequency.




Issued: 2016-3-25

4.1.5 Test Data


At main terminal: Pass

Tested Wire: Live Operation Mode: wireless charging



Tested Wire: Neutral


Operation Mode: wireless charging






Issued: 2016-3-25

4.1.6 Emission Curve Tested Wire: Live



Tested Wire: Neutral



4.1.7 Measurement Uncertainty

Uncertainty: 2.58 dB at a level of confidence of 95%



Issued: 2016-3-25


4.2 Radiated Emission (below 30MHz)

Test Result: Pass

4.2.1 Used Test Equipment

Oscu Test Equ	seu Test Equipment						
Equip. No.	Equipment	Model	Manufacturer	Cal. Due date (YYYY- MM-DD)	Calibration Interval		
EM030-01	3m Semi-Anechoic Chamber	9×6×6 m3	ETS•LINDGREN	2015-04-02	1Y		
EM030-02	Control room for 3m Semi-Anechoic Chamber	4×4×3 m3	ETS•LINDGREN	2015-06-03	1Y		
EM031-02	EMI Test Receiver (9 kHz~7 GHz)	R&S ESR7	R&S	2015-06-03	1Y		
EM011-04	Loop Antenna (0.009 - 30) MHz	HFH2-Z2	SCHWARZBECK	2015-05-25	1Y		
EM031-02-01	Coaxial cable	/	R&S	2015-05-25	1Y		

4.2.2 Block Diagram of Test Setup





Issued: 2016-3-25

4.2.3 Test Setup and Procedure

Radiated testing was performed at a 3 meters semi-anechoic chamber. The EUT was placed on 10mm above ground. The table was 360 degrees to determine the position of the highest radiation. The center of the loop shall be 2 m above the ground. EUT is set 3 meters from the EMI receiving antenna; the levels are quasi peak value readings. The frequency spectrum from 0.009MHz to 30MHz was investigated.

Loop antenna was used as receiving antenna. Both horizontal and vertical polarization of the antenna was set on measurement. In order to find the maximum emission, all of the interface cables were manipulated according to FCC OST/ MP-5:1986 requirement during radiated test. The bandwidth setting on R&S Test Receiver was 200Hz from 9kHz to 150kHz and 9kHz from 150kHz to 30MHz. The frequency range from 0.009MHz to 30MHz was checked.

4.2.4 Limit

Equipment	Operating frequency	RF Power gen- erated by equip- ment (watts) Field strength limit (uV/		Distance (meters)
Any type unless otherwise specified (miscellaneous).	Any ISM frequency		25	300 1300
	Any non-ISM frequency	Below 500 500 or more	15 15×SQRT(power/500)	300 1300

Measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (20 dB/decade). So, any non-ISM frequency at distance 3m was 63.5dBuV/m




Issued: 2016-3-25

4.2.5 Test Data and Curve

Test mode: wireless charging

Horizontal:




AV

Frequency (MHz)	Average (dBµV/m)	Bandwidth (kHz)	Pol	Corr. (dB)	Margin - AVG (dB)	Limit - AVG (dBμV/m)
0.178000	50.1	9.000	Н	21.0	13.4	63.5
0.538000	33.8	9.000	Н	21.6	29.7	63.5
0.898000	34.6	9.000	Н	22.1	28.9	63.5



Issued: 2016-3-25

Vertical:



ΑV

Frequency (MHz)	Average (dBµV/m)	Bandwidth (kHz)	Pol	Corr. (dB)	Margin - AVG (dB)	Limit - AVG (dBµV/m)	
0.178000	49.6	9.000	Н	21.0	13.9	63.5	
0.538000	31.9	9.000	Н	21.6	31.6	63.5	
1.082000	32.1	9.000	Н	22.1	31.4	63.5	
1.626000	32.6	9.000	Н	21.7	30.9	63.5	



Issued: 2016-3-25

4.3 Radiated Emission (30 MHz -1000 MHz)

Test Result: Not Applicable

Remark: The wireless charger frequency is below 1.705MHz

4.4 Radiated Emission above 1 GHz

Test Result: Not Applicable

Remark: The wireless charger frequency is below 1.705MHz

FCC ID: 2AGZ2-PO1AAW1 Page 14 of 15



Issued: 2016-3-25

5 Appendix I - Photos of test setup

